

## RF EXPOSURE EVALUATION METHOD

FCC ID:2AFII-BT09

SAR Test Exclusion Thresholds for 100 MHz - 6 GHz and  $\leq 50$  mm

Approximate SAR Test Exclusion Power Thresholds at Selected Frequencies and Test Separation Distances are illustrated in the following Table.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where } f(\text{GHz}) \text{ is the RF channel transmit frequency in GHz}$

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

Maximum measured transmitter power.

BT 3.0

1Mbps			
Test Channel	Frequency (MHz)	Peak Output Power (dBm)	Peak Output Power (mW)
CH00	2402	0.94	1.242
CH39	2441	2.30	1.698
CH78	2480	1.94	1.563
2Mbps			
CH00	2402	1.21	1.321
CH39	2441	2.68	1.854
CH78	2480	3.03	2.009
3Mbps			
CH00	2402	1.29	1.346
CH39	2441	2.91	1.954
CH78	2480	2.92	1.959

BT 4.0

Test Channel	Frequency (MHz)	Maximum Conducted Output Power(PK)	Maximum Conducted Output Power(PK)
		(dBm)	mW
CH00	2402	2.43	1.750
CH19	2440	2.38	1.730
CH39	2480	2.90	1.950

Remark: The best case gain of the antenna is 0.54dBi.

0.54 dBi logarithmic terms convert to numeric result is nearly 1.13

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq$  50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}]$

#### BT 3.0

Test Channel	Range	tune up max power (dBm)	$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})]$	[ $f(\text{GHz})$ ]	Result	Limit
<b>1Mbps</b>						
CH00	0.5~2.5	2.5	1.778	5	2.402	0.551
CH39	0.5~2.5	2.5	1.778	5	2.441	0.556
CH78	0.5~2.5	2.5	1.778	5	2.480	0.560
<b>2Mbps</b>						
CH00	1.2~3.2	3.2	2.089	5	2.402	0.648
CH39	1.2~3.2	3.2	2.089	5	2.441	0.653
CH78	1.2~3.2	3.2	2.089	5	2.480	0.658
<b>3Mbps</b>						
CH00	1~3	3	1.995	5	2.402	0.618
CH39	1~3	3	1.995	5	2.441	0.623
CH78	1~3	3	1.995	5	2.480	0.628

#### BT 4.0

Test Channel	Range	tune up max power (dBm)	$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})]$	[ $f(\text{GHz})$ ]	Result	Limit
CH00	1~3	3	1.995	5	2.402	0.618
CH39	1~3	3	1.995	5	2.441	0.623
CH78	1~3	3	1.995	5	2.480	0.628

The test Result is less than 3.0 for 1-g SAR and  $\leq$  7.5 for 10-g extremity SAR.

**Conclusion:** No SAR is required.