

Radio Frequency Exposure Report

On Behalf of

GL Technologies (Hong Kong) Limited
Unit 210D, 2/F, Enterprise Place Hong Kong Science Park, Shatin, N.T, Hong Kong


Product Name:	GL-MT300N-V2
Model/Type No.:	GL-MT300N-V2
FCC ID:	2AFIW- 300NV2
Prepared By:	Shenzhen Hongcai Testing Technology Co., Ltd. 1st-3rd Floor, Building C, Shuanghuan Xin Yi Dai Hi-Tech Industrial Park, No.8 Baoqing Road, Baolong Industrial Zone, Longgang District, Shenzhen, Guangdong, China Tel: +86-755-86337020 Fax:+86-755-86337028
Report Number:	HCT17DR084E-2
Tested Date:	April 8~14, 2017
Issued Date:	April 14, 2017
Tested By:	Jerry Zhao 

Reviewed By:



Owen Yang

Approved By:



Tony Wu

Owen.Yang
EMC Technical Supervisor

Tony Wu
EMC Technical Manager

TABLE OF CONTENTS

1 - GENERAL INFORMATION	3
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	3
1.2 OBJECTIVE	4
1.3 GENERAL DESCRIPTION OF TEST	4
1.4 HUMAN EXPOSURE ASSESSMENT RESULTS	5



1 - GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant:	GL Technologies (Hong Kong) Limited
Address of Applicant:	Unit 210D, 2/F, Enterprise Place Hong Kong Science Park, Shatin, N.T, Hong Kong
Manufacturer:	GL Technologies (Hong Kong) Limited
Address of Manufacturer:	Unit 210D, 2/F, Enterprise Place Hong Kong Science Park, Shatin, N.T, Hong Kong

General Description of E.U.T

Items	Description
EUT Description:	GL-MT300N-V2
Model No.:	GL-MT300N-V2
Trade Mark:	GL- [®] iNet
Frequency Band:	IEEE 802.11b : 2412MHz ~ 2462MHz; IEEE 802.11g : 2412MHz ~ 2462MHz; IEEE 802.11n HT20 : 2412MHz ~ 2462MHz; IEEE 802.11n HT40 : 2422MHz ~ 2452MHz;
Channel Spacing:	IEEE 802.11b : 5MHz IEEE 802.11g : 5MHz IEEE 802.11n HT20 : 5MHz IEEE 802.11n HT40 : 5MHz
Number of Channels:	IEEE 802.11b : 11 Channels; IEEE 802.11g : 11 Channels; IEEE 802.11n HT20 : 11 Channels; IEEE 802.11n HT40 : 7 Channels;
Transmit Data Rate:	maximum of 150Mbps
Type of Modulation:	IEEE 802.11b : CCK IEEE 802.11g : OFDM IEEE 802.11n HT20 : OFDM IEEE 802.11n HT40 : OFDM
Antenna Type:	PCB ANTENNA
Antenna Gain:	Ant 1: 3.2dBi Ant 2: 3.2dBi
Power Rating:	Input: DC 5V

Remark: * The test data gathered are from the production sample provided by the manufacturer.

1.2 Objective

The objective of the following report is used to demonstrate that EUT operated in a manner that ensures the public is not exposed to radio frequency energy levels in excess of the relative provisions of FCC 47CFR Part 1.1307

1.3 General Description of Test

Items	Description
EUT Frequency band	<input type="checkbox"/> FHSS: 2.400GHz ~ 2.483GHz <input checked="" type="checkbox"/> WLAN: 2.400GHz ~ 2.483GHz <input type="checkbox"/> WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz <input type="checkbox"/> WLAN: 5.745GHz ~ 5825GHz <input type="checkbox"/> Others: _____
Device category	<input type="checkbox"/> Portable (<20cm separation) <input type="checkbox"/> Mobile (>20cm separation) <input checked="" type="checkbox"/> Others <u>Stationary type (>20cm separation)</u>
Exposure classification	<input type="checkbox"/> Occupational/Controlled exposure ($S = 5\text{mW/cm}^2$) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure $(S=1\text{mW/cm}^2)$ <input type="checkbox"/> Others: _____
Antenna diversity	<input type="checkbox"/> Single antenna <input checked="" type="checkbox"/> Multiple antennas: <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input checked="" type="checkbox"/> Tx/Rx diversity
Max. output power	22.99dBm(0.199W)
Antenna gain (Max)	3.2dBi (Numeric gain:2.089)
Evaluation applied	<input checked="" type="checkbox"/> MPE Evaluation <input type="checkbox"/> SAR Evaluation
Note: <ol style="list-style-type: none"> 1. The maximum output power is 22.99dBm at IEEE 802.11b mode 2462MHz (with 2.089 numeric antenna gain.) 2. For mobile or fixed location transmitters, no SAR consideration applied. The minimum separation generally be used is at least 20 cm, even if the calculations indicate that the MPE distance would be lesser. 	

1.4 Human Exposure Assessment Results

Calculation

Given $E = \frac{\sqrt{30 \times P \times G}}{d}$ & $S = \frac{E^2}{3770}$

Where E = Field Strength in Volts / meter

P = Power in Watts

G = Numeric antenna gain

d = Distance in meters

S = Power Density in milliwatts / square centimeter

Combining equations and re-arranging the terms to express the distance as a function of the remaining variables yields:

$$S = \frac{30 \times P \times G}{3770 d^2}$$

Changing to units of mW and cm, using:

$$P \text{ (mW)} = P \text{ (W)} / 1000 \text{ and}$$

$$d \text{ (cm)} = 100 * d \text{ (m)}$$

Yields

$$S = \frac{30 \times (P/1000) \times G}{3770 \times (d/100)^2} = 0.0796 \times \frac{P \times G}{d^2}$$

Equation 1

Where d = distance in cm

P = Power in mW

G = Numeric antenna gain

S = Power Density in mW/cm²

EUT parameter (data from the separate report)	
Given	Where G: numerical gain of transmitting antenna; TP: Transmitted power in watt; d: distance from the transmitting antenna in meter
$E = \frac{\sqrt{30 \times P \times G}}{d}$ & $S = \frac{E^2}{3770}$	
Max average output power in Watt (TP)	22.99dBm(0.199W)
Max Antenna gain (G)	3.2dBi (Numeric gain:2.089)
Exposure classification	$S=1\text{mW/cm}^2$
Minimum distance in meter (d) (from transmitting structure to the human body)	20cm (0.2m)

Yields

$$S = \frac{30 \times P \times G}{3770d^2}, \quad P=0.199W, G=2.089, d=0.2$$

$$S=0.083 \text{mW/cm}^2$$

Or

$$d = \sqrt{\frac{30 \times P \times G}{3770S}}, \quad S=1, P=0.199W, G=2.089$$

$$d=0.057 \text{m}$$

Conclusion:

$S=0.083 \text{mW/cm}^2$ is significant lower than the General Population Exposure Power Density Limit 1mW/cm^2 or except the distance when human body proximity to the antenna is less than 5.6 cm then will reach the General Population Exposure Power Density Limit

(For mobile or fixed location transmitters, the maximum power density is 1.0 mW / cm^2 even if the calculation indicates that the power density would be larger.)

