



Test Mode: 03; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:High



race: (Discrete)

	Read	Antenna	Cable	Preamp	Limit	Over		
Freq	Level	Factor	Loss	Factor	Line	Limit	Pol/Phase	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1 *	5700.000	104.82	32.01	6.40	36.89	106.34	68.20	38.14 HORIZONTAL Peak
2	5725.000	61.24	32.07	6.25	36.89	62.67	68.20	-5.53 HORIZONTAL Peak
3	5748.011	62.72	32.10	6.20	36.89	64.13	68.20	-4.07 HORIZONTAL Peak


Test Mode: 03; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:High



Trace: (Discrete)

		ReadAntenna	Cable	Preamp		Limit	Over		
	Freq	Level	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dBuV/m	dBuV/m	dB		
1 *	5700.000	105.82	32.01	6.40	36.89	107.34	68.20	39.14 VERTICAL	Peak
2	5725.000	61.10	32.07	6.25	36.89	62.53	68.20	-5.67 VERTICAL	Peak
3	5727.882	62.34	32.07	6.25	36.89	63.77	68.20	-4.43 VERTICAL	Peak


Test Mode: 03; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:Low



race: (Discrete)

	Freq	Read	Antenna	Cable	Preamp	Limit	Over		
	MHz	Level	Factor	Loss	Factor	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	5458.831	49.68	31.79	6.26	36.88	50.85	54.00	-3.15	HORIZONTAL Average
2	5458.831	61.58	31.79	6.26	36.88	62.75	74.00	-11.25	HORIZONTAL Peak
3	5462.311	61.22	31.79	6.26	36.88	62.39	68.20	-5.81	HORIZONTAL Peak
4	5500.000	92.88	31.80	6.40	36.88	94.20	-----	-----	HORIZONTAL Average
5 *	5500.000	107.48	31.80	6.40	36.88	108.80	68.20	40.60	HORIZONTAL Peak


Test Mode: 03; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:Low



Trace: (Discrete)

	Freq	Read	Antenna	Cable	Preamp	Limit	Over		
	MHz	Level	Factor	Loss	Factor	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	5405.938	49.89	31.79	6.06	36.88	50.86	54.00	-3.14	VERTICAL Average
2	5420.214	61.81	31.79	6.13	36.88	62.85	74.00	-11.15	VERTICAL Peak
3	5463.872	61.13	31.80	6.31	36.88	62.36	68.20	-5.84	VERTICAL Peak
4	5500.000	91.10	31.80	6.40	36.88	92.42	-----	-----	VERTICAL Average
5 *	5500.000	107.49	31.80	6.40	36.88	108.81	68.20	40.61	VERTICAL Peak


Test Mode: 03; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:High



Trace: (Discrete)

	Freq	ReadAntenna Level	Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1 *	5700.000	105.45	32.01	6.40	36.89	106.97	68.20	38.77	HORIZONTAL	Peak
2	5725.000	61.55	32.07	6.25	36.89	62.98	68.20	-5.22	HORIZONTAL	Peak
3	5729.882	62.38	32.07	6.25	36.89	63.81	68.20	-4.39	HORIZONTAL	Peak


Test Mode: 03; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:High



race: (Discrete)


	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Limit Level	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dB		
1 *	5700.000	105.59	32.01	6.40	36.89	107.11	68.20	38.91	VERTICAL Peak
2	5725.000	61.22	32.07	6.25	36.89	62.65	68.20	-5.55	VERTICAL Peak
3	5740.893	62.47	32.10	6.20	36.89	63.88	68.20	-4.32	VERTICAL Peak

Test Mode: 03; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:Low




	Freq	Read	Antenna	Cable	Preamp	Limit	Over		
	MHz	Level	Factor	Loss	Factor	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	5436.613	49.59	31.79	6.20	36.88	50.70	54.00	-3.30	HORIZONTAL Average
2	5445.107	62.02	31.79	6.20	36.88	63.13	74.00	-10.87	HORIZONTAL Peak
3	5462.277	61.64	31.79	6.26	36.88	62.81	68.20	-5.39	HORIZONTAL Peak
4	5510.000	95.35	31.80	6.40	36.88	96.67	-----	-----	HORIZONTAL Average
5 *	5510.000	104.37	31.80	6.40	36.88	105.69	68.20	37.49	HORIZONTAL Peak

Test Mode: 03; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:Low



	Freq	ReadAntenna Level	Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	5402.350	50.16	31.79	6.06	36.88	51.13	54.00	-2.87	VERTICAL	Average
2	5402.350	61.91	31.79	6.06	36.88	62.88	74.00	-11.12	VERTICAL	Peak
3	5464.654	61.91	31.80	6.31	36.88	63.14	68.20	-5.06	VERTICAL	Peak
4	5510.000	94.97	31.80	6.40	36.88	96.29	-----	-----	VERTICAL	Average
5 *	5510.000	104.32	31.80	6.40	36.88	105.64	68.20	37.44	VERTICAL	Peak


Test Mode: 03; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:High



Trace: (Discrete)

	Read	Antenna	Cable	Preamp	Limit	Over		
Freq	Level	Factor	Loss	Factor	Line	Limit	Pol/Phase	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1 *	5670.000	103.91	31.97	6.37	36.89	105.36	68.20	37.16 HORIZONTAL Peak
2	5725.000	61.56	32.07	6.25	36.89	62.99	68.20	-5.21 HORIZONTAL Peak


Test Mode: 03; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:High



race: (Discrete)

	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1 *	5670.000	105.07	31.97	6.37	36.89	106.52	68.20	38.32	VERTICAL	Peak
2	5725.000	60.89	32.07	6.25	36.89	62.32	68.20	-5.88	VERTICAL	Peak
3	5748.764	62.40	32.10	6.20	36.89	63.81	68.20	-4.39	VERTICAL	Peak


Test Mode: 03; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:20MHz; Channel:Low



Trace: (Discrete)


	Freq	Read	Antenna	Cable	Preamp	Limit	Over		
	MHz	Level	Factor	Loss	Factor	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	5408.314	49.81	31.79	6.06	36.88	50.78	54.00	-3.22	HORIZONTAL Average
2	5422.359	62.04	31.79	6.13	36.88	63.08	74.00	-10.92	HORIZONTAL Peak
3	5461.591	61.38	31.79	6.26	36.88	62.55	68.20	-5.65	HORIZONTAL Peak
4	5500.000	96.50	31.80	6.40	36.88	97.82	-----	-----	HORIZONTAL Average
5 *	5500.000	106.97	31.80	6.40	36.88	108.29	68.20	40.09	HORIZONTAL Peak

Test Mode: 03; Polarity: Vertical; Modulation:802.11ac; Bandwidth:20MHz; Channel:Low



	Freq	Read	Antenna	Cable	Preamp	Limit	Over		
	MHz	Level	Factor	Loss	Factor	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	5452.116	49.61	31.79	6.26	36.88	50.78	54.00	-3.22	VERTICAL Average
2	5452.116	62.28	31.79	6.26	36.88	63.45	74.00	-10.55	VERTICAL Peak
3	5467.115	61.20	31.80	6.31	36.88	62.43	68.20	-5.77	VERTICAL Peak
4	5500.000	97.10	31.80	6.40	36.88	98.42	-----	-----	VERTICAL Average
5 *	5500.000	106.91	31.80	6.40	36.88	108.23	68.20	40.03	VERTICAL Peak


Test Mode: 03; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:20MHz; Channel:High



Trace: (Discrete)

	Freq	ReadAntenna Level Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1 *	5700.000	104.72	32.01	6.40	36.89	106.24	68.20	38.04	HORIZONTAL Peak
2	5725.000	61.57	32.07	6.25	36.89	63.00	68.20	-5.20	HORIZONTAL Peak


Test Mode: 03; Polarity: Vertical; Modulation:802.11ac; Bandwidth:20MHz; Channel:High



race: (Discrete)


	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Limit Level	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dB		
1 *	5700.000	106.16	32.01	6.40	36.89	107.68	68.20	39.48	VERTICAL Peak
2	5725.000	61.48	32.07	6.25	36.89	62.91	68.20	-5.29	VERTICAL Peak
3	5741.093	62.83	32.10	6.20	36.89	64.24	68.20	-3.96	VERTICAL Peak

Test Mode: 03; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:40MHz; Channel:Low



race: (Discrete)	Frequency (MHz)									
	Freq	ReadAntenna	Cable	Preamp		Limit	Over	Pol/Phase	Remark	
		Level	Factor	Loss	Factor	Level	Line			Limit
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	5427.575	49.87	31.79	6.13	36.88	50.91	54.00	-3.09	HORIZONTAL	Average
2	5427.575	62.14	31.79	6.13	36.88	63.18	74.00	-10.82	HORIZONTAL	Peak
3	5461.298	61.51	31.79	6.26	36.88	62.68	68.20	-5.52	HORIZONTAL	Peak
4	5510.000	94.20	31.80	6.40	36.88	95.52	-----	-----	HORIZONTAL	Average
5 *	5510.000	104.69	31.80	6.40	36.88	106.01	68.20	37.81	HORIZONTAL	Peak


Test Mode: 03; Polarity: Vertical; Modulation:802.11ac; Bandwidth:40MHz; Channel:Low



Trace: (Discrete)

	Freq	Read	Antenna	Cable	Preamp	Limit	Over		
	MHz	Level	Factor	Loss	Factor	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	5416.473	49.93	31.79	6.13	36.88	50.97	54.00	-3.03	VERTICAL Average
2	5428.409	62.03	31.79	6.13	36.88	63.07	74.00	-10.93	VERTICAL Peak
3	5468.292	61.04	31.80	6.31	36.88	62.27	68.20	-5.93	VERTICAL Peak
4	5510.000	93.68	31.80	6.40	36.88	95.00	-----	-----	VERTICAL Average
5 *	5510.000	104.70	31.80	6.40	36.88	106.02	68.20	37.82	VERTICAL Peak


Test Mode: 03; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:40MHz; Channel:High



Trace: (Discrete)

	Freq	ReadAntenna Level	Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1 *	5670.000	103.40	31.97	6.37	36.89	104.85	68.20	36.65	HORIZONTAL	Peak
2	5725.000	60.83	32.07	6.25	36.89	62.26	68.20	-5.94	HORIZONTAL	Peak


Test Mode: 03; Polarity: Vertical; Modulation:802.11ac; Bandwidth:40MHz; Channel:High



Trace: (Discrete)


		ReadAntenna		Cable	Preamp		Limit	Over		
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1 *	5670.000	104.94	31.97	6.37	36.89	106.39	68.20	38.19	VERTICAL	Peak
2	5725.000	61.65	32.07	6.25	36.89	63.08	68.20	-5.12	VERTICAL	Peak

Test Mode: 03; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:80MHz; Channel:Low




	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
		Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	5457.675	49.52	31.79	6.26	36.88	50.69	54.00	-3.31	HORIZONTAL	Average
2	5457.675	61.56	31.79	6.26	36.88	62.73	74.00	-11.27	HORIZONTAL	Peak
3	5469.140	61.21	31.80	6.31	36.88	62.44	68.20	-5.76	HORIZONTAL	Peak
4	5530.000	90.63	31.83	6.37	36.89	91.94	-----	-----	HORIZONTAL	Average
5 *	5530.000	100.53	31.83	6.37	36.89	101.84	68.20	33.64	HORIZONTAL	Peak

Test Mode: 03; Polarity: Vertical; Modulation:802.11ac; Bandwidth:80MHz; Channel:Low




	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	5433.748	49.64	31.79	6.20	36.88	50.75	54.00	-3.25	VERTICAL	Average
2	5433.748	61.60	31.79	6.20	36.88	62.71	74.00	-11.29	VERTICAL	Peak
3	5466.092	61.48	31.80	6.31	36.88	62.71	68.20	-5.49	VERTICAL	Peak
4	5530.000	90.37	31.83	6.37	36.89	91.68	-----	-----	VERTICAL	Average
5 *	5530.000	99.51	31.83	6.37	36.89	100.82	68.20	32.62	VERTICAL	Peak

Test Mode: 03; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:80MHz; Channel:High



	Read	Antenna	Cable	Preamp	Limit	Over		
Freq	Level	Factor	Loss	Factor	Line	Limit	Pol/Phase	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1 *	5610.000	101.46	31.91	6.32	36.89	102.80	68.20	34.60 HORIZONTAL Peak
2	5751.864	62.49	32.10	6.20	36.89	63.90	68.20	-4.30 HORIZONTAL Peak


Test Mode: 03; Polarity: Vertical; Modulation:802.11ac; Bandwidth:80MHz; Channel:High



Trace: (Discrete)

		Read	Antenna	Cable	Preamp		Limit	Over		
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1 *	5610.000	100.29	31.91	6.32	36.89	101.63	68.20	33.43	VERTICAL	Peak
2	5758.168	62.32	32.13	6.15	36.89	63.71	68.20	-4.49	VERTICAL	Peak


Test Mode: 03; Polarity: Horizontal; Modulation:802.11ax; Bandwidth:20MHz; Channel:Low



race: (Discrete)

	Freq	Read	Antenna	Cable	Preamp	Limit	Over		
	MHz	Level	Factor	Loss	Factor	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	5408.790	49.87	31.79	6.06	36.88	50.84	54.00	-3.16	HORIZONTAL Average
2	5418.309	62.05	31.79	6.13	36.88	63.09	74.00	-10.91	HORIZONTAL Peak
3	5461.230	61.01	31.79	6.26	36.88	62.18	68.20	-6.02	HORIZONTAL Peak
4	5500.000	96.09	31.80	6.40	36.88	97.41	-----	-----	HORIZONTAL Average
5 *	5500.000	108.23	31.80	6.40	36.88	109.55	68.20	41.35	HORIZONTAL Peak


Test Mode: 03; Polarity: Vertical; Modulation:802.11ax;Bandwidth:20MHz; Channel:Low



Trace: (Discrete)

	Freq	Read	Antenna	Cable	Preamp	Limit	Over		
	MHz	Level	Factor	Loss	Factor	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	5401.187	62.19	31.79	6.06	36.88	63.16	74.00	-10.84	VERTICAL Peak
2	5417.237	49.83	31.79	6.13	36.88	50.87	54.00	-3.13	VERTICAL Average
3	5462.311	61.31	31.79	6.26	36.88	62.48	68.20	-5.72	VERTICAL Peak
4	5500.000	95.51	31.80	6.40	36.88	96.83	-----	-----	VERTICAL Average
5 *	5500.000	107.80	31.80	6.40	36.88	109.12	68.20	40.92	VERTICAL Peak


Test Mode: 03; Polarity: Horizontal; Modulation:802.11ax; Bandwidth:20MHz; Channel:High



race: (Discrete)

	Read	Antenna	Cable	Preamp	Limit	Over		
Freq	Level	Factor	Loss	Factor	Line	Limit	Pol/Phase	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1 *	5700.000	106.19	32.01	6.40	36.89	107.71	68.20	39.51 HORIZONTAL Peak
2	5725.000	61.55	32.07	6.25	36.89	62.98	68.20	-5.22 HORIZONTAL Peak
3	5726.483	62.82	32.07	6.25	36.89	64.25	68.20	-3.95 HORIZONTAL Peak


Test Mode: 03; Polarity: Vertical; Modulation:802.11ax; Bandwidth:20MHz; Channel:High



race: (Discrete)


	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
		Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1 *	5700.000	107.69	32.01	6.40	36.89	109.21	68.20	41.01	VERTICAL	Peak
2	5725.000	60.81	32.07	6.25	36.89	62.24	68.20	-5.96	VERTICAL	Peak
3	5757.448	62.45	32.13	6.15	36.89	63.84	68.20	-4.36	VERTICAL	Peak

Test Mode: 03; Polarity: Horizontal; Modulation:802.11ax; Bandwidth:40MHz; Channel:Low



	Freq	Read	Antenna	Cable	Preamp	Limit	Over		
	MHz	Level	Factor	Loss	Factor	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	5426.325	49.78	31.79	6.13	36.88	50.82	54.00	-3.18	HORIZONTAL Average
2	5438.979	61.88	31.79	6.20	36.88	62.99	74.00	-11.01	HORIZONTAL Peak
3	5461.019	61.18	31.79	6.26	36.88	62.35	68.20	-5.85	HORIZONTAL Peak
4	5510.000	93.56	31.80	6.40	36.88	94.88	-----	-----	HORIZONTAL Average
5 *	5510.000	106.59	31.80	6.40	36.88	107.91	68.20	39.71	HORIZONTAL Peak


Test Mode: 03; Polarity: Vertical; Modulation:802.11ax;Bandwidth:40MHz; Channel:Low



Trace: (Discrete)

	Freq	Read	Antenna	Cable	Preamp	Limit	Over		
	MHz	Level	Factor	Loss	Factor	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	5447.756	49.53	31.79	6.26	36.88	50.70	54.00	-3.30	VERTICAL Average
2	5447.756	61.80	31.79	6.26	36.88	62.97	74.00	-11.03	VERTICAL Peak
3	5467.173	60.98	31.80	6.31	36.88	62.21	68.20	-5.99	VERTICAL Peak
4	5510.000	94.16	31.80	6.40	36.88	95.48	-----	-----	VERTICAL Average
5 *	5510.000	106.99	31.80	6.40	36.88	108.31	68.20	40.11	VERTICAL Peak


Test Mode: 03; Polarity: Horizontal; Modulation: 802.11ax; Bandwidth: 40MHz; Channel: High



Trace: (Discrete)

	Freq	ReadAntenna	Cable	Preamp	Limit	Over		
	MHz	Level	Factor	Loss	Factor	Line	Limit	Pol/Phase
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dB	dB
1 *	5670.000	104.89	31.97	6.37	36.89	106.34	68.20	38.14 HORIZONTAL Peak
2	5725.000	61.21	32.07	6.25	36.89	62.64	68.20	-5.56 HORIZONTAL Peak
3	5759.487	62.43	32.13	6.15	36.89	63.82	68.20	-4.38 HORIZONTAL Peak


Test Mode: 03; Polarity: Vertical; Modulation: 802.11ax; Bandwidth: 40MHz; Channel: High



Trace: (Discrete)


	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Limit Level	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dB		
1 *	5670.000	106.83	31.97	6.37	36.89	108.28	68.20	40.08	VERTICAL Peak
2	5725.000	61.24	32.07	6.25	36.89	62.67	68.20	-5.53	VERTICAL Peak
3	5759.063	62.80	32.13	6.15	36.89	64.19	68.20	-4.01	VERTICAL Peak

Test Mode: 03; Polarity: Horizontal; Modulation:802.11ax; Bandwidth:80MHz; Channel:Low



		Read	Antenna	Cable	Preamp		Limit	Over		
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	5438.204	61.52	31.79	6.20	36.88	62.63	74.00	-11.37	HORIZONTAL	Peak
2	5450.879	49.57	31.79	6.26	36.88	50.74	54.00	-3.26	HORIZONTAL	Average
3	5468.064	61.20	31.80	6.31	36.88	62.43	68.20	-5.77	HORIZONTAL	Peak
4	5530.000	90.19	31.83	6.37	36.89	91.50	-----	-----	HORIZONTAL	Average
5 *	5530.000	101.97	31.83	6.37	36.89	103.28	68.20	35.08	HORIZONTAL	Peak


Test Mode: 03; Polarity: Vertical; Modulation:802.11ax; Bandwidth:80MHz; Channel:Low



Trace: (Discrete)


	Freq	Read	Antenna	Cable	Preamp	Limit	Over		
	MHz	Level	Factor	Loss	Factor	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	5442.663	49.55	31.79	6.20	36.88	50.66	54.00	-3.34	VERTICAL Average
2	5452.667	61.79	31.79	6.26	36.88	62.96	74.00	-11.04	VERTICAL Peak
3	5468.961	61.24	31.80	6.31	36.88	62.47	68.20	-5.73	VERTICAL Peak
4	5530.000	89.72	31.83	6.37	36.89	91.03	-----	-----	VERTICAL Average
5 *	5530.000	102.85	31.83	6.37	36.89	104.16	68.20	35.96	VERTICAL Peak

Test Mode: 03; Polarity: Horizontal; Modulation:802.11ax; Bandwidth:80MHz; Channel:High




	Read	Antenna	Cable	Preamp	Limit	Over		
Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	Remark
1 *	5610.000	102.10	31.91	6.32	36.89	103.44	68.20	35.24 HORIZONTAL Peak
2	5748.815	62.34	32.10	6.20	36.89	63.75	68.20	-4.45 HORIZONTAL Peak

Test Mode: 03; Polarity: Vertical; Modulation:802.11ax; Bandwidth:80MHz; Channel:High



	Freq	ReadAntenna Level	Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1 *	5610.000	103.71	31.91	6.32	36.89	105.05	68.20	36.85	VERTICAL	Peak
2	5739.681	62.20	32.10	6.20	36.89	63.61	68.20	-4.59	VERTICAL	Peak


Test Mode: 04; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:Low



Trace: (Discrete)


	Freq	ReadAntenna Level	Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	5648.304	61.93	31.95	6.35	36.89	63.34	68.20	-4.86	HORIZONTAL	Peak
2	5715.000	61.63	32.04	6.33	36.89	63.11	109.40	-46.29	HORIZONTAL	Peak
3	5725.000	61.74	32.07	6.25	36.89	63.17	122.20	-59.03	HORIZONTAL	Peak
4	5745.000	104.31	32.10	6.20	36.89	105.72	125.20	-19.48	HORIZONTAL	Peak

Test Mode: 04; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:Low



		Read	Antenna	Cable	Preamp		Limit	Over		
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	5641.798	62.46	31.95	6.35	36.89	63.87	68.20	-4.33	VERTICAL	Peak
2	5715.000	63.78	32.04	6.33	36.89	65.26	109.40	-44.14	VERTICAL	Peak
3	5725.000	66.79	32.07	6.25	36.89	68.22	122.20	-53.98	VERTICAL	Peak
4	5745.000	109.27	32.10	6.20	36.89	110.68	125.20	-14.52	VERTICAL	Peak


Test Mode: 04; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:High



Trace: (Discrete)

		Read	Antenna	Cable	Preamp		Limit	Over		
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	5825.000	103.88	32.23	6.04	36.90	105.25	125.20	-19.95	HORIZONTAL	Peak
2	5850.000	61.63	32.25	6.00	36.90	62.98	122.20	-59.22	HORIZONTAL	Peak
3	5860.000	62.73	32.27	5.96	36.90	64.06	109.40	-45.34	HORIZONTAL	Peak
4	5944.843	63.42	32.36	6.05	36.90	64.93	68.20	-3.27	HORIZONTAL	Peak


Test Mode: 04; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:High



Trace: (Discrete)

		Read	Antenna	Cable	Preamp		Limit	Over		
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	5825.000	108.90	32.23	6.04	36.90	110.27	125.20	-14.93	VERTICAL	Peak
2	5850.000	65.13	32.25	6.00	36.90	66.48	122.20	-55.72	VERTICAL	Peak
3	5860.000	63.71	32.27	5.96	36.90	65.04	109.40	-44.36	VERTICAL	Peak
4	5942.488	63.31	32.36	6.05	36.90	64.82	68.20	-3.38	VERTICAL	Peak


Test Mode: 04; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:Low



Trace: (Discrete)


	Freq	ReadAntenna Level	Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	5644.150	62.11	31.95	6.35	36.89	63.52	68.20	-4.68	HORIZONTAL	Peak
2	5715.000	61.17	32.04	6.33	36.89	62.65	109.40	-46.75	HORIZONTAL	Peak
3	5725.000	61.83	32.07	6.25	36.89	63.26	122.20	-58.94	HORIZONTAL	Peak
4	5745.000	104.41	32.10	6.20	36.89	105.82	125.20	-19.38	HORIZONTAL	Peak

Test Mode: 04; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:Low




	Freq	ReadAntenna Level	Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	5643.735	61.95	31.95	6.35	36.89	63.36	68.20	-4.84	VERTICAL	Peak
2	5715.000	63.18	32.04	6.33	36.89	64.66	109.40	-44.74	VERTICAL	Peak
3	5725.000	65.20	32.07	6.25	36.89	66.63	122.20	-55.57	VERTICAL	Peak
4	5745.000	109.40	32.10	6.20	36.89	110.81	125.20	-14.39	VERTICAL	Peak

Test Mode: 04; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:High



	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Limit Level	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dB		
1	5825.000	104.22	32.23	6.04	36.90	105.59	125.20	-19.61	HORIZONTAL Peak
2	5850.000	61.70	32.25	6.00	36.90	63.05	122.20	-59.15	HORIZONTAL Peak
3	5860.000	62.27	32.27	5.96	36.90	63.60	109.40	-45.80	HORIZONTAL Peak
4	5936.368	64.42	32.34	6.00	36.90	65.86	68.20	-2.34	HORIZONTAL Peak


Test Mode: 04; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:High



Trace: (Discrete)

	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Limit Level	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dB		
1	5825.000	108.97	32.23	6.04	36.90	110.34	125.20	-14.86	VERTICAL Peak
2	5850.000	64.87	32.25	6.00	36.90	66.22	122.20	-55.98	VERTICAL Peak
3	5860.000	64.95	32.27	5.96	36.90	66.28	109.40	-43.12	VERTICAL Peak
4	5932.762	63.35	32.34	6.00	36.90	64.79	68.20	-3.41	VERTICAL Peak


Test Mode: 04; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:Low



Trace: (Discrete)

	Read	Antenna	Cable	Preamp	Limit	Over		
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	5649.029	62.31	31.95	6.35	36.89	63.72	68.20	-4.48
2	5715.000	61.19	32.04	6.33	36.89	62.67	109.40	-46.73
3	5725.000	62.08	32.07	6.25	36.89	63.51	122.20	-58.69
4	5755.000	103.79	32.10	6.20	36.89	105.20	125.20	-20.00


Test Mode: 04; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:Low



Trace: (Discrete)

	Freq	ReadAntenna Level	Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	5641.376	62.19	31.95	6.35	36.89	63.60	68.20	-4.60	VERTICAL	Peak
2	5715.000	63.57	32.04	6.33	36.89	65.05	109.40	-44.35	VERTICAL	Peak
3	5725.000	65.18	32.07	6.25	36.89	66.61	122.20	-55.59	VERTICAL	Peak
4	5755.000	105.82	32.10	6.20	36.89	107.23	125.20	-17.97	VERTICAL	Peak


Test Mode: 04; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:High



Trace: (Discrete)

	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Limit Level	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	5795.000	102.96	32.19	6.10	36.89	104.36	125.20	-20.84	HORIZONTAL Peak
2	5850.000	61.97	32.25	6.00	36.90	63.32	122.20	-58.88	HORIZONTAL Peak
3	5860.000	62.35	32.27	5.96	36.90	63.68	109.40	-45.72	HORIZONTAL Peak
4	5936.868	62.87	32.34	6.00	36.90	64.31	68.20	-3.89	HORIZONTAL Peak


Test Mode: 04; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:High



Trace: (Discrete)


		Read	Antenna	Cable	Preamp		Limit	Over		
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	5795.000	106.69	32.19	6.10	36.89	108.09	125.20	-17.11	VERTICAL	Peak
2	5850.000	63.95	32.25	6.00	36.90	65.30	122.20	-56.90	VERTICAL	Peak
3	5860.000	63.99	32.27	5.96	36.90	65.32	109.40	-44.08	VERTICAL	Peak
4	5928.544	63.10	32.34	6.00	36.90	64.54	68.20	-3.66	VERTICAL	Peak

Test Mode: 04; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:20MHz; Channel:Low



		ReadAntenna	Cable	Preamp		Limit	Over			
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	5640.830	62.38	31.95	6.35	36.89	63.79	68.20	-4.41	HORIZONTAL	Peak
2	5715.000	61.86	32.04	6.33	36.89	63.34	109.40	-46.06	HORIZONTAL	Peak
3	5725.000	61.84	32.07	6.25	36.89	63.27	122.20	-58.93	HORIZONTAL	Peak
4	5745.000	104.23	32.10	6.20	36.89	105.64	125.20	-19.56	HORIZONTAL	Peak


Test Mode: 04; Polarity: Vertical; Modulation:802.11ac; Bandwidth:20MHz; Channel:Low



Trace: (Discrete)

		ReadAntenna	Cable	Preamp		Limit	Over			
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	5648.026	62.09	31.95	6.35	36.89	63.50	68.20	-4.70	VERTICAL	Peak
2	5715.000	62.15	32.04	6.33	36.89	63.63	109.40	-45.77	VERTICAL	Peak
3	5725.000	65.12	32.07	6.25	36.89	66.55	122.20	-55.65	VERTICAL	Peak
4	5745.000	107.32	32.10	6.20	36.89	108.73	125.20	-16.47	VERTICAL	Peak


Test Mode: 04; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:20MHz; Channel:High



Trace: (Discrete)

	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Limit Level	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dB		
1	5825.000	104.44	32.23	6.04	36.90	105.81	125.20	-19.39	HORIZONTAL Peak
2	5850.000	62.51	32.25	6.00	36.90	63.86	122.20	-58.34	HORIZONTAL Peak
3	5860.000	63.13	32.27	5.96	36.90	64.46	109.40	-44.94	HORIZONTAL Peak
4	5943.586	62.80	32.36	6.05	36.90	64.31	68.20	-3.89	HORIZONTAL Peak


Test Mode: 04; Polarity: Vertical; Modulation:802.11ac; Bandwidth:20MHz; Channel:High



Trace: (Discrete)


	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Limit Level	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dB		
1	5825.000	107.26	32.23	6.04	36.90	108.63	125.20	-16.57	VERTICAL Peak
2	5850.000	62.02	32.25	6.00	36.90	63.37	122.20	-58.83	VERTICAL Peak
3	5860.000	62.22	32.27	5.96	36.90	63.55	109.40	-45.85	VERTICAL Peak
4	5936.996	63.69	32.34	6.00	36.90	65.13	68.20	-3.07	VERTICAL Peak

Test Mode: 04; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:40MHz; Channel:Low




		Read	Antenna	Cable	Preamp		Limit	Over		
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	5645.354	62.64	31.95	6.35	36.89	64.05	68.20	-4.15	HORIZONTAL	Peak
2	5715.000	61.67	32.04	6.33	36.89	63.15	109.40	-46.25	HORIZONTAL	Peak
3	5725.000	62.65	32.07	6.25	36.89	64.08	122.20	-58.12	HORIZONTAL	Peak
4	5755.000	104.56	32.10	6.20	36.89	105.97	125.20	-19.23	HORIZONTAL	Peak

Test Mode: 04; Polarity: Vertical; Modulation:802.11ac; Bandwidth:40MHz; Channel:Low



	Freq	ReadAntenna Level	Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	5643.365	61.92	31.95	6.35	36.89	63.33	68.20	-4.87	VERTICAL	Peak
2	5715.000	62.89	32.04	6.33	36.89	64.37	109.40	-45.03	VERTICAL	Peak
3	5725.000	65.61	32.07	6.25	36.89	67.04	122.20	-55.16	VERTICAL	Peak
4	5755.000	105.96	32.10	6.20	36.89	107.37	125.20	-17.83	VERTICAL	Peak


Test Mode: 04; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:40MHz; Channel:High



Trace: (Discrete)

	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Limit Level	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	5795.000	102.64	32.19	6.10	36.89	104.04	125.20	-21.16	HORIZONTAL Peak
2	5850.000	62.00	32.25	6.00	36.90	63.35	122.20	-58.85	HORIZONTAL Peak
3	5860.000	62.36	32.27	5.96	36.90	63.69	109.40	-45.71	HORIZONTAL Peak
4	5941.339	63.27	32.36	6.05	36.90	64.78	68.20	-3.42	HORIZONTAL Peak


Test Mode: 04; Polarity: Vertical; Modulation:802.11ac; Bandwidth:40MHz; Channel:High



Trace: (Discrete)

	Freq	Read	Antenna	Cable	Preamp	Limit	Over		
	MHz	Level	Factor	Loss	Factor	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	5795.000	102.87	32.19	6.10	36.89	104.27	125.20	-20.93	VERTICAL Peak
2	5850.000	63.04	32.25	6.00	36.90	64.39	122.20	-57.81	VERTICAL Peak
3	5860.000	62.13	32.27	5.96	36.90	63.46	109.40	-45.94	VERTICAL Peak
4	5925.907	62.82	32.34	6.00	36.90	64.26	68.20	-3.94	VERTICAL Peak


Test Mode: 04; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:80MHz; Channel:middle



Trace: (Discrete)


		ReadAntenna		Cable	Preamp		Limit	Over		
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	5717.159	64.83	32.04	6.33	36.89	66.31	110.01	-43.70	HORIZONTAL	Peak
2	5775.000	101.81	32.16	6.10	36.89	103.18	125.20	-22.02	HORIZONTAL	Peak
3	5853.041	65.50	32.25	6.00	36.90	66.85	115.27	-48.42	HORIZONTAL	Peak
4	5933.114	63.34	32.34	6.00	36.90	64.78	68.20	-3.42	HORIZONTAL	Peak

Test Mode: 04; Polarity: Vertical; Modulation:802.11ac; Bandwidth:80MHz; Channel:middle



	Freq	ReadAntenna Level Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	5718.966	68.38	32.04	6.33	36.89	69.86	110.51	-40.65	VERTICAL Peak
2	5775.000	104.64	32.16	6.10	36.89	106.01	125.20	-19.19	VERTICAL Peak
3	5856.741	67.01	32.27	5.96	36.90	68.34	110.31	-41.97	VERTICAL Peak
4	5934.677	63.24	32.34	6.00	36.90	64.68	68.20	-3.52	VERTICAL Peak


Test Mode: 04; Polarity: Horizontal; Modulation:802.11ax; Bandwidth:20MHz; Channel:Low



Trace: (Discrete)

	Freq	ReadAntenna Level Factor	Cable Loss	Preamp Factor	Level	Limit Line	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	5644.012	61.96	31.95	6.35	36.89	63.37	68.20	-4.83	HORIZONTAL Peak
2	5715.000	61.18	32.04	6.33	36.89	62.66	109.40	-46.74	HORIZONTAL Peak
3	5725.000	62.08	32.07	6.25	36.89	63.51	122.20	-58.69	HORIZONTAL Peak
4	5745.000	104.03	32.10	6.20	36.89	105.44	125.20	-19.76	HORIZONTAL Peak


Test Mode: 04; Polarity: Vertical; Modulation:802.11ax; Bandwidth:20MHz; Channel:Low



Trace: (Discrete)

		ReadAntenna		Cable	Preamp		Limit	Over		
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	5646.642	62.14	31.95	6.35	36.89	63.55	68.20	-4.65	VERTICAL	Peak
2	5715.000	62.29	32.04	6.33	36.89	63.77	109.40	-45.63	VERTICAL	Peak
3	5725.000	64.15	32.07	6.25	36.89	65.58	122.20	-56.62	VERTICAL	Peak
4	5745.000	105.45	32.10	6.20	36.89	106.86	125.20	-18.34	VERTICAL	Peak


Test Mode: 04; Polarity: Horizontal; Modulation:802.11ax; Bandwidth:20MHz; Channel:High



Trace: (Discrete)

	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Limit Level	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dB		
1	5825.000	105.92	32.23	6.04	36.90	107.29	125.20	-17.91	HORIZONTAL Peak
2	5850.000	63.87	32.25	6.00	36.90	65.22	122.20	-56.98	HORIZONTAL Peak
3	5860.000	62.73	32.27	5.96	36.90	64.06	109.40	-45.34	HORIZONTAL Peak
4	5941.546	63.37	32.36	6.05	36.90	64.88	68.20	-3.32	HORIZONTAL Peak


Test Mode: 04; Polarity: Vertical; Modulation:802.11ax; Bandwidth:20MHz; Channel:High



Trace: (Discrete)


	Freq	ReadAntenna	Cable	Preamp	Limit	Over			
	MHz	Level	Factor	Loss	Factor	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	5825.000	107.97	32.23	6.04	36.90	109.34	125.20	-15.86	VERTICAL Peak
2	5850.000	66.35	32.25	6.00	36.90	67.70	122.20	-54.50	VERTICAL Peak
3	5860.000	65.75	32.27	5.96	36.90	67.08	109.40	-42.32	VERTICAL Peak
4	5942.017	63.25	32.36	6.05	36.90	64.76	68.20	-3.44	VERTICAL Peak

Test Mode: 04; Polarity: Horizontal; Modulation:802.11ax; Bandwidth:40MHz; Channel:Low




		ReadAntenna		Cable	Preamp		Limit	Over		
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	5645.507	62.68	31.95	6.35	36.89	64.09	68.20	-4.11	HORIZONTAL	Peak
2	5715.000	61.20	32.04	6.33	36.89	62.68	109.40	-46.72	HORIZONTAL	Peak
3	5725.000	64.10	32.07	6.25	36.89	65.53	122.20	-56.67	HORIZONTAL	Peak
4	5755.000	103.38	32.10	6.20	36.89	104.79	125.20	-20.41	HORIZONTAL	Peak

Test Mode: 04; Polarity: Vertical; Modulation:802.11ax; Bandwidth:40MHz; Channel:Low




	ReadAntenna	Cable	Preamp	Limit	Over				
Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	5648.723	61.87	31.95	6.35	36.89	63.28	68.20	-4.92	VERTICAL Peak
2	5715.000	64.20	32.04	6.33	36.89	65.68	109.40	-43.72	VERTICAL Peak
3	5725.000	66.02	32.07	6.25	36.89	67.45	122.20	-54.75	VERTICAL Peak
4	5755.000	105.00	32.10	6.20	36.89	106.41	125.20	-18.79	VERTICAL Peak

Test Mode: 04; Polarity: Horizontal; Modulation:802.11ax; Bandwidth:40MHz; Channel:High




		Read	Antenna	Cable	Preamp		Limit	Over		
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	5795.000	103.73	32.19	6.10	36.89	105.13	125.20	-20.07	HORIZONTAL	Peak
2	5850.000	62.60	32.25	6.00	36.90	63.95	122.20	-58.25	HORIZONTAL	Peak
3	5860.000	62.45	32.27	5.96	36.90	63.78	109.40	-45.62	HORIZONTAL	Peak
4	5927.327	63.17	32.34	6.00	36.90	64.61	68.20	-3.59	HORIZONTAL	Peak

Test Mode: 04; Polarity: Vertical; Modulation:802.11ax; Bandwidth:40MHz; Channel:High




	Freq	ReadAntenna	Cable	Preamp	Limit	Over			
	MHz	Level	Factor	Loss	Factor	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	5795.000	104.62	32.19	6.10	36.89	106.02	125.20	-19.18	VERTICAL Peak
2	5850.000	61.68	32.25	6.00	36.90	63.03	122.20	-59.17	VERTICAL Peak
3	5860.000	62.78	32.27	5.96	36.90	64.11	109.40	-45.29	VERTICAL Peak
4	5936.461	63.16	32.34	6.00	36.90	64.60	68.20	-3.60	VERTICAL Peak

Test Mode: 04; Polarity: Horizontal; Modulation:802.11ax; Bandwidth:80MHz; Channel:middle



	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
		Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	5724.993	65.75	32.07	6.25	36.89	67.18	122.18	-55.00	HORIZONTAL	Peak
2	5775.000	102.38	32.16	6.10	36.89	103.75	125.20	-21.45	HORIZONTAL	Peak
3	5858.900	63.20	32.27	5.96	36.90	64.53	109.71	-45.18	HORIZONTAL	Peak
4	5934.677	62.84	32.34	6.00	36.90	64.28	68.20	-3.92	HORIZONTAL	Peak

Test Mode: 04; Polarity: Vertical; Modulation:802.11ax; Bandwidth:80MHz; Channel:middle



	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
		Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	5723.184	67.61	32.07	6.25	36.89	69.04	118.06	-49.02	VERTICAL	Peak
2	5775.000	103.87	32.16	6.10	36.89	105.24	125.20	-19.96	VERTICAL	Peak
3	5856.432	68.41	32.27	5.96	36.90	69.74	110.40	-40.66	VERTICAL	Peak
4	5928.117	63.38	32.34	6.00	36.90	64.82	68.20	-3.38	VERTICAL	Peak

7.10 Frequency Stability

Test Requirement 47 CFR Part 15, Subpart C 15.407 (g)
Test Method: ANSI C63.10 (2013) Section 6.8

7.10.1 E.U.T. Operation

Operating Environment:
Temperature: 21.3 °C Humidity: 50.9 % RH Atmospheric Pressure: 1015 mbar

7.10.2 Test Mode Description

Pre-scan / Final test	Mode Code	Description
		TX mode (U-NII-1)_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n(HT20); data rate @ MCS0 is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT20); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT80); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE20); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE40); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE80). Only the data of worst case is recorded in the report.
Final test	01	
		TX mode (U-NII-2A)_Keep the EUT in continuously transmitting mode with all modulation types.All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n(HT20); data rate @ MCS0 is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT20); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT80); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE20); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE40); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE80). Only the data of worst case is recorded in the report.
Final test	02	
		TX mode (U-NII-2C)_Keep the EUT in continuously transmitting mode with all modulation types.All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n(HT20); data rate @ MCS0 is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT20); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT80); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE20); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE40); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE80). Only the data of worst case is recorded in the report.
Final test	03	
		TX mode (U-NII-3)_Keep the EUT in continuously transmitting mode with all modulation types.All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n(HT20); data rate @ MCS0 is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT20); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT80); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE20); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE40); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE80). Only the data of worst case is recorded in the report.
Final test	04	




Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained herein reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

IEEE 802.11ac(VHT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT80); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE20); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE40); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE80). Only the data of worst case is recorded in the report.

7.10.3 Test Setup Diagram



7.10.4 Measurement Procedure and Data

Please Refer to Appendix for Details

7.11 Radiated Emissions (above 1GHz)

Test Requirement 47 CFR Part 15, Subpart C 15.209 & 15.407(b)

Test Method: KDB 789033 D02 II G

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

*(1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

(2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

(3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

(4) For transmitters operating in the 5.725-5.85 GHz band:

(i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

7.11.1 E.U.T. Operation

Operating Environment:

Temperature: 21.5 °C

Humidity: 52.7 % RH

Atmospheric Pressure: 1015 mbar



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/terms-and-conditions/terms-e-document.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

7.11.2 Test Mode Description


Pre-scan / Final test	Mode Code	Description
		TX mode (U-NII-1)_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n(HT20); data rate @ MCS0 is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT20); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT80); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE20); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE40); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE80). Only the data of worst case is recorded in the report.
Final test	01	
		TX mode (U-NII-2A)_Keep the EUT in continuously transmitting mode with all modulation types.All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n(HT20); data rate @ MCS0 is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT20); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT80); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE20); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE40); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE80). Only the data of worst case is recorded in the report.
Final test	02	
		TX mode (U-NII-2C)_Keep the EUT in continuously transmitting mode with all modulation types.All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n(HT20); data rate @ MCS0 is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT20); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT80); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE20); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE40); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE80). Only the data of worst case is recorded in the report.
Final test	03	
		TX mode (U-NII-3)_Keep the EUT in continuously transmitting mode with all modulation types.All data rates for each modulation type have been tested and found the data rate @ 6Mbps is the worst case of IEEE 802.11a; data rate @ MCS0 is the worst case of IEEE 802.11n(HT20); data rate @ MCS0 is the worst case of IEEE 802.11n(HT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT20); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT40); data rate @ MCS0 is the worst case of IEEE 802.11ac(VHT80); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE20); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE40); data rate @ MCS0 is the worst case of IEEE 802.11ax(HE80). Only the data of worst case is recorded in the report.
Final test	04	



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained herein reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

7.11.3 Test Setup Diagram




7.11.4 Measurement Procedure and Data

- a. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- g. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- i. Repeat above procedures until all frequencies measured was complete.

Remark:

1. Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
2. Scan from 1GHz to 40GHz, the disturbance above 18GHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
4. As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.


Test Mode: 01; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:Low



Trace: (Discrete)

	Freq	Read	Antenna	Cable	Preamp	Limit	Over		
	MHz	Level	Factor	Loss	Factor	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dB		
1	1271.123	43.79	25.11	2.46	38.33	33.03	68.20	-35.17	HORIZONTAL Peak
2	1702.042	44.13	25.72	2.80	37.89	34.76	74.00	-39.24	HORIZONTAL Peak
3	3455.508	46.19	28.88	4.20	36.96	42.31	68.20	-25.89	HORIZONTAL Peak
4	4392.376	45.84	30.66	4.70	36.81	44.39	74.00	-29.61	HORIZONTAL Peak
5	10360.000	41.19	39.28	7.29	37.37	50.39	68.20	-17.81	HORIZONTAL Peak
6	15540.000	37.64	39.05	9.88	35.39	51.18	74.00	-22.82	HORIZONTAL Peak


Test Mode: 01; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:Low



Trace: (Discrete)

	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1145.507	44.60	24.48	2.32	38.42	32.98	74.00	-41.02	VERTICAL	Peak
2	1702.042	44.06	25.72	2.80	37.89	34.69	74.00	-39.31	VERTICAL	Peak
3	3435.590	45.70	28.87	4.16	36.97	41.76	68.20	-26.44	VERTICAL	Peak
4	4430.628	46.24	30.72	4.78	36.81	44.93	68.20	-23.27	VERTICAL	Peak
5	10360.000	40.61	39.28	7.29	37.37	49.81	68.20	-18.39	VERTICAL	Peak
6	15540.000	38.13	39.05	9.88	35.39	51.67	74.00	-22.33	VERTICAL	Peak


Test Mode: 01; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:middle



Trace: (Discrete)

	Freq	Read	Antenna	Cable	Preamp	Limit	Over		
	MHz	Level	Factor	Loss	Factor	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dB		
1	1249.269	43.84	25.02	2.34	38.35	32.85	68.20	-35.35	HORIZONTAL Peak
2	1687.347	44.44	25.69	2.80	37.91	35.02	74.00	-38.98	HORIZONTAL Peak
3	3435.590	46.52	28.87	4.16	36.97	42.58	68.20	-25.62	HORIZONTAL Peak
4	4443.453	45.43	30.73	4.83	36.81	44.18	68.20	-24.02	HORIZONTAL Peak
5	10400.000	40.84	39.33	7.32	37.36	50.13	68.20	-18.07	HORIZONTAL Peak
6	15600.000	38.77	38.99	9.88	35.39	52.25	74.00	-21.75	HORIZONTAL Peak


Test Mode: 01; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:middle



Trace: (Discrete)

	Freq	Read	Antenna	Cable	Preamp	Limit	Over		
	MHz	Level	Factor	Loss	Factor	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dB		
1	1135.617	44.59	24.45	2.25	38.43	32.86	74.00	-41.14	VERTICAL Peak
2	1697.129	44.02	25.71	2.80	37.89	34.64	74.00	-39.36	VERTICAL Peak
3	3465.510	45.65	28.88	4.22	36.95	41.80	68.20	-26.40	VERTICAL Peak
4	4304.400	45.95	30.48	4.65	36.81	44.27	74.00	-29.73	VERTICAL Peak
5	10400.000	40.18	39.33	7.32	37.36	49.47	68.20	-18.73	VERTICAL Peak
6	15600.000	38.39	38.99	9.88	35.39	51.87	74.00	-22.13	VERTICAL Peak


Test Mode: 01; Polarity: Horizontal; Modulation:802.11a; Bandwidth:20MHz; Channel:High



Trace: (Discrete)

	Freq	Read	Antenna	Cable	Preamp	Limit	Over		
	MHz	Level	Factor	Loss	Factor	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dB		
1	1267.454	44.13	25.10	2.44	38.33	33.34	68.20	-34.86	HORIZONTAL Peak
2	1565.191	44.56	25.55	2.80	38.00	34.91	74.00	-39.09	HORIZONTAL Peak
3	3485.601	45.56	28.89	4.27	36.95	41.77	68.20	-26.43	HORIZONTAL Peak
4	4354.454	45.77	30.59	4.68	36.81	44.23	74.00	-29.77	HORIZONTAL Peak
5	10480.000	40.18	39.46	7.40	37.36	49.68	68.20	-18.52	HORIZONTAL Peak
6	15720.000	37.82	38.78	9.87	35.39	51.08	74.00	-22.92	HORIZONTAL Peak


Test Mode: 01; Polarity: Vertical; Modulation:802.11a; Bandwidth:20MHz; Channel:High



Trace: (Discrete)

	Freq	Read	Antenna	Cable	Preamp	Limit	Over		
	MHz	Level	Factor	Loss	Factor	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dB		
1	1148.823	44.59	24.49	2.34	38.42	33.00	74.00	-41.00	VERTICAL Peak
2	1663.137	44.38	25.65	2.80	37.91	34.92	74.00	-39.08	VERTICAL Peak
3	3445.535	46.31	28.87	4.18	36.96	42.40	68.20	-25.80	VERTICAL Peak
4	4329.354	46.16	30.54	4.67	36.81	44.56	74.00	-29.44	VERTICAL Peak
5	10480.000	40.11	39.46	7.40	37.36	49.61	68.20	-18.59	VERTICAL Peak
6	15720.000	38.11	38.78	9.87	35.39	51.37	74.00	-22.63	VERTICAL Peak


Test Mode: 01; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:Low



Trace: (Discrete)

	Freq	Read	Antenna	Cable	Preamp	Limit	Over		
	MHz	Level	Factor	Loss	Factor	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dB		
1	1145.507	45.06	24.48	2.32	38.42	33.44	74.00	-40.56	HORIZONTAL Peak
2	1697.129	44.02	25.71	2.80	37.89	34.64	74.00	-39.36	HORIZONTAL Peak
3	3465.510	46.02	28.88	4.22	36.95	42.17	68.20	-26.03	HORIZONTAL Peak
4	4495.125	44.99	30.80	5.05	36.82	44.02	68.20	-24.18	HORIZONTAL Peak
5	10360.000	40.35	39.28	7.29	37.37	49.55	68.20	-18.65	HORIZONTAL Peak
6	15540.000	37.67	39.05	9.88	35.39	51.21	74.00	-22.79	HORIZONTAL Peak


Test Mode: 01; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:Low



Trace: (Discrete)

	Freq	Read	Antenna	Cable	Preamp	Limit	Over		
	MHz	Level	Factor	Loss	Factor	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dB		
1	1249.269	43.99	25.02	2.34	38.35	33.00	68.20	-35.20	VERTICAL Peak
2	1653.550	44.33	25.64	2.80	37.93	34.84	68.20	-33.36	VERTICAL Peak
3	3445.535	45.55	28.87	4.18	36.96	41.64	68.20	-26.56	VERTICAL Peak
4	4291.977	45.94	30.45	4.64	36.81	44.22	74.00	-29.78	VERTICAL Peak
5	10360.000	40.14	39.28	7.29	37.37	49.34	68.20	-18.86	VERTICAL Peak
6	15540.000	37.43	39.05	9.88	35.39	50.97	74.00	-23.03	VERTICAL Peak


Test Mode: 01; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:middle



Trace: (Discrete)


	Freq	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Level	Limit	Over Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1285.904	43.00	25.16	2.53	38.33	32.36	68.20	-35.84	HORIZONTAL	Peak
2	1697.129	44.32	25.71	2.80	37.89	34.94	74.00	-39.06	HORIZONTAL	Peak
3	3465.510	46.07	28.88	4.22	36.95	42.22	68.20	-25.98	HORIZONTAL	Peak
4	4316.859	45.85	30.51	4.66	36.81	44.21	74.00	-29.79	HORIZONTAL	Peak
5	10400.000	40.28	39.33	7.32	37.36	49.57	68.20	-18.63	HORIZONTAL	Peak
6	15600.000	38.31	38.99	9.88	35.39	51.79	74.00	-22.21	HORIZONTAL	Peak

Test Mode: 01; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:middle




	Freq	Read	Antenna	Cable	Preamp	Limit	Over		
	MHz	Level	Factor	Loss	Factor	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dB		
1	1285.904	43.55	25.16	2.53	38.33	32.91	68.20	-35.29	VERTICAL Peak
2	1692.231	43.88	25.70	2.80	37.89	34.49	74.00	-39.51	VERTICAL Peak
3	3386.297	45.84	28.83	4.10	36.99	41.78	68.20	-26.42	VERTICAL Peak
4	4169.698	46.30	30.09	4.60	36.80	44.19	74.00	-29.81	VERTICAL Peak
5	10400.000	40.80	39.33	7.32	37.36	50.09	68.20	-18.11	VERTICAL Peak
6	15600.000	38.60	38.99	9.88	35.39	52.08	74.00	-21.92	VERTICAL Peak

Test Mode: 01; Polarity: Horizontal; Modulation:802.11n; Bandwidth:20MHz; Channel:High




	Freq	Read	Antenna	Cable	Preamp	Limit	Over		
	MHz	Level	Factor	Loss	Factor	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	1293.359	43.38	25.18	2.57	38.31	32.82	68.20	-35.38	HORIZONTAL Peak
2	1702.042	44.57	25.72	2.80	37.89	35.20	74.00	-38.80	HORIZONTAL Peak
3	3415.787	45.99	28.85	4.13	36.97	42.00	68.20	-26.20	HORIZONTAL Peak
4	4367.058	45.74	30.62	4.68	36.81	44.23	74.00	-29.77	HORIZONTAL Peak
5	10480.000	40.36	39.46	7.40	37.36	49.86	68.20	-18.34	HORIZONTAL Peak
6	15720.000	38.78	38.78	9.87	35.39	52.04	74.00	-21.96	HORIZONTAL Peak

Test Mode: 01; Polarity: Vertical; Modulation:802.11n; Bandwidth:20MHz; Channel:High



	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1274.802	43.99	25.12	2.48	38.33	33.26	68.20	-34.94	VERTICAL	Peak
2	1697.129	43.94	25.71	2.80	37.89	34.56	74.00	-39.44	VERTICAL	Peak
3	3475.541	45.87	28.89	4.25	36.95	42.06	68.20	-26.14	VERTICAL	Peak
4	4341.886	45.93	30.57	4.67	36.81	44.36	74.00	-29.64	VERTICAL	Peak
5	10480.000	39.80	39.46	7.40	37.36	49.30	68.20	-18.90	VERTICAL	Peak
6	15720.000	39.01	38.78	9.87	35.39	52.27	74.00	-21.73	VERTICAL	Peak


Test Mode: 01; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:Low



Trace: (Discrete)

	Freq	Read	Antenna	Cable	Preamp	Limit	Over		
	MHz	Level	Factor	Loss	Factor	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dB		
1	1203.199	44.15	24.70	2.34	38.39	32.80	74.00	-41.20	HORIZONTAL Peak
2	1692.231	44.36	25.70	2.80	37.89	34.97	74.00	-39.03	HORIZONTAL Peak
3	3415.787	46.55	28.85	4.13	36.97	42.56	68.20	-25.64	HORIZONTAL Peak
4	4050.904	46.57	29.87	4.60	36.80	44.24	74.00	-29.76	HORIZONTAL Peak
5	10380.000	40.01	39.33	7.32	37.37	49.29	68.20	-18.91	HORIZONTAL Peak
6	15570.000	37.87	38.99	9.88	35.39	51.35	74.00	-22.65	HORIZONTAL Peak


Test Mode: 01; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:Low



Trace: (Discrete)


	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1249.269	44.66	25.02	2.34	38.35	33.67	68.20	-34.53	VERTICAL	Peak
2	1677.621	45.02	25.68	2.80	37.91	35.59	74.00	-38.41	VERTICAL	Peak
3	3455.508	45.60	28.88	4.20	36.96	41.72	68.20	-26.48	VERTICAL	Peak
4	4495.125	45.32	30.80	5.05	36.82	44.35	68.20	-23.85	VERTICAL	Peak
5	10380.000	40.06	39.33	7.32	37.37	49.34	68.20	-18.86	VERTICAL	Peak
6	15570.000	38.53	38.99	9.88	35.39	52.01	74.00	-21.99	VERTICAL	Peak

Test Mode: 01; Polarity: Horizontal; Modulation:802.11n; Bandwidth:40MHz; Channel:High



	Freq	Read	Antenna	Cable	Preamp	Limit	Over		
	MHz	Level	Factor	Loss	Factor	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dB		
1	1168.920	44.54	24.55	2.39	38.40	33.08	74.00	-40.92	HORIZONTAL Peak
2	1677.621	44.44	25.68	2.80	37.91	35.01	74.00	-38.99	HORIZONTAL Peak
3	3415.787	46.03	28.85	4.13	36.97	42.04	68.20	-26.16	HORIZONTAL Peak
4	4206.011	45.97	30.18	4.60	36.81	43.94	74.00	-30.06	HORIZONTAL Peak
5	10460.000	40.40	39.42	7.37	37.36	49.83	68.20	-18.37	HORIZONTAL Peak
6	15690.000	38.41	38.86	9.87	35.39	51.75	74.00	-22.25	HORIZONTAL Peak


Test Mode: 01; Polarity: Vertical; Modulation:802.11n; Bandwidth:40MHz; Channel:High



Trace: (Discrete)

		ReadAntenna		Cable	Preamp		Limit	Over		
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1256.512	44.03	25.05	2.38	38.35	33.11	68.20	-35.09	VERTICAL	Peak
2	1672.779	45.14	25.67	2.80	37.91	35.70	74.00	-38.30	VERTICAL	Peak
3	3485.601	45.74	28.89	4.27	36.95	41.95	68.20	-26.25	VERTICAL	Peak
4	4341.886	45.47	30.57	4.67	36.81	43.90	74.00	-30.10	VERTICAL	Peak
5	10460.000	40.84	39.42	7.37	37.36	50.27	68.20	-17.93	VERTICAL	Peak
6	15690.000	38.39	38.86	9.87	35.39	51.73	74.00	-22.27	VERTICAL	Peak


Test Mode: 01; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:20MHz; Channel:Low



Trace: (Discrete)

	Freq	Read	Antenna	Cable	Preamp	Limit	Over		
	MHz	Level	Factor	Loss	Factor	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dB		
1	1217.190	44.44	24.79	2.32	38.37	33.18	74.00	-40.82	HORIZONTAL Peak
2	1587.975	44.62	25.57	2.80	37.98	35.01	74.00	-38.99	HORIZONTAL Peak
3	3485.601	45.90	28.89	4.27	36.95	42.11	68.20	-26.09	HORIZONTAL Peak
4	4379.699	45.24	30.64	4.69	36.81	43.76	74.00	-30.24	HORIZONTAL Peak
5	10360.000	40.41	39.28	7.29	37.37	49.61	68.20	-18.59	HORIZONTAL Peak
6	15540.000	38.22	39.05	9.88	35.39	51.76	74.00	-22.24	HORIZONTAL Peak


Test Mode: 01; Polarity: Vertical; Modulation:802.11ac; Bandwidth:20MHz; Channel:Low



Trace: (Discrete)


	Freq	Read	Antenna	Cable	Preamp	Limit	Over		
	MHz	Level	Factor	Loss	Factor	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dB		
1	1297.103	44.38	25.19	2.58	38.31	33.84	68.20	-34.36	VERTICAL Peak
2	1677.621	43.74	25.68	2.80	37.91	34.31	74.00	-39.69	VERTICAL Peak
3	3396.098	46.84	28.84	4.10	36.98	42.80	68.20	-25.40	VERTICAL Peak
4	4181.768	46.47	30.12	4.60	36.80	44.39	74.00	-29.61	VERTICAL Peak
5	10360.000	41.32	39.28	7.29	37.37	50.52	68.20	-17.68	VERTICAL Peak
6	15540.000	38.51	39.05	9.88	35.39	52.05	74.00	-21.95	VERTICAL Peak

Test Mode: 01; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:20MHz; Channel:middle




	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
		Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1162.182	44.55	24.53	2.40	38.42	33.06	74.00	-40.94	HORIZONTAL	Peak
2	1639.274	44.33	25.62	2.80	37.93	34.82	68.20	-33.38	HORIZONTAL	Peak
3	3425.675	46.36	28.86	4.15	36.97	42.40	68.20	-25.80	HORIZONTAL	Peak
4	4218.186	46.47	30.22	4.60	36.81	44.48	74.00	-29.52	HORIZONTAL	Peak
5	10400.000	40.36	39.33	7.32	37.36	49.65	68.20	-18.55	HORIZONTAL	Peak
6	15600.000	38.25	38.99	9.88	35.39	51.73	74.00	-22.27	HORIZONTAL	Peak

Test Mode: 01; Polarity: Vertical; Modulation:802.11ac; Bandwidth:20MHz; Channel:middle



	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1175.697	44.51	24.58	2.38	38.40	33.07	74.00	-40.93	VERTICAL	Peak
2	1574.265	44.37	25.56	2.80	38.00	34.73	74.00	-39.27	VERTICAL	Peak
3	3435.590	45.68	28.87	4.16	36.97	41.74	68.20	-26.46	VERTICAL	Peak
4	4417.841	46.22	30.70	4.74	36.81	44.85	68.20	-23.35	VERTICAL	Peak
5	10400.000	40.20	39.33	7.32	37.36	49.49	68.20	-18.71	VERTICAL	Peak
6	15600.000	38.52	38.99	9.88	35.39	52.00	74.00	-22.00	VERTICAL	Peak


Test Mode: 01; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:20MHz; Channel:High



Trace: (Discrete)


	Freq	Read	Antenna	Cable	Preamp	Limit	Over		
	MHz	Level	Factor	Loss	Factor	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dB		
1	1138.904	44.33	24.46	2.27	38.42	32.64	74.00	-41.36	HORIZONTAL Peak
2	1601.804	44.20	25.58	2.80	37.98	34.60	74.00	-39.40	HORIZONTAL Peak
3	3357.061	46.29	28.81	4.09	37.01	42.18	74.00	-31.82	HORIZONTAL Peak
4	4218.186	46.11	30.22	4.60	36.81	44.12	74.00	-29.88	HORIZONTAL Peak
5	10480.000	39.94	39.46	7.40	37.36	49.44	68.20	-18.76	HORIZONTAL Peak
6	15720.000	38.12	38.78	9.87	35.39	51.38	74.00	-22.62	HORIZONTAL Peak

Test Mode: 01; Polarity: Vertical; Modulation:802.11ac; Bandwidth:20MHz; Channel:High



	Freq	Read	Antenna	Cable	Preamp	Limit	Over		
	MHz	Level	Factor	Loss	Factor	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dB		
1	1297.103	43.97	25.19	2.58	38.31	33.43	68.20	-34.77	VERTICAL Peak
2	1687.347	45.30	25.69	2.80	37.91	35.88	74.00	-38.12	VERTICAL Peak
3	3318.471	45.53	28.77	4.07	37.02	41.35	68.20	-26.85	VERTICAL Peak
4	4157.664	46.48	30.06	4.60	36.80	44.34	74.00	-29.66	VERTICAL Peak
5	10480.000	39.92	39.46	7.40	37.36	49.42	68.20	-18.78	VERTICAL Peak
6	15720.000	38.73	38.78	9.87	35.39	51.99	74.00	-22.01	VERTICAL Peak


Test Mode: 01; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:40MHz; Channel:Low



Trace: (Discrete)

	Freq	Read	Antenna	Cable	Preamp	Limit	Over		
	MHz	Level	Factor	Loss	Factor	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dB		
1	1234.909	44.35	24.93	2.30	38.37	33.21	74.00	-40.79	HORIZONTAL Peak
2	1687.347	44.10	25.69	2.80	37.91	34.68	74.00	-39.32	HORIZONTAL Peak
3	3366.778	46.04	28.82	4.09	36.99	41.96	68.20	-26.24	HORIZONTAL Peak
4	4495.125	45.09	30.80	5.05	36.82	44.12	68.20	-24.08	HORIZONTAL Peak
5	10380.000	40.22	39.33	7.32	37.37	49.50	68.20	-18.70	HORIZONTAL Peak
6	15570.000	38.19	38.99	9.88	35.39	51.67	74.00	-22.33	HORIZONTAL Peak


Test Mode: 01; Polarity: Vertical; Modulation:802.11ac; Bandwidth:40MHz; Channel:Low



Trace: (Discrete)


	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1135.617	44.52	24.45	2.25	38.43	32.79	74.00	-41.21	VERTICAL	Peak
2	1574.265	44.53	25.56	2.80	38.00	34.89	74.00	-39.11	VERTICAL	Peak
3	3495.691	45.52	28.90	4.30	36.94	41.78	68.20	-26.42	VERTICAL	Peak
4	4456.315	45.55	30.75	4.88	36.81	44.37	68.20	-23.83	VERTICAL	Peak
5	10380.000	39.87	39.33	7.32	37.37	49.15	68.20	-19.05	VERTICAL	Peak
6	15570.000	37.89	38.99	9.88	35.39	51.37	74.00	-22.63	VERTICAL	Peak

Test Mode: 01; Polarity: Horizontal; Modulation:802.11ac; Bandwidth:40MHz; Channel:High



	Freq	Read	Antenna	Cable	Preamp	Limit	Over		
	MHz	Level	Factor	Loss	Factor	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dB		
1	1260.149	43.92	25.07	2.40	38.35	33.04	68.20	-35.16	HORIZONTAL Peak
2	1697.129	44.49	25.71	2.80	37.89	35.11	74.00	-38.89	HORIZONTAL Peak
3	3445.535	45.99	28.87	4.18	36.96	42.08	68.20	-26.12	HORIZONTAL Peak
4	4495.125	45.80	30.80	5.05	36.82	44.83	68.20	-23.37	HORIZONTAL Peak
5	10460.000	40.39	39.42	7.37	37.36	49.82	68.20	-18.38	HORIZONTAL Peak
6	15690.000	38.17	38.86	9.87	35.39	51.51	74.00	-22.49	HORIZONTAL Peak

Test Mode: 01; Polarity: Vertical; Modulation:802.11ac; Bandwidth:40MHz; Channel:High



Trace: (Discrete)

	Freq	ReadAntenna	Cable	Preamp		Limit	Over			
	MHz	Level	Factor	Loss	Factor	Level	Line	Limit	Pol/Phase	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB		
1	1148.823	44.21	24.49	2.34	38.42	32.62	74.00	-41.38	VERTICAL	Peak
2	1697.129	43.98	25.71	2.80	37.89	34.60	74.00	-39.40	VERTICAL	Peak
3	3485.601	45.87	28.89	4.27	36.95	42.08	68.20	-26.12	VERTICAL	Peak
4	4495.125	45.18	30.80	5.05	36.82	44.21	68.20	-23.99	VERTICAL	Peak
5	10460.000	39.81	39.42	7.37	37.36	49.24	68.20	-18.96	VERTICAL	Peak
6	15690.000	38.63	38.86	9.87	35.39	51.97	74.00	-22.03	VERTICAL	Peak