

www.tuv.com

Appendix 10

 Prüfbericht - Nr.:
 19660259 001
 Seite 1 von 2

 Test Report No.
 Page 1 of 2

RF Exposure Report

Following FCC KDB 447498 D01 General SAR test exclusion guidelines

The corresponding SAR exclusion threshold condition, listed below:

- 1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation Distances ≤ 50 mm are determined by: [(max. power of channel, including tune-up tolerance, mW)/ (min. test separation distance, mm)] · [√f (GHz)] ≤ 3.0 for 1-g SAR and ≤ 7.5 for 10-g Extremity SAR, where
 - f(GHz) is the RF channel transmit frequency in GHz
 - Power and distance are rounded to the nearest mW and mm before calculation.
 - The result is rounded to one decimal place for comparison The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion(447498 D01 General RF Exposure Guidance v05r02)
- 2) At 100 MHz to 6 GHz and for test separation distances > 50 mm, the SAR test exclusion threshold Is determined according to the following
 - [Power allowed at numeric threshold for 50 mm in step 1) + (test separation distance 50 mm)-(f(MHz)/150)] mW, at 100 MHz to 1500 MHz
 - [Power allowed at numeric threshold for 50 mm in step 1) + (test separation distance 50 mm)·10] mW at > 1500 MHz and \leq 6 GHz
- 3) At frequencies below 100 MHz, the following may be considered for SAR test exclusion,
 - The power threshold at the corresponding test separation distance at 100 MHz in step 2) is multiplied by [1 + log(100/f(MHz))] for test separation distances > 50 mm and < 200 mm
 - The power threshold determined by the equation in a) for 50 mm and 100 MHz is multiplied by ½ for test separation distances ≤ 50 mm
 - SAR measurement procedures are not established below 100 MHz When SAR test exclusion cannot be applied, a KDB inquiry is required to determine SAR evaluation requirements for any test results to be acceptable.



www.tuv.com

Appendix 10

Prüfbericht - Nr.:	19660259 001	Seite 2 von 2
Test Report No.	13000233 001	Page 2 of 2

SAR Test Exclusion Thresholds

Maximum Measured Transmitter Power:

Frequency (GHz)	Max.Power (mW)	Min.Test Separation distance	SAR Test Exclusion Calculation Values	1-g Extremity SAR Test exclusion Thresholds	Results
2.402 – 2.480	0.517	5mm	0.160	3	Pass

Hence, the EUT is exempted from routine SAR evaluation

Note:

1. Calculate SAR exclusion threshold from condition 1) formulas.

Daigram.

