

## Global United Technology Services Co., Ltd.

Report No.: GTS201608000121E04

# **FCC REPORT**

**Applicant:** Quantum Creations LLC.

Address of Applicant: 16410 NE 19th Avenue Suite 102 North, Miami Beach, Florida

United States 33162

**Equipment Under Test (EUT)** 

Product Name: PC Stick

A-1063-AAP, A-1063-AAP-1, A-1063-AAP-2, A-1063-AAP-3,

Model No.: A-1063-AAP-4, A-1063-AAP-5, A-1063-AAP-6,

A-1063-AAP-7, A-1063-AAP-8

Trade Mark: Azulle

**FCC ID:** 2AFJI20161063

Applicable standards: FCC CFR Title 47 Part 15 Subpart C Section 15.247:2015

Date of sample receipt: August 25, 2016

**Date of Test:** August 26-September 02, 2016

Date of report issued: September 07, 2016

Test Result: PASS \*

Authorized Signature:

Robinson Lo Laboratory Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the GTS product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of GTS or testing done by GTS in connection with, distribution or use of the product described in this report must be approved by GTS in writing.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

<sup>\*</sup> In the configuration tested, the EUT complied with the standards specified above.



## 2 Version

Version No.	Date	Description
00	September 07, 2016	Original

Prepared By:	Tiger Chan	Date:	September 07, 2016	
	Project Engineer			
Check By:	Andy wa	Date:	September 07, 2016	
	Reviewer			

Project No.: GTS201608000121

Page 2 of 31



## 3 Contents

			Page
1	COV	ER PAGE	1
2	VER	SION	2
3	CON	TENTS	3
4	TES	T SUMMARY	4
	4.1	MEASUREMENT UNCERTAINTY	4
5	GEN	ERAL INFORMATION	
	5.1	CLIENT INFORMATION	
	5.2	GENERAL DESCRIPTION OF EUT	5
	5.3	TEST MODE	
	5.4	DESCRIPTION OF SUPPORT UNITS	
	5.5	TEST FACILITY	
	5.6	TEST LOCATION	7
6	TES	T INSTRUMENTS LIST	8
7	TES	T RESULTS AND MEASUREMENT DATA	9
	7.1	ANTENNA REQUIREMENT	9
	7.2	CONDUCTED EMISSIONS	10
	7.3	CONDUCTED OUTPUT POWER	
	7.4	CHANNEL BANDWIDTH	
	7.5	Power Spectral Density	
	7.6	BAND EDGES	
	7.6.1		
	7.6.2		
	7.7	SPURIOUS EMISSION	
	7.7.1 7.7.2		
_			
8	TES	T SETUP PHOTO	30
g	FUT	CONSTRUCTIONAL DETAILS	31



## 4 Test Summary

Test Item	Section in CFR 47	Result
Antenna requirement	15.203/15.247 (c)	Pass
AC Power Line Conducted Emission	15.207	Pass
Conducted Output Power	15.247 (b)(3)	Pass
Channel Bandwidth	15.247 (a)(2)	Pass
Power Spectral Density	15.247 (e)	Pass
Band Edge	15.247(d)	Pass
Spurious Emission	15.205/15.209	Pass

Pass: The EUT complies with the essential requirements in the standard.

Remark: Test according to ANSI C63.10:2013 and ANSI C63.4:2014.

## 4.1 Measurement Uncertainty

Test Item	Frequency Range Measurement Uncertainty		Notes		
Radiated Emission	9kHz ~ 30MHz	± 4.34dB	(1)		
Radiated Emission	30MHz ~ 1000MHz	± 4.24dB	(1)		
Radiated Emission	1GHz ~ 26.5GHz	± 4.68dB	(1)		
AC Power Line Conducted Emission	0.15MHz ~ 30MHz	± 3.45dB	(1)		
Note (1): The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%.					



## **5** General Information

## 5.1 Client Information

Applicant:	Quantum Creations LLC.			
Address of Applicant:	16410 NE 19th Avenue Suite 102 North, Miami Beach, Florida United States 33162			
Manufacturer:	SHENZHEN MELE STAR TECHNOLOGY LIMITED			
Address of Manufacturer:	3F,Bldg#1,28 Cuijing Road, Pingshan New District, Shenzhen, PR China.			
Factory:	Shenzhen MeLE Precision Technology Limited			
Address of Factory:	3F East,Bldg#1,28 Cuijing Road, Pingshan New District, Shenzhen, PR China.			

## 5.2 General Description of EUT

Product Name:	PC Stick		
Model No.:	A-1063-AAP, A-1063-AAP-1, A-1063-AAP-2, A-1063-AAP-3,		
	A-1063-AAP-4, A-1063-AAP-5, A-1063-AAP-6, A-1063-AAP-7,		
	A-1063-AAP-8		
Operation Frequency:	2402MHz~2480MHz		
Channel Numbers:	40		
Channel Separation:	2MHz		
Modulation Type:	GFSK		
Antenna Type:	FPCB Antenna		
Antenna gain:	0.5dBi		
Power supply:	SWITCHING ADAPTER:		
	Model No.:FJ-SW0503000N		
	Input: AC 100~240V~50/60Hz 0.6A Max		
	Output: DC 5V 3A		



Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2402MHz	11	2422MHz	21	2442MHz	31	2462MHz
2	2404MHz	12	2424MHz	22	2444MHz	32	2464MHz
. !			. !	•	• !		. !
9	2418MHz	19	2438MHz	29	2458MHz	39	2478MHz
10	2420MHz	20	2440MHz	30	2460MHz	40	2480MHz

#### Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The lowest channel	2402MHz
The middle channel	2442MHz
The Highest channel	2480MHz



## 5.3 Test mode

Transmitting mode Keep the EUT in continuously transmitting mode

Remark: During the test, the dutycycle >98%, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.

## 5.4 Description of Support Units

None

## 5.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

### • FCC —Registration No.: 600491

Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fuly described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files. Registration 600491, June 22, 2016.

## • Industry Canada (IC) —Registration No.: 9079A-2

The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 9079A-2, August 15, 2016.

### 5.6 Test Location

All tests were performed at:

Global United Technology Services Co., Ltd.

No. 301-309, 3/F., Jinyuan Business Building, No.2, Laodong Industrial Zone,

Xixiang Road, Baoan District, Shenzhen, Guangdong, China

Tel: 0755-27798480 Fax: 0755-27798960

Telephone: +86 (0) 755 2779 8480 Fax: +86 (0) 755 2779 8960



## 6 Test Instruments list

Radi	Radiated Emission:							
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)		
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	GTS250	July. 03 2015	July. 02 2020		
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A		
3	Spectrum Analyzer	Agilent	E4440A	GTS533	June. 29 2016	June. 28 2017		
4	<b>EMI Test Receiver</b>	Rohde & Schwarz	ESU26	GTS203	June. 29 2016	June. 28 2017		
5	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	GTS214	June. 29 2016	June. 28 2017		
6	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	9120D-829	GTS208	June. 29 2016	June. 28 2017		
7	Horn Antenna	ETS-LINDGREN	3160	GTS217	June. 29 2016	June. 28 2017		
8	EMI Test Software	AUDIX	E3	N/A	June. 29 2016	June. 28 2017		
9	Coaxial Cable	GTS	N/A	GTS213	June. 29 2016	June. 28 2017		
10	Coaxial Cable	GTS	N/A	GTS211	June. 29 2016	June. 28 2017		
11	Coaxial cable	GTS	N/A	GTS210	June. 29 2016	June. 28 2017		
12	Coaxial Cable	GTS	N/A	GTS212	June. 29 2016	June. 28 2017		
13	Amplifier(100kHz-3GHz)	HP	8347A	GTS204	June. 29 2016	June. 28 2017		
14	Amplifier(2GHz-20GHz)	HP	8349B	GTS206	June. 29 2016	June. 28 2017		
15	Amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	GTS218	June. 29 2016	June. 28 2017		
16	Band filter	Amindeon	82346	GTS219	June. 29 2016	June. 28 2017		
17	Power Meter	Anritsu	ML2495A	GTS540	June. 29 2016	June. 28 2017		
18	Power Sensor	Anritsu	MA2411B	GTS541	June. 29 2016	June. 28 2017		

Con	Conducted Emission:							
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)		
1	Shielding Room	ZhongYu Electron	7.3(L)x3.1(W)x2.9(H)	GTS252	May 16 2014	May 15 2019		
2	EMI Test Receiver	R&S	ESCI 7	GTS552	June 29 2016	June 28 2017		
3	Pulse Limiter	R&S	ESH3-Z2	GTS224	June 29 2016	June 28 2017		
4	Coaxial Switch	ANRITSU CORP	MP59B	GTS225	June 29 2016	June 28 2017		
5	Artificial Mains Network	SCHWARZBECK MESS	NSLK8127	GTS226	June 29 2016	June 28 2017		
6	Coaxial Cable	GTS	N/A	GTS227	June 29 2016	June 28 2017		
7	EMI Test Software	AUDIX	E3	N/A	N/A	N/A		
8	Thermo meter	KTJ	TA328	GTS233	June 29 2016	June 28 2017		

Gen	General used equipment:								
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)			
1	Barometer	ChangChun	DYM3	GTS257	June 29 2016	June 28 2017			

Telephone: +86 (0) 755 2779 8480 Fax: +86 (0) 755 2779 8960



## 7 Test results and Measurement Data

## 7.1 Antenna requirement

**Standard requirement:** FCC Part15 C Section 15.203 /247(c)

#### 15.203 requirement:


An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

#### 15.247(c) (1)(i) requirement:

(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

#### **EUT Antenna:**

The antenna is FPCB antenna, the best case gain of the antenna is 0.5dBi






## 7.2 Conducted Emissions

Test Requirement:	FCC Part15 C Section 15.207				
Test Method:	ANSI C63.10:2013				
Test Frequency Range:	150KHz to 30MHz				
Class / Severity:	Class B				
Receiver setup:	RBW=9KHz, VBW=30KHz, Sv	weep time=auto			
Limit:	Fraguera virga da (MIII-)	Limit (c	dBuV)		
	Frequency range (MHz)	Quasi-peak	Average		
	0.15-0.5	66 to 56*	56 to 46*		
	0.5-5	56	46		
	5-30	60	50		
Toot ootup.	* Decreases with the logarithm	i or the frequency.			
Test setup:	Reference Plane		-		
	AUX Equipment E.U.T  Test table/Insulation plane  Remark: E.U.T. Equipment Under Test LISN Line impedence Stabilization Network Test table height=0.8m	Filter — AC pow			
Test procedure:	<ol> <li>The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment.</li> <li>The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs).</li> <li>Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed</li> </ol>				
Test Instruments:	according to ANSI C63.10:2013 on conducted measurement.				
	Refer to section 6.0 for details				
Test mode:	Refer to section 5.3 for details				
Test results:	Pass				



#### Measurement data

Line:



Site : Shielded room

Condition : FCC PART15 CLASSB QP LISN-2013 LINE

Job No. : 0121


Test mode : Bluetooth4.0 mode

Test Engineer: Boy

	Freq	Kead Level	Leve1	Factor	Cable Loss	Limit Line	Over Limit	Remark
	MHz	dBuV	dBuV	d₿	dB	dBuV	₫B	
1	0.150	45.39	45.66	0.15	0.12	66.00	-20.34	QP
2	0.150	29.64	29.91	0.15	0.12	56.00	-26.09	Average
3	0.516	39.01	39. 24	0.12	0.11	56.00	-16.76	QP
<b>4</b> 5	0.516	31. 25	31.48	0.12	0.11	46.00	-14.52	Average
5	0.552	37.01	37.25	0.13	0.11	56.00	-18.75	QP
6	0.552	24.61	24.85	0.13	0.11	46.00	-21.15	Average
7	0.654	34.01	34. 27	0.13	0.13	56.00	-21.73	QP
8	0.654	23.06	23.32	0.13	0.13	46.00	-22.68	Average
9	0.984	34.49	34.76	0.14	0.13	56.00	-21.24	QP
10	0.984	23.28	23.55	0.14	0.13	46.00	-22.45	Average
11	1.839	32.59	32.85	0.12	0.14	56.00	-23.15	QP
12	1.839	22.07	22.33	0.12	0.14	46.00	-23.67	Average



#### Neutral:



Site : Shielded room

Condition : FCC PART15 CLASSB QP LISN-2013 NEUTRAL

Job No. : 0121

Test mode : Bluetooth4.0 mode

Test Engineer: Boy


	Freq	Read Leve1	Leve1	LISN Factor	Cable Loss	Limit Line	Over Limit	Remark
	MHz	dBuV	dBuV	dB	d₿	dBuV	——dB	
1	0.157	45.71	45.90	0.07	0.12	65.60	-19.70	QP
2	0. 157	30.58	30.77	0.07	0.12	55.60	-24.83	Average
3	0.516	40.40	40.57	0.06	0.11	56.00	-15.43	QP
4 5	0.516	30.76	30.93	0.06	0.11	46.00	-15.07	Average
	0.989	34.09	34. 29	0.07	0.13	56.00	-21.71	QP
6	0.989	21.73	21.93	0.07	0.13	46.00	-24.07	Average
7	1.374	33. 11	33. 33	0.09	0.13	56.00	-22.67	QP
8	1.374	21. 17	21.39	0.09	0.13	46.00	-24.61	Average
9	2.581	33.32	33.57	0.10	0.15	56.00	-22.43	QP
10	2.581	20.98	21. 23	0.10	0.15	46.00	-24.77	Average
11	18.820	37.34	38.02	0.46	0.22	60.00	-21.98	QP
12	18, 820	31, 29	31, 97	0.46	0, 22	50, 00	-18.03	Average

#### Notes:

- 1. An initial pre-scan was performed on the line and neutral lines with peak detector.
- 2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
- 3. Final Level =Receiver Read level + LISN Factor + Cable Loss
- 4. If the average limit is met when using a quasi-peak detector receiver, the EUT shall be deemed to meet both limits and measurement with the average detector receiver is unnecessary.



## 7.3 Conducted Output Power




#### **Measurement Data**

Test channel	Peak Output Power (dBm)	Limit(dBm)	Result
Lowest	-2.64		
Middle	-2.82	30.00	Pass
Highest	-1.16		


Page 13 of 31




#### Test plot as follows:



### Lowest channel




#### Middle channel



Highest channel



## 7.4 Channel Bandwidth




#### **Measurement Data**


Test channel	Channel Bandwidth (KHz)	Limit(KHz)	Result
Lowest	650.722		
Middle	659.929	>500	Pass
Highest	672.381		




#### Test plot as follows:



#### Lowest channel




### Middle channel



Highest channel



## 7.5 Power Spectral Density




#### **Measurement Data**


Test channel	Power Spectral Density (dBm)	Limit(dBm/3kHz)	Result
Lowest	-2.81		
Middle	-2.94	8.00	Pass
Highest	-1.39		




## Test plot as follows:



### Lowest channel



#### Middle channel



Highest channel




## 7.6 Band edges


## 7.6.1 Conducted Emission Method

Test Requirement:	FCC Part15 C Section 15.247 (d)			
Test Method:	KDB558074 D01 DTS Meas Guidance V03			
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.			
Test setup:	Spectrum Analyzer  E.U.T  Non-Conducted Table  Ground Reference Plane			
Test Instruments:	Refer to section 6.0 for details			
Test mode:	Refer to section 5.3 for details			
Test results:	Pass			

## Test plot as follows:







Highest channel



## 7.6.2 Radiated Emission Method

Test Requirement:		FCC Part15 C Section 15.209 and 15.205				
Test Method:		ANSI C63.10:2013				
Test Frequency Range:		All of the restrict bands were tested, only the worst band's (2310MHz to 2500MHz) data was showed.				
Test site:	Measurement Di	stance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value	
·		Peak	1MHz	3MHz	Peak	
	Above 1GHz	RMS	1MHz	3MHz	Average	
Limit:	Freque	ncy	Limit (dBuV/	m @3m)	Value	
			54.0		Average	
	Above 1	GHZ	74.0	0	Peak	
Test setup:	Antenna Tower  Horn Antenna  Spectrum Analyzer  Table  Amplifier					
Test Procedure:	<ol> <li>The EUT was placed on the top of a rotating table (0.8m for below 1GHz and 1.5 meters for above 1GHz) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.</li> <li>The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</li> <li>The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</li> <li>For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.</li> <li>The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</li> <li>If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.</li> <li>The radiation measurements are performed in X, Y, Z axis positioning. And found the X axis positioning which it is worse case, only the test</li> </ol>					
Test Instruments:		worst case mode is recorded in the report.  Refer to section 6.0 for details				
Test mode:		Refer to section 6.0 for details  Refer to section 5.3 for details				
Test results:	Pass	o.o for details	<u> </u>			
	Fd55					

## Measurement data:

 ${\it Xixiang Road, Baoan District, Shenzhen, Guangdong, China}$ 

Telephone: +86 (0) 755 2779 8480 Fax: +86 (0) 755 2779 8960



Remark: The pre-test were performed on lowest, middle and highest frequencies, only the worst case's (lowest and highest frequencies) data was showed.

Test channel:	Lowest
---------------	--------

#### Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2390.00	44.28	27.59	5.38	30.18	47.07	74.00	-26.93	Vertical
2400.00	45.27	27.58	5.39	30.18	64.06	74.00	-25.94	Vertical
2390.00	44.97	27.59	5.38	30.18	47.76	74.00	-26.24	Horizontal
2400.00	43.46	27.58	5.39	30.18	66.25	74.00	-27.75	Horizontal

## Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2390.00	34.52	27.59	5.38	30.18	37.31	54.00	-16.69	Vertical
2400.00	35.84	27.58	5.39	30.18	48.63	54.00	-15.37	Vertical
2390.00	34.56	27.59	5.38	30.18	37.35	54.00	-16.65	Horizontal
2400.00	37.62	27.58	5.39	30.18	50.41	54.00	-13.59	Horizontal

Test channel:	Highest
---------------	---------

#### Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	46.56	27.53	5.47	29.93	49.63	74.00	-24.37	Vertical
2500.00	45.46	27.55	5.49	29.93	48.57	74.00	-25.43	Vertical
2483.50	47.63	27.53	5.47	29.93	50.70	74.00	-23.30	Horizontal
2500.00	46.59	27.55	5.49	29.93	49.70	74.00	-24.30	Horizontal

## Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	37.36	27.53	5.47	29.93	40.43	54.00	-13.57	Vertical
2500.00	35.16	27.55	5.49	29.93	38.27	54.00	-15.73	Vertical
2483.50	38.69	27.53	5.47	29.93	41.76	54.00	-12.24	Horizontal
2500.00	35.20	27.55	5.49	29.93	38.31	54.00	-15.69	Horizontal

## Remark:

- Final Level = Receiver Read level + Antenna Factor + Cable Loss Preamplifier Factor
- 2. The emission levels of other frequencies are very lower than the limit and not show in test report.

Global United Technology Services Co., Ltd.

No. 301-309, 3/F., Jinyuan Business Building, No.2, Laodong Industrial Zone,

Xixiang Road, Baoan District, Shenzhen, Guangdong, China

Telephone: +86 (0) 755 2779 8480 Fax: +86 (0) 755 2779 8960



## 7.7 Spurious Emission


## 7.7.1 Conducted Emission Method

Test Requirement:	FCC Part15 C Section 15.247 (d)					
Test Method:	KDB558074 D01 DTS Meas Guidance V03					
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.					
Test setup:	Spectrum Analyzer  E.U.T  Non-Conducted Table  Ground Reference Plane					
Test Instruments:	Refer to section 6.0 for details					
Test mode:	Refer to section 5.3 for details					
Test results:	Pass					




#### Test plot as follows:

#### Lowest channel




#### 30MHz~10GHz






30MHz~10GHz


## Highest channel




30MHz~10GHz



10GHz~25GHz



10GHz~25GHz



10GHz~25GHz

Telephone: +86 (0) 755 2779 8480 Fax: +86 (0) 755 2779 8960



## 7.7.2 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209								
Test Method:	ANSI C63.10: 2013								
Test Frequency Range:	30MHz to 25GHz								
Test site:	Measurement Dis	Measurement Distance: 3m							
Receiver setup:	Frequency	Detector	RBW	VBW	Value				
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak				
	Above 1GHz	Peak	1MHz	3MHz	Peak				
	Above IGHZ	RMS	1MHz	3MHz	Average				
Limit:	Frequen	Frequency Limit (dBuV/m @3m)							
	30MHz-88	Quasi-peak							
	88MHz-216	6MHz	43.5	0	Quasi-peak				
	216MHz-96	0MHz	46.0	0	Quasi-peak				
	960MHz-1	GHz	54.0	0	Quasi-peak				
	Above 10	\U-	54.0	0	Average				
	Above 10	Peak							
	**************************************	EUT-		Test Antenna√  < 1m 4m >√	amplifier«				
	Above 1GHz		Rece	Plea	ampinier*				



	Tum Table+ < 1m 4m >-/    Tum Table+   Preamplifier+   Pre
Test Procedure:	1. The EUT was placed on the top of a rotating table (0.8m for below 1GHz and 1.5 meters for above 1GHz) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
	2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
	3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
	4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
	The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
	6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasipeak or average method as specified and then reported in a data sheet.
	7. The radiation measurements are performed in X, Y, Z axis positioning. And found the X axis positioning which it is worse case, only the test worst case mode is recorded in the report.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.3 for details
Test results:	Pass



## **Measurement Data**

## ■ Below 1GHz

- DCIOW I								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
35.88	45.11	14.54	0.62	30.07	30.20	40.00	-9.80	Vertical
50.59	44.39	15.22	0.78	30.00	30.39	40.00	-9.61	Vertical
100.23	38.97	15.11	1.19	29.70	25.57	43.50	-17.93	Vertical
138.39	45.24	10.30	1.50	29.46	27.58	43.50	-15.92	Vertical
209.31	43.60	12.87	1.89	29.29	29.07	43.50	-14.43	Vertical
389.36	44.37	16.83	2.80	29.55	34.45	46.00	-11.55	Vertical
52.39	40.21	15.14	0.79	29.98	26.16	40.00	-13.84	Horizontal
120.70	37.03	12.38	1.37	29.56	21.22	43.50	-22.28	Horizontal
210.05	45.74	12.87	1.90	29.30	31.21	43.50	-12.29	Horizontal
370.70	50.59	16.51	2.72	29.64	40.18	46.00	-5.82	Horizontal
477.17	46.61	18.01	3.21	29.34	38.49	46.00	-7.51	Horizontal
656.53	42.37	20.66	3.94	29.24	37.73	46.00	-8.27	Horizontal



## ■ Above 1GHz

Test channel	l:			Low	est			
Peak value:				•				
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4804.00	37.44	31.78	8.60	32.09	45.73	74.00	-28.27	Vertical
7206.00	31.92	36.15	11.65	32.00	47.72	74.00	-26.28	Vertical
9608.00	31.55	37.95	14.14	31.62	52.02	74.00	-21.98	Vertical
12010.00	*					74.00		Vertical
14412.00	*					74.00		Vertical
4804.00	41.75	31.78	8.60	32.09	50.04	74.00	-23.96	Horizontal
7206.00	33.69	36.15	11.65	32.00	49.49	74.00	-24.51	Horizontal
9608.00	30.98	37.95	14.14	31.62	51.45	74.00	-22.55	Horizontal
12010.00	*					74.00		Horizontal
14412.00	*					74.00		Horizontal
Average val	IIE.	•	•	•	•		•	•

Average var	uc.							
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4804.00	26.23	31.78	8.60	32.09	34.52	54.00	-19.48	Vertical
7206.00	20.59	36.15	11.65	32.00	36.39	54.00	-17.61	Vertical
9608.00	19.66	37.95	14.14	31.62	40.13	54.00	-13.87	Vertical
12010.00	*					54.00		Vertical
14412.00	*					54.00		Vertical
4804.00	30.47	31.78	8.60	32.09	38.76	54.00	-15.24	Horizontal
7206.00	22.77	36.15	11.65	32.00	38.57	54.00	-15.43	Horizontal
9608.00	19.40	37.95	14.14	31.62	39.87	54.00	-14.13	Horizontal
12010.00	*					54.00		Horizontal
14412.00	*					54.00		Horizontal

## Remark:

<sup>1.</sup> Final Level =Receiver Read level + Antenna Factor + Cable Loss - Preamplifier Factor

<sup>2. &</sup>quot;\*", means this data is the too weak instrument of signal is unable to test.



Test channe	l:			Mid	dle			
Peak value:					,			
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4884.00	37.28	31.85	8.67	32.12	45.68	74.00	-28.32	Vertical
7326.00	31.81	36.37	11.72	31.89	48.01	74.00	-25.99	Vertical
9768.00	31.45	38.35	14.25	31.62	52.43	74.00	-21.57	Vertical
12210.00	*					74.00		Vertical
14652.00	*					74.00		Vertical
4884.00	41.56	31.85	8.67	32.12	49.96	74.00	-24.04	Horizontal
7326.00	33.57	36.37	11.72	31.89	49.77	74.00	-24.23	Horizontal
9768.00	30.87	38.35	14.25	31.62	51.85	74.00	-22.15	Horizontal
12210.00	*					74.00		Horizontal
14652.00	*					74.00		Horizontal
Average val	ue:							
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4884.00	26.11	31.85	8.67	32.12	34.51	54.00	-19.49	Vertical
7326.00	20.51	36.37	11.72	31.89	36.71	54.00	-17.29	Vertical
9768.00	19.59	38.35	14.25	31.62	40.57	54.00	-13.43	Vertical
12210.00	*					54.00		Vertical
14652.00	*					54.00		Vertical
4884.00	30.34	31.85	8.67	32.12	38.74	54.00	-15.26	Horizontal
7326.00	22.68	36.37	11.72	31.89	38.88	54.00	-15.12	Horizontal
9768.00	19.32	38.35	14.25	31.62	40.30	54.00	-13.70	Horizontal
12210.00	*					54.00		Horizontal
14652.00	*					54.00		Horizontal

#### Remark:

<sup>1.</sup> Final Level =Receiver Read level + Antenna Factor + Cable Loss - Preamplifier Factor

<sup>2. &</sup>quot;\*", means this data is the too weak instrument of signal is unable to test.



Test channel	:			ŀ	Highest			
Peak value:								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Pream Factor (dB)	. 1 16//61	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4960.00	36.60	31.93	8.73	32.16	45.10	74.00	-28.90	Vertical
7440.00	31.36	36.59	11.79	31.78	47.96	74.00	-26.04	Vertical
9920.00	31.05	38.81	14.38	31.88	52.36	74.00	-21.64	Vertical
12400.00	*					74.00		Vertical
14880.00	*					74.00		Vertical
4960.00	40.74	31.93	8.73	32.16	49.24	74.00	-24.76	Horizontal
7440.00	33.05	36.59	11.79	31.78	49.65	74.00	-24.35	Horizontal
9920.00	30.41	38.81	14.38	31.88	51.72	74.00	-22.28	Horizontal
12400.00	*					74.00		Horizontal
14880.00	*					74.00		Horizontal
Average val	ue:							
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Pream Factor (dB)	. 1 1 5/151	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4960.00	25.61	31.93	8.73	32.16	34.11	54.00	-19.89	Vertical
7440.00	20.17	36.59	11.79	31.78	36.77	54.00	-17.23	Vertical
9920.00	19.29	38.81	14.38	31.88	40.60	54.00	-13.40	Vertical
12400.00	*					54.00		Vertical
14880.00	*					54.00		Vertical
4960.00	29.77	31.93	8.73	32.16	38.27	54.00	-15.73	Horizontal
7440.00	22.30	36.59	11.79	31.78	38.90	54.00	-15.10	Horizontal
9920.00	18.97	38.81	14.38	31.88	40.28	54.00	-13.72	Horizontal
12400.00	*					54.00		Horizontal
14880.00	*					54.00		Horizontal

#### Remark:


<sup>1.</sup> Final Level =Receiver Read level + Antenna Factor + Cable Loss - Preamplifier Factor


<sup>2. &</sup>quot;\*", means this data is the too weak instrument of signal is unable to test.



## 8 Test Setup Photo

Radiated Emission







Conducted Emission



## 9 EUT Constructional Details

Reference to the test report No. GTS201608000121E01

-----End-----