

FCC RADIO TEST REPORT-BT FCC ID: 2AFK7-PCB-I316

Product: Smart Phone

Trade Name: PCBOX

Model No.: PCB-i316

Serial Model: SOFR50BP

Report No.: NTEK-2016NT02264448F4

Issue Date: 11 Mar. 2016

Prepared for

BLUEBANK COMMUNICATION TECHNOLOGY CO.LTD.
NO. 13-2, JIANG YING ROAD, NAN AN DISTRICT,
CHONGQING, P.R. CHINA

Prepared by

NTEK TESTING TECHNOLOGY CO., LTD.

1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen, P.R. China

Tel.: +86-0755-61156588 Fax.: +86-0755-61156599 Website:www.ntek.org.cn



TABLE OF CONTENTS

1	TE	ST RESULT CERTIFICATION	3
2	SU	MMARY OF TEST RESULTS	4
3	FA	CILITIES AND ACCREDITATIONS	5
	3.1	FACILITIES	5
	3.2	LABORATORY ACCREDITATIONS AND LISTINGS	
	3.3	MEASUREMENT UNCERTAINTY	
4		ENERAL DESCRIPTION OF EUT	
5		ESCRIPTION OF TEST MODES	
6	SE	TUP OF EQUIPMENT UNDER TEST	10
	6.1	BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM	10
	6.2	SUPPORT EQUIPMENT	11
	6.3	EQUIPMENTS LIST FOR ALL TEST ITEMS	
7	TE	ST REQUIREMENTS	13
	7.1	CONDUCTED EMISSIONS TEST	
	7.2	RADIATED SPURIOUS EMISSION	
	7.3	6DB BANDWIDTH	
	7.4	20DB BANDWIDTH	
	7.5	DUTY CYCLE	
	7.6	MAXIMUM OUTPUT POWER	
	7.7 7.8	POWER SPECTRAL DENSITYCONDUCTED BAND EDGE MEASUREMENT	
	7.8 7.9	ANTENNA APPLICATION	



1 TEST RESULT CERTIFICATION

Applicant's name:	Bluebank Communication Technology Co.Ltd.	
Address:	No. 13-2, Jiang Ying Road, Nan An District, Chongqing, P.R. China	
Manufacture's Name	Bluebank Communication Technology Co.Ltd.	
Address	No. 13-2, Jiang Ying Road, Nan An District, Chongqing, P.R. China	
Product description		
Product name:	Smart Phone	
Model and/or type reference:	PCB-i316	
Serial Model:	SOFR50BP	

Measurement Procedure Used:

APPLICABLE STANDARDS	
APPLICABLE STANDARD/ TEST PROCEDURE	TEST RESULT
FCC 47 CFR Part 2, Subpart J:2015	
FCC 47 CFR Part 15, Subpart C:2015	
KDB 174176 D01 Line Conducted FAQ v01r01	Complied
ANSI C63.10-2013	
FCC KDB 558074 D01 DTS Meas Guidance v03r04	

This device described above has been tested by NTEK Testing Technology Co., Ltd., and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of NTEK Testing Technology Co., Ltd., this document may be altered or revised by NTEK Testing Technology Co., Ltd., personnel only, and shall be noted in the revision of the document.

The test results of this report relate only to the tested sample identified in this report.

Date of Test		20 Feb. 2010 ~ 11 Mai. 2010
Testing Engineer	:	Eileen Wu.
	·	(Eileen Liu)
Technical Manager	: <u></u>	Jason chen
		(Jason Chen)
Authorized Signatory	:	Sam. Chen
		(Sam Chen)



2 SUMMARY OF TEST RESULTS

FCC Part15 (15.247), Subpart C				
Standard Section	Test Item	Verdict	Remark	
15.207	Conducted Emission	PASS		
15.247 (a)(2)	6dB Bandwidth	PASS		
15.247 (b)	Maximum Output Power	PASS		
15.247 (c)	Radiated Spurious Emission	PASS		
15.247 (d)	Power Spectral Density	PASS		
15.205	Band Edge Emission	PASS		
15.203	Antenna Requirement	PASS		

Remark:

- 1. "N/A" denotes test is not applicable in this Test Report.
- All test items were verified and recorded according to the standards and without any deviation during the test.
- This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



3 FACILITIES AND ACCREDITATIONS

3.1 FACILITIES

All measurement facilities used to collect the measurement data are located at

1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street, Bao'an District, Shenzhen P.R. China

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.10 and CISPR Publication 22.

3.2 LABORATORY ACCREDITATIONS AND LISTINGS

Site Description

EMC Lab. : Accredited by CNAS, 2014.09.04

The certificate is valid until 2017.09.03

The Laboratory has been assessed and proved to be in compliance with

CNAS-CL01:2006 (identical to ISO/IEC 17025:2005) The Certificate Registration Number is L5516.

Accredited by Industry Canada, August 29, 2012 The Certificate Registration Number is 9270A-1.

Name of Firm : NTEK Testing Technology Co., Ltd

Site Location : 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang

Street, Bao'an District, Shenzhen P.R. China.

3.3 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement y±U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95 %.

No.	Item	Uncertainty
1	Conducted Emission Test	±1.38dB
2	RF power, conducted	±0.16dB
3	Spurious emissions, conducted	±0.21dB
4	All emissions, radiated(<1G)	±4.68dB
5	All emissions, radiated(>1G)	±4.89dB
6	Temperature	±0.5°C
7	Humidity	±2%



4 GENERAL DESCRIPTION OF EUT

Product Feature and Specification		
Equipment	Smart Phone	
Trade Name	PCBOX	
FCC ID	2AFK7-PCB-I316	
Model No.	PCB-i316	
Serial Model	SOFR50BP	
Model Difference	All the model are the same circuit and RF module, except the model name.	
Operating Frequency	2412-2462MHz for 802.11b/g/11n(HT20);	
Modulation	DSSS with DBPSK/DQPSK/CCK for 802.11b; OFDM with BPSK/QPSK/16QAM/64QAM for 802.11g/n;	
Number of Channels	11 channels for 802.11b/g/11n(HT20);	
Antenna Type	FPCB Antenna	
Antenna Gain	1 dBi	
	☑DC supply: DC 3.8V/2300mAh from Li-ion Battery or DC 5V from USB Port.	
Power supply		
HW Version	N/A	
SW Version	N/A	

Note: Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.



Revision History

Report No.	Version	Description	Issued Date
NTEK-2016NT02264448F4	Rev.01	Initial issue of report	Mar 11, 2016



5 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

Test of channel included the lowest and middle and highest frequency to perform the test, then record on this report.

The data rates (802.11b: 1 Mbps; 802.11g: 6 Mbps; 802.11n (HT20): MCS0; 802.11n (HT40): MCS0) associated with the highest powers each mode were used for all test.

The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement –X, Y, and Z-plane. The Y-plane results were found as the worst case and were shown in this report.

Frequency and Channel list for 802.11b/g/n (HT20):

Channel	Frequency(MHz)
1	2412
2	2417
	•••
5	2432
6	2437
	•••
10	2457
11	2462

Note: $fc=2412MHz+k\times5MHz$ k=0 to 10



The following summary table is showing all test modes to demonstrate in compliance with the standard.

For AC Conducted Emission		
Final Test Mode	Description	
Mode 5	Link Mode	

Note: AC power line Conducted Emission was tested under maximum output power.

	For Radiated Test Cases
Final Test Mode	Description
Mode 1	802.11b CH1/ CH6/ CH11
Mode 2	802.11g CH1/ CH6/ CH11
Mode 3	802.11n HT20 CH1/ CH6/ CH11

Note: For radiated test cases, the worst mode data rate was reported only, because this data rate has the highest RF output power at preliminary tests, and no other significantly frequencies found in conducted spurious emission.

For Conducted Test Cases		
Final Test Mode	Description	
Mode 1	802.11b CH1/ CH6/ CH11	
Mode 2	802.11g CH1/ CH6/ CH11	
Mode 3	802.11n HT20 CH1/ CH6/ CH11	


Note: The engineering test program was provided and the EUT was programmed to be in continuously transmitting mode.


All the data rates and modes were tested, the data of the worst mode are record on this report.




6 SETUP OF EQUIPMENT UNDER TEST

6.1 BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM









6.2 SUPPORT EQUIPMENT

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

tooto.					
Item	Equipment	Mfr/Brand	Model/Type No.	FCC ID	Note
1.	Smart Phone	PCBOX	PCB-i316	XXXX- PCB-I316	EUT
2.	Adapter	N/A	WTA0501000USA1	N/A	Peripherals
3.	Earphone	N/A	L662	N/A	Peripherals
4.	N/A	N/A	N/A	N/A	Auxiliary equipment

Item	Cable Type	Shielded Type	Ferrite Core	Length
C-1	USB Cable	NO	NO	1.0m
C-2	Earphone	NO	NO	0.8m
C-3	RF Cable	NO	NO	0.5m

Notes:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in <code>[Length]</code> column.
- (3) "YES" is means "shielded" "with core"; "NO" is means "unshielded" "without core".



6.3 EQUIPMENTS LIST FOR ALL TEST ITEMS

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Spectrum Analyzer	Agilent	E4407B	MY45108040	2015.07.06	2016.07.05	1 year
2	Test Receiver	R&S	ESPI	101318	2015.06.07	2016.06.06	1 year
3	Bilog Antenna	TESEQ	CBL6111D	31216	2015.07.06	2016.07.05	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	6200264416	2015.06.07	2016.06.06	1 year
5	Spectrum Analyzer	ADVANTEST	R3132	150900201	2015.06.07	2016.06.06	1 year
6	Horn Antenna	EM	EM-AH-1018 0	2011071402	2015.07.06	2016.07.05	1 year
7	Horn Ant	Schwarzbeck	BBHA 9170	9170-181	2015.07.06	2016.07.05	1 year
8	Amplifier	EM	EM-30180	060538	2015.07.06	2016.07.05	1 year
9	Loop Antenna	ARA	PLA-1030/B	1029	2015.06.08	2016.06.07	1 year
10	Power Meter	R&S	NRVS	100696	2015.07.06	2016.07.05	1 year
11	Power Sensor	R&S	URV5-Z4	0395.1619.0 5	2015.07.06	2016.07.05	1 year
12	Test Cable	N/A	R-01	N/A	2015.07.06	2016.07.05	1 year
13	Test Cable	N/A	R-02	N/A	2015.07.06	2016.07.05	1 year
14	Test Receiver	R&S	ESCI	101160	2015.06.06	2016.06.05	1 year
15	LISN	R&S	ENV216	101313	2015.08.24	2016.08.23	1 year
16	LISN	EMCO	3816/2	00042990	2015.08.24	2016.08.23	1 year
17	50Ω Coaxial Switch	Anritsu	MP59B	6200264417	2015.06.07	2016.06.06	1 year
18	Passive Voltage Probe	R&S	ESH2-Z3	100196	2015.06.07	2016.06.06	1 year
19	Absorbing clamp	R&S	MOS-21	100423	2015.06.08	2016.06.07	1 year
20	Test Cable	N/A	C01	N/A	2015.06.08	2016.06.07	1 year
21	Test Cable	N/A	C02	N/A	2015.06.08	2016.06.07	1 year
22	Test Cable	N/A	C03	N/A	2015.06.08	2016.06.07	1 year
23	Attenuation	MCE	24-10-34	BN9258	2015.06.08	2016.06.07	1 year

Note: Each piece of equipment is scheduled for calibration once a year.



7 TEST REQUIREMENTS

7.1 CONDUCTED EMISSIONS TEST

7.1.1 Applicable Standard

According to FCC Part 15.207(a) and KDB 174176 D01 Line Conducted FAQ v01r01

7.1.2 Conformance Limit

Fraguanov(MHz)	Conducted Emission Limit				
Frequency(MHz)	Quasi-peak	Average			
0.15-0.5	66-56*	56-46*			
0.5-5.0	56	46			
5.0-30.0	60	50			


Note: 1. *Decreases with the logarithm of the frequency

- 2. The lower limit shall apply at the transition frequencies
- 3. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

7.1.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.1.4 Test Configuration




7.1.5 Test Procedure

According to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 Conducted emissions the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.

- 1. The EUT was placed 0.4 meter from the conducting wall of the shielding room.
- 2. The EUT was placed on a table which is 0.8m above ground plane.
- 3. Connect EUT to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- 4. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40cm long.
- 5. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- 6. LISN at least 80 cm from nearest part of EUT chassis.
- 7. The frequency range from 150KHz to 30MHz was searched.
- 8. Set the test-receiver system to Peak Detect Function and specified bandwidth(IF bandwidth=9KHz) with Maximum Hold Mode
- 9. For the actual test configuration, please refer to the related Item -EUT Test Photos.







Limit: FCC Part 15B_(0.15-30MHz) _Main_QP

Made: BT20

Mode: BT3.0 Note: Adapter

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		
		MHz	dBu∀	dB	dBu∀	dBu∀	dB	Detector	Comment
1		0.2979	36.45	10.14	46.59	60.30	-13.71	QP	
2		0.2979	30.24	10.14	40.38	50.30	-9.92	AVG	
3		0.4020	39.79	10.03	49.82	57.81	-7.99	QP	
4		0.4020	33.53	10.03	43.56	47.81	-4.25	AVG	
5		0.4500	42.77	9.92	52.69	56.87	-4.18	QP	
6	*	0.4500	33.58	9.92	43.50	46.87	-3.37	AVG	
7		0.5500	41.90	9.79	51.69	56.00	-4.31	QP	
8		0.5500	32.01	9.79	41.80	46.00	-4.20	AVG	
9		0.7980	40.84	9.80	50.64	56.00	-5.36	QP	
10		0.7980	30.52	9.80	40.32	46.00	-5.68	AVG	
11		1.6859	40.34	9.77	50.11	56.00	-5.89	QP	
12		1.6859	27.88	9.77	37.65	46.00	-8.35	AVG	

Power:


AC 120V/60Hz

Humidity:

56 %

^{*:}Maximum data x:Over limit !:over margin





Limit: FCC Part 15B_(0.15-30MHz) _Main_QP

Power:

AC 120V/60Hz


Humidity:

Mode: BT3.0 Note: Adapter

_				Reading	Correct	measure-				
	No.	Mk.	Freq.	Level	Factor	ment	Limit	Over		
			MHz	dBu∀	dB	dBu∀	dBu∀	dB	Detector	Comment
_	1		0.3019	36.86	10.13	46.99	60.19	-13.20	QP	
-	2		0.3019	28.71	10.13	38.84	50.19	-11.35	AVG	
_	3		0.3980	39.49	10.05	49.54	57.89	-8.35	QP	
	4		0.3980	29.59	10.05	39.64	47.89	-8.25	AVG	
_	5		0.4620	42.22	9.91	52.13	56.66	-4.53	QP	
	6		0.4620	31.87	9.91	41.78	46.66	-4.88	AVG	
_	7		0.5540	41.52	9.82	51.34	56.00	-4.66	QP	
_	8	*	0.5540	33.29	9.82	43.11	46.00	-2.89	AVG	
_	9		0.7980	40.69	9.83	50.52	56.00	-5.48	QP	
-	10		0.7980	27.69	9.83	37.52	46.00	-8.48	AVG	
_	11		2.1859	39.87	9.75	49.62	56.00	-6.38	QP	
	12		2.1859	26.87	9.75	36.62	46.00	-9.38	AVG	
_										

^{*:}Maximum data x:Over limit !:over margin





Limit: FCC Part 15B_(0.15-30MHz) _Main_QP

Power: AC 240V/50Hz


Humidity: 56 %

Mode: BT3.0 Note: Adapter

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		
		MHz	dBu∀	dB	dBu∀	dBu∀	dB	Detector	Comment
1		0.4339	42.31	9.97	52.28	57.18	-4.90	QP	
2		0.4339	34.83	9.97	44.80	47.18	-2.38	AVG	
3		0.4779	43.73	9.87	53.60	56.38	-2.78	QP	
4		0.4779	34.23	9.87	44.10	46.38	-2.28	AVG	
5		0.5779	43.08	9.82	52.90	56.00	-3.10	QP	
6		0.5779	34.88	9.82	44.70	46.00	-1.30	AVG	
7		0.6820	44.08	9.81	53.89	56.00	-2.11	QP	
8	*	0.6820	35.09	9.81	44.90	46.00	-1.10	AVG	
9		1.1220	42.44	9.86	52.30	56.00	-3.70	QP	
10		1.1220	32.51	9.86	42.37	46.00	-3.63	AVG	
11		1.5900	42.60	9.80	52.40	56.00	-3.60	QP	
12		1.5900	32.30	9.80	42.10	46.00	-3.90	AVG	

^{*:}Maximum data x:Over limit !:over margin





Power:

AC 240V/50Hz

Humidity:

Limit: FCC Part 15B_(0.15-30MHz) _Main_QP Mode: BT3.0

Mode: BT3.0 Note: Adapter

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		
		MHz	dBuV	dB	dBuV	dBu∀	dB	Detector	Comment
1		0.2899	40.86	10.12	50.98	60.52	-9.54	QP	
2		0.2899	30.64	10.12	40.76	50.52	-9.76	AVG	
3		0.4859	41.74	9.85	51.59	56.24	-4.65	QP	
4		0.4859	32.37	9.85	42.22	46.24	-4.02	AVG	
5		0.5819	42.85	9.82	52.67	56.00	-3.33	QP	
6		0.5819	32.47	9.82	42.29	46.00	-3.71	AVG	
7		0.6780	42.59	9.81	52.40	56.00	-3.60	QP	
8		0.6780	31.77	9.81	41.58	46.00	-4.42	AVG	
9	*	1.1180	43.04	9.86	52.90	56.00	-3.10	QP	
10		1.1180	31.32	9.86	41.18	46.00	-4.82	AVG	
11		1.5540	42.30	9.80	52.10	56.00	-3.90	QP	
12		1.5540	32.76	9.80	42.56	46.00	-3.44	AVG	

^{*:}Maximum data x:Over limit !:over margin



7.2 RADIATED SPURIOUS EMISSION

7.2.1 Applicable Standard

According to FCC Part 15.247(d) and 15.209 and DA 00-705

7.2.2 Conformance Limit

According to FCC Part 15.247(d): radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)). According to FCC Part15.205. Restricted bands

7.000rding to 1 00 1 dit 10.20	According to FCC Fart 15.205, Nestricted bands					
MHz	MHz	MHz	GHz			
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15			
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46			
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75			
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5			
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2			
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5			
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7			
6.26775-6.26825	123-138	2200-2300	14.47-14.5			
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2			
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4			
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12			
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0			
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8			
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5			
12.57675-12.57725	322-335.4	3600-4400	(2)			
13.36-13.41						

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

restricted band specified on 15.255(a), then the 15.255(a) firms in the table below has to be followed.					
Restricted Frequency(MHz)	Field Strength (μV/m)	Field Strength (dBµV/m)	Measurement Distance		
0.009~0.490	2400/F(KHz)	20 log (uV/m)	300		
0.490~1.705	2400/F(KHz)	20 log (uV/m)	30		
1.705~30.0	30	29.5	30		
30-88	100	40	3		
88-216	150	43.5	3		
216-960	200	46	3		
Above 960	500	54	3		

Limits of Radiated Emission Measurement(Above 1000MHz)

Fraguanov/MHz)	Class B (dBuV/m) (at 3M)			
Frequency(MHz)	PEAK	AVERAGE		
Above 1000	74	54		

Remark :1. Emission level in dBuV/m=20 log (uV/m)

- 2. Measurement was performed at an antenna to the closed point of EUT distance of meters.
- 3. Distance extrapolation factor =40log(Specific distance/ test distance)(dB); Limit line=Specific limits(dBuV) + distance extrapolation factor.


7.2.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.




7.2.4 Test Configuration


(a) For radiated emissions below 30MHz



(b) For radiated emissions from 30MHz to 1000MHz



(c) For radiated emissions above 1000MHz





7.2.5 Test Procedure

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.10-2013. The test distance is 3m.The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 and CAN/CSA-CEI/IEC CISPR 22.

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT. Use the following spectrum analyzer settings:

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

- a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 0.8 m for below 1GHz and 1.5m for above 1GHz the ground at a 3 meter. The table was rotated 360 degrees to determine the position of the highest radiation
- c. The height of the equipment or of the substitution antenna shall be 0.8 m for below 1GHz and 1.5m for above 1GHz; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

During the radiated emission test, the Spectrum Analyzer was set with the following configurations:

Frequency Band (MHz)	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	QP	120 kHz	300 kHz
Above 1000	Peak	1 MHz	1 MHz
Above 1000	Average	1 MHz	10 Hz

Note: for the frequency ranges below 30 MHz, a narrower RBW is used for these ranges but the measured value should add a RBW correction factor (RBWCF) where RBWCF [dB] =10*lg(100 [kHz]/narrower RBW [kHz]). , the narrower RBW is 1 kHz and RBWCF is 20 dB for the frequency 9 kHz to 150 kHz, and the narrower RBW is 10 kHz and RBWCF is 10 dB for the frequency 150 kHz to 30 MHz.



7.2.6 Test Results

■ Spurious Emission below 30MHz (9KHz to 30MHz)

EUT:	Smart Phone	Model No.:	PCB-i316
Temperature:	20 ℃	Relative Humidity:	48%
Test Mode:	Mode1/Mode2/Mode3	Test By:	Eileen Liu

Freq.	Ant.Pol.	Emission L	evel(dBuV/m)	Limit 3	m(dBuV/m)	Over(dB)		
(MHz)	H/V	PK	PK \ AV ^		AV	PK	AV	

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Distance extrapolation factor =20log(Specific distance/ test distance)(dB); Limit line=Specific limits(dBuV) + distance extrapolation factor





All the modulation modes have been tested, and the worst result was report as below:



Site NTEK 9*6*6 Chamber #1

Limit: FCC_PART15_B_03m_QP

Mode: BT

Polarization: Horizontal Temperature:


Power: Humidity: 50 %

Note:

No	Mk	Freq.	Rëading Level	Correct Factor	Measure- ment	Limit	Over		Antennā Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1		31.6202	11.31	18.99	30.30	40.00	-9.70	QP			
2		41.5670	13.98	13.70	27.68	40.00	-12.32	QP			
3	İ	130.3788	23.74	10.89	34.63	40.00	-5.37	QP			
4	*	226.8934	24.43	10.88	35.31	40.00	-4.69	QP			
5		316.5889	23.68	13.14	36.82	47.00	-10.18	QP			
6		547.0977	19.35	17.94	37.29	47.00	-9.71	QP			

*:Maximum data x:Over limit !:over margin





Limit: FCC_PART15_B_03m_QP

Mode: BT Note:

Polarization: Vertical

Humidity: 50 % Power:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure- ment	Limit	Over		Antenna Height	Table Degree	
		MHz	dBu∀	dB	dBuV/m	dBuV/m	dB	Detector	cm	degree	Comment
1	İ	42.4508	22.83	13.29	36.12	40.00	-3.88	QP			
2	*	84.4054	27.50	9.16	36.66	40.00	-3.34	QP			
3	ļ	96.4360	25.84	10.22	36.06	40.00	-3.94	QP			
4	İ	158.6673	22.70	11.55	34.25	40.00	-5.75	QP			
5	İ	229.2931	24.33	10.82	35.15	40.00	-4.85	QP			
6		378.5842	18.68	14.96	33.64	47.00	-13.36	QP			

^{*:}Maximum data x:Over limit !:over margin



Spurious Emission Above 1GHz (1GHz to 27GHz)

EUT:	Smart Phone	Model No.:	PCB-i316
Temperature:	20 ℃	Relative Humidity:	48%
Test Mode:	Mode1/Mode2/Mode3	Test By:	Eileen Liu

All the modulation modes have been tested, and the worst result was report as below:

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Remark	Commont					
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Remark	Comment					
	Low Channel (2402 MHz)-Above 1G											
4824.215	52.32	10.44	62.76	74.00	-11.24	Pk	Vertical					
4824.215	36.29	10.44	46.73	54.00	-7.27	AV	Vertical					
7236.102	48.95	12.39	61.34	74.00	-12.66	Pk	Vertical					
7236.102	32.64	12.39	45.03	54.00	-8.97	AV	Vertical					
4824.364	52.41	10.44	62.85	74.00	-11.15	Pk	Horizontal					
4824.364	32.69	10.44	43.13	54.00	-10.87	AV	Horizontal					
7236.119	48.44	12.39	60.83	74.00	-13.17	Pk	Horizontal					
7236.119	30.31	12.39	42.70	54.00	-11.30	AV	Horizontal					
	,	Mid Chanr	nel (2441 MHz)-Abo	ve 1G								
4874.218	53.69	10.40	64.09	74.00	-9.91	Pk	Vertical					
4874.218	32.47	10.40	42.87	54.00	-11.13	AV	Vertical					
7311.203	49.42	12.75	62.17	74.00	-11.83	Pk	Vertical					
7311.203	33.63	12.75	46.38	54.00	-7.62	AV	Vertical					
4874.198	52.21	10.40	62.61	74.00	-11.39	Pk	Horizontal					
4874.198	33.96	10.40	44.36	54.00	-9.64	AV	Horizontal					
7311.107	47.42	12.75	60.17	74.00	-13.83	Pk	Horizontal					
7311.107	32.12	12.75	44.87	54.00	-9.13	AV	Horizontal					
		High Chani	nel (2480 MHz)- Abo	ove 1G								
4924.226	52.16	10.39	62.55	74.00	-11.45	Pk	Vertical					
4924.226	33.64	10.39	44.03	54.00	-9.97	AV	Vertical					
7386.125	47.49	12.68	60.17	74.00	-13.83	Pk	Vertical					
7386.125	31.52	12.68	44.20	54.00	-9.80	AV	Vertical					
4924.652	53.46	10.39	63.85	74.00	-10.15	Pk	Horizontal					
4924.652	32.25	10.39	42.64	54.00	-11.36	AV	Horizontal					
7386.332	50.09	12.68	62.77	74.00	-11.23	Pk	Horizontal					
7386.332	32.42	12.68	45.10	54.00	-8.90	AV	Horizontal					

Note: (1) All Readings are Peak Value (VBW=3MHz) and Peak Value (VBW=10Hz).

- (2) Emission Level= Reading Level+Probe Factor +Cable Loss.
- (3) Data of measurement within this frequency range shown " -- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.



■ Spurious Emission in Restricted Band 2310-2390MHz and 2483.5-2500MHz

EUT:	Smart Phone	Model No.:	PCB-i316
Temperature:	20 ℃	Relative Humidity:	48%
Test Mode:	Mode1/Mode2/Mode3	Test By:	Eileen Liu

All the modulation modes were tested, the data of the worst mode are described in the following table

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector	Comment				
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Type	Comment				
	802.11b										
2390	60.31	-13.06	47.25	74.00	-26.75	peak	Vertical				
2390	59.45	-13.06	46.39	74.00	-27.61	peak	Horizontal				
2483.5	61.95	-12.78	49.17	74.00	-24.83	peak	Vertical				
2483.5	60.87	-12.78	48.09	74.00	-25.91	peak	Horizontal				
			802.11	g							
2390	60.31	-13.06	47.25	74.00	-26.75	peak	Vertical				
2390	59.45	-13.06	46.39	74.00	-27.61	peak	Horizontal				
2483.5	61.95	-12.78	49.17	74.00	-24.83	peak	Vertical				
2483.5	60.87	-12.78	48.09	74.00	-25.91	peak	Horizontal				
			802.11n(20)							
2390	60.31	-13.06	47.25	74.00	-26.75	peak	Vertical				
2390	59.45	-13.06	46.39	74.00	-27.61	peak	Horizontal				
2483.5	61.95	-12.78	49.17	74.00	-24.83	peak	Vertical				
2483.5	60.87	-12.78	48.09	74.00	-25.91	peak	Horizontal				



7.3 6DB BANDWIDTH

7.3.1 Applicable Standard

According to FCC Part 15.247(a)(2) and KDB 558074 DTS 01 Meas. Guidance v03r04

7.3.2 Conformance Limit

The minimum permissible 6dB bandwidth is 500 kHz.

7.3.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.3.4 Test Setup

Please refer to Section 6.1 of this test report.

7.3.5 Test Procedure

The testing follows KDB 558074 DTS 01 Meas. Guidance v03r04

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT was operating in controlled its channel.

Use the following spectrum analyzer settings:

Span = the frequency band of operation

RBW = 100KHz

 $VBW \geq 3^*RBW$

Sweep = auto

Detector function = peak

Trace = max hold




7.3.6 Test Results


EUT:	Smart Phone	Model No.:	PCB-i316
Temperature:	20 ℃	Relative Humidity:	48%
Test Mode:	Mode1/Mode2/Mode3	Test By:	Eileen Liu

Channel	Frequency (MHz)	6dB bandwidth (kHz)	Limit (kHz)	Result
		802.11b		
1	2412	10086.000	500	Pass
6	2437	10095.000	500	Pass
11	2462	10096.000	500	Pass
		802.11g		
1	2412	16410.000	500	Pass
6	2437	16410.000	500	Pass
11	2462	16391.000	500	Pass
		802.11n HT20		
1	2412	17643.000	500	Pass
6	2437	17641.000	500	Pass
11	2462	16898.000	500	Pass

























7.4 20DB BANDWIDTH

7.4.1 Applicable Standard

According to FCC Part 15.247(a)(2) and KDB 558074 DTS 01 Meas. Guidance v03r04

7.4.2 Conformance Limit

No limit requirement.

7.4.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.4.4 Test Setup

Please refer to Section 6.1 of this test report.

7.4.5 Test Procedure

The testing follows KDB 558074 DTS 01 Meas. Guidance v03r04

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT was operating in controlled its channel.

Use the following spectrum analyzer settings:

Span = the frequency band of operation

RBW = 100KHz

 $VBW \geq 3^*RBW$

Sweep = auto

Detector function = peak

Trace = max hold




7.4.6 Test Results


EUT:	Smart Phone	Model No.:	PCB-i316
Temperature:	20 ℃	Relative Humidity:	48%
Test Mode:	Mode1/Mode2/Mode3	Test By:	Eileen Liu

Channel	Frequency (MHz)	20dB bandwidth (kHz)	Limit (kHz)	Result		
802.11b						
1	2412	15612.000	N/A	Pass		
6	2437	15179.000	N/A	Pass		
11	2462	15174.000	N/A	Pass		
802.11g						
1	2412	17463.000	N/A	Pass		
6	2437	17833.000	N/A	Pass		
11	2462	17630.000	N/A	Pass		
802.11n HT20						
1	2412	18407.000	N/A	Pass		
6	2437	18480.000	N/A	Pass		
11	2462	18601.000	N/A	Pass		


























7.5 DUTY CYCLE

7.5.1 Applicable Standard

According to KDB 558074)6)b), issued 06/09/2015

7.5.2 Conformance Limit

No limit requirement.

7.5.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.5.4 Test Setup

Please refer to Section 6.1 of this test report.

7.5.5 Test Procedure

The zero-span mode on a spectrum analyzer or EMI receiver if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on and off times of the transmitted signal. Set the center frequency of the instrument to the center frequency of the transmission. Set RBW \geq OBW if possible; otherwise, set RBW to the largest available value. Set VBW \geq RBW. Set detector = peak or average. The zero-span measurement method shall not be used unless both RBW and VBW are > 50/T and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring duty cycle shall not be used if T \leq 16.7 microseconds.)

The transmitter output is connected to the Spectrum Analyzer. We tested accroding to the zero-span measurement method, 6.0)b) in KDB 558074(issued 06/09/2015)

The largest availble value of RBW is 8 MHz and VBW is 50 MHz. The zero-span method of measuring duty cycle shall not be used if $T \le 6.25$ microseconds. (50/6.25 = 8)

The zero-span method was used because all measured T data are > 6.25 microseconds and both RBW and VBW are > 50/T.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT was operating in controlled its channel.

Use the following spectrum analyzer settings:

Span = Zero Span

RBW = 8MHz(the largest available value)

VBW = 8MHz (≥ RBW)

Number of points in Sweep >100

Detector function = peak

Trace = Clear write

Measure T_{total} and T_{on}

Calculate Duty Cycle = T_{on} / T_{total} and Duty Cycle Factor=10*log(1/Duty Cycle)




7.5.6 Test Results

EUT:	Smart Phone	Model No.:	PCB-i316
Temperature:	20 ℃	Relative Humidity:	48%
Test Mode:	Mode1/Mode2/Mode3	Test By:	Eileen Liu


Mode	Data rate	Channel	T_{on}	T _{total}	Duty Cycle	Duty Cycle Factor (dB)
802.11b	1Mbps	6	1.283	1.353	0.9483	0.231
802.11g	6Mbps	6	1.387	1.437	0.9652	0.154
802.11n HT20	MCS0	6	1.290	1.347	0.9577	0.188

Note: All the modulation modes were tested, the data of the worst mode are described in the following table.











7.6 MAXIMUM OUTPUT POWER

7.6.1 Applicable Standard

According to FCC Part 15.247(b)(3) and KDB 558074 DTS 01 Meas. Guidance v03r04

7.6.2 Conformance Limit

The maximum peak conducted output power of the intentional radiator for systems using digital modulation in the 2400 - 2483.5 MHz bands shall not exceed: 1 Watt (30dBm). If transmitting antenna of directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

7.6.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.6.4 Test Setup

Please refer to Section 6.1 of this test report.

7.6.5 Test Procedure

The testing follows KDB 558074 DTS 01 Meas. Guidance v03r04 section 9.2.2

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT was operating in controlled its channel.

- a) Set instrument center frequency to DTS channel center frequency.
- b) Set span to at least 1.5 times the OBW.
- c) Set RBW = 1-5% of the OBW, not to exceed 1MHz.
- d) Set VBW ≥3 x RBW.
- e) Number of points in sweep $\ge 2x$ span / RBW.

(This gives bin-to-bin spacing ≤ RBW/2, so that narrowband signals are not lost between frequency bins.)

- f) Sweep time = auto.
- g) Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.
- h) If transmit duty cycle < 98 %, use a sweep trigger with the level set to enable triggering only on full power pulses. The transmitter shall operate at maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle ≥ 98 %, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to "free run".
- i) Trace average at least 100 traces in power averaging (i.e., RMS) mode.
- j) Compute power by integrating the spectrum across the OBW of the signal using the instrument's band power measurement function, with band limits set equal to the OBW band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at intervals equal to the RBW extending across the entire OBW of the spectrum.




7.6.6 Test Results


EUT:	Smart Phone	Model No.:	PCB-i316
Temperature:	20 ℃	Relative Humidity:	48%
Test Mode:	Mode1/Mode2/Mode3	Test By:	Eileen Liu

Test Channel	Frequency (MHz)	Power Setting	Average Output Power (dBm)	LIMIT (dBm)	Verdict	
			802.11b			
1	2412	MAXIMUM	13.31	30	PASS	
6	2437	MAXIMUM	13.95	30	PASS	
11	2462	MAXIMUM	13.50	30	PASS	
	802.11g					
1	2412	MAXIMUM	7.54	30	PASS	
6	2437	MAXIMUM	9.29	30	PASS	
11	2462	MAXIMUM	9.72	30	PASS	
802.11n HT20						
1	2412	MAXIMUM	6.63	30	PASS	
6	2437	MAXIMUM	8.30	30	PASS	
11	2462	MAXIMUM	7.41	30	PASS	


























7.7 POWER SPECTRAL DENSITY

7.7.1 Applicable Standard

According to FCC Part 15.247(e) and KDB 558074 DTS 01 Meas. Guidance v03r04

7.7.2 Conformance Limit

The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

7.7.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.7.4 Test Setup

Please refer to Section 6.1 of this test report.

7.7.5 Test Procedure

The testing follows Measurement Procedure 10.3 Method AVGPSD of FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r04

This procedure may be used when the maximum (average) conducted output power was used to demonstrate compliance to the output power limit. This is the baseline method for determining the maximum (average) conducted PSD level. If the instrument has an RMS power averaging detector, it must be used; otherwise, use the sample detector. The EUT must be configured to transmit continuously (duty cycle ≥ 98%); otherwise sweep triggering/signal gating must be implemented to ensure that measurements are made only when the EUT is transmitting at its maximum power control level (no transmitter off time is to be considered).

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT was operating in controlled its channel.

- a) Set instrument center frequency to DTS channel center frequency.
- b) Set span to at least 1.5 times the OBW.
- c) Set RBW to: 3 kHz ≤ RBW ≤ 100 kHz. .
- d) Set VBW ≥3 x RBW.
- e) Detector = power averaging (RMS) or sample detector (when RMS not available).
- f) Ensure that the number of measurement points in the sweep $\geq 2 \times \text{span/RBW}$.
- g) Sweep time = auto couple.
- h) Employ trace averaging (RMS) mode over a minimum of 100 traces.
- i) Use the peak marker function to determine the maximum amplitude level.
- j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat (note that this may require zooming in on the emission of interest and reducin




7.7.6 Test Results


EUT:	Smart Phone	Model No.:	PCB-i316
Temperature:	20 ℃	Relative Humidity:	48%
Test Mode:	Mode1/Mode2/Mode3	Test By:	Eileen Liu

Test Channel	Frequency (MHz)	Power Density (dBm/3KHz)	Limit (dBm/3KHz)	Verdict		
	, ,	802.11b	,			
1	2412	-17.48	8	PASS		
6	2437	-15.88	8	PASS		
11	2462	-15.95	8	PASS		
	802.11g					
1	2412	-22.96	8	PASS		
6	2437	-23.15	8	PASS		
11	2462	-22.91	8	PASS		
802.11n HT20						
1	2412	-24.65	8	PASS		
6	2437	-23.32	8	PASS		
11	2462	-24.52	8	PASS		


























7.8 CONDUCTED BAND EDGE MEASUREMENT

7.8.1 Applicable Standard

According to FCC Part 15.247(d) and KDB 558074 DTS 01 Meas. Guidance v03r04

7.8.2 Conformance Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

7.8.3 Measuring Instruments

The Measuring equipment is listed in the section 6.3 of this test report.

7.8.4 Test Setup

Please refer to Section 6.1 of this test report.

7.8.5 Test Procedure

The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r04.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.

The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously.

The EUT was operating in controlled its channel.

Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.

Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.

Repeat above procedures until all measured frequencies were complete.




7.8.6 Test Results


EUT:	Smart Phone	Model No.:	PCB-i316
Temperature:	20 ℃	Relative Humidity:	48%
Test Mode:	Mode1/Mode2/Mode3	Test By:	Eileen Liu


Frequency Band	Delta Peak to band emission(dBc)	>Limit(dBc)	Verdict				
	802.11b						
2400	41.75	20	Pass				
2483.5	59.97	20	Pass				
	802.11g						
2400	31.69	20	Pass				
2483.5	47.12	20	Pass				
802.11n HT20							
2400	39.69	20	Pass				
2483.5	49.98	20	Pass				





















7.9 ANTENNA APPLICATION

7.9.1 Antenna Requirement

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

7.9.2 **Result**

The EUT antenna is permanent attached antenna. It comply with the standard requirement.

END OF REPORT