



# FCC Part 15C Test Report

## FCC ID: 2AFK9KT-MC-U01B

Product Name:	<b>YoSmart Hub</b>
Trademark:	<b>N/A</b>
Model Name :	<b>KT-MC-U01B</b> <b>KT-MC-UXXY</b> ('XX' is 2 digit numbers which represents the software version, for example, 01 represents the software version 0.1. 'Y' is 1 character which represents the color of product, for example 'B' represents black.)
Prepared For :	<b>KingTing Tech. Corporation</b>
Address :	17165 Von Karman Avenue, Suite 105, Irvine CA, US
Prepared By :	<b>Shenzhen BCTC Technology Co., Ltd.</b>
Address :	No.101, Yousong Road, Longhua New District, Shenzhen, China
Test Date:	<b>Aug. 7 - Aug. 17, 2015</b>
Date of Report :	<b>Aug. 18, 2015</b>
Report No.:	<b>BCTC-15080225</b>



## TEST RESULT CERTIFICATION

**Applicant's name** ..... : KingTing Tech. Corporation

Address ..... : 17165 Von Karman Avenue, Suite 105, Irvine CA, US

**Manufacture's Name** ..... : Guangdong KingTing Technology Co., Ltd.

Address ..... : 2B-2101 Hecheng century, Bantian Street, Longgang District, Shenzhen City, China

### Product description

Product name ..... : YoSmart Hub

Model and/or type reference : KT-MC-U01B

Serial Model ..... : KT-MC-UXXY ('XX' is 2 digit numbers which represents the software version, for example, 01 represents the software version 0.1. 'Y' is 1 character which represents the color of product, for example 'B' represents black.)

**Standards** ..... : FCC Part15.249

Test procedure ..... ANSI C63.10-2013

This device described above has been tested by BCTC, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of BCTC, this document may be altered or revised by BCTC, personal only, and shall be noted in the revision of the document.

Testing Engineer : Eric Yang

(Eric Yang)

Technical Manager : Sophia Lee

(Sophia Lee)

Authorized Signatory :

(Casey Wang)



**Table of Contents**

	<b>Page</b>
<b>1 . SUMMARY OF TEST RESULTS</b>	<b>5</b>
<b>1.1 TEST FACILITY</b>	6
<b>1.2 MEASUREMENT UNCERTAINTY</b>	6
<b>2 . GENERAL INFORMATION</b>	<b>7</b>
<b>2.1 GENERAL DESCRIPTION OF EUT</b>	7
<b>2.2 DESCRIPTION OF TEST MODES</b>	8
<b>2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED</b>	9
<b>2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)</b>	9
<b>2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS</b>	10
<b>3 . EMC EMISSION TEST</b>	<b>11</b>
<b>3.1 CONDUCTED EMISSION MEASUREMENT</b>	11
<b>3.1.1 POWER LINE CONDUCTED EMISSION LIMITS</b>	11
<b>3.1.2 TEST PROCEDURE</b>	11
<b>3.1.3 DEVIATION FROM TEST STANDARD</b>	11
<b>3.1.4 TEST SETUP</b>	12
<b>3.1.5 EUT OPERATING CONDITIONS</b>	12
<b>3.1.6 TEST RESULTS</b>	13
<b>3.2 RADIATED EMISSION MEASUREMENT</b>	15
<b>3.2.1 RADIATED EMISSION LIMITS</b>	15
<b>3.2.2 TEST PROCEDURE</b>	16
<b>3.2.3 DEVIATION FROM TEST STANDARD</b>	16
<b>3.2.4 TEST SETUP</b>	17
<b>3.2.5 EUT OPERATING CONDITIONS</b>	18
<b>3.2.6 TEST RESULTS (BETWEEN 9KHZ – 30 MHZ)</b>	19
<b>3.2.7 TEST RESULTS (BETWEEN 30MHZ – 1GHZ)</b>	20
<b>3.2.8 TEST RESULTS (ABOVE 1000 MHZ)</b>	22
<b>4 . 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE</b>	<b>23</b>
<b>4.1 DEVIATION FROM STANDARD</b>	24
<b>4.2 TEST SETUP</b>	24
<b>4.3 EUT OPERATION CONDITIONS</b>	24
<b>4.4 TEST RESULTS</b>	24
<b>5 . BANDWIDTH TEST</b>	<b>25</b>
<b>5.1 APPLIED PROCEDURES / LIMIT</b>	25

**Table of Contents**

	<b>Page</b>
<b>5.1.1 TEST PROCEDURE</b>	<b>25</b>
<b>5.1.2 DEVIATION FROM STANDARD</b>	<b>25</b>
<b>5.1.3 TEST SETUP</b>	<b>25</b>
<b>5.1.4 EUT OPERATION CONDITIONS</b>	<b>25</b>
<b>5.1.5 TEST RESULTS</b>	<b>26</b>
<b>6 . ANTENNA REQUIREMENT</b>	<b>27</b>
<b>6.1 STANDARD REQUIREMENT</b>	<b>27</b>
<b>6.2 EUT ANTENNA</b>	<b>27</b>
<b>7 . EUT TEST PHOTO</b>	<b>28</b>
<b>8 . PHOTO OF THE EUT</b>	<b>30</b>



## 1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

<b>FCC Part15 (15.249) , Subpart C</b>			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	
15.249 (a)(2)	20dB Bandwidth	PASS	
15.249	Radiated Spurious Emission	PASS	
15.205	Band Edge Emission	PASS	
15.203	Antenna Requirement	PASS	

**NOTE:**

(1)" N/A" denotes test is not applicable in this Test Report



## 1.1 TEST FACILITY

Shenzhen BCTC Technology Co., Ltd.

Address : No.101, YouSong Road, Longhua New District, Shenzhen, China

FCC Registered No.: 187086

## 1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement  $y \pm U$  , where expended uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$  , providing a level of confidence of approximately **95 %** .

No.	Item	Uncertainty
1	Conducted Emission Test	$\pm 1.38\text{dB}$
2	RF power, conducted	$\pm 0.16\text{dB}$
3	Spurious emissions, conducted	$\pm 0.21\text{dB}$
4	All emissions, radiated(<1G)	$\pm 4.68\text{dB}$
5	All emissions, radiated(>1G)	$\pm 4.89\text{dB}$
6	Temperature	$\pm 0.5^\circ\text{C}$
7	Humidity	$\pm 2\%$



## 2. GENERAL INFORMATION

### 2.1 GENERAL DESCRIPTION OF EUT

Equipment	YoSmart Hub	
Trade Name	N/A	
Model Name	KT-MC-U01B	
Serial Model	KT-MC-UXXY ('XX' is 2 digit numbers which represents the software version, for example, 01 represents the software version 0.1. 'Y' is 1 character which represents the color of product, for example 'B' represents black.)	
Model Difference	All the model are the same circuit and RF module, except model names.	
Product Description	The EUT is a YoSmart Hub	
	Operation Frequency:	915MHz
	Modulation Type:	GFSK
	Number Of Channel	1CH
	Antenna Designation:	Please see Note 3.
	Antenna Gain (dBi)	1.0dbi
	Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.	
Channel List	Please refer to the Note 2.	
Power	DC 5V from adapter	
Battery	N/A	
Connecting I/O Port(s)	Please refer to the User's Manual	

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2.

Table for Filed Antenna

Ant	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	NOTE
A	N/A	N/A	internal Antenna	N/A	1.0	



## 2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	TX Mode
Mode 2	Link Mode

For Conducted Emission	
Final Test Mode	Description
Mode 2	Link Mode

For Radiated Emission	
Final Test Mode	Description
Mode 1	TX Mode


Note:

- (1) The measurements are performed at the highest, middle, lowest available channels.
- (2) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported



## 2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Radiated Spurious Emission Test



## 2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	YoSmart Hub	N/A	KT-MC-U01B	N/A	EUT
E-2	Adapter	N/A	ODL-28850100	N/A	DC 5V/1A

Item	Shielded Type	Ferrite Core	Length	Note
C1	NO	NO	0.8M	

Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in 『Length』 column.



## 2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

### Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Test Receiver	R&S	ESCI	1166.5950K 03-101165-ha	2015.06.05	2016.06.05	1 year
2	LISN	R&S	NSLK81 26	812646 6	2014.08.24	2015.08.23	1 year
3	LISN	R&S	NSLK81 26	812648 7	2014.08.24	2015.08.23	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	620026441 7	2015.06.05	2016.06.05	1 year
5	RF cables	R&S	R204	R20X	2015.06.05	2016.06.05	1 year

### Radiation Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Spectrum Analyzer	Agilent	E4407B	MY4510957 2	2014.08.25	2015.08.24	1 year
2	Test Receiver	R&S	ESPI	101396	2014.08.25	2015.08.24	1 year
3	Bilog Antenna	SCHWARZB ECK	VULB9160	VULB9160- 3369	2014.08.25	2015.08.24	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	620026441 6	2015.06.07	2016.06.06	1 year
5	Spectrum Analyzer	ADVANTEST	R3132	150900201	2015.06.07	2016.06.06	1 year
6	Horn Antenna	SCHWARZB ECK	9120D	9120D-1275	2014.08.25	2015.08.24	1 year
7	Horn Ant	Schwarzbeck	BBHA 9170	9170-181	2014.07.06	2015.07.05	1 year
8	Amplifier	SCHWARZBE CK	BBV9718	9718-270	2014.08.25	2015.08.24	1 year
9	Amplifier	SCHWARZBE CK	BBV9743	9743-119	2014.08.25	2015.08.24	1 year
10	Loop Antenna	ARA	PLA-1030/B	1029	2015.06.08	2016.06.07	1 year
11	Power Meter	R&S	NRVS	100696	2014.07.06	2015.07.05	1 year
12	Power Sensor	R&S	URV5-Z4	0395.1619. 05	2014.07.06	2015.07.05	1 year
13	RF cables	R&S	N/A	N/A	2014.07.06	2015.07.05	1 year



### 3. EMC EMISSION TEST

#### 3.1 CONDUCTED EMISSION MEASUREMENT

##### 3.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)		Standard
	Quasi-peak	Average	Quasi-peak	Average	
0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	CISPR
0.50 -5.0	73.00	60.00	56.00	46.00	CISPR
5.0 -30.0	73.00	60.00	60.00	50.00	CISPR

0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	73.00	60.00	56.00	46.00	FCC
5.0 -30.0	73.00	60.00	60.00	50.00	FCC

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " \* " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz


#### 3.1.2 TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

#### 3.1.3 DEVIATION FROM TEST STANDARD

No deviation

### 3.1.4 TEST SETUP



**Note:**

1. Support units were connected to second LISN.
2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes


### 3.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.



### 3.1.6 TEST RESULTS


EUT :	YoSmart Hub	Model Name. :	KT-MC-U01B
Temperature :	26°C	Relative Humidity :	54%
Pressure :	1010hPa	Phase :	/
Test Voltage :	DC 5V FROM ADAPTER	Test Mode :	Mode 1



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
1		0.4140	38.51	10.11	48.62	57.57	-8.95	QP	
2	*	0.4140	30.15	10.11	40.26	47.57	-7.31	AVG	
3		0.7060	29.31	10.14	39.45	56.00	-16.55	QP	
4		0.7060	19.95	10.14	30.09	46.00	-15.91	AVG	
5		0.9660	25.26	10.16	35.42	56.00	-20.58	QP	
6		0.9660	16.85	10.16	27.01	46.00	-18.99	AVG	
7		3.7980	29.54	10.17	39.71	56.00	-16.29	QP	
8		3.7980	19.81	10.17	29.98	46.00	-16.02	AVG	
9		5.2260	25.56	10.14	35.70	60.00	-24.30	QP	
10		5.2260	15.78	10.14	25.92	50.00	-24.08	AVG	
11		14.9740	13.53	10.15	23.68	60.00	-36.32	QP	
12		14.9740	-0.41	10.15	9.74	50.00	-40.26	AVG	



EUT :	YoSmart Hub	Model Name. :	KT-MC-U01B
Temperature :	26°C	Relative Humidity :	54%
Pressure :	1010hPa	Phase :	N
Test Voltage :	DC 5V FROM ADAPTER	Test Mode :	Mode 1



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
1		0.4020	36.36	10.11	46.47	57.81	-11.34	QP	
2	*	0.4020	27.09	10.11	37.20	47.81	-10.61	AVG	
3		0.7060	29.03	10.14	39.17	56.00	-16.83	QP	
4		0.7060	17.07	10.14	27.21	46.00	-18.79	AVG	
5		1.0260	25.64	10.17	35.81	56.00	-20.19	QP	
6		1.0260	13.90	10.17	24.07	46.00	-21.93	AVG	
7		4.1100	30.26	10.16	40.42	56.00	-15.58	QP	
8		4.1100	16.56	10.16	26.72	46.00	-19.28	AVG	
9		5.7260	25.24	10.11	35.35	60.00	-24.65	QP	
10		5.7260	10.86	10.11	20.97	50.00	-29.03	AVG	
11		20.6380	12.66	10.18	22.84	60.00	-37.16	QP	
12		20.6380	-0.86	10.18	9.32	50.00	-40.68	AVG	



### 3.2 RADIATED EMISSION MEASUREMENT

#### 3.2.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

#### LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Class A (dBuV/m) (at 3M)		Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE	PEAK	AVERAGE
Above 1000	80	60	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP



### 3.2.2 TEST PROCEDURE

- a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

Note:


Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported

### 3.2.3 DEVIATION FROM TEST STANDARD


No deviation

### 3.2.4 TEST SETUP


#### (A) Radiated Emission Test-Up Frequency Below 30MHz



#### (B) Radiated Emission Test-Up Frequency 30MHz~1GHz



## (C) Radiated Emission Test-Up Frequency Above 1GHz



### 3.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.



### 3.2.6 TEST RESULTS (BETWEEN 9KHZ – 30 MHZ)

EUT:	YoSmart Hub	Model Name. :	KT-MC-U01B
Temperature:	20°C	Relative Humidity:	48%
Pressure:	1010 hPa	Test Voltage :	AC120V/60Hz
Test Mode :	TX	Polarization :	--

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	PASS
--	--	--	--	PASS

**NOTE:**

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log (\text{specific distance}/\text{test distance})$ (dB);  
Limit line = specific limits(dBuV) + distance extrapolation factor.



### 3.2.7 TEST RESULTS (BETWEEN 30MHZ – 1GHZ)

EUT :	YoSmart Hub	Model Name :	KT-MC-U01B
Temperature :	26°C	Relative Humidity :	54%
Pressure :	1010 hPa	Polarization :	Horizontal
Test Voltage :	DC 5V from adapter		
Test Mode :	TX		

Frequency (MHz)	Meter Reading (dB $\mu$ V)	Factor (dB)	Emission Level (dB $\mu$ V/m)	Limits (dB $\mu$ V/m)	Margin (dB)	Detector Type
99.8777	37.44	-16.49	20.95	43.50	-22.55	QP
199.9856	43.18	-16.20	26.98	43.50	-16.52	QP
250.3012	50.06	-14.19	35.87	46.00	-10.13	QP
350.4768	53.97	-11.38	42.59	46.00	-3.41	QP
451.1350	51.50	-9.00	42.50	46.00	-3.50	QP
801.7863	43.39	-2.49	40.90	46.00	-5.10	QP
915.0000	103.39	-3.16	100.23	114.00	-13.77	PK
915.0000	93.39	-3.16	90.23	94.00	-3.77	AV

Remark:  
Factor = Antenna Factor + Cable Loss – Pre-amplifier.  
All interfaces was connected, and TX mode was link.



EUT :	YoSmart Hub	Model Name :	KT-MC-U01B
Temperature :	26°C	Relative Humidity :	54%
Pressure :	1010 hPa	Polarization :	Vertical
Test Voltage :	DC 5V from adapter		
Test Mode :	TX		

Frequency (MHz)	Meter Reading (dB $\mu$ V)	Factor (dB)	Emission Level (dB $\mu$ V/m)	Limits (dB $\mu$ V/m)	Margin (dB)	Detector Type
31.8427	44.87	-8.27	36.60	40.00	-3.40	QP
49.8814	45.29	-10.27	35.02	40.00	-4.98	QP
150.0108	41.34	-12.86	28.48	43.50	-15.02	QP
250.3012	44.67	-14.19	30.48	46.00	-15.52	QP
451.1350	49.28	-9.00	40.28	46.00	-5.72	QP
550.9480	45.84	-7.09	38.75	46.00	-7.25	QP
915.0000	104.26	-3.23	101.03	114.00	-12.97	PK
915.0000	93.87	-3.23	90.64	94.00	-3.36	AV

Remark:  
Factor = Antenna Factor + Cable Loss – Pre-amplifier.  
All interfaces was connected, and TX mode was link.



### 3.2.8 TEST RESULTS (ABOVE 1000 MHZ)

Polar (H/V)	Normal Voltage							Detector Type
	Frequency (MHz)	Meter Reading (dBuV)	Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)		
<hr/>								
V	1830.00	65.02	-3.57	61.45	74	-12.55	Pk	
V	1830.00	56.09	-3.57	52.52	54	-1.48	AV	
V	2745.00	63.24	-3.84	59.40	74	-14.60	Pk	
V	2745.00	55.06	-3.84	51.22	54	-2.78	AV	
V	3660.00	62.45	-4.59	57.86	74	-16.14	Pk	
V	3660.00	54.18	-4.59	49.59	54	-4.41	AV	
H	1830.00	65.15	-3.62	61.53	74	-12.47	Pk	
H	1830.00	54.20	-3.62	50.58	54	-3.42	AV	
H	2745.00	63.34	-3.93	59.41	74	-14.59	Pk	
H	2745.00	54.87	-3.93	50.94	54	-3.06	AV	
H	3660.00	62.49	-4.62	57.87	74	-16.13	Pk	
H	3660.00	54.18	-4.62	49.56	54	-4.44	AV	

**Remark:**

Absolute Level= ReadingLevel+ Factor, Margin= Limit- Absolute Level



#### 4. 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE APPLICABLE STANDARD

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

#### TEST PROCEDURE

- a. The measuring distance of at 3 m shall be used for measurements at frequency up to 25GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 1.5 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.
- g. For the radiated emission test above 1GHz:

Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response.

The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported



#### 4.1 DEVIATION FROM STANDARD

No deviation.

#### 4.2 TEST SETUP

#### 4.3 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

#### 4.4 TEST RESULTS

EUT :	Balight	Model Name :	LK152001-RD
Temperature :	25 °C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	By Battery
Test Mode :	TX Mode		

Frequency (MHz)	Antenna polarization (H/V)	Emission (dBuV/m)	Limit (dBuV/m)	Result
				Pass
902	H	40.21	46.00	Pass
902	V	40.09	46.00	Pass
928	H	40.27	46.00	Pass
928	V	40.14	46.00	Pass

If the PK measured levels comply with average limit, then the average level were deemed to comply with average limit.



## 5. BANDWIDTH TEST

### 5.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.249) , Subpart C			
Section	Test Item	Frequency Range (MHz)	Result
15.249	Bandwidth	900~928	PASS

#### 5.1.1 TEST PROCEDURE

1. Set resolution bandwidth (RBW) = 1-5% or DTS BW, not to exceed 100 kHz.
2. Set the video bandwidth (VBW)  $\geq 3 \times$  RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

#### 5.1.2 DEVIATION FROM STANDARD

No deviation.

#### 5.1.3 TEST SETUP



#### 5.1.4 EUT OPERATION CONDITIONS


The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.



### 5.1.5 TEST RESULTS

EUT :	YoSmart Hub	Model Name :	KT-MC-U01B
Temperature :	25°C	Relative Humidity :	60%
Pressure :	1012 hPa	Test Voltage :	DC 5V from adapter
Test Mode :	TX Mode		

Channel	Frequency (MHz)	20dB bandwidth (MHz)
	915	0.474





## 6. ANTENNA REQUIREMENT

### 6.1 STANDARD REQUIREMENT



15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

### 6.2 EUT ANTENNA

The EUT antenna is Integrated antenna. It comply with the standard requirement.

## 7. EUT TEST PHOTO

RE





**C E**



## 8. PHOTO OF THE EUT

