

INTERTEK TESTING SERVICES

RF Exposure

The Equipment under Test (EUT) is a control unit for THE GOAL LIGHT 30 HORN SOUND operating at 2.4GHz band. It is powered by DC 3.0V (2 x 1.5V AAA batteries). For more detail information pls. refer to the user manual.

Antenna Type: Integral antenna.

Antenna Gain: 2dBi.

The normal radiated output power (e.i.r.p) is: 1.0dBm (tolerance: +/- 3dB).

The normal conducted output power is: -1.0dBm (tolerance: +/- 3dB).

Modulation Type: GFSK.

According to the KDB 447498:

The Maximum peak radiated emission for the EUT is 95.7dB μ V/m at 3m in the frequency 2427MHz

The EIRP = $[(FS^*D)^2 / 30] \text{ mW} = 0.47 \text{ dBm}$
which is within the production variation.

The maximum conducted output power specified is 2.0dBm = 1.6mW

The source- based time-averaging conducted output power
= $1.6 * \text{Duty cycle mW} < 1.6 \text{ mW} (\text{Duty cycle} < 100\%)$

The SAR Exclusion Threshold Level:

$$\begin{aligned} &= 3.0 * (\text{min. test separation distance, mm}) / \text{sqrt(freq. in GHz)} \\ &= 3.0 * 5 / \text{sqrt}(2.427) \text{ mW} \\ &= 9.6 \text{ mW} \end{aligned}$$

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.

The duty cycle is simply the on-time divided by the period:

The duration of one cycle = 2.0000 ms

Effective period of the cycle = 144.9 μ s = 0.1449 ms

DC = 0.1449ms / 2.0000 ms = 0.0725 or 7.25%

FCC ID: 2AFKK99378