

### 6.5.3 Test data

Pass: Please refer to appendix A for details

BlueAsia

## 6.6 Conducted spurious emissions

<b>Test Standard</b>	47 CFR Part 15, Subpart C 15.247 (d)
<b>Test Method</b>	ANSI C63.10 (2013) Section 7.8.8
<b>Test Mode (Pre-Scan)</b>	TX
<b>Test Mode (Final Test)</b>	TX

### 6.6.1 Limit


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20dB.

Attenuation below the general limits specified in §15.209(a) is not required.

In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

### 6.6.2 Test setup



### 6.6.3 Test data

Pass: Please refer to appendix A for details

BlueAsia


## 6.7 Carrier Frequencies Separation

<b>Test Standard</b>	47 CFR Part 15, Subpart C 15.247 (a)(1)
<b>Test Method</b>	ANSI C63.10 (2013) Section 7.8.2
<b>Test Mode (Pre-Scan)</b>	TX
<b>Test Mode (Final Test)</b>	TX

### 6.7.1 Limit

2/3 of the 20dB bandwidth base on the transmission power is less than 0.125W

### 6.7.2 Test setup



### 6.7.3 Test data

Pass: Please refer to appendix A for details


## 6.8 Hopping Channel Number

<b>Test Standard</b>	47 CFR Part 15, Subpart C 15.247 (a)(1) (iii)
<b>Test Method</b>	ANSI C63.10 (2013) Section 7.8.3
<b>Test Mode (Pre-Scan)</b>	TX
<b>Test Mode (Final Test)</b>	TX

### 6.8.1 Limit

<b>Frequency range(MHz)</b>	<b>Number of hopping channels (minimum)</b>
902-928	50 for 20dB bandwidth <250kHz
	25 for 20dB bandwidth ≥250kHz
2400-2483.5	15
5725-5850	75

### 6.8.2 Test setup



### 6.8.3 Test data

Pass: Please refer to appendix A for details

*BlueAsia of Technical Services (Shenzhen) Co.,Ltd.*

Tel: +86-755-23059481

Email: [marketing@cblueasia.com](mailto:marketing@cblueasia.com) [www.cblueasia.com](http://www.cblueasia.com)

Version:v1.2


## 6.9 Dwell Time

<b>Test Standard</b>	47 CFR Part 15, Subpart C 15.247(a)(1) (iii)
<b>Test Method</b>	ANSI C63.10 (2013) Section 7.8.4
<b>Test Mode (Pre-Scan)</b>	TX
<b>Test Mode (Final Test)</b>	TX

### 6.9.1 Limit

Frequency(MHz)	Limit
902-928	0.4s within a 20s period(20dB bandwidth<250kHz)
	0.4s within a 10s period(20dB bandwidth≥250kHz)
2400-2483.5	0.4s within a period of 0.4s multiplied by the number of hopping channels
5725-5850	0.4s within a 30s period

### 6.9.2 Test setup



### 6.9.3 Test data

Pass: Please refer to appendix A for details

## 6.10 Radiated spurious emissions

<b>Test Standard</b>	47 CFR Part 15, Subpart C 15.247(d) 47 CFR Part 15, Subpart C 15.209
<b>Test Method</b>	ANSI C63.10 (2013) Section 6.3,6.4,6.5,6.6
<b>Test Mode (Pre-Scan)</b>	TX
<b>Test Mode (Final Test)</b>	TX


### 6.10.1 Limit

<b>Frequency(MHz)</b>	<b>Field strength(microvolts/meter)</b>	<b>Measurement distance(meters)</b>
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3


*Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.*

### 6.10.2 Test setup


Below 1GHz:



30MHz-1GHz:



Above 1GHz:



### 6.10.3 Procedure

- a) For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b) For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c) The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d) The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e) For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f) The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g) If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h) Test the EUT in the lowest channel, the middle channel, the highest channel.
- i) The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j) Repeat above procedures until all frequencies measured was complete.

*Note 1: Scan from 9 kHz to 25GHz, the disturbance above 12.75GHz and below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported. Fundamental frequency is blocked by filter, and only spurious emission is shown.*

*Note 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.*


*Note 3: The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:*

$$\text{Level (dBuV)} = \text{Reading (dBuV)} + \text{Factor (dB/m)}$$

### 6.10.4 Test data


Below 1GHz

[Test mode: TX]; [Polarity: Horizontal]



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	55.0274	-0.37	19.34	18.97	40.00	-21.03	QP	P	
2	77.5928	-0.80	15.69	14.89	40.00	-25.11	QP	P	
3	142.3243	-1.97	20.19	18.22	43.50	-25.28	QP	P	
4	343.1800	0.37	21.19	21.56	46.00	-24.44	QP	P	
5	629.4772	-1.14	27.81	26.67	46.00	-19.33	QP	P	
6 *	942.1305	0.37	31.18	31.55	46.00	-14.45	QP	P	

**Test Result: Pass**


[**Test mode: TX**]; [**Polarity: Vertical**]


No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	P/F	Remark
1	47.1599	-1.74	19.44	17.70	40.00	-22.30	QP	P	
2	70.0903	-1.49	16.66	15.17	40.00	-24.83	QP	P	
3	150.0108	-2.07	20.57	18.50	43.50	-25.00	QP	P	
4	349.2500	-0.94	21.33	20.39	46.00	-25.61	QP	P	
5	640.6110	-1.00	27.71	26.71	46.00	-19.29	QP	P	
6 *	938.8326	0.67	31.05	31.72	46.00	-14.28	QP	P	

**Test Result: Pass**


Above 1GHz:

[Test mode: TX low channel]; [Polarity: Horizontal]



No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		4804.000	37.97	6.31	44.28	74.00	-29.72	peak	
2		5864.500	39.48	8.93	48.41	74.00	-25.59	peak	
3		7206.000	36.74	10.39	47.13	74.00	-26.87	peak	
4	*	8426.000	37.42	11.31	48.73	74.00	-25.27	peak	
5		9608.000	33.50	13.01	46.51	74.00	-27.49	peak	
6		11351.75	34.77	13.74	48.51	74.00	-25.49	peak	

**Test Result: Pass**

[**Test mode: TX low channel**]; [**Polarity: Vertical**]


No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		4804.000	39.57	6.31	45.88	74.00	-28.12	peak	
2		5888.000	39.08	9.05	48.13	74.00	-25.87	peak	
3		7206.000	38.16	10.39	48.55	74.00	-25.45	peak	
4		8155.750	37.38	11.49	48.87	74.00	-25.13	peak	
5		9608.000	33.56	13.01	46.57	74.00	-27.43	peak	
6	*	11575.00	35.72	14.79	50.51	74.00	-23.49	peak	

**Test Result: Pass**

[**Test mode: TX middle channel**]; [**Polarity: Horizontal**]

**Radiated Emission Measurement**

Project No.: REH


Data #:3

2025/5/19




No.	Mk.	Freq.	Reading	Correct	Measure-	Limit	Over	Detector	Comment
			Level	Factor	ment				
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		4882.000	39.49	6.43	45.92	74.00	-28.08	peak	
2		5864.500	38.65	8.93	47.58	74.00	-26.42	peak	
3		7323.000	35.53	10.17	45.70	74.00	-28.30	peak	
4		8097.000	37.60	11.79	49.39	74.00	-24.61	peak	
5		9764.000	33.56	13.76	47.32	74.00	-26.68	peak	
6	*	10623.25	36.38	13.42	49.80	74.00	-24.20	peak	

**Test Result: Pass**

[**Test mode: TX middle channel**]; [**Polarity: Vertical**]

**Test Result: Pass**

[Test mode: TX High channel]; [Polarity: Horizontal]



Test Result: Pass

[Test mode: TX High channel]; [Polarity: Vertical]

**Radiated Emission Measurement**

Project No.: REH

Data #:6

2025/5/19



No. Mk.	Freq. MHz	Reading	Correct	Measure-	Limit dBuV/m	Over dB	Detector	Comment
		Level dBuV	Factor dB	ment dBuV/m				
1	4960.000	37.93	7.41	45.34	74.00	-28.66	peak	
2	5958.500	38.52	9.01	47.53	74.00	-26.47	peak	
3	7440.000	37.38	11.03	48.41	74.00	-25.59	peak	
4	8484.750	37.88	11.43	49.31	74.00	-24.69	peak	
5	9920.000	32.46	13.16	45.62	74.00	-28.38	peak	
6 *	11445.75	34.82	14.55	49.37	74.00	-24.63	peak	

**Test Result: Pass**

DH1, DH3, DH5 all have been tested, during the test, GFSK, pi/4DQPSK, 8DPSK, modulation were all pre-scanned. Only the (DH1/GFSK) of the worst mode would be recorded in this report.

When scanning in the range of 1GHz~ 40GHz and the interference above 12.75GHz is very small, it is a low noise signal. The point shown in the figure above is the highest emission that can be found during the test, so only the above point is shown. The fundamental frequency is blocked by the filter. Only stray emission.

## 6.11 Radiated emissions which fall in the restricted bands

<b>Test Standard</b>	47 CFR Part 15, Subpart C 15.247(d) 47 CFR Part 15, Subpart C 15.205
<b>Test Method</b>	ANSI C63.10 (2013) Section 6.10.5
<b>Test Mode (Pre-Scan)</b>	TX
<b>Test Mode (Final Test)</b>	TX


### 6.11.1 Limit

<b>Frequency(MHz)</b>	<b>Field strength(microvolts/meter)</b>	<b>Measurement distance(meters)</b>
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3


*Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.*

### 6.11.2 Test setup


Below 1GHz:



30MHz-1GHz:



Above 1GHz:



### 6.11.3 Procedure

- a) For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b) For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c) The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d) The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e) For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f) The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g) If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h) Test the EUT in the lowest channel, the middle channel, the highest channel.
- i) The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j) Repeat above procedures until all frequencies measured was complete.

Note 1: Level (dBuV) = Reading (dBuV) + Factor (dB/m)

Note 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.