



### 3.6 Hopping Channel Number

Test Requirement:	47 CFR Part 15C Section 15.247 (a)(1)
Test Method:	ANSI C63.10: 2013 Section 7.8.3
Test Setup:	 <p>The diagram illustrates the test setup for measuring hopping channel number. A Spectrum Analyzer is positioned above a Non-Conducted Table. A red line connects the Spectrum Analyzer to a device labeled 'E.U.T' (Equipment Under Test) which is placed on the table. The table is supported by a grey rectangular frame representing the 'Ground Reference Plane'.</p>
Instruments Used:	Refer to section 2.9 for details
Test Mode:	Hopping transmitting with all kind of modulation
Limit:	At least 15 channels
Test Results:	Pass


The detailed test data see: **Appendix E**

### 3.7 Band-edge for RF Conducted Emissions

Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10: 2013 Section 7.8.6
Test Setup:	
Instruments Used:	Refer to section 2.9 for details
Exploratory Test Mode:	Hopping and Non-hopping transmitting with all kind of modulation and all kind of data type.
Final Test Mode:	Through Pre-scan, find the worst case of all modulation type.
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test Results:	Pass

The detailed test data see: **Appendix F**

### 3.8 RF Conducted Spurious Emissions

Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10: 2013 Section 11.11
Test Setup:	
Instruments Used:	Refer to section 2.9 for details
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Through Pre-scan, find the worst case of all modulation type.
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test Results:	Pass

The detailed test data see: **Appendix G**



### 3.9 Radiated Spurious Emissions

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205				
Test Method:	ANSI C63.10: 2013 Section 11.12				
Test Site:	Measurement Distance: 3m or 10m (Semi-Anechoic Chamber)				
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	0.009MHz-0.090MHz	Peak	10kHz	30kHz	Peak
	0.009MHz-0.090MHz	Average	10kHz	30kHz	Average
	0.090MHz-0.110MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	0.110MHz-0.490MHz	Peak	10kHz	30kHz	Peak
	0.110MHz-0.490MHz	Average	10kHz	30kHz	Average
	0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	120kHz	300kHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz (DC $\geq$ 0.98) $\geq$ 1/T (DC<0.98)	Average
Limit:	Frequency	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz-0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz-88MHz	100	40.0	Quasi-peak	3
	88MHz-216MHz	150	43.5	Quasi-peak	3
	216MHz-960MHz	200	46.0	Quasi-peak	3
	960MHz-1GHz	500	54.0	Quasi-peak	3
	Above 1GHz	500	54.0	Average	3
Remark: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.					

## Test Setup:




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz





Figure 3. Above 1 GHz

## Test Procedure:


- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters(for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- Test the EUT in the lowest channel, the middle channel ,the Highest channel.
- The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, And found the X axis positioning which it is worse case.
- Repeat above procedures until all frequencies measured was complete.



Test Configuration:	<p>Measurements Below 1000MHz</p> <ul style="list-style-type: none"><li>• RBW = 120 kHz</li><li>• VBW = 300 kHz</li><li>• Detector = Peak</li><li>• Trace mode = max hold</li></ul> <p>Peak Measurements Above 1000 MHz</p> <ul style="list-style-type: none"><li>• RBW = 1 MHz</li><li>• VBW <math>\geq 3</math> MHz</li><li>• Detector = Peak</li><li>• Sweep time = auto</li><li>• Trace mode = max hold</li></ul> <p>Average Measurements Above 1000MHz</p> <ul style="list-style-type: none"><li>• RBW = 1 MHz</li><li>• VBW = 10 Hz, when duty cycle is no less than 98 percent.</li><li>• VBW <math>\geq 1/T</math>, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.</li></ul>
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates. Charge+Transmitting mode.
Final Test Mode:	Pretest the EUT at Transmitting mode. Through Pre-scan, find the DH5 of data type is the worst case of All modulation type.
Instruments Used:	Refer to section 2.9 for details
Test Results:	Pass

**Test data**
**For 30-1000MHz**


NO.	Freq. [MHz]	Reading Level [dB $\mu$ V]	Correct Factor [dB/m]	Result Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Height [cm]	Angle [°]	Remark	Polarity
1	32.33	43.89	-9.68	34.21	40.00	5.79	100	281	QP	Vertical
2	56.00	45.89	-8.35	37.54	40.00	2.46	100	229	QP	Vertical
3	71.72	39.92	-10.41	29.51	40.00	10.49	100	313	QP	Vertical
4	97.91	43.14	-12.93	30.21	43.50	13.29	100	26	QP	Vertical
5	167.38	38.28	-8.12	30.16	43.50	13.34	100	86	QP	Vertical
6	197.65	44.01	-11.06	32.95	43.50	10.55	100	59	QP	Vertical




NO.	Freq. [MHz]	Reading Level [dB $\mu$ V]	Correct Factor [dB/m]	Result Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Height [cm]	Angle [°]	Remark	Polarity
1	55.61	32.04	-8.32	23.72	40.00	16.28	100	251	QP	Horizontal
2	78.70	37.67	-12.20	25.47	40.00	14.53	200	185	QP	Horizontal
3	99.47	36.98	-12.71	24.27	43.50	19.23	200	135	QP	Horizontal
4	199.40	45.29	-11.08	34.21	43.50	9.29	100	281	QP	Horizontal
5	336.00	32.56	-5.92	26.64	46.00	19.36	100	85	QP	Horizontal
6	441.94	31.55	-3.00	28.55	46.00	17.45	100	98	QP	Horizontal




For above 1GHz

DH5 2402MHz




NO.	Freq. [MHz]	Reading Level [dB $\mu$ V]	Correct Factor [dB/m]	Result Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Height [cm]	Angle [°]	Remark	Polarity
1	4804.59	44.86	-4.61	40.25	74.00	33.75	150	198	Peak	Vertical
2	7206.21	44.13	-1.76	42.37	74.00	31.63	150	198	Peak	Vertical
3	9608.58	44.62	0.88	45.50	74.00	28.50	150	0	Peak	Vertical
4	4804.59	37.17	-4.61	32.56	54.00	21.44	150	198	AV	Vertical
5	7206.21	35.08	-1.76	33.32	54.00	20.68	150	198	AV	Vertical
6	9608.58	39.30	0.88	40.18	54.00	13.82	150	0	AV	Vertical




NO.	Freq. [MHz]	Reading Level [dB $\mu$ V]	Correct Factor [dB/m]	Result Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Height [cm]	Angle [°]	Remark	Polarity
1	4804.59	51.37	-4.61	46.76	74.00	27.24	150	125	Peak	Horizon
2	7206.21	44.13	-1.76	42.37	74.00	31.63	150	216	Peak	Horizon
3	9608.58	44.46	0.88	45.34	74.00	28.66	150	107	Peak	Horizon
4	4804.59	46.89	-4.61	42.28	54.00	11.72	150	107	AV	Horizon
5	7206.21	36.48	-1.76	34.72	54.00	19.28	150	107	AV	Horizon
6	9608.58	39.85	0.88	40.73	54.00	13.27	150	107	AV	Horizon



## DH5 2441MHz




NO.	Freq. [MHz]	Reading Level [dB $\mu$ V]	Correct Factor [dB/m]	Result Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Height [cm]	Angle [°]	Remark	Polarity
1	4882.59	45.15	-4.72	40.43	74.00	33.57	150	91	Peak	Vertical
2	7323.22	43.58	-1.49	42.09	74.00	31.91	150	74	Peak	Vertical
3	9763.84	48.06	1.64	49.70	74.00	24.30	150	40	Peak	Vertical
4	4882.59	37.35	-4.72	32.63	54.00	21.37	150	110	AV	Vertical
5	7323.22	35.19	-1.49	33.70	54.00	20.30	150	40	AV	Vertical
6	9764.59	44.76	1.64	46.40	54.00	7.60	150	40	AV	Vertical




NO.	Freq. [MHz]	Reading Level [dB $\mu$ V]	Correct Factor [dB/m]	Result Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Height [cm]	Angle [°]	Remark	Polarity
1	4881.84	50.39	-4.72	45.67	74.00	28.33	150	253	Peak	Horizon
2	7323.22	44.47	-1.49	42.98	74.00	31.02	150	20	Peak	Horizon
3	9763.84	50.58	1.64	52.22	74.00	21.78	150	91	Peak	Horizon
4	4882.59	45.07	-4.72	40.35	54.00	13.65	150	127	AV	Horizon
5	7323.22	36.47	-1.49	34.98	54.00	19.02	150	73	AV	Horizon
6	9764.59	47.22	1.64	48.86	54.00	5.14	150	91	AV	Horizon



## DH5 2480MHz



NO.	Freq. [MHz]	Reading Level [dBµV]	Correct Factor [dB/m]	Result Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Remark	Polarity
1	4960.60	44.97	-4.86	40.11	74.00	33.89	150	56	Peak	Vertical
2	7440.22	43.58	-1.34	42.24	74.00	31.76	150	37	Peak	Vertical
3	9919.85	47.95	2.26	50.21	74.00	23.79	150	73	Peak	Vertical
4	4960.60	37.91	-4.86	33.05	54.00	20.95	150	19	AV	Vertical
5	7440.22	34.53	-1.34	33.19	54.00	20.81	150	305	AV	Vertical
6	9920.60	44.78	2.27	47.05	54.00	6.95	150	73	AV	Vertical



NO.	Freq. [MHz]	Reading Level [dBµV]	Correct Factor [dB/m]	Result Level [dBµV/m]	Limit [dBµV/m]	Margin [dB]	Height [cm]	Angle [°]	Remark	Polarity
1	4959.85	50.56	-4.86	45.70	74.00	28.30	150	75	Peak	Horizon
2	7440.22	42.81	-1.34	41.47	74.00	32.53	150	109	Peak	Horizon
3	9919.85	48.59	2.26	50.85	74.00	23.15	150	18	Peak	Horizon
4	4960.60	45.16	-4.86	40.30	54.00	13.70	150	75	AV	Horizon
5	7440.22	34.54	-1.34	33.20	54.00	20.80	150	75	AV	Horizon
6	9920.60	44.50	2.27	46.77	54.00	7.23	150	36	AV	Horizon



## Note:

1. The Measurement (Result Level) is calculated by Reading Level adding the Correct Factor(maybe including Ant.Factor and the Cable Factor etc.), The basic equation is as follows:

$$\text{Result Level} = \text{Reading Level} + \text{Correct Factor}(\text{including Ant.Factor, Cable Factor etc.})$$

2. The amplitude of 9KHz to 30MHz spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

3. The amplitude of 18GHz to 25GHz spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be report.

4. All channels had been pre-test,DH5 is the worst case, only the worst case was reported.

### 3.10 Restricted bands around fundamental frequency

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205		
Test Method:	ANSI C63.10: 2013 Section 11.12		
Test Site:	Measurement Distance: 3m or 10m (Semi-Anechoic Chamber)		
Limit:	Frequency	Limit (dBuV/m)	Remark
	30MHz-88MHz	40.0	Quasi-peak
	88MHz-216MHz	43.5	Quasi-peak
	216MHz-960MHz	46.0	Quasi-peak
	960MHz-1GHz	54.0	Quasi-peak
	Above 1GHz	54.0	Average Value
		74.0	Peak Value
Test Setup:			




Figure 1. 30MHz to 1GHz




Figure 2. Above 1 GHz

Test Procedure:	<ol style="list-style-type: none"> <li>For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.</li> <li>For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.</li> <li>The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.</li> <li>The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.</li> <li>For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.</li> <li>The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.</li> <li>Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for each power and modulation for lowest and highest channel</li> <li>Test the EUT in the lowest channel , the Highest channel</li> <li>The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, And found the X axis positioning which it is worse case.</li> <li>Repeat above procedures until all frequencies measured was complete.</li> </ol>
Test Configuration:	Measurements Below 1000MHz

Dongguan DN Testing Co., Ltd.

Add: No. 1, West Fourth Street, Xingfa South Road, Wusha Community, Chang'an Town, Dongguan City, Guangdong P.R.China

Web: [www.dn-testing.com](http://www.dn-testing.com)

Tel: +86-769-88087383

E-mail: [service@dn-testing.com](mailto:service@dn-testing.com)




	<ul style="list-style-type: none"><li>• RBW = 120 kHz</li><li>• VBW = 300 kHz</li><li>• Detector = Peak</li><li>• Trace mode = max hold</li></ul> <p>Peak Measurements Above 1000 MHz</p> <ul style="list-style-type: none"><li>• RBW = 1 MHz</li><li>• VBW <math>\geq 3</math> MHz</li><li>• Detector = Peak</li><li>• Sweep time = auto</li><li>• Trace mode = max hold</li></ul> <p>Average Measurements Above 1000MHz</p> <ul style="list-style-type: none"><li>• RBW = 1 MHz</li><li>• VBW = 10 Hz, when duty cycle is no less than 98 percent.</li><li>• VBW <math>\geq 1/T</math>, when duty cycle is less than 98 percent where T is the minimum</li></ul> <p>transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.</p>
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates. Transmitting mode.
Final Test Mode:	Pretest the EUT Transmitting mode. Through Pre-scan, find the DH5 of data type is the worst case of all modulation type. Only the worst case is recorded in the report.
Instruments Used:	Refer to section 2.9 for details
Test Results:	Pass




Test Date

DH5 2402MHz




NO.	Freq. [MHz]	Reading Level [dB $\mu$ V]	Correct Factor [dB/m]	Result Level [dB $\mu$ V/m]	AV Limit [dB $\mu$ V/m]	Margin [dB]	Height [cm]	Angle [°]	Remark	Polarity
1	2381.61	50.53	-0.83	49.70	74.00	24.30	150	281	Peak	Vertical
2	2390.01	48.30	-0.80	47.50	74.00	26.50	150	73	Peak	Vertical
3	2380.78	39.97	-0.83	39.14	54.00	14.86	150	51	AV	Vertical
4	2390.01	39.54	-0.80	38.74	54.00	15.26	150	271	AV	Vertical




NO.	Freq. [MHz]	Reading Level [dB $\mu$ V]	Correct Factor [dB/m]	Result Level [dB $\mu$ V/m]	AV Limit [dB $\mu$ V/m]	Margin [dB]	Height [cm]	Angle [°]	Remark	Polarity
1	2382.43	50.62	-0.83	49.79	74.00	24.21	150	268	Peak	Horizon
2	2390.01	48.89	-0.80	48.09	74.00	25.91	150	234	Peak	Horizon
3	2381.08	40.20	-0.83	39.37	54.00	14.63	150	151	AV	Horizon
4	2390.01	38.98	-0.80	38.18	54.00	15.82	150	68	AV	Horizon

## DH5 2480MHz



NO.	Freq. [MHz]	Reading Level [dB $\mu$ V]	Correct Factor [dB/m]	Result Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Height [cm]	Angle [°]	Remark	Polarity
1	2483.50	48.34	-0.29	48.05	74.00	25.95	150	190	Peak	Vertical
2	2487.66	50.14	-0.26	49.88	74.00	24.12	150	8	Peak	Vertical
3	2483.50	39.03	-0.29	38.74	54.00	15.26	150	356	AV	Vertical
4	2488.32	40.07	-0.26	39.81	54.00	14.19	150	247	AV	Vertical



NO.	Freq. [MHz]	Reading Level [dB $\mu$ V]	Correct Factor [dB/m]	Result Level [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]	Height [cm]	Angle [°]	Remark	Polarity
1	2483.50	48.11	-0.29	47.82	74.00	26.18	150	118	Peak	Horizon
2	2487.42	50.15	-0.26	49.89	74.00	24.11	150	245	Peak	Horizon
3	2483.50	39.26	-0.29	38.97	54.00	15.03	150	85	AV	Horizon
4	2487.00	39.70	-0.26	39.44	54.00	14.56	150	62	AV	Horizon

## Note:

1. The Measurement (Result Level) is calculated by Reading Level adding the Correct Factor(maybe including Ant.Factor and the Cable Factor etc.), The basic equation is as follows:

Result Level= Reading Level + Correct Factor(including Ant.Factor ,Cable Factor etc.

- 2.All channels had been pre-test, DH5 is the worst case, only the worst case was reported.

### 3.11 AC Power Line Conducted Emissions




Final Test Mode:	Through Pre-scan, find the the worst case.
Instruments Used:	Refer to section 2.9 for details
Test Results:	PASS

### Measurement Data

An initial pre-scan was performed on the live and neutral lines with peak detector.

Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.

Live Line:



### Final Data List

NO.	Freq. [MHz]	Factor [dB]	QP Value [dBμV]	QP Limit [dBμV]	QP Margin [dB]	AV Value [dBμV]	AV Limit [dBμV]	AV Margin [dB]	Verdict
1	0.1734	9.91	45.55	64.80	19.25	33.16	54.80	21.64	PASS
2	0.2935	9.89	41.04	60.43	19.39	26.89	50.43	23.54	PASS
3	0.4213	9.79	43.86	57.42	13.56	24.57	47.42	22.85	PASS
4	0.5062	9.88	43.61	56.00	12.39	22.37	46.00	23.63	PASS
5	3.0670	9.74	31.70	56.00	24.30	20.05	46.00	25.95	PASS
6	4.7062	9.78	28.83	56.00	27.17	19.50	46.00	26.50	PASS