

# **FCC RADIO TEST REPORT**

FCC ID: 2AFKV-V001

Product: Vue

Trade Name: N/A

Model Name: Classic

Serial Model: Trendy

Report No.: UNIA2018070613-1FR-01

# **Prepared for**

Vigo Technologies Inc

479 Jessie Street, San Francisco, California 94103 United States

# Prepared by

Shenzhen United Testing Technology Co., Ltd.

2F, Annex Bldg, Jiahuangyuan Tech Park, #365 Baotian 1 Rd, Tiegang Community, Xixiang Str, Bao'an District, Shenzhen, China





# **TEST RESULT CERTIFICATION**

Report No.: UNIA2018070613-1FR-01

Applicant's name	Vigo Ted	chnologies Inc			
Address:	479 Jess United S		rancisco, Califorr	nia 94103	
Manufacture's Name:	Vigo Ted	chnologies Inc			
Address:	479 Jess United S		rancisco, Califorr	nia 94103	
Product description					
Product name:	Vue				
Trade Mark:	N/A				
Model and/or type reference .:	Classic, 7	Γrendy			
Standards:	FCC Rule	es and Regulations. 3.10: 2013	ons Part 15 Subpa	art C Section	15.249
This device described above Co., Ltd., and the test results with the FCC requirements. A report.  This report shall not be reproducument may be altered or personnel only, and shall be a Date of Test	show that And it is a duced ex revised b noted in t	at the equipme pplicable only cept in full, wit y Shenzhen U	nt under test (E to the tested sa hout the written nited Testing Te	UT) is in cor mple identifi approval of	mpliance ed in the UNI, this
Date (s) of performance of tests.	:	Jul. 06, 2018 -	- Aug. 17, 2018		
Date of Issue	:	Aug. 17, 2018			
Test Result	:	Pass			
		,	A.		
Prepared by:	_	8	in yang/Editor	log K	
Reviewer:	-	Sherw	Dian/Supervis	sor	
Approved & Authorized Signa	er: _		Live		
		. 1	iuze/Manager		





Table of Contents	Page
1 . TEST SUMMARY	4
2 . GENERAL INFORMATION	5
2.1 GENERAL DESCRIPTION OF EUT	5
2.2 Carrier Frequency of Channels	6
2.3 Operation of EUT during testing	6
2.4 DESCRIPTION OF TEST SETUP	6
2.5 MEASUREMENT INSTRUMENTS LIST	7
3. CONDUCTED EMISSIONS TEST	8
3.1 Conducted Power Line Emission Limit	8
3.2 Test Setup	8
3.3 Test Procedure	8
3.4 Test Result	F <sup>1</sup> 8
4 RADIATED EMISSION TEST	11
4.1 Radiation Limit	11
4.2 Test Setup	J 11
4.3 Test Procedure	12
4.4 Test Result	12
5 BAND EDGE	18
5.1 Limits	18
5.2 Test Procedure	18
5.3 Test Result	18
6 OCCUPIED BANDWIDTH MEASUREMENT	21
6.1 Test Setup	21
6.2 Test Procedure	21
6.3 Measurement Equipment Used	21
6.4 Test Result	21
7 ANTENNA REQUIREMENT	23
8 PHOTOGRAPH OF TEST	24
8.1 Radiated Emission	24
8.2 Conducted Emission	25





#### 1. TEST SUMMARY

#### 1.1 TEST PROCEDURES AND RESULTS

DESCRIPTION OF TEST

CONDUCTED EMISSIONS TEST

RADIATED EMISSION TEST

BAND EDGE

OCCUPIED BANDWIDTH MEASUREMENT

ANTENNA REQUIREMENT

RESULT

COMPLIANT

COMPLIANT

COMPLIANT

COMPLIANT

#### 1.2 TEST FACILITY

Test Firm : Shenzhen United Testing Technology Co., Ltd.

Address : 2F, Annex Bldg, Jiahuangyuan Tech Park, #365 Baotian 1 Rd, Tiegang

Community, Xixiang Str, Bao'an District, Shenzhen, China

The testing quality ability of our laboratory meet with "Quality Law of People's Republic of China" Clause 19. The testing quality system of our laboratory meets with ISO/IEC-17025 requirements, which is approved by CNAS. This approval result is accepted by MRA of APLAC.

Our test facility is recognized, certified, or accredited by the following organizations:

CNAS-LAB Code: L6494

The EMC Laboratory has been assessed and in compliance with CNAS-CL01 accreditation criteria for testing Laboratories (identical to ISO/IEC 17025:2017 General Requirements) for the Competence of testing Laboratories.

**Designation Number: CN1227** 

Test Firm Registration Number: 674885

The EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications commission. The acceptance letter from the FCC is maintained in our files.

#### 1.3 MEASUREMENT UNCERTAINTY

Measurement Uncertainty

Conducted Emission Expanded Uncertainty = 2.23dB, k=2 Radiated emission expanded uncertainty(9kHz-30MHz) = 3.08dB, k=2 Radiated emission expanded uncertainty(30MHz-1000MHz) = 4.42dB, k=2 Radiated emission expanded uncertainty(Above 1GHz) = 4.06dB, k=2 Page 5 of 25

Report No.: UNIA2018070613-1FR-01



# 2. GENERAL INFORMATION

# 2.1 GENERAL DESCRIPTION OF EUT

Equipment	Vue
Trade Mark	N/A
Model Name	Classic
Serial No.	Trendy
	All models have the same functionality, software and
Model Difference	electronics, only the color, front frame shape and model
	names may differ. Test sample model: Classic.
FCC ID	2AFKV-V001
Antenna Type	Integral Antenna
Antenna Gain	5.05dBi
Frequency Range	2402-2480MHz
Number of Channels	40CH
Modulation Type	GFSK
Battery	DC 3.7V, 90mAh*2
Dawer Carras	DC 3.7V from Battery or charging case (DC 5V from
Power Source	adapter with AC 120(240)V/60Hz)
	M/N: EQ-24BCN
Adapter Model	Input: AC 100~240V, 50/60Hz, 0.8A
	Output: DC 5V, 3A
_	





2.2 Carrier Frequency of Channels

- 1	Channel List									
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)			
01	2402	11	2422	21	2442	31	2462			
02	2404	12	2424	22	2444	32	2464			
03	2406	13	2426	23	2446	33	2466			
04	2408	14	2428	24	2448	34	2468			
05	2410	15	2430	25	2450	35	2470			
06	2412	16	2432	26	2452	36	2472			
07	2414	17	2434	27	2454	37	2474			
08	2416	18	2436	28	2456	38	2476			
09	2418	19	2438	29	2458	39	2478			
10	2420	20	2440	30	2460	40	2480			

# 2.3 Operation of EUT during testing


**Operating Mode** 

The mode is used: Transmitting mode

Low Channel: 2402MHz Middle Channel: 2440MHz High Channel: 2480MHz

## 2.4 DESCRIPTION OF TEST SETUP

Operation of EUT during Conducted testing:



Operation of EUT during Radiation and Above1GHz Radiation testing:

EUT



# 2.5 MEASUREMENT INSTRUMENTS LIST

Item	Equipment	Manufacturer	Model No.	Serial No.	Calibrated until
1		CONDUCTED	EMISSIONS TEST	-	
1	AMN	Schwarzbeck	NNLK8121	8121370	2018.9.9
2	AMN	ETS	3810/2	00020199	2018.9.9
3	EMI TEST RECEIVER	Rohde&Schwarz	ESCI	101210	2018.9.9
4	AAN	TESEQ	T8-Cat6	38888	2018.9.9
	I, N	RADIATED	EMISSION TEST		
1	Horn Antenna	Sunol	DRH-118	A101415	2018.9.29
2	BicoNILog Antenna	Sunol	JB1 Antenna	A090215	2018.9.29
3	PREAMP	HP	8449B	3008A00160	2018.9.9
4	PREAMP	HP	8447D	2944A07999	2018.9.9
5	EMI TEST RECEIVER	Rohde&Schwarz	ESR3	101891	2018.9.9
6	VECTOR Signal Generator	Rohde&Schwarz	SMU200A	101521	2018.9.28
7	Signal Generator	Agilent	E4421B	MY4335105	2018.9.28
8	MXA Signal Analyzer	Agilent	N9020A	MY50510140	2018.9.28
9	MXA Signal Analyzer	Agilent	N9020A	MY51110104	2018.9.9
10	ANT Tower&Turn table Controller	Champro	EM 1000	60764	2018.9.28
11	Anechoic Chamber	Taihe Maorui	9m*6m*6m	966A0001	2018.9.9
12	Shielding Room	Taihe Maorui	6.4m*4m*3m	643A0001	2018.9.9
13	RF Power sensor	DARE	RPR3006W	15I00041SNO88	2019.3.14
14	RF Power sensor	DARE	RPR3006W	15I00041SNO89	2019.3.14
15	RF power divider	Anritsu	K241B	992289	2018.9.28
16	Wideband radio communication tester	Rohde&Schwarz	CMW500	154987	2018.9.28
17	Biconical antenna	Schwarzbeck	VHA 9103	91032360	2018.9.8
18	Biconical antenna	Schwarzbeck	VHA 9103	91032361	2018.9.8
19	Broadband Hybrid Antennas	Schwarzbeck	VULB9163	VULB9163#958	2018.9.8
20	Horn Antenna	Schwarzbeck	BBHA9120D	9120D-1680	2019.1.12
21	Active Receive Loop Antenna	Schwarzbeck	FMZB 1919B	00023	2018.11.02
22	Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170651	2019.03.14
23	Microwave Broadband Preamplifier	Schwarzbeck	BBV 9721	100472	2018.10.24
24	Active Loop Antenna	Com-Power	AL-130R	10160009	2019.05.10
25	Power Meter	KEYSIGHT	N1911A	MY50520168	2019.05.10



## CONDUCTED EMISSIONS TEST


#### 3.1 Conducted Power Line Emission Limit

For unintentional device, according to § 15.107(a) Line Conducted Emission Limits is as following

Fraguency	Maximum RF Line Voltage(dBμV)						
Frequency	CLA	SS A	CLASS B				
(MHz)	Q.P.	Ave.	Q.P.	Ave.			
0.15~0.50	79	66	66~56*	56~46*			
0.50~5.00	73	60	56	46			
5.00~30.0	73	60	60	50			

<sup>\*</sup> Decreasing linearly with the logarithm of the frequency
For intentional device, according to §15.207(a) Line Conducted Emission Limit is same as above table.

#### 3.2 Test Setup



#### 3.3 Test Procedure


- 1, The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. A wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10
- 2, Support equipment, if needed, was placed as per ANSI C63.10.
- 3, All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
- 4, If a EUT received DC power from the USB Port of Notebook PC, the PC's adapter received AC120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- 5, All support equipments received AC power from a second LISN, if any.
- 6, The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7, Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.

#### 3.4 Test Result

#### **PASS**


#### Remark:

- 1. All modes were tested at AC 120V and 240V, only the worst result of AC 120V was reported.
- 2. All modes of Low, Middle, and High channel were tested, only the worst result of Middle Channel was reported as below:






Temperature:	24°C	Relative Humidity:	51%					
Test Date:	Jul. 20, 2018	Pressure:	1030hPa					
Test Voltage:	AC 120V, 60Hz	AC 120V, 60Hz Phase: Li						
Test Mode:	Transmitting mode of 2440GFSK M	ransmitting mode of 2440GFSK MHz						




	No.	Frequency	QuasiPeak reading	Average reading	Correction factor	QuasiPeak result	Average result	QuasiPeak limit	Average limit	QuasiPeak margin	Average margin	Remark
_		(MHz)	(dBuV)	(dBuV)	(dB)	(dBuV)	(dBuV)	(dBuV)	(dBuV)	(dB)	(dB)	
	1*	0.1700	44.88	30.80	8.90	53.78	39.70	64.96	54.96	-11.18	-15.26	Pass
	2P	0.2300	38.94	23.99	10.05	48.99	34.04	62.45	52.45	-13.46	-18.41	Pass
	3P	1.5380	23.05	10.17	10.15	33.20	20.32	56.00	46.00	-22.80	-25.68	Pass
	4P	4.5300	24.55	10.98	10.11	34.66	21.09	56.00	46.00	-21.34	-24.91	Pass
	5P	13.0500	26.17	10.05	10.20	36.37	20.25	60.00	50.00	-23.63	-29.75	Pass
	6P	21.9860	35.94	27.45	10.51	46.45	37.96	60.00	50.00	-13.55	-12.04	Pass

Remark: Factor = Insertion Loss + Cable Loss, Result=Reading + Factor, Margin=Result - Limit.





Temperature:	24°C	Relative Humidity:	51%				
Test Date:	Jul. 20, 2018	Pressure:	1030hPa				
Test Voltage:	AC 120V, 60Hz	Phase:	Neutral				
Test Mode:	Transmitting mode of GFSK 2440MHz						



No.	Frequency	QuasiPeak reading	Average reading	Correction factor	QuasiPeak result	Average result	QuasiPeak limit	Average limit	QuasiPeak margin	Average margin	Remark
	(MHz)	(dBuV)	(dBuV)	(dB)	(dBuV)	(dBu∀)	(dBuV)	(dBuV)	(dB)	(dB)	
1*	0.1700	44.03	29.92	8.90	52.93	38.82	64.96	54.96	-12.03	-16.14	Pass
2P	0.2300	38.61	21.72	10.05	48.66	31.77	62.45	52.45	-13.79	-20.68	Pass
3P	1.5220	19.36	6.37	10.14	29.50	16.51	56.00	46.00	-26.50	-29.49	Pass
4P	3.9300	18.88	4.51	10.12	29.00	14.63	56.00	46.00	-27.00	-31.37	Pass
5P	13.0420	24.47	10.05	10.20	34.67	20.25	60.00	50.00	-25.33	-29.75	Pass
6P	22.1340	34.22	25.92	10.52	44.74	36.44	60.00	50.00	-15.26	-13.56	Pass

Remark: Factor = Insertion Loss + Cable Loss, Result=Reading + Factor, Margin=Result - Limit.



## **4 RADIATED EMISSION TEST**

## 4.1 Radiation Limit


For unintentional device, according to § 15.109(a), except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency (MHz)	Distance Radiated (Meters) (dBµV/m)		Radiated (µV/m)
30-88	3	40	100
88-216	88-216 3		150
216-960	3	46	200
Above 960	3	54	500


For intentional device, according to § 15.209(a), the general requirement of field strength of radiated emissions from intentional radiators at a distance of 3 meters shall not exceed the above table.

## 4.2 Test Setup

## 1. Radiated Emission Test-Up Frequency Below 30MHz




#### 2. Radiated Emission Test-Up Frequency 30MHz~1GHz





3. Radiated Emission Test-Up Frequency Above 1GHz



## 4.3 Test Procedure

- 1. Below 1GHz measurement the EUT is placed on turntable which is 0.8m above ground plane. And above 1GHz measurement EUT was placed on low permittivity and low tangent turn table which is 1.5m above ground plane.
- 2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
- 3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
- 4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
- 5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- 6. Repeat above procedures until the measurements for all frequencies are complete.
- 7. The test frequency range from 9kHz to 25GHz per FCC PART 15.33(a).

#### Note


For battery operated equipment, the equipment tests shall be performed using a new battery.

#### 4.4 Test Result

## **PASS**

#### Remark:


- 1. All the test modes completed for test. The worst case of Radiated Emission is Middle channel, the test data of this mode was reported.
- 2. By preliminary testing and verifying three axis (X, Y and Z) position of EUT transmitted status, it was found that "Z axis" position was the worst, and test data recorded in this report.
- 3. Radiated emission test from 9KHz to 10th harmonic of fundamental was verified, and no emission found except system noise floor in 9KHz to 30MHz and not recorded in this report.





## Below 1GHz Test Results:

Temperature:	25℃	Relative Humidity:	48%				
Test Date:	Jul. 20, 2018	Pressure:	1030hPa				
Test Voltage:	DC 3.7V from Battery	OC 3.7V from Battery Polarization: Ho					
Test Mode:	Transmitting mode of GFSK 2440M	ransmitting mode of GFSK 2440MHz					




Remark: Absolute Level= Reading Level+ Factor, Margin= Absolute Level – Limit Factor=Ant. Factor + Cable Loss – Pre-amplifier





Temperature:	25℃	Relative Humidity:	48%
Test Date:	Jul. 20, 2018	Pressure:	1030hPa
Test Voltage:	DC 3.7V from Battery	Polarization:	Vertical
Test Mode:	Transmitting mode of GFSK 2440M	1Hz	, Fi



Remark: Absolute Level= Reading Level+ Factor, Margin= Absolute Level – Limit Factor=Ant. Factor + Cable Loss – Pre-amplifier

#### Remark:

- (1) Measuring frequencies from 9 kHz to the 1 GHz, Radiated emission test from 9kHz to 30MHz was verified, and no any emission was found except system noise floor.
- (2) \* denotes emission frequency which appearing within the Restricted Bands specified in provision of 15.205, then the general radiated emission limits in 15.209 apply.
- (3) The IF bandwidth of EMI Test Receiver between 30MHz to 1GHz was 120KHz, 1 MHz for measuring above 1 GHz, below 30MHz was 10KHz.





# Above 1 GHz Test Results: CH Low (2402MHz)

## Horizontal:

Frequency	Reading Result	Factor	Emission Level	Limits	Margin	Detector
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Туре
2402	107.88	-5.84	102.04	114	-11.96	peak
2402	83.51	-5.84	77.67	94	-16.33	AVG
4804	51.62	-3.64	47.98	74	-26.02	peak
4804	42.57	-3.64	38.93	54	-15.07	AVG
7206	50.79	-0.95	49.84	74	-24.16	peak
7206	41.24	-0.95	40.29	54	-13.71	AVG

Remark: Factor = Antenna Factor + Cable Loss - Pre-amplifier. Margin= Absolute Level - Limit

## Vertical:

Frequency	Reading Result	Factor	Emission Level	Limits	Margin	Detector
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Туре
2402	108.01	-5.84	102.17	114	-11.83	peak
2402	83.32	-5.84	77.48	94	-16.52	AVG
4804	52.75	-3.64	49.11	74	-24.89	peak
4804	43.40	-3.64	39.76	54	-14.24	AVG
7206	52.07	-0.95	51.12	74	-22.88	peak
7206	41.96	-0.95	41.01	54	-12.99	AVG

Remark: Factor = Antenna Factor + Cable Loss - Pre-amplifier. Margin= Absolute Level - Limit



# CH Middle (2440MHz)

## Horizontal:

Frequency	Reading Result	Factor	Emission Level	Limits	Margin	Detector
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Туре
2440	109.15	-5.71	103.44	114	-10.56	peak
2440	84.72	-5.71	79.01	94	-14.99	AVG
4880	55.68	-3.51	52.17	74	-21.83	peak
4880	45.41	-3.51	41.9	54	-12.1	AVG
7320	54.26	-0.82	53.44	74	-20.56	peak
7320	42.52	-0.82	41.7	54	-12.3	AVG

Remark: Factor = Antenna Factor + Cable Loss - Pre-amplifier. Margin= Absolute Level - Limit

## Vertical:

Frequency	Reading Result	Factor	Emission Level	Limits	Margin	Detector
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Туре
2440	109.51	-5.71	103.8	114	-10.20	peak
2440	84.88	-5.71	79.17	94	-14.83	AVG
4880	55.79	-3.51	52.28	74	-21.72	peak
4880	45.63	-3.51	42.12	54	-11.88	AVG
7320	54.57	-0.82	53.75	74	-20.25	peak
7320	42.64	-0.82	41.82	54	-12.18	AVG

Remark: Factor = Antenna Factor + Cable Loss - Pre-amplifier. Margin= Absolute Level - Limit



#### Horizontal:

Frequency	Reading Result	Factor	Emission Level	Limits	Margin	Detector
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Туре
2480	108.70	-5.65	103.05	114	-10.95	peak
2480	84.25	-5.65	78.6	94	-15.4	AVG
4960	55.03	-3.43	51.6	74	-22.4	peak
4960	45.21	-3.43	41.78	54	-12.22	AVG
7440	53.97	-0.75	53.22	74	-20.78	peak
7440	42.38	-0.75	41.63	54	-12.37	AVG
Remark: Fact	Remark: Factor = Antenna Factor + Cable Loss – Pre-amplifier. Margin= Absolute Level – Limit					

#### Vertical:

Frequency	Reading Result	Factor	Emission Level	Limits	Margin	Detector
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Туре
2480	108.57	-5.65	102.92	114.00	-11.08	peak
2480	84.83	-5.65	79.18	94.00	-14.82	AVG
4960	55.61	-3.43	52.18	74.00	-21.82	peak
4960	45.89	-3.43	42.46	54.00	-11.54	AVG
7440	54.35	-0.75	53.60	74.00	-20.40	peak
7440	42.91	-0.75	42.16	54.00	-11.84	AVG
	2					

#### Remark

- (1) Measuring frequencies from 1 GHz to the 25 GHz •
- (2) "F" denotes fundamental frequency; "H" denotes spurious frequency. "E" denotes band edge frequency.

Remark: Factor = Antenna Factor + Cable Loss - Pre-amplifier. Margin= Absolute Level - Limit

- (3) \* denotes emission frequency which appearing within the Restricted Bands specified in provision of 15.205, then the general radiated emission limits in 15.209 apply.
- (4) Data of measurement within this frequency range shown "--- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (5) The IF bandwidth of EMI Test Receiver between 30MHz to 1GHz was 120KHz, 1 MHz for measuring above 1 GHz, below 30MHz was 10KHz. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for peak measurement with peak detector at frequency above 1GHz. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 10Hz for Average measurement with peak detection at frequency above 1GHz.
- (6) When the test results of Peak Detected below the limits of Average Detected, the Average Detected is not need completed. For example: Top Channel at Fundamental 73.16dBuV/m(PK Value) <93.98(AV Limit), at harmonic 53.20 dBuV/m(PK Value) <54 dBuV/m(AV Limit), the Average Detected not need to completed.
- (7) All modes of operation were investigated and the worst-case emissions are reported.

Page 18 of 25



#### **5 BAND EDGE**

#### 5.1 Limits

FCC PART 15.249(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

Report No.: UNIA2018070613-1FR-01

#### 5.2 Test Procedure

The band edge compliance of RF radiated emission should be measured by following the guidance in ANSI C63.10 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization etc. Set RBW to 100KHz and VBM to 300KHz to measure the peak field strength and set RBW to 1MHz and VBW to 10Hz to measure the average radiated field strength. The conducted RF band edge was measured by using a spectrum analyzer. Set span wide enough to capture the highest in-band emission and the emission at the band edge. Set RBW to 100 kHz and VBW to 300 kHz, to measure the conducted peak band edge.

5.3 Test Result

**PASS** 





Radiated Band Edge Test:

Operation Mode: TX CH Low (2402MHz)

Horizontal (Worst case):

	,					
Frequency	Reading Result	Factor	Emission Level	Limits	Margin	Detector
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Туре
2310	56.42	-5.81	50.61	74	-23.39	peak
2310	1	-5.81	/	54	/	AVG
2390	54.89	-5.84	49.05	74	-24.95	peak
2390	/	-5.84	1	54	/	AVG
of Barton				•	•	

Remark: Factor = Antenna Factor + Cable Loss - Pre-amplifier.

## Vertical:

Frequency	Reading Result	Factor	Emission Level	Limits	Margin	Detector
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Type
2310	56.73	-5.81	50.92	74	-23.08	peak
2310	/	-5.81	/	54	/	AVG
2390	54.14	-5.84	48.3	74	-25.7	peak
2390	/	-5.84	1	54	/	AVG

Remark: Factor = Antenna Factor + Cable Loss - Pre-amplifier.



Operation Mode: TX CH High (2480MHz)

# Horizontal (Worst case):

Frequency	Reading Result	Factor	Emission Level	Limits	Margin	Detector
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Туре
2483.5	55.83	-5.65	50.18	74	-23.82	peak
2483.5	/	-5.65	/	54	/	AVG
2500	54.52	-5.72	48.8	74	-25.2	peak
2500	1	-5.72	1	54	/	AVG

Remark: Factor = Antenna Factor + Cable Loss - Pre-amplifier.

## Vertical:

Frequency	Reading Result	Factor	Emission Level	Limits	Margin	Detector
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Type
2483.5	56.20	-5.65	50.55	74	-23.45	peak
2483.5	/	-5.65	/	54	/	AVG
2500	54.76	-5.72	49.04	74	-24.96	peak
2500	1	-5.72	12/	54	/	AVG

Remark: Factor = Antenna Factor + Cable Loss - Pre-amplifier.



## 6 OCCUPIED BANDWIDTH MEASUREMENT

#### 6.1 Test Setup

Same as Radiated Emission Measurement

## 6.2 Test Procedure

- 1. The EUT was placed on a turn table which is 0.8m above ground plane.
- 2. Set EUT as normal operation.
- 3. Based on ANSI C63.10 section 6.9.2: RBW=30KHz, VBW=100KHz, Span=3MHz.
- 4. The useful radiated emission from the EUT was detected by the spectrum analyzer with peak detector.

## 6.3 Measurement Equipment Used

Same as Radiated Emission Measurement

#### 6.4 Test Result

## **PASS**

Frequency	20dB Bandwidth (MHz)	Result
2402 MHz	1.079	PASS
2440 MHz	1.072	PASS
2480 MHz	1.070	PASS

## CH: 2402MHz







CH: 2440MHz



## CH: 2480MHz



Page 23 of 25

Report No.: UNIA2018070613-1FR-01




## Standard Applicable:


For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

## Antenna Connected Construction

The antenna used in this product is an Integral Antenna, the directional gains of antenna used for transmitting is 5.05dBi.

## **ANTENNA**







# **8 PHOTOGRAPH OF TEST**

# 8.1 Radiated Emission









## 8.2 Conducted Emission



\*\*\*End of Report\*\*\*