



Shenzhen CTL Testing Technology Co., Ltd.
Tel: +86-755-89486194 E-mail: ctl@ctl-lab.com

TEST REPORT

FCC PART 15.247

Report Reference No.: CTL2001034051-WF01

Compiled by:
(position+printed name+signature)

Happy Guo
(File administrators)

Happy Guo

Tested by:
(position+printed name+signature)

Nice Nong
(Test Engineer)

Nice Nong

Approved by:
(position+printed name+signature)

Ivan Xie
(Manager)

Ivan Xie

Product Name.....: MaaxBoard Mini

Model/Type reference.....: MaaXBoard Mini

List Model(s).....: N/A

Trade Mark.....: N/A

FCC ID.....: 2AFLY-MAAX-MINI

Applicant's name.....: Embest Technology Co., Ltd

Address of applicant.....: TowerB 4/F, Shanshui Building, Nanshan Yungu Innovation
Industry Park, Liuxian Ave.No.1183, Nanshan District, ShenZhen,
China.

Test Firm.....: Shenzhen CTL Testing Technology Co., Ltd.

Address of Test Firm.....: Floor 1-A, Baisha Technology Park, No.3011, ShaheXi Road,
Nanshan District, Shenzhen, China 518055

Test specification.....:

Standard.....: 47 CFR FCC Part 15 Subpart C 15.247

TRF Originator.....: Shenzhen CTL Testing Technology Co., Ltd.

Master TRF.....: Dated 2011-01

Date of receipt of test item.....: Jan. 16, 2020

Date of sampling.....: Jan. 16, 2020

Date of Test Date.....: Jan. 16, 2020-Mar. 24, 2020

Data of Issue.....: Mar. 25, 2020

Result.....: Pass

Shenzhen CTL Testing Technology Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen CTL Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen CTL Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

TEST REPORT

Test Report No. : CTL2001034051-WF01	Mar. 25, 2020 Date of issue
---	--------------------------------

Equipment under Test : MaaxBoard Mini

Model /Type : MaaXBoard Mini

Listed Models : N/A

Applicant : **Embest Technology Co., Ltd**

Address : TowerB 4/F, Shanshui Building, Nanshan Yungu
Innovation Industry Park, Liuxian Ave.No.1183,
Nanshan District, ShenZhen, China.

Manufacturer : **Embest Technology Co., Ltd**

Address : TowerB 4/F, Shanshui Building, Nanshan Yungu
Innovation Industry Park, Liuxian Ave.No.1183,
Nanshan District, ShenZhen, China.

Test result	Pass *
--------------------	---------------

*In the configuration tested, the EUT complied with the standards specified page 5.

The test results presented in this report relate only to the object tested.

This report shall not be reproduced, except in full, without the written approval of the issuing testing laboratory.

**** Modified History ****

[illegible]

Table of Contents**Page**

1. SUMMARY.....	5
1.1. TEST STANDARDS.....	5
1.2. TEST DESCRIPTION.....	5
1.3. TEST FACILITY.....	6
1.4. STATEMENT OF THE MEASUREMENT UNCERTAINTY.....	6
2. GENERAL INFORMATION.....	8
2.1. ENVIRONMENTAL CONDITIONS.....	8
2.2. GENERAL DESCRIPTION OF EUT.....	8
2.3. DESCRIPTION OF TEST MODES AND TEST FREQUENCY.....	8
2.4. EQUIPMENTS USED DURING THE TEST.....	9
2.5. RELATED SUBMITTAL(S) / GRANT (S).....	10
2.6. MODIFICATIONS.....	10
3. TEST CONDITIONS AND RESULTS.....	11
3.1. CONDUCTED EMISSIONS TEST.....	11
3.2. RADIATED EMISSIONS AND BAND EDGE.....	14
3.3. MAXIMUM PEAK OUTPUT POWER.....	21
3.4. 20dB BANDWIDTH.....	22
3.5. FREQUENCY SEPARATION.....	23
3.6. NUMBER OF HOPPING FREQUENCY.....	24
3.7. TIME OF OCCUPANCY (DWELL TIME).....	25
3.8. OUT-OF-BAND EMISSIONS.....	29
3.9. PSEUDORANDOM FREQUENCY HOPPING SEQUENCE.....	30
3.10. ANTENNA REQUIREMENT.....	31
4. TEST SETUP PHOTOS OF THE EUT.....	32
5. PHOTOS OF THE EUT.....	33

1. SUMMARY

1.1. TEST STANDARDS

The tests were performed according to following standards:

[FCC Rules Part 15.247](#): Frequency Hopping, Direct Spread Spectrum and Hybrid Systems that are in operation within the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz

[ANSI C63.10: 2013](#): American National Standard for Testing Unlicensed Wireless Devices

1.2. Test Description

FCC PART 15.247		
FCC Part 15.207	AC Power Conducted Emission	PASS
FCC Part 15.247(a)(1)(i)	20dB Bandwidth & 99% Bandwidth	PASS
FCC Part 15.247(d)	Spurious RF Conducted Emission	PASS
FCC Part 15.247(b)	Maximum Peak Output Power	PASS
FCC Part 15.247(b)	Pseudorandom Frequency Hopping Sequence	PASS
FCC Part 15.247(a)(1)(iii)	Number of hopping frequency& Time of Occupancy	PASS
FCC Part 15.247(a)(1)	Frequency Separation	PASS
FCC Part 15.205/15.209	Radiated Emissions	PASS
FCC Part 15.247(d)	Band Edge Compliance of RF Emission	PASS
FCC Part 15.203/15.247 (b)	Antenna Requirement	PASS

1.3. Test Facility

1.3.1 Address of the test laboratory

Shenzhen CTL Testing Technology Co., Ltd.

Floor 1-A, Baisha Technology Park, No. 3011, Shahexi Road, Nanshan, Shenzhen 518055 China

There is one 3m semi-anechoic chamber and two line conducted labs for final test. The Test Sites meet the requirements in documents ANSI C63.4 and CISPR 32/EN 55032 requirements.

1.3.2 Laboratory accreditation

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L7497

Shenzhen CTL Testing Technology Co., Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2005 General Requirements) for the Competence of Testing and Calibration Laboratories.

A2LA-Lab Cert. No. 4343.01

Shenzhen CTL Testing Technology Co., Ltd, EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

IC Registration No.: 9618B

CAB identifier: CN0041

The 3m alternate test site of Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements with Registration No.: 9618B on Jan. 22, 2019.

FCC-Registration No.: 399832

Designation No.: CN1216

Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 399832, December 08, 2017.

1.4. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 "Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements" and is documented in the Shenzhen CTL Testing Technology Co., Ltd. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for CTL laboratory is reported:

Test	Measurement Uncertainty	Notes
Transmitter power conducted	±0.57 dB	(1)
Transmitter power Radiated	±2.20 dB	(1)
Conducted spurious emission 9KHz-40 GHz	±2.20 dB	(1)
Occupied Bandwidth	±0.01ppm	(1)
Radiated Emission 30~1000MHz	±4.10dB	(1)
Radiated Emission Above 1GHz	±4.32dB	(1)

Conducted Disturbance0.15~30MHz	$\pm 3.20\text{dB}$	(1)
---------------------------------	---------------------	-----

- (1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

2. GENERAL INFORMATION

2.1. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Normal Temperature:	25°C
Relative Humidity:	55 %
Air Pressure:	101 kPa

2.2. General Description of EUT

Product Name:	MaaxBoard Mini
Model/Type reference:	MaaXBoard Mini
Power supply:	DC 5.0V
Bluetooth :	
Supported type:	Bluetooth BR/EDR
Modulation:	GFSK, $\pi/4$ DQPSK, 8DPSK
Operation frequency:	2402MHz~2480MHz
Channel number:	79
Channel separation:	1MHz
Antenna type:	Ceramics Antenna
Antenna gain:	1dBi

Note: For more details, please refer to the user's manual of the EUT.

2.3. Description of Test Modes and Test Frequency

The Applicant provides communication tools software to control the EUT for staying in continuous transmitting (Duty Cycle more than 98%) and receiving mode for testing .There are 79 channels provided to the EUT and Channel 00/39/78 were selected to test.

Operation Frequency :

Channel	Frequency (MHz)
00	2402
01	2403
:	:
38	2440
39	2441
40	2442
:	:
77	2479
78	2480

Preliminary tests were performed in each mode and packet length of BT, and found worst case as below, finally test were conducted at those mode and recorded in this report.

Test Items	Worst case
Conducted Emissions	DH5 Middle channel
Radiated Emissions and Band Edge	DH5
Maximum Conducted Output Power	DH5/2DH5/3DH5
20dB Bandwidth	DH5/2DH5/3DH5
Frequency Separation	DH5/2DH5/3DH5 Middle channel
Number of hopping frequency	DH5/2DH5/3DH5
Time of Occupancy (Dwell Time)	DH1/DH3/DH5 Middle channel 2DH1/2DH3/2DH5 Middle channel 3DH1/3DH3/3DH5 Middle channel
Out-of-band Emissions	DH5/2DH5/3DH5

2.4. Equipments Used during the Test

Test Equipment	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Due Date
LISN	R&S	ESH2-Z5	860014/010	2019/05/21	2020/05/20
Double cone logarithmic antenna	Schwarzbeck	VULB 9168	824	2019/05/23	2020/05/22
Horn Antenna	Ocean Microwave	OBH100400	26999002	2019/11/28	2020/11/27
EMI Test Receiver	R&S	ESCI	1166.5950.03	2019/05/21	2020/05/20
Spectrum Analyzer	Agilent	E4407B	MY41440676	2019/05/20	2020/05/19
Spectrum Analyzer	Agilent	N9020A	US46220290	2019/05/20	2020/05/19
Spectrum Analyzer	Keysight	N9020A	MY53420874	2019/05/20	2020/05/19
Controller	EM Electronics	EM 1000	060859	2019/05/21	2020/05/20
Horn Antenna	Sunol Sciences Corp.	DRH-118	A062013	2019/05/23	2020/05/22
Active Loop Antenna	Da Ze	ZN30900A	/	2019/05/23	2020/05/22
Amplifier	Agilent	8449B	3008A02306	2019/05/21	2020/05/20
Amplifier	Agilent	8447D	2944A10176	2019/05/21	2020/05/20
Amplifier	Brief&Smart	LNA-4018	2104197	2019/05/20	2020/05/19
Temperature/Humidity Meter	Gangxing	CTH-608	02	2019/05/22	2020/05/21
Power Sensor	Agilent	U2021XA	MY55130004	2019/05/20	2020/05/19
Power Sensor	Agilent	U2021XA	MY55130006	2019/05/20	2020/05/19
Power Sensor	Agilent	U2021XA	MY54510008	2019/05/20	2020/05/19
Power Sensor	Agilent	U2021XA	MY55060003	2019/05/20	2020/05/19
Spectrum Analyzer	RS	FSP	1164.4391.38	2019/05/20	2020/05/19

Test Software	
Name of Software	Version
TST-PASS:	1.0.2
ES-K1(Below 1GHz):	V1.71
e3(Above 1GHz):	6.111221a

The calibration interval was one year

2.5. Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended to comply with Section 15.247 of the FCC Part 15, Subpart C Rules.

2.6. Modifications

No modifications were implemented to meet testing criteria.

3. TEST CONDITIONS AND RESULTS

3.1. Conducted Emissions Test


LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.207

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

TEST CONFIGURATION



TEST PROCEDURE


1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system; a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10:2013.
2. Support equipment, if needed, was placed as per ANSI C63.10:2013.
3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10:2013.
4. The adapter received AC120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
5. All support equipments received AC power from a second LISN, if any.
6. The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
7. Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
8. During the above scans, the emissions were maximized by cable manipulation.

TEST RESULTS

Remark: All modes of GFSK, Pi/4 DQPSK, and 8DPSK were test at Low, Middle, and High channel; only the worst result of GFSK Middle Channel was reported as below:

SCAN TABLE: "Voltage (9K-30M)FIN"

Short Description: 150K-30M Voltage

**MEASUREMENT RESULT: "CTL200312602_fin"**

2020-3-12 16:18

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.168000	48.50	11.2	65	16.6	QP	L1	GND
0.474000	33.10	11.2	56	23.3	QP	L1	GND
17.335500	33.20	11.1	60	26.8	QP	L1	GND
17.556000	32.70	11.1	60	27.3	QP	L1	GND
18.015000	33.90	11.1	60	26.1	QP	L1	GND


MEASUREMENT RESULT: "CTL200312602_fin2"

2020-3-12 16:18

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.163500	36.50	11.2	55	18.8	AV	L1	GND
0.217500	28.50	11.2	53	24.4	AV	L1	GND
0.433500	23.90	11.2	47	23.3	AV	L1	GND
17.277000	22.00	11.1	50	28.0	AV	L1	GND
18.208500	24.20	11.2	50	25.8	AV	L1	GND
18.280500	24.40	11.2	50	25.6	AV	L1	GND

SCAN TABLE: "Voltage (9K-30M)FIN"

Short Description: 150K-30M Voltage

**MEASUREMENT RESULT: "CTL200312601_fin"**

2020-3-12 16:15

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.163500	48.50	11.2	65	16.8	QP	N	GND
0.213000	41.90	11.2	63	21.2	QP	N	GND
0.478500	36.60	11.2	56	19.8	QP	N	GND
1.306500	33.50	11.2	56	22.5	QP	N	GND
16.570500	33.50	11.1	60	26.5	QP	N	GND
16.593000	33.40	11.1	60	26.6	QP	N	GND

MEASUREMENT RESULT: "CTL200312601_fin2"

2020-3-12 16:15

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.159000	37.10	11.2	56	18.4	AV	N	GND
0.384000	27.10	11.2	48	21.1	AV	N	GND
0.483000	25.80	11.2	46	20.5	AV	N	GND
0.640500	21.20	11.2	46	24.8	AV	N	GND
1.095000	22.80	11.2	46	23.2	AV	N	GND
1.315500	23.00	11.2	46	23.0	AV	N	GND

3.2. Radiated Emissions and Band Edge

Limit

For intentional device, according to § 15.209(a), the general requirement of field strength of radiated emission out of authorized band shall not exceed the following table at a 3 meters measurement distance.


In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a)

Radiated emission limits


Frequency (MHz)	Distance (Meters)	Radiated (dB μ V/m)	Radiated (μ V/m)
0.009-0.49	3	$20\log(2400/F(\text{KHz}))+40\log(300/3)$	$2400/F(\text{KHz})$
0.49-1.705	3	$20\log(24000/F(\text{KHz}))+40\log(30/3)$	$24000/F(\text{KHz})$
1.705-30	3	$20\log(30)+40\log(30/3)$	30
30-88	3	40.0	100
88-216	3	43.5	150
216-960	3	46.0	200
Above 960	3	54.0	500

TEST CONFIGURATION


(A) Radiated Emission Test Set-Up, Frequency Below 30MHz



(B) Radiated Emission Test Set-Up, Frequency below 1000MHz



(C) Radiated Emission Test Set-Up, Frequency above 1000MHz



Test Procedure


1. Below 1GHz measurement the EUT is placed on a turntable which is 0.8m above ground plane, and above 1GHz measurement EUT was placed on a low permittivity and low loss tangent turn table which is 1.5m above ground plane.
2. Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0° to 360° to acquire the highest emissions from EUT
3. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
4. Repeat above procedures until all frequency measurements have been completed.

TEST RESULTS

Remark:

1. We measured Radiated Emission at GFSK, $\pi/4$ DQPSK and 8DPSK mode from 9 KHz to 25GHz and recorded worst case at GFSK DH5 mode.
2. For below 1GHz testing recorded worst at GFSK DH5 low channel.
3. Radiated emission test from 9 KHz to 10th harmonic of fundamental was verified, and no emission found except system noise floor in 9 KHz to 30MHz and not recorded in this report.

For 30MHz-1GHz



For 1GHz to 25GHz

Note: GFSK, Pi/4 DQPSK and 8DPSK all have been tested, only worse case GFSK is reported.

GFSK (above 1GHz)

Frequency(MHz):			2402		Polarity:			HORIZONTAL	
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4804.00	55.09	PK	74	18.91	50.58	33.49	6.91	35.89	4.51
4804.00	50.12	AV	54	3.88	45.61	33.49	6.91	35.89	4.51
5039.75	46.34	PK	74	27.66	39.48	34.06	7.04	34.24	6.86
5039.75	--	AV	54	--	--	--	--	--	--
7206.00	49.21	PK	74	24.79	38.11	36.95	9.18	35.03	11.10
7206.00	--	AV	54	--	--	--	--	--	--

Frequency(MHz):			2402		Polarity:			VERTICAL	
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4804.00	54.62	PK	74	19.38	50.11	33.49	6.91	35.89	4.51
4804.00	50.06	AV	54	3.94	45.55	33.49	6.91	35.89	4.51
5039.75	46.11	PK	74	27.89	39.25	34.06	7.04	34.24	6.86
5039.75	--	AV	54	--	--	--	--	--	--
7206.00	49.12	PK	74	24.88	38.02	36.95	9.18	35.03	11.10
7206.00	--	AV	54	--	--	--	--	--	--

Frequency(MHz):			2441		Polarity:			HORIZONTAL	
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4882.00	54.31	PK	74	19.69	47.95	33.60	6.95	34.19	6.36
4882.00	50.38	AV	54	3.62	44.02	33.60	6.95	34.19	6.36
5145.05	46.41	PK	74	27.59	38.81	34.56	7.15	34.11	7.60
5145.05	--	AV	54	--	--	--	--	--	--
7323.00	49.03	PK	74	24.97	37.33	37.46	9.23	35.00	11.70
7323.00	--	AV	54	--	--	--	--	--	--

Frequency(MHz):			2441		Polarity:			VERTICAL	
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4882.00	54.21	PK	74	19.79	47.85	33.60	6.95	34.19	6.36
4882.00	50.05	AV	54	3.95	43.69	33.60	6.95	34.19	6.36
5145.05	46.24	PK	74	27.76	38.64	34.56	7.15	34.11	7.60
5145.05	--	AV	54	--	--	--	--	--	--
7323.00	48.92	PK	74	25.08	37.22	37.46	9.23	35.00	11.70
7323.00	--	AV	54	--	--	--	--	--	--

Frequency(MHz):			2480		Polarity:			HORIZONTAL	
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4960.00	54.02	PK	74	19.98	49.1	33.84	7.00	35.92	4.92
4960.00	50.14	AV	54	3.86	45.22	33.84	7.00	35.92	4.92
5225.75	46.38	PK	74	27.62	39.1	34.45	7.12	34.29	7.28
5225.75	--	AV	54	--	--	--	--	--	--
7440.00	49.21	PK	74	24.79	37.26	37.64	9.28	34.97	11.95
7440.00	--	AV	54	--	--	--	--	--	--

Frequency(MHz):			2480		Polarity:			VERTICAL	
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
4960.00	54.09	PK	74	19.91	49.17	33.84	7.00	35.92	4.92
4960.00	49.86	AV	54	4.14	44.94	33.84	7.00	35.92	4.92
5225.75	46.35	PK	74	27.65	39.07	34.45	7.12	34.29	7.28
5225.75	--	AV	54	--	--	--	--	--	--
7440.00	49.08	PK	74	24.92	37.13	37.64	9.28	34.97	11.95
7440.00	--	AV	54	--	--	--	--	--	--

REMARKS:

1. Emission level (dBuV/m) =Raw Value (dBuV)+Correction Factor (dB/m)
2. Correction Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
3. Margin value = Limit value- Emission level.
4. -- Mean the PK detector measured value is below average limit.
5. The other emission levels were very low against the limit.
6. RBW1MHz VBW3MHz Peak detector is for PK value; RBW 1MHz VBW10Hz Peak detector is for AV value.

Results of Band Edges Test (Radiated)

Note: GFSK, Pi/4 DQPSK and 8DPSK all have been tested, only worse case GFSK is reported.

Frequency(MHz):			2402		Polarity:			HORIZONTAL	
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2402.00	99.25	PK	—	—	65.86	28.78	4.61	0	33.39
2402.00	92.57	AV	—	—	59.18	28.78	4.61	0	33.39
2341.15	43.47	PK	74	30.53	10.39	28.52	4.56	0	33.08
2341.15	—	AV	54	—	—	—	—	—	—
2390.00	49.31	PK	74	24.69	15.99	28.72	4.60	0	33.32
2390.00	—	AV	54	—	—	—	—	—	—
2400.00	50.12	PK	74	23.88	16.73	28.78	4.61	0	33.39
2400.00	—	AV	54	—	—	—	—	—	—

Frequency(MHz):			2402		Polarity:			VERTICAL	
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2402.00	98.72	PK	—	—	65.33	28.78	4.61	0	33.39
2402.00	90.24	AV	—	—	56.85	28.78	4.61	0	33.39
2341.15	46.21	PK	74	27.79	13.13	28.52	4.56	0	33.08
2341.15	—	AV	54	—	—	—	—	—	—
2390.00	48.47	PK	74	25.53	15.15	28.72	4.60	0	33.32
2390.00	—	AV	54	—	—	—	—	—	—
2400.00	49.52	PK	74	24.48	16.13	28.78	4.61	0	33.39
2400.00	—	AV	54	—	—	—	—	—	—

Frequency(MHz):			2480		Polarity:			HORIZONTAL	
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2480.00	99.52	PK	—	—	65.9	28.92	4.70	0.00	33.62
2480.00	92.61	AV	—	—	58.99	28.92	4.70	0.00	33.62
2483.50	49.48	PK	74	24.52	15.85	28.93	4.70	0.00	33.63
2483.50	—	AV	54	—	—	—	—	—	—
2490.75	48.31	PK	74	25.69	14.65	28.95	4.71	0.00	33.66
2490.75	—	AV	54	—	—	—	—	—	—
2500.00	43.76	PK	74	30.24	10.08	28.96	4.72	0.00	33.68
2500.00	—	AV	54	—	—	—	—	—	—

Frequency(MHz):			2480		Polarity:			VERTICAL	
Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
2480.00	98.61	PK	—	—	64.99	28.92	4.70	0.00	33.62
2480.00	91.24	AV	—	—	57.62	28.92	4.70	0.00	33.62
2483.50	49.41	PK	74	24.59	15.78	28.93	4.70	0.00	33.63
2483.50	—	AV	54	—	—	—	—	—	—
2490.75	48.14	PK	74	25.86	14.48	28.95	4.71	0.00	33.66
2490.75	—	AV	54	—	—	—	—	—	—
2500.00	43.51	PK	74	30.49	9.83	28.96	4.72	0.00	33.68
2500.00	—	AV	54	—	—	—	—	—	—

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m)
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) - Pre-amplifier Factor
3. Margin value = Limit value - Emission level.
4. -- Mean the PK detector measured value is below average limit.
5. The other emission levels were very low against the limit.
6. RBW 1MHz VBW 3MHz Peak detector is for PK value; RBW 1MHz VBW 10Hz Peak detector is for AV value.
7. For fundamental frequency, RBW 3MHz VBW 3MHz Peak detector is for PK Value; RMS detector is for AV value.

3.3. Maximum Peak Output Power

Limit

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels: 1 watt.

For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

Test Procedure

Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum.

Test Configuration



Test Results

See Appendix 2.

3.4. 20dB Bandwidth

Limit

For frequency hopping systems operating in the 2400MHz-2483.5MHz no limit for 20dB bandwidth.

Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 30 KHz RBW and 100 KHz VBW.

The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

Test Configuration



Test Results

See Appendix 1.

3.5. Frequency Separation

LIMIT

According to 15.247(a)(1), frequency hopping systems shall have hopping channel carrier frequencies separated by minimum of 25KHz or the $2/3 \times 20\text{dB}$ bandwidth of the hopping channel, whichever is greater.

TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100 KHz RBW and 300 KHz VBW.

TEST CONFIGURATION



TEST RESULTS

See Appendix 3.

3.6. Number of hopping frequency

Limit

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels.

Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator. Set spectrum analyzer start 2400MHz to 2483.5MHz with 100 KHz RBW and 300 KHz VBW.

Test Configuration



Test Results

See Appendix 4.

3.7. Time of Occupancy (Dwell Time)

Limit

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator. Set center frequency of spectrum analyzer=operating frequency with 1MHz RBW and 1MHz VBW, Span 0Hz.

Test Configuration



Test Results


Modulation	Packet	Pulse time (ms)	Dwell time (s)	Limit (s)	Result
GFSK	DH1	0.375	0.120	0.40	Pass
	DH3	1.631	0.261		
	DH5	2.881	0.307		
π/4DQPSK	2-DH1	0.385	0.123	0.40	Pass
	2-DH3	1.633	0.261		
	2-DH5	2.863	0.305		
8DPSK	3-DH1	0.383	0.123	0.40	Pass
	3-DH3	1.583	0.253		
	3-DH5	2.873	0.306		

Note:


- We have tested all mode at high,middle and low channel,and recoreded worst case at middle channel.
- $\text{Dwell time} = \text{Pulse time (ms)} \times (1600 \div 2 \div 79) \times 31.6$ Second for DH1, 2-DH1, 3-DH1
 $\text{Dwell time} = \text{Pulse time (ms)} \times (1600 \div 4 \div 79) \times 31.6$ Second for DH3, 2-DH3, 3-DH3
 $\text{Dwell time} = \text{Pulse time (ms)} \times (1600 \div 6 \div 79) \times 31.6$ Second for DH5, 2-DH5, 3-DH5

Test plot as follows:


GFSK Modulation




DH1




DH3




DH5

$\pi/4$ DQPSK Modulation

2-DH1




2-DH3




2-DH5


8DPSK Modulation



3-DH1



3-DH3



3-DH5

3.8. Out-of-band Emissions

Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required.

Test Procedure

Connect the transmitter output to spectrum analyzer using a low loss RF cable, and set the spectrum analyzer to RBW=100 kHz, VBW= 300 kHz, peak detector, and max hold. Measurements utilizing these settings are made of the in-band reference level, band edge and out-of-band emissions.

Test Configuration



Test Results

See Appendix 5.

3.9. Pseudorandom Frequency Hopping Sequence

TEST APPLICABLE


For 47 CFR Part 15C section 15.247 (a) (1) requirement:

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hop-ping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hop-ping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

EUT Pseudorandom Frequency Hopping Sequence Requirement


The pseudorandom frequency hopping sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first one of 9 consecutive ones, for example: the shift register is initialized with nine ones.

- Number of shift register stages:9
- Length of pseudo-random sequence:29-1=511 bits
- Longest sequence of zeros:8(non-inverted signal)



Linear Feedback Shift Register for Generation of the PRBS sequence

An example of pseudorandom frequency hopping sequence as follows:



Each frequency used equally one the average by each transmitter.

The system receiver have input bandwidths that match the hopping channel bandwidths of their corresponding transmitter and shift frequencies in synchronization with the transmitted signals.

3.10. Antenna Requirement

Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.


And according to FCC 47 CFR Section 15.247 (c), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

Refer to statement below for compliance

The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.



Antenna Connected Construction

The maximum gain of antenna was 1dBi.









Antenna

4. Test Setup Photos of the EUT



5. Photos of the EUT





***** End of Report *****

Appendix for 15.247

TABLE OF CONTENTS

Appendix for 15.247.....	1
TABLE OF CONTENTS.....	1
1. Bandwidth.....	2
1.1 Test Result.....	2
1.2 Test Graph - 20dB Bandwidth.....	2
1.3 Test Graph - 99% Occupied Bandwidth.....	5
2. Maximum Conducted Output Power.....	8
2.1 Test Result.....	8
2.2 Test Graph.....	8
3. Carrier frequency separation.....	11
3.1 Test Result.....	11
3.2 Test Graph.....	12
4. Number of hopping frequencies.....	13
4.1 Test Result.....	13
4.2 Test Graph.....	13
5. Unwanted Emissions in Non-restricted Frequency Bands.....	14
5.1 Test Result.....	14
5.2 Test Graph.....	14


1. Bandwidth

1.1 Test Result


Test Mode	Frequency (MHz)	TX Type	ANT No.	20dB Bandwidth	Verdict
				Test Result (MHz)	
GFSK	2402	SISO	1	0.944	PASS
	2441	SISO	1	0.950	PASS
	2480	SISO	1	0.946	PASS
Pi/4DQPSK	2402	SISO	1	1.346	PASS
	2441	SISO	1	1.347	PASS
	2480	SISO	1	1.347	PASS
8DPSK	2402	SISO	1	1.313	PASS
	2441	SISO	1	1.317	PASS
	2480	SISO	1	1.321	PASS

Test Mode	Frequency (MHz)	TX Type	ANT No.	99% Occupied Bandwidth	
				Test Result (MHz)	
GFSK	2402	SISO	1	0.887	Only for Report Use
	2441	SISO	1	0.888	Only for Report Use
	2480	SISO	1	0.885	Only for Report Use
Pi/4DQPSK	2402	SISO	1	1.241	Only for Report Use
	2441	SISO	1	1.239	Only for Report Use
	2480	SISO	1	1.234	Only for Report Use
8DPSK	2402	SISO	1	1.233	Only for Report Use
	2441	SISO	1	1.230	Only for Report Use
	2480	SISO	1	1.227	Only for Report Use


1.2 Test Graph - 20dB Bandwidth




GFSK_2441MHz_DH5_SISO_ANT1




GFSK_2480MHz_DH5_SISO_ANT1




Pi/4DQPSK_2402MHz_2DH5_SISO_ANT1




Pi/4DQPSK_2441MHz_2DH5_SISO_ANT1




Pi/4DQPSK_2480MHz_2DH5_SISO_ANT1



8DPSK_2402MHz_3DH5_SISO_ANT1



8DPSK_2441MHz_3DH5_SISO_ANT1




8DPSK_2480MHz_3DH5_SISO_ANT1




1.3 Test Graph - 99% Occupied Bandwidth


GFSK_2402MHz_DH5_SISO_ANT1




GFSK_2441MHz_DH5_SISO_ANT1




GFSK_2480MHz_DH5_SISO_ANT1




Pi/4DQPSK_2402MHz_2DH5_SISO_ANT1




Pi/4DQPSK_2441MHz_2DH5_SISO_ANT1




Pi/4DQPSK_2480MHz_2DH5_SISO_ANT1




8DPSK_2402MHz_3DH5_SISO_ANT1



8DPSK_2441MHz_3DH5_SISO_ANT1



8DPSK_2480MHz_3DH5_SISO_ANT1




2. Maximum Conducted Output Power

2.1 Test Result


Test Mode	Frequency (MHz)	Tx Type	Measured Peak Output Power (dBm)	Limits (dBm)	Verdict
			Ant 1		
GFSK	2402	SISO	4.86	30	recalc
	2441	SISO	3.88	30	recalc
	2480	SISO	2.70	30	recalc
Pi/4DQPSK	2402	SISO	5.64	20.97	PASS
	2441	SISO	4.42	20.97	PASS
	2480	SISO	3.61	20.97	PASS
8DPSK	2402	SISO	5.93	20.97	PASS
	2441	SISO	4.73	20.97	PASS
	2480	SISO	3.96	20.97	PASS

2.2 Test Graph


GFSK_2402MHz_DH5_SISO_ANT1




GFSK_2441MHz_DH5_SISO_ANT1




GFSK_2480MHz_DH5_SISO_ANT1




Pi/4DQPSK_2402MHz_2DH5_SISO_ANT1




Pi/4DQPSK_2441MHz_2DH5_SISO_ANT1




Pi/4DQPSK_2480MHz_2DH5_SISO_ANT1




8DPSK_2402MHz_3DH5_SISO_ANT1



8DPSK_2441MHz_3DH5_SISO_ANT1



8DPSK_2480MHz_3DH5_SISO_ANT1




3. Carrier frequency separation


3.1 Test Result

Test Mode	TX Type	ANT No.	Channel Separation (MHz)	20dB Bandwidth (MHz)	Limits (MHz)	Verdict
GFSK	SISO	1	0.993	0.950	≥ 0.950	PASS
Pi/4DQPSK	SISO	1	0.990	1.347	≥ 0.898	PASS
8DPSK	SISO	1	1.002	1.321	≥ 0.881	PASS

3.2 Test Graph



8DPSK_Hopping_3DH5_SISO_ANT1




4. Number of hopping frequencies

4.1 Test Result


Test Mode	TX Type	ANT No.	Num of Hopping Frequencies	Limits	Verdict
GFSK	SISO	1	83	≥ 15	PASS
Pi/4DQPSK	SISO	1	35	≥ 15	PASS
8DPSK	SISO	1	79	≥ 15	PASS

4.2 Test Graph


GFSK_Hopping_DH5_SISO_ANT1



Pi/4DQPSK_Hopping_2DH5_SISO_ANT1



8DPSK_Hopping_3DH5_SISO_ANT1




5. Unwanted Emissions in Non-restricted Frequency Bands

5.1 Test Result


Test Mode	Frequency (MHz)	TX Type	ANT No.	Spurious Conducted Emission (dBm)	Limits (dBm)	Verdict
GFSK	2402	SISO	1	Refer to test graph	-15.21	recalc
	2441	SISO	1	Refer to test graph	-15.21	recalc
	2480	SISO	1	Refer to test graph	-15.21	recalc
	Hopping	SISO	1	Refer to test graph	-15.21	PASS
Pi/4DQPSK	2402	SISO	1	Refer to test graph	-16.60	PASS
	2441	SISO	1	Refer to test graph	-16.60	PASS
	2480	SISO	1	Refer to test graph	-16.60	PASS
	Hopping	SISO	1	Refer to test graph	-16.60	PASS
8DPSK	2402	SISO	1	Refer to test graph	-16.65	PASS
	2441	SISO	1	Refer to test graph	-16.65	PASS
	2480	SISO	1	Refer to test graph	-16.65	PASS
	Hopping	SISO	1	Refer to test graph	-16.65	PASS

5.2 Test Graph


GFSK_DH5_SISO_ANT1_REF




GFSK_2402MHz_DH5_SISO_ANT1




GFSK_2402MHz_DH5_SISO_ANT1




GFSK_2441MHz_DH5_SISO_ANT1




GFSK_2480MHz_DH5_SISO_ANT1




GFSK_2480MHz_DH5_SISO_ANT1




GFSK_Hopping_DH5_SISO_ANT1




GFSK_Hopping_DH5_SISO_ANT1




PI/4DQPSK_2DH5_SISO_ANT1_REF




Pi/4DQPSK_2402MHz_2DH5_SISO_ANT1




Pi/4DQPSK_2402MHz_2DH5_SISO_ANT1




Pi/4DQPSK_2441MHz_2DH5_SISO_ANT1




Pi/4DQPSK_2480MHz_2DH5_SISO_ANT1




Pi/4DQPSK_2480MHz_2DH5_SISO_ANT1




Pi/4DQPSK_Hopping_2DH5_SISO_ANT1




Pi/4DQPSK_Hopping_2DH5_SISO_ANT1




8DPSK_3DH5_SISO_ANT1_REF




8DPSK_2402MHz_3DH5_SISO_ANT1




8DPSK_2402MHz_3DH5_SISO_ANT1




8DPSK_2441MHz_3DH5_SISO_ANT1




8DPSK_2480MHz_3DH5_SISO_ANT1



8DPSK_2480MHz_3DH5_SISO_ANT1



8DPSK_Hopping_3DH5_SISO_ANT1



8DPSK_Hopping_3DH5_SISO_ANT1

