

INTERTEK TESTING SERVICES

RF Exposure

The equipment under test (EUT) is a ACTIVITY TRACKER II with Bluetooth function. The EUT was powered by a Li-ion rechargeable battery which is charged by USB Power Adapter with AC 120V, 60Hz. For more detail information pls. refer to the user manual.

Bluetooth Version: 4.0 (single mode) Low Energy Standard

Modulation Type: GFSK

Antenna Type: Integral antenna.

Antenna Gain: 0.0dBi.

The nominal conducted output power specified: -3.0dBm +/-1dB.

The nominal radiated output power (e.i.r.p) specified: -3.0dBm (+/- 1dB)

According to the KDB 447498:

The maximum peak radiated emission for the EUT is 92.7dB μ V/m at 3m in the frequency 2402MHz

The EIRP = [(FS*D) ^2 / 30] mW = -2.5dBm
which is within the production variation.

The minimum peak radiated emission for the EUT is 91.6dB μ V/m at 3m in the frequency 2480MHz

The EIRP = [(FS*D) ^2 / 30] mW = -3.6dBm
which is within the production variation.

The maximum conducted output power specified is -2.0dBm = 0.63mW

The source- based time-averaging conducted output power

= 0.63 * Duty Cycle mW (where Duty Cycle \leq 1)

= 0.63 mW

The SAR Exclusion Threshold Level:

= 3.0 * (min. test separation distance, mm) / sqrt(freq. in GHz)

= 3.0 * 5 / sqrt (2.480) mW

= 9.5 mW

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.