



# TEST REPORT

**FCC ID: 2AFNIG710**

Applicant :

BU TECHNOLOGY SAS

Address :

Calle 16# 5-56 centro comercial el diamante 2 local 201 cali Colombia

**Equipment under Test (EUT):**

Name : Tablet PC

Model : G710

**Standards**

: FCC PART 15, SUBPART C: 2014 (Section 15.247)  
ANSI C63.4:2014; ANSI C63.10:2013

**Report No** : T1850961 04

**Date of Test** : July28- August 20, 2015

**Date of Issue** : August 21, 2015

**Test Result** : PASS

<b>Test Result :</b>	PASS *
----------------------	--------

\* In the configuration tested, the EUT complied with the standards specified above  
Authorized Signature

A handwritten signature in black ink, appearing to read "Mark Zhu".

(Mark Zhu)  
Manager

The manufacturer should ensure that all the products in series production are in conformity with the product sample detailed in this report. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of Shenzhen Alpha Product Testing Co., Ltd. Or test done by Shenzhen Alpha Product Testing Co., Ltd. Approvals in connection with, distribution or use of the product described in this report must be approved by Shenzhen Alpha Product Testing Co., Ltd. Approvals in writing.

## TABLE OF CONTENT

<b>Description</b>	<b>Page</b>
<b>1 General Information</b>	<b>4</b>
1.1 Description of Device (EUT)	4
1.2 Description of Test Facility	5
<b>2 EMC Equipment List</b>	<b>6</b>
<b>3 Test Procedure</b>	<b>7</b>
<b>4 Summary of Measurement</b>	<b>8</b>
4.1 Summary of test result	8
4.2 Test connection	8
4.3 Assistant equipment used for test	9
4.4 Test mode	9
4.5 Test Conditions	9
4.6 Measurement Uncertainty (95% confidence levels, k=2)	9
<b>5 Spurious Emission</b>	<b>10</b>
5.1 Radiation Emission	10
5.1.1 Radiation Emission Limits(15.209)	10
5.1.2 Test Setup	10
5.1.3 Test Procedure	12
5.1.4 Test Equipment Setting For emission test Result	12
5.1.5 Test Condition	13
5.1.6 Test Result	13
<b>6 POWER LINE CONDUCTED EMISSION</b>	<b>19</b>
6.1 Conducted Emission Limits(15.207)	19
6.2 Test Setup	19
6.3 Test Procedure	20
6.4 Test Results	20
<b>7 Conducted Maximum Output Power</b>	<b>23</b>
7.1 Test limit	23
7.2 Test Procedure	23
7.3 Test Setup	23
7.4 Test Results	23
<b>8 PEAK POWER SPECTRAL DENSITY</b>	<b>24</b>
8.1 Test limit	24
8.2 Method of measurement	24
8.3 Test Setup	24
8.4 Test Results	25
<b>9 Bandwidth</b>	<b>28</b>
9.1 Test limit	28
9.2 Method of measurement	28
9.3 Test Setup	28
9.4 Test Results	28
<b>10 Band Edge Check</b>	<b>31</b>
10.1 Test limit	31
10.2 Test Procedure	31
10.3 Test Setup	31
10.4 Test Result	31
<b>11 Antenna Requirement</b>	<b>35</b>

11.1	Standard Requirement-----	35
11.2	Result-----	35
<b>12</b>	<b>Test setup photos-----</b>	<b>36</b>
<b>13</b>	<b>Photos of EUT-----</b>	<b>36</b>

# 1 General Information

## 1.1 Description of Device (EUT)

Trade Name : 

EUT : TABLET PC

Model No. G710

DIFF : N/A

Antenna Type : Integrated Antenna, Maximum Gain is 0dBi for WLAN

Operation Frequency : 2402-2480MHz

Channel number : 40 Channels

Modulation type : GFSK

Power Supply : DC 3.7V Supply by battery

Adapter Manufacturer: NIL  
Model No.:XJX-001-13

Applicant : BU TECHNOLOGY SAS

Address : Calle 16# 5-56 centro comercial el diamante 2 local 201 cali Colombia

Manufacturer : SHENZHEN YEPO TIME ELECTRONICS CO.,LTD

Address : 2F,Bldg B, Chuangye Park, Phoenix 3th Industrial Zone,  
Fuyong Street, Bao'an District, Shenzhen, China.

## 1.2 Description of Test Facility

Shenzhen Alpha Product Testing Co., Ltd  
Building B, East Area of Nanchang Second, Industrial Zone, Gushu 2nd Road,  
Bao'an, Shenzhen, China

August 11, 2014 File on Federal Communication Commission  
Registration Number: 203110

July 18, 2014 Certificated by IC  
Registration Number: 12135A

## 2 EMC Equipment List

Equipment	Manufacture	Model No.	Serial No.	Last cal.	Cal Interval
3m Semi-Anechoic	ETS-LINDGREN	N/A	SEL0017	2015.01.19	1 Year
Spectrum analyzer	Agilent	E4407B	MY46185649	2015.01.19	1 Year
Receiver	R&S	ESCI	1166.5950K03-1 011	2015.01.19	1 Year
Receiver	R&S	ESCI	101202	2015.01.19	1 Year
Bilog Antenna	Schwarzbeck	VULB 9168	VULB9168-438	2015.01.21	1 Year
Horn Antenna	EMCO	3115	640201028-06	2015.01.21	1 Year
Active Loop Antenna	Beijing Daze	ZN30900A	SEL0097	2015.01.21	1 Year
Cable	Resenberger	N/A	No.1	2015.01.19	1 Year
Cable	SCHWARZBECK	N/A	No.2	2015.01.19	1 Year
Cable	SCHWARZBECK	N/A	No.3	2015.01.19	1 Year
Pre-amplifier	Schwarzbeck	BBV9743	9743-019	2015.01.19	1 Year
Pre-amplifier	R&S	AFS33-18002650 -30-8P-44	SEL0080	2015.01.19	1 Year
Base station	Agilent	E5515C	GB44300243	2015.01.19	1 Year
Temperature controller	Terchy	MHQ	120	2015.01.19	1 Year
Power divider	Anritsu	K240C	020346	2015.01.19	1 Year
Signal Generator	HP	83732B	VS3449051	2015.01.19	1 Year
Power Meter	Anritsu	ML2487A	6K00001491	2015.01.19	1 Year
Power sensor	Anritsu	ML2491A	32516	2015.01.19	1 Year
L.I.S.N.#1	Schwarzbeck	NSLK8126	8126466	2016.01.19	1 Year
L.I.S.N.#2	ROHDE&SCHWARZ	ENV216	101043	2016.01.19	1 Year

### 3 Test Procedure

**POWER LINE CONDUCTED INTERFERENCE:** The test procedure used was ANSI Standard ANSI C63.4:2014 using a 50  $\mu$  H LISN. Both Lines were observed. The bandwidth of the receiver was 10 kHz with an appropriate sweep speed. The ambient temperature of the EUT was 25°C with a humidity of 58%.

**RADIATION INTERFERENCE:** The test procedure used was ANSI Standard ANSI C63.4:2014 using a ANRITSU spectrum analyzer with a pre-selector. The analyzer was calibrated in dB above a micro volt at the output of the antenna. The resolution bandwidth was 100 kHz and the video bandwidth was 300 kHz up to 1 GHz and 1 MHz with a video BW of 3MHz above 1 GHz. The ambient temperature of the EUT was 25°C with a humidity of 58%.

**FORMULA OF CONVERSION FACTORS:** The Field Strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dBuV) to the antenna correction factor supplied by the antenna manufacturer and cable loss. The antenna correction factors and cable loss are stated in terms of dB. The gain of the Pre-selector was accounted for in the Spectrum Analyzer Meter Reading.

Example:

Freq (MHz) METER READING + ACF + CABLE = FS  
33.20 dBuV + 10.36 dB + 0.9 dB = 44.46 dBuV/m @ 3m

**ANSI STANDARD ANSI C63.4:2014 10.1.7 MEASUREMENT PROCEDURES:** The EUT was placed on a table 80 cm high and with dimensions of 1m by 1.5m. The EUT was placed in the center of the table (1.5m side). The table used for radiated measurements is capable of continuous rotation. When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes. The situation was similar for the conducted measurement except that the table did not rotate. The EUT was setup as described in ANSI Standard ANSI C63.4:2014 10.1.7 with the EUT 40 cm from the vertical ground wall.


## 4 Summary of Measurement

### 4.1 Summary of test result

Test Item	Test Requirement	Standards Paragraph	Result
Spurious Emission	FCC PART 15:2014	Section 15.247&15.209	Compliance
Conduction Emission	FCC PART 15:2014	Section 15.207	Compliance
Bandwidth Test	FCC PART 15:2014	Section 15.247	Compliance
Peak Power	FCC PART 15:2014	Section 15.247	Compliance
Power Density	FCC PART 15:2014	Section 15.247	Compliance
Band Edge	FCC PART 15:2014	Section 15.247	Compliance
Antenna Requirement	FCC PART 15:2014	Section 15.203	Compliance

Note: The EUT has been tested as an independent unit. And Continual Transmitting in maximum power (The adapter be used during Test)

### 4.2 Test connection



### 4.3 Assistant equipment used for test

Description : Adapter  
 Manufacturer : NIL  
 Model No. : XJX-001-13  
 Input : AC 100-240V, 50-60Hz  
 Output : 5.0V DC, 1300mA

### 4.4 Test mode

Tested mode, channel, and data rate information		
Mode	Channel	Frequency (MHz)
GFSK	Low :CH1	2402
	Middle: CH20	2440
	High: CH40	2480

### 4.5 Test Conditions

Temperature range	21-25°C
Humidity range	40-75%
Pressure range	86-106kPa

### 4.6 Measurement Uncertainty (95% confidence levels, k=2)

Item	MU	Remark
Uncertainty for Power point Conducted Emissions Test	2.42dB	
Uncertainty for Radiation Emission test in 3m chamber (below 30MHz)	2.13 dB	Polarize: V
	2.57dB	Polarize: H
Uncertainty for Radiation Emission test in 3m chamber (30MHz to 1GHz)	3.54dB	Polarize: V
	4.1dB	Polarize: H
Uncertainty for Radiation Emission test in 3m chamber (1GHz to 25GHz)	2.08dB	Polarize: H
	2.56dB	Polarize: V
Uncertainty for radio frequency	$1 \times 10^{-9}$	
Uncertainty for conducted RF Power	0.65dB	
Uncertainty for temperature	0.2°C	
Uncertainty for humidity	1%	
Uncertainty for DC and low frequency voltages	0.06%	

## 5 Spurious Emission

### 5.1 Radiation Emission

#### 5.1.1 Radiation Emission Limits(15.209)

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3



Harmonic emissions limits comply with below 54 dBuV/m at 3m. Other emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or comply with the radiated emissions limits specified in section 15.209(a) limit in the table below has to be followed.


**NOTE:**

- The tighter limit applies at the band edges.
- Emission Level(dB uV/m)=20log Emission Level(uV/m)

#### 5.1.2 Test Setup

See the next page





Above 1GHz Test Setup

### 5.1.3 Test Procedure

- The measuring distance of 3m shall be used for measurements at frequency up to 1GHz and above 1GHz. The EUT was placed on a rotating 0.8 m high above ground for below 1GHz and 1.5m high for above 1GHz testing. The table was rotated 360 degrees to determine the position of the highest radiation
- The Test antenna shall vary between 1m and 4m. Both Horizontal and Vertical antenna are set of make measurement.
- The initial step in collecting conducted emission data is a spectrum analyzer Peak detector mode pre-scanning the measurement frequency range. Significant Peaks are then marked. and then QP Detector mode premeasured
- If Peak value complies with QP limit below 1GHz. The EUT deemed to comply with QP limit. But the Peak value and average value both need to comply with applicable limit above 1GHz.
- For the actual test configuration, please see the test setup photo.

### 5.1.4 Test Equipment Setting For emission test Result

9 kHz~150 kHz	RBW 200 Hz	VBW 1 kHz
150 kHz~30 MHz	RBW 9 kHz	VBW 30 kHz
30 MHz~1 GHz	RBW 120 kHz	VBW 300 kHz
Above 1GHz	RBW 1 MHz	VBW 3 MHz

### 5.1.5 Test Condition

Continuously transmitting with maximum power.

### 5.1.6 Test Result

We have scanned the 9 kHz from 25 GHz to the EUT.

Detailed information please see the following page.


From 9 kHz to 30 MHz: Conclusion: PASS

Note: The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Data: 3

File: D:\Test Data 2015\Y\YuanPeng\15.08.13 PC.EM6 (12)

Date: 2015-08-10 Time: 16:50:24



Condition : FCC PART 15 B      3m      POL: HORIZONTAL

EUT :

Model No :

Test Mode : BT4.0

Power :

Test Engineer :


Remark :

Temp : 24.2°C

Hum : 54%

Item	Freq	Read	Antenna	Preamp	Cable	Level	Limit	Margin	Remark
		Level	Factor	Factor	Cable Loss	dBuV	dBuV	dBuV	
	MHz	dBuV	dB	dB	dB				
1	59.65	50.14	12.75	30.90	0.24	32.23	40.00	-7.77	Peak
2	68.15	51.95	11.21	30.26	0.29	33.19	40.00	-6.81	Peak
3	137.42	41.38	13.22	29.36	0.41	25.65	43.50	-17.85	Peak
4	250.30	48.84	11.57	28.24	0.48	32.65	46.00	-13.35	Peak
5	691.99	36.02	19.56	25.91	1.19	30.86	46.00	-15.14	Peak
6	897.00	36.12	21.61	25.11	1.22	33.84	46.00	-12.16	Peak

Remark: Level = Read Level + Antenna Factor - Preamp Factor + Cable Loss



Condition : FCC PART 15 B 3m POL: VERTICAL

EUT :

Model No :

Test Mode : BT4.0

Power :

Test Engineer :

Remark :

Temp : 24.2°C

Hum : 54%

Item	Freq	Read	Antenna	Preamp	Cable	Level	Limit	Margin	Remark
		Level	Factor	Factor	Cable Loss	dBuV	dBuV	dBuV	
	MHz	dBuV	dB	dB	dB				
1	59.44	52.72	12.75	30.89	0.32	34.90	40.00	-5.10	Peak
2	68.15	54.32	11.21	30.26	0.29	35.56	40.00	-4.44	Peak
3	150.01	43.61	14.16	29.45	0.39	28.71	43.50	-14.79	Peak
4	251.18	41.99	11.61	28.23	0.49	25.86	46.00	-20.14	Peak
5	734.49	35.72	20.09	25.49	1.30	31.62	46.00	-14.38	Peak
6	958.79	36.98	22.16	25.01	1.97	36.10	46.00	-9.90	Peak

From 1G-25GHz

<b>EUT</b>	TABLET PC	<b>Model Name</b>	G710
<b>Temperature</b>	26°C	<b>Relative Humidity</b>	56%
<b>Pressure</b>	960hPa	<b>Test voltage</b>	DC 3.7V From battery
<b>Test Mode</b>	TX Low		

No	Freq (MHz)	Read Level (dBuV/m)	Antenna Factor (dB/m)	Cable loss(d B)	Amp Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4804	40.41	33.95	10.18	34.26	50.28	74	23.72	PK
2	4804	32.02	33.95	10.18	34.26	41.89	54	12.11	AV
3	7206	/							
4	9608	/							
5	12010	/							

Antenna Polarity: Horizontal

1	4804	40.49	33.95	10.18	34.26	50.36	74	23.64	PK
2	4804	31.87	33.95	10.18	34.26	41.74	54	12.26	AV
3	7206	/							
4	9608	/							
5	12010	/							

Note:

1,Measuring frequency from 1GHz to 25GHz

2,Spectrum Set for PK measure: RBW=1MHz, VBW=1MHz, Sweep time=Auto, Detector: PK

2,Spectrum Set for AV measure: RBW=1MHz, VBW=3MHz, Sweep time=Auto, Detector: RMS

3, Result = Read level + Antenna factor + cable loss-Amp factor

4, All the other emissions not reported were too low to read and deemed to comply with FCC limit.

<b>EUT</b>	TABLET PC	<b>Model Name</b>	G710
<b>Temperature</b>	26°C	<b>Relative Humidity</b>	56%
<b>Pressure</b>	960hPa	<b>Test voltage</b>	DC 3.7V From battery
<b>Test Mode</b>	TX Middle		

No	Freq (MHz)	Read Level (dBuV/m)	Antenna Factor (dB/m)	Cable loss(d B)	Amp Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4880	41.95	33.93	10.2	34.29	51.79	74	22.21	PK
2	4880	32.13	33.93	10.2	34.29	41.97	54	12.03	AV
3	7320	/							
4	9760	/							
5	12200	/							

Antenna Polarity: Horizontal

1	4880	41.37	33.93	10.2	34.29	51.21	74	22.79	PK
2	4880	32.84	33.93	10.2	34.29	42.68	54	11.32	AV
3	7320	/							
4	9760	/							
5	12200	/							

Note:

- 1, Measuring frequency from 1GHz to 25GHz
- 2, Spectrum Set for PK measure: RBW=1MHz, VBW=1MHz, Sweep time=Auto, Detector: PK
- 2, Spectrum Set for AV measure: RBW=1MHz, VBW=3MHz, Sweep time=Auto, Detector: RMS
- 3, Result = Read level + Antenna factor + cable loss-Amp factor
- 4, All the other emissions not reported were too low to read and deemed to comply with FCC limit.

<b>EUT</b>	TABLET PC	<b>Model Name</b>	G710
<b>Temperature</b>	26°C	<b>Relative Humidity</b>	56%
<b>Pressure</b>	960hPa	<b>Test voltage</b>	DC 3.7V From battery
<b>Test Mode</b>	TX High		

No	Freq (MHz)	Read Level (dBuV/m)	Antenna Factor (dB/m)	Cable loss(d B)	Amp Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	4960	42.38	33.98	10.22	34.25	52.33	74	21.67	PK
2	4960	32.89	33.98	10.22	34.25	42.84	54	11.16	AV
3	7440	/							
4	9920	/							
5	12400	/							

## Antenna Polarity: Horizontal

1	4960	42.75	33.98	10.22	34.25	52.7	74	21.3	PK
2	4960	32.42	33.98	10.22	34.25	42.37	54	11.63	AV
3	7440	/							
4	9920	/							
5	12400	/							

## Note:

- 1, Measuring frequency from 1GHz to 25GHz
- 2, Spectrum Set for PK measure: RBW=1MHz, VBW=1MHz, Sweep time=Auto, Detector: PK
- 2, Spectrum Set for AV measure: RBW=1MHz, VBW=3MHz, Sweep time=Auto, Detector: RMS
- 3, Result = Read level + Antenna factor + cable loss-Amp factor
- 4, All the other emissions not reported were too low to read and deemed to comply with FCC limit.


## 6 POWER LINE CONDUCTED EMISSION

### 6.1 Conducted Emission Limits(15.207)

Frequency MHz	Limits dB( $\mu$ V)	
	Quasi-peak Level	Average Level
0.15 -0.50	66 -56*	56 - 46*
0.50 -5.00	56	46
5.00 -30.00	60	50

Notes: 1. \*Decreasing linearly with logarithm of frequency.  
 2. The lower limit shall apply at the transition frequencies.  
 3. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.

### 6.2 Test Setup



### 6.3 Test Procedure

The EUT is put on the plane 0.8m high above the ground by insulating support and is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC lines are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to ANSI ANSI C63.4:2014 on Conducted Emission Measurement. The bandwidth of test receiver (R & S ESCDLB ECHO 50) is set at 9 kHz.

### 6.4 Test Results

TX MODE

Worse case is reported only


**PASS**

Detailed information please see the following page.

Data: 19

File: E:\TEST REPORT\Y\YuanPeng\G710.EM6 (20)

Date: 2015-08-13 Time: 18:18:36



Condition : FCC PART 15 B QP POL: LINE Temp:25.7 °C Hum:51 %  
EUT :  
Model No : G  
Test Mode : BT4.0  
Power : DC 5V from adapter AC 120V/60Hz  
Test Engineer:  
Remark :


Item	Freq	Read	LISN	Preamp	Cable	Level	Limit	Margin	Remark
			Factor	Factor	Lose	dB	dBuV	dBuV	dBuV
	MHz	dBuV	dB	dB	dB	dBuV	dBuV	dBuV	
1	0.150	37.54	0.03	-9.72	0.10	47.39	66.00	-18.61	Peak
2	0.237	33.35	0.03	-9.72	0.10	43.20	62.22	-19.02	Peak
3	0.507	33.21	0.03	-9.72	0.10	43.06	56.00	-12.94	Peak
4	0.899	31.67	0.04	-9.71	0.10	41.52	56.00	-14.48	Peak
5	1.772	28.81	0.05	-9.70	0.10	38.66	56.00	-17.34	Peak
6	3.840	31.12	0.08	-9.69	0.12	41.01	56.00	-14.99	Peak

Remarks: Level = Read + LISN Factor - Preamp Factor + Cable loss

Data: 17

File: E:\TEST REPORT\Y\YuanPeng\G710.EM6 (20)

Date: 2015-08-13 Time: 18:15:03



Condition : FCC PART 15 B QP POL: NEUTRAL Temp:25.7 °C Hum:51 %

EUT :

Model No : G710

Test Mode : BT 4.0

Power : DC 5V from adapter AC 120V/60Hz

Test Engineer:

Remark :

Item	Freq	Read	LISN	Preamp	Cable	Level	Limit	Margin	Remark
	MHz	dBuV	Factor	Factor	dB	dBuV	dBuV	dBuV	
1	0.187	35.65	0.03	-9.72	0.10	45.50	64.15	-18.65	Peak
2	0.437	30.17	0.03	-9.72	0.10	40.02	57.11	-17.09	Peak
3	0.727	31.07	0.04	-9.72	0.10	40.93	56.00	-15.07	Peak
4	1.010	29.80	0.04	-9.71	0.10	39.65	56.00	-16.35	Peak
5	3.840	32.32	0.08	-9.69	0.12	42.21	56.00	-13.79	Peak
6	16.486	22.07	0.26	-9.41	0.28	32.02	60.00	-27.98	Peak

Remarks: Level = Read + LISN Factor - Preamp Factor + Cable loss

## 7 Conducted Maximum Output Power

### 7.1 Test limit

Please refer section 15.247.

### 7.2 Test Procedure

Details see the KDB558074 Meas Guidance V03


7.2.1 Place the EUT on the table and set it in transmitting mode.

7.2.2 Measure out each mode and each bands peak output power of EUT.

Note: The cable loss and attenuator loss were offset into measure device as amplitude offset.

Details see the KDB558074 DTS Meas Guidance V03

### 7.3 Test Setup



### 7.4 Test Results

# PASS

Detailed information please see the following page.

Channel	Frequency (MHz)	PK Output Power (dBm)	PK Output Power (mW)	Limit (dBm)
CH0	2402	-5.61	0.275	30
CH19	2440	-5.78	0.264	30
CH39	2480	-5.89	0.258	30

## 8 PEAK POWER SPECTRAL DENSITY

### 8.1 Test limit


- 8.1.1 Please refer section 15.247.
- 8.1.2 For direct sequence systems, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3kHz band during any time interval of continuous transmission.
- 8.1.3 The direct sequence operating of the hybrid system, with the frequency hopping operation turned off, shall comply with the power density requirements of paragraph (d) of this section.

### 8.2 Method of measurement

Details see the KDB558074 DTS Meas Guidance V03

- 8.2.1 Place the EUT on the table and set it in transmitting mode.
- 8.2.2 Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
- 8.2.3 Set the spectrum analyzer as RBW = 3 kHz, VBW = 10 kHz, span=5-30%EBW, detail see the test plot.
- 8.2.4 Record the maximum reading.
- 8.2.5 Repeat the above procedure until the measurements for all frequencies are completed.

### 8.3 Test Setup




## 8.4 Test Results

**PASS.**


Detailed information please see the following page.

Channel	Frequency (MHz)	Power Spectral Density (dBm)	Limit (dBm)	Result
CH0	2402	-15.958	8	PASS
CH19	2440	-14.533	8	PASS
CH39	2480	-14.024	8	PASS


CH Low:



CH Middle:



CH High:



## 9 Bandwidth

### 9.1 Test limit

Please refer section FCC part 15.247


For direct sequence systems, the minimum 6dB bandwidth shall be at least 500 kHz.

### 9.2 Method of measurement

Details see the KDB558074 D01 Meas Guidance

- a) The bandwidth is measured at an amplitude level reduced 20dB from the reference level. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency. Once the reference level is established, the equipment is conditioned with typical modulating signal to produce the worst-case (i.e. the widest) bandwidth.
- b) The test receiver set RBW = 100 kHz, VBW $\geq$ 3RBW, Sweep time set auto, detail see the test plot.

### 9.3 Test Setup



### 9.4 Test Results

PASS.

Detailed information please see the following page.

Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Limit (MHz)	Result
CH0	2402	0.691	0.5	PASS
CH19	2440	0.696	0.5	PASS
CH39	2480	0.691	0.5	PASS


CH Low:



CH Middle:



CH High:



## 10 Band Edge Check

### 10.1 Test limit

Please refer section RSS-GEN&15.247.

### 10.2 Test Procedure

- 12.2.1 Put the EUT on a 0.8m high table, power on the EUT. Emissions were scanned and measured rotating the EUT to 360 degrees, Find the maximum Emission
- 12.2.2 Check the spurious emissions out of band.
- 12.2.3 RBW set to 1MHz ,VBW set to 3MHz ,peak detector for peak value  
RBW set to 1MHz, VBW set to 3MHz, RMS detector for AV value.

### 10.3 Test Setup

Same as 5.2.2.

### 10.4 Test Result

PASS.


Detailed information please see the following page.

## Radiated measurement:



## Conducted measurement:

CH Low:



CH High:



## 11 Antenna Requirement

### 11.1 Standard Requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

### 11.2 Result

The antennas used for this product are PCB Antenna for Bluetooth, no antenna other than that furnished by the responsible party shall be used with the device, the maximum peak gain of the transmit antenna is only 0 dBi .

## **12 Test setup photos**

Please refer to test setup photo document.

## **13 Photos of EUT**

Please refer to EUT photo document.

-----END OF THE REPORT-----