Federal Communication Commission Equipment Authorization Division, Application Processing Branch 7435 Oakland Mills Road Columbia, MD 21048

DATE: 2015-10-14

Attn: Office of Engineering and Technology Subject: Attestation Letter regarding UNII devices

FCC ID: 2AFNK-D2C315

Software security questions and answers per KDB 594280 D02:

Soliw	Software security questions and answers per KDB 594280 D02:			
	Software Security description – General Description			
1	Describe how any software/firmware update will	We do not release the		
	be obtained, downloaded, and installed. Software	firmware on our website		
	that is accessed through manufacturer's website	for downloading. Our		
	or device's management system, must describe	direct host manufacturer		
	the different levels of security.	(OEM) can request the		
		firmware from us and it		
		will be made available via		
		secure server.		
2	Describe all the radio frequency parameters that	Radio frequency		
	are modified by any software/firmware without	parameters are limited by		
	any hardware changes. Are these parameters in	US regulatory domain and		
	some way limited, such that, it will not exceed	country code to limit		
	the authorized parameters?	frequency and transmit		
		power levels. These limits		
		are stored in non-volatile		
		memory by the module		
		manufacturer at the time of		
		production. They will not		
		exceed the authorized		
_		values.		
3	Describe in detail the authentication protocols	The firmware is installed		
	that are in place to ensure that the source of the	on each single module		
	software/firmware is legitimate. Describe in	during manufacturing		
	detail how the software is protected against	process. The correct		
	modification	firmware is verified and		
		installed by the module		
		manufacturer.		
		In addition, the firmware		

		binary is encrypted using open SSL encryption and the firmware updates can only be stored in non-volatile memory when the firmware is authenticated. The encryption key is known by the module manufacturer only.
4	Describe in detail the verification protocols in place to ensure that installed software/firmware is legitimate	The firmware binary is encrypted. The process to flash a new firmware is using a secret key to decrypt the firmware, only correct decrypted firmware is stored in non-volatile memory (see #3).
5	Describe in detail the verification protocols in place to ensure that installed software/firmware is legitimate	Standard open SSL encryption is used (see #3).
6	For a device that can be configured as a master and client (with active or passive scanning), explain how the device ensures compliance for each mode? In particular if the device acts as master in some band of operation and client in another; how is compliance ensured in each band of operation? Software Security description – Third-Party	The device ensures the compliance by checking the configured parameter and operation values according to the regulatory domain and country code in each band. Access Control
1	How is unauthorized software/firmware changes prevented?	Unauthorized firmware is not accepted by the firmware update process. See General Description #5, #3
2	Is it possible for third parties to load device drivers that could modify the RF parameters, country of operation or other parameters which impact device compliance? If so, describe procedures to ensure that only approved drivers are loaded.	The embedded software is protected via the measures explained in the previous section. Distributions of host operating software are encrypted with a key.
3	Explain if any third parties have the capability to operate a US sold device on any other regulatory domain, frequencies, or in any manner that is in	No, third parties don't have the capability to access and change radio

	violation of the certification.	parameters. US sold
	violation of the certification.	1 *
		modules are factory
1	Wilst t. 41:1tiss for LIC	configured to US.
4	What prevents third parties from loading non -US	Only encrypted and
	versions of the software/firmware on the device?	verified firmware is
		applied and stored in the
		non-volatile memory.
5	For modular devices, describe how authentication	The module is not
	is achieved when used with different hosts.	available for sale or
		installation outside of
		company licensing
		agreements. Modules are
		always installed in host
		systems in a factory by end
		integrators (OEM)
		responsible for loading
		authorized software.
	Software Security description – USER CONFIC	GURATION GUID
1	To whom is the UI accessible? (Professional	The UI is accessible to
	installer, end user, other.)	anyone using the device.
	a. What parameters are viewable to the	Various device status
	professional installer/end user?	information is made
		available like log
		information, connection
		status, operation mode,
		operation frequency, etc.
		Radio parameters are
		described in c.i
	b. What parameters are accessible or modifiable	This device is not subject
	to the professional installer?	to professional installation
	i. Are the parameters in some way	-
	limited, so that the installers will not	
	enter parameters that exceed those	
	authorized?	
	ii. What controls exist that the user	
	cannot operate the device outside its	
	authorization in the U.S.?	
	c. What configuration options are available to	The end user is able to
	the end-user?	configure the operation
		frequency, modulation,
		reduce the output power
		levels etc. The end user
		cannot change the antenna
		camot change the antenna

			gain and country code, those settings are programmed at factory production time.
	limited, so	or that the installers will not meters that exceed those	Yes, the parameters can only be changed within the limits of country code US.
	cannot op	erols exist that the user erate the device outside its ion in the U.S.?	The country code and regulatory domain control do limit all the parameters set by UI
	d. Is the country coochanged in the Ul	le factory set? Can it be	The country code is factory set and is never changed by UI.
	that the de	t controls exist to ensure evice can only operate authorization in the U.S.?	The country code is factory set and is never changed by UI
	e. What are the defa device is restarted	ult parameters when the 1?	At each boot up the country code and the antenna gain are read from the non-volatile memory, those values are configured during module production.
2			Not supported
3	and client (with active this is user configural exist, within the UI, the each mode. If the development of t	be configured as a master e or passive scanning), if ole, describe what controls o ensure compliance for rice acts as a master in some thers, how is this configured?	No end user controls or user interface operation to change master/client operation.
4	types of access points point-to-multipoint, a	be configured as different s, such as point-to-point or and use different types of nat controls exist to ensure	The device does not support these modes/features.

LifeShare Technologies LLC 2177 Intelliplex Dr., Suite 150 Shelbyville, IN 46176

compliance with applicable limits and the proper	
antenna is used for each mode of operation. See	
Section 15.407(a).	

Sincerely

(signature)

Name and Title: doug.stevens

/PM

Company:LifeShare Technologies LLC

Address:2177 Intelliplex Dr., Suite 150Shelbyville, IN 46176

Phone:+317 825-0320 Fax:+317 825-0320

Email:doug.stevens@lifesharetech.com