

RF Exposure Evaluation

FCC ID: 2AFNM-JT2692

1. Client Information

Applicant : Shenzhen Jinruitai Electronics Co.,Ltd
Address : 4F, Building A, Taixinglong Industrial Town, Zhongwu Xixiang, Baoan District, Shenzhen City, GuangDong Province, China
Manufacturer : Shenzhen Jinruitai Electronics Co.,Ltd
Address : 4F, Building A, Taixinglong Industrial Town, Zhongwu Xixiang, Baoan District, Shenzhen City, GuangDong Province, China

2. General Description of EUT

EUT Name	: Sport Bluetooth Speaker	
Models No.	: JT2692	
Model Difference	: N/A	
Product Description	Operation Frequency: 2402~2480MHz	
	Number of Channel:	Bluetooth 4.0 (BLE): 40 channels
	Max Peak Output Power:	4.50 dBm Conducted Power
	Antenna Gain:	-0.46 dBi PCB Antenna
	Modulation Type:	GFSK
Power Supply	: DC Voltage supplied from Host System by USB cable. DC power by Li-ion Battery.	
Power Rating	: DC 5.0V by USB cable. DC 3.7V 1800mAh Li-ion Battery.	
Connecting I/O Port(S)	: Please refer to the User's Manual	

Note:

More test information about the EUT please refer the RF Test Report.

[TB-RF-074-1.0](#)

SAR Test Exclusion Calculations

1. FCC: According to KDB 447498 D01 Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies v05r02.

- (1) Clause 4.3: General SAR test reduction and exclusion guidance

- Sub clause 4.31: Standalone SAR test exclusion considerations

- 1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6GHz at test separation distance ≤ 5 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation, mm})] * [\sqrt{f_{(\text{GHz})}}] \leq 3.0 \text{ for 1-g SAR}$$
$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation, mm})] * [\sqrt{f_{(\text{GHz})}}] \leq 7.5.0 \text{ for 10-g SAR}$$

- 2.

- Calculation:

Test separation: 5mm					
BLE(GFSK)					
Frequency (GHz)	Conducted Power (dBm)	Turn-up Power Tolerance (dB)	Max power of tune up tolerance (mw)	Calculation Value	Threshold Value
2.402	4.50	± 0.5	3.162	0.980	3.0
2.442	2.67	± 0.5	2.075	0.648	3.0
2.480	2.29	± 0.5	1.901	0.599	3.0

So standalone SAR measurements are not required.