

# **FCC Part 15C Test Report**

**FCC ID: 2AFNYKEY-WT06** 

Product Name:	Wireless Ultrasonic Sensor
Trademark:	N/A
Model Name :	KEY-WT06
Prepared For :	Xiamen Keytop Comm.&Tech.Co.,Ltd
Address :	RM301,No.58, Guanri Road,Siming District, XiaMen, China
Prepared By:	Shenzhen BCTC Technology Co., Ltd.
Address :	No.101, Yousong Road, Longhua New District, Shenzhen, China
Test Date:	Aug. 15 - Aug. 21, 2015
Date of Report :	Aug. 21, 2015
Report No.:	BCTC-15080188



## **TEST RESULT CERTIFICATION**

Report No.: BCTC-15080188

Applicant's name:	Xiamen Keytop Comm.&Tech.Co.,Ltd
Addross .	DM204 No FO Changi Dood Ciming Dietri

Address .....: RM301,No.58, Guanri Road,Siming District, XiaMen, China

Manufacture's Name.....: Xiamen Keytop Comm.&Tech.Co.,Ltd

Address ...... RM301,No.58, Guanri Road,Siming District, XiaMen, China

**Product description** 

Product name...... Wireless Ultrasonic Sensor

Model and/or type reference : KEY-WT06

Serial Model..... N/A

Standards..... FCC Part15.249

Test procedure...... ANSI C63.10-2013

This device described above has been tested by BCTC, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.


This report shall not be reproduced except in full, without the written approval of BCTC, this document may be altered or revised by BCTC, personal only, and shall be noted in the revision of the document.

Testing Engineer	:	Evic Yang
		(Eric Yang)
Technical Manager	:	Sophie Lu
		(Sophia Lee)
Authorized Signatory	:	Casey Wang Sites Office APPROVED
		(Casey Wang)



## **Table of Contents**

	Page
1 . SUMMARY OF TEST RESULTS	5
1.1 TEST FACILITY	6
1.2 MEASUREMENT UNCERTAINTY	6
2 . GENERAL INFORMATION	7
2.1 GENERAL INFORMATION  2.1 GENERAL DESCRIPTION OF EUT	7
	_
2.2 DESCRIPTION OF TEST MODES	8
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTE	
2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)	9
2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS	10
3 . EMC EMISSION TEST	11
3.1 CONDUCTED EMISSION MEASUREMENT	11
3.1.1 POWER LINE CONDUCTED EMISSION LIMITS	11
3.1.2 TEST PROCEDURE	11
3.1.3 DEVIATION FROM TEST STANDARD 3.1.4 TEST SETUP	11 12
3.1.5 EUT OPERATING CONDITIONS	12
3.1.6 TEST RESULTS	13
3.2 RADIATED EMISSION MEASUREMENT	14
3.2.1 RADIATED EMISSION LIMITS	14
3.2.2 TEST PROCEDURE	15
3.2.3 DEVIATION FROM TEST STANDARD 3.2.4 TEST SETUP	15 16
3.2.5 EUT OPERATING CONDITIONS	17
3.2.6 TEST RESULTS (BETWEEN 9KHZ – 30 MHZ)	18
3.2.7 TEST RESULTS (BETWEEN 30MHZ – 1GHZ)	19
3.2.8 TEST RESULTS (ABOVE 1000 MHZ)	21
4.100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE	22
4.1 DEVIATION FROM STANDARD	23
4.2 TEST SETUP	23
4.3 EUT OPERATION CONDITIONS 4.4 TEST RESULTS	23 23
5 . BANDWIDTH TEST	24
5.1 APPLIED PROCEDURES / LIMIT	24





## **Table of Contents**

	Page
5.1.1 TEST PROCEDURE	24
5.1.2 DEVIATION FROM STANDARD	24
5.1.3 TEST SETUP	24
5.1.4 EUT OPERATION CONDITIONS	24
5.1.5 TEST RESULTS	25
6 . ANTENNA REQUIREMENT	26
6.1 STANDARD REQUIREMENT	26
6.2 EUT ANTENNA	26
7 . EUT TEST PHOTO	27
8 . PHOTO OF THE EUT	28



## 1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.249) , Subpart C				
Standard Section	Test Item	Judgment	Remark	
15.207	Conducted Emission	N/A		
15.249 (a)(2)	20dB Bandwidth	PASS		
15.249	Fundamental &Radiated Spurious Emission Measurement	PASS		
15.205	Band Edge Emission	PASS		
15.203	Antenna Requirement	PASS		

#### NOTE:

(1)" N/A" denotes test is not applicable in this Test Report



#### 1.1 TEST FACILITY

Shenzhen BCTC Technology Co., Ltd.

Add.: No.101, Yousong Road, Longhua New District, Shenzhen, China

FCC Registered No.: 187086

#### 1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement  $y \pm U$ , where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95 %  $\circ$ 

No.	Item	Uncertainty
1	Conducted Emission Test	±1.38dB
2	RF power,conducted	±0.16dB
3	Spurious emissions,conducted	±0.21dB
4	All emissions,radiated(<1G)	±4.68dB
5	All emissions,radiated(>1G)	±4.89dB
6	Temperature	±0.5°C
7	Humidity	±2%



## 2. GENERAL INFORMATION

## 2.1 GENERAL DESCRIPTION OF EUT

Equipment	Wireless Ultrasonic Sens	sor	
Trade Name	N/A		
Model Name	KEY-WT06		
Serial Model	N/A		
Model Difference	N/A		
	The EUT is a Wireless U	Iltrasonic Sensor	
	Operation Frequency:	915MHz	
	Modulation Type:	FSK	
	Number Of Channel	1CH	
Product Description	Antenna Designation:	Please see Note 3.	
	Antenna Gain (dBi)	Odbi	
	Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.		
Channel List	Please refer to the Note 2.		
Power	N/A		
Battery	DC1.5V		
Connecting I/O Port(s)	Please refer to the User	s Manual	

#### Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

# Table for Filed Antenna

Ant	Brand	Model Name	Antenna Type	Connector	Gain (dBi)	NOTE
Α	N/A	N/A	Internal Antenna	N/A	0	

Tel: 400-788-9558 0755-33019988



#### 2.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Report No.: BCTC-15080188

Pretest Mode	Description
Mode 1	TX Mode
Mode 2	Link Mode

For Conducted Emission		
Final Test Mode	Description	
Mode 2	Link Mode	

For Radiated Emission		
Final Test Mode	Description	
Mode 1	TX Mode	

#### Note:

- (1) The measurements are performed at the highest, middle, lowest available channels.
- (2) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported, data rates is 256 kbps

FCC Report



#### 2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

D = =1: = 4 = =1	C	<b>Emission</b>	T4
Radiated	Shirinis	⊢missinn	IPSI

E-1 EUT

## 2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
	Wireless				
E-1	Ultrasonic	N/A	KEY-WT06	N/A	EUT
	Sensor				

Item	Shielded Type	Ferrite Core	Length	Note

#### Note:

- (1) The support equipment was authorized by Declaration of Confirmation.
- (2) For detachable type I/O cable should be specified the length in cm in <code>"Length\_"</code> column.



## 2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Conduction Test equipment

Item	Kind of	Manufactu	Type No.	Serial No.	Last	Calibrated	Calibratio
пеш	Equipment	rer	Type No.	Serial No.	calibration	until	n period
1	Test Receiver	R&S	ESCI	1166.5950K 03-101165- ha	2015.06.05	2016.06.05	1 year
2	LISN	R&S	NSLK81 26	812646 6	2014.08.24	2015.08.23	1 year
3	LISN	R&S	NSLK81 26	812648 7	2014.08.24	2015.08.23	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	620026441 7	2015.06.05	2016.06.05	1 year
5	RF cables	R&S	R204	R20X	2015.06.05	2016.06.05	1 year

# Radiation Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until	Calibration period
1	Spectrum Analyzer	Agilent	E4407B	MY4510957 2	2014.08.25	2015.08.24	1 year
2	Test Receiver	R&S	ESPI	101396	2014.08.25	2015.08.24	1 year
3	Bilog Antenna	SCHWARZB ECK	VULB9160	VULB9160- 3369	2014.08.25	2015.08.24	1 year
4	50Ω Coaxial Switch	Anritsu	MP59B	620026441 6	2015.06.07	2016.06.06	1 year
5	Spectrum Analyzer	ADVANTEST	R3132	150900201	2015.06.07	2016.06.06	1 year
6	Horn Antenna	SCHWARZB ECK	9120D	9120D-1275	2014.08.25	2015.08.24	1 year
7	Horn Ant	Schwarzbeck	BBHA 9170	9170-181	2015.07.06	2016.07.05	1 year
8	Amplifier	SCHWARZBE CK	BBV9718	9718-270	2014.08.25	2015.08.24	1 year
9	Amplifier	SCHWARZBE CK	BBV9743	9743-119	2014.08.25	2015.08.24	1 year
10	Loop Antenna	ARA	PLA-1030/B	1029	2015.06.08	2016.06.07	1 year
11	Power Meter	R&S	NRVS	100696	2015.07.06	2016.07.05	1 year
12	Power Sensor	R&S	URV5-Z4	0395.1619. 05	2015.07.06	2016.07.05	1 year
13	RF cables	R&S	N/A	N/A	2015.07.06	2016.07.05	1 year



#### 3. EMC EMISSION TEST

#### 3.1 CONDUCTED EMISSION MEASUREMENT

#### 3.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)		Standard
FREQUENCT (IVITZ)	Quasi-peak	Average	Quasi-peak	Average	Stariuaru
0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	CISPR
0.50 -5.0	73.00	60.00	56.00	46.00	CISPR
5.0 -30.0	73.00	60.00	60.00	50.00	CISPR

0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	73.00	60.00	56.00	46.00	FCC
5.0 -30.0	73.00	60.00	60.00	50.00	FCC

#### Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " \* " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

#### The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

#### 3.1.2 TEST PROCEDURE


- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

#### 3.1.3 DEVIATION FROM TEST STANDARD

No deviation



#### 3.1.4 TEST SETUP



Note: 1.Support units were connected to second LISN.

2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

#### 3.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.



Shenzhen BCTC Technology Co., Ltd. Report No.: BCTC-15080188

## 3.1.6 TEST RESULTS

EUT:	Wireless Ultrasonic Sensor	Model Name. :	KEY-WT06
Temperature :	<b>26</b> ℃	Relative Humidity:	54%
Pressure :	1010hPa	Phase :	L
Test Voltage :	AC120V/60Hz	Test Mode:	Mode 1

NOTE: This EUT is powered by the battery only, this test item is not applicable.



#### 3.2 RADIATED EMISSION MEASUREMENT

#### 3.2.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies	Field Strength	Measurement Distance
(MHz)	(micorvolts/meter)	(meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

## LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

	Class A (dBu	ıV/m) (at 3M)	BM) Class B (dBuV/m) (at 3		
FREQUENCY (MHz)	PEAK	AVERAGE	PEAK	AVERAGE	
Above 1000	80	60	74	54	

#### Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RB / VB (emission in restricted	4 Mile / 4 Mile for Dook 4 Mile / 40/Jefor Average
band)	1 MHz / 1 MHz for Peak, 1 MHz / <i>10Hz</i> for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP



#### 3.2.2 TEST PROCEDURE

- a. The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported


#### 3.2.3 DEVIATION FROM TEST STANDARD

No deviation




## 3.2.4 TEST SETUP

## (A) Radiated Emission Test-Up Frequency Below 30MHz




# (B) Radiated Emission Test-Up Frequency 30MHz~1GHz





## (C) Radiated Emission Test-Up Frequency Above 1GHz



#### 3.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.



## 3.2.6 TEST RESULTS (BETWEEN 9KHZ - 30 MHZ)

EUT:	Wireless Ultrasonic Sensor	Model Name. :	KEY-WT06
Temperature:	<b>20</b> ℃	Relative Humidtity:	48%
Pressure:	1010 hPa	Test Voltage:	DC1.5V
Test Mode:	TX	Polarization:	

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
				PASS
				PASS

#### NOTE:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor =40 log (specific distance/test distance)(dB);

Limit line = specific limits(dBuv) + distance extrapolation factor.



# 3.2.7 TEST RESULTS (BETWEEN 30MHZ - 1GHZ)

EUT:	Wireless Ultrasonic Sensor	Model Name :	KEY-WT06
Temperature:	26℃	Relative Humidity:	54%
Pressure:	1010 hPa	Polarization:	Horizontal
Test Voltage :	DC1.5V		
Test Mode :	TX		

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Data eter Tuna
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Detector Type
53.8817	31.16	-10.93	20.23	40.00	-19.77	QP
99.8777	30.26	-16.49	13.77	43.50	-29.73	QP
130.3788	37.32	-14.08	23.24	43.50	-20.26	QP
195.1365	45.08	-15.90	29.18	43.50	-14.32	QP
325.5957	45.91	-11.92	33.99	46.00	-12.01	QP
625.0779	30.59	-5.52	25.07	46.00	-20.93	QP
915	103.72	-3.16	100.56	114	-13.44	PK
915	93.45	-3.16	90.29	94	-3.71	AV

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier. All interfaces was connected, and TX mode was link.

FCC Report

Tel: 400-788-9558 0755-33019988

Web:Http//www.bctc-lab.com



Shenzhen BCTC Technology Co., Ltd. Report No.: BCTC-15080188

EUT:	Wireless Ultrasonic Sensor	Model Name :	KEY-WT06
Temperature:	<b>26</b> ℃	Relative Humidity:	54%
Pressure:	1010 hPa	Polarization:	Vertical
Test Voltage :	DC1.5V		
Test Mode :	TX		

Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector Type
(MHz)	(dBµV)	(dB)	(dBµV/m)	(dBµV/m)	(dB)	Detector Type
33.7986	31.26	-8.43	22.83	40.00	-17.17	QP
129.9225	35.24	-14.11	21.13	43.50	-22.37	QP
207.8500	40.07	-15.98	24.09	43.50	-19.41	QP
325.5957	37.99	-11.92	26.07	46.00	-19.93	QP
554.8253	37.08	-6.96	30.12	46.00	-15.88	QP
972.3374	27.45	-0.39	27.06	54.00	-26.94	QP
915	104.36	-3.16	101.2	114	-12.8	PK
915	94.07	-3.16	90.91	94	-3.09	AV

Remark:

Factor = Antenna Factor + Cable Loss – Pre-amplifier. All interfaces was connected, and TX mode was link.



# 3.2.8 TEST RESULTS (ABOVE 1000 MHZ)

Normal Voltage

Report No.: BCTC-15080188

Polar	Frequency	Meter Reading	Factor	Emission Level	Limits	Margin	Detector
(H/V)	(MHz)	(dBuV)	(dB)	(dBuV/m)	(dBuV/m)	(dB)	Туре
V	1830	65.12	-3.57	61.55	74	-12.45	Pk
V	1830	53.05	-3.57	49.48	54	-4.52	AV
V	2745	64.74	-3.84	60.9	74	-13.1	Pk
V	2745	53.02	-3.84	49.18	54	-4.82	AV
V	3660	63.45	-4.59	58.86	74	-15.14	Pk
V	3660	54.32	-4.59	49.73	54	-4.27	AV
Н	1830	64.55	-3.62	60.93	74	-13.07	Pk
Н	1830	54.23	-3.62	50.61	54	-3.39	AV
Н	2745	65.02	-3.93	61.09	74	-12.91	Pk
Н	2745	53.82	-3.93	49.89	54	-4.11	AV
Н	3660	65.12	-3.57	61.55	74	-12.45	Pk
Н	3660	53.05	-3.57	49.48	54	-4.52	AV

## Remark:

Absolute Level= ReadingLevel+ Factor, Margin= Limit- Absolute Level



# 4. 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE APPLICABLE STANDARD

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

#### **TEST PROCEDURE**

- a. The measuring distance of at 3 m shall be used for measurements at frequency up to 25GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The height of the equipment or of the substitution antenna shall be 1.5 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.
- g. For the radiated emission test above 1GHz:
  - Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response.
  - The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane. Note:

Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported



## **4.1 DEVIATION FROM STANDARD**

No deviation.

#### **4.2 TEST SETUP**

#### 4.3 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

## 4.4 TEST RESULTS

EUT:	Balight	Model Name :	LK152001-RD
Temperature:	<b>25</b> ℃	Relative Humidity:	60%
Pressure:	1012 hPa	Test Voltage :	DC1.5V
Test Mode :	TX Mode		

Frequency	Antenna polarization	Emission	Limit	Result
(MHz)	(H/V)	(dBuV/m)	(dBuV/m)	Pass
902	Н	40.25	46.00	Pass
902	V	40.19	46.00	Pass
928	Н	40.38	46.00	Pass
928	V	40.08	46.00	Pass

If the PK measured levels comply with average limit, then the average level were deemed to comply with average limit.



#### 5. BANDWIDTH TEST

#### 5.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.249) , Subpart C				
Section Test Item Frequency Range (MHz) Result				
15.249	Bandwidth	900~928	PASS	


#### **5.1.1 TEST PROCEDURE**

- 1. Set resolution bandwidth (RBW) = 1-5% or DTS BW, not to exceed 100 kHz.
- 2. Set the video bandwidth (VBW)  $\geq$  3 x RBW.
- 3. Detector = Peak.
- 4. Trace mode = max hold.
- 5. Sweep = auto couple.
- 6. Allow the trace to stabilize.
- 7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

#### **5.1.2 DEVIATION FROM STANDARD**

No deviation.

#### 5.1.3 TEST SETUP



#### **5.1.4 EUT OPERATION CONDITIONS**

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.


FCC Report Tel: 400-788-9558 0755-33019988



#### 5.1.5 TEST RESULTS

EUT:	Wireless Ultrasonic Sensor	Model Name :	KEY-WT06
Temperature:	<b>25</b> ℃	Relative Humidity:	60%
Pressure :	1012 hPa	Test Voltage :	DC1.5V
Test Mode :	TX Mode		

Channel	Frequency (MHz)	20dB bandwidth (MHz)
1	915	0.474





#### **6. ANTENNA REQUIREMENT**

#### **6.1 STANDARD REQUIREMENT**

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

#### **6.2 EUT ANTENNA**

The EUT antenna is Integrated antenna. It comply with the standard requirement.

FCC Report Tel: 400-788-9558 0755-33019988 Web:Http//www.bctc-lab.com



# 7. EUT TEST PHOTO

RΕ







## 8. PHOTO OF THE EUT

