

THEDREAMTECH CO.LTD.

To: Federal Communications Commission
7435 Oakland Mills Road
Columbia, MD

FCC ID: 2AFOVTHEDRTCWCTT051

To Whom It May Concern:

This letter is to ascertain that **THEDREAMTECH CO.LTD.** Product **Slim Wireless Charger, 2AFOVTHEDRTCWCTT051**, has been the units used for conducting FCC compliance testing, and it meets KDB 680106 Clause 5(2) all 6 conditions as stated below hence PBA is not required.

1	Power transfer frequency is less than 1 MHz → The power transfer frequency of DUT(Device Under Test) is between 110 kHz and 205 kHz.
2	Output power from each primary coil is less than 5 watts → Output power from each coils are Max. 5 watts.
3	The transfer system includes only single primary and secondary coils. This includes charging systems that may have multiple primary coils and clients that are able to detect and allow coupling only between individual pairs of coils → The DUT(Device Under Test) are consist of one charging coil use. So the DUT can detect and allow coupling only between TX and RX Coil.
4	Client device is inserted in or placed directly in contact with the transmitter → When the client device is placed directly in contact with transmitter, then charging is able to start.
5	The maximum coupling surface area of the transmit (charging) device is between 60 cm ² and 400 cm ² . → The Maximum coupling surface area of the charging transmit is 54.76 cm ² .
6	Aggregate leakage fields at 10 cm surrounding the device from all simultaneous transmitting coils are demonstrated to be less than 30% of the MPE limit. → The highest leakage filed is less than 30 % of the MPE(Maximum Permissible Exposure) limit.

If you have any question or concerns, pls. contact us.

Sincerely,



Client's signature

Name: Song Hee-Jun

Address: 603ho, B Dong, Dontankiseong-ro 316, Hwaseong-si, Gyeonggi-do, Korea