## RF Exposure evaluation

According to KDB 447498 D01 General RF Exposure Guidance v05 The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq$  50 mm are determined by: [(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]  $\cdot$  [ $\sqrt{f(GHz)}$ ]  $\leq$  3.0 for 1-g SAR and  $\leq$  7.5 for 10-g extremity SAR, where

- f(GHz) is the RF channel transmit frequency in GHz
- ${}^{\raisebox{-.4ex}{$\scriptscriptstyle \bullet$}}$  Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

```
eirp = pt x gt = (EXd)^2/30

where:

pt = transmitter output power in watts,

gt = numeric gain of the transmitting antenna (unitless),

E = electric field strength in V/m, --- 10^{((dBuV/m)/20)}/10^6

d = measurement distance in meters (m)---3m

So pt = (EXd)^2/30 x gt

Ant gain 2dBi ;so Ant numeric gain=1.58

Field strength =103.52 dBuV/m @3m

So Pt={ [10^{(103.52-/20)}/10^6 x3]^2/30x1.58 }x1000 mW = 4.27 mW

So ( 4.27 mW/5mm)x \sqrt{2}.403 GHz = 1.3 < 3
```

Then SAR evaluation is not required