

# RF EXPOSURE REPORT

Applicant	DIAMOND PRODUCT LLC CO. JIMMYJANE
Address	12 EAST SIR FRANCIS DRAKE BLVD. STE B1 LARKSPUR, CA

Manufacturer or Supplier	Sheenway Asia Ltd.
Address	Room 1313,13/F, Austin Tower, 22-26 Austin Avenue, Tsimshatsui, Hong Kong
Product	Form Vibrator
Brand Name	JIMMYJANE
Model	Form 8
Additional Model & Model Difference	N/A
Date of tests	Aug. 02, 2015 ~ Aug. 28, 2015

- FCC Part 2 (Section 2.1091)
- **KDB 447498 D03**
- **☐** IEEE C95.1

#### CONCLUSION: The submitted sample was found to **COMPLY** with the test requirement

T	
Tested by Blue Zheng	Approved by Chris Chen
Project Engineer / EMC Department	Assistant Manager / EMC Department

Date: Aug. 28, 2015

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification



### Test Report No.: FS150818N027

## **Table of Contents**

RELE	ASE CONTROL RECORD	3
1.	CERTIFICATION	4
2.	RF EXPOSURE DEFINE	.5
3.	CLASSIFICATION	.5
	SAR TEST EXCLUSION THRESHOLDS	

Tel: +86 769 8593 5656 Fax: +86 769 8593 1080

Email: <a href="mailto:customerservice.dg@cn.bureauveritas.com">customerservice.dg@cn.bureauveritas.com</a>



## **RELEASE CONTROL RECORD**

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
FS150818N027	Original release	Aug. 28, 2015

No. 34, Chenwulu Section, Guantai Rd., Houjie Town, Dongguan City, Guangdong 523942, China

Fax: +86 769 8593 1080

Tel: +86 769 8593 5656

Email: customerservice.dg@cn.bureauveritas.com

Tillia <u>customerservice.ag@cn.bureauventas.cc</u>



### 1. CERTIFICATION

FCC ID:	2AFQJFORM8
PRODUCT:	Form Vibrator
BRAND NAME:	JIMMYJANE
MODEL NO.:	Form 8
ADDITIONAL NO.:	N/A
TEST SAMPLE:	Engineering Sample
APPLICANT:	DIAMOND PRODUCT LLC CO. JIMMYJANE
STANDARDS:	FCC Part 2 (Section 2.1091)
	KDB 447498 D03
	IEEE C95.1

Tel: +86 769 8593 5656 Fax: +86 769 8593 1080

Email: <a href="mailto:customerservice.dg@cn.bureauveritas.com">customerservice.dg@cn.bureauveritas.com</a>



Test Report No.: FS150818N027

#### 2. RF EXPOSURE DEFINE

The corresponding SAR Exclusion Threshold condition, listed below:

1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]  $\cdot [\sqrt{f(GHz)}] \le 3.0$  for 1-g SAR and  $\le 7.5$  for 10-g extremity SAR,16 where

- f(GHz) is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is  $\leq$  50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

- 2) At 100 MHz to 6 GHz and for test separation distances > 50 mm, the SAR test exclusion threshold is determined according to the following:
  - a) [Threshold at 50 mm in step 1) + (test separation distance 50 mm)-( f(MHz)/150)] mW, at 100MHz to 1500 MHz
  - b) [Threshold at 50 mm in step 1) + (test separation distance 50 mm)·10] mW at > 1500 MHz and ≤ 6 GHz
- 3) At frequencies below 100 MHz, the following may be considered for SAR test exclusion.
  - a) The threshold at the corresponding test separation distance at 100 MHz in step 2) is multiplied by [1 + log(100/f(MHz))] for test separation distances > 50 mm and < 200 mm.
  - b) The threshold determined by the equation in a) for 50 mm and 100 MHz is multiplied by ½ for test separation distances ≤ 50 mm.
  - c) SAR measurement procedures are not established below 100 MHz. When SAR test exclusion cannot be applied, a KDB inquiry is required to determine SAR evaluation requirements for any test results to be acceptable.

#### 3. CLASSIFICATION

The antenna of this product, under normal use condition, is at less than 20cm away from the body of the user. So, this device is classified as **Portable Device**.

Tel: +86 769 8593 5656 Fax: +86 769 8593 1080

Email: customerservice.dg@cn.bureauveritas.com

Page 5 of 6 Report Version 1



### 4. SAR TEST EXCLUSION THRESHOLDS

According to the KDB 447498:

The maximun Average output power specified is 6.21dBm = 4.18mW

The SAR Exclusion Threshold Level:

- = 3.0 \* (min. test separation distance, mm) / sqrt(freq. in GHz)
- = 3.0 \* 5 / sqrt (2.480) mW
- = 9.53 mW

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.

Email: customerservice.dg@cn.bureauveritas.com

Tel: +86 769 8593 5656

Fax: +86 769 8593 1080