

TEST REPORT

Applicant : WESTUNITIS CO., LTD.
Address : 29F GRAND FRONT OSAKA South Building, 4-20 Ofukacho, Kita-ku, Osaka 530-0011 JAPAN

Products : InfoLinker
Model No. : WUZ-01B-NB01
Serial No. : 501550014

FCC ID : 2AFRZWUZ-01B-NB01

Test Standard : CFR 47 FCC Rules and Regulations Part 15

Test Results : Passed

Date of Test : October 14 ~ December 2, 2015



Kousei Shibata
Manager
Japan Quality Assurance Organization
KITA-KANSAI Testing Center
SAITO EMC Branch
7-3-10, Saito-asagi, Ibaraki-shi, Osaka 567-0085, Japan



- The measurement values stated in Test Report was made with traceable to National Institute of Advanced Industrial Science and Technology (AIST) of Japan and National Institute of Information and Communications Technology (NICT) of Japan.
- The applicable standard, testing condition and testing method which were used for the tests are based on the request of the applicant.
- The test results presented in this report relate only to the offered test sample.
- The contents of this test report cannot be used for the purposes, such as advertisement for consumers.
- This test report shall not be reproduced except in full without the written approval of JQA.
- VLAC does not approve, certify or warrant the product by this test report.

TABLE OF CONTENTS

		Page
1	Description of the Equipment Under Test	3
2	Summary of Test Results	4
3	Test Procedure.....	5
4	Test Location	5
5	Recognition of Test Laboratory	5
6	Description of Test Setup	6
7	Test Requirements	9

DEFINITIONS FOR ABBREVIATION AND SYMBOLS USED IN THIS TEST REPORT

EUT	: Equipment Under Test	EMC	: Electromagnetic Compatibility
AE	: Associated Equipment	EMI	: Electromagnetic Interference
N/A	: Not Applicable	EMS	: Electromagnetic Susceptibility
N/T	: Not Tested		

- indicates that the listed condition, standard or equipment is applicable for this report.
 - indicates that the listed condition, standard or equipment is not applicable for this report.

1 Description of the Equipment Under Test

1. Manufacturer : WESTUNITIS CO., LTD.
29F GRAND FRONT OSAKA South Building, 4-20 Ofukacho,
Kita-ku, Osaka 530-0011 JAPAN

2. Products : InfoLinker

3. Model No. : WUZ-01B-NB01

4. Serial No. : 501550014

5. Product Type : Mass Production

6. Date of Manufacture : June, 2015

7. Power Rating : 3.7VDC (Lithium-ion Battery WHB-001 300mAh)
5.0VDC (USB)

8. Grounding : None

9. Transmitting Frequency : 2402.0 MHz(00CH) – 2480.0MHz(78CH)

10. Receiving Frequency : 2402.0 MHz(00CH) – 2480.0MHz(78CH)

11. Max. RF Output Power : 7.74dBm(Measure Value)

12. Antenna Type : 1/2 λ Type Antenna (Integral)

13. Antenna Gain : -3.0 dBi

14. Category : Spread Spectrum Transmitter(FHSS)

15. EUT Authorization : Certification

16. Received Date of EUT : October 9, 2015

17. Channel Plan

The carrier spacing is 1 MHz.

The carrier frequency is designated by the absolute frequency channel number (ARFCN).

The carrier frequency is expressed in the equation shown as follows:

Normal Mode:

Transmitting Frequency (in MHz) = 2402.0 + n

Receiving Frequency (in MHz) = 2402.0 + n

where, n : channel number ($0 \leq n \leq 78$)

2 Summary of Test Results

Applied Standard : CFR 47 FCC Rules and Regulations Part 15
Subpart C – Intentional Radiators

The EUT described in clause 1 was tested according to the applied standard shown above.
Details of the test configuration is shown in clause 6.

The conclusion for the test items of which are required by the applied standard is indicated under the test result.

- The test result was **passed** for the test requirements of the applied standard.
- The test result was **failed** for the test requirements of the applied standard.
- The test result was **not judged** the test requirements of the applied standard.

In the approval of test results,

- Determining compliance with the limits in this report was based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.
- No deviations were employed from the applied standard.
- No modifications were conducted by JQA to achieve compliance to the limitations.

Reviewed by:



Shigeru Osawa
Deputy Manager
JQA KITA-KANSAI Testing Center
SAITO EMC Branch

Tested by:



Takeshi Choda
Assistant Manager
JQA KITA-KANSAI Testing Center
SAITO EMC Branch

3 Test Procedure

Test Requirements : §15.247, §15.207 and §15.209

Test Procedure : ANSI C63.10-2013
Testing unlicensed wireless devices.

FCC Public Notice DA 00-705, released March 30, 2000.

KDB 447498
RF exposure and equipment authorization requirements

4 Test Location

Japan Quality Assurance Organization (JQA)
KITA-KANSAI Testing Center
7-7, Ishimaru, 1-chome, Minoh-shi, Osaka, 562-0027, Japan
SAITO EMC Branch
7-3-10, Saito-asagi, Ibaraki-shi, Osaka 567-0085, Japan

5 Recognition of Test Laboratory

JQA KITA-KANSAI Testing Center SAITO EMC Branch is accredited under ISO/IEC 17025 by following accreditation bodies and the test facility is registered by the following bodies.

VLAC Accreditation No. : VLAC-001-2 (Expiry date : March 30, 2016)
VCCI Registration No. : A-0002 (Expiry date : March 30, 2016)
BSMI Registration No. : SL2-IS-E-6006, SL2-IN-E-6006, SL2-R1/R2-E-6006, SL2-A1-E-6006
(Expiry date : September 14, 2016)
IC Registration No. : 2079E-3, 2079E-4 (Expiry date : July 16, 2017)

Accredited as conformity assessment body for Japan electrical appliances and material law by METI.
(Expiry date : February 22, 2016)

6 Description of Test Setup

6.1 Test Configuration

The equipment under test (EUT) consists of :

	Item	Manufacturer	Model No.	Serial No.	FCC ID
A	InfoLinker	WESTUNITIS	WUZ-01B-NB01	501550014	2AFRZWUZ-01B-NB01
B	Li-ion Battery	WESTUNITIS	WHLB-001	--	N/A

The auxiliary equipment used for testing :


	Item	Manufacturer	Model No.	Serial No.	FCC ID
C	Earphone	--	--	--	N/A
D	Note PC	Fujitsu	FMV A 05010P	CP660964-01	None
E	AC Adapter (for PC)	Fujitsu	ADP-65JH AB	CP500588-01	N/A
F	Mouse	Hewlett Packard	M-UAE96	265986-011	N/A
G	Smart Phone	Sharp	SH-06E	--	None

Type of Cable:


No.	Description	Identification (Manu. etc.)	Connector Shielded	Cable Shielded	Ferrite Core	Length (m)
1	Earphone cable	--	--	NO	NO	1.2
2	USB Cable1	--	YES	YES	NO	1.2
3	USB Cable2	--	YES	YES	NO	1.8
4	DC Cable	--	--	NO	YES	1.8
5	AC Cable	--	--	NO	NO	1.0

6.2 Test Arrangement (Drawings)


a) Single Unit



b) Earphone used



c) Bluetooth Tx and USB Charging



6.3 Operating Condition

Power Supply Voltage : 3.7VDC (for Battery)
5.0VDC (for USB)

Transmitting/Receiving
Bluetooth 4.0 + EDR
Transmitting frequency : 2402.0 MHz(0CH) – 2480.0 MHz(78CH)
Receiver frequency : 2402.0 MHz(0CH) – 2480.0 MHz(78CH)

The test were carried under 2 mode shown as follows:

- 1) BDR
- 2) EDR

In Spurious Emissions(Conducted) and Radiated Emissions, the worst case is BDR mode.

Modulation Type

1. DH1/ DH3/ DH5 Packet (Modulation Type : GFSK)
2. 2DH1/ 2DH3/ 2DH5 Packet (Modulation Type : pi/4-DQPSK)
3. 3DH1/ 3DH3/ 3DH5 Packet (Modulation Type : 8DPSK)

Other Clock Frequency
1.5GHz (CPU)

The EUT was rotated through three orthogonal axis (X, Y and Z axis) in radiated measurement.
The EUT with temporary antenna port was used in conducted measurement.

The test were carried out using the following test program supplied by applicant;

- Software Name: Real Time Tuning Tool
- Software Version: Version 2.0.0.55
- Storage Location: Controller PC

7 Test Requirements

7.0 Summary of the Test Results

Test Item	FCC Specification	Reference of the Test Report	Results	Remarks
Antenna Requirement	Section 15.203	Section 1.12	Passed	-
Channel Separation	Section 15.247(a)(1)	Section 7.1	Passed	-
Minimum Hopping Channel	Section 15.247(a)(1)(iii)	Section 7.2	Passed	-
Occupied Bandwidth	Section 15.247(a)(1)	Section 7.3	Passed	-
Dwell Time	Section 15.247(a)(1)(iii)	Section 7.4	Passed	-
Peak Output Power (Conduction)	Section 15.247(b)(1)	Section 7.5	Passed	-
Peak Power Density (Conduction)	Section 15.247(e)	-	-	-
Spurious Emissions (Conduction)	Section 15.247(d)	Section 7.7	Passed	-
AC Powerline Conducted Emission	Section 15.207	Section 7.8	Passed	-
Radiated Emission	Section 15.247(d)	Section 7.9	Passed	-
SAR Test Exclusion	Section 15.247(i)	Section 7.10	Passed	-

7.1 Channel Separation

For the requirements, - Applicable [- Tested. - Not tested by applicant request.]
 - Not Applicable

7.1.1 Test Results

For the standard, - Passed - Failed - Not judged

Channel Separation is 1.000 MHz
Channel Separation (Inquiry) is 2.000 MHz

Uncertainty of Measurement Results ± 0.9 %(2σ)

Remarks : _____


7.1.2 Test Instruments

Shielded Room S4				
Type	Model	Serial No. (ID)	Manufacturer	Cal. Due
Spectrum Analyzer	E4446A	US44300388 (A-39)	Agilent	2016/08/11
RF Cable	SUCOFLEX102	14253/2 (C-52)	HUBER+SUHNER	2016/08/16
Attenuator	54A-10	W5675 (D-28)	Weinschel	2016/08/16

NOTE : The calibration interval of the above test instruments is 12 months.

7.1.3 Test Method and Test Setup (Diagrammatic illustration)

The test system is shown as follows:



The setting of the spectrum analyzer are shown as follows:

Res. Bandwidth	100 kHz
Video Bandwidth	300 kHz
Span	3 MHz / 5 MHz
Sweep Time	AUTO
Trace	Maxhold


7.1.4 Test Data

Test Date :October 14, 2015
Temp.:26°C, Humi:45%


Mode of EUT	Channel Separation (MHz)	Limit* (MHz)
Hopping	1.000	0.863
Inquiry	2.000	0.507

Note: Two-thirds of the maximum 20 dB bandwidth of the hopping channel or 25 kHz (whichever is greater). Refer to the section 7.3.

Mode of EUT : Hopping



Mode of EUT : Inquiry



7.2 Minimum Hopping Channel

For the requirements, - Applicable [- Tested. - Not tested by applicant request.]
 - Not Applicable

7.2.1 Test Results

For the standard, - Passed - Failed - Not judged

Number of Channel is	79
Number of Channel (Inquiry) is	32
Number of Channel (AFH) is	20

Remarks : _____


7.2.2 Test Instruments

Shielded Room S4				
Type	Model	Serial No. (ID)	Manufacturer	Cal. Due
Spectrum Analyzer	E4446A	US44300388 (A-39)	Agilent	2016/08/11
RF Cable	SUCOFLEX102	14253/2 (C-52)	HUBER+SUHNER	2016/08/16
Attenuator	54A-10	W5675 (D-28)	Weinschel	2016/08/16

NOTE : The calibration interval of the above test instruments is 12 months.

7.2.3 Test Method and Test Setup (Diagrammatic illustration)

The test system is shown as follows:



The setting of the spectrum analyzer are shown as follows:


Res. Bandwidth	300 kHz
Video Bandwidth	300 kHz
Span	30 MHz
Sweep Time	AUTO
Trace	Maxhold

7.2.4 Test Data


Test Date : October 14, 2015
Temp. : 26°C, Humi : 45%

Mode of EUT	Minimum Hopping Channel	Limit
Hopping	79	15
Inquiry	32	15
AFH(minimum)	20	15


Mode of EUT : Hopping(1/3)




Mode of EUT : Hopping(2/3)




Mode of EUT : Hopping(3/3)




Mode of EUT : Inquiry(1/3)




Mode of EUT : Inquiry(2/3)




Mode of EUT : Inquiry(3/3)




Mode of EUT : AFH(minimum)(1/3)



Mode of EUT : AFH(minimum) (2/3)



Mode of EUT : AFH(minimum) (3/3)



7.3 Occupied Bandwidth

For the requirements, - Applicable [- Tested. - Not tested by applicant request.]
 - Not Applicable

7.3.1 Test Results

For the standard, - Passed - Failed - Not judged

The 99% Bandwidth is 1193.9 kHz at 2441.0 MHz
The 20dB Bandwidth is 1295.0 kHz at 2480.0 MHz

Uncertainty of Measurement Results ± 0.9 %(2σ)

Remarks : _____


7.3.2 Test Instruments

Shielded Room S4				
Type	Model	Serial No. (ID)	Manufacturer	Cal. Due
Spectrum Analyzer	E4446A	US44300388 (A-39)	Agilent	2016/08/11
Attenuator	54A-10	W5675 (D-28)	Weinschel	2016/08/16
RF Cable	SUCOFLEX102	14253/2 (C-52)	HUBER+SUHNER	2016/08/16

NOTE : The calibration interval of the above test instruments is 12 months.

7.3.3 Test Method and Test Setup (Diagrammatic illustration)

The test system is shown as follows:



The setting of the spectrum analyzer are shown as follows:

Res. Bandwidth	30 kHz
Video Bandwidth	100 kHz
Span	2 MHz / 3 MHz
Sweep Time	AUTO
Trace	Maxhold

7.3.4 Test Data

Mode of EUT : BDR+EDR

Test Date :October 14, 2015Temp.:26°C, Humi:45%

The resolution bandwidth was set to about 1% of emission bandwidth, -20dBc display line was placed on the screen (or 99% bandwidth), the occupied bandwidth is the delta frequency between the two points where the display line intersects the signal trace.

1)Packet Setting : DH5(Modulation type : GFSK)

Channel	Frequency (MHz)	99% Bandwidth (kHz)	-20dBc Bandwidth (kHz)	Two-thirds of the 20 dB bandwidth (kHz)
00	2402.0	847.9	956.2	637.5
39	2441.0	840.8	860.4	573.6
78	2480.0	834.0	859.5	573.0

2)Packet Setting : 2DH5(Modulation type : pi/4-DQPSK)



Channel	Frequency (MHz)	99% Bandwidth (kHz)	-20dBc Bandwidth (kHz)	Two-thirds of the 20 dB bandwidth (kHz)
00	2402.0	1172.9	1277.0	851.3
39	2441.0	1177.7	1276.0	850.7
78	2480.0	1185.1	1271.0	847.3


3)Packet Setting : 3DH5(Modulation type : 8DPSK)

Channel	Frequency (MHz)	99% Bandwidth (kHz)	-20dBc Bandwidth (kHz)	Two-thirds of the 20 dB bandwidth (kHz)
00	2402.0	1180.7	1286.0	857.3
39	2441.0	1193.9	1294.0	862.7
78	2480.0	1193.2	1295.0	863.3

1)Packet Setting : DH5(Modulation type : GFSK)



Low Channel


Transmit Freq Error -10.056 kHz
Occupied Bandwidth 956.175 kHzTransmit Freq Error -10.796 kHz
Occupied Bandwidth 860.423 kHz



2)Packet Setting : 2DH5(Modulation type : pi/4-DQPSK)



Low Channel


Transmit Freq Error -13.486 kHz
Occupied Bandwidth 1.277 MHzTransmit Freq Error -14.571 kHz
Occupied Bandwidth 1.276 MHz



3)Packet Setting : 3 DH5(Modulation type : 8DPSK)

Low Channel






Mode of EUT : Inquiry

Test Date :October 14, 2015
Temp.:26°C, Humi:45%

The resolution bandwidth was set to about 1% of emission bandwidth, -20dBc display line was placed on the screen (or 99% bandwidth), the occupied bandwidth is the delta frequency between the two points where the display line intersects the signal trace.

Frequency (MHz)	99% Bandwidth (kHz)	-20dBc Bandwidth (kHz)	Two-thirds of the 20 dB bandwidth (kHz)
2441.0	831.3	760.6	507.1



7.4 Dwell Time

For the requirements, - Applicable [- Tested. - Not tested by applicant request.]
 - Not Applicable

7.4.1 Test Results

For the standard, - Passed - Failed - Not judged

Dwell Time is 310.0 msec
Dwell Time (Inquiry) is 78.8 msec
Dwell Time (AFH) is 310.0 msec

Uncertainty of Measurement Results ± 0.6 %(2o)

Remarks : _____


7.4.2 Test Instruments

Shielded Room S4				
Type	Model	Serial No. (ID)	Manufacturer	Cal. Due
Spectrum Analyzer	E4446A	US44300388 (A-39)	Agilent	2016/08/11
Attenuator	54A-10	W5675 (D-28)	Weinschel	2016/08/16
RF Cable	SUCOFLEX102	14253/2 (C-52)	HUBER+SUHNER	2016/08/16

NOTE : The calibration interval of the above test instruments is 12 months.

7.4.3 Test Method and Test Setup (Diagrammatic illustration)

The test system is shown as follows:



The setting of the spectrum analyzer are shown as follows:


Res. Bandwidth	1 MHz
Video Bandwidth	1 MHz
Span	Zero Span

7.4.4 Test Data

Test Date :October 14, 2015
Temp.:26°C, Humi:45%

Mode of EUT	Dwell Time (msec)	Limit (msec)
DH1	129.0	400
DH3	265.0	400
DH5	310.0	400
Inquiry	78.8	400

DH1(Modulation type : GFSK)




Note : The system makes worst case 1600 hops per second or 1 time slot has a length of 625 μ s with 79 channels. A DH1 Packet need 1 time slot for transmitting and 1 time slot for receiving. Then the system makes worst case 800 hops per second with 79 channels. So the system has each channel 10.1266 times per second and so for 31.6 seconds the system have 320.0 times of appearance.

Each tx-time per appearance is 0.403 ms.


Dwell time = 320.0 * 0.403 = 129.0 ms

DH3(Modulation type : GFSK)




Note : A DH3 Packet need 3 time slot for transmitting and 1 time slot for receiving. Then the system makes worst case 400 hops per second with 79 channels. So the system have each channel 5.063 times per second and so for 31.6 seconds the system have 160.0 times of appearance.
Each tx-time per appearance is 1.656 ms.
Dwell time = $160.0 * 1.656 = 265.0$ ms

DH5(Modulation type : GFSK)



Note : A DH5 Packet need 5 time slot for transmitting and 1 time slot for receiving. Then the system makes worst case 266.667 hops per second with 79 channels. So the system have each channel 3.3755 times per second and so for 31.6 seconds the system have 106.7 times of appearance. Each tx-time per appearance is 2.905 ms.
Dwell time = 106.7 * 2.905 = 310.0 ms

Inquiry



Note : The system have 32 hopping channel in Inquiry mode.

The time period = $32 * 0.4 = 12.8$ seconds


In maximum case the Bluetooth system have three blocks of 2560 ms in 12.8 s period. One block has 256 burst at each hopping channel.

Each tx-time per appearance is 0.1026 ms.

Dwell time = $0.1026 * 256 * 3 = 78.8$ ms


Mode of EUT	Dwell Time (msec)	Limit (msec)
DH1(AFH)	129.0	400
DH3(AFH)	265.0	400
DH5(AFH)	310.0	400

DH1(AFH mode, Modulation type : GFSK)




Note : The system makes worst case 1600 hops per second or 1 time slot has a length of 625 μ s with 79 channels. A DH1 Packet need 1 time slot for transmitting and 1 time slot for receiving. Then the system makes worst case 800 hops per second with 20 channels. So the system has each channel 40 times per second and so for 8 seconds the system have 320.0 times of appearance. Each tx-time per appearance is 0.403 ms.
Dwell time = 320.0 * 0.403 = 129.0 ms

DH3(AFH mode, Modulation type : GFSK)



Note : A DH3 Packet need 3 time slot for transmitting and 1 time slot for receiving. Then the system makes worst case 400 hops per second with 20 channels. So the system have each channel 20 times per second and so for 8 seconds the system have 160.0 times of appearance.
Each tx-time per appearance is 1.656 ms.
Dwell time = $160.0 * 1.656 = 265.0$ ms

DH5(AFH mode, Modulation type : GFSK)



Note : A DH5 Packet need 5 time slot for transmitting and 1 time slot for receiving. Then the system makes worst case 266.667 hops per second with 20 channels. So the system have each channel 13.33335 times per second and so for 8 seconds the system have 106.7 times of appearance. Each tx-time per appearance is 2.905 ms.
Dwell time = $106.7 \times 2.905 = 310.0$ ms

7.5 Peak Output Power(Conduction)

For the requirements, - Applicable [- Tested. - Not tested by applicant request.]
 - Not Applicable

7.5.1 Test Results

For the standard, - Passed - Failed - Not judged

Peak Output Power is 7.74 dBm at 2402.0 MHz

Uncertainty of Measurement Results ± 0.9 dB(2σ)

Remarks : _____


7.5.2 Test Instruments

Shielded Room S4				
Type	Model	Serial No. (ID)	Manufacturer	Cal. Due
Power Meter	N1911A	GB45100291 (B-63)	Agilent	2016/07/16
Power Sensor	N1921A	US44510470 (B-64)	Agilent	2016/07/16
Attenuator	54A-10	W5675 (D-28)	Weinschel	2016/08/16

NOTE : The calibration interval of the above test instruments is 12 months.

7.5.3 Test Method and Test Setup (Diagrammatic illustration)

The Conducted RF Power Output was measured with a power meter, one attenuator and a short, low loss cable.



7.5.4 Test Data

1) DH5 (Modulation type : GFSK)

Test Date: October 14, 2015
Temp.: 26 °C, Humi: 45 %

CH	Transmitting Frequency [MHz]	Correction Factor [dB]	Meter Reading [dBm]	Conducted Peak Output Power		Limits [dBm]	Margin [dB]
				[dBm]	[mW]		
00	2402	9.64	-1.90	7.74	5.94	20.97	+13.23
39	2441	9.65	-2.10	7.55	5.69	20.97	+13.42
78	2480	9.65	-3.23	6.42	4.39	20.97	+14.55

Calculated result at 2402.000 MHz, as the worst point shown on underline:

$$\begin{array}{rcl} \text{Correction Factor} & = & 9.64 \text{ dB} \\ +) \underline{\text{Meter Reading}} & = & -1.90 \text{ dBm} \\ \text{Result} & = & 7.74 \text{ dBm} = 5.94 \text{ mW} \end{array}$$

Minimum Margin: $20.97 - 7.74 = 13.23$ (dB)

NOTES

1. The correction factor shows the attenuation pad loss including the short, low loss cable or adapter.
2. Setting of measuring instrument(s) :

Detector Function	Video B.W.
Peak	Off

2) 2DH5(Modulation type : pi/4-DQPSK)

Test Date: October 14, 2015
Temp.: 26 °C, Humi: 45 %

CH	Transmitting Frequency [MHz]	Correction Factor [dB]	Meter Reading [dBm]	Conducted Peak Output Power [dBm] [mW]		Limits [dBm]	Margin [dB]
				Peak [dBm]	Output [mW]		
00	2402	9.64	-5.51	4.13	2.59	20.97	+16.84
39	2441	9.65	-5.14	4.51	2.82	20.97	+16.46
78	2480	9.65	-6.85	2.80	1.91	20.97	+18.17

Calculated result at 2441.000 MHz, as the worst point shown on underline:

$$\begin{array}{lcl} \text{Correction Factor} & = & 9.65 \text{ dB} \\ +) \underline{\text{Meter Reading}} & = & \underline{-5.14 \text{ dBm}} \\ \text{Result} & = & 4.51 \text{ dBm} = 2.82 \text{ mW} \end{array}$$

Minimum Margin: $20.97 - 4.51 = 16.46 \text{ (dB)}$

NOTES

1. The correction factor shows the attenuation pad loss including the short, low loss cable or adapter.
2. Setting of measuring instrument(s) :

Detector Function	Video B.W.
Peak	Off

3) 3DH5(Modulation type : 8DPSK)

Test Date: October 14, 2015
Temp.: 26 °C, Humi: 45 %

CH	Transmitting Frequency [MHz]	Correction Factor [dB]	Meter Reading [dBm]	Conducted Peak Output Power [dBm] [mW]		Limits [dBm]	Margin [dB]
				Peak [dBm]	Output [mW]		
00	2402	9.64	-4.92	4.72	2.96	20.97	+16.25
39	2441	9.65	-4.66	4.99	3.16	20.97	+15.98
78	2480	9.65	-6.59	3.06	2.02	20.97	+17.91

Calculated result at 2441.000 MHz, as the worst point shown on underline:

$$\begin{array}{lcl} \text{Correction Factor} & = & 9.65 \text{ dB} \\ +) \underline{\text{Meter Reading}} & = & \underline{-4.66 \text{ dBm}} \\ \text{Result} & = & 4.99 \text{ dBm} = 3.16 \text{ mW} \end{array}$$

Minimum Margin: $20.97 - 4.99 = 15.98 \text{ (dB)}$

NOTES

1. The correction factor shows the attenuation pad loss including the short, low loss cable or adapter.
2. Setting of measuring instrument(s) :

Detector Function	Video B.W.
Peak	Off

7.6 Peak Power Density(Conduction)

For the requirements, - Applicable [- Tested. - Not tested by applicant request.]
 - Not Applicable

Remarks : _____

7.7 Spurious Emissions(Conduction)

For the requirements, - Applicable [- Tested. - Not tested by applicant request.]
 - Not Applicable

7.7.1 Test Results

For the standard, - Passed - Failed - Not judged

Uncertainty of Measurement Results	9 kHz – 1 GHz	<u>± 1.4</u>	dB(2σ)
	1 GHz – 18 GHz	<u>± 1.7</u>	dB(2σ)
	18 GHz – 40 GHz	<u>± 2.3</u>	dB(2σ)

Remarks : _____


7.7.2 Test Instruments

Shielded Room S4				
Type	Model	Serial No. (ID)	Manufacturer	Cal. Due
Spectrum Analyzer	E4446A	US44300388 (A-39)	Agilent	2016/08/11
Attenuator	54A-10	W5675 (D-28)	Weinschel	2016/08/16
RF Cable	SUCOFLEX102	14253/2 (C-52)	HUBER+SUHNER	2016/08/16

NOTE : The calibration interval of the above test instruments is 12 months.

7.7.3 Test Method and Test Setup (Diagrammatic illustration)

The test system is shown as follows:




The setting of the spectrum analyzer are shown as follows:

Frequency Range	30 MHz - 25 GHz	Band-Edge
Res. Bandwidth	100 kHz	100 kHz
Video Bandwidth	300 kHz	300 kHz
Sweep Time	AUTO	AUTO
Trace	Maxhold	Maxhold


7.7.4 Test Data

Mode of EUT : BDR (worst case)


Low Channel



Middle Channel




High Channel




Band-Edge Emission


Low Channel(Hopping off), Band-Edge Emission




High Channel(Hopping off), Band-Edge Emission



Low Channel(Hopping on), Band-Edge Emission



High Channel(Hopping on), Band-Edge Emission



7.8 AC Powerline Conducted Emission

For the requirements, - Applicable [- Tested. - Not tested by applicant request.]
 - Not Applicable

7.8.1 Test Results

For the standard, - Passed - Failed - Not judged

Min. Limit Margin (Quasi-Peak) 20.7 dB at 0.150 MHz

Uncertainty of Measurement Results ± 2.6 dB(2σ)

Remarks : _____

7.8.2 Test Instruments

Shielded Room S1				
Type	Model	Serial No. (ID)	Manufacturer	Cal. Due
Test Receiver	ESU 26	100170 (A-6)	Rohde & Schwarz	2016/04/25
RF Cable	RG223/U	--- (H-9)	HUBER+SUHNER	2016/07/09
AMN	KNW-407FR	8-2019-1 (D-103)	Kyoritsu	2016/10/15

NOTE : The calibration interval of the above test instruments is 12 months.


7.8.3 Test Method and Test Setup (Diagrammatic illustration)

The preliminary tests were performed using the scan mode of test receiver or spectrum analyzer to observe the emissions characteristics of the EUT.

The EUT configuration, cable configuration and mode of operation were determined for producing the maximum level of emissions.

This configurations was used for final tests.

– Side View –



NOTE

AMN : Artificial Mains Network

7.8.4 Test Data

Mode of EUT : All modes have been investigated and the worst case mode for channel (39ch: 2441MHz) has been listed.


Test voltage : 120VAC 60Hz

Test Date: December 2, 2015

Temp.: 20 °C, Humi.: 44 %

Measured phase : L1

Frequency [MHz]	Corr. Factor [dB]	Meter Readings [dB(μV)]		Limits [dB(μV)]		Results [dB(μV)]		Margin [dB]		Remarks
		QP	AVE	QP	AVE	QP	AVE	QP	AVE	
0.150	10.4	31.8	--	66.0	56.0	42.2	--	+23.8	--	-
0.668	10.3	20.7	--	56.0	46.0	31.0	--	+25.0	--	-
3.087	10.5	13.6	--	56.0	46.0	24.1	--	+31.9	--	-
3.765	10.5	< 10.0	--	56.0	46.0	< 20.5	--	> +35.5	--	-
4.079	10.5	< 10.0	--	56.0	46.0	< 20.5	--	> +35.5	--	-
15.656	11.2	12.1	--	60.0	50.0	23.3	--	+36.7	--	-




NOTES

1. The spectrum was checked from 0.15 MHz to 30 MHz.
2. The correction factor includes the AMN insertion loss and the cable loss.
3. The symbol of “<” means “or less”.
4. The symbol of “>” means “more than”.
5. The symbol of “-” means “not applicable”.
6. Calculated result at 0.150 MHz, as the worst point shown on underline:
Correction Factor + Meter Reading (QP) = 10.4 + 31.8 = 42.2 dB(μV)
7. QP : Quasi-Peak Detector / AVE : Average Detector
8. Test receiver setting(s) : CISPR QP 9 kHz / Average 9 kHz

Test voltage : 120VAC 60HzTest Date: December 2, 2015
Temp.: 20 °C, Humi.: 44 %Measured phase : L2

Frequency [MHz]	Corr. Factor [dB]	Meter Readings [dB(μV)]		Limits [dB(μV)]		Results [dB(μV)]		Margin [dB]		Remarks
		QP	AVE	QP	AVE	QP	AVE	QP	AVE	
0.150	10.3	35.0	--	66.0	56.0	45.3	--	+20.7	--	-
0.668	10.3	20.6	--	56.0	46.0	30.9	--	+25.1	--	-
3.087	10.5	13.3	--	56.0	46.0	23.8	--	+32.2	--	-
3.765	10.5	< 10.0	--	56.0	46.0	< 20.5	--	> +35.5	--	-
4.079	10.5	< 10.0	--	56.0	46.0	< 20.5	--	> +35.5	--	-
15.656	11.3	11.9	--	60.0	50.0	23.2	--	+36.8	--	-

**NOTES**

1. The spectrum was checked from 0.15 MHz to 30 MHz.
2. The correction factor includes the AMN insertion loss and the cable loss.
3. The symbol of “<” means “or less”.
4. The symbol of “>” means “more than”.
5. The symbol of “--” means “not applicable”.
6. Calculated result at 0.150 MHz, as the worst point shown on underline:
Correction Factor + Meter Reading (QP) = 10.3 + 35.0 = 45.3 dB(μV)
7. QP : Quasi-Peak Detector / AVE : Average Detector
8. Test receiver setting(s) : CISPR QP 9 kHz / Average 9 kHz

7.9 Radiated Emission

For the requirements, - Applicable [- Tested. - Not tested by applicant request.]
 - Not Applicable

7.9.1 Test Results

For the standard, - Passed - Failed - Not judged

Min. Limit Margin (Average) 13.1 dB at 800.0 MHz

Uncertainty of Measurement Results	9 kHz – 30 MHz	<u>± 3.0</u>	dB(2σ)
	30 MHz – 300 MHz	<u>± 3.8</u>	dB(2σ)
	300 MHz – 1000 MHz	<u>± 4.8</u>	dB(2σ)
	1 GHz – 6 GHz	<u>± 4.7</u>	dB(2σ)
	6 GHz – 18 GHz	<u>± 4.6</u>	dB(2σ)
	18 GHz – 40 GHz	<u>± 5.5</u>	dB(2σ)

Remarks : Y axis Position

7.9.2 Test Instruments

Anechoic Chamber A2				
Type	Model	Serial No. (ID)	Manufacturer	Cal. Due
Test Receiver	ESU 26	100170 (A-6)	Rohde & Schwarz	2016/04/25
Loop Antenna	HFH2-Z2	872096/25 (C-2)	Rohde & Schwarz	2016/07/26
RF Cable	RG213/U	--- (H-28)	HUBER+SUHNER	2016/07/26
Pre-Amplifier	310N	304573 (A-17)	SONOMA	2016/04/15
Biconical Antenna	VHA9103/BBA9106	2355 (C-30)	Schwarzbeck	2016/05/24
Log-periodic Antenna	UHALP9108-A1	0694 (C-31)	Schwarzbeck	2016/05/24
RF Cable	S 10162 B-11 etc.	--- (H-4)	HUBER+SUHNER	2016/04/15
Site Attenuation	--	--- (H-15)	----	2016/01/05
Pre-Amplifier	TPA0118-36	1010 (A-37)	TOYO	2016/05/11
Double-Ridge Guide Horn Antenna	TR17206	73370006 (C-29)	ADVANTEST	2016/06/23
Horn Antenna	91888-2	562 (C-41-1)	EATON	2016/06/16
Horn Antenna	91889-2	568 (C-41-2)	EATON	2016/06/16
Horn Antenna	3160-04	9903-1053 (C-55)	EMCO	2016/06/29
Horn Antenna	3160-05	9902-1061 (C-56)	EMCO	2016/06/29
Horn Antenna	3160-06	9712-1045 (C-57)	EMCO	2016/06/29
Horn Antenna	3160-07	9902-1113 (C-58)	EMCO	2016/06/29
Horn Antenna	3160-08	9904-1099 (C-59)	EMCO	2016/06/29
Horn Antenna	3160-09	9808-1117 (C-48)	EMCO	2016/06/28
Attenuator	54A-10	W5713 (D-29)	Weinschel	2016/08/16
Attenuator	2-10	BA6214 (D-79)	Weinschel	2016/11/19
RF Cable	SUCOFLEX104	267479/4 (C-66)	HUBER+SUHNER	2016/01/19
RF Cable	SUCOFLEX104	267414/4 (C-67)	HUBER+SUHNER	2016/01/19
RF Cable	SUCOFLEX102EA	3041/2EA (C-69)	HUBER+SUHNER	2016/01/19
Band Rejection Filter	BRM50701	029 (D-93)	MICRO-TRONICS	2016/02/08
SVSWR	--	--- (H-19)	----	2016/02/27

NOTE : The calibration interval of the above test instruments is 12 months.

7.9.3 Test Method and Test Setup (Diagrammatic illustration)

7.9.3.1 Radiated Emission 9 kHz – 30 MHz


The preliminary tests were performed at the measurement distance that specified for compliance to determine the emission characteristics of the EUT.

The EUT configuration (in X, Y and Z axis), cable configuration and mode of operation were determined for producing the maximum level of emissions.

The measurement were performed about three antenna orientations (parallel, perpendicular, and ground-parallel).

This configurations was used for the final tests.

– Side View –




7.9.3.2 Radiated Emission 30 MHz – 1000 MHz

The preliminary tests were performed at the measurement distance that specified for compliance to determine the emission characteristics of the EUT.

The EUT configuration(in X, Y and Z axis), cable configuration and mode of operation were determined for producing the maximum level of emissions.

This configurations was used for the final tests.

– Side View –



7.9.3.3 Radiated Emission above 1 GHz

The preliminary tests were performed at the measurement distance that specified for compliance to determine the emission characteristics of the EUT.

The EUT configuration(in X, Y and Z axis), cable configuration and mode of operation were determined for producing the maximum level of emissions.

This configurations was used for the final tests.

The setting of the measuring instruments are shown as follows:


Type	Peak	Average
Detector Function	Peak	Peak
Res. Bandwidth	1 MHz	1 MHz
Video Bandwidth	3 MHz	$\geq 1/T * 1)$
Video Filtering	Linear Voltage	Linear Voltage
Sweep Time	AUTO	AUTO
Trace	Max Hold	Max Hold

Note: 1. T: Minimum transmission duration

Average (VBW) Setting:

Mode	Interval	Cycle	Duty cycle	Burst on period(T)	Min. VBW(1/T)	VBW Setting
	(msec)	(msec)	(%)	(msec)	(kHz)	(kHz))
BDR(DH5)	0.87	3.75	76.8%	2.91	0.34	0.50

– Side View –



NOTE

When the EUT is manipulated through three different orientations, the scan height upper range for the measurement antenna is limited to 2.5 m or 0.5 m above the top of the EUT.


7.9.4 Test Data

7.9.4.1 Band-edge Compliance

Test Date : October 15, 2015
Temp. : 23°C, Humi : 48%


Mode of EUT : BDR, Hopping off (0ch: 2402 MHz) (worst case)

Antenna Polarization : Horizontal




Note: The trace 1 is Peak . The trace 2 is Average.

Mode of EUT : BDR, Hopping off (0ch: 2402 MHz) (worst case)
Antenna Polarization : Vertical




Note: The trace 1 is Peak . The trace 2 is Average.

Mode of EUT : BDR, Hopping off (78ch: 2480 MHz) (worst case)
Antenna Polarization : Horizontal



Note: The trace 1 is Peak . The trace 2 is Average.

Mode of EUT : BDR, Hopping off (78ch: 2480 MHz) (worst case)
Antenna Polarization : Vertical



Note: The trace 1 is Peak . The trace 2 is Average.

7.9.4.2 Other Spurious Emission (9kHz – 30MHz)Test Date : November 30, 2015
Temp.: 19°C, Humi: 54%

Mode of EUT : All modes have been investigated and the worst case mode has been listed.


Results : No spurious emissions in the range 20dB below the limit.

7.9.4.3 Other Spurious Emission (30MHz – 1000MHz)

Mode of EUT : All modes have been investigated and the worst case mode has been listed.

Test voltage : 120VAC 60HzTest Date: November 30, 2015
Temp.: 19 °C, Humi: 54 %Antenna pole : Horizontal


Frequency [MHz]	Antenna Factor [dB(1/m)]	Corr. Factor [dB]	Meter Readings [dB(μV)]	Limits [dB(μV/m)]	Results [dB(μV/m)]	Margin [dB]	Remarks
800.00	20.7	-22.9	35.1	46.0	32.9	+13.1	-
806.39	20.8	-22.9	33.2	46.0	31.1	+14.9	-

**NOTES**

1. Test Distance : 3 m
2. The spectrum was checked from 30 MHz to 1000 MHz.
3. The correction factor is composed of cable loss, pad attenuation and/or amplifier gain.
4. The symbol of “<” means “or less”.
5. The symbol of “>” means “more than”.
6. Calculated result at 800.00 MHz, as the worst point shown on underline:
Antenna Factor + Coorection Factor + Meter Reading = 20.7 + (-22.9) + 35.1 = 32.9 dB(μV/m)
Antenna Height : 1.12 m, Turntable Angle : 182 °
7. Test receiver setting(s) : CISPR QP 120 kHz (QP : Quasi-Peak)

Test voltage : 120VAC 60HzTest Date: November 30, 2015Temp.: 19 °C, Humi: 54 %Antenna pole : Vertical

Frequency [MHz]	Antenna Factor [dB(1/m)]	Corr. Factor [dB]	Meter Readings [dB(μV)]	Limits [dB(μV/m)]	Results [dB(μV/m)]	Margin [dB]	Remarks
800.00	20.7	-22.9	< 27.0	46.0	< 24.8	> +21.2	-
806.39	20.8	-22.9	< 27.0	46.0	< 24.9	> +21.1	-



NOTES

1. Test Distance : 3 m
2. The spectrum was checked from 30 MHz to 1000 MHz.
3. The correction factor is composed of cable loss, pad attenuation and/or amplifier gain.
4. The symbol of “<” means “or less”.
5. The symbol of “>” means “more than”.
6. Calculated result at 806.39 MHz, as the worst point shown on underline:
Antenna Factor + Coorection Factor + Meter Reading = 20.8 + (-22.9) + <27.0 = <24.9 dB(μV/m)
Antenna Height : 1.16 m, Turntable Angle : 323 °
7. Test receiver setting(s) : CISPR QP 120 kHz (QP : Quasi-Peak)

7.9.4.4 Other Spurious Emission (Above 1000MHz)

Mode of EUT : BDR (worst case)

Test Date: October 15, 2015
 Temp.: 23 °C, Humi: 48 %

Frequency [MHz]	Antenna Factor [dB(1/m)]	Corr. Factor [dB]	D.C.F. [dB]	Meter Readings [dB(μV)]				Limits [dB(μV/m)]		Results [dB(μV/m)]		Margin [dB]	Remarks
				Horizontal		Vertical		PK	AVE	PK	AVE		
Test condition : Tx Low Ch													
4003.2	32.7	-32.6	-24.7	47.0	41.4	47.3	41.5	74.0	54.0	47.4	16.9	+26.6	
4804.0	32.9	-31.7	-24.7	57.3	55.1	52.9	50.0	74.0	54.0	58.5	31.6	+15.5	
12010.0	39.1	-29.1	-24.7	48.5	40.6	48.0	39.1	74.0	54.0	58.5	25.9	+15.5	
19216.0	40.5	-35.6	-24.7	< 50.0	< 40.0	< 50.0	< 40.0	74.0	54.0	< 54.9	< 20.2	> +19.1	
Test condition : TX Middle Ch													
4068.3	32.6	-32.5	-24.7	46.1	38.9	47.4	41.3	74.0	54.0	47.5	16.7	+26.5	
4882.0	33.0	-31.6	-24.7	58.1	56.2	54.2	51.5	74.0	54.0	59.5	32.9	+14.5	
7323.0	36.6	-31.3	-24.7	54.5	51.6	# 53.5	49.9	74.0	54.0	59.8	32.2	+14.2	
12205.0	38.8	-29.6	-24.7	47.4	38.7	# 48.4	40.2	74.0	54.0	57.6	24.7	+16.4	
19528.0	40.4	-35.5	-24.7	< 50.0	< 40.0	< 50.0	< 40.0	74.0	54.0	< 54.9	< 20.2	> +19.1	
Test condition : TX High Ch													
4133.3	32.2	-32.5	-24.7	46.3	38.8	45.4	36.5	74.0	54.0	46.0	13.8	+28.0	
4960.0	33.2	-31.5	-24.7	58.8	57.0	56.2	54.2	74.0	54.0	60.5	34.0	+13.5	
7440.0	36.7	-31.3	-24.7	51.4	49.6	52.1	48.3	74.0	54.0	57.5	30.3	+16.5	
12400.0	38.8	-29.9	-24.7	46.4	37.3	46.4	36.3	74.0	54.0	55.3	21.5	+18.7	
19840.0	40.4	-35.6	-24.7	< 50.0	< 40.0	< 50.0	< 40.0	74.0	54.0	< 54.8	< 20.1	> +19.2	
22320.0	40.6	-35.5	-24.7	< 50.0	< 40.0	< 50.0	< 40.0	74.0	54.0	< 55.1	< 20.4	> +18.9	

Calculated result at 4960.0 MHz, as the worst point shown on underline:

$$\begin{aligned}
 \text{Antenna Factor} &= 33.2 \text{ dB(1/m)} \\
 \text{Corr. Factor} &= -31.5 \text{ dB} \\
 \text{D.C.F.(For AVE only)} &= -24.7 \text{ dB} \\
 +) \text{ Meter Reading} &= 58.8 \text{ dB(μV)} \\
 \text{Result} &= 60.5 \text{ dB(μV/m)}
 \end{aligned}$$

Minimum Margin: $74.0 - 60.5 = 13.5$ (dB)

NOTES

- Test Distance : 3 m
- The spectrum was checked from 1 GHz to 25 GHz (10th harmonic of the highest fundamental frequency).
- The correction factor is shown as follows:
 $\text{Corr. Factor [dB]} = \text{Cable Loss} - \text{Pre-Amp. Gain [dB]}$
- The symbol of " $<$ " means "or less".
- The symbol of " $>$ " means "more than".
- PK : Peak / AVE : Average
- D.C.F. Calculation. (D.C.F. : Duty Cycle Correction Factor)
 - Time to cycle through all channels = $t = T \text{ [ms]} \times 20$ (AFH minimum hopping channels), where T = burst on duration
 - $100 \text{ ms} / t = h \rightarrow$ Round up to next highest integer, to account for worst case, H
 - The Worst Case Dwell Time [ms] = $T \times H$ (For this case, $T = 2.91 \text{ ms}$, $H = 2$, $2.91 \times 2 = 5.82$)
 - $\text{D.C.F. [dB]} = 20 \times \log(\text{The Worst Case Dwell Time} / 100 \text{ [ms]}) = 20 \times \log(5.82 / 100) = -24.7$

7.10 SAR Test Exclusion

7.10.1 Maximum Output Power (Average)

Mode	Ch#	Frequency (MHz)	Average Power (dBm)	
			Measured	Spec. Max.
Bluetooth	0	2402	7.64	8.0
	39	2441	7.34	
	78	2480	6.25	

Power measurement is required for the transmission mode configuration with the highest maximum output power specified for production units. (Bluetooth configurations are considered separately.)

- When the same highest maximum output power specification applies to multiple transmission modes, the largest channel bandwidth configuration with the lowest order modulation and lowest data rate is measured.
- When the same highest maximum output power is specified for multiple largest channel bandwidth configurations with the same lowest order modulation or lowest order modulation and lowest data rate, power measurement is required for all equivalent Bluetooth configurations with the same maximum output power.

7.10.2 Standalone SAR Test Exclusion Considerations (KDB 447498 D01)

The 1 g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* \leq 50 mm are determined by;

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f_{(\text{GHz})}}] \leq 3.0, \text{ where}$$

- $f_{(\text{GHz})}$ is the RF channel transmit frequency in GHz.
- Power and distance are rounded to the nearest mW and mm before calculation.
- The result is rounded to one decimal place for comparison.
- When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied.

SAR exclusion calculations for antenna \leq 50 mm from the user

Band	Freq. (MHz)	Max. Power		Distance (mm)	Threshold	Test Exclusion
		(dBm)	(mW)			
Bluetooth	2480	8.0	6	< 5	1.9	YES

The minimum user separation distance was assumed to be 0 mm for the purpose of the SAR exclusion calculations.

Conclusion:

The device qualifies for the Standalone SAR test exclusion because the computed value is < 3 .