



15.4 TEST DATA

[TestMode: TX mode]; [Line: Nutral]; [Power:120V/60Hz]



Test Result: Pass

[TestMode: TX mode]; [Line: Line]; [Power:120V/60Hz]



Site: Phase: **L1** Temperature: (C)
Limit: FCC Class B Conduction(QP) Power: Humidity: %RH
EUT: SOUNDPEATS Wireless Headphones
M/N: RunFree
Mode: T X mode
Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB		
1	*	0.5100	23.69	10.08	33.77	56.00	-22.23	QP	
2		0.5100	12.22	10.08	22.30	46.00	-23.70	AVG	
3		1.1740	16.63	10.14	26.77	56.00	-29.23	QP	
4		1.1740	10.91	10.14	21.05	46.00	-24.95	AVG	
5		3.0180	14.39	10.22	24.61	56.00	-31.39	QP	
6		3.0180	3.15	10.22	13.37	46.00	-32.63	AVG	
7		5.8100	9.44	10.04	19.48	60.00	-40.52	QP	
8		5.8100	-1.73	10.04	8.31	50.00	-41.69	AVG	
9		11.6780	3.16	10.08	13.24	60.00	-46.76	QP	
10		11.6780	-6.03	10.08	4.05	50.00	-45.95	AVG	
11		28.6860	5.31	10.05	15.36	60.00	-44.64	QP	
12		28.6860	0.81	10.05	10.86	50.00	-39.14	AVG	

Test Result: Pass

16 RADIATED SPURIOUS EMISSIONS


Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 6.4,6.5,6.6
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Charlie
Temperature	25℃
Humidity	60%

16.1 LIMITS

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

16.2 BLOCK DIAGRAM OF TEST SETUP



16.3 PROCEDURE

- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.


Remark:

- 1) For emission below 1GHz, through pre-scan found the worst case is the lowest channel. Only the worst case is recorded in the report.
- 2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor
- 3) Scan from 9kHz to 25GHz, the disturbance above 12.75GHz and below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported. fundamental frequency is blocked by filter, and only spurious emission is shown.
- 4) For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

16.4 TEST DATA


Below 1GHz

[TestMode: TX]; [Polarity: Horizontal]



Test Result: Pass


[TestMode: TX]; [Polarity: Vertical]



Test Result: Pass

Above 1GHz

[TestMode: TX lowest channel]; [Polarity: Horizontal]



Site Polarization: **Horizontal** Temperature: (C)

Limit: FCC Part15 (PK) Power: Humidity: %RH

EUT: SOUNDPEATS Wireless Headphones

M/N: RunFree


Mode: TX-L

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4804.000	39.62	4.05	43.67	74.00	-30.33	peak	
2		5653.000	39.89	6.76	46.65	74.00	-27.35	peak	
3		7206.000	39.19	7.93	47.12	74.00	-26.88	peak	
4		8273.250	40.47	9.03	49.50	74.00	-24.50	peak	
5		9608.000	37.74	10.90	48.64	74.00	-25.36	peak	
6	*	11316.500	38.62	13.59	52.21	74.00	-21.79	peak	

Test Result: Pass

[TestMode:TX lowest channel]; [Polarity: Vertical]




Site
Limit: FCC Part15 (PK)
EUT: SOUNDPEATS Wireless Headphones
M/N: RunFree
Mode: TX-L
Note:

Polarization: **Vertical** Temperature: (C)
Power: Humidity: %RH

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		
1		4804.000	38.72	4.05	42.77	74.00	-31.23	peak	
2		5911.500	39.90	6.85	46.75	74.00	-27.25	peak	
3		7206.000	39.38	7.93	47.31	74.00	-26.69	peak	
4		8285.000	40.05	9.03	49.08	74.00	-24.92	peak	
5		9608.000	38.54	10.90	49.44	74.00	-24.56	peak	
6	*	11316.500	39.46	13.59	53.05	74.00	-20.95	peak	

Test Result: Pass

[TestMode: TX middle channel]; [Polarity: Horizontal]



Site Polarization: **Horizontal** Temperature: (C)

Limit: FCC Part15 (PK) Power: Humidity: %RH

EUT: SOUNDPEATS Wireless Headphones

M/N: RunFree


Mode: TX-M

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		
1		4882.000	39.48	4.37	43.85	74.00	-30.15	peak	
2		5888.000	39.15	6.82	45.97	74.00	-28.03	peak	
3		7323.000	37.80	8.21	46.01	74.00	-27.99	peak	
4		8191.000	39.81	8.99	48.80	74.00	-25.20	peak	
5		9764.000	38.27	11.30	49.57	74.00	-24.43	peak	
6	*	11316.500	38.81	13.59	52.40	74.00	-21.60	peak	

Test Result: Pass

[TestMode: TX middle channel]; [Polarity: Vertical]



Site: Polarization: **Vertical** Temperature: (C)

Limit: FCC Part15 (PK) Power: Humidity: %RH

EUT: SOUNDPEATS Wireless Headphones

M/N: RunFree


Mode: TX-M

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4882.000	41.14	4.37	45.51	74.00	-28.49	peak	
2		6052.500	42.78	4.12	46.90	74.00	-27.10	peak	
3		7323.000	39.11	8.21	47.32	74.00	-26.68	peak	
4		8484.750	39.94	9.12	49.06	74.00	-24.94	peak	
5		9764.000	38.15	11.30	49.45	74.00	-24.55	peak	
6	*	11739.500	38.84	13.78	52.62	74.00	-21.38	peak	

Test Result: Pass

[TestMode: TX highest channel]; [Polarity: Horizontal]



Site Polarization: **Horizontal** Temperature: (C)

Limit: FCC Part15 (PK) Power: Humidity: %RH

EUT: SOUNDPEATS Wireless Headphones

M/N: RunFree


Mode: TX-H

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4960.000	39.71	5.42	45.13	74.00	-28.87	peak	
2		5876.250	39.85	6.81	46.66	74.00	-27.34	peak	
3		7440.000	39.12	8.48	47.60	74.00	-26.40	peak	
4		8308.500	40.95	9.04	49.99	74.00	-24.01	peak	
5		9920.000	37.69	11.69	49.38	74.00	-24.62	peak	
6	*	11410.500	39.07	13.63	52.70	74.00	-21.30	peak	

Test Result: Pass

[TestMode: TX highest channel]; [Polarity: Vertical]



Site: Polarization: **Vertical** Temperature: (C)

Limit: FCC Part15 (PK) Power: Humidity: %RH

EUT: SOUNDPEATS Wireless Headphones

M/N: RunFree

Mode: TX-H

Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4960.000	38.81	5.42	44.23	74.00	-29.77	peak	
2		5700.000	40.46	6.81	47.27	74.00	-26.73	peak	
3		7440.000	39.07	8.48	47.55	74.00	-26.45	peak	
4		8508.250	39.67	9.13	48.80	74.00	-25.20	peak	
5		9920.000	36.89	11.69	48.58	74.00	-25.42	peak	
6	*	11398.750	38.55	13.63	52.18	74.00	-21.82	peak	

Test Result: Pass

17 RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS


Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 6.10.5
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Charlie
Temperature	25°C
Humidity	60%

17.1 LIMITS

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

17.2 BLOCK DIAGRAM OF TEST SETUP



17.3 PROCEDURE

- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.


- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark 1: $\text{Level} = \text{Read Level} + \text{Cable Loss} + \text{Antenna Factor} - \text{Preamp Factor}$

Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.


17.4 TEST DATA

[TestMode: TX lowest channel]; [Polarity: Horizontal]



Test Result: Pass

[TestMode: TX lowest channel]; [Polarity: Vertical]




Site Polarization: **Vertical** Temperature: (C)
Limit: FCC Part15 (PK) Power: Humidity: %RH
EUT: SOUNDPEATS Wireless Headphones
M/N: RunFree
Mode: TX-L
Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		2310.000	44.49	-4.27	40.22	74.00	-33.78	peak	
2	*	2390.000	44.51	-3.82	40.69	74.00	-33.31	peak	

Test Result: Pass

[TestMode: TX highest channel]; [Polarity: Horizontal]



Site Polarization: **Horizontal** Temperature: (C)

Limit: FCC Part15 (PK) Power: Humidity: %RH

EUT: SOUNDPEATS Wireless Headphones

M/N: RunFree

Mode: TX-H


Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over		
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	Comment
1		2483.500	43.01	-3.96	39.05	74.00	-34.95	peak	
2	*	2500.000	43.22	-4.00	39.22	74.00	-34.78	peak	

Test Result: Pass

[TestMode: TX highest channel]; [Polarity: Vertical]

Radiated Emission Measurement



Site Polarization: **Vertical** Temperature: (C)

Limit: FCC Part15 (PK) Power: Humidity: %RH

EUT: SOUNDPEATS Wireless Headphones

M/N: RunFree

Mode: TX-H

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	Comment
1	*	2483.500	48.65	-3.96	44.69	74.00	-29.31	peak	
2		2500.000	46.19	-4.00	42.19	74.00	-31.81	peak	

Test Result: Pass