

RF-EXPOSURE ASSESSMENT REPORT

FCC 47 CFR Part 2.1091 Industry Canada RSS-102

RF-Exposure evaluation of mobile equipment

Report Reference No...... G0M-1707-6706-TFC091ME-V01

Testing Laboratory Eurofins Product Service GmbH

Address..... Storkower Str. 38c

15526 Reichenwalde

Germany

Accreditation:



FCC Test Firm Designation Number: DE0008

IC Testing Laboratory site: 3470A-2

Applicant's name Kinematics GmbH

Address...... Spreeallee 2

16321 Bernau bei Berlin

GERMANY

Test specification:

KDB 447498 D01 v06:2015-10-23

RSS-102, Issue 5:2015-03

Equipment under test (EUT):

Product description Energy module with haptical user interface + bluetooth

interface for toy building set

Model No. Powerbrain 2IM.1PB.300

Additional Model(s) None

Brand Name(s) TinkerBots

Hardware version 2IM.1PB.300

Firmware / Software version Powerbrain Version 0.1

FCC-ID: 2AFV5-TB1701 IC: 20598-TB1701

Test result Passed



Possible test case verdicts:			
- neither assessed nor tested	:	N/N	
- required by standard but not appl. to t	est object:	N/A	
- required by standard but not tested	:	N/T	
- not required by standard for the test o	bject:	N/R	
- test object does meet the requirement	·:	P (Pass)	
- test object does not meet the requiren	nent:	F (Fail)	
Testing:			
Test Lab Temperature	:	20 – 23 °C	
Test Lab Humidity	:	32 – 38 %	
Date of receipt of test item	:	2017-07-20	
Date of assessment		2017-07-26	
Compiled by:	Sebastian Suck	COW	
Assessed by (+ signature): (Responsible for Assessment)	Toralf Jahn		F 0
Approved by (+ signature): (Head of Lab)	Christian Webe	r	C. Weber
Date of issue:	2017-08-23		
Total number of pages:	12		

General remarks:

The test results presented in this report relate only to the object tested.

The results contained in this report reflect the results for this particular model and serial number. It is the responsibility of the manufacturer to ensure that all production models meet the intent of the requirements detailed within this report.

This report shall not be reproduced, except in full, without the written approval of the Issuing testing laboratory.

Additional comments:



Version History

Version	Issue Date	Remarks	Revised by
01	2017-08-23	Initial Release	



REPORT INDEX

1	EQUIPMENT (TEST ITEM) DESCRIPTION	5
1.1	Reference Documents	6
1.2	Standalone Radiation Sources	7
2	RESULT SUMMARY	8
3	RF-EXPOSURE CLASSIFICATIONS	9
4	ASSESSMENT	10
4.1	MPE Assessment Conditions – 47 CFR 2.1091 / RSS-102	10
42	Single-Transmitter Assessment – 47 CFR 2 1091 / RSS-102	12



1 Equipment (Test item) Description

Description	Energy module with haptical user interface + bluetooth interface for toy building set	
Model	Powerbrain 2IM.1PB.300	
Additional Model(s)	None	
Brand Name(s)	TinkerBots	
Serial number	None	
Hardware version	2IM.1PB.300	
Software / Firmware version	Powerbrain Version 0.1	
PMN	TINKERBOTS	
HVIN	TB1701	
FVIN	N/A	
HMN	N/A	
FCC-ID	2AFV5-TB1701	
IC	20598-TB1701	
Equipment type	End product	



1.1 Reference Documents

Document type	Document No.	Issued by	Date
FCC 247 Test Report	G0M-1707-6706-TFC247BL-V01	Eurofins Product Service GmbH	2017-08-23



1.2 Standalone Radiation Sources

Mode #	Description		
	Frequency range [MHz]	2400 - 2483.5	
	Transmission modes	GFSK	
	Maximum conducted power [dBm]	-0.2	
Divista eth I. C	Maximum radiated power [dBm]	-0.2	
Bluetooth LE	Maximum transmission duty cycle [%]	100	
	Antenna gain [dBi]	0	
	Antenna diameter [cm]	1.2	
	Assessment Frequency [MHz]	2402	



2 Result Summary

FCC 47 CFR Part 2.1091, IC RSS-102						
Product Specific Standard Section	Requirement	Result	Remarks			
47 CFR 2.1091	Maximum permissible exposure @ 20cm below limit	PASS				
RSS-102 2.5.2 Maximum permissible exposure @ 20cm below limit PASS						
Remarks:	Remarks:					



3 RF-Exposure Classifications

Device Types			
Fixed	A fixed device is defined as a device physically secured at one fixed location and cannot be easily re-located.		
Mobile	A mobile device is defined as a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons. (47 CFR 2.1091)		
Portable	A portable device is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user. (47 CFR 2.1093)		
	Exposure Categories		
Occupational / Controlled	Limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure.		
General population / uncontrolled	Exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure.		



4 Assessment

4.1 MPE Assessment Conditions – 47 CFR 2.1091 / RSS-102

	JC. 10 47 CTK	2.1	091 / ISED RSS-102	:	VERDICT: PASS
Assessment according		Reference Method			
to reference	е		FCC OET Bulletin	n 65 / RSS-102 & Sa	fety Code 6
Device type	Э			mobile	
Exposure cate	gory			General public	
	IC Limits - O	ccu	pational / Controlle	ed Exposure	
Frequency range [MHz]	Electric field strength [V/N		Magnetic field strength [A/M]	Power density [W/m ²]	Averaging time [min]
0.003-10*	170		180	-	Instantaneous*
0.1-10	-		1.6 / f	-	6**
1.29-10	193 / f ^{0.5}		-	-	6**
10-20	61.4		0.163	-10	6
20-48	129.8 / f ^{0.25}	,	0.3444 / f ^{0.25}	44.72 / f ^{0.5}	6
48-100	49.33		0.1309	6.455	6
100-6000	15.60 f ^{0.25}		0.04138 f ^{0.25}	0.6455 f ^{0.5}	6
6000-15000	137		0.364	50	6
15000-150000	137		0.364	50	616000 / f ^{1.2}
150000-300000	0.354 f ^{0.5}		9.40 x 10 ⁻⁴ f ^{0.5}	3.33 x 10 ⁻⁴ f	616000 / f ^{1.2}
IC	Limits – Gener	ral F	Population / Uncont	rolled Exposure	
Frequency range [MHz]	Electric field strength [V/N		Magnetic field strength [A/M]	Power density [W/m²]	Averaging time [min]
0.003-10*	83		90	-	Instantaneous*
0.1-10	-		0.73 / f	-	6**
1.1-10	87 / f ^{0.5}		-	-	6**
10-20	27.46		0.0728	2	6
20-48	58.07 / f ^{0.25}		0.1540 / f ^{0.25}	8.944 / f ^{0.5}	6
48-300	22.06		0.05852	1.291	6
300-6000	3.142 f ^{0.3417}	7	$0.008335 f^{0.3417}$	0.02619 f ^{0.6834}	6
6000-15000	61.4		0.163	10	6
15000-150000	61.4		0.163	10	616000 / f ^{1.2}
13000-130000					



Product Service

FCC Limits – Occupational / Controlled Exposure					
Frequency range [MHz]	Electric field strength [V/M]	Magnetic field strength [A/M]	Power density [mW/cm ²]	Averaging time [min]	
0.3 – 3.0	614	1.63	(100)*	6	
3.0 - 30	1842 / f	4.89 / f	(900 / f ²)*	6	
30 - 300	61.4	0.163	1.0	6	
300 - 1500	N/A	N/A	f / 300	6	
1500 - 100000	N/A	N/A	5.0	6	
FC	FCC Limits – General Population / Uncontrolled Exposure				

Frequency range [MHz]	Electric field strength [V/M]	Magnetic field strength [A/M]	Power density [mW/cm ²]	Averaging time [min]
0.3 – 1.34	614	1.63	(100)*	30
1.34 - 30	842 / f	2.19 / f	(180 / f ²)*	30
30 - 300	27.5	0.073	0.2	30
300 - 1500	N/A	N/A	f / 1500	30
1500 - 100000	N/A	N/A	1.0	30

^{* =} Plane wave equivalent power density; f in MHz

Assessment Relations

$$\lambda[m] = \frac{c\left[\frac{m}{s}\right]}{f[Hz]}; R_{FF}[m] \ge \frac{2 \cdot D[m]^2}{\lambda[m]}$$

$$S[mW/cm^2] = \frac{P_{E.I.R.P.}[mW]}{4\pi R[cm]^2}$$
; $R[cm] = \sqrt{\frac{P_{E.I.R.P.}[mW]}{4\pi S[mW/cm^2]}}$

$$P_R[mW] = P_C[mW] \cdot G \; ; \; P_R[dBm] = P_C[dBm] + G[dBi]$$

$$DCC[dB] = 10 \cdot Log_{10} \left(\frac{DC[\%]}{100} \right)$$

Assessment procedure

For each radio and frequency band the worst case transmission mode with the highest peak conducted or radiated power is evaluated at the frequency that results in the most restrictive rfexposure limit. From the peak power values, antenna gains and duty cycles taken from the reference documents, the source average radiated power values are calculated. From the average radiated power the power densities at antenna far-field distance, at 20cm separation distance from the radiation source is calculated. Compliance with the RF-Exposure limit is determined at 20cm separation distance.



4.2 Single-Transmitter Assessment – 47 CFR 2.1091 / RSS-102

Assessment result - Bluetooth LE				
Transmission mode				
Operating mode frequency range [MHz]	2400	- 2483.5		
Assessment frequency (f) [MHz]	2	402		
Transmission duty cycle (DC) [%]	•	100		
Peak conducted power (P _C) [dBm]	-	0.2		
Peak radiated power (P _R) [dBm e.i.r.p.]	-	0.2		
Peak Antenna gain (G) [dBi]		0		
Maximum Antenna Diameter D [cm]		1.2		
Antenna far-field distance				
Transmission frequency wavelength (λ)	0.125 m	12.49 cm		
Antenna far-field distance (R _{FF})	0.002 m	0.23 cm		
Power evaluation				
Peak conducted power (P _C)	0.95 mW	-0.20 dBm		
Peak Antenna Gain (G)	1.00	0.00 dBi		
Calculated peak radiated power (P _{R-Calc})	0.95 mW	-0.20 dBm		
Measured peak radiated power (P _R)	0.95 mW	-0.20 dBm		
Source average Power				
Maximum transmission duty cycle (DC)	100	0.0 %		
Duty cycle correction (DCC)	1.00	0.00 dB		
Measured peak radiated power (P _R)	0.95 mW	-0.20 dBm		
Averaged peak radiated power (P _{RAVG})	0.95 mW	-0.20 dBm		
Power density				
Compliance power density limit FCC	1.000 mW/cm ²	10.00 W/m ²		
Compliance power density limit IC	0.535 mW/cm ²	5.35 W/m ²		
Power density @ Antenna far-field distance	1.429 mW/cm ²	14.292 W/m ²		
Power density @ 20cm	0.000 mW/cm ²	0.002 W/m ²		
Distance for compliance power density FCC	0.003 m	0.28 cm		
Distance for compliance power density IC	0.004 m	0.38 cm		
Verdict				
The power density of the EUT	at 20cm is below the FCC	MPE limit!		
The power density of the EUT	at 20cm is below the IC N	MPE limit!		
Comments:	Comments:			