

FCC Test Report

Part 15 subpart C

Client Information:

Applicant: Guangzhou Maipai Electronics Co.,Ltd.
Applicant add.: Room 202, No.94, Shinan Road, Xianchong Village, Qiaonan Street, Panyu District of Guangzhou.

Product Information:

Product Name: wireless mouse

Model No.: M7111

Derivative model No.: N/A

Brand Name: N/A

Standards: CFR 47 FCC PART 15 SUBPART C:2013 section 249

Prepared By:

Dongguan Yaxu (AiT) Technology Limited

Add. : No. 22, Jinqianling Third Street, Jitigang, Huangjiang, Dongguan, Guangdong, China.

Date of Receipt: Nov. 30, 2015

Date of Test: Dec. 01~ 10, 2015

Date of Issue: Dec. 10, 2015

Test Result: Pass

This device described above has been tested by Dongguan Yaxu (AiT) Technology Limited, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

ATT SZ commissioned AiT(Dongguan) to test the device described above, and then AiT(Dongguan) use the UTL(Dongguan)'s test site do this case.

This test report must not be used by the client to claim product endorsement by any agency of the U.S. government.

Reviewed by: Seal-Chen

Approved by: Jerry

1 Contents

	Page
COVER PAGE	
1 CONTENTS	2
2 TEST SUMMARY	2
2.1 COMPLIANCE WITH FCC PART 15 SUBPART C	2
2.2 MEASUREMENT UNCERTAINTY	4
3 TEST FACILITY	5
3.1 DEVIATION FROM STANDARD	5
3.2 ABNORMALITIES FROM STANDARD CONDITIONS	5
4 GENERAL INFORMATION	5
4.1 GENERAL DESCRIPTION OF EUT	5
5 DESCRIPTION OF TEST CONDITIONS	8
5.1 E.U.T. OPERATION	8
5.2 EUT PERIPHERAL LIST	9
5.3 TEST PERIPHERAL LIST	9
5.4 DESCRIPTION OF TEST MODES	9
6 EQUIPMENTS LIST FOR ALL TEST ITEMS	10
7 TEST RESULT	11
7.1 ANTENNA REQUIREMENT	11
7.2 FIELD STRENGTH OF FUNDAMENTAL & FIELD STRENGTH OF UNWANTED EMISSIONS & BAND EDGE	12
7.2.1 Duty cycle measurement:	17
7.2.2 Fundamental field strength measurement:	17
7.2.3 Radiated Emissions Test Data	18
7.2.4 Band Edge Measurement:	22
7.2.5 Restricted Bands Measurement:	23
7.3 OCCUPIED BANDWIDTH	24
7.4 CONDUCTED EMISSIONS AT MAINS TERMINALS 150 kHz TO 30 MHz	26
8 PHOTOGRAPHS	27
8.1 RADIATED EMISSION TEST SETUP	27
9 EUT CONSTRUCTIONAL DETAILS	28

2 Test Summary

2.1 Compliance with FCC Part 15 subpart C

Test	Test Requirement	Standard Paragraph	Result
------	------------------	--------------------	--------

Field Strength of Fundamental	FCC PART 15 C section 15.249 (a)	ANSI C63.10: Clause 6.6	PASS
Field Strength of Unwanted Emissions	FCC PART 15 C section 15.249 (a) section 15.249 (d)	ANSI C63.10: Clause 6.4, 6.6 and 6.7	PASS
Band Edges	FCC PART 15 C section 15.249 (d)	ANSI C63.10: Clause 6.9.2	PASS
Occupied Bandwidth	FCC PART 15 C section 15.215(c)	ANSI C63.10: Clause 6.9.1	PASS
Conducted Emissions at Mains Terminals	FCC PART 15 C section 15.207	ANSI C63.10: Clause 6.2	N/A

Remark:

EUT: In this whole report EUT means Equipment Under Test.

Tx: In this whole report Tx (or tx) means Transmitter.

Rx: In this whole report Rx (or rx) means Receiver.

RF: In this whole report RF means Radio Frequency.

ANSI C63.10: the detail version is ANSI C63.10:2009 in the whole report.

2.2 Measurement Uncertainty

All measurements involve certain levels of uncertainties, the maximum value of the uncertainty as below:

No.	Item	Uncertainty
1	Conducted Emission Test	1.20dB
2	Radiated Emission Test	3.30dB
3	RF power,conducted	0.16dB
4	RF power density,conducted	0.24dB
5	Spurious emissions,conducted	0.21dB
6	All emissions,radiated(<1G)	4.68dB
7	All emissions,radiated(>1G)	4.89dB

3 Test Facility

.FCC- Registration No: 248337

DongGuan Yaxu(AiT) Technology Limited
No. 22,JinQianLing Street 3, JiTiGang Village, Huang-Jiang Town, DongGuan, Guangdong, 523757 China.

3.1 Deviation from standard

None

3.2 Abnormalities from standard conditions

None

4 General Information

4.1 General Description of EUT

Manufacturer:	Guangzhou Maipai Electronics Co.,Ltd.
Manufacturer Address:	Room 202,No.94,Shinan Road,Xianchong Village,Qiaonan Street, Panyu District of Guangzhou.
EUT Name:	wireless mouse
Model No.:	M7111
FCC ID:	2AFVEM7111
Operation frequency:	2409 MHz to 2476 MHz
Number of channel:	8 channels
Modulation Type :	MSK
Antenna Type:	Internal antenna(PCB)
Antenna Gain:	0 dBi
HW:	ASY_TLSR8566_V1.0
SW:	V1.1
Brand Name:	N/A
Serial No:	N/A
Derivative model No.:	N/A

Power Supply Range:	DC 3.0V(2*1.5V AAA battery)
Power Supply:	DC 3.0V from battery
Power Cord:	N/A
Signal Cable:	N/A

Note: This device support 250kbps, 1Mbps, 2Mbps. because the firmware limitation, this product only supports 250kbps data rate. And users can not enable other data rate by themselves.

Description of Channel:			
Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2409	5	2445
2	2417	6	2455
3	2426	7	2465
4	2440	8	2476

5 Description of Test conditions

5.1 E.U.T. Operation

Test Voltage:	DC 3.0V from battery(user new batteries)
Temperature:	20.0 -25.0 °C
Humidity:	38-50 % RH
Atmospheric Pressure:	1000 -1010 mbar
Test frequencies and frequency range:	According to the 15.31(m) Measurements on intentional radiators or receivers, other than TV broadcast receivers, shall be performed and, if required, reported for each band in which the device can be operated with the device operating at the number of frequencies in each band specified in the following table: According to the 15.33 (a) For an intentional radiator, the spectrum shall be investigated from the lowest radio frequency signal generated in the device, without going below 9 kHz, up to at least the frequency shown in the following table:

Number of fundamental frequencies to be tested in EUT transmit band

Frequency range in which device operates	Number of frequencies	Location in frequency range of operation
1 MHz or less	1	Middle
1 MHz to 10 MHz	2	1 near top and 1 near bottom
More than 10 MHz	3	1 near top, 1 near middle and 1 near bottom

Frequency range of radiated emission measurements

Lowest frequency generated in the device	Upper frequency range of measurement
9 kHz to below 10 GHz	10th harmonic of highest fundamental frequency or to 40 GHz, whichever is lower
At or above 10 GHz to below 30 GHz	5th harmonic of highest fundamental frequency or to 100 GHz, whichever is lower
At or above 30 GHz	5th harmonic of highest fundamental frequency or to 200 GHz, whichever is lower, unless otherwise specified

5.2 EUT Peripheral List

No.	Equipment	Manufacturer	Model No.	Serial No.	Power cord	signal cable
1	N/A	N/A	N/A	N/A	N/A	N/A

5.3 Test Peripheral List

No.	Equipment	Manufacturer	Model No.	Serial No.	Power cord	signal cable
1	N/A	N/A	N/A	N/A	N/A	N/A

5.4 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	CH1
Mode 2	CH4
Mode 3	CH8

For Conducted Emission	
Final Test Mode	Description
/	/

For Radiated Emission	
Final Test Mode	Description
Mode 1	CH1
Mode 2	CH4
Mode 3	CH8

Note:

(1) The measurements are performed at the highest, middle, lowest available channels.

(2) The EUT was programmed to be in continuously transmitting mode and the transmit duty cycle is not less than 98%.

6 Equipments List for All Test Items

No	Test Equipment	Manufacturer	Model No	Serial No	Cal. Date	Cal. Due Date
1	Spectrum Analyzer	ADVANTEST	R3182	150900201	2015.06.29	2016.06.28
2	EMI Measuring Receiver	R&S	ESR	101660	2014.12.12	2015.12.11
3	Low Noise Pre Amplifier	Tsj	MLA-10K01-B01-27	1205323	2015.06.29	2016.06.28
4	Low Noise Pre Amplifier	Tsj	MLA-0120-A02-34	2648A04738	2015.12.02	2016.12.01
5	TRILOG Super Broadband test Antenna	SCHWARZBEC K	VULB9160	9160-3206	2015.12.03	2016.12.02
6	Broadband Horn Antenna	SCHWARZBEC K	BBHA9120D	452	2015.12.03	2016.12.02
7	SHF-EHF Horn	SCHWARZBEC K	BBHA9170	BBHA917036 7	2015.12.03	2016.12.02
8	Loop Antenna	ARA	PLA-1030/B	1029	2015.03.20	2016.03.19
9	Radiated Cable 1# (30MHz-1GHz)	FUJIKURA	5D-2W	01	2015.01.04	2016.01.03
10	Radiated Cable 2# (1GHz -25GHz)	FUJIKURA	10D2W	02	2014.12.25	2015.12.24
11	Conducted Cable 1#(9KHz-30MHz)	FUJIKURA	1D-2W	01	2015.01.04	2016.01.03
12	SMA Antenna connector	Dosin	Dosin-SMA	N/A	N/A	N/A


7 Test Result

7.1 Antenna Requirement

Standard requirement

EUT Antenna

The antenna is Internal antenna(PCB) and no consideration of replacement. The maximum gain of the antenna is 0 dBi.



Test result: The unit does meet the FCC requirements.

7.2 Field Strength of Fundamental& Field Strength of Unwanted Emissions& Band Edge

Test Requirement: FCC Part15 C section 15.249

(a) Except as provided in paragraph (b) of this section, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

Fundamental Frequency (MHz)	Field Strength of Fundamental (dB μ V/m @ 3m)	Field Strength of Harmonics (dB μ V/m @ 3m)
902 to 928	94.0	54.0
2400 to 2483.5	94.0	54.0
5725 to 5875	94.0	54.0
24000 to 24250	108.0	68.0

(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in Section 15.209, whichever is the lesser attenuation.

Limits: The fundamental frequency range is in the frequency band of the EUT is 2409 MHz ~ 2476MHz.

The limit for AVG field strength dB μ V/m for the fundamental frequency = 94.0 dB μ V/m.

The limit for Peak field strength dB μ V/m for the fundamental frequency = 114.0 dB μ V/m.

No fundamental is allowed in the restricted bands.

The limit for AVG field strength dB μ V/m for the harmonics and other above 1G frequencies = 54.0 dB μ V/m.

The limit for Peak field strength dB μ V/m for the harmonics and other above 1G frequencies = 74.0 dB μ V/m.

Test Method: ANSI C63.10: Clause 6.4, 6.6 and 6.7 for Field Strength of Fundamental& Field Strength of Unwanted Emissions

ANSI C63.10: Clause 6.9.2 for Band Edge

Status Pre-test the EUT in continuous transmitting mode with setup as stand-alone in X, Y, Z three axes, found the worst case is X axes and report the data.

Measurement Distance: 3m (Semi-Anechoic Chamber)

Frequency range 9 kHz – 25 GHz for transmitting mode.

Test instrumentation resolution bandwidth

9 kHz (9 kHz - 30 MHz), 120 kHz (30 MHz - 1000 MHz), 1 MHz (1000 MHz – 25 GHz)

Detector: For PK and QP value:

RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz

VBW \geq RBW

Sweep = auto

Detector function = peak

Trace = max hold

For AV value:

RBW = 1 MHz for $f \geq 1$ GHz,

VBW = 10 Hz

Sweep = auto

Detector function = peak

Trace = max hold

Test Procedure:**1)9 kHz to 30 MHz emissions:**

For testing performed with the loop antenna, testing was performed in accordance to ANSI C63.10. The centre of the loop was positioned 1 m above the ground and positioned with its plane vertical at the specified distance from the EUT, During testing the loop was rotated about its vertical axis for maximum response at each azimuth and also investigated with the loop positioned in the horizontal plane.

2)30 MHz to 1 GHz emissions:

For testing performed with the bi-log type antenna, testing was performed in accordance to ANSI C63.10. The measurement is performed with the EUT rotated 360°, the antenna height scanned between 1m and 4m, and the antenna rotated to repeat the measurement for both the horizontal and vertical antenna polarizations.

3)1 GHz to 25 GHz emissions:

Test site with RF absorbing material covering the ground plane that met the site validation criterion called out in CISPR 16-1-4:2007 was used to perform radiated emission test above 1 GHz.


For testing performed with the horn antenna, testing was performed in accordance to ANSI C63.10. The measurement is performed with the EUT rotated 360°, the antenna height scan between 1m and 4m, and the antenna rotated to repeat the measurement for both the horizontal and vertical antenna polarizations.

For the radiated emission test above 1GHz:


Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.

Test Configuration:


1) 9 kHz to 30 MHz emissions:



2) 30 MHz to 1 GHz emissions:




3) 1 GHz to 10 GHz emissions:



The field strength is calculated by adding the Antenna Factor, Cable Loss & Per-amplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Loss – Preamplifier Factor

7.2.1 Duty cycle measurement:



Date: 8 DEC 2015 13:38:22

7.2.2 Fundamental field strength measurement:

Frequency (MHz)	Meter Reading (dB μ V)	Factor (dB)	Emission Level (dB μ V/m)	Limits (dB μ V/m)	Margin (dB)	Detector Type	Antenna polarization
2409	95.68	-5.55	90.13	114	-23.87	Peak	V
2409	84.67	-5.55	79.12	94	-14.88	AVG	V
2409	94.38	-5.55	88.83	114	-25.17	Peak	H
2409	83	-5.55	77.45	94	-16.55	AVG	H
2440	93.68	-5.36	88.32	114	-25.68	Peak	V
2440	83.12	-5.36	77.76	94	-16.24	AVG	V
2440	94.67	-5.36	89.31	114	-24.69	Peak	H
2440	84.67	-5.36	79.31	94	-14.69	AVG	H
2476	96.11	-5.01	91.1	114	-22.9	Peak	V
2476	85.98	-5.01	80.97	94	-13.03	AVG	V
2476	98.67	-5.01	93.66	114	-20.34	Peak	H
2476	87.86	-5.01	82.85	94	-11.15	AVG	H

Note: Measurement Level = Reading Level + Factor

Factor=Ant Factor + Cable Loss– Pre-amplifier.

7.2.3 Radiated Emissions Test Data

9 kHz~30 MHz Field Strength of Unwanted Emissions. Quasi-Peak Measurement

The measurements with active loop antenna were greater than 20dB below the limit, so the test data were not recorded in the test report.

30 MHz~1 GHz Field Strength of Unwanted Emissions. Quasi-Peak Measurement

EUT:	wireless mouse	Model Name :	M7111
Temperature:	25 °C	Test Data	2015-12-03
Pressure:	1010 hPa	Relative Humidity:	60%
Test Mode :	TX 2440 mode(worse-case)	Test Voltage :	DC 3.0V from battery
Measurement Distance	3 m	Frenqucy Range	30MHz to 1GHz
RBW/VBW	100KHz / 300KHz for spectrum, RBW=120KHz for receiver.		

(a) Antenna polarization: Horizontal

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type
39.67	31.27	-11.78	19.49	40	-20.51	QUASI-PEAK
80.25	33.68	-16.68	17	40	-23	QUASI-PEAK
144.64	35.85	-13.17	22.68	43.5	-20.82	QUASI-PEAK
240.17	34.61	-11.25	23.36	46	-22.64	QUASI-PEAK
460.25	32	-8.67	23.33	46	-22.67	QUASI-PEAK
551.78	35.83	-4.52	31.31	46	-14.69	QUASI-PEAK

(b) Antenna polarization: Vertical

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type
45.68	38.65	-11.38	27.27	40	-12.73	QUASI-PEAK
121.35	40	-17.66	22.34	43.5	-21.16	QUASI-PEAK
277.13	34.67	-11.35	23.32	43.5	-20.18	QUASI-PEAK
392.54	35.24	-9.12	26.12	46	-19.88	QUASI-PEAK
443.28	33.51	-5.37	28.14	46	-17.86	QUASI-PEAK
516.38	40.39	-4.38	36.01	46	-9.99	QUASI-PEAK

Note:

Measurement Level = Reading Level + Factor

Factor=Ant Factor + Cable Loss– Pre-amplifier.

Above 1GHz Field Strength of Unwanted Emissions Measurement

EUT:	wireless mouse	Model Name :	M7111
Temperature:	25 °C	Test Data	2015-12-03
Pressure:	1010 hPa	Relative Humidity:	60%
Test Mode :	TX mode	Test Voltage :	DC 3.0V from battery
Measurement Distance	3 m	Frenqucy Range	1GHz to 25GHz
RBW/VBW	1MHz/1MHz for Peak, 1MHz/10Hz for Average. non-restricted band: 100KHz/300KHz for Peak.		

(a) Antenna polarization: Horizontal

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type
4818	55.16	5.06	60.22	74	-13.78	PEAK
4818	44.38	5.06	49.44	54	-4.56	AVERAGE
7227	42.85	7.03	49.88	74	-24.12	PEAK
7227	42.38	7.03	49.41	54	-4.59	AVERAGE
9636	35.17	10.63	45.8	74	-28.2	PEAK
9636	26.97	10.63	37.6	54	-16.4	AVERAGE

(b) Antenna polarization: Vertical

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type
4818	54.68	5.06	59.74	74	-14.26	PEAK
4818	43.18	5.06	48.24	54	-5.76	AVERAGE
7227	46.37	7.03	53.4	74	-20.6	PEAK
7227	37.15	7.03	44.18	54	-9.82	AVERAGE
9636	36.55	10.63	47.18	74	-26.82	PEAK
9636	26.97	10.63	37.6	54	-16.4	AVERAGE

Note:

10~25GHz at least have 20dB margin. No recording in the test report.

Measurement Level = Reading Level + Factor

Factor=Ant Factor + Cable Loss- Pre-amplifier.

Low Channel: 2409 MHz

(a) Antenna polarization: Horizontal

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type
4880	55.97	5.14	61.11	74	-12.89	PEAK
4880	45.64	5.14	50.78	54	-3.22	AVERAGE
7320	50.19	7.52	57.71	74	-16.29	PEAK
7320	40.33	7.52	47.85	54	-6.15	AVERAGE
9760	47.69	11.36	59.05	74	-14.95	PEAK
9760	37.14	11.36	48.5	54	-5.5	AVERAGE

(b) Antenna polarization: Vertical

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type
4880	55.97	5.14	61.11	74	-12.89	PEAK
4880	45.72	5.14	50.86	54	-3.14	AVERAGE
7320	52	7.52	59.52	74	-14.48	PEAK
7320	41.99	7.52	49.51	54	-4.49	AVERAGE
9760	43.37	11.36	54.73	74	-19.27	PEAK
9760	32.87	11.36	44.23	54	-9.77	AVERAGE

Note:

10~25GHz at least have 20dB margin. No recording in the test report.

Measurement Level = Reading Level + Factor

Factor=Ant Factor + Cable Loss– Pre-amplifier.

Middle Channel: 2440 MHz

(a) Antenna polarization: Horizontal

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type
4952	52.67	5.22	57.89	74	-16.11	PEAK
4952	42.22	5.22	47.44	54	-6.56	AVERAGE
7428	51.17	8.06	59.23	74	-14.77	PEAK
7428	41.38	8.06	49.44	54	-4.56	AVERAGE
9904	47.16	12.1	59.26	74	-14.74	PEAK
9904	37.22	12.1	49.32	54	-4.68	AVERAGE

(b) Antenna polarization: Vertical

Frequency (MHz)	Reading Level (dBuV)	Correct Factor (dB)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector Type
4952	50.67	5.22	55.89	74	-18.11	PEAK
4952	41.12	5.22	46.34	54	-7.66	AVERAGE
7428	48	8.06	56.06	74	-17.94	PEAK
7428	37.68	8.06	45.74	54	-8.26	AVERAGE
9904	44.16	12.1	56.26	74	-17.74	PEAK
9904	34.02	12.1	46.12	54	-7.88	AVERAGE

Note:

10~25GHz at least have 20dB margin. No recording in the test report.

Measurement Level = Reading Level + Factor

Factor=Ant Factor + Cable Loss– Pre-amplifier.

High Channel: 2476MHz

7.2.4 Band Edge Measurement:

Ant.Pol. H/V	Freq. (MHz)	Reading		Ant/CF CF(dB)	Act		Limit	
		Peak (dBuv)	AV (dBuv)		Peak (dBuv/m)	AV (dBuv/m)	Peak (dBuv/m)	AV (dBuv/m)
Lowest 2409 MHz								
V	2400	43.15	32.97	-5.72	37.43	27.25	74	54
H	2400	42.33	32.17	-5.72	36.61	26.45	74	54
Highest 2476MHz								
V	2483.5	42.98	31.05	-4.98	38	26.07	74	54
H	2483.5	35.74	27.11	-4.98	30.76	22.13	74	54

Remark:

1). The field strength is calculated by adding the Antenna Factor. Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level =Receiver Reading + Antenna Factor + Cable Loss –Preamplifier Factor.

Test result: The unit does meet the FCC requirements.

7.2.5 Restricted Bands Measurement:

EUT:	wireless mouse	Model Name :	M7111
Temperature:	25 °C	Test Data	2015-12-03
Pressure:	1010 hPa	Relative Humidity:	60%
Test Mode :	TX mode	Test Voltage :	DC 3.0V from battery
Note:	1. The transmitter was setup to transmit at the lowest channel. Then the field strength was measured at 2310-2390 MHz. 2. The transmitter was setup to transmit at the highest channel. Then the field strength was measured at 2483.5-2500 MHz. 3. The data of 2390MHz and 2483.5MHz was the worst.		

Ant.Pol. H/V	Freq. (MHz)	Reading		Ant/CF CF(dB)	Act		Limit	
		Peak (dBuv)	AV (dBuv)		Peak (dBuv/m)	AV (dBuv/m)	Peak (dBuv/m)	AV (dBuv/m)
V	2390	40.17	30.87	-5.79	34.38	25.08	74	54
H	2390	39.68	29.78	-5.79	33.89	23.99	74	54
V	2483.5	40.52	30.65	-4.98	35.54	25.67	74	54
H	2483.5	40.22	30.11	-4.98	35.24	25.13	74	54

Remark:

- (1) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode.
- (2) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna
- (3) Corr.Factor = Antenna Factor + Cable Loss – Pre-amplifier.

7.3 Occupied Bandwidth

Test Requirement: FCC Part 15 C section 15.215


(c) Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

Test Method: ANSI C63.10: Clause 6.9.1


Operation within the band 2409 MHz to 2476MHz

Method of measurement: A small sample of the transmitter output was fed into the Spectrum Analyzer and the attached plot was taken.

Test in the frequency 2409 MHz (20 dB bandwidth)




Test in the frequency 2440 MHz (20 dB bandwidth)



Date: 9 DEC 2015 16:43:41

Test in the frequency 2476MHz (20 dB bandwidth)



Date: 9 DEC 2015 16:46:08

7.4 Conducted Emissions at Mains Terminals 150 kHz to 30 MHz

Test Requirement:	FCC Part 15 C section 15.207
Test Method:	ANSI C63.10: Clause 6.2
Frequency Range:	150 kHz to 30 MHz
Detector:	Peak for pre-scan (9 kHz Resolution Bandwidth)
Test Result	N/A (Please see the remark as below)

Remark: Because the EUT employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines. Measurements to demonstrate compliance with the conducted limits are not required for devices.

8 Photographs

8.1 Radiated Emission Test Setup

Below 1G



Above 1G






9 EUT Constructional Details


















****End of report****