

# INTERTEK TESTING SERVICES

---

## RF Exposure

The equipment under test (EUT) is a 2.4G Wireless Mouse operating at 2.4G Band. The EUT can be powered by DC 1.5V (1 x 1.5V AA Alkaline battery). For more detail information pls. refer to the user manual.

Antenna Type: PCB antenna

Modulation Type: GFSK

Antenna Gain: 3.85dBi Max

The nominal conducted output power specified: -6.85 dBm ( $\pm 3$ dB)

The nominal radiated output power (e.i.r.p) specified: -3.0 dBm ( $\pm 3$ dB)

According to the KDB 447498:

The maximum peak radiated emission for the EUT is 92.5dB $\mu$ V/m at 3m in the frequency 2441.65MHz

The EIRP =  $[(FS^*D)^2 / 30]$  mW = -2.73 dBm  
which is within the production variation.

The minimum peak radiated emission for the EUT is 90.0dB $\mu$ V/m at 3m in the frequency 2480.65MHz

The EIRP =  $[(FS^*D)^2 / 30]$  mW = -5.23 dBm  
which is within the production variation.

The maximum radiated output power specified is 0 dBm = 1 mW

The source- based time-averaging conducted output power

= 1 \* Duty factor mW (where Duty Factor  $\leq 1$ )

= 1 mW

The SAR Exclusion Threshold Level:

=  $3.0 * (\text{min. test separation distance, mm}) / \sqrt{\text{freq. in GHz}}$

=  $3.0 * 5 / \sqrt{2.48065}$  mW

= 9.53 mW

Since the source-based time-averaging conducted output power is well below the SAR low threshold level, so the EUT is considered to comply with SAR requirement without testing.