RF Exposure evaluation

According to 447498 D01 General RF Exposure Guidance v05 The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by: [(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] \cdot [$\sqrt{f(GHz)}$] \leq 3.0 for 1-g SAR and \leq 7.5 for 10-g extremity SAR, where

 $\ensuremath{\text{f(GHz)}}$ is the RF channel transmit frequency in GHz Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

```
eirp = pt x gt = (EXd)^2/30 where:

pt = transmitter output power in watts,

gt = numeric gain of the transmitting antenna (unitless),

E = electric field strength in V/m, --- 10^{((dBuV/m)/20)}/10^6

d = measurement distance in meters (m)---3m

So pt = (EXd)^2/30 x gt

Field strength = 98.11dBuV/m @3m

Ant gain 0dBi; so Ant numeric gain=1

So pt=\{[10^{(98.11/20)}/10^6x3]^2/(30x1)\}x1000mW =1.94mW

So (1.94mW/5mm)x \sqrt{2.402GHz} = 0.6<3
```

Then SAR evaluation is not required