

Products

 Prüfbericht - Nr.:
 14041727 001
 Seite 1 von 14

 Test Report No.:
 Page 1 of 14

Auftraggeber: EMES Smart Devices Limited Client: Rm 8, 5/F, Sunbeam Centre

27 Shing Yip St, Kwun Tong

Hong Kong

Gegenstand der Prüfung: Bluetooth Low Energy Watch

Test Item:

Bezeichnung: Please refer to multiple Serien-Nr.: Engineering sample

Identification: models on page 3 Serial No.:

 Wareneingangs-Nr.:
 A000262929-001,
 Eingangsdatum:
 06.10.2015,

 Receipt No.:
 A000260125-001
 Date of Receipt:
 26.09.2015

Zustand des Prüfgegenstandes bei Anlieferung: Test sample(s) is/are not damaged and

Zustand des Prüfgegenstandes bei Anlieferung:Test sample(s) is/ar suitable for testing.

Prüfort: Hong Kong Productivity Council

Testing Location: HKPC Building, 78 Tat Chee Avenue, Kowloon, Hong Kong

Prüfgrundlage: FCC Part 15 Subpart C
Test Specification: ANSI C63.10-2013

Prüfergebnis: Das vorstehend beschriebene Gerät wurde geprüft und entspricht oben

Test Results: genannter Prüfgrundlage.

The above mentioned product was tested and passed.

Prüflaboratorium: TÜV Rheinland Hong Kong Ltd.

Testing Laboratory: 8 - 10/F., Goldin Financial Global Square, 7 Wang Tai Road, Kowloon Bay,

Kowloon, Hong Kong

geprüft/ tested by: kontrolliert/ reviewed by:

Hugo Wan Sharon Li

12.11.2015 Senior Project Manager

Datum Name/Stellung Unterschrift Datum Name/Stellung Unterschrift Unterschrift

Datum Name/Stellung Unterschrift Datum Name/Stellung Unterschrift

Sonstiges / Other Aspects: FCCID: 2AFXM-000002

passed entspricht Prüfgrundlage Abbreviations: P(ass) Abkürzungen: P(ass) failed entspricht nicht Prüfgrundlage F(ail) F(ail) not applicable N/A N/A nicht anwendbar N/T not tested nicht getestet

Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens.

This test report relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any safety mark on this or similar products.



Table of Content

	Page
Cover Page	1
Table of Content	2
Product information Manufacturers declarations	3 4 4 5
Test Set-up and Operation Mode	6 6 6
Test Methodology Radiated Emission Field Strength Calculation	7
List of Test and Measurement Instruments	8
Results FCC Part 15 – Subpart C	
Subclause 15.204 – Antenna Information	9
Subclause 15.207 – Disturbance Voltage on AC Mains	9
FCC 15.247 (a)(2) – 6dB Bandwidth Measurement	10
FCC 15.247 (b) (1), (3) – Maximum Peak Output Power	10
FCC 15.247 (d) – Spurious Conducted Emissions	
FCC 15.247 (d) – Radiated Spurious Emissions	Pass12
FCC 15.247 (d) – Band Edge Emissions (Conducted)	13
FCC 15.247 (e) - Power Spectral Density	Pass14
Appendix 1 – Test protocols	14 pages
Appendix 2 – Test setup	2 pages
Appendix 3 – Photo documentation	9 pages
Appendix 4 – Product documentation	14 pages
Appendix 5 – Radio Frequency Exposure	2 nages

Date: 12.11.2015



Product information

Manufacturers declarations

	Transceiver
Operating frequency range	2402 - 2480 MHz
Type of modulation	GFSK / FHSS
Number of channels	40
Channel separation	2 MHz
Type of antenna	Chip antenna
Antenna gain (dBi)	0.5
Power level	fix
Type of equipment	stand alone radio device
Connection to public utility power line	No
Nominal voltage	V _{nor} : 3.0 VDC
Independent Operation Modes	Bluetooth communication

Product function and intended use

The Equipment Under Test (EUT) is a Bluetooth Low Energy watch which is powered by battery. It can be connected to Bluetooth enabled smart phone and transfer information to smart phone for data collection.

For details, please refer to the user manual.

Multiple models

The manufacturer declares that the EUT has 5 models as listed in the below table. They are all identical in electrical including schematics, PCB layout and components used except the model number and housing color only.

Due to the manufacturer declaration of equivalence, the model 9328-002 was provided by client as a representative for testing and construction photo taking.

FCCID: 2AFXM-000002

Models	
9328-002	
9328-004	
9328-007	
9328-009	
SMARTL1	

Test Report No.: 14041727 001 Date: 12.11.2015 page 3 of 14



Submitted documents

Circuit Diagram Block Diagram Bill of material User Manual Label Artwork

Remark

--

Test Report No.: 14041727 001 Date: 12.11.2015 page 4 of 14



Independent Operation Modes

The basic operation modes are:

- Radio communication link maintained with data transfer.

For further information refer to User Manual

Related Submittal(s) Grants

This is a single application for certification of the transmitter.

Test Report No.: 14041727 001 Date: 12.11.2015 page 5 of 14





Test Set-up and Operation Mode

Principle of Configuration Selection

Emission: The EUT was configured to measure its highest possible radiation level. The test modes

were adapted accordingly in reference to the instructions for use.

Test Operation and Test Software

Test operation should refer to test methodology.

- 1) The EUT was powered by the button cell.
- 2) A control software provided by client was used on laptop computer to control the transmission frequencies 2402, 2440 and 2480MHz. at highest RF output power and longest burst time.

Special Accessories and Auxiliary Equipment

The product has been tested together with the following additional accessory:

nil

Countermeasures to achieve EMC Compliance

nil

Test Report No.: 14041727 001 Date: 12.11.2015 page 6 of 14



Test Methodology

Radiated Emission

The radiated emission measurements were performed according to the procedures in ANSI C63.10-2013.

For emission measurement at or below 1GHz, the equipment under test (EUT) was placed at the middle of the 80 cm height turntable. For emission testing above 1GHz, the EUT was placed at the middle of 1.5m height turntable. In above two measurement, the turntable is 3 meters far from the measuring antenna. During the testing, the EUT was operated standalone and arranged for maximum emissions. The EUT was tested in three orthogonal planes.

The investigation is performed with the EUT rotated 360° , the antenna height scanned between 1m and 4m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations. Repeat the measurement steps until the maximum emissions were obtained.

All radiated tests were performed at an antenna to EUT with 3 meters distance, unless stated otherwise in particular parts of this test report.

Field Strength Calculation

The field strength at 3 m was established by adding the meter reading of the spectrum analyzer to the factors associated with antenna correction factor, cable loss, preamplifiers and filter attenuation.

The equation is expressed as follow:

FS = R + AF + CF + FA - PA

Where FS = Field Strength in dBuV/m at 3 meters.

R = Reading of Spectrum Analyzer in dBuV.

AF = Antenna Factor in dB.

CF = Cable Attenuation Factor in dB.

FA = Filter Attenuation Factor in dB.

PA = Preamplifier Factor in dB.

FA and PA are only be used for the measuring frequency above 1 GHz.

Test Report No.: 14041727 001 Date: 12.11.2015 page 7 of 14



List of Test and Measurement Instruments

Hong Kong Productivity Council (FCC Registration number: 90656)

Radiated Emission

Equipment	Manufacturer	Туре	S/N	Cal. Date	Cal. Due Date
Semi-anechoic					
Chamber	Frankonia	Nil	Nil	14 Apr 2015	14 Apr 2016
Cable	Hubersuhner	SUCOFLEX 104	72799 /6	31 Mar 2014	31 Mar 2016
Test Receiver	R&S	ESU26	100050	12 Feb 2015	12 Feb 2016
Bi-conical Antenna	R&S	HK116	100241	01 Sep 2015	01 Sep 2017
Log Periodic Antenna	R&S	HL223	841516/017	01 Sep 2015	01 Sep 2017
Coaxial cable	Harbour	LL335	N/A	10 Jun 2014	10 Jun 2016
Microwave amplifer 0.5- 26.5GHz, 25dB gain	HP	83017A	3950M00241	17 Jul 2014	17 Jul 2016
High Pass Filter (cutoff freq. =1000MHz)	Trilithic	23042	9829213	28 Oct 2013	28 Dec 2015
Horn Antenna	EMCO	3115	9002-3347	26 Aug 2015	26 Aug 2017
Active Loop Antenna	EMCO	6502	9107-2651	15 Aug 2015	15 Aug 2016
Spectrum Analyzer	Rohde & Schwarz	FSP30	100007	13 Jan 2015	13 Jan 2017

Test Report No.: 14041727 001 Date: 12.11.2015 page 8 of 14





Results FCC Part 15 - Subpart C

Subclause 15.203 – Antenna Information

Pass

FCC Requirement: No antenna other than that furnished by the responsible party shall be used with the

device

Results: Permanent attached antenna

Verdict: Pass

Subclause 15.204 - Antenna Information

Pass

FCC Requirement: Provide information for every antenna proposed for the use with the EUT

Results:

a) Antenna type: Chip Antenna

b) Manufacturer Johanson Technology c) Model no: 2450AT18B100

d) Gain with reference to an isotropic radiator: 0.5 dBi

Verdict: Pass

Subclause 15.207 - Disturbance Voltage on AC Mains

N/A

There is no AC mains power port on EUT. Hence this test is not applicable.

Test Report No.: 14041727 001 Date: 12.11.2015 page 9 of 14



FCC 15.247 (a)(2) - 6dB Bandwidth Measurement

Pass

FCC Requirement: Systems using digital modulation techniques may operate in the 902 – 928 MHz, 2400 –

2483.5 MHz, and 5725 – 5850 MHz bands. The minimum 6dB bandwidth shall be at

least 500kHz.

Test Specification: KDB 558074 D01 DTS Meas Guidance v03r02 Mode of operation: BLE Tx mode, (2402MHz, 2440MHz, 2480MHz)

Port of testing : Temporary antenna port

Detector : Peak

RBW/VBW : 100KHz/ 300KHz

Supply voltage : 3.0 VDC from DC power supply

Temperature : 23°C Humidity : 50%

Results: For test protocols please refer to Appendix 1, page 2-3.

Channel frequency (MHz)	6 dB left (MHz)	6 dB right (MHz)	6dB bandwidth (MHz)
2402	2401.646	2402.342	0.696
2440	2439.652	2440.336	0.684
2480	2479.646	2480.336	0.690

FCC 15.247 (b) (1), (3) - Maximum Peak Output Power

Pass

FCC Requirement: For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-

5850MHz bands: 1 Watt (30dBm)

Test Specification: KDB 558074 D01 DTS Meas Guidance v03r02 Mode of operation: BLE Tx mode, (2402MHz, 2440MHz, 2480MHz)

Port of testing : Temporary antenna port

Detector : Peak

RBW/VBW : ≥ DTS BW / ≥ 3xRBW

Span : $\geq 3 \times RBW$

Supply voltage : 3.0 VDC from DC power supply

Temperature : 23°C Humidity : 50%

Results: For test protocols please refer to Appendix 1, page 4-5.

Frequency (MHz)	Maximum peak output power (dBm)	Cable attenuation (dB)	Output power (dBm)	Limit (W/dBm)	Verdict
2402	-13.43	1.5	-11.93	1 / 30.0	Pass
2440	-16.21	1.5	-14.71	1 / 30.0	Pass
2480	-18.28	1.5	-16.78	1 / 30.0	Pass

Test Report No.: 14041727 001 Date: 12.11.2015 page 10 of 14



FCC 15.247 (d) - Spurious Conducted Emissions

Pass

Test Specification: KDB 558074 D01 DTS Meas Guidance v03r02 Mode of operation: Tx mode (2402MHz, 2440MHz, 2480MHz)

Port of testing : Temporary antenna port

Detector : Peak

RBW/VBW : 100 kHz / 300 kHz

Supply voltage : 3.0 VDC from DC power supply

Temperature : 23 °C Humidity : 50 %

FCC Requirement: In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or

digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on

either an RF conducted or a radiated measurement.

Results: All three transmit frequency modes comply with the limit stated in subclause 15.247(d).

For test protocols refer to Appendix 1, page 6-11.

Operating frequency (MHz)	Spurious frequency (MHz)	Spurious Level (dBm)	Reference value (dBm)	Delta (dB)	Verdict
2402	3064.980	-53.73	-12.20	-41.53	Pass
2440	0.0355	-54.28	-14.96	-39.32	Pass
2440	2987.160	-43.67	-14.69	-28.98	Pass
2480	0.0355	-52.75	-17.14	-35.61	Pass
2400	3661.600	-44.00	-17.14	-26.86	Pass

Test Report No.: 14041727 001 Date: 12.11.2015 page 11 of 14



FCC 15.247 (d) - Radiated Spurious Emissions

Pass

Test Specification : ANSI C63.10 – 2013

Mode of operation : Tx mode (2402MHz, 2440MHz, 2480MHz), hopping off

Port of testing : Enclosure Detector : Peak

RBW/VBW : 100 kHz / 300 kHz for f < 1 GHz

1 MHz / 3 MHz for f > 1 GHz

Measurement range : 9kHz to 25GHz Supply voltage : 3.0 VDC from battery

Temperature : 23°C Humidity : 50%

FCC Requirement: In any 100kHz bandwidth outside the frequency band at least 20dB below the highest

level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in section15.205(a), must also comply with the radiated emission

limits specified in section 15.209(a).

Results: Pre-scan has been conducted to determine the worst-case mode from all possible

combinations in available packet length.

All three transmit frequency modes comply with the field strength within the restricted

bands. There is no spurious found below 30MHz.

Tx frequency 2402MHz	Vertical Polarization	
Freq	Level	Limit/ Detector
MHz	dBμV/m	dBμV/m
2356.026	46.48	74.0 / P
4804.128	57.23	74.0 / P
4804.000	47.28	54.0 / A
Tx frequency 2402MHz	Horizontal Polarization	
Freq	Level	Limit/ Detector
MHz	dBμV/m	dBμV/m
2372.948	46.57	74.0 / P
Tx frequency 2440MHz	Vertical Polarization	
Freq	Level	Limit/ Detector
MHz	dBμV/m	dBμV/m
4879.696	56.95	74.0 / P
4880.000	46.98	54.0 / A
Tx frequency 2440MHz	Horizontal Polarization	
Freq	Level	Limit/ Detector
MHz	dBμV/m	dBμV/m
4880.096	55.54	74.0 / P
4880.032	43.68	54.0 / A

Test Report No.: 14041727 001 Date: 12.11.2015 page 12 of 14



Tx frequency 2480MHz	Vertical Polarization	
Freq MHz	Level dBμV/m	Limit/ Detector dBµV/m
2493.389	46.60	74.0 / P
4959.487	55.89	74.0 / P
4959.903	43.39	54.0 / A
Tx frequency 2480MHz	Horizontal Polarization	
Freq MHz	Level dBμV/m	Limit/ Detector dBμV/m
2489.238	47.07	74.0 / P

FCC 15.247 (d) – Band Edge Emissions (Conducted)

Pass

Test Specification: KDB 558074 D01 DTS Meas Guidance v03r02

Mode of operation: BLE Tx mode (2402MHz, 2480MHz)

Port of testing : Temporary antenna port

Detector : Peak

RBW/VBW : 100 kHz / 300 kHz

Supply voltage : 3.0 VDC from DC power supply

Temperature : 23°C Humidity : 50%

FCC Requirement: In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or

digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on

either an RF conducted or a radiated measurement.

Results: The peak found outside any 100 kHz bandwidth of the operating frequency band comply

with the requirement. For test protocols refer to Appendix 1, page 12.

Operating frequency (MHz)	Spurious frequency (MHz)	Spurious Level (dBm)	Reference value (dBm)	Delta (dB)	Verdict
2402	2399.940	-56.76	-12.20	-44.56	Pass
2480	2483.520	-61.27	-17.14	-44.13	Pass

Test Report No.: 14041727 001 Date: 12.11.2015 page 13 of 14



FCC 15.247 (e) - Power Spectral Density

Pass

FCC Requirement: For digitally modulated systems, the power spectral density conducted from the

intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band

during any time interval of continuous transmission.

Test Specification: KDB 558074 D01 DTS Meas Guidance v03r02 Mode of operation: BLE Tx mode (2402MHz, 2440MHz, 2480MHz)

Port of testing : Temporary antenna port

Detector : Peak

RBW/VBW : ≥100 kHz / ≥3xRBW span : ≥1.5 x DTS BW

Supply voltage : 3.0 VDC from DC power supply

Temperature : 23°C Humidity : 50%

Results: For test protocols please refer to Appendix 1, page 13-14.

			, p. g	
	Operating frequency (MHz)	Power density (dBm)	Limit (dBm)	Verdict
	2402	-12.20	8.0	Pass
	2440	-14.96	8.0	Pass
	2480	-17.14	8.0	Pass

Test Report No.: 14041727 001 Date: 12.11.2015 page 14 of 14