

RF EXPOSURE EVALUATION

1. PRODUCT INFORMATION

Product Description	TPMS Sensor	NGC	SGC .	100
Model Name	N02		超测	- 4
FCC ID	2AFZB-ZUTMBKPED	of Global Compliance	The double com	C AMESTAL

2. EVALUATION METHOD

According to 447498 D01 General RF Exposure Guidance v05

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] $\cdot [\sqrt{f(GHz)}] \le 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR.

Where f(GHz) is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

3. CALCULATION

According to the follow transmitter output power (P_t) formula: P_t = ($E \times d$) 2 / ($30 \times g_t$) P_t =transmitter output power in watts g_t =numeric gain of the transmitting antenna (unitess) E=electric field strength in V/m d=measurement distance in meters (m)

Pt=-24.67dBm=0.0034mW

The result for RF exposure evaluation SAR= $(0.0034\text{mW} /5\text{mm}) \cdot [\sqrt{0.43392}(\text{GHz})] = 0.00045 < 3.0 for 1-g SAR$

4. CONCLUSION

The SAR evaluation is not required.

The results spowfill this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by 100°C, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a true www.ago.gott.com.