FCC RF Test Report

APPLICANT: Xiaomi Communications Co., Ltd.

EQUIPMENT: Mobile Phone

BRAND NAME : MI

MODEL NAME : M1804C3CG

FCC ID : 2AFZZ-RMSC3CG

STANDARD : FCC Part 15 Subpart C §15.247

CLASSIFICATION : (DTS) Digital Transmission System

The product was received on Apr. 16, 2018 and testing was completed on Jun. 08, 2018. We, Sporton International (Kunshan) Inc., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Kunshan) Inc., the test report shall not be reproduced except in full.



Approved by: James Huang / Manager

Sporton International (Kunshan) Inc.

No.3-2 Ping-Xiang Rd, Kunshan Development Zone Kunshan City Jiangsu Province 215335 China

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AFZZ-RMSC3CG Page Number : 1 of 33
Report Issued Date : Jun. 12, 2018

Report No.: FR841616-01B

Report Version : Rev. 01

TABLE OF CONTENTS

RE	VISIO	N HISTORY	3
SUI	MMAR	RY OF TEST RESULT	4
1	GENE	ERAL DESCRIPTION	5
	1.1	Applicant	5
	1.2	Manufacturer	5
	1.3	Product Feature of Equipment Under Test	5
	1.4	Product Specification of Equipment Under Test	5
	1.5	Modification of EUT	6
	1.6	Testing Location	6
	1.7	Applicable Standards	6
2	TEST	CONFIGURATION OF EQUIPMENT UNDER TEST	7
	2.1	Carrier Frequency Channel	7
	2.2	Test Mode	8
	2.3	Connection Diagram of Test System	9
	2.4	Support Unit used in test configuration and system	9
	2.5	EUT Operation Test Setup	10
	2.6	Measurement Results Explanation Example	10
3	TEST	RESULT	11
	3.1	6dB Bandwidth Measurement	11
	3.2	Output Power Measurement	14
	3.3	Power Spectral Density Measurement	15
	3.4	Conducted Band Edges and Spurious Emission Measurement	20
	3.5	Radiated Band Edges and Spurious Emission Measurement	25
	3.6	AC Conducted Emission Measurement	29
	3.7	Antenna Requirements	31
4	LIST	OF MEASURING EQUIPMENT	32
5	UNCE	ERTAINTY OF EVALUATION	33
API	PENDI	IX A. CONDUCTED TEST RESULTS	
API	PENDI	IX B. AC CONDUCTED EMISSION TEST RESULT	
API	PENDI	IX C. RADIATED SPURIOUS EMISSION	
API	PENDI	IX D. DUTY CYCLE PLOTS	
API	PENDI	IX E. SETUP PHOTOGRAPHS	

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AFZZ-RMSC3CG Page Number : 2 of 33
Report Issued Date : Jun. 12, 2018
Report Version : Rev. 01
Report Template No.: BU5-FR15CBT4.0 Version 2.0

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE	
FR841616-01B	Rev. 01	Initial issue of report	Jun. 12, 2018	

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AFZZ-RMSC3CG Page Number : 3 of 33
Report Issued Date : Jun. 12, 2018
Report Version : Rev. 01
Report Template No.: BU5-FR15CBT4.0 Version 2.0

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	6dB Bandwidth	≥ 0.5MHz	Pass	-
3.2	15.247(b)(3)	Peak Output Power	≤ 30dBm	Pass	-
3.3	15.247(e)	Power Spectral Density	≤ 8dBm/3kHz	Pass	-
3.4	15.247(d)	Conducted Band Edges and Spurious Emission	≤ 20dBc	Pass	-
3.5	15.247(d)	Radiated Band Edges and Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 4.80 dB at 40.670 MHz
3.6	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 10.82 dB at 0.518 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	N/A	Pass	-

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AFZZ-RMSC3CG Page Number : 4 of 33
Report Issued Date : Jun. 12, 2018
Report Version : Rev. 01
Report Template No.: BU5-FR15CBT4.0 Version 2.0

1 General Description

1.1 Applicant

Xiaomi Communications Co., Ltd.

The Rainbow City of China Resources, NO.68, Qinghe Middle Street, Haidian District, Beijing, China

Report No.: FR841616-01B

1.2 Manufacturer

Xiaomi Communications Co., Ltd.

The Rainbow City of China Resources, NO.68, Qinghe Middle Street, Haidian District, Beijing, China

1.3 Product Feature of Equipment Under Test

Product Feature					
Equipment	Mobile Phone				
Brand Name	MI				
Model Name	M1804C3CG				
FCC ID	2AFZZ-RMSC3CG				
	GSM/GPRS/EGPRS/WCDMA/HSPA				
EUT supports Radios application	DC-HSDPA/HSPA+/LTE				
EOT Supports Radios application	WLAN 2.4GHz 802.11b/g/n HT20				
	Bluetooth v3.0 + EDR/ Bluetooth v 4.0 LE/Bluetooth v4.2 LE				
	Conducted: 868673030020056/868673030020064				
IMEI Code	Conduction: 868672030013517/868672030013525				
	Radiation: 868673030019793/868673030019801				
HW Version	P2				
SW Version	MIUI9				
EUT Stage	Production Unit				

Remark:

- **1.** The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
- 2. There are two types of EUT, the difference between two samples is for memory, the sample 1 is 2+32GB capacity and the sample 2 is 2+16GB capacity. According to the difference, we only choose sample 1 to perform full test.

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification					
Tx/Rx Frequency Range	2402 MHz ~ 2480 MHz				
Number of Channels	40				
Carrier Frequency of Each Channel	40 Channel(37 hopping + 3 advertising channel)				
Maximum Output Power to Antenna	-1.60 dBm (0.0007 W)				
Antenna Type / Gain	IFA Antenna type with gain 1.33 dBi				
Type of Modulation	Bluetooth LE : GFSK				

 Sporton International (Kunshan) Inc.
 Page Number
 : 5 of 33

 TEL: +86-512-57900158
 Report Issued Date
 : Jun. 12, 2018

 FAX: +86-512-57900958
 Report Version
 : Rev. 01

 FCC ID: 2AFZZ-RMSC3CG
 Report Template No.: BU5-FR15CBT4.0 Version 2.0

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Testing Location

Sporton International (Kunshan) Inc. is accredited to ISO 17025 by National Voluntary Laboratory Accreditation Program (NVLAP code: 600155-0) and the FCC designation No. is CN5013.

Report No.: FR841616-01B

Test Site	Sporton Interna	Sporton International (Kunshan) Inc.					
Test Site Location	No.3-2 Ping-Xi Province 21533 TEL: +86-512- FAX: +86-512-	57900158	Development 2	Zone Kunshan City Jiangsu			
Test Site No.		Sporton Site No.		FCC Test Firm Registration No.			
	TH01-KS	03CH02-KS	CO01-KS	630927			

Note: The test site complies with ANSI C63.4 2014 requirement.

1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15 Subpart C §15.247
- FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04
- ANSI C63.10-2013

Remark:

- All test items were verified and recorded according to the standards and without any deviation during the test.
- 2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

 Sporton International (Kunshan) Inc.
 Page Number
 : 6 of 33

 TEL: +86-512-57900158
 Report Issued Date
 : Jun. 12, 2018

 FAX: +86-512-57900958
 Report Version
 : Rev. 01

FCC ID: 2AFZZ-RMSC3CG Report Template No.: BU5-FR15CBT4.0 Version 2.0

2 Test Configuration of Equipment Under Test

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
	0	2402	21	2444
	1	2404	22	2446
	2	2406	23	2448
	3	2408	24	2450
	4	2410	25	2452
	5	2412	26	2454
	6	2414	27	2456
	7	2416	28	2458
	8	2418	29	2460
	9	2420	30	2462
2400-2483.5 MHz	10	2422	31	2464
	11	2424	32	2466
	12	2426	33	2468
	13	2428	34	2470
	14	2430	35	2472
	15	2432	36	2474
	16	2434	37	2476
	17	2436	38	2478
	18	2438	39	2480
	19	2440	-	-
	20	2442	-	-

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AFZZ-RMSC3CG Page Number : 7 of 33
Report Issued Date : Jun. 12, 2018
Report Version : Rev. 01

Report Template No.: BU5-FR15CBT4.0 Version 2.0

2.2 Test Mode

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Z plane) were recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

The following summary table is showing all test modes to demonstrate in compliance with the standard.


	Summary table of Test Cases
Test Item	Data Rate / Modulation
rest item	Bluetooth – LE / GFSK
Conducted	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps
TCs	Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps
105	Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps
Radiated	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps
	Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps
TCs	Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps
AC	Made 1: CSM 950 Idle + Divotoeth Link + W/I AN Link/2 4C) + Fernhane + LISP
Conducted	Mode 1: GSM 850 Idle + Bluetooth Link + WLAN Link(2.4G) + Earphone + USB
Emission	Cable1(Charging from Adapter1)
Remark: For	Radiated Test Cases, The tests were performed with Adapter 1, Earphone , USB Cable 1.

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AFZZ-RMSC3CG Page Number : 8 of 33
Report Issued Date : Jun. 12, 2018
Report Version : Rev. 01

Report No.: FR841616-01B

2.3 Connection Diagram of Test System



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded,1.8m
2.	Notebook	Lenovo	G480	N/A	N/A	AC I/P: Unshielded, 1.8 m DC O/P: Shielded, 1.8 m
3.	Bluetooth Earphone	Xiaomi	LYEJ02LM	N/A	N/A	N/A
4.	WLAN AP	D-link	DIR-855	KA2DIR855A2	N/A	Unshielded,1.8m
5.	Earphone	Lenovo	SH100	N/A	Unshielded,1.2m	N/A

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AFZZ-RMSC3CG Page Number : 9 of 33
Report Issued Date : Jun. 12, 2018
Report Version : Rev. 01
Report Template No.: BU5-FR15CBT4.0 Version 2.0

2.5 EUT Operation Test Setup

For Bluetooth LE function, the engineering test program was provided and enabled to make EUT continuous transmit/receive.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss

Offset = RF cable loss

Following shows an offset computation example with cable loss 5.4 dB

 $Offset(dB) = RF \ cable \ loss(dB).$ = 5.4 (dB)

Page Number : 10 of 33
Report Issued Date : Jun. 12, 2018
Report Version : Rev. 01

Report No.: FR841616-01B

3 Test Result

3.1 6dB Bandwidth Measurement

3.1.1 Limit of 6dB Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.1.3 Test Procedures

- 1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04.
- 2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
- 3. Set to the maximum power setting and enable the EUT transmit continuously.
- 4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
- 5. Measure and record the results in the test report.

3.1.4 Test Setup




Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AFZZ-RMSC3CG Page Number : 11 of 33
Report Issued Date : Jun. 12, 2018
Report Version : Rev. 01
Report Template No.: BU5-FR15CBT4.0 Version 2.0

3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.

6 dB Bandwidth Plot on Channel 00




Date: 30.MAY.2018 10:33:23

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AFZZ-RMSC3CG Page Number : 12 of 33
Report Issued Date : Jun. 12, 2018
Report Version : Rev. 01


Report No.: FR841616-01B

6 dB Bandwidth Plot on Channel 19



Date: 30.MAY.2018 10:37:14

6 dB Bandwidth Plot on Channel 39



Date: 30.MAY.2018 10:40:07

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AFZZ-RMSC3CG Page Number : 13 of 33
Report Issued Date : Jun. 12, 2018
Report Version : Rev. 01

Report No.: FR841616-01B

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna of directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


3.2.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.2.3 Test Procedures

- The testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas.
 Guidance v04 section 9.1.3 PKPM1 Peak power meter method.
- 2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
- 3. Set to the maximum power setting and enable the EUT transmit continuously.
- 4. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Peak Output Power

Please refer to Appendix A.

3.2.6 Test Result of Average Output Power (Reporting Olny)

Please refer to Appendix A.

Sporton International (Kunshan) Inc. TEL: +86-512-57900158

FAX: +86-512-57900958 FCC ID: 2AFZZ-RMSC3CG Page Number : 14 of 33

Report No.: FR841616-01B

Report Issued Date : Jun. 12, 2018
Report Version : Rev. 01

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.


3.3.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.3.3 Test Procedures

- The testing follows Measurement Procedure 10.2 Method PKPSD of FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04
- 2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
- 3. Set to the maximum power setting and enable the EUT transmit continuously.
- 4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
- 5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
- 6. Measure and record the results in the test report.
- 7. The Measured power density (dBm)/ 100kHz is a reference level and used as 20dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.

Sporton International (Kunshan) Inc.


TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AFZZ-RMSC3CG Page Number : 15 of 33
Report Issued Date : Jun. 12, 2018

Report No.: FR841616-01B

Report Version : Rev. 01
Report Template No.: BU5-FR15CBT4.0 Version 2.0


3.3.6 Test Result of Power Spectral Density Plots (100kHz)

PSD 100kHz Plot on Channel 00



Date: 30.MAY.2018 10:34:06

PSD 100kHz Plot on Channel 19




Date: 30.MAY.2018 10:37:48

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AFZZ-RMSC3CG Page Number : 16 of 33
Report Issued Date : Jun. 12, 2018
Report Version : Rev. 01

Report No.: FR841616-01B

PSD 100kHz Plot on Channel 39




Date: 30.MAY.2018 10:40:39

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AFZZ-RMSC3CG Page Number : 17 of 33
Report Issued Date : Jun. 12, 2018
Report Version : Rev. 01

Report Template No.: BU5-FR15CBT4.0 Version 2.0


3.3.7 Test Result of Power Spectral Density Plots (3kHz)

PSD 3kHz Plot on Channel 00



Date: 30.MAY.2018 15:10:09

PSD 3kHz Plot on Channel 19




Date: 30.MAY.2018 10:37:31

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AFZZ-RMSC3CG Page Number : 18 of 33
Report Issued Date : Jun. 12, 2018
Report Version : Rev. 01

Report No.: FR841616-01B

PSD 3kHz Plot on Channel 39



Date: 30.MAY.2018 10:40:22

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AFZZ-RMSC3CG Page Number : 19 of 33
Report Issued Date : Jun. 12, 2018
Report Version : Rev. 01

Report No.: FR841616-01B

3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission

All harmonics/spurious must be at least 20 dB down from the highest emission level within the authorized band.


3.4.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.4.3 Test Procedure

- 1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04.
- 2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
- 3. Set to the maximum power setting and enable the EUT transmit continuously.
- 4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
- 5. Measure and record the results in the test report.
- 6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup



Sporton International (Kunshan) Inc. TEL: +86-512-57900158

FAX: +86-512-57900958 FCC ID: 2AFZZ-RMSC3CG Page Number : 20 of 33


Report Issued Date : Jun. 12, 2018

Report No.: FR841616-01B

Report Version : Rev. 01


3.4.5 Test Result of Conducted Band Edges Plots

Low Band Edge Plot on Channel 00



Date: 30.MAY.2018 10:34:19

High Band Edge Plot on Channel 39



Date: 30.MAY.2018 10:40:50


Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AFZZ-RMSC3CG Page Number : 21 of 33
Report Issued Date : Jun. 12, 2018
Report Version : Rev. 01

Report No.: FR841616-01B


3.4.6 Test Result of Conducted Spurious Emission Plots

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 00



Date: 30.MAY.2018 10:34:35

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 00




Date: 30.MAY.2018 10:35:05

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AFZZ-RMSC3CG Page Number : 22 of 33
Report Issued Date : Jun. 12, 2018
Report Version : Rev. 01


Report No.: FR841616-01B

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 19



Date: 30.MAY.2018 10:37:58

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 19




Date: 30.MAY.2018 10:38:13

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AFZZ-RMSC3CG Page Number : 23 of 33
Report Issued Date : Jun. 12, 2018
Report Version : Rev. 01


Report No.: FR841616-01B

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 39



Date: 30.MAY.2018 10:41:00

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 39



Date: 30.MAY.2018 10:41:18

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AFZZ-RMSC3CG Page Number : 24 of 33
Report Issued Date : Jun. 12, 2018
Report Version : Rev. 01

Report No.: FR841616-01B

3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency	Field Strength	Measurement Distance
(MHz)	(microvolts/meter)	(meters)
0.009 - 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AFZZ-RMSC3CG Page Number : 25 of 33

Report Issued Date : Jun. 12, 2018

Report Version : Rev. 01

Report No.: FR841616-01B

3.5.3 Test Procedures

- 1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04.
- 2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.

Report No.: FR841616-01B

- 3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
- 4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
- 5. Corrected Reading: Antenna Factor + Cable Loss + Read Level Preamp Factor = Level
- 6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
- 7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
- 8. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for f < 1 GHz; VBW ≥ RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \ge 1$ GHz for peak measurement. For average measurement:
 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW ≥ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

 Sporton International (Kunshan) Inc.
 Page Number
 : 26 of 33


 TEL: +86-512-57900158
 Report Issued Date
 : Jun. 12, 2018

 FAX: +86-512-57900958
 Report Version
 : Rev. 01


FCC ID: 2AFZZ-RMSC3CG Report Template No.: BU5-FR15CBT4.0 Version 2.0

3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AFZZ-RMSC3CG Page Number : 27 of 33
Report Issued Date : Jun. 12, 2018
Report Version : Rev. 01

Report No.: FR841616-01B

3.5.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

Report No.: FR841616-01B

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C

3.5.7 Duty Cycle

Please refer to Appendix D.

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix C .

 Sporton International (Kunshan) Inc.
 Page Number
 : 28 of 33

 TEL: +86-512-57900158
 Report Issued Date
 : Jun. 12, 2018

 FAX: +86-512-57900958
 Report Version
 : Rev. 01

FCC ID: 2AFZZ-RMSC3CG Report Template No.: BU5-FR15CBT4.0 Version 2.0

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Report No.: FR841616-01B

Ereguency of emission (MUz)	Conducted limit (dBμV)				
Frequency of emission (MHz)	Quasi-peak	Average			
0.15-0.5	66 to 56*	56 to 46*			
0.5-5	56	46			
5-30	60	50			

^{*}Decreases with the logarithm of the frequency.

3.6.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.6.3 Test Procedures

- 1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
- 2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
- 3. All the support units are connecting to the other LISN.
- 4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
- 5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
- 6. Both sides of AC line were checked for maximum conducted interference.
- 7. The frequency range from 150 kHz to 30 MHz was searched.
- 8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.


 Sporton International (Kunshan) Inc.
 Page Number
 : 29 of 33

 TEL: +86-512-57900158
 Report Issued Date
 : Jun. 12, 2018

 FAX: +86-512-57900958
 Report Version
 : Rev. 01

 FCC ID: 2AFZZ-RMSC3CG
 Report Template No.: BU5-FR15CBT4.0 Version 2.0

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AFZZ-RMSC3CG Page Number : 30 of 33
Report Issued Date : Jun. 12, 2018
Report Version : Rev. 01

Report No.: FR841616-01B

3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

Report No.: FR841616-01B

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AFZZ-RMSC3CG Page Number : 31 of 33
Report Issued Date : Jun. 12, 2018
Report Version : Rev. 01

4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Aug. 08, 2017	May 30, 2018~ Jun. 01, 2018	Aug. 07, 2018	Conducted (TH01-KS)
Pulse Power Senor	Anritsu	MA2411B	0917070	300MHz~40GH z	Jan. 18, 2018	May 30, 2018~ Jun. 01, 2018	Jan. 17, 2019	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	50MHz Bandwidth	Jan. 18, 2018	May 30, 2018~ Jun. 01, 2018	Jan. 17, 2019	Conducted (TH01-KS)
EMI Test Receiver	R&S	ESR7	101403	9kHz~7GHz;Ma x 30dBm	Aug. 08, 2017	Jun. 08, 2018	Aug. 07, 2018	Radiation (03CH02-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY551502 08	10Hz-44G,MAX 30dB	Apr. 17, 2018	Jun. 08, 2018	Apr. 16, 2019	Radiation (03CH02-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Oct. 22, 2017	Jun. 08, 2018	Oct. 21, 2018	Radiation (03CH02-KS)
Bilog Antenna	TeseQ	CBL6112D	23182	30MHz-2GHz	Jan. 29, 2018	Jun. 08, 2018	Jan. 28, 2019	Radiation (03CH02-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	75957	1GHz~18GHz	Oct. 21, 2017	Jun. 08, 2018	Oct. 20, 2018	Radiation (03CH02-KS)
SHF-EHF Horn	Schwarzbeck	BBHA 9170	BBHA1702 49	15GHz~40GHz	Feb. 07, 2018	Jun. 08, 2018	Feb. 06, 2019	Radiation (03CH02-KS)
Amplifier	SONOMA	310N	187289	9KHz-1GHz	Aug. 07, 2017	Jun. 08, 2018	Aug. 06, 2018	Radiation (03CH02-KS)
Amplifier	Agilent	8449B	3008A023 84	1GHz~26.5GHz	Oct. 12, 2017	Jun. 08, 2018	Oct. 11, 2018	Radiation (03CH02-KS)
Amplifier	MITEQ	TTA1840-35- HG	1887435	18~40GHz	Oct. 12, 2017	Jun. 08, 2018	Oct. 11, 2018	Radiation (03CH02-KS)
AC Power Source	Chroma	61601	616010002 473	N/A	NCR	Jun. 08, 2018	NCR	Radiation (03CH02-KS)
Turn Table	MF	MF7802	N/A	0~360 degree	NCR	Jun. 08, 2018	NCR	Radiation (03CH02-KS)
Antenna Mast	MF	MF7802	N/A	1 m~4 m	NCR	Jun. 08, 2018	NCR	Radiation (03CH02-KS)
EMI Receiver	R&S	ESCI7	100768	9kHz~7GHz;	Apr. 19, 2018	May 12, 2018	Apr. 18, 2019	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060103	9kHz~30MHz	Oct. 13, 2017	May 12, 2018	Oct. 12, 2018	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060105	9kHz~30MHz	Oct. 13, 2017	May 12, 2018	Oct. 12, 2018	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP00000 0811	AC 0V~300V, 45Hz~1000Hz	Oct. 12, 2017	May 12, 2018	Oct. 11, 2018	Conduction (CO01-KS)

NCR: No Calibration Required

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AFZZ-RMSC3CG Page Number : 32 of 33
Report Issued Date : Jun. 12, 2018

Report No. : FR841616-01B

Report Version : Rev. 01
Report Template No.: BU5-FR15CBT4.0 Version 2.0



Uncertainty of Evaluation 5

<u>Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)</u>

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.9dB
01 33 % (0 = 20C(y))	

Report No.: FR841616-01B

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence	4.2 dB
of 95% (U = 2Uc(y))	4.2 UB

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence	4.2 dB
of 95% (U = 2Uc(y))	4.2 UB

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence	4.7 dB
of 95% (U = 2Uc(y))	4.7 uB

Sporton International (Kunshan) Inc. Page Number : 33 of 33 TEL: +86-512-57900158 Report Issued Date: Jun. 12, 2018 Report Version FAX: +86-512-57900958 : Rev. 01 Report Template No.: BU5-FR15CBT4.0 Version 2.0

FCC ID: 2AFZZ-RMSC3CG

Report Number: FR841616-01B

Bluetooth Low Energy

Test Engineer:	Silent Hai	Temperature:	21~25	°C
Test Date:	2018/5/30~2018/6/1	Relative Humidity:	51~55	%

TEST RESULTS DATA 6dB and 99% Occupied Bandwidth

Mod.	Data Rate	N⊤x	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail		
BLE	1Mbps 1		0	2402	1.03	0.67	0.50	Pass		
BLE	1Mbps 1		BLE 1Mbps		19	2440	1.03	0.67	0.50	Pass
BLE	1Mbps 1		39	2480	1.03	0.67	0.50	Pass		

TEST RESULTS DATA

Peak Power Table

Mod.	Data Rate	N⊤x	CH.	Freq. (MHz)	Peak Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail	
BLE	1Mbps	1	0	2402	-2.33	30.00	1.33	-1.00	36.00	Pass	
BLE	1Mbps	1	19	2440	-1.60	30.00	1.33	-0.27	36.00	Pass	
BLE	1Mbps	1	39	2480	-1.97	30.00	1.33	-0.64	36.00	Pass	

TEST RESULTS DATA Average Power Table

(Reporting Only)

Mod.	Data Rate	N⊤x	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)
BLE	1Mbps	1	0	2402	2.14	-2.68
BLE	1Mbps	1	19	2440	2.14	-1.94
BLE	1Mbps	1	39	2480	2.14	-2.28


TEST RESULTS DATA

Peak Power Density

Mod.	Data Rate	N⊤x	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	(dBm (dBi)		Pass/Fail
BLE	1Mbps	1	0	2402	-2.91	-19.35	1.33	8.00	Pass
BLE	1Mbps	1	19	2440	-1.92	-18.40	1.33	8.00	Pass
BLE	1Mbps	1	39	2480	-2.88	-19.33	1.33	8.00	Pass


Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 20dBc limit.

Appendix B. AC Conducted Emission Test Results



TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AFZZ-RMSC3CG Page Number : B1 of B3
Report Issued Date : Jun. 12, 2018
Report Version : Rev. 01
Report Template No.: BU5-FR15CBT4.0 Version 2.0

Report No.: FR841616-01B



Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AFZZ-RMSC3CG

Page Number : B2 of B3 Report Issued Date: Jun. 12, 2018 Report Version : Rev. 01 Report Template No.: BU5-FR15CBT4.0 Version 2.0 Test Engineer : Amos Zhang


Temperature : 24.1~24.4°C

Relative Humidity : 40~42%

Test Voltage : 120Vac / 60Hz

Phase : Neutral

Report No.: FR841616-01B



Site : CO01-KS

Condition : FCC PART 15C LISN-N-171013-060103 NEUTRAL

mode : Mode 1

:868672030013517/868672030013525 #27

	Freq	Level				LISN Factor		Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
18 19 20	2.422	38.82	-17.18	56.00	28.30	0.32	10.20	Average QP Average

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AFZZ-RMSC3CG Page Number : B3 of B3
Report Issued Date : Jun. 12, 2018
Report Version : Rev. 01

Appendix C. Radiated Spurious Emission

15C 2.4GHz 2400~2483.5MHz

BLE (Band Edge @ 3m)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBµV/m)	(dB)	(dBµV/m)	(dBµV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
		2358.75	51.42	-22.58	74	51.21	31.76	5.12	36.67	125	38	Р	Н
D. F		2370.97	41.47	-12.53	54	41.22	31.78	5.12	36.65	125	38	Α	Н
	*	2402	85.86	-	-	85.56	31.8	5.14	36.64	125	38	Р	Н
BLE CH 00	*	2402	85.17	-	-	84.87	31.8	5.14	36.64	125	38	Α	Н
2402MHz		2376.17	51.45	-22.55	74	51.2	31.78	5.12	36.65	132	96	Р	V
2402111112		2372.92	41.62	-12.38	54	41.37	31.78	5.12	36.65	132	96	Α	V
	*	2402	90.2	-	-	89.9	31.8	5.14	36.64	132	96	Р	V
	*	2402	89.39	1	-	89.09	31.8	5.14	36.64	132	96	Α	V
	*	2480	91.22	ı	-	90.57	32.09	5.24	36.68	111	39	Р	Н
	*	2480	90.68	-	-	90.03	32.09	5.24	36.68	111	39	Α	Н
D. F.		2483.56	50.75	-23.25	74	50.1	32.09	5.24	36.68	111	39	Р	Н
BLE CH 39		2483.51	41.55	-12.45	54	40.9	32.09	5.24	36.68	111	39	Α	Н
2480MHz	*	2480	93.18	-	-	92.53	32.09	5.24	36.68	146	96	Р	V
240011112	*	2480	92.76	1	-	92.11	32.09	5.24	36.68	146	96	Α	٧
		2485.24	51.13	-22.87	74	50.48	32.09	5.24	36.68	146	96	Р	V
		2483.51	41.78	-12.22	54	41.13	32.09	5.24	36.68	146	96	Α	V
Remark		o other spurious		eak and	Average lim	it line.							

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AFZZ-RMSC3CG Page Number : C1 of C5 Report Issued Date : Jun. 12, 2018

Report No.: FR841616-01B

Report Version : Rev. 01

15C 2.4GHz 2400~2483.5MHz

BLE (Harmonic @ 3m)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBµV/m)	(dB)	$(dB\mu V/m)$	(dB _µ V)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BLE		4804	39.66	-34.34	74	62.24	34.22	7.7	64.5	102	5	Р	Н
CH 00													
2402MHz		4804	39.72	-34.28	74	62.3	34.22	7.7	64.5	102	0	Р	V
		4880	40.1	-33.9	74	62.62	34.31	7.77	64.6	102	0	Р	Н
BLE CH 19		7320	39.95	-34.05	74	59.88	35.8	9.29	65.02	102	0	Р	Н
2440MHz		4880	39.72	-34.28	74	62.24	34.31	7.77	64.6	102	0	Р	V
244011112		7320	39.87	-34.13	74	59.8	35.8	9.29	65.02	102	0	Р	V
DI E		4960	40.83	-33.17	74	63.31	34.43	7.82	64.73	102	0	Р	Н
BLE CH 39		7440	40.5	-33.5	74	60.3	35.87	9.41	65.08	102	0	Р	Н
2480MHz		4960	41.11	-32.89	74	63.59	34.43	7.82	64.73	102	0	Р	V
2.0311112		7440	40.55	-33.45	74	60.35	35.87	9.41	65.08	102	0	Р	V

Remark

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCCID: 2AFZZ-RMSC3CG Page Number : C2 of C5
Report Issued Date : Jun. 12, 2018

Report No.: FR841616-01B

Report Version : Rev. 01

^{1.} No other spurious found.

^{2.} All results are PASS against Peak and Average limit line.

15C Emission below 1GHz

2.4GHz BLE (LF)

BLE	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBµV/m)	(dB)	(dBµV/m)	(dBµV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
		30	22.23	-17.77	40	29.19	24.5	0.57	32.03	-	-	Р	Н
		32.91	21.78	-18.22	40	30.42	22.79	0.61	32.04	-	ı	Р	Н
		42.61	24.18	-15.82	40	38.17	17.44	0.65	32.08	100	318	Р	Н
		112.45	20.92	-22.58	43.5	34.07	17.68	1.08	31.91	ï	1	Р	Н
		171.62	26.32	-17.18	43.5	41.29	15.46	1.34	31.77	1	-	Р	Н
2.4GHz BLE		288.02	23.99	-22.01	46	34.51	18.82	1.88	31.22	ı	1	Р	Н
LF		32.91	32.83	-7.17	40	41.47	22.79	0.61	32.04	i	1	Р	V
		40.67	35.2	-4.8	40	48.26	18.35	0.64	32.05	100	25	Р	V
		49.4	29.57	-10.43	40	46.71	14.25	0.71	32.1	ı	1	Р	٧
		86.26	20.88	-19.12	40	37.7	14.26	0.96	32.04	ı	-	Р	٧
		171.62	25.26	-18.24	43.5	40.23	15.46	1.34	31.77	ı	-	Р	٧
		954.41	31.2	-22.8	54	28.1	27	3.21	27.11	ı	1	Р	٧
Remark	1. No other spurious found. rk 2. All results are PASS against limit line.												

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AFZZ-RMSC3CG Page Number : C3 of C5 Report Issued Date : Jun. 12, 2018

Report No. : FR841616-01B

Report Version : Rev. 01

Note symbol

	Fundamental Frequency which can be ignored. However, the level of any						
*	unwanted emissions shall not exceed the level of the fundamental frequency per						
	15.209(c).						
!	Test result is over limit line.						
P/A	Peak or Average						
H/V	Horizontal or Vertical						

Sporton International (Kunshan) Inc.
TEL: +86-512-57900158

FAX: +86-512-57900958 FCC ID: 2AFZZ-RMSC3CG Page Number : C4 of C5
Report Issued Date : Jun. 12, 2018
Report Version : Rev. 01

Report No. : FR841616-01B

A calculation example for radiated spurious emission is shown as below:

Report No.: FR841616-01B

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		(MHz)	(dBµV/m)	(dB)	(dBµV/m)	(dBµV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	Р	Н
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	Α	Н

1. Level($dB\mu V/m$) =

Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBµV) - Preamp Factor(dB)

2. Over Limit(dB) = Level(dB μ V/m) – Limit Line(dB μ V/m)

For Peak Limit @ 2390MHz:

- 1. Level(dBµV/m)
- = Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBµV) Preamp Factor(dB)
- $= 32.22(dB/m) + 4.58(dB) + 54.51(dB\mu V) 35.86 (dB)$
- $= 55.45 (dB\mu V/m)$
- 2. Over Limit(dB)
- = Level($dB\mu V/m$) Limit Line($dB\mu V/m$)
- $= 55.45(dB\mu V/m) 74(dB\mu V/m)$
- = -18.55(dB)

For Average Limit @ 2390MHz:

- 1. Level(dBµV/m)
- = Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBµV) Preamp Factor(dB)
- $= 32.22(dB/m) + 4.58(dB) + 42.6(dB\mu V) 35.86 (dB)$
- $= 43.54 (dB\mu V/m)$
- 2. Over Limit(dB)
- = Level($dB\mu V/m$) Limit Line($dB\mu V/m$)
- $= 43.54(dB\mu V/m) 54(dB\mu V/m)$
- = -10.46(dB)

Both peak and average measured complies with the limit line, so test result is "PASS".

 Sporton International (Kunshan) Inc.
 Page Number
 : C5 of C5

 TEL: +86-512-57900158
 Report Issued Date
 : Jun. 12, 2018

 FAX: +86-512-57900958
 Report Version
 : Rev. 01


FCC ID: 2AFZZ-RMSC3CG Report Template No.: BU5-FR15CBT4.0 Version 2.0



Appendix D. Duty Cycle Plots

Band	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting
Bluetooth LE	61.11	0.383	2.611	3KHz

Bluetooth LE



Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AFZZ-RMSC3CG Page Number : D1 of D1
Report Issued Date : Jun. 12, 2018
Report Version : Rev. 01

Report No.: FR841616-01B