## **FCC RF Test Report**

APPLICANT : Xiaomi Communications Co., Ltd.

**EQUIPMENT**: Mobile Phone

BRAND NAME : Redmi

MODEL NAME : M1903C3EH

FCC ID : 2AFZZ-RMSC3EH STANDARD : 47 CFR Part 2, 27(L)

CLASSIFICATION : PCS Licensed Transmitter Held to Ear (PCE)

The product was received on Mar. 12, 2019 and completely tested on Jun. 03, 2019. We, Sporton International (Kunshan) Inc., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.26-2015 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Kunshan) Inc., the test report shall not be reproduced except in full.

JasonJia

Reviewed by: Jason Jia / Supervisor

Approved by: James Huang / Manager

Sporton International (Kunshan) Inc.

No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300

People's Republic of China

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AFZZ-RMSC3EH Page Number : 1 of 21
Report Issued Date : Jun. 06, 2019
Report Version : Rev. 01

Report Template No.: BU5-FG27 Version 2.0

## **TABLE OF CONTENTS**

RE	VISIO	N HISTORY	3
SU	MMAF	RY OF TEST RESULT	4
1	GENE	ERAL DESCRIPTION	5
	1.1	Applicant	5
	1.2	Product Feature of Equipment Under Test	5
	1.3	Product Specification of Equipment Under Test	6
	1.4	Modification of EUT	
	1.5	Maximum EIRP Power, Frequency Tolerance, and Emission Designator	
	1.6	Testing Location	
	1.7	Applicable Standards	
2	TEST	CONFIGURATION OF EQUIPMENT UNDER TEST	9
	2.1	Test Mode	g
	2.2	Connection Diagram of Test System	
	2.3	Support Unit used in test configuration	
	2.4	Measurement Results Explanation Example	
	2.5	Frequency List of Low/Middle/High Channels	
3	CONI	DUCTED TEST RESULT	11
	3.1	Measuring Instruments	11
	3.2	Test Setup	
	3.3	Test Result of Conducted Test	
	3.4	Conducted Output Power and ERP/EIRP	
	3.5	Peak-to-Average Ratio	
	3.6	99% Occupied Bandwidth and 26dB Bandwidth Measurement	
	3.7	Conducted Band Edge	
	3.8	Conducted Spurious Emission	
	3.9	Frequency Stability	
4	RADI	ATED TEST ITEMS	
	4.1	Measuring Instruments	
	4.2	Test Setup	
	4.3	Test Result of Radiated Test	
	4.4	Field Strength of Spurious Radiation Measurement	
5	LIST	OF MEASURING EQUIPMENT	20
6	UNCE	ERTAINTY OF EVALUATION	21
ΑP	PEND	IX A. TEST RESULTS OF CONDUCTED TEST	
ΑP	PEND	IX B. TEST RESULTS OF RADIATED TEST	
ΑP	PEND	IX C. TEST SETUP PHOTOGRAPHS	

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AFZZ-RMSC3EH Page Number : 2 of 21
Report Issued Date : Jun. 06, 2019
Report Version : Rev. 01

Report Template No.: BU5-FG27 Version 2.0

## **REVISION HISTORY**

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG931208-01C	Rev. 01	Initial issue of report	Jun. 06, 2019

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AFZZ-RMSC3EH Page Number : 3 of 21
Report Issued Date : Jun. 06, 2019
Report Version : Rev. 01

Report Template No.: BU5-FG27 Version 2.0

## **SUMMARY OF TEST RESULT**

Report Section	FCC Rule	Description	Limit	Result	Remark
2.4	§2.1046	Conducted Output Power	Reporting Only	PASS	-
3.4	§27.50(d)(4)	Equivalent Isotropic Radiated Power	< 1 Watts	PASS	1
3.5	N/A	Peak-to-Average Ratio	< 13 dB	PASS	-
3.6	§2.1049	Occupied Bandwidth	Reporting Only	PASS	-
3.7	§2.1051 §27.53(h)	Band Edge Measurement	< 43+10log10(P[Watts])	PASS	-
3.8	§2.1051 §27.53(h)	Conducted Emission	< 43+10log10(P[Watts])	PASS	-
3.9	§2.1055 §27.54	Frequency Stability for Temperature & Voltage	Within Authorized Band	PASS	-
4.4	§2.1053 §27.53(h)	Field Strength of Spurious Radiation	< 43+10log10(P[Watts])	PASS	Under limit 40.78 dB at 6936.000 MHz

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AFZZ-RMSC3EH Page Number : 4 of 21
Report Issued Date : Jun. 06, 2019
Report Version : Rev. 01

Report Template No.: BU5-FG27 Version 2.0

## 1 General Description

## 1.1 Applicant

Xiaomi Communications Co., Ltd.

The Rainbow City of China Resources, NO.68, Qinghe Middle Street, Haidian District, Beijing, China

## 1.2 Product Feature of Equipment Under Test

	Product Feature
Equipment	Mobile Phone
Brand Name	Redmi
Model Name	M1903C3EH
FCC ID	2AFZZ-RMSC3EH
EUT supports Radios application	GSM/GPRS/EGPRS/WCDMA/HSPA/ DC-HSDPA/HSPA+(16QAM uplink is not supported)/LTE WLAN 2.4GHz 802.11b/g/n HT20 Bluetooth BR /EDR/ LE FM Receiver / GNSS
IMEI Code	Conducted: 869323040059228/869323040059236 Radiation: 869323040058808/869323040058816
HW Version	V2
SW Version	MIUI10
EUT Stage	Identical Prototype

#### Remark:

- **1.** The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
- 2. There are two types of EUT sample 1 and sample 2, the differences between two samples is for memory, sample 1 is 2+32GB capacity and sample 2 is 2+16GB capacity. According to the difference, we only choose sample 1 to perform full tests.

Sporton International (Kunshan) Inc.

FAX: +86-512-57900958 FCC ID: 2AFZZ-RMSC3EH

TEL: +86-512-57900158

Page Number : 5 of 21
Report Issued Date : Jun. 06, 2019
Report Version : Rev. 01

Report Template No.: BU5-FG27 Version 2.0

## 1.3 Product Specification of Equipment Under Test

Standards	-related Pro	oduct Specification			
	GSM/GPRS/EDGE:				
	850:	824.2 MHz ~ 848.8 MHz			
	1900:	1850.2 MHz ~ 1909.8MHz			
Tx Frequency	WCDMA:				
	Band V:	826.4 MHz ~ 846.6 MHz			
	Band II:	1852.4 MHz ~ 1907.6 MHz			
	Band IV:	1712.4 MHz ~ 1752.6 MHz			
	GSM/GPR	RS/EDGE:			
	850:	869.2 MHz ~ 893.8 MHz			
	1900:	1930.2 MHz ~ 1989.8 MHz			
Rx Frequency	WCDMA:				
	Band V:	871.4 MHz ~ 891.6 MHz			
	Band II:	1932.4 MHz ~ 1987.6 MHz			
	Band IV:	2112.4 MHz ~ 2152.6 MHz			
Maximum Output Power to Antenna	Band IV:	23.03 dBm			
Antenna Type	PIFA Antenna				
Antenna Gain	AWS Band: -0.20 dBi				
	GSM: GMS	K			
	GPRS: GMSK				
	EDGE: GMSK / 8PSK				
Type of Modulation	WCDMA: BPSK (Uplink)				
	HSDPA/DC-HSDPA: QPSK (Uplink)				
	HSUPA: QPSK (Uplink)				
		QAM (uplink is not supported)			
	DC-HSDPA	a: 64QAM			

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AFZZ-RMSC3EH Page Number : 6 of 21
Report Issued Date : Jun. 06, 2019
Report Version : Rev. 01

Report Template No.: BU5-FG27 Version 2.0

### 1.4 Modification of EUT

No modifications are made to the EUT during all test items.

# 1.5 Maximum EIRP Power, Frequency Tolerance, and Emission Designator

FCC Rule	System	Type of Modulation	Maximum EIRP (W)	Frequency Tolerance (ppm)	Emission Designator
Part 27L	WCDMA Band IV RMC 12.2Kbps	BPSK	0.1919	0.0167 ppm	4M13F9W

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AFZZ-RMSC3EH Page Number : 7 of 21
Report Issued Date : Jun. 06, 2019
Report Version : Rev. 01

Report Template No.: BU5-FG27 Version 2.0

### 1.6 Testing Location

Sporton International (Kunshan) Inc. is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International (Kunshan) Inc.				
	No. 1098, Pengxi North	Road, Kunshan Econom	ic Development Zone		
Test Site Location	Jiangsu Province 215300 People's Republic of China				
Test Site Location	TEL: +86-512-57900158				
	FAX: +86-512-57900958				
	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.		
Test Site No.	03CH04-KS TH01-KS	CN1257	314309		

### 1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 2, 27(L)
- ANSI C63.26-2015
- FCC KDB 971168 D01 Power Meas. License Digital Systems v03r01
- FCC KDB 412172 D01 Determining ERP and EIRP v01r01

#### Remark:

- 1. All test items were verified and recorded according to the standards and without any deviation during the test.
- 2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AFZZ-RMSC3EH Page Number : 8 of 21
Report Issued Date : Jun. 06, 2019
Report Version : Rev. 01

Report Template No.: BU5-FG27 Version 2.0

## 2 Test Configuration of Equipment Under Test

#### 2.1 Test Mode

Antenna port conducted and radiated test items were performed according to KDB 971168 D01 Power Meas. License Digital Systems v03r01 with maximum output power.

Radiated measurements were performed with rotating EUT in different three orthogonal test planes to find the maximum emission.

Radiated emissions were investigated as following frequency range:


30 MHz to 10th harmonic for WCDMA Band IV.

All modes and data rates and positions were investigated.

Test modes are chosen to be reported as the worst case configuration below:

Test Modes						
Band	Band Radiated TCs Conducted TCs					
WCDMA Band IV	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link				

### 2.2 Connection Diagram of Test System



Page Number : 9 of 21
Report Issued Date : Jun. 06, 2019
Report Version : Rev. 01

Report Version : Rev. 01
Report Template No.: BU5-FG27 Version 2.0

### 2.3 Support Unit used in test configuration

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m
2.	DC Power Supply	GW INSTEK	GPS-3030D	N/A	N/A	Unshielded, 1.8 m

Report No.: FG931208-01C

### 2.4 Measurement Results Explanation Example

#### For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

The following shows an offset computation example with RF cable loss 5.4 dB and a 10dB attenuator.

#### Example:

 $Offset(dB) = RF \ cable \ loss(dB) + attenuator \ factor(dB).$ =5.4 + 10 = 15.4 (dB)

## 2.5 Frequency List of Low/Middle/High Channels

Frequency List					
Band Channel/Frequency(MHz) Lowest Middle Highest					
WCDMA	Channel	1312	1413	1513	
Band IV	Frequency	1712.4	1732.6	1752.6	

 Sporton International (Kunshan) Inc.
 Page Number
 : 10 of 21

 TEL: +86-512-57900158
 Report Issued Date
 : Jun. 06, 2019

 FAX: +86-512-57900958
 Report Version
 : Rev. 01

FCC ID : 2AFZZ-RMSC3EH

Report Template No.: BU5-FG27 Version 2.0


#### 3 Conducted Test Result

## 3.1 Measuring Instruments


See list of measuring instruments of this test report.

### 3.2 Test Setup


#### 3.2.1 Conducted Output Power



# 3.2.2 Peak-to-Average Ratio, Occupied Bandwidth, Conducted Band-Edge and Conducted Spurious Emission



#### 3.2.3 Frequency Stability



#### 3.3 Test Result of Conducted Test

Please refer to Appendix A.

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCCID: 2AFZZ-RMSC3EH Page Number : 11 of 21
Report Issued Date : Jun. 06, 2019
Report Version : Rev. 01

Report Template No.: BU5-FG27 Version 2.0

### 3.4 Conducted Output Power and ERP/EIRP

#### 3.4.1 Description of the Conducted Output Power and ERP/EIRP

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

The EIRP of mobile transmitters must not exceed 1 Watts for WCDMA Band IV.

According to KDB 412172 D01 Power Approach,

 $EIRP = P_T + G_T - L_C$ , ERP = EIRP - 2.15, where

 $P_T$  = transmitter output power in dBm

 $G_T$  = gain of the transmitting antenna in dBi

L<sub>C</sub> = signal attenuation in the connecting cable between the transmitter and antenna in dB

#### 3.4.2 Test Procedures

- 1. The testing follows ANSI C63.26 Section 5.2
- 2. The transmitter output port was connected to the system simulator.
- 3. Set EUT at maximum power through the system simulator.
- 4. Select lowest, middle, and highest channels for each band and different modulation.
- 5. Measure and record the power level from the system simulator.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AFZZ-RMSC3EH Page Number : 12 of 21
Report Issued Date : Jun. 06, 2019
Report Version : Rev. 01

Report Template No.: BU5-FG27 Version 2.0

### 3.5 Peak-to-Average Ratio

#### 3.5.1 Description of the PAR Measurement

The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

#### 3.5.2 Test Procedures

- 1. The testing follows ANSI C63.26 Section 5.2.3.4 (CCDF).
- 2. The EUT was connected to spectrum and system simulator via a power divider.
- 3. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
- 4. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
- 5. Record the deviation as Peak to Average Ratio.

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AFZZ-RMSC3EH Page Number : 13 of 21
Report Issued Date : Jun. 06, 2019
Report Version : Rev. 01

Report Template No.: BU5-FG27 Version 2.0

### 3.6 99% Occupied Bandwidth and 26dB Bandwidth Measurement

#### 3.6.1 Description of 99% Occupied Bandwidth and 26dB Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

#### 3.6.2 Test Procedures

- 1. The testing follows ANSI C63.26 Section 5.4
- 2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
- The spectrum analyzer center frequency is set to the nominal EUT channel center frequency.
   The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
- 4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
- 5. Set the detection mode to peak, and the trace mode to max hold.
- Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace.
   (this is the reference value)
- 7. Determine the "-26 dB down amplitude" as equal to (Reference Value X).
- 8. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the "–X dB down amplitude" determined in step 6. If a marker is below this "-X dB down amplitude" value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
- 9. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.

Report Template No.: BU5-FG27 Version 2.0

### 3.7 Conducted Band Edge

#### 3.7.1 Description of Conducted Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least 43 + 10 log (P) dB.

#### 3.7.2 Test Procedures

- 1. The testing follows ANSI C63.26 section 5.7
- 2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
- 3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
- 4. The band edges of low and high channels for the highest RF powers were measured.
- 5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
- 6. The limit line is derived from 43 + 10log(P) dB below the transmitter power P(Watts)

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AFZZ-RMSC3EH Page Number : 15 of 21
Report Issued Date : Jun. 06, 2019
Report Version : Rev. 01

Report Template No.: BU5-FG27 Version 2.0

### 3.8 Conducted Spurious Emission

#### 3.8.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least 43 + 10 log (P) dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10<sup>th</sup> harmonic.

#### 3.8.2 Test Procedures

- 1. The testing follows ANSI C63.26 section 5.7
- 2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
- 3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
- 4. The middle channel for the highest RF power within the transmitting frequency was measured.
- 5. The conducted spurious emission for the whole frequency range was taken.
- 6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
- 7. The limit line is derived from 43 + 10log(P) dB below the transmitter power P(Watts)

Sporton International (Kunshan) Inc.

FAX: +86-512-57900958 FCC ID: 2AFZZ-RMSC3EH

TEL: +86-512-57900158

Page Number : 16 of 21
Report Issued Date : Jun. 06, 2019
Report Version : Rev. 01

Report Template No.: BU5-FG27 Version 2.0

## 3.9 Frequency Stability

#### 3.9.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within ±0.00025% (±2.5ppm) of the center frequency.

#### 3.9.2 Test Procedures for Temperature Variation

- 1. The testing follows ANSI C63.26 section 5.6.4
- 2. The EUT was set up in the thermal chamber and connected with the system simulator.
- With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
- 4. With power OFF, the temperature was raised in 10°C step up to 50°C. The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

#### 3.9.3 Test Procedures for Voltage Variation

- 1. The testing follows ANSI C63.26 section 5.6.5
- 2. The EUT was placed in a temperature chamber at 20±5°C and connected with the system simulator.
- 3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value for other than hand carried battery equipment.
- 4. For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.
- 5. The variation in frequency was measured for the worst case.

Report Template No.: BU5-FG27 Version 2.0


### 4 Radiated Test Items

## 4.1 Measuring Instruments


See list of measuring instruments of this test report.

## 4.2 Test Setup

#### 4.2.1 For radiated test from 30MHz to 1GHz



#### 4.2.2 For radiated test above 1GHz



### 4.3 Test Result of Radiated Test

Please refer to Appendix B.

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AFZZ-RMSC3EH Page Number : 18 of 21
Report Issued Date : Jun. 06, 2019
Report Version : Rev. 01

Report Template No.: BU5-FG27 Version 2.0

### 4.4 Field Strength of Spurious Radiation Measurement

#### 4.4.1 Description of Field Strength of Spurious Radiated Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least 43 + 10 log (P) dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

#### 4.4.2 Test Procedures

- 1. The testing follows ANSI C63.26 Section 5.5
- 2. The EUT was placed on a rotatable wooden table 0.8 meters for frequency below 1GHz and 1.5 meter for frequency above 1GHz above the ground.
- 3. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
- 4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
- 5. The height of the receiving antenna is varied between one meter and four meters to search for the maximum spurious emission for both horizontal and vertical polarizations.
- 6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking record of maximum spurious emission.
- 7. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
- 8. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
- 9. Taking the record of output power at antenna port.
- 10. Repeat step 7 to step 8 for another polarization.
- 11. EIRP (dBm) = S.G. Power Tx Cable Loss + Tx Antenna Gain
- 12.ERP (dBm) = EIRP 2.15
- 13. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
- 14. The limit line is derived from 43 + 10log(P) dB below the transmitter power P(Watts)

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AFZZ-RMSC3EH Page Number : 19 of 21
Report Issued Date : Jun. 06, 2019
Report Version : Rev. 01

Report Template No.: BU5-FG27 Version 2.0

## 5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Aug. 07, 2018	Jun. 03, 2019	Aug. 06, 2019	Conducted (TH01-KS)
Thermal Chamber	Hongzhan	LP-150U	H2014011440	-40~+150°C 20%~95%RH	Jun. 27, 2018	Jun. 03, 2019	Jun. 26, 2019	Conducted (TH01-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55150208	10Hz-44GHz	Oct. 10. 2018	Jun. 03, 2019	Oct. 09. 2019	Radiation (03CH04-KS)
Bilog Antenna	TeseQ	CBL6111D	44483	30MHz-1GHz	Dec. 28, 2018	Jun. 03, 2019	Dec. 27, 2019	Radiation (03CH04-KS)
Horn Antenna	Schwarzbeck	BBHA9120D	1648	1GHz~18GHz	Jan. 27, 2019	Jun. 03, 2019	Jan. 26, 2020	Radiation (03CH04-KS)
SHF-EHF Horn	Com-power	AH-840	101070	18GHz~40GHz	Jan. 05, 2019	Jun. 03, 2019	Jan. 04, 2020	Radiation (03CH04-KS)
Amplifier	Burgeon	BPA-530	102219	0.01MHz ~3000MHz	Nov. 19, 2018	Jun. 03, 2019	Nov. 18, 2019	Radiation (03CH04-KS)
Amplifier	MITEQ	TTA1840-35 -HG	2014749	18~40GHz	Jan. 14, 2019	Jun. 03, 2019	Jan. 13, 2020	Radiation (03CH04-KS)
Amplifier	Keysight	83017A	MY53270319	500MHz~26.5GHz	Oct. 12. 2018	Jun. 03, 2019	Oct. 11. 2019	Radiation (03CH04-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Jun. 03, 2019	NCR	Radiation (03CH04-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Jun. 03, 2019	NCR	Radiation (03CH04-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Jun. 03, 2019	NCR	Radiation (03CH04-KS)

NCR: No Calibration Required

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AFZZ-RMSC3EH Page Number : 20 of 21
Report Issued Date : Jun. 06, 2019
Report Version : Rev. 01

Report Template No.: BU5-FG27 Version 2.0

## 6 Uncertainty of Evaluation

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.26-2015. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

#### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of	2 2 d D
Confidence of 95% (U = 2Uc(y))	3.3dB

#### Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of	2.8dB
Confidence of 95% (U = 2Uc(y))	2.0UB

#### Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Management I was a take to the face of a cool of	
Measuring Uncertainty for a Level of	2.8dB
Confidence of 95% (U = 2Uc(y))	2.0UB

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AFZZ-RMSC3EH Page Number : 21 of 21
Report Issued Date : Jun. 06, 2019
Report Version : Rev. 01

Report Template No.: BU5-FG27 Version 2.0

## **Appendix A. Test Results of Conducted Test**

## Conducted Output Power(Average power)

Conducted Power (*Unit: dBm)					
Band	WCDMA Band IV				
Channel	1312 1413 151				
Frequency	1712.4	1732.6	1752.6		
AMR 12.2K	22.87	22.88	23.02		
RMC 12.2K	22.89	22.89	<mark>23.03</mark>		
HSDPA Subtest-1	21.93	22.06	21.90		
HSDPA Subtest-2	21.94	22.02	21.91		
HSDPA Subtest-3	21.44	21.54	21.43		
HSDPA Subtest-4	21.44	21.54	21.42		
DC-HSDPA Subtest-1	21.92	22.01	21.92		
DC-HSDPA Subtest-2	21.85	21.85 22.08			
DC-HSDPA Subtest-3	21.42 21.48		21.38		
DC-HSDPA Subtest-4	21.38	21.36	21.45		
HSUPA Subtest-1	21.44	21.88	21.42		
HSUPA Subtest-2	20.95	20.52	20.84		
HSUPA Subtest-3	20.63	20.53	20.57		
HSUPA Subtest-4	20.85	20.88	20.87		
HSUPA Subtest-5	22.00	21.90	21.90		

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AFZZ-RMSC3EH Page Number : A1 of A11
Report Issued Date : Jun. 06, 2019
Report Version : Rev. 01

Report Template No.: BU5-FG27 Version 2.0

## **EIRP**

WCDMA Band IV (G <sub>T</sub> - L <sub>C</sub> = -0.20 dB)						
Channel	1312	1413	1513			
	(Low)	(Mid)	(High)			
Frequency	4740.4	4700.0	1752.6			
(MHz)	1712.4	1732.6				
Conducted Power (dBm)	22.89	22.89	23.03			
Conducted Power (Watts)	0.1945	0.1945	0.2009			
EIRP(dBm)	22.69	22.69	22.83			
EIRP(Watts)	0.1858	0.1858	0.1919			

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AFZZ-RMSC3EH Page Number : A2 of A11
Report Issued Date : Jun. 06, 2019
Report Version : Rev. 01

Report Template No.: BU5-FG27 Version 2.0

## Peak-to-Average Ratio


Mode	WCDMA Band IV(dB)	Limit: 13dB
Mod.	RMC 12.2Kbps	Result
Lowest CH	3.10	
Middle CH	2.84	PASS
Highest CH	2.67	

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AFZZ-RMSC3EH Page Number : A3 of A11
Report Issued Date : Jun. 06, 2019
Report Version : Rev. 01

Report Template No.: BU5-FG27 Version 2.0





Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AFZZ-RMSC3EH Page Number : A4 of A11
Report Issued Date : Jun. 06, 2019
Report Version : Rev. 01

Report Template No.: BU5-FG27 Version 2.0

## 26dB Bandwidth


Mode	WCDMA Band IV(MHz)		
Mod.	RMC 12.2Kbps		
Lowest CH	4.705		
Middle CH	4.725		
Highest CH	4.725		

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AFZZ-RMSC3EH Page Number : A5 of A11
Report Issued Date : Jun. 06, 2019
Report Version : Rev. 01

Report Template No.: BU5-FG27 Version 2.0





Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AFZZ-RMSC3EH Page Number : A6 of A11
Report Issued Date : Jun. 06, 2019
Report Version : Rev. 01

Report Template No.: BU5-FG27 Version 2.0


## Occupied Bandwidth


Mode	WCDMA Band IV(MHz)
Mod.	RMC 12.2Kbps
Lowest CH	4.116
Middle CH	4.116
Highest CH	4.126

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AFZZ-RMSC3EH Page Number : A7 of A11
Report Issued Date : Jun. 06, 2019
Report Version : Rev. 01

Report Template No.: BU5-FG27 Version 2.0






Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AFZZ-RMSC3EH Page Number : A8 of A11
Report Issued Date : Jun. 06, 2019
Report Version : Rev. 01

Report Template No.: BU5-FG27 Version 2.0

## **Conducted Band Edge**




Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AFZZ-RMSC3EH Page Number : A9 of A11
Report Issued Date : Jun. 06, 2019
Report Version : Rev. 01

Report Template No.: BU5-FG27 Version 2.0

## **Conducted Spurious Emission**



Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AFZZ-RMSC3EH Page Number : A10 of A11
Report Issued Date : Jun. 06, 2019
Report Version : Rev. 01

Report Template No.: BU5-FG27 Version 2.0

## Frequency Stability

Test Conditions	Middle Channel	WCDMA Band IV (RMC 12.2Kbps)	Limit Note 2.
Temperature (°C)	Voltage (Volt)	Deviation (ppm)	Result
50	Normal Voltage	0.0069	
40	Normal Voltage	0.0156	
30	Normal Voltage	0.0017	
20(Ref.)	Normal Voltage	0.0000	
10	Normal Voltage	0.0012	
0	Normal Voltage	0.0058	
-10	Normal Voltage	0.0150	PASS
-20	Normal Voltage	0.0167	
-30	Normal Voltage	0.0092	
20	Maximum Voltage	0.0092	
20	Normal Voltage	0.0000	
20	Battery End Point	0.0167	

#### Note:

- 1. Normal Voltage = 3.85V ; Battery End Point (BEP) =3.4V; Maximum Voltage =4.4V
- **2.** The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AFZZ-RMSC3EH Page Number : A11 of A11
Report Issued Date : Jun. 06, 2019
Report Version : Rev. 01

Report Template No.: BU5-FG27 Version 2.0

## **Appendix B. Test Results of Radiated Test**

## **Radiated Spurious Emission**

WCDMA Band IV(RMC)								
Channel	Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	3465	-61.76	-13	-48.76	-72.50	2.604	13.34	Н
	5199	-57.75	-13	-44.75	-68.26	3.011	13.52	Н
	6936	-54.24	-13	-41.24	-64.44	3.271	13.47	Н
	3465	-60.98	-13	-47.98	-71.72	2.604	13.34	V
	5199	-57.62	-13	-44.62	-68.13	3.011	13.52	V
	6936	-53.78	-13	-40.78	-63.98	3.271	13.47	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

Sporton International (Kunshan) Inc.

TEL: +86-512-57900158 FAX: +86-512-57900958 FCC ID: 2AFZZ-RMSC3EH Page Number : B1 of B1
Report Issued Date : Jun. 06, 2019
Report Version : Rev. 01

Report Template No.: BU5-FG27 Version 2.0