



FCC RF Test Report

APPLICANT : Xiaomi Communications Co., Ltd.
EQUIPMENT : Mobile Phone
BRAND NAME : MI
MODEL NAME : M1808D2TG
FCC ID : 2AFZZ-XMD2TG
STANDARD : FCC 47 CFR Part 2, 22(H), 24(E), 27(L)
CLASSIFICATION : PCS Licensed Transmitter Held to Ear (PCE)

The product was received on Jul. 30, 2018 and completely tested on Aug. 07, 2018. We, Sporton International (Kunshan) Inc., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.26-2015 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Kunshan) Inc., the test report shall not be reproduced except in full.



Approved by: James Huang / Manager

Sporton International (Kunshan) Inc.
No. 1098, Pengxi North Road, Kunshan Economic Development Zone,
Jiangsu Province 215335, China



TABLE OF CONTENTS

REVISION HISTORY.....3

SUMMARY OF TEST RESULT4

1 GENERAL DESCRIPTION5

 1.1 Applicant.....5

 1.2 Manufacturer5

 1.3 Product Feature of Equipment Under Test5

 1.4 Product Specification of Equipment Under Test6

 1.5 Modification of EUT7

 1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator8

 1.7 Testing Location9

 1.8 Applicable Standards9

2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST.....10

 2.1 Test Mode.....10

 2.2 Connection Diagram of Test System11

 2.3 Support Unit used in test configuration11

 2.4 Measurement Results Explanation Example11

 2.5 Frequency List of Low/Middle/High Channels.....12

3 CONDUCTED TEST RESULT.....13

 3.1 Measuring Instruments.....13

 3.2 Test Setup13

 3.3 Test Result of Conducted Test.....13

 3.4 Conducted Output Power and ERP/EIRP14

 3.5 Peak-to-Average Ratio15

 3.6 99% Occupied Bandwidth and 26dB Bandwidth Measurement.....16

 3.7 Conducted Band Edge17

 3.8 Conducted Spurious Emission18

 3.9 Frequency Stability.....19

4 RADIATED TEST ITEMS20

 4.1 Measuring Instruments.....20

 4.2 Test Setup20

 4.3 Test Result of Radiated Test.....20

 4.4 Field Strength of Spurious Radiation Measurement21

5 LIST OF MEASURING EQUIPMENT22

6 UNCERTAINTY OF EVALUATION23

APPENDIX A. TEST RESULTS OF CONDUCTED TEST

APPENDIX B. TEST RESULTS OF RADIATED TEST

APPENDIX C. TEST SETUP PHOTOGRAPHS



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.4	§2.1046	Conducted Output Power	Reporting Only	PASS	-
	§22.913(a)(5)	Effective Radiated Power	< 7 Watts	PASS	-
	§24.232(c)	Equivalent Isotropic Radiated Power	< 2 Watts	PASS	-
	§27.50(d)(4)	Equivalent Isotropic Radiated Power	< 1 Watts	PASS	-
3.5	§24.232(d)	Peak-to-Average Ratio	< 13 dB	PASS	-
3.6	§2.1049	Occupied Bandwidth	Reporting Only	PASS	-
3.7	§2.1051 §22.917(a) §24.238(a) §27.53(h)	Band Edge Measurement	< 43+10log10(P[Watts])	PASS	-
3.8	§2.1051 §22.917(a) §24.238(a) §27.53(h)	Conducted Emission	< 43+10log10(P[Watts])	PASS	-
3.9	§2.1055 §22.355	Frequency Stability for Temperature & Voltage	< 2.5 ppm for Part 22H	PASS	-
	§2.1055 §24.235 §27.54		Within Authorized Band		
4.4	§2.1053 §22.917(a) §24.238(a) §27.53(h)	Field Strength of Spurious Radiation	< 43+10log10(P[Watts])	PASS	Under limit 30.50 dB at 2510.000 MHz



1 General Description

1.1 Applicant

Xiaomi Communications Co., Ltd.

The Rainbow City of China Resources, NO.68, Qinghe Middle Street, Haidian District, Beijing, China

1.2 Manufacturer

Xiaomi Communications Co., Ltd.

The Rainbow City of China Resources, NO.68, Qinghe Middle Street, Haidian District, Beijing, China

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Phone
Brand Name	MI
Model Name	M1808D2TG
FCC ID	2AFZZ-XMD2TG
EUT supports Radios application	GSM/GPRS/EGPRS/WCDMA/HSPA/DC-HSDPA/ HSPA+ (16QAM uplink is not supported)/LTE/ WLAN 2.4GHz 802.11b/g/n HT20 WLAN 5GHz 802.11a/n HT20/HT40 WLAN 5GHz 802.11ac VHT20/VHT40/VHT80 Bluetooth BR/EDR/LE
IMEI Code	Conducted: 869808030002634/869808030002642 Radiation: 869808030001339/869808030001347
HW Version	P2.0
SW Version	MIUI9
EUT Stage	Identical Prototype

Remark:

1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
2. There are two types of EUT, the difference between two samples is for memory, the sample 1 is 6+128GB capacity and the sample 2 is 4+64GB capacity. According to the difference, we only choose sample 1 to perform full test



1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx Frequency	GSM/GPRS/EDGE: 850: 824.2 MHz ~ 848.8 MHz 1900: 1850.2 MHz ~ 1909.8MHz WCDMA: Band V: 826.4 MHz ~ 846.6 MHz Band II: 1852.4 MHz ~ 1907.6 MHz Band IV: 1712.4 MHz ~ 1752.6 MHz
Rx Frequency	GSM/GPRS/EDGE: 850: 869.2 MHz ~ 893.8 MHz 1900: 1930.2 MHz ~ 1989.8 MHz WCDMA: Band V: 871.4 MHz ~ 891.6 MHz Band II: 1932.4 MHz ~ 1987.6 MHz Band IV: 2112.4 MHz ~ 2152.6 MHz
Maximum Output Power to Antenna	Top Antenna: GSM/GPRS/EDGE: 850: 27.81 dBm 1900: 26.07 dBm Bottom Antenna: GSM/GPRS/EDGE: 850: 32.66 dBm 1900: 29.37 dBm WCDMA: Band V: 23.93 dBm Band II: 23.89 dBm Band IV: 23.68 dBm
Antenna Type	Fixed Internal Antenna
Antenna Gain	Top Antenna: Cellular Band: -6.0 dBi PCS Band: -3.30 dBi Bottom Antenna: Cellular Band: -3.40 dBi PCS Band: 1.10 dBi AWS Band: 0.80 dBi
Type of Modulation	GSM: GMSK GPRS: GMSK EDGE: GMSK / 8PSK WCDMA: BPSK (Uplink) HSDPA/DC-HSDPA: QPSK (Uplink) HSUPA: QPSK (Uplink) HSPA+: 16QAM (uplink is not supported) DC-HSDPA: 64QAM



1.5 Modification of EUT

No modifications are made to the EUT during all test items.



1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator

FCC Rule	System	Type of Modulation	Maximum ERP/EIRP (W)		Frequency Tolerance (ppm)	Emission Designator
			Top	Bottom		
Part 22H	GSM850 GSM	GMSK	0.0925	0.5140	0.0574 ppm	244KGXW
Part 22H	GSM850 EDGE class 8	8PSK	0.0571	0.1321	0.0538 ppm	246KG7W
Part 22H	WCDMA Band V RMC 12.2Kbps	BPSK	-	0.0689	0.0442 ppm	4M15F9W
Part 24E	GSM1900 GSM	GMSK	0.1892	1.1143	0.0218 ppm	243KGXW
Part 24E	GSM1900 EDGE class 8	8PSK	0.1472	0.4603	0.0255 ppm	247KG7W
Part 24E	WCDMA Band II RMC 12.2Kbps	BPSK	-	0.3155	0.0239 ppm	4M13F9W
Part 27L	WCDMA Band IV RMC 12.2Kbps	BPSK	-	0.2805	0.0167 ppm	4M13F9W



1.7 Testing Location

Sporton International (Kunshan) Inc. is accredited to ISO 17025 by National Voluntary Laboratory Accreditation Program (NVLAP code: 600155-0).

Test Site	Sporton International (Kunshan) Inc.		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone, Jiangsu Province 215335, China TEL : 86-512-57900158 FAX : 86-512-57900958		
Test Site No.	Sporton Site No.	FCC designation No.	FCC Test Firm Registration No.
	TH01-KS 03CH04-KS	CN5013	630927

1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 2, 22(H), 24(E), 27(L)
- ANSI C63.26-2015
- FCC KDB 971168 D01 Power Meas. License Digital Systems v03r01
- FCC KDB 412172 D01 Determining ERP and EIRP v01r01

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

2.1 Test Mode

Antenna port conducted and radiated test items were performed according to KDB 971168 D01 Power Meas. License Digital Systems v03r01 with maximum output power.

Radiated measurements were performed with rotating EUT in different three orthogonal test planes to find the maximum emission.

Radiated emissions were investigated as following frequency range:


1. 30 MHz to 10th harmonic for GSM850 and WCDMA Band V.
2. 30 MHz to 10th harmonic for WCDMA Band IV.
3. 30 MHz to 10th harmonic for GSM1900 and WCDMA Band II.

All modes and data rates and positions were investigated.

Test modes are chosen to be reported as the worst case configuration below:

Test Modes		
Band	Radiated TCs	Conducted TCs
GSM 850	<ul style="list-style-type: none"> ■ GSM Link ■ EDGE class 8 Link 	<ul style="list-style-type: none"> ■ GSM Link ■ EDGE class 8 Link
GSM 1900	<ul style="list-style-type: none"> ■ GSM Link ■ EDGE class 8 Link 	<ul style="list-style-type: none"> ■ GSM Link ■ EDGE class 8 Link
WCDMA Band V	<ul style="list-style-type: none"> ■ RMC 12.2Kbps Link 	<ul style="list-style-type: none"> ■ RMC 12.2Kbps Link
WCDMA Band II	<ul style="list-style-type: none"> ■ RMC 12.2Kbps Link 	<ul style="list-style-type: none"> ■ RMC 12.2Kbps Link
WCDMA Band IV	<ul style="list-style-type: none"> ■ RMC 12.2Kbps Link 	<ul style="list-style-type: none"> ■ RMC 12.2Kbps Link

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m
2.	DC Power Supply	GW INSTRON	GPS-3030D	N/A	N/A	Unshielded, 1.8 m

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

$$\text{Offset} = \text{RF cable loss} + \text{attenuator factor}.$$

The following shows an offset computation example with RF cable loss 4.3 dB and a 10dB attenuator.

Example :

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\ &= 4.3 + 10 = 14.3 \text{ (dB)} \end{aligned}$$



2.5 Frequency List of Low/Middle/High Channels

Frequency List				
Band	Channel/Frequency(MHz)	Lowest	Middle	Highest
GSM850	Channel	128	189	251
	Frequency	824.2	836.4	848.8
WCDMA Band V	Channel	4132	4182	4233
	Frequency	826.4	836.4	846.6
GSM1900	Channel	512	661	810
	Frequency	1850.2	1880.0	1909.8
WCDMA Band II	Channel	9262	9400	9538
	Frequency	1852.4	1880.0	1907.6
WCDMA Band IV	Channel	1312	1413	1513
	Frequency	1712.4	1732.6	1752.6

3 Conducted Test Result

3.1 Measuring Instruments


See list of measuring instruments of this test report.

3.2 Test Setup


3.2.1 Conducted Output Power



3.2.2 Peak-to-Average Ratio, Occupied Bandwidth, Conducted Band-Edge and Conducted Spurious Emission



3.2.3 Frequency Stability



3.3 Test Result of Conducted Test

Please refer to Appendix A.



3.4 Conducted Output Power and ERP/EIRP

3.4.1 Description of the Conducted Output Power and ERP/EIRP

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

The ERP of mobile transmitters must not exceed 7 Watts for GSM850 and WCDMA Band V.

The EIRP of mobile transmitters must not exceed 2 Watts for GSM1900 and WCDMA Band II.

The EIRP of mobile transmitters must not exceed 1 Watts for WCDMA Band IV.

According to KDB 412172 D01 Power Approach,

$EIRP = P_T + G_T - L_C$, $ERP = EIRP - 2.15$, where

P_T = transmitter output power in dBm

G_T = gain of the transmitting antenna in dBi

L_C = signal attenuation in the connecting cable between the transmitter and antenna in dB

3.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2
2. The transmitter output port was connected to the system simulator.
3. Set EUT at maximum power through the system simulator.
4. Select lowest, middle, and highest channels for each band and different modulation.
5. Measure and record the power level from the system simulator.



3.5 Peak-to-Average Ratio

3.5.1 Description of the PAR Measurement

The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.5.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2.3.4 (CCDF).
2. The EUT was connected to spectrum and system simulator via a power divider.
3. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
4. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
5. Record the deviation as Peak to Average Ratio.



3.6 99% Occupied Bandwidth and 26dB Bandwidth Measurement

3.6.1 Description of 99% Occupied Bandwidth and 26dB Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

3.6.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.4
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
5. Set the detection mode to peak, and the trace mode to max hold.
6. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace. (this is the reference value)
7. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
8. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “-X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
9. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.



3.7 Conducted Band Edge

3.7.1 Description of Conducted Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

3.7.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The band edges of low and high channels for the highest RF powers were measured.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
6. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)



3.8 Conducted Spurious Emission

3.8.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.

3.8.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
7. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)



3.9 Frequency Stability

3.9.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.

3.9.2 Test Procedures for Temperature Variation

1. The testing follows ANSI C63.26 section 5.6.4
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C step up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.9.3 Test Procedures for Voltage Variation

1. The testing follows ANSI C63.26 section 5.6.5
2. The EUT was placed in a temperature chamber at $20\pm 5^{\circ}\text{C}$ and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value for other than hand carried battery equipment.
4. For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.
5. The variation in frequency was measured for the worst case.


4 Radiated Test Items

4.1 Measuring Instruments


See list of measuring instruments of this test report.

4.2 Test Setup

4.2.1 For radiated test from 30MHz to 1GHz



4.2.2 For radiated test above 1GHz



4.3 Test Result of Radiated Test

Please refer to Appendix B.



4.4 Field Strength of Spurious Radiation Measurement

4.4.1 Description of Field Strength of Spurious Radiated Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

4.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.5
2. The EUT was placed on a rotatable wooden table 0.8 meters for frequency below 1GHz and 1.5 meter for frequency above 1GHz above the ground.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between one meter and four meters to search for the maximum spurious emission for both horizontal and vertical polarizations.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking record of maximum spurious emission.
7. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
8. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
9. Taking the record of output power at antenna port.
10. Repeat step 7 to step 8 for another polarization.
11. $EIRP \text{ (dBm)} = S.G. \text{ Power} - Tx \text{ Cable Loss} + Tx \text{ Antenna Gain}$
12. $ERP \text{ (dBm)} = EIRP - 2.15$
13. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
14. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)



5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV30	101338	10Hz~30GHz	Apr. 19, 2018	Aug. 07, 2018	Apr. 18, 2019	Conducted (TH01-KS)
Thermal Chamber	Ten Billion	TTC-B3S	TBN-960502	-40~+150°C	Oct. 12, 2017	Aug. 07, 2018	Oct. 11, 2018	Conducted (TH01-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55370528	10Hz-44GHz	Oct. 10, 2017	Aug. 05, 2018	Oct. 09, 2018	Radiation (03CH04-KS)
Bilog Antenna	TeseQ	CBL6111D	44483	30MHz-1GHz	Jan. 29, 2018	Aug. 05, 2018	Jan. 28, 2019	Radiation (03CH04-KS)
Horn Antenna	Schwarzbeck	BBHA9120D	1648	1GHz~18GHz	Dec. 16, 2017	Aug. 05, 2018	Dec. 15, 2018	Radiation (03CH04-KS)
SHF-EHF Horn	Schwarzbeck	BBHA 9170	BBHA170249	15GHz~40GHz	Feb. 07, 2018	Aug. 05, 2018	Feb. 06, 2019	Radiation (03CH04-KS)
Amplifier	Burgeon	BPA-530	102219	0.01MHz ~3000MHz	Dec. 16, 2017	Aug. 05, 2018	Dec. 15, 2018	Radiation (03CH04-KS)
Amplifier	MITEQ	TTA1840-35 -HG	2014749	18~40GHz	Feb. 08, 2018	Aug. 05, 2018	Feb. 07, 2019	Radiation (03CH04-KS)
high gain Amplifier	MITEQ	AMF-7D-00 101800-30-1	2025788	1Ghz-18Ghz	Apr. 17, 2018	Aug. 05, 2018	Apr. 16, 2019	Radiation (03CH04-KS)
Amplifier	Keysight	83017A	MY53270203	500MHz~26.5GHz	Dec. 16, 2017	Aug. 05, 2018	Dec. 15, 2018	Radiation (03CH04-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Aug. 05, 2018	NCR	Radiation (03CH04-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Aug. 05, 2018	NCR	Radiation (03CH04-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Aug. 05, 2018	NCR	Radiation (03CH04-KS)

NCR: No Calibration Required



6 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.3dB
---	-------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.8dB
---	-------



Appendix A. Test Results of Conducted Test

Conducted Output Power(Average power)

Top Antenna:

Conducted Power (*Unit: dBm)						
Band	GSM850			GSM1900		
Channel	128	189	251	512	661	810
Frequency	824.2	836.4	848.8	1850.2	1880.0	1909.8
GSM	27.63	27.81	27.62	25.84	26.07	25.98
GPRS class 8	27.62	27.79	27.60	25.83	26.06	25.96
GPRS class 10	24.65	24.79	24.63	22.74	22.69	22.89
GPRS class 11	22.61	22.79	22.55	20.65	20.60	20.76
GPRS class 12	21.78	21.60	21.58	19.56	19.54	19.74
EGPRS class 8	25.61	25.72	25.62	24.88	24.83	24.98
EGPRS class 10	22.26	22.10	22.08	21.82	21.79	21.95
EGPRS class 11	19.91	20.01	20.00	19.61	19.60	20.00
EGPRS class 12	19.10	19.06	18.73	18.60	18.82	18.89

Bottom Antenna:

Conducted Power (*Unit: dBm)						
Band	GSM850			GSM1900		
Channel	128	189	251	512	661	810
Frequency	824.2	836.4	848.8	1850.2	1880.0	1909.8
GSM	32.58	32.66	32.51	29.17	29.37	29.32
GPRS class 8	32.56	32.63	32.48	29.16	29.35	29.31
GPRS class 10	29.41	29.50	29.61	26.36	25.90	26.33
GPRS class 11	27.61	27.98	27.76	24.09	24.26	24.41
GPRS class 12	26.02	26.36	26.27	23.50	23.58	23.56
EGPRS class 8	26.48	26.76	26.61	25.48	25.10	25.53
EGPRS class 10	23.67	23.65	23.60	22.00	22.06	22.40
EGPRS class 11	21.73	21.72	21.58	20.14	20.11	20.54
EGPRS class 12	20.24	20.33	20.20	18.79	18.53	19.01



Conducted Power (*Unit: dBm)									
Band	WCDMA Band V			WCDMA Band II			WCDMA Band IV		
Channel	4132	4182	4233	9262	9400	9538	1312	1413	1513
Frequency	826.4	836.4	846.6	1852.4	1880	1907.6	1712.4	1732.6	1752.6
AMR 12.2K	23.82	23.88	23.92	23.82	23.76	23.85	23.28	23.49	23.61
RMC 12.2K	23.84	23.90	23.93	23.84	23.77	23.89	23.29	23.56	23.68
HSDPA Subtest-1	22.73	22.68	22.67	22.63	22.61	22.56	22.20	22.41	22.47
HSDPA Subtest-2	22.73	22.66	22.71	22.59	22.66	22.59	22.23	22.41	22.49
HSDPA Subtest-3	22.23	22.16	22.16	22.08	22.13	22.16	21.72	21.93	21.94
HSDPA Subtest-4	22.24	22.19	22.17	22.08	22.14	22.11	21.73	21.94	21.94
DC-HSDPA Subtest-1	22.73	22.68	22.67	22.48	22.63	22.59	22.20	22.41	22.47
DC-HSDPA Subtest-2	22.73	22.66	22.71	22.51	22.62	22.48	22.23	22.41	22.49
DC-HSDPA Subtest-3	22.23	22.16	22.16	22.05	22.08	22.08	21.72	21.93	21.94
DC-HSDPA Subtest-4	22.24	22.19	22.17	22.01	22.01	22.15	21.73	21.94	21.94
HSUPA Subtest-1	22.69	22.60	22.62	22.60	22.60	22.56	22.17	22.31	22.47
HSUPA Subtest-2	20.68	20.57	20.65	20.58	20.59	20.55	20.19	20.34	20.44
HSUPA Subtest-3	21.68	21.65	21.66	21.57	21.54	21.58	21.16	21.38	21.36
HSUPA Subtest-4	20.63	20.60	20.62	20.56	20.57	20.57	20.19	20.34	20.37
HSUPA Subtest-5	22.70	22.60	22.70	22.60	22.60	22.50	22.20	22.40	22.40



ERP/EIRP

Top Antenna

GSM850 ($G_T - L_C = -6.00$ dBi)			
Channel	128	189	251
	(Low)	(Mid)	(High)
Frequency (MHz)	824.2	836.4	848.8
Conducted Power (dBm)	27.63	27.81	27.62
Conducted Power (Watts)	0.5794	0.6039	0.5781
ERP(dBm)	19.48	19.66	19.47
ERP(Watts)	0.0887	0.0925	0.0885

EDGE850 ($G_T - L_C = -6.00$ dBi)			
Channel	128	189	251
	(Low)	(Mid)	(High)
Frequency (MHz)	824.2	836.4	848.8
Conducted Power (dBm)	25.61	25.72	25.62
Conducted Power (Watts)	0.3639	0.3733	0.3648
ERP(dBm)	17.46	17.57	17.47
ERP(Watts)	0.0557	0.0571	0.0558



GSM1900 (G _T - L _C = -3.30 dBi)			
Channel	512	661	810
	(Low)	(Mid)	(High)
Frequency	1850.2	1880	1909.8
(MHz)			
Conducted Power (dBm)	25.84	26.07	25.98
Conducted Power (Watts)	0.3837	0.4046	0.3963
EIRP(dBm)	22.54	22.77	22.68
EIRP(Watts)	0.1795	0.1892	0.1854

EDGE1900 (G _T - L _C = -3.30 dBi)			
Channel	512	661	810
	(Low)	(Mid)	(High)
Frequency	1850.2	1880	1909.8
(MHz)			
Conducted Power (dBm)	24.88	24.83	24.98
Conducted Power (Watts)	0.3076	0.3041	0.3148
EIRP(dBm)	21.58	21.53	21.68
EIRP(Watts)	0.1439	0.1422	0.1472



Bottom Antenna

GSM850 (G _T - L _C = -3.40 dBi)			
Channel	128	189	251
	(Low)	(Mid)	(High)
Frequency	824.2	836.4	848.8
(MHz)			
Conducted Power (dBm)	32.58	32.66	32.51
Conducted Power (Watts)	1.8113	1.8450	1.7824
ERP(dBm)	27.03	27.11	26.96
ERP(Watts)	0.5047	0.5140	0.4966

EDGE850 (G _T - L _C = -3.40 dBi)			
Channel	128	189	251
	(Low)	(Mid)	(High)
Frequency	824.2	836.4	848.8
(MHz)			
Conducted Power (dBm)	26.48	26.76	26.61
Conducted Power (Watts)	0.4446	0.4742	0.4581
ERP(dBm)	20.93	21.21	21.06
ERP(Watts)	0.1239	0.1321	0.1276



GSM1900 (G _T - L _C = 1.10 dBi)			
Channel	512	661	810
	(Low)	(Mid)	(High)
Frequency	1850.2	1880	1909.8
(MHz)			
Conducted Power (dBm)	29.17	29.37	29.32
Conducted Power (Watts)	0.8260	0.8650	0.8551
EIRP(dBm)	30.27	30.47	30.42
EIRP(Watts)	1.0641	1.1143	1.1015

EDGE1900 (G _T - L _C = 1.10 dBi)			
Channel	512	661	810
	(Low)	(Mid)	(High)
Frequency	1850.2	1880	1909.8
(MHz)			
Conducted Power (dBm)	25.48	25.10	25.53
Conducted Power (Watts)	0.3532	0.3236	0.3573
EIRP(dBm)	26.58	26.20	26.63
EIRP(Watts)	0.4550	0.4169	0.4603



WCDMA Band V ($G_T - L_C = -3.40$ dBi)			
Channel	4132	4182	4233
	(Low)	(Mid)	(High)
Frequency	826.4	836.4	846.6
(MHz)			
Conducted Power (dBm)	23.84	23.90	23.93
Conducted Power (Watts)	0.2421	0.2455	0.2472
ERP(dBm)	18.29	18.35	18.38
ERP(Watts)	0.0675	0.0684	0.0689

WCDMA Band II ($G_T - L_C = 1.10$ dBi)			
Channel	9262	9400	9538
	(Low)	(Mid)	(High)
Frequency	1852.4	1880	1907.6
(MHz)			
Conducted Power (dBm)	23.84	23.77	23.89
Conducted Power (Watts)	0.2421	0.2382	0.2449
EIRP(dBm)	24.94	24.87	24.99
EIRP(Watts)	0.3119	0.3069	0.3155

WCDMA Band IV ($G_T - L_C = 0.80$ dBi)			
Channel	1312	1413	1513
	(Low)	(Mid)	(High)
Frequency	1712.4	1732.6	1752.6
(MHz)			
Conducted Power (dBm)	23.29	23.56	23.68
Conducted Power (Watts)	0.2133	0.2270	0.2333
EIRP(dBm)	24.09	24.36	24.48
EIRP(Watts)	0.2564	0.2729	0.2805




Peak-to-Average Ratio

Mode	GSM850(dB)		Limit: 13dB
Mod.	GSM	EDGE class 8	Result
Lowest CH	0.35	3.45	PASS
Middle CH	0.32	3.45	
Highest CH	0.32	3.71	

Mode	GSM1900(dB)		Limit: 13dB
Mod.	GSM	EDGE class 8	Result
Lowest CH	0.2	3.33	PASS
Middle CH	0.17	3.25	
Highest CH	0.17	3.22	


Mode	WCDMA Band V(dB)	WCDMA Band II(dB)	WCDMA Band IV(dB)	Limit: 13dB
Mod.	RMC 12.2Kbps	RMC 12.2Kbps	RMC 12.2Kbps	Result
Lowest CH	2.72	2.78	2.9	PASS
Middle CH	2.87	2.9	2.84	
Highest CH	2.49	2.81	3.1	





GSM1900 (GSM)


Lowest Channel



Date: 7.AUG.2018 19:07:39


GSM1900 (EDGE class 8)

Lowest Channel




Date: 7.AUG.2018 19:25:01

Middle Channel




Date: 7.AUG.2018 19:07:51

Middle Channel



Date: 7.AUG.2018 19:25:17

Highest Channel



Date: 7.AUG.2018 19:08:02

Highest Channel




Date: 7.AUG.2018 19:25:26



WCDMA Band V (RMC 12.2Kbps)


Lowest Channel



Date: 7.AUG.2018 21:00:13


WCDMA Band II (RMC 12.2Kbps)

Lowest Channel




Date: 7.AUG.2018 20:13:14

Middle Channel




Date: 7.AUG.2018 21:00:22

Middle Channel




Date: 7.AUG.2018 20:13:21

Highest Channel




Date: 7.AUG.2018 21:00:30

Highest Channel



Date: 7.AUG.2018 20:13:29





26dB Bandwidth

Mode	GSM850(MHz)	
Mod.	GSM	EDGE class 8
Lowest CH	0.312	0.31
Middle CH	0.31	0.306
Highest CH	0.313	0.31


Mode	GSM1900(MHz)	
Mod.	GSM	EDGE class 8
Lowest CH	0.32	0.309
Middle CH	0.312	0.312
Highest CH	0.314	0.312

Mode	WCDMA Band V(MHz)	WCDMA Band II(MHz)	WCDMA Band IV(MHz)
Mod.	RMC 12.2Kbps	RMC 12.2Kbps	RMC 12.2Kbps
Lowest CH	4.725	4.725	4.715
Middle CH	4.725	4.725	4.715
Highest CH	4.745	4.725	4.705



GSM850 (GSM)


Lowest Channel



Date: 7.AUG.2018 18:16:58


GSM850 (EDGE class 8)

Lowest Channel




Date: 7.AUG.2018 18:35:47

Middle Channel




Date: 7.AUG.2018 18:17:32

Middle Channel




Date: 7.AUG.2018 18:36:21

Highest Channel



Date: 7.AUG.2018 18:18:04

Highest Channel




Date: 7.AUG.2018 18:36:53



GSM1900 (GSM)

Lowest Channel



Date: 7.AUG.2018 18:52:26

GSM1900 (EDGE class 8)

Lowest Channel




Date: 7.AUG.2018 19:10:35

Middle Channel




Date: 7.AUG.2018 18:52:59

Middle Channel




Date: 7.AUG.2018 19:11:05

Highest Channel



Date: 7.AUG.2018 18:53:49

Highest Channel




Date: 7.AUG.2018 19:11:37



WCDMA Band V (RMC 12.2Kbps)


Lowest Channel



Date: 7.AUG.2018 20:32:12


WCDMA Band II (RMC 12.2Kbps)

Lowest Channel




Date: 7.AUG.2018 19:58:20

Middle Channel




Date: 7.AUG.2018 20:32:56

Middle Channel




Date: 7.AUG.2018 19:58:54

Highest Channel




Date: 7.AUG.2018 20:38:03

Highest Channel



Date: 7.AUG.2018 19:59:29





Occupied Bandwidth

Mode	GSM850(MHz)	
Mod.	GSM	EDGE class 8
Lowest CH	0.24	0.245
Middle CH	0.244	0.246
Highest CH	0.241	0.244


Mode	GSM1900(MHz)	
Mod.	GSM	EDGE class 8
Lowest CH	0.243	0.247
Middle CH	0.243	0.244
Highest CH	0.241	0.242

Mode	WCDMA Band V(MHz)	WCDMA Band II(MHz)	WCDMA Band IV(MHz)
Mod.	RMC 12.2Kbps	RMC 12.2Kbps	RMC 12.2Kbps
Lowest CH	4.126	4.126	4.126
Middle CH	4.136	4.116	4.116
Highest CH	4.146	4.126	4.126



GSM850 (GSM)


Lowest Channel



Date: 7.AUG.2018 18:18:38


GSM850 (EDGE class 8)

Lowest Channel




Date: 7.AUG.2018 18:39:32

Middle Channel




Date: 7.AUG.2018 18:19:14

Middle Channel




Date: 7.AUG.2018 18:40:05

Highest Channel



Date: 7.AUG.2018 18:19:49

Highest Channel




Date: 7.AUG.2018 18:40:41



GSM1900 (GSM)


Lowest Channel



Date: 7.AUG.2018 18:56:13


GSM1900 (EDGE class 8)

Lowest Channel




Date: 7.AUG.2018 19:14:31

Middle Channel




Date: 7.AUG.2018 18:56:46

Middle Channel




Date: 7.AUG.2018 19:15:28

Highest Channel



Date: 7.AUG.2018 18:57:19

Highest Channel




Date: 7.AUG.2018 19:16:08



WCDMA Band V (RMC 12.2Kbps)


Lowest Channel



Date: 7.AUG.2018 20:39:07


WCDMA Band II (RMC 12.2Kbps)

Lowest Channel




Date: 7.AUG.2018 20:01:53

Middle Channel




Date: 7.AUG.2018 20:48:15

Middle Channel




Date: 7.AUG.2018 20:02:24

Highest Channel



Date: 7.AUG.2018 20:48:46

Highest Channel



Date: 7.AUG.2018 20:02:56





Conducted Band Edge

