FCC RF Test Report

APPLICANT : Xiaomi Communications Co., Ltd.

EQUIPMENT: Mobile Phone

BRAND NAME : MI

MODEL NAME : M1803E1A

FCC ID : 2AFZZ-XME1A

STANDARD : FCC Part 15 Subpart C §15.225

CLASSIFICATION: (DXX) Low Power Communication Device Transmitter

The product was received on Apr. 20, 2018 and testing was completed on Jun. 07, 2018. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by: Joseph Lin / Supervisor

Approved by: Jones Tsai / Manager

SPORTON INTERNATIONAL INC.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C.

Page Number : 1 of 21
Report Issued Date : Jun. 11, 2018
Report Version : Rev. 01

Testing Laboratory 1190

Report No.: FR842002D

TABLE OF CONTENTS

TABL	LE OF CONTENTS	
	SION HISTORY	
	MARY OF THE TEST RESULT	
	ENERAL DESCRIPTION	
1.1		
1.2		
1.3		
1.4	and the same of the first section of the first section of the same of the first section of th	
1.5	5 Modification of EUT	6
1.6	6 Testing Location	
1.7	7 Applicable Standards	
2. TE	ST CONFIGURATION OF EQUIPMENT UNDER TEST	8
2.1	1 Descriptions of Test Mode	8
2.2	2 Connection Diagram of Test System	9
2.3	3 Table for Supporting Units	9
2.4	4 EUT Operation Test Setup	9
3. TE	ST RESULTS	10
3.1	1 AC Power Line Conducted Emissions Measurement	10
3.2	2 20dB and 99% OBW Spectrum Bandwidth Measurement	12
3.3	3 Frequency Stability Measurement	13
3.4	4 Field Strength of Fundamental Emissions and Mask Measurement	1
3.5	5 Radiated Emissions Measurement	16
3.6	6 Antenna Requirements	19
4. LIS	ST OF MEASURING EQUIPMENT	20
	NCERTAINTY OF EVALUATION	
APPE	ENDIX A. TEST RESULTS OF CONDUCTED EMISSION TEST	
APPE	ENDIX B. TEST RESULTS OF CONDUCTED TEST ITEMS	
B1	Test Result of 20dB Spectrum Bandwidth	

APPENDIX C. TEST RESULTS OF RADIATED TEST ITEMS

- C1. Test Result of Field Strength of Fundamental Emissions
- C2. Results of Radiated Emissions (9 kHz~30MHz)
- C3. Results of Radiated Emissions (30MHz~1GHz)

APPEDNIX D. SETUP PHOTOGRAPHS

B2. Test Result of Frequency Stability

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AFZZ-XME1A Page Number : 2 of 21
Report Issued Date : Jun. 11, 2018
Report Version : Rev. 01

Report No.: FR842002D

REVISION HISTORY

Report No. : FR842002D

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR842002D	Rev. 01	Initial issue of report	Jun. 11, 2018

 SPORTON INTERNATIONAL INC.
 Page Number
 : 3 of 21

 TEL: 886-3-327-3456
 Report Issued Date
 : Jun. 11, 2018

 FAX: 886-3-328-4978
 Report Version
 : Rev. 01

SUMMARY OF THE TEST RESULT

Report No. : FR842002D

Report Section	FCC Rule	Description of Test	Result	Remark
3.1	15.207	AC Power Line Conducted Emissions	Complies	Under limit 15.71 dB at 0.152MHz
	15.215(c)	20dB Spectrum Bandwidth	Complies	-
3.2	-	99% OBW Spectrum Bandwidth	Complies	-
3.3	15.225(e)	Frequency Stability	Complies	-
3.4	15.225(a)(b)(c)	Field Strength of Fundamental Emissions	Complies	Max level 58.71 dBµV/m at 13.560 MHz
3.5	15.225(d) & 15.209	Radiated Spurious Emissions	Complies	Under limit 9.40 dB at 40.800MHz
3.6	15.203	Antenna Requirements	Complies	-

 SPORTON INTERNATIONAL INC.
 Page Number
 : 4 of 21

 TEL: 886-3-327-3456
 Report Issued Date
 : Jun. 11, 2018

 FAX: 886-3-328-4978
 Report Version
 : Rev. 01

1. General Description

1.1 Applicant

Xiaomi Communications Co., Ltd.

The Rainbow City of China Resources, NO.68, Qinghe Middle Street, Haidian District, Beijing, China

Report No.: FR842002D

1.2 Manufacturer

Xiaomi Communications Co., Ltd.

The Rainbow City of China Resources, NO.68, Qinghe Middle Street, Haidian District, Beijing, China

1.3 Product Feature of Equipment Under Test

Product Feature				
Equipment	Mobile Phone			
Brand Name	MI			
Model Name	M1803E1A			
FCC ID	2AFZZ-XME1A			
	CDMA/EV-DO/GSM/GPRS/EGPRS/WCDMA/HSPA/			
	DC-HSDPA/HSPA+(16QAM uplink is notsupported)/LTE/NFC			
	WLAN 2.4GHz 802.11b/g/n HT20			
EUT supports Radios application	WLAN 5GHz 802.11a/n HT20/HT40			
	WLAN 5GHz 802.11ac VHT20/VHT40/VHT80			
	Bluetooth v3.0 + EDR/Bluetooth v4.0 LE/Bluetooth v4.2 LE/			
	Bluetooth v5.0 LE			
	Conducted: 867252030140353/867252030140361			
IMEI Code	Conduction: 867252030157993/867252030158009			
	Radiation: 867252030140353/867252030140361			
HW Version	P2			
SW Version	MIUI 9			
EUT Stage	Identical Prototype			

Remark:

- 1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
- 2. There are two types of EUT, the difference between two samples is for memory, the sample 1 is 6+64GB capacity and the sample 2 is 6+128GB capacity. According to the difference, we only choose sample 1 to perform full test.

 SPORTON INTERNATIONAL INC.
 Page Number
 : 5 of 21

 TEL: 886-3-327-3456
 Report Issued Date
 : Jun. 11, 2018

 FAX: 886-3-328-4978
 Report Version
 : Rev. 01

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification			
Tx/Rx Frequency Range	13.553 ~ 13.567MHz		
Channel Number	1		
20dBW	2.64 KHz		
99%OBW	2.26 KHz		
Antenna Type	Planar Antenna		
Type of Modulation	ASK		

Report No.: FR842002D

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

 SPORTON INTERNATIONAL INC.
 Page Number
 : 6 of 21

 TEL: 886-3-327-3456
 Report Issued Date
 : Jun. 11, 2018

 FAX: 886-3-328-4978
 Report Version
 : Rev. 01

1.6 Testing Location

SPORTON INTERNATIONAL INC. is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code: 1190) and under the FCC-recognized accredited testing laboratories by Mutual Recognition Agreement (MRA) in FCC Test.

Report No.: FR842002D

Test Site	SPORTON INTERNATIONAL INC.		
	No. 52, Hwa Ya 1 st Rd., Hwa Ya Technology Park,		
Tool Cita Lacation	Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C.		
Test Site Location	TEL: +886-3-327-3456		
	FAX: +886-3-328-4978		
Took Cita No	Sport	on Site No.	
Test Site No.	TH03-HY CO05-HY		

Test Site	SPORTON INTERNATIONAL INC.			
	No.52, Huaya 1st Rd., Guishar	n Dist. Taoyuan City Taiwa	เท	
Test Site Location	Tel: 886-3-327-3456			
	FAX: +886-3-327-0978			
	Sporton Site No.	FCC designation No.	FCC Test Firm	
Test Site No.	Sporton Site No.	rcc designation No.	Registration No.	
	03CH07-HY	TW1190	553509	

Note: The test site complies with ANSI C63.4 2014 requirement.

1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15 Subpart C §15.225
- ANSI C63.10-2013

 SPORTON INTERNATIONAL INC.
 Page Number
 : 7 of 21

 TEL: 886-3-327-3456
 Report Issued Date
 : Jun. 11, 2018

 FAX: 886-3-328-4978
 Report Version
 : Rev. 01

2. Test Configuration of Equipment Under Test

2.1 Descriptions of Test Mode

Investigation has been done on all the possible configurations.

The following table is a list of the test modes shown in this test report.

Test Items			
AC Power Line Conducted Emissions Field Strength of Fundamental Emissions			
20dB Spectrum Bandwidth	Frequency Stability		
Radiated Emissions 9kHz~30MHz	Radiated Emissions 30MHz~1GHz		

Report No.: FR842002D

The EUT pre-scanned in four NFC type, A, B, F, V. The worst type (type F) was recorded in this report. Pre-scanned tests, X, Y, Z in three orthogonal panels to determine the final configuration (Y plane as worst plane) from all possible combinations.


	Test Cases					
AC Conducted Emission	Mode 1: GSM850 Idle + Bluetooth Link + WLAN Link(2.4G) + USB Cable1(Charging from Adapter) + NFC Tx + SIM 1					
Remark: For Radiated Test Cases, The tests were performed with Adapter and USB Cable1						

 SPORTON INTERNATIONAL INC.
 Page Number
 : 8 of 21

 TEL: 886-3-327-3456
 Report Issued Date
 : Jun. 11, 2018

 FAX: 886-3-328-4978
 Report Version
 : Rev. 01

2.2 Connection Diagram of Test System



2.3 Table for Supporting Units

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded,1.8m
2.	NOTE BOOK	Dell	Latitude E6320	FCC DoC	NOTE BOOK	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
3.	Bluetooth Earphone	Sony Ericsson	MW600	PY700A2029	N/A	N/A
4.	WLAN AP	ASUS	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded,1.8m
5.	NFC Card	Metro Taipei	Easy Card	N/A	N/A	N/A

2.4 EUT Operation Test Setup

The EUT was programmed to be in continuously transmitting mode.

The ancillary equipment, NFC card, is used to make the EUT (NFC) continuously transmit at 13.56MHz and is placed around 3 cm gap to the EUT.

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AFZZ-XME1A Page Number : 9 of 21
Report Issued Date : Jun. 11, 2018
Report Version : Rev. 01

Report No.: FR842002D

3. Test Results

3.1 AC Power Line Conducted Emissions Measurement

3.1.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Report No.: FR842002D

Frequency of Emission	Conducted Limit (dBμV)		
(MHz)	Quasi-Peak	Average	
0.15-0.5	66 to 56*	56 to 46*	
0.5-5	56	46	
5-30	60	50	

^{*}Decreases with the logarithm of the frequency.

3.1.2 Measuring Instruments


See list of measuring instruments of this test report.

3.1.3 Test Procedures

- 1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
- 2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
- 3. All the support units are connecting to the other LISN.
- 4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
- 5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
- 6. Both sides of AC line were checked for maximum conducted interference.
- 7. The frequency range from 150 kHz to 30 MHz was searched.
- 8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.



3.1.4 Test setup



3.1.5 Test Result of AC Conducted Emission

Please refer to Appendix A.

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AFZZ-XME1A Page Number : 11 of 21 Report Issued Date: Jun. 11, 2018 Report Version : Rev. 01

Report No.: FR842002D

3.2 20dB and 99% OBW Spectrum Bandwidth Measurement

3.2.1 Limit

Intentional radiators must be designed to ensure that the 20dB and 99% emission bandwidth in the specific band 13.553~13.567MHz.


3.2.2 Measuring Instruments

See list of measuring instruments of this test report.

3.2.3 Test Procedures

- 1. The spectrum analyzer connected via a receive antenna placed near the EUT in peak Max hold mode.
- 2. The resolution bandwidth of 1 kHz and the video bandwidth of 3 kHz were used.
- 3. Measured the spectrum width with power higher than 20dB below carrier.
- 4. Measured the 99% OBW.

3.2.4 Test Setup



3.2.5 Test Result of Conducted Test Items

Please refer to Appendix B.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AFZZ-XME1A Page Number : 12 of 21
Report Issued Date : Jun. 11, 2018
Report Version : Rev. 01

Report No.: FR842002D

3.3 Frequency Stability Measurement

3.3.1 Limit

The frequency tolerance of the carrier signal shall be maintained within +/- 0.01% (100ppm) of the operating frequency over a temperature variation of -20 degrees to +50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.


3.3.2 Measuring Instruments

See list of measuring instruments of this test report.

3.3.3 Test Procedures

- 1. The spectrum analyzer connected via a receive antenna placed near the EUT.
- 2. EUT have transmitted signal and fixed channelize.
- 3. Set the spectrum analyzer span to view the entire emissions bandwidth.
- 4. Set RBW = 1 kHz, VBW = 3 kHz with peak detector and maxhold settings.
- 5. The fc is declaring of channel frequency. Then the frequency error formula is $(fc-f)/fc \times 10^6$ ppm and the limit is less than ± 100 ppm.
- 6. Extreme temperature rule is -20°C~50°C.

3.3.4 Test Setup



3.3.5 Test Result of Conducted Test Items

Please refer to Appendix B.

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AFZZ-XME1A Page Number : 13 of 21
Report Issued Date : Jun. 11, 2018
Report Version : Rev. 01

Report No.: FR842002D

3.4 Field Strength of Fundamental Emissions and Mask Measurement

3.4.1 Limit

Rules and specifications	FCC CFR 47 Part 15 section 15.225			
Description	Compliance with the spectrum mask is tested with RBW set to 9kHz.			
From of Francisco (MIII-)	Field Strength	Field Strength	Field Strength	Field Strength
Freq. of Emission (MHz)	(µV/m) at 30m	(dBµV/m) at 30m	(dBµV/m) at 10m	(dBµV/m) at 3m
1.705~13.110	30	29.5	48.58	69.5
13.110~13.410	106	40.5	59.58	80.5
13.410~13.553	334	50.5	69.58	90.5
13.553~13.567	15848	84.0	103.08	124.0
13.567~13.710	334	50.5	69.58	90.5
13.710~14.010	106	40.5	59.58	80.5
14.010~30.000	30	29.5	48.58	69.5

3.4.2 Measuring Instruments

See list of measuring instruments of this test report.

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AFZZ-XME1A Page Number : 14 of 21
Report Issued Date : Jun. 11, 2018
Report Version : Rev. 01


Report No.: FR842002D

3.4.3 Test Procedures

- Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the loop receiving antenna mounted antenna tower was placed 3 meters far away from the turntable.
- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- 3. The height of the receiving antenna was fixed at one meter above ground to find the maximum emissions field strength.
- 4. For Fundamental emissions, use the receiver to measure QP reading.
- 5. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
- 6. Compliance with the spectrum mask is tested with RBW set to 9kHz. Note: Emission level ($dB\mu V/m$) = 20 log Emission level ($\mu V/m$).

3.4.4 Test Setup

For radiated emissions below 30MHz



3.4.5 Test Result of Field Strength of Fundamental Emissions and Mask

Please refer to Appendix C.

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AFZZ-XME1A Page Number : 15 of 21
Report Issued Date : Jun. 11, 2018
Report Version : Rev. 01

Report No.: FR842002D

3.5 Radiated Emissions Measurement

3.5.1 Limit

The field strength of any emissions which appear outside of 13.110 ~14.010MHz band shall not exceed the general radiated emissions limits.

Report No.: FR842002D

Frequencies	Field Strength	Measurement Distance
(MHz)	(μV/m)	(meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

See list of measuring instruments of this test report.

3.5.3 Measuring Instrument Setting

The following table is the setting of receiver.

Receiver Parameter	Setting
Attenuation	Auto
Frequency Range: 9kHz~150kHz	RBW 200Hz for QP
Frequency Range: 150kHz~30MHz	RBW 9kHz for QP
Frequency Range: 30MHz~1000MHz	RBW 120kHz for Peak

Note: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz. Radiated emission limits in these two bands are based on measurements employing an average detector.

3.5.4 Test Procedures

1. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.

Report No.: FR842002D

- 2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
- The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
- For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
- Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
- When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
- In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. Antenna Requirements


FAX: 886-3-328-4978 FCC ID: 2AFZZ-XME1A

Report Version : Rev. 01 Report Template No.: BU5-FR15CNFC Version 2.0

: 17 of 21

3.5.5 Test Setup

For radiated emissions above 30MHz



3.5.6 Test Result of Radiated Emissions Measurement

Please refer to Appendix C.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AFZZ-XME1A Page Number : 18 of 21
Report Issued Date : Jun. 11, 2018
Report Version : Rev. 01

Report No.: FR842002D

3.6 Antenna Requirements

3.6.1 Standard Applicable

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited.

The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.6.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

Page Number : 19 of 21
Report Issued Date : Jun. 11, 2018
Report Version : Rev. 01

Report No.: FR842002D

4. List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristi cs	Calibration Date	Test Date	Due Date	Remark
AC Power Source	AC POWER	AFC-500W	F10407001 1	50Hz~60Hz	Mar. 21, 2018	May 28, 2018	Mar. 20, 2019	Conducted (TH03-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP30	101329	9kHz~30GHz	Jun. 26, 2017	May 28, 2018	Jun. 25, 2018	Conducted (TH03-HY)
Temperature Chamber	ESPEC	SU-641	92013721	-30℃ ~70℃	Dec. 06, 2017	May 28, 2018	Dec. 05, 2019	Conducted (TH03-HY)
Bilog Antenna	TESEQ	CBL 6111D&00800 N1D01N-06	35419&03	30MHz to 1GHz	Dec. 18, 2017	May 28, 2018~ May 30, 2018	Dec. 17, 2018	Radiation (03CH07-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100315	9 kHz~30 MHz	Nov. 10, 2017	May 28, 2018~ May 30, 2018	Nov. 09, 2018	Radiation (03CH07-HY)
Controller	ChainTek	Chaintek 3000	N/A	Control Turn table	NCR	May 28, 2018~ May 30, 2018	NCR	Radiation (03CH07-HY)
Antenna Mast	Max-Full	MFA520BS	N/A	1m~4m	NCR	May 28, 2018~ May 30, 2018	NCR	Radiation (03CH07-HY)
Turn Table	ChainTek	Chaintek 3000	N/A	0~360 Degree	NCR	May 28, 2018~ May 30, 2018	NCR	Radiation (03CH07-HY)
EMI Test Receiver	Agilent	N9038A(MXE)	MY532900 53	20Hz to 26.5GHz	Jan. 16, 2018	May 28, 2018~ May 30, 2018	Jan. 15, 2019	Radiation (03CH07-HY)
Amplifier	SONOMA	310N	187231	9kHz~1GHz	Jan. 08, 2018	May 28, 2018~ May 30, 2018	Jan. 07, 2019	Radiation (03CH07-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	NCR	Jun. 07, 2018	NCR	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102388	3.6GHz	Dec. 08, 2017	Jun. 07, 2018	Dec. 07, 2018	Conduction (CO05-HY)
Hygrometer	Testo	608-H1	34913912	N/A	Mar. 06, 2018	Jun. 07, 2018	Mar. 05, 2019	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Nov. 30, 2017	Jun. 07, 2018	Nov. 29, 2018	Conduction (CO05-HY)
LF Cable	HUBER + SUHNER	RG-214/U	LF01	N/A	Jan. 03, 2018	Jun. 07, 2018	Jan. 02, 2019	Conduction (CO05-HY)
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100851	N/A	Jan. 03, 2018	Jun. 07, 2018	Jan. 02, 2019	Conduction (CO05-HY)

NCR: No Calibration Required

 ${\it SPORTON\ INTERNATIONAL\ INC.}$

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AFZZ-XME1A Page Number : 20 of 21
Report Issued Date : Jun. 11, 2018
Report Version : Rev. 01

Report No.: FR842002D

5. Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence	2.7dB
of 95% (U = 2Uc(y))	

Report No.: FR842002D

Uncertainty of Radiated Emission Measurement (9 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence	3.4dB
of 95% (U = 2Uc(y))	

<u>Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)</u>

Measuring Uncertainty for a Level of Confidence	5.7 dB
of 95% (U = 2Uc(y))	•··· •·=


 SPORTON INTERNATIONAL INC.
 Page Number
 : 21 of 21

 TEL: 886-3-327-3456
 Report Issued Date
 : Jun. 11, 2018

 FAX: 886-3-328-4978
 Report Version
 : Rev. 01

Appendix A. Test Results of Conducted Emission Test

Test Engineer :	Arthur Heigh	Temperature :	21~25°C
rest Engineer :	Arthur Fisieri	Relative Humidity :	51~55%
Test Voltage :	120Vac / 60Hz	Phase :	Line



Final_Result

Frequency	QuasiPeak	CAverage	Limit	Margin	Lina	Filter	Corr.
(MHz)	(dBµV)	(dBµV)	(dBµV)	(dB)	Line	Filter	(dB)
0.150000		30.11	56.00	25.89	L1	OFF	19.5
0.150000	44.85		66.00	21.15	L1	OFF	19.5
0.235500		33.10	52.25	19.15	L1	OFF	19.5
0.235500	35.68		62.25	26.57	L1	OFF	19.5
0.298500		26.02	50.28	24.26	L1	OFF	19.5
0.298500	29.81		60.28	30.47	L1	OFF	19.5
0.363750		26.26	48.64	22.38	L1	OFF	19.5
0.363750	28.58		58.64	30.06	L1	OFF	19.5
0.435750		24.72	47.14	22.42	L1	OFF	19.5
0.435750	27.58		57.14	29.56	L1	OFF	19.5
0.640500		24.70	46.00	21.30	L1	OFF	19.6
0.640500	29.61		56.00	26.39	L1	OFF	19.6
13.560000		57.70	50.00	-7.70	L1	OFF	20.0
13.560000	62.34		60.00	-2.34	L1	OFF	20.0
22.062750		26.28	50.00	23.72	L1	OFF	20.3
22.062750	34.93		60.00	25.07	L1	OFF	20.3

(1) with antenna

Remark: 13.560MHz is the NFC RF fundamental signal.

SPORTON INTERNATIONAL INC.


TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AFZZ-XME1A Page Number : A1 of A4
Report Issued Date : Jun. 11, 2018
Report Version : Rev. 01

Report No.: FR842002D

 Test Engineer :
 Arthur Hsieh
 Temperature :
 21~25℃

 Relative Humidity :
 51~55%

 Test Voltage :
 120Vac / 60Hz
 Phase :
 Neutral



Final_Result

Frequency	QuasiPeak	CAverage	Limit	Margin	Line	Filter	Corr.
		_			Lilic	1 iiici	
(MHz)	(dBµV)	(dBµV)	(dBµV)	(dB)			(dB)
0.152250		29.34	55.88	26.54	N	OFF	19.5
0.152250	50.17		65.88	15.71	N	OFF	19.5
0.197250		26.28	53.73	27.45	N	OFF	19.5
0.197250	36.86		63.73	26.87	N	OFF	19.5
0.233250		33.47	52.33	18.86	N	OFF	19.5
0.233250	36.83		62.33	25.50	N	OFF	19.5
0.303000		24.77	50.16	25.39	N	OFF	19.5
0.303000	27.11		60.16	33.05	N	OFF	19.5
0.368250	-	26.38	48.54	22.16	N	OFF	19.5
0.368250	28.44		58.54	30.10	N	OFF	19.5
0.606750		23.07	46.00	22.93	N	OFF	19.6
0.606750	26.54		56.00	29.46	N	OFF	19.6
13.560000		56.96	50.00	-6.96	N	OFF	20.1
13.560000	61.47		60.00	-1.47	N	OFF	20.1
20.980500		25.15	50.00	24.85	N	OFF	20.4
20.980500	28.72		60.00	31.28	N	OFF	20.4

(1) with antenna

Remark: 13.560MHz is the NFC RF fundamental signal.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AFZZ-XME1A Page Number : A2 of A4
Report Issued Date : Jun. 11, 2018
Report Version : Rev. 01

Report No.: FR842002D

Test Engineer : Arthur Hsieh

Arthur Hsieh


Temperature : 21~25°C
Relative Humidity : 51~55%

Test Voltage : 120Vac / 60Hz

Phase : Line



Report No.: FR842002D



Final_Result

Frequency	QuasiPeak	CAverage	Limit	Margin	Line	Filter	Corr.
(MHz)	(dBµV)	(dBµV)	(dBµV)	(dB)			(dB)
13.560000		24.46	50.00	25.54	L1	OFF	19.7
13.560000	31.86		60.00	28.14	L1	OFF	19.7

(2) With dummy load

Remark: Only the fundamental NFC signal needs to be retested per C63.4.

SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AFZZ-XME1A Page Number : A3 of A4
Report Issued Date : Jun. 11, 2018
Report Version : Rev. 01

Test Engineer : Arthur Hsieh


Temperature : 25.1~25.3°C

Relative Humidity : 55~58%

Test Voltage : 120Vac / 60Hz

Phase : Neutral





Final_Result

Frequency (MHz)	QuasiPeak (dBµV)	CAverage (dBµV)	Limit (dBµV)	Margin (dB)	Line	Filter	Corr. (dB)
13.560000		19.04	50.00	30.96	N	OFF	19.8
13.560000	24.88		60.00	35.12	N	OFF	19.8

(2) With dummy load

Remark: Only the fundamental NFC signal needs to be retested per C63.4.


SPORTON INTERNATIONAL INC.

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AFZZ-XME1A Page Number : A4 of A4
Report Issued Date : Jun. 11, 2018
Report Version : Rev. 01

Report No.: FR842002D

Appendix B. Test Results of Conducted Test Items

B1.Test Result of 20dB Spectrum Bandwidth



TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AFZZ-XME1A Page Number : B1 of B2
Report Issued Date : Jun. 11, 2018
Report Version : Rev. 01

Report No.: FR842002D

B2. Test Result of Frequency Stability

Voltage vs. Freque	ency Stability	Temperature vs.	Frequency Stability
Voltage (Vac)	Measurement Frequency (MHz)	Temperature (°C)	Measurement Frequency (MHz)
120	13.560220	-20	13.560320
102	13.560220	-10	13.560310
138	13.560220	0	13.560300
		10	13.560300
		20	13.560240
		30	13.560220
		40	13.560220
		50	13.560220
Max.Deviation (MHz)	0.000220	Max.Deviation (MHz)	0.000320
Max.Deviation (ppm)	16.2242	Max.Deviation (ppm)	23.5988
Limit	FS < ±100 ppm	Limit	FS < ±100 ppm
Test Result	PASS	Test Result	PASS

Report No.: FR842002D

 SPORTON INTERNATIONAL INC.
 Page Number
 : B2 of B2


 TEL: 886-3-327-3456
 Report Issued Date
 : Jun. 11, 2018

 FAX: 886-3-328-4978
 Report Version
 : Rev. 01



Appendix C. Test Results of Radiated Test Items

C1. Test Result of Field Strength of Fundamental Emissions



TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AFZZ-XME1A Page Number : C1 of C3
Report Issued Date : Jun. 11, 2018
Report Version : Rev. 01

Report No.: FR842002D

C2. Results of Radiated Spurious Emissions (9 kHz~30MHz)

Test Mode :	: NFC	Tx		Polariz	ation :	Hori	zontal		
Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Ant Pos	Table Pos	Remark
(MHz)	(dBµV/m)	(dB)	(dBµV/m)	(dBµV)	(dB)	(dB)	(cm)	(deg)	A
0.00956	45.58	-82.41	127.99	24.52	20.63	0.43	-	-	Average
0.06123	46.35	-65.52	111.87	25.82	20.1	0.43	-	-	Average
0.09912	47.14	-60.54	107.68	26.62	20.09	0.43	-	-	QP
0.11168	43.51	-63.13	106.64	22.99	20.09	0.43	-	-	Average
0.15646	44.18	-59.54	103.72	23.69	20.06	0.43	-	-	Average
0.491	41.09	-32.71	73.8	20.67	19.99	0.43	100	0	QP
13.024	35.3	-34.2	69.5	14.96	19.91	0.43	-	-	QP
22.273	35.99	-33.51	69.5	14.39	20.4	1.2	-	-	QP
28.31	35.82	-33.68	69.5	14.37	20.25	1.2	-	-	QP

Report No.: FR842002D

Test Mode :	: NFC	Tx	Polarization : Vertical							
Frequency	Level	Over	Limit	Read	Antenna	Cable	Ant	Table	Remark	
(MU=)	(dBu\/m)	Limit	Line	Level	Factor	Loss	Pos	Pos		
(MHz)	(dBµV/m)		(dBµV/m)	(dBµV)	(dB)	(dB)	(cm)	(deg)	A	
0.00905	44.52	-83.95	128.47	23.46	20.63	0.43	-	-	Average	
0.06342	45.57	-65.99	111.56	25.04	20.1	0.43	-	-	Average	
0.09476	45.2	-62.87	108.07	24.68	20.09	0.43	-	-	QP	
0.12344	43.37	-62.41	105.78	22.87	20.07	0.43	-	-	Average	
0.15442	45.88	-57.95	103.83	25.39	20.06	0.43	-	-	Average	
0.491	41.47	-32.33	73.8	21.05	19.99	0.43	100	0	QP	
12.632	35.07	-34.43	69.5	14.72	19.92	0.43	-	-	QP	
21.616	36.65	-32.85	69.5	15.1	20.35	1.2	-	-	QP	
28.825	35.25	-34.25	69.5	13.89	20.16	1.2	-	-	QP	

Note:

- 1. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
- 2. Distance extrapolation factor = 40 log (specific distance / test distance) (dB);
- 3. Limit line = specific limits $(dB\mu V)$ + distance extrapolation factor.

SPORTON INTERNATIONAL INC.Page Number: C2 of C3TEL: 886-3-327-3456Report Issued Date: Jun. 11, 2018

FAX: 886-3-328-4978 Report Version : Rev. 01
FCC ID: 2AFZZ-XME1A Report Template No.: BU5-FR15CNFC Version 2.0

C3. Results of Radiated Spurious Emissions (30MHz~1GHz)

Test Mode : NFC Tx				Po	larization	Horizontal					
Frequency	Leve	el	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Remark
(MHz)	(dBµV	/m)	(dB)	$(dB\mu V/m)$	(dBµV)	(dB)	(dB)	(dB)	(cm)	(deg)	
31.89	22.1	9	-17.81	40	29.24	23.58	1.2	31.83	-	-	Peak
101.28	25.3	3	-18.17	43.5	39.29	15.96	1.83	31.75	-	-	Peak
169.86	24.7	5	-18.75	43.5	38.82	15.57	2.06	31.7	-	-	Peak
759.2	31.4	4	-14.56	46	31.24	27.83	4.18	31.81	-	-	Peak
867.7	31.0	7	-14.93	46	29	28.98	4.58	31.49	-	-	Peak
951.7	33.3	2	-12.68	46	29.07	30.44	4.71	30.9	100	0	Peak

Test Mode : NFC Tx					Pol	larization	Vertical				
Frequency	Leve	el	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Remark
(MHz)	(dBµV	/m)	(dB)	($dB\mu V/m$)	(dBµV)	(dB)	(dB)	(dB)	(cm)	(deg)	
40.8	30.6	3	-9.4	40	42.4	18.81	1.2	31.81	100	0	Peak
57.27	28.8	8	-11.12	40	47.35	12.12	1.2	31.79	-	-	Peak
85.35	25.2	2	-14.78	40	41.56	13.87	1.55	31.76	-	-	Peak
779.5	33.1	5	-12.85	46	32.79	27.98	4.18	31.8	-	-	Peak
850.2	30.5	2	-15.48	46	28.86	28.78	4.45	31.57	-	-	Peak
956.6	32.2	6	-13.74	46	27.71	30.69	4.71	30.85	-	-	Peak

Note:

- 1. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
- 2. Emission level (dB μ V/m) = 20 log Emission level (μ V/m).
- 3. Corrected Reading: Antenna Factor + Cable Loss + Read Level Preamp Factor= Level.

 ${\it SPORTON\ INTERNATIONAL\ INC.}$

TEL: 886-3-327-3456 FAX: 886-3-328-4978 FCC ID: 2AFZZ-XME1A Page Number : C3 of C3
Report Issued Date : Jun. 11, 2018
Report Version : Rev. 01

Report No.: FR842002D