

# FCC TEST REPORT

**Product Name:** Mobile Phone  
**Trade Mark:** MI  
**Model No.:** MDE5  
**Report Number:** 170726002RFC-3  
**Test Standards:** FCC 47 CFR Part 15 Subpart C  
**FCC ID:** 2AFZZ-XMSD5  
**Test Result:** PASS  
**Date of Issue:** September 4, 2017

Prepared for:

**Xiaomi Communications Co., Ltd.**  
**The Rainbow City of China Resources, NO.68, Qinghe Middle Street,**  
**Haidian District, Beijing, China**

Prepared by:

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**  
**16/F, Block A, Building 6, Baoneng Science and Technology Park,**  
**Qingxiang Road No.1, Longhua New District, Shenzhen, China**  
**TEL: +86-755-2823 0888**  
**FAX: +86-755-2823 0886**

Tested by:   
 Kevin Liang  
 Senior Engineer

Reviewed by:   
 Jim Long  
 Senior Supervisor

Approved by:   
 Billy Li  
 Technical Director

Date: September 4, 2017

**Version**

Version No.	Date	Description
V1.0	September 4, 2017	Original



## CONTENTS

<b>1. GENERAL INFORMATION</b> .....	<b>4</b>
<b>1.1 CLIENT INFORMATION</b> .....	<b>4</b>
<b>1.2 EUT INFORMATION</b> .....	<b>4</b>
1.2.1 GENERAL DESCRIPTION OF EUT .....	4
1.2.2 DESCRIPTION OF ACCESSORIES.....	5
<b>1.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD</b> .....	<b>6</b>
<b>1.4 OTHER INFORMATION</b> .....	<b>6</b>
<b>1.5 DESCRIPTION OF SUPPORT UNITS</b> .....	<b>7</b>
<b>1.6 TEST LOCATION</b> .....	<b>7</b>
<b>1.7 TEST FACILITY</b> .....	<b>7</b>
<b>1.8 DEVIATION FROM STANDARDS</b> .....	<b>8</b>
<b>1.9 ABNORMALITIES FROM STANDARD CONDITIONS</b> .....	<b>8</b>
<b>1.10 OTHER INFORMATION REQUESTED BY THE CUSTOMER</b> .....	<b>8</b>
<b>1.11 MEASUREMENT UNCERTAINTY</b> .....	<b>8</b>
<b>2. TEST SUMMARY</b> .....	<b>9</b>
<b>3. EQUIPMENT LIST</b> .....	<b>10</b>
<b>4. TEST CONFIGURATION</b> .....	<b>11</b>
<b>4.1 ENVIRONMENTAL CONDITIONS FOR TESTING</b> .....	<b>11</b>
4.1.1 NORMAL OR EXTREME TEST CONDITIONS .....	11
4.1.2 RECORD OF NORMAL ENVIRONMENT.....	11
<b>4.2 TEST CHANNELS</b> .....	<b>11</b>
<b>4.3 EUT TEST STATUS</b> .....	<b>11</b>
<b>4.4 PRE-SCAN</b> .....	<b>12</b>
4.4.1 PRE-SCAN UNDER ALL RATES .....	12
4.4.2 WORST-CASE DATA RATES .....	12
<b>4.5 TEST SETUP</b> .....	<b>12</b>
4.5.1 FOR RADIATED EMISSIONS TEST SETUP.....	12
4.5.2 FOR CONDUCTED EMISSIONS TEST SETUP .....	13
4.5.3 FOR CONDUCTED RF TEST SETUP .....	13
<b>4.6 SYSTEM TEST CONFIGURATION</b> .....	<b>13</b>
<b>4.7 DUTY CYCLE</b> .....	<b>14</b>
<b>5. RADIO TECHNICAL REQUIREMENTS SPECIFICATION</b> .....	<b>17</b>
<b>5.1 REFERENCE DOCUMENTS FOR TESTING</b> .....	<b>17</b>
<b>5.2 ANTENNA REQUIREMENT</b> .....	<b>17</b>
<b>5.3 CONDUCTED PEAK OUTPUT POWER</b> .....	<b>18</b>
<b>5.4 6 dB BANDWIDTH</b> .....	<b>20</b>
<b>5.5 POWER SPECTRAL DENSITY</b> .....	<b>26</b>
<b>5.6 CONDUCTED OUT OF BAND EMISSION</b> .....	<b>32</b>
<b>5.7 RADIATED SPURIOUS EMISSIONS</b> .....	<b>41</b>
<b>5.8 BAND EDGE MEASUREMENTS (RADIATED)</b> .....	<b>47</b>
<b>5.9 CONDUCTED EMISSION</b> .....	<b>58</b>
<b>APPENDIX 1 PHOTOS OF TEST SETUP</b> .....	<b>61</b>
<b>APPENDIX 2 PHOTOS OF EUT CONSTRUCTIONAL DETAILS</b> .....	<b>61</b>

# 1. GENERAL INFORMATION

## 1.1 CLIENT INFORMATION

<b>Applicant:</b>	Xiaomi Communications Co., Ltd.
<b>Address of Applicant:</b>	The Rainbow City of China Resources, NO.68, Qinghe Middle Street, Haidian District, Beijing, China
<b>Manufacturer:</b>	Xiaomi Communications Co., Ltd.
<b>Address of Manufacturer:</b>	The Rainbow City of China Resources, NO.68, Qinghe Middle Street, Haidian District, Beijing, China

## 1.2 EUT INFORMATION

### 1.2.1 General Description of EUT

<b>Product Name:</b>	Mobile Phone		
<b>Model No.:</b>	MDE5		
<b>Add. Model No.:</b>	N/A		
<b>Trade Mark:</b>	MI		
<b>DUT Stage:</b>	Identical Prototype		
<b>EUT Supports Function:</b>	<b>GSM Bands:</b>	GSM 850/ PCS 1900	
	<b>UTRA Bands:</b>	Band II/ Band IV/ Band V	
	<b>CDMA Band:</b>	BC0/ BC1/ BC10	
	<b>E-UTRA Bands:</b>	FDD Band 2/ Band 4/ Band 5/ Band 7/ Band 12/ Band 13/ Band 17/ Band 25/ Band 26/ Band 30	
		TDD Band 38/ Band 41	
	<b>2.4 GHz ISM Band:</b>	IEEE 802.11b/g/n	
		Bluetooth V3.0+EDR/ Bluetooth V4.1 LE/ Bluetooth V5.0 LE	
	<b>5 GHz U-NII Bands:</b>	5 150 MHz to 5 250 MHz	IEEE 802.11a/n/ac
		5 250 MHz to 5 350 MHz	IEEE 802.11a/n/ac
		5 470 MHz to 5 725 MHz	IEEE 802.11a/n/ac
5 725 MHz to 5 850 MHz		IEEE 802.11a/n/ac	
<b>RNSS Bands:</b>	1559 MHz to 1610 MHz	GPS/GLONASS/Galileo	
<b>NFC:</b>	13.553 MHz to 13.567 MHz		
<b>Software Version:</b>	MIUI 8		
<b>Hardware Version:</b>	P2.0		
<b>IMEI Code:</b>	865736030026044, 865736030026051		
<b>Sample Received Date:</b>	July 27, 2017		
<b>Sample Tested Date:</b>	July 27, 2017 to August 12, 2017		

### 1.2.2 Description of Accessories

Adapter	
Trade Mark:	XIAOMI
Model No.:	MDY-08-EY
Input:	100-240V~50/60 Hz 0.5A
Output:	5V $\equiv$ 3A/9V $\equiv$ 2A/12V $\equiv$ 1.5A
AC Cable:	N/A
DC Cable:	N/A

Battery	
Trade Mark:	MI
Model No.:	BM3B
Battery Type:	Lithium-ion Polymer Rechargeable Battery
Rated Voltage:	3.85 Vdc
Limited Charge Voltage:	4.4 Vdc
Rated Capacity:	3300 mAh

Cable(1)	
Trade Mark:	MI
Model No.:	L6BU2018-CS-H
Description:	USB Type-C Plug Cable
Cable Type:	Shielded without ferrite
Length:	1.0 Meter

Cable(2)	
Trade Mark:	MI
Model No.:	KLC-2588-1
Description:	USB Type-C Plug Cable
Cable Type:	Shielded without ferrite
Length:	1.0 Meter

Cable(3)	
Trade Mark:	MI
Model No.:	KLC-2469
Description:	USB Type-C to 3.5 mm Headphone Jack Adapter
Cable Type:	Unshielded without ferrite

Cable(4)	
Trade Mark:	MI
Model No.:	0QT000XI0007
Description:	USB Type-C to 3.5 mm Headphone Jack Adapter
Cable Type:	Unshielded without ferrite

### 1.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD

<b>Operational Band</b>	2400 MHz to 2483.5 MHz	
<b>Frequency Range:</b>	IEEE 802.11b/g/n-HT20: 2412 MHz to 2462 MHz IEEE 802.11n-HT40: 2422 MHz to 2452 MHz	
<b>Support Standards:</b>	IEEE 802.11b, IEEE 802.11g, IEEE 802.11n-HT20, IEEE 802.11n-HT40	
<b>Type of Modulation:</b>	IEEE 802.11b: DSSS(CCK, DQPSK, DBPSK) IEEE 802.11g: OFDM(64-QAM, 16-QAM, QPSK, BPSK) IEEE 802.11n-HT20: OFDM(64-QAM, 16-QAM, QPSK, BPSK) IEEE 802.11n-HT40: OFDM(64-QAM, 16-QAM, QPSK, BPSK)	
<b>Data Rate:</b>	IEEE 802.11b: Up to 11 Mbps IEEE 802.11g: Up to 54 Mbps IEEE 802.11n-HT20: Up to MCS15 IEEE 802.11n-HT40: Up to MCS15	
<b>Number of Channels:</b>	IEEE 802.11b: 11 IEEE 802.11g: 11 IEEE 802.11n-HT20: 11 IEEE 802.11n-HT40: 7	
<b>Channel Separation:</b>	5 MHz	
<b>Antenna Type:</b>	Chain 0	PIFA Antenna
	Chain 1	PIFA Antenna
<b>Antenna Gain:</b>	Chain 0	-1.68 dBi
	Chain 1	-3.94 dBi
<b>Directional gain:</b>	0.27 dBi	
<b>Maximum Peak Power:</b>	SISO_ Chain 0	IEEE 802.11b: 20.97 dBm IEEE 802.11g: 22.36 dBm IEEE 802.11n-HT20: 21.07 dBm IEEE 802.11n-HT40: 20.06 dBm
	SISO_ Chain 1	IEEE 802.11b: 19.21 dBm IEEE 802.11g: 20.48 dBm IEEE 802.11n-HT20: 19.62 dBm IEEE 802.11n-HT40: 18.64 dBm
	CDD_ Chain 0+1	IEEE 802.11g: 24.63 dBm
	MIMO_ Chain 0+1	IEEE 802.11n-HT20: 23.39 dBm IEEE 802.11n-HT40: 22.39 dBm
<b>Normal Test Voltage:</b>	3.85 Vdc	

### 1.4 OTHER INFORMATION

Operation Frequency Each of Channel							
IEEE 802.11b, IEEE 802.11g, IEEE 802.11n-HT20							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412 MHz	4	2427 MHz	7	2442 MHz	10	2457 MHz
2	2417 MHz	5	2432 MHz	8	2447 MHz	11	2462 MHz
3	2422 MHz	6	2437 MHz	9	2452 MHz	--	--
IEEE 802.11n-HT40							
--	--	4	2427 MHz	7	2442 MHz	--	--
--	--	5	2432 MHz	8	2447 MHz	--	--
3	2422 MHz	6	2437 MHz	9	2452 MHz	--	--

## 1.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested with associated equipment below.

### 1) Support Equipment

Description	Manufacturer	Model No.	Serial Number	Supplied by
N/A	N/A	N/A	N/A	N/A

### 2) Support Cable

Cable No.	Description	Connector	Length	Supplied by
1	Antenna Cable	SMA	0.30 Meter	UnionTrust
2	Antenna Cable	SMA	0.30 Meter	UnionTrust

## 1.6 TEST LOCATION

### Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China 518109  
 Telephone: +86 (0) 755 2823 0888  
 Fax: +86 (0) 755 2823 0886

## 1.7 TEST FACILITY

The test facility is recognized, certified, or accredited by the following organizations:

### CNAS-Lab Code: L9069

The measuring equipment utilized to perform the tests documented in this report has been calibrated once a year or in accordance with the manufacturer's recommendations, and is traceable under the ISO/IEC/EN 17025 to international or national standards. Equipment has been calibrated by accredited calibration laboratories.

### IC-Registration No.: 21600-1

The 3m Semi-anechoic chamber of Shenzhen UnionTrust Quality and Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 21600-1.

### A2LA-Lab Certificate No.: 4312.01

Shenzhen UnionTrust Quality and Technology Co., Ltd. has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

### FCC Accredited Lab.

Designation Number: CN1194  
 Test Firm Registration Number: 259480

### 1.8 DEVIATION FROM STANDARDS

None.

### 1.9 ABNORMALITIES FROM STANDARD CONDITIONS

None.

### 1.10 OTHER INFORMATION REQUESTED BY THE CUSTOMER

None.

### 1.11 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the Product as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

No.	Item	Measurement Uncertainty
1	Conducted emission 9KHz-150KHz	±3.8 dB
2	Conducted emission 150KHz-30MHz	±3.4 dB
3	Radiated emission 9KHz-30MHz	±4.9 dB
4	Radiated emission 30MHz-1GHz	±4.7 dB
5	Radiated emission 1GHz-18GHz	±5.1 dB
6	Radiated emission 18GHz-26GHz	±5.2 dB
7	Radiated emission 26GHz-40GHz	±5.2 dB

## 2. TEST SUMMARY

FCC 47 CFR Part 15 Subpart C Test Cases			
Test Item	Test Requirement	Test Method	Result
Antenna Requirement	FCC 47 CFR Part 15 Subpart C Section 15.203/15.247 (c)	ANSI C63.10-2013	PASS
AC Power Line Conducted Emission	FCC 47 CFR Part 15 Subpart C Section 15.207	ANSI C63.10-2013	PASS
Conducted Peak Output Power	FCC 47 CFR Part 15 Subpart C Section 15.247 (b)(3)	KDB 558074 D01 v04 Section 9.1.3	PASS
6dB Bandwidth	FCC 47 CFR Part 15 Subpart C Section 15.247 (a)(2)	KDB 558074 D01 v04 Section 8.1	PASS
Power Spectral Density	FCC 47 CFR Part 15 Subpart C Section 15.247 (e)	KDB 558074 D01 v04 Section 10.2	PASS
Conducted Out of Band Emission	FCC 47 CFR Part 15 Subpart C Section 15.247(d)	KDB 558074 D01 v04 Section 11	PASS
Radiated Spurious Emissions	FCC 47 CFR Part 15 Subpart C Section 15.205/15.209	KDB 558074 D01 v04 Section 12.1	PASS
Band Edge Measurements (Radiated)	FCC 47 CFR Part 15 Subpart C Section 15.205/15.209	KDB 558074 D01 v04 Section 12.1	PASS
<b>Note:</b>			
1) N/A: In this whole report not application.			

### 3. EQUIPMENT LIST

Radiated Emission Test Equipment List						
Used	Equipment	Manufacturer	Model No.	Serial Number	Cal. date (mm dd, yyyy)	Cal. Due date (mm dd, yyyy)
<input checked="" type="checkbox"/>	3M Chamber & Accessory Equipment	ETS-LINDGREN	3M	N/A	Dec. 20, 2015	Dec. 19, 2018
<input checked="" type="checkbox"/>	Receiver	R&S	ESIB26	100114	Dec. 22, 2016	Dec. 22, 2017
<input type="checkbox"/>	EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY51440197	Dec. 22, 2016	Dec. 22, 2017
<input type="checkbox"/>	Loop Antenna	ETS-LINDGREN	6502	00202525	Jun. 24, 2015	Jun. 23, 2018
<input checked="" type="checkbox"/>	Broadband Antenna	ETS-LINDGREN	3142E	00201566	Jul. 24, 2015	Jul. 23, 2018
<input checked="" type="checkbox"/>	Preamplifier	HP	8447F	2805A02960	Dec. 22, 2016	Dec. 22, 2017
<input type="checkbox"/>	Broadband Antenna (Pre-amplifier)	ETS-LINDGREN	3142E-PA	00201891	Dec. 30, 2016	Dec. 30, 2017
<input type="checkbox"/>	Horn Antenna	ETS-LINDGREN	3117	00164202	Jul. 24, 2015	Jul. 23, 2018
<input checked="" type="checkbox"/>	Horn Antenna (Pre-amplifier)	ETS-LINDGREN	3117-PA	00201874	Dec. 30, 2016	Dec. 30, 2017
<input type="checkbox"/>	Horn Antenna	ETS-LINDGREN	3116C	00200180	Jul. 28, 2015	Jul. 27, 2018
<input checked="" type="checkbox"/>	Horn Antenna (Pre-amplifier)	ETS-LINDGREN	3116C-PA	00202652	Jul. 29, 2015	Jul. 28, 2018
<input checked="" type="checkbox"/>	Multi device Controller	ETS-LINDGREN	7006-001	00160105	N/A	N/A
<input checked="" type="checkbox"/>	Band Rejection Filter (2400MHz~2500MHz)	Micro-Tronics	BRM50702	G248	Jun. 21, 2017	Jun. 20, 2018
<input type="checkbox"/>	Band Rejection Filter (5150MHz~5880MHz)	Micro-Tronics	BRM50716	G1868	Jun. 15, 2017	Jun. 14, 2018
<input checked="" type="checkbox"/>	Test Software	Audix	e3	Software Version: 9.160323		

Conducted Emission Test Equipment List						
Used	Equipment	Manufacturer	Model No.	Serial Number	Cal. date (mm dd, yyyy)	Cal. Due date (mm dd, yyyy)
<input checked="" type="checkbox"/>	Receiver	R&S	ESR7	1316.3003K07-101181-K3	Dec. 22, 2016	Dec. 22, 2017
<input checked="" type="checkbox"/>	Pulse Limiter	R&S	ESH3-Z2	0357.8810.54	Dec. 22, 2016	Dec. 22, 2017
<input checked="" type="checkbox"/>	LISN	R&S	ESH2-Z5	860014/024	Dec. 22, 2016	Dec. 22, 2017
<input type="checkbox"/>	LISN	ETS-Lindgren	3816/2SH	00201088	Aug. 24, 2016	Aug. 23, 2017
<input checked="" type="checkbox"/>	Test Software	Audix	e3	Software Version: 9.160323		

Conducted RF test Equipment List						
Used	Equipment	Manufacturer	Model No.	Serial Number	Cal. date (mm dd, yyyy)	Cal. Due date (mm dd, yyyy)
<input checked="" type="checkbox"/>	EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY51440197	Dec. 22, 2016	Dec. 22, 2017
<input type="checkbox"/>	Receiver	R&S	ESR7	1316.3003K07-101181-K3	Dec. 22, 2016	Dec. 22, 2017
<input checked="" type="checkbox"/>	USB Wideband Power Sensor	KEYSIGHT	U2021XA	MY55430035	Dec. 22, 2016	Dec. 22, 2017
<input checked="" type="checkbox"/>	USB Wideband Power Sensor	KEYSIGHT	U2021XA	MY55430023	Dec. 22, 2016	Dec. 22, 2017

## 4. TEST CONFIGURATION

### 4.1 ENVIRONMENTAL CONDITIONS FOR TESTING

#### 4.1.1 Normal or Extreme Test Conditions

Environment Parameter	Selected Values During Tests		
	Ambient		
Test Condition	Temperature (°C)	Voltage (V)	Relative Humidity (%)
NT/NV	+15 to +35	3.85	20 to 75
<b>Remark:</b>			
1) NV: Normal Voltage; NT: Normal Temperature			

#### 4.1.2 Record of Normal Environment

Test Item	Temperature (°C)	Relative Humidity (%)	Pressure (Kpa)	Tested by
AC Power Line Conducted Emission	26.2	49	100.0	Bessy Xu
Conducted Peak Output Power	24.6	52	99.92	Tiny You
6dB Bandwidth	24.6	52	99.92	Tiny You
Power Spectral Density	24.6	52	99.92	Tiny You
Conducted Out of Band Emission	24.6	52	99.92	Tiny You
Radiated Spurious Emissions	26.5	45	98.69	Terence Chen
Band Edge Measurements (Radiated)	26.5	57	99.08	Tony Kang

## 4.2 TEST CHANNELS

Mode	Tx/Rx Frequency	Test RF Channel Lists		
		Lowest(L)	Middle(M)	Highest(H)
IEEE 802.11b	2412 MHz to 2462 MHz	Channel 1	Channel 6	Channel 11
		2412 MHz	2437 MHz	2462 MHz
IEEE 802.11g	2412 MHz to 2462 MHz	Channel 1	Channel 6	Channel 11
		2412 MHz	2437 MHz	2462 MHz
IEEE 802.11n-HT20	2412 MHz to 2462 MHz	Channel 1	Channel 6	Channel 11
		2412 MHz	2437 MHz	2462 MHz
IEEE 802.11n-HT40	2422 MHz to 2452 MHz	Channel 3	Channel 6	Channel 9
		2422 MHz	2437 MHz	2452 MHz

## 4.3 EUT TEST STATUS

Mode	Tx/Rx Function	Description
IEEE 802.11b IEEE 802.11g IEEE 802.11n-HT20 IEEE 802.11n-HT40	1Tx/1Rx	1. Keep the EUT in continuously transmitting or receiving with modulation test single.
IEEE 802.11g IEEE 802.11n-HT20 IEEE 802.11n-HT40	2Tx/2Rx	2. Keep the EUT in continuously transmitting or receiving with modulation test single.

4.4 PRE-SCAN

4.4.1 Pre-scan under all rates

Mode and Frequency	Maximum Conducted Average Power (dBm)_Chain 0							
	1		2		5.5		11	
IEEE 802.11b 2437 MHz	18.12		18.11		18.06		18.07	
IEEE 802.11g 2437 MHz	6	9	12	18	24	36	48	54
	17.28	17.23	17.25	17.19	17.16	17.21	17.22	17.23
IEEE 802.11n-HT20 2437 MHz	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
	15.80	15.77	15.74	15.71	15.60	15.60	15.63	15.67
	MCS8	MCS9	MCS10	MCS11	MCS12	MCS13	MCS14	MCS15
IEEE 802.11n-HT40 2437 MHz	15.82	15.81	15.76	15.74	15.61	15.62	15.68	15.73
	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
	15.05	15.03	15.01	14.95	14.89	14.85	14.90	14.89
IEEE 802.11n-HT40 2437 MHz	MCS8	MCS9	MCS10	MCS11	MCS12	MCS13	MCS14	MCS15
	15.05	15.02	15.03	14.94	14.92	14.87	14.92	14.93

4.4.2 Worst-case data rates

Mode	Worst-case data rates
IEEE 802.11b	1 Mbps
IEEE 802.11g	6 Mbps
IEEE 802.11n-HT20	MCS8
IEEE 802.11n-HT40	MCS8

4.5 TEST SETUP

4.5.1 For Radiated Emissions test setup






Figure 1. Below 30MHz


Figure 2. 30MHz to 1GHz



4.5.2 For Conducted Emissions test setup



4.5.3 For Conducted RF test setup



4.6 SYSTEM TEST CONFIGURATION

For emissions testing, the equipment under test (EUT) setup to transmit continuously to simplify the measurement methodology. Care was taken to ensure proper power supply voltages during testing. During testing, radiated emission were performed with the EUT set to transmit at the channel with highest output power as worst-case scenario. It was powered by a 3.85Vdc rechargeable Li-on battery. Only the worst case data were recorded in this test report.

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

[Http://www.uttlab.com](http://www.uttlab.com)

The signal is maximized through rotation and placement in the three orthogonal axes. The antenna height and polarization are varied during the search for maximum signal level. The antenna height is varied from 1 to 4 meters. Radiated emissions are taken at three meters unless the signal level is too low for measurement at that distance. If necessary, a pre-amplifier is used and/or the test is conducted at a closer distance. Therefore, all final radiated testing was performed with the EUT in (see table below) orientation.

Frequency	Mode	Antenna Port	Worst-case axis positioning
Above 1GHz	1TX	Chain 0	Y axis
	1TX	Chain 1	Y axis
	2TX	Chain 0+1	Y axis

All readings are extrapolated back to the equivalent three meter reading using inverse scaling with distance. Analyzer resolution is 100 kHz or greater for frequencies below 1000 MHz. The resolution is 1 MHz or greater for frequencies above 1000 MHz. The spurious emissions more than 20 dB below the permissible value are not reported.

Radiated emission measurement were performed from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.



#### 4.7 DUTY CYCLE



Mode	Data rates (Mbps)	On Time (msec)	Period (msec)	Duty Cycle (linear)	Duty Cycle (%)	Duty Cycle Factor (dB)	1/ T Minimum VBW (kHz)	Average Factor (dB)
IEEE 802.11b	1	12.460	12.570	0.99	99.12	0.00	0.01	-0.08
IEEE 802.11g	6	2.060	2.180	0.94	94.50	0.25	0.49	-0.49
IEEE 802.11n-HT20	MCS8	1.920	2.050	0.94	93.66	0.28	0.52	-0.57
IEEE 802.11n-HT20	MCS8	0.945	1.070	0.88	88.32	0.54	1.06	-1.08

**Remark:**

- 1) Duty cycle= On Time/ Period;
- 2) Duty Cycle factor =  $10 * \log(1/ \text{Duty cycle})$ ;
- 3) Average factor =  $20 \log_{10} \text{Duty Cycle}$ .

The test plot as follows





## 5. RADIO TECHNICAL REQUIREMENTS SPECIFICATION

### 5.1 REFERENCE DOCUMENTS FOR TESTING

No.	Identity	Document Title
1	FCC 47 CFR Part 2	Frequency allocations and radio treaty matters; general rules and regulations
2	FCC 47 CFR Part 15	Radio Frequency Devices
3	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices
4	KDB 558074 D01 DTS Meas Guidance v04	Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247
5	KDB 662911 D01 Multiple Transmitter Output v02r01	Emissions Testing of Transmitters with Multiple Outputs in the Same Band

### 5.2 ANTENNA REQUIREMENT

Standard Requirement
<p><b>15.203 requirement:</b> An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.</p>
<p><b>15.247(b) (4) requirement:</b> The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.</p>
<p><b>EUT Antenna:</b> Both antenna in the interior of the equipment and no consideration of replacement. The transmit signals are correlated with each other and the antenna gain of both chains is not the same, the best case directional gain of the antenna is 0.27dBi (See section 5.3).</p>

### 5.3 CONDUCTED PEAK OUTPUT POWER

**Test Requirement:** FCC 47 CFR Part 15 Subpart C Section 15.247 (b)(3)  
**Test Method:** KDB 558074 D01 v04, Section 9.1.3  
**Limit:** For systems using digital modulation in the 2400-2483.5 MHz bands: 1 Watt.  
**Test Procedure:**

1. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the power meter.
2. Measure out each test modes' peak or average output power, record the power level.

 Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.  
**Test Setup:** Refer to section 4.4.3 for details.  
**Instruments Used:** Refer to section 3 for details  
**Test Mode:** Transmitter mode  
**Test Results:** Pass  
**Test Data:**

Mode	Channel/ Frequency (MHz)	Maximum Conducted Peak Output Power (dBm)				Pass / Fail
		SISO_Chain 0	SISO_Chain 1	Total Power Chain 0+1	Limit (dBm)	
IEEE 802.11b	1(2412)	20.85	19.04	---	30	Pass
	6(2437)	20.79	19.21	---	30	Pass
	11(2462)	20.97	19.02	---	30	Pass
IEEE 802.11g	1(2412)	22.51	20.51	<b>24.63</b>	30	Pass
	6(2437)	22.36	20.48	24.53	30	Pass
	11(2462)	22.31	20.17	24.38	30	Pass
IEEE 802.11n-HT20	1(2412)	20.98	19.49	23.31	30	Pass
	6(2437)	21.03	19.62	23.39	30	Pass
	11(2462)	21.07	19.25	23.26	30	Pass
IEEE 802.11n-HT40	3(2422)	19.80	18.64	22.27	30	Pass
	6(2437)	20.06	18.57	22.39	30	Pass
	9(2452)	19.98	18.46	22.30	30	Pass

**Remark:**  
 1. Power with Duty Factor = Measured Power + Duty Cycle Factor  
 2. Total (Chain 0+1) =  $10 \cdot \log[(10^{\text{Chain 0}/10}) + (10^{\text{Chain 1}/10})]$   
 3. Directional gain and the maximum conducted output power limit see table below:

Frequency Band	Chain 0 Antenna Gain (dBi)	Chain 1 Antenna Gain (dBi)	Correlated chains directional gain (dBi)	Peak Power Limit (dBm)
2400 MHz to 2483.5 MHz	-1.68	-3.94	0.27	30.00
Unequal antenna gains, with equal transmit powers. Directional gain is to be computed as follows: If transmit signals are correlated, then Directional gain = $10 \log[(10^{G_1}/20 + 10^{G_2}/20 + \dots + 10^{G_N}/20)^2 / NANT]$ dBi [Note the "20"s in the denominator of each exponent and the square of the sum of terms; the object is to combine the signal levels coherently.]				

Mode	Channel/ Frequency (MHz)	Maximum Conducted Average Power (dBm)					
		SISO		Duty Cycle Factor (dB)	SISO		MIMO Total Power Chain 0+1
		Measured Power			Power with Duty Factor		
		Chain 0	Chain 1		Chain 0	Chain 1	
IEEE 802.11b	1(2412)	18.12	16.18	0.00	18.12	16.18	--
	6(2437)	18.08	16.34		18.08	16.34	--
	11(2462)	18.14	16.41		<b>18.14</b>	16.41	--
IEEE 802.11g	1(2412)	17.03	15.06	0.25	17.28	15.31	19.42
	6(2437)	17.01	15.15		17.26	15.40	19.44
	11(2462)	17.11	15.31		17.36	15.56	<b>19.56</b>
IEEE 802.11n-HT20	1(2412)	15.54	13.96	0.28	15.82	14.24	18.11
	6(2437)	15.52	14.13		15.80	14.41	18.17
	11(2462)	15.72	14.27		16.00	14.55	18.35
IEEE 802.11n-HT40	3(2422)	14.51	12.81	0.54	15.05	13.35	17.29
	6(2437)	14.21	12.66		14.75	13.20	17.05
	9(2452)	14.54	12.85		15.08	13.39	17.33

Remark:


1. Power with Duty Factor = Measured Power + Duty Cycle Factor
2. Total (Chain 0+1) =  $10 \cdot \log[(10^{\text{Chain 0}/10}) + (10^{\text{Chain 1}/10})]$


## 5.46 DB BANDWIDTH


<b>Test Requirement:</b>	FCC 47 CFR Part 15 Subpart C Section 15.247 (a)(2)
<b>Test Method:</b>	KDB 558074 D01 v04, Section 8.1
<b>Limit:</b>	For direct sequence systems, the minimum 6dB bandwidth shall be at least 500kHz
<b>Test Procedure:</b>	Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer. Use the following spectrum analyzer settings: a) Set RBW = 100 kHz. b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW. c) Detector = Peak. d) Trace mode = max hold. e) Sweep = auto couple. f) Allow the trace to stabilize. g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.  Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.
<b>Test Setup:</b>	Refer to section 4.4.3 for details.
<b>Instruments Used:</b>	Refer to section 3 for details
<b>Test Mode:</b>	Transmitter mode
<b>Test Results:</b>	Pass
<b>Test Data:</b>	


Mode	Channel/ Frequency (MHz)	6 dB Bandwidth (MHz)	99% Bandwidth (MHz)	6 dB Bandwidth Limit	Pass / Fail
<b>Chain 0</b>					
IEEE 802.11b	1(2412)	7.120	12.645	> 500 kHz	Pass
	6(2437)	8.076	12.881	> 500 kHz	Pass
	11(2462)	7.117	12.668	> 500 kHz	Pass
IEEE 802.11g	1(2412)	15.53	16.419	> 500 kHz	Pass
	6(2437)	15.68	16.447	> 500 kHz	Pass
	11(2462)	15.74	16.401	> 500 kHz	Pass
IEEE 802.11n-HT20	1(2412)	15.70	17.587	> 500 kHz	Pass
	6(2437)	16.67	17.644	> 500 kHz	Pass
	11(2462)	16.38	17.611	> 500 kHz	Pass
IEEE 802.11n-HT40	3(2422)	35.14	35.849	> 500 kHz	Pass
	6(2437)	35.83	36.165	> 500 kHz	Pass
	9(2452)	35.17	35.899	> 500 kHz	Pass
<b>Chain 1</b>					
IEEE 802.11b	1(2412)	8.070	12.710	> 500 kHz	Pass
	6(2437)	8.057	12.720	> 500 kHz	Pass
	11(2462)	8.080	13.528	> 500 kHz	Pass
IEEE 802.11g	1(2412)	14.78	16.421	> 500 kHz	Pass
	6(2437)	14.45	16.449	> 500 kHz	Pass
	11(2462)	15.76	16.468	> 500 kHz	Pass
IEEE 802.11n-HT20	1(2412)	15.98	17.595	> 500 kHz	Pass
	6(2437)	17.24	17.617	> 500 kHz	Pass
	11(2462)	16.99	17.612	> 500 kHz	Pass
IEEE 802.11n-HT40	3(2422)	35.42	36.007	> 500 kHz	Pass
	6(2437)	35.81	36.154	> 500 kHz	Pass
	9(2452)	35.21	36.063	> 500 kHz	Pass

The test plot as follows:









### 5.5 POWER SPECTRAL DENSITY

**Test Requirement:** FCC 47 CFR Part 15 Subpart C Section 15.247 (e)  
**Test Method:** KDB 558074 D01 v04, Section 10.2  
**Limit:** For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3kHz band during any time interval of continuous transmission.  
**Test Procedure:** Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.  
 Use the following spectrum analyzer settings:  
 a) Set analyzer center frequency to DTS channel center frequency.  
 b) Set the span to 1.5 times the DTS bandwidth.  
 c) Set the RBW to:  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ .  
 d) Set the VBW  $\geq 3 \times \text{RBW}$ .  
 e) Detector = peak.  
 f) Sweep time = auto couple.  
 g) Trace mode = max hold.  
 h) Allow trace to fully stabilize.  
 i) Use the peak marker function to determine the maximum amplitude level within the RBW.  
 j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

**Test Setup:** Refer to section 4.4.3 for details.  
**Instruments Used:** Refer to section 3 for details  
**Test Mode:** Transmitter mode  
**Test Results:** Pass  
**Test Data:**

Mode	Channel/ Frequency (MHz)	Power spectral density (dBm)				Pass / Fail
		SISO_ Chain 0	SISO_ Chain 1	Total Power MIMO_ Chain 0+1	Limit @3kHz (dBm)	
IEEE 802.11b	1(2412)	-6.959	-8.462	---	8	Pass
	6(2437)	-7.148	-7.501	---	8	Pass
	11(2462)	-6.298	-8.676	---	8	Pass
IEEE 802.11g	1(2412)	-9.565	-10.855	-7.15	8	Pass
	6(2437)	-9.835	-11.009	-7.37	8	Pass
	11(2462)	-9.751	-12.062	-7.74	8	Pass
IEEE 802.11n-HT20	1(2412)	-8.648	-8.919	<b>-5.77</b>	8	Pass
	6(2437)	-9.640	-8.200	-5.85	8	Pass
	11(2462)	-9.072	-10.567	-6.75	8	Pass
IEEE 802.11n-HT40	3(2422)	-12.324	-14.589	-10.30	8	Pass
	6(2437)	-12.795	-15.036	-10.76	8	Pass
	9(2452)	-11.773	-15.050	-10.10	8	Pass


- Remark:
- Power with Duty Factor = Measured Power + Duty Cycle Factor
  - Total (Chain 0+1) =  $10 \cdot \log[(10^{\text{Chain } 0/10}) + (10^{\text{Chain } 1/10})]$
  - Directional gain and the maximum conducted power spectral density limit see table below:


Frequency Band	Chain 0 Antenna Gain (dBi)	Chain 1 Antenna Gain (dBi)	Correlated chains directional gain (dBi)	Peak Power Limit (dBm)
2400 MHz to 2483.5 MHz	-1.68	-3.94	0.27	8.00
Unequal antenna gains, with equal transmit powers. Directional gain is to be computed as follows: If transmit signals are correlated, then $\text{Directional gain} = 10 \log\left[\frac{10^{G_1/20} + 10^{G_2/20} + \dots + 10^{G_N/20}}{N}\right]^2 / N$ dBi [Note the "20"s in the denominator of each exponent and the square of the sum of terms; the object is to combine the signal levels coherently.]				




The test plot as follows:












## 5.6 CONDUCTED OUT OF BAND EMISSION


<b>Test Requirement:</b>	FCC 47 CFR Part 15 Subpart C Section 15.247(d)
<b>Test Method:</b>	KDB 558074 D01 v04, Section 11
<b>Limit:</b>	In any 100kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.
<b>Test Procedure:</b>	<p>Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.</p> <p>Use the following spectrum analyzer settings:</p> <p><b>Step 1: Measurement Procedure REF</b></p> <ol style="list-style-type: none"> <li>a) Set instrument center frequency to DTS channel center frequency.</li> <li>b) Set the span to <math>\geq 1.5</math> times the DTS bandwidth.</li> <li>c) Set the RBW = 100 kHz.</li> <li>d) Set the VBW <math>\geq 3 \times</math> RBW.</li> <li>e) Detector = peak.</li> <li>f) Sweep time = auto couple.</li> <li>g) Trace mode = max hold.</li> <li>h) Allow trace to fully stabilize.</li> <li>i) Use the peak marker function to determine the maximum PSD level.</li> <li>j) Note that the channel found to contain the maximum PSD level can be used to establish the reference level.</li> </ol> <p><b>Step 2: Measurement Procedure OOBE</b></p> <ol style="list-style-type: none"> <li>a) Set RBW = 100 kHz.</li> <li>b) Set VBW <math>\geq 300</math> kHz.</li> <li>c) Detector = peak.</li> <li>d) Sweep = auto couple.</li> <li>e) Trace Mode = max hold.</li> <li>f) Allow trace to fully stabilize.</li> <li>g) Use the peak marker function to determine the maximum amplitude level.</li> </ol> <p>Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.</p>
<b>Test Setup:</b>	Refer to section 4.4.3 for details.
<b>Instruments Used:</b>	Refer to section 3 for details
<b>Test Mode:</b>	Transmitter mode
<b>Test Results:</b>	Pass
<b>Test Data:</b>	


The test plot as follows:




















### 5.7 RADIATED SPURIOUS EMISSIONS

**Test Requirement:** FCC 47 CFR Part 15 Subpart C Section 15.205/15.209

**Test Method:** KDB 558074 D01 v04, Section 12.1

**Receiver Setup:**

Frequency	RBW
0.009 MHz-0.150 MHz	200/300 kHz
0.150 MHz -30 MHz	9/10 kHz
30 MHz-1 GHz	100/120 kHz
Above 1 GHz	1 MHz

**Limits:**

**Spurious Emissions**

Frequency	Field strength (microvolt/meter)	Limit (dB $\mu$ V/m )	Remark	Measurement distance (m)
0.009 MHz-0.490 MHz	2400/F(kHz)	--	--	300
0.490 MHz-1.705 MHz	24000/F(kHz)	--	--	30
1.705 MHz-30 MHz	30	--	--	30
30 MHz-88 MHz	100	40.0	Quasi-peak	3
88 MHz-216 MHz	150	43.5	Quasi-peak	3
216 MHz-960 MHz	200	46.0	Quasi-peak	3
960MHz-1GHz	500	54.0	Quasi-peak	3
Above 1 GHz	500	54.0	Average	3

**Remark:**

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dB $\mu$ V/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.

**Test Setup:** Refer to section 4.4.1 for details.

**Test Procedures:**

1. From 30 MHz to 1GHz test procedure as below:
  - 1) The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
  - 2) The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
  - 3) The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
  - 4) For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rota table table was turned from 0 degrees to 360 degrees to find the maximum reading.
  - 5) The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
  - 6) If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
2. Above 1GHz test procedure as below:
  - 1) Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change form table 0.8 meter to 1.5 meter( Above 18GHz the distance is 1 meter and table is 1.5 meter).
  - 2) Test the EUT in the lowest channel ,middle channel, the Highest channel
  - 3) The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found

**Shenzhen UnionTrust Quality and Technology Co., Ltd.**

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China

Tel: +86-755-28230888

Fax: +86-755-28230886

E-mail: info@uttlab.com

[Http://www.uttlab.com](http://www.uttlab.com)

the Y axis positioning which it is worse case.

4) Repeat above procedures until all frequencies measured was complete.

**Equipment Used:** Refer to section 3 for details.

**Test Result:** Pass


**The measurement data as follows:**

**Radiated Emission Test Data (9 KHz ~ 30 MHz):**


The amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required to be report.

**Radiated Emission Test Data (30 MHz ~ 1 GHz Worst Case):**  
**Worst-Case Configuration**

**Horizontal**



No.	Frequency (MHz)	Reading (dBuV)	Correction factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1*	30.212	36.57	-11.33	25.24	40.00	-14.76	QP
2	43.538	36.68	-17.80	18.88	40.00	-21.12	QP
3	80.804	36.98	-19.33	17.65	40.00	-22.35	QP
4	145.811	31.79	-17.21	14.58	43.50	-28.92	QP
5	210.129	34.14	-15.00	19.14	43.50	-24.36	QP
6	311.452	34.63	-10.90	23.73	46.00	-22.27	QP



Radiated Emission Test Data (Above 1GHz):						
SISO Chain 0_IEEE 802.11b_Lowest Channel:						
No.	Frequency (MHz)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	4824.00	41.97	74.00	-32.03	Peak	Horizontal
2	7236.00	46.43	74.00	-27.57	Peak	Horizontal
3	4824.00	41.21	74.00	-32.79	Peak	Vertical
4	7236.00	45.07	74.00	-28.93	Peak	Vertical

SISO Chain 1_IEEE 802.11b_Lowest Channel:						
No.	Frequency (MHz)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	4824.00	43.28	74.00	-30.72	Peak	Horizontal
2	7236.00	46.56	74.00	-27.44	Peak	Horizontal
3	4824.00	41.11	74.00	-32.89	Peak	Vertical
4	7236.00	45.41	74.00	-28.59	Peak	Vertical

SISO Chain 0_IEEE 802.11b_Middle Channel:						
No.	Frequency (MHz)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	4874.00	41.58	74.00	-32.42	Peak	Horizontal
2	7311.00	46.09	74.00	-27.91	Peak	Horizontal
3	4874.00	41.11	74.00	-32.89	Peak	Vertical
4	7311.00	44.86	74.00	-29.14	Peak	Vertical

SISO Chain 1_IEEE 802.11b_Middle Channel:						
No.	Frequency (MHz)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	4874.00	44.02	74.00	-29.98	Peak	Horizontal
2	7311.00	46.20	74.00	-27.80	Peak	Horizontal
3	4874.00	40.18	74.00	-33.82	Peak	Vertical
4	7311.00	45.09	74.00	-28.91	Peak	Vertical

SISO Chain 0_IEEE 802.11b_Highest Channel:						
No.	Frequency (MHz)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	4924.00	41.45	74.00	-32.55	Peak	Horizontal
2	7386.00	45.94	74.00	-28.06	Peak	Horizontal
3	4924.00	40.63	74.00	-33.37	Peak	Vertical
4	7386.00	44.70	74.00	-29.30	Peak	Vertical

SISO Chain 1_IEEE 802.11b_Highest Channel:						
No.	Frequency (MHz)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	4924.00	45.31	74.00	-28.69	Peak	Horizontal
2	7386.00	46.62	74.00	-27.38	Peak	Horizontal
3	4924.00	41.97	74.00	-32.03	Peak	Vertical
4	7386.00	45.81	74.00	-28.19	Peak	Vertical

CDD Chain 0 + Chain 1_IIEEE 802.11g_Lowest Channel:						
No.	Frequency (MHz)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	4824.00	42.69	74.00	-31.31	Peak	Horizontal
2	7236.00	46.27	74.00	-27.73	Peak	Horizontal
3	4824.00	41.13	74.00	-32.87	Peak	Vertical
4	7236.00	44.65	74.00	-29.35	Peak	Vertical

CDD Chain 0 + Chain 1_IIEEE 802.11g_Middle Channel:						
No.	Frequency (MHz)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	4874.00	43.15	74.00	-30.85	Peak	Horizontal
2	7311.00	47.31	74.00	-26.69	Peak	Horizontal
3	4874.00	41.08	74.00	-32.92	Peak	Vertical
4	7311.00	45.52	74.00	-28.48	Peak	Vertical

CDD Chain 0 + Chain 1_IIEEE 802.11g_Highest Channel:						
No.	Frequency (MHz)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	4924.00	41.74	74.00	-32.26	Peak	Horizontal
2	7386.00	47.10	74.00	-26.90	Peak	Horizontal
3	4924.00	40.37	74.00	-33.63	Peak	Vertical
4	7386.00	45.23	74.00	-28.77	Peak	Vertical

MIMO Chain 0 + Chain 1_IIEEE 802.11n-HT20_Lowest Channel:						
No.	Frequency (MHz)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	4824.00	42.00	74.00	-32.00	Peak	Horizontal
2	7236.00	46.40	74.00	-27.60	Peak	Horizontal
3	4824.00	41.03	74.00	-32.97	Peak	Vertical
4	7236.00	46.90	74.00	-27.10	Peak	Vertical

MIMO Chain 0 + Chain 1_IIEEE 802.11n-HT20_Middle Channel:						
No.	Frequency (MHz)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	4874.00	42.44	74.00	-31.56	Peak	Horizontal
2	7311.00	46.92	74.00	-27.08	Peak	Horizontal
3	4874.00	42.09	74.00	-31.91	Peak	Vertical
4	7311.00	45.86	74.00	-28.14	Peak	Vertical

MIMO Chain 0 + Chain 1_IIEEE 802.11n-HT20_Highest Channel:						
No.	Frequency (MHz)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	4924.00	42.77	74.00	-31.23	Peak	Horizontal
2	7386.00	47.15	74.00	-26.85	Peak	Horizontal
3	4924.00	41.61	74.00	-32.39	Peak	Vertical
4	7386.00	45.88	74.00	-28.12	Peak	Vertical

MIMO Chain 0 + Chain 1 _IEEE 802.11n-HT40_Lowest Channel:						
No.	Frequency (MHz)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	4844.00	44.37	74.00	-29.63	Peak	Horizontal
2	7266.00	47.73	74.00	-26.27	Peak	Horizontal
3	4844.00	42.44	74.00	-31.56	Peak	Vertical
4	7266.00	45.81	74.00	-28.19	Peak	Vertical

MIMO Chain 0 + Chain 1 _IEEE 802.11n-HT40_Middle Channel:						
No.	Frequency (MHz)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	4874.00	42.45	74.00	-31.55	Peak	Horizontal
2	7311.00	47.21	74.00	-26.79	Peak	Horizontal
3	4874.00	41.82	74.00	-32.18	Peak	Vertical
4	7311.00	46.27	74.00	-27.73	Peak	Vertical

MIMO Chain 0 + Chain 1 _IEEE 802.11n-HT40_Highest Channel:						
No.	Frequency (MHz)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Antenna Polaxis
1	4904.00	42.05	74.00	-31.95	Peak	Horizontal
2	7356.00	47.13	74.00	-26.87	Peak	Horizontal
3	4904.00	41.88	74.00	-32.12	Peak	Vertical
4	7356.00	45.81	74.00	-28.19	Peak	Vertical

**Remark:**

As shown in this section, for frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. So, only the peak measurements were shown in the report.

### 5.8 BAND EDGE MEASUREMENTS (RADIATED)

**Test Requirement:** FCC 47 CFR Part 15 Subpart C Section 15.205/15.209

**Test Method:** KDB 558074 D01 v04, Section 12.1

**Limits:**

Radiated emissions which fall in the restricted bands, as defined in section 15.205(a), must also comply with the radiated emission limits specified in section 15.209(a).

Frequency	Limit (dB $\mu$ V/m @3m)	Remark
30 MHz-88 MHz	40.0	Quasi-peak Value
88 MHz-216 MHz	43.5	Quasi-peak Value
216 MHz-960 MHz	46.0	Quasi-peak Value
960 MHz-1 GHz	54.0	Quasi-peak Value
Above 1 GHz	54.0	Average Value
	74.0	Peak Value

**Test Setup:** Refer to section 4.4.1 for details.

**Test Procedures:**

Radiated band edge measurements at 2390 MHz and 2483.5 MHz were made with the unit transmitting in the low end of the channel range and the high end closest to the restricted bands respectively. The emissions were made on the 966 Semi-Chamber. Use (resolution bandwidth (RBW) = 1 MHz, video bandwidth (VBW) = 3 MHz for peak levels and RBW = 1 MHz and VBW = 10 Hz or 1/T for average levels).



1. Use radiated spurious emission test procedure described in clause 5.10. The transmitter output (antenna port) was connected to the test receiver.
2. Set the PK and AV limit line.
3. Record the fundamental emission and emissions out of the band-edge.
4. Determine band-edge compliance as required.



**Equipment Used:** Refer to section 3 for details.

**Test Result:** Pass



**The measurement data as follows:**



SISO Chain 0 IEEE 802.11b









SISO Chain 1 IEEE 802.11b









CDD\_Chain 0 + Chain 1\_ IEEE 802.11g









MIMO\_Chain 0+1\_ IEEE 802.11n-HT20





MIMO\_Chain 0 + Chain 1\_ IEEE 802.11n-HT40





### 5.9 CONDUCTED EMISSION

**Test Requirement:** 47 CFR Part 15C Section 15.207

**Test Method:** ANSI C63.10-2013 Section 6.2

**Limits:**

Frequency range (MHz)	Limits (dB(μV))	
	Quasi-peak	Average
0,15 to 0,50	66 to 56	56 to 46
0,50 to 5	56	46
5 to 30	60	50

**Remark:**

1. The lower limit shall apply at the transition frequencies.
2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 to 0.50 MHz.

**Test Setup:** Refer to section 4.4.2 for details.

**Test Procedures:**

Test frequency range :150KHz-30MHz

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50Ω/50μH + 5Ω linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

**Equipment Used:** Refer to section 3 for details.


**Test Result:** Pass

The measurement data as follows:


Quasi Peak and Average:

Mode: WIFI Link

Live Line



No.	Frequency (MHz)	Reading (dBuV)	Correction factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.154	15.90	10.20	26.10	55.80	-29.70	Average
2*	0.154	38.50	10.20	48.70	65.80	-17.10	QP
3	2.834	13.70	10.30	24.00	46.00	-22.00	Average
4	2.834	23.00	10.30	33.30	56.00	-22.70	QP
5	17.573	14.50	12.40	26.90	50.00	-23.10	Average
6	17.573	28.60	12.40	41.00	60.00	-19.00	QP



No.	Frequency (MHz)	Reading (dBuV)	Correction factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.150	27.50	10.20	37.70	56.00	-18.30	Average
2*	0.150	40.60	10.20	50.80	66.00	-15.20	QP
3	2.470	14.90	10.50	25.40	46.00	-20.60	Average
4	2.470	23.90	10.50	34.40	56.00	-21.60	QP
5	17.797	18.10	12.50	30.60	50.00	-19.40	Average
6	17.797	29.10	12.50	41.60	60.00	-18.40	QP

**Remark:**

1. An initial pre-scan was performed on the Phase and neutral lines with peak detector. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission were detected.

## APPENDIX 1 PHOTOS OF TEST SETUP

See test photos attached in Appendix 1 for the actual connections between Product and support equipment.

## APPENDIX 2 PHOTOS OF EUT CONSTRUCTIONAL DETAILS

Refer to Appendix 2 for EUT external and internal photos.

\*\*\* End of Report \*\*\*

---

---

The test report is effective only with both signature and specialized stamp. The result(s) shown in this report refer only to the sample(s) tested. Without written approval of UnionTrust, this report can't be reproduced except in full.

---

---