

**Conducted Band Edge****WCDMA Band V (RMC 12.2Kbps)****Lowest Band Edge****Highest Band Edge****WCDMA Band II (RMC 12.2Kbps)****Lowest Band Edge****Highest Band Edge**



WCDMA Band IV (RMC 12.2Kbps)

Lowest Band Edge



Highest Band Edge






Conducted Spurious Emission


WCDMA Band V (RMC 12.2Kbps)

Lowest Channel




WCDMA Band II (RMC 12.2Kbps)


Lowest Channel




Middle Channel




Middle Channel



Highest Channel




Highest Channel






WCDMA Band IV (RMC 12.2Kbps)


Lowest Channel



Middle Channel



Highest Channel



**Frequency Stability**

Test Conditions	Middle Channel	WCDMA Band V (RMC 12.2KbpsRMC 12.2Kbps)	Limit 2.5ppm
Temperature (°C)	Voltage (Volt)	Deviation (ppm)	Result
50	Normal Voltage	0.0006	PASS
40	Normal Voltage	0.0031	
30	Normal Voltage	0.0044	
20(Ref.)	Normal Voltage	0.0000	
10	Normal Voltage	0.0082	
0	Normal Voltage	0.0093	
-10	Normal Voltage	0.0096	
-20	Normal Voltage	0.0066	
-30	Normal Voltage	0.0078	
20	Maximum Voltage	0.0090	
20	Normal Voltage	0.0000	
20	Battery End Point	0.0265	

Test Conditions	Middle Channel	WCDMA Band II (RMC 12.2Kbps)	Limit Note 2.
Temperature (°C)	Voltage (Volt)	Deviation (ppm)	Result
50	Normal Voltage	0.0001	PASS
40	Normal Voltage	0.0008	
30	Normal Voltage	0.0010	
20(Ref.)	Normal Voltage	0.0000	
10	Normal Voltage	0.0013	
0	Normal Voltage	0.0023	
-10	Normal Voltage	0.0036	
-20	Normal Voltage	0.0024	
-30	Normal Voltage	0.0045	
20	Maximum Voltage	0.0051	
20	Normal Voltage	0.0000	
20	Battery End Point	0.0118	

Note:

1. Normal Voltage = 3.85V. ; Battery End Point (BEP) = 3.6 V. ; Maximum Voltage =4.25 V
2. The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.



Test Conditions	Middle Channel	WCDMA Band IV (RMC 12.2Kbps)	Limit Note 2.
Temperature (°C)	Voltage (Volt)	Deviation (ppm)	Result
50	Normal Voltage	0.0014	PASS
40	Normal Voltage	0.0003	
30	Normal Voltage	0.0002	
20(Ref.)	Normal Voltage	0.0000	
10	Normal Voltage	0.0020	
0	Normal Voltage	0.0013	
-10	Normal Voltage	0.0012	
-20	Normal Voltage	0.0006	
-30	Normal Voltage	0.0027	
20	Maximum Voltage	0.0038	
20	Normal Voltage	0.0000	
20	Battery End Point	0.0128	

Note:

1. Normal Voltage = 3.85V. ; Battery End Point (BEP) = 3.6 V. ; Maximum Voltage =4.25 V
2. The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.



Appendix B. Test Results of Radiated Test

Radiated Spurious Emission

Test Engineer :	Zhao hui Liang	Temperature :	22~25℃
		Relative Humidity :	48~52%

GSM850 (GSM) (ANT0)									
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	1672.8	-65.77	-13	-52.77	-71.85	-69.02	4.00	9.40	H
	2509.2	-63.89	-13	-50.89	-74.04	-67.46	4.88	10.60	H
	3345.6	-64.07	-13	-51.07	-75.90	-69.00	5.52	12.60	H
	1672.8	-66.95	-13	-53.95	-72.75	-70.20	4.00	9.40	V
	2509.2	-63.61	-13	-50.61	-74.09	-67.18	4.88	10.60	V
	3345.6	-63.30	-13	-50.30	-75.51	-68.23	5.52	12.60	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

GSM850 (EDGE 1 Tx slots) (ANT0)									
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	1672.8	-66.68	-13	-53.68	-72.76	-69.93	4.00	9.40	H
	2509.2	-63.86	-13	-50.86	-74.01	-67.43	4.88	10.60	H
	3345.6	-63.91	-13	-50.91	-75.74	-68.84	5.52	12.60	H
	1672.8	-67.10	-13	-54.10	-72.90	-70.35	4.00	9.40	V
	2509.2	-63.83	-13	-50.83	-74.31	-67.40	4.88	10.60	V
	3345.6	-63.37	-13	-50.37	-75.58	-68.30	5.52	12.60	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



GSM1900 (GSM) (ANT2)									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	3760	-61.80	-13	-48.80	-76.25	-68.55	5.85	12.60	H
	5640	-61.97	-13	-48.97	-78.85	-67.77	7.30	13.10	H
	7520	-56.96	-13	-43.96	-79.26	-60.11	8.35	11.50	H
	3760	-61.09	-13	-48.09	-75.72	-67.84	5.85	12.60	V
	5640	-62.11	-13	-49.11	-78.88	-67.91	7.30	13.10	V
	7520	-56.90	-13	-43.90	-79.08	-60.05	8.35	11.50	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

GSM1900 (EDGE 1 Tx slots) (ANT2)									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	3760	-61.47	-13	-48.47	-75.92	-68.22	5.85	12.60	H
	5640	-61.89	-13	-48.89	-78.77	-67.69	7.30	13.10	H
	7520	-56.94	-13	-43.94	-79.24	-60.09	8.35	11.50	H
	3760	-60.23	-13	-47.23	-74.86	-66.98	5.85	12.60	V
	5640	-62.14	-13	-49.14	-78.91	-67.94	7.30	13.10	V
	7520	-56.82	-13	-43.82	-79	-59.97	8.35	11.50	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

WCDMA Band V(RMC 12.2Kbps) (ANT1)									
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	1672.8	-66.69	-13	-53.69	-72.77	-69.94	4.00	9.40	H
	2509.2	-64.27	-13	-51.27	-74.42	-67.84	4.88	10.60	H
	3345.6	-63.56	-13	-50.56	-75.39	-68.49	5.52	12.60	H
	1672.8	-66.51	-13	-53.51	-72.31	-69.76	4.00	9.40	V
	2509.2	-63.58	-13	-50.58	-74.06	-67.15	4.88	10.60	V
	3345.6	-63.40	-13	-50.40	-75.61	-68.33	5.52	12.60	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



WCDMA Band II(RMC 12.2Kbps) (ANT2)									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	3760	-62.11	-13	-49.11	-76.56	-68.86	5.85	12.60	H
	5640	-61.98	-13	-48.98	-78.86	-67.78	7.30	13.10	H
	7520	-56.70	-13	-43.70	-79.00	-59.85	8.35	11.50	H
	3760	-61.83	-13	-48.83	-76.46	-68.58	5.85	12.60	V
	5640	-61.75	-13	-48.75	-78.52	-67.55	7.30	13.10	V
	7520	-57.02	-13	-44.02	-79.2	-60.17	8.35	11.50	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

WCDMA Band IV(RMC 12.2Kbps) (ANT2)									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	3465.2	-63.32	-13	-50.32	-75.86	-70.17	5.65	12.50	H
	5197.8	-61.57	-13	-48.57	-78.81	-67.24	7.13	12.80	H
	6930.4	-58.94	-13	-45.94	-79.47	-62.34	8.40	11.80	H
	3465.2	-61.61	-13	-48.61	-74.69	-68.46	5.65	12.50	V
	5197.8	-61.51	-13	-48.51	-78.7	-67.18	7.13	12.80	V
	6930.4	-58.82	-13	-45.82	-79.36	-62.22	8.40	11.80	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.