



# FCC RF Test Report

**APPLICANT** : Xiaomi Communications Co., Ltd.  
**EQUIPMENT** : Mobile Phone  
**BRAND NAME** : XIAOMI  
**MODEL NAME** : 2211133G  
**FCC ID** : 2AFZZ133G  
**STANDARD** : FCC Part 15 Subpart C §15.209  
**CLASSIFICATION** : (DCD) Part 15 Low Power Transmitter Below 1705 kHz  
**TEST DATE(S)** : Oct. 04, 2022 ~ Oct. 21, 2022

We, Sporton International Inc. (Kunshan), would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.

Jason Jia



Approved by: Jason Jia

**Sporton International Inc. (Kunshan)**

**No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300  
People's Republic of China**



# Table of Contents

**History of this test report.....3**

**Summary of Test Result.....4**

**1 General Description .....5**

    1.1 Applicant.....5

    1.2 Manufacturer .....5

    1.3 Product Feature of Equipment Under Test .....5

    1.4 Modification of EUT .....5

    1.5 Test Location .....6

    1.6 Test Software .....6

    1.7 Applied Standards .....6

**2 Test Configuration of Equipment Under Test .....7**

    2.1 Test Mode .....7

    2.2 Connection Diagram of Test System .....8

    2.3 Support Unit used in test configuration and system .....9

**3 Test Result .....10**

    3.1 20dB and 99% Occupied Bandwidth Measurement .....10

    3.2 Radiated Emission Measurement .....12

    3.3 AC Conducted Emission Measurement .....20

    3.4 Antenna Requirements.....24

**4 List of Measuring Equipment.....25**

**5 Uncertainty of Evaluation .....26**

**Appendix A. Setup Photographs**





### Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	2.1049	20dB Bandwidth	Reporting Only	-
3.1	2.1049	99% Occupied Bandwidth	Reporting Only	-
3.2	15.209	Radiated Emission	Pass	Under limit 6.76 dB at 50.370 MHz
3.3	15.207	AC Conducted Emission	Pass	Under limit 8.50 dB at 0.158 MHz
3.4	15.203	Antenna Requirements	Pass	-

**Declaration of Conformity:**  
The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

**Comments and Explanations:**  
The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.



# 1 General Description

## 1.1 Applicant

Xiaomi Communications Co., Ltd.

#019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085

## 1.2 Manufacturer

Xiaomi Communications Co., Ltd.

#019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085

## 1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Phone
Brand Name	XIAOMI
Model Name	2211133G
FCC ID	2AFZZ133G
IMEI Code	Conducted: 866917060030754/866917060030762 Conduction: 866917060031976/866917060031984 Radiation: 866917060031471/866917060031489
HW Version	P2
SW Version	MIUI 14
WPT Frequency Range	110 kHz~ 148 kHz
WPT Type of Modulation	ASK
WPT Antenna Type	Coil Antenna
EUT Stage	Identical Prototype

**Remark:** The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

## 1.4 Modification of EUT

No modifications are made to the EUT during all test items.



### 1.5 Test Location

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

<b>Test Firm</b>	Sporton International Inc. (Kunshan)		
<b>Test Site Location</b>	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158 FAX : +86-512-57900958		
<b>Test Site No.</b>	<b>Sporton Site No.</b>	<b>FCC Designation No.</b>	<b>FCC Test Firm Registration No.</b>
	CO01-KS 03CH02-KS TH01-KS	CN1257	314309

### 1.6 Test Software

Item	Site	Manufacture	Name	Version
1.	03CH02-KS	AUDIX	E3	6.2009-8-24a
2.	CO01-KS	AUDIX	E3	6.2009-8-24

### 1.7 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.209, §15.207
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01.
- ♦ ANSI C63.10-2013

**Remark:** All test items were verified and recorded according to the standards and without any deviation during the test.



## 2 Test Configuration of Equipment Under Test

### 2.1 Test Mode


- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 1000 MHz).
- b. AC power line Conducted Emission was tested under maximum output power.

Test Items	Function Type
AC Conducted Emission	Mode 1 : GSM850 Idle+ Bluetooth Link+ WLAN Link(2.4G)+ USB Cable (Charging from Adapter) + WPC(reverse)
RF Conducted / Radiated Emission	Mode 1 : Wireless Charging(Reverse charging for other phone)


**Remark:** The tests were performed with Adapter and USB Cable.

## 2.2 Connection Diagram of Test System

For Conducted Emission:



For Radiated Emission:



## 2.3 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Base Station	Anritsu	MT8821C	N/A	N/A	Unshielded,1.8m
2.	WLAN AP	D-link	DIR-655	KA21R655B1	N/A	Unshielded,1.8m
3.	Bluetooth Earphone	Xiaomi	LYEJ02LM	N/A	N/A	N/A
4.	Notebook	Lenovo	G480	QDS-BRCM1050I	N/A	shielded cable DC O/P 1.8m , Unshielded AC I/P cable 1.8m
5.	SD Card	Kingston	8GB	N/A	N/A	N/A
6.	Mobile phone	Xiaomi	N/A	N/A	N/A	N/A

### 3 Test Result

#### 3.1 20dB and 99% Occupied Bandwidth Measurement

##### 3.1.1 Limit of 20dB and 99% Occupied Bandwidth

Reporting only


##### 3.1.2 Measuring Instruments

See list of measuring equipment of this test report.

##### 3.1.3 Test Procedures

1. The 20dB bandwidth is measured with a spectrum analyzer connected via a receiver antenna placed near the EUT while wirelessly charging a charging board.
2. Use the following spectrum analyzer settings for 99 % Bandwidth measurement.
3. Measure and record the results in the test report.


##### 3.1.4 Test Setup






### 3.1.5 Test Result of 20dB and 99% Bandwidth

#### 20 dB Bandwidth Plot



#### 99% Occupied Bandwidth Plot



**Remark:** Because the measured signal is CW adjusting the RBW per C63.10 would not be practical since measured bandwidth will always follow the RBW and the result will be approximately twice the RBW.



### 3.2 Radiated Emission Measurement

#### 3.2.1 Limit of Radiated Emission

The emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

Receiver Parameter	Setting
Frequency Range: 9kHz~150kHz	RBW 200Hz for QP
Frequency Range: 150kHz~30MHz	RBW 9kHz for QP
Frequency Range: 30MHz~1000MHz	RBW 120kHz for Peak

**Note:** The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz. Radiated emission limits in these two bands are based on measurements employing an average detector.

For radiated emissions from 9kHz to 1GHz test distance is 3m

For 9kHz ~ 30MHz

1. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
2. Distance extrapolation factor = 40 log (specific distance / test distance) (dB);
3. specific line (dBµV/m) = 20 log Emission level (µV/m)
4. Limit line = specific limits (dBµV/m) + distance extrapolation factor.

#### 3.2.2 Measuring Instruments


See list of measuring equipment of this test report.

### 3.2.3 Measuring Instrument Setting

Follow the guidelines in ANSI C63.10-2013 with respect to maximizing the emission by rotating the EUT, measuring the emission for three EUT orthogonal planes, and adjusting the measurement antenna height and polarization. A pre-amp and a high pass filter are used for this test in order to get the good signal level.


### 3.2.4 Test Setup of Radiated Emission

For radiated emissions below 30MHz



**Note:** There is a comparison data of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.


For radiated emissions above 30MHz





3.2.5 Test Result of Fundamental Emission

Test Engineer :	Fang Wang	Temperature :	21~22°C
Polarization :	Horizontal	Relative Humidity :	41~42%




Site : 03CH02-KS  
 Condition : WPC 3m NFC-ANTENNA HORIZONTAL

1	0.14	65.54	-39.39	104.93	45.18	20.27	0.09	---	---	Peak
1	0.14	65.54	-39.39	104.93	45.18	20.27	0.09	---	---	Peak
1	0.14	65.54	-39.39	104.93	45.18	20.27	0.09	---	---	Peak



Test Engineer :	Fang Wang	Temperature :	21~22°C
Polarization :	Vertical	Relative Humidity :	41~42%




Site : 03CH02-KS  
 Condition : WPC 3m NFC-ANTENNA VERTICAL

1	0.14	56.18	-48.79	104.97	35.82	20.27	0.09	---	---	Peak
---	------	-------	--------	--------	-------	-------	------	-----	-----	------



3.2.6 Test Result of Radiated Emission (9kHz ~ 30MHz)

Test Engineer :	Fang Wang	Temperature :	21~22°C
Polarization :	Horizontal	Relative Humidity :	41~42%




Site : 03CH02-KS  
 Condition : WPC 3m NFC-ANTENNA HORIZONTAL

	Freq	Level	Over	Limit	ReadAntenna	Cable	A/Pos	T/Pos	Remark	
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	cm	deg	
1	0.05	53.32	-60.80	114.12	32.23	21.00	0.09	---	---	Average
2	0.07	48.22	-62.36	110.58	27.53	20.60	0.09	---	---	Average
3	1.12	50.91	-15.66	66.57	30.00	20.81	0.10	---	---	QP
4	3.44	40.36	-29.18	69.54	19.70	20.54	0.12	---	---	QP
5	10.79	35.11	-34.43	69.54	14.60	20.26	0.25	---	---	QP
6	28.64	31.81	-37.73	69.54	11.74	19.54	0.53	---	---	QP



Test Engineer :	Fang Wang	Temperature :	21~22°C
Polarization :	Vertical	Relative Humidity :	41~42%




Site : 03CH02-KS  
 Condition : WPC 3m NFC-ANTENNA VERTICAL

	Freq	Level	Over	Limit	ReadAntenna	Cable	A/Pos	T/Pos	Remark	
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	cm	deg	
1	0.07	44.34	-66.67	111.01	23.65	20.60	0.09	---	---	Average
2	0.08	44.45	-64.83	109.28	23.76	20.60	0.09	---	---	Average
3	1.12	50.35	-16.23	66.58	29.44	20.81	0.10	---	---	QP
4	3.33	34.86	-34.68	69.54	14.18	20.56	0.12	---	---	QP
5	17.69	36.16	-33.38	69.54	16.33	19.48	0.35	---	---	QP
6	27.97	31.24	-38.30	69.54	11.26	19.46	0.52	---	---	QP



3.2.7 Test Result of Radiated Emission (30MHz ~ 1000MHz)

Test Engineer :	Fang Wang	Temperature :	21~22°C
Polarization :	Horizontal	Relative Humidity :	41~42%




Site : 03CH02-KS  
 Condition : FCC WPC 3m LF 49921 HORIZONTAL

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Cable Factor	Preamp Loss	A/Pos	T/Pos	Remark	
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	65.89	23.61	-16.39	40.00	40.66	14.21	1.14	32.40	---	---	Peak
2	164.83	24.90	-18.60	43.50	39.25	16.18	1.87	32.40	---	---	Peak
3	191.02	27.91	-15.59	43.50	43.24	15.04	2.03	32.40	---	---	Peak
4	334.58	31.73	-14.27	46.00	41.22	20.22	2.69	32.40	---	---	Peak
5	430.61	31.74	-14.26	46.00	38.52	22.54	3.08	32.40	---	---	Peak
6	549.92	28.53	-17.47	46.00	32.64	25.10	3.19	32.40	---	---	Peak



Test Engineer :	Fang Wang	Temperature :	21~22°C
Polarization :	Vertical	Relative Humidity :	41~42%



Site : 03CH02-KS  
 Condition : FCC WPC 3m LF 49921 VERTICAL

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Cable Factor	Preamp Loss	A/Pos	T/Pos	Remark	
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	50.37	33.24	-6.76	40.00	50.15	14.49	1.00	32.40	---	---	Peak
2	191.02	22.94	-20.56	43.50	38.27	15.04	2.03	32.40	---	---	Peak
3	334.58	31.46	-14.54	46.00	40.95	20.22	2.69	32.40	---	---	Peak
4	430.61	28.77	-17.23	46.00	35.55	22.54	3.08	32.40	---	---	Peak
5	702.21	28.53	-17.47	46.00	30.22	26.75	3.96	32.40	---	---	Peak
6	821.52	31.29	-14.71	46.00	30.67	28.39	4.24	32.01	---	---	Peak



### 3.3 AC Conducted Emission Measurement

#### 3.3.1 Limits of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dBµV)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.


#### 3.3.2 Measuring Instruments

See list of measuring equipment of this test report.

#### 3.3.3 Test Procedure

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.


### 3.3.4 Test Setup





3.3.5 Test Result of AC Conducted Emission

Test Engineer :	Amos Zhang	Temperature :	25.3~26.2°C
		Relative Humidity :	38~40%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		




Site : CO01-KS  
 Condition : 15C RSS247-QP LISN-060105-LINE LINE

	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
1	0.156	56.09	-9.60	65.69	45.60	0.06	10.43	QP
2	0.156	33.69	-22.00	55.69	23.20	0.06	10.43	Average
3 *	0.169	55.68	-9.35	65.03	45.20	0.05	10.43	QP
4	0.169	33.78	-21.25	55.03	23.30	0.05	10.43	Average
5	0.229	45.93	-16.55	62.48	35.50	0.03	10.40	QP
6	0.229	27.03	-25.45	52.48	16.60	0.03	10.40	Average
7	0.315	41.89	-17.95	59.84	31.50	0.05	10.34	QP
8	0.315	25.99	-23.85	49.84	15.60	0.05	10.34	Average
9	0.494	38.69	-17.41	56.10	28.51	-0.03	10.21	QP
10	0.494	24.39	-21.71	46.10	14.21	-0.03	10.21	Average
11	1.671	38.46	-17.54	56.00	28.50	-0.11	10.07	QP
12	1.671	29.26	-16.74	46.00	19.30	-0.11	10.07	Average



Test Engineer :	Amos Zhang	Temperature :	25.3~26.2°C
		Relative Humidity :	38~40%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		



Site : CO01-KS  
 Condition : 15C RSS247-QP LISN-060105-NEUTRAL NEUTRAL

	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
1 *	0.158	57.06	-8.50	65.56	46.60	0.03	10.43	QP
2	0.158	35.06	-20.50	55.56	24.60	0.03	10.43	Average
3	0.169	54.66	-10.33	64.99	44.19	0.04	10.43	QP
4	0.169	32.36	-22.63	54.99	21.89	0.04	10.43	Average
5	0.239	45.89	-16.24	62.13	35.49	0.01	10.39	QP
6	0.239	26.99	-25.14	52.13	16.59	0.01	10.39	Average
7	1.071	41.49	-14.51	56.00	31.50	-0.11	10.10	QP
8	1.071	27.79	-18.21	46.00	17.80	-0.11	10.10	Average
9	1.296	40.48	-15.52	56.00	30.50	-0.11	10.09	QP
10	1.296	28.28	-17.72	46.00	18.30	-0.11	10.09	Average
11	1.671	40.46	-15.54	56.00	30.51	-0.12	10.07	QP
12	1.671	28.76	-17.24	46.00	18.81	-0.12	10.07	Average

Note:

- Level(dBμV) = Read Level(dBμV) + LISN Factor(dB) + Cable Loss(dB)
- Over Limit(dB) = Level(dBμV) – Limit Line(dBμV)



### **3.4 Antenna Requirements**

#### **3.4.1 Standard Applicable**

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited.

The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

#### **3.4.2 Antenna Anti-Replacement Construction**

An embedded-in antenna design is used.



## 4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV30	101338	10Hz~30GHz	Apr. 12, 2022	Oct. 19, 2022	Apr. 11, 2023	Conducted (TH01-KS)
EMI Test Receiver	R&S	ESR7	101403	9kHz~7GHz;Max 30dBm	Oct. 16, 2021	Oct. 04, 2022	Oct. 15, 2022	Radiation (03CH02-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Oct. 30, 2021	Oct. 04, 2022	Oct. 29, 2022	Radiation (03CH02-KS)
Bilog Antenna	TeseQ	CBL6111D	44483	30MHz-1GHz	Dec. 22, 2021	Oct. 04, 2022	Dec. 21, 2022	Radiation (03CH02-KS)
Amplifier	SONOMA	310N	413741	9KHz-1GHz	Jan. 05, 2022	Oct. 04, 2022	Jan. 04, 2023	Radiation (03CH02-KS)
AC Power Source	Chroma	61601	616010002473	N/A	NCR	Oct. 04, 2022	NCR	Radiation (03CH02-KS)
Turn Table	MF	MF7802	N/A	0~360 degree	NCR	Oct. 04, 2022	NCR	Radiation (03CH02-KS)
Antenna Mast	MF	MF7802	N/A	1 m~4 m	NCR	Oct. 04, 2022	NCR	Radiation (03CH02-KS)
EMI Receiver	R&S	ESC17	100768	9kHz~7GHz;	May 24, 2022	Oct. 21, 2022	May 23, 2023	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060103	9kHz~30MHz	Oct. 13, 2022	Oct. 21, 2022	Oct. 12, 2023	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060105	9kHz~30MHz	May 24, 2022	Oct. 21, 2022	May 23, 2023	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP000000811	AC 0V~300V, 45Hz~1000Hz	Oct. 12, 2022	Oct. 21, 2022	Oct. 11, 2023	Conduction (CO01-KS)

NCR: No Calibration Required



## 5 Uncertainty of Evaluation

Test Item	Uncertainty
Occupied Channel Bandwidth	±0.10 %

### Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.78dB
---	--------

### Uncertainty of Radiated Emission Measurement (9 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	4.0dB
---	-------

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	4.0dB
---	-------

----- THE END -----