



FCC RF Test Report

APPLICANT : Xiaomi Communications Co., Ltd.
EQUIPMENT : Mobile Phone
BRAND NAME : Redmi
MODEL NAME : 21091116UG
FCC ID : 2AFZZ16UG
STANDARD : 47 CFR Part 2, Part 27 Subpart Q
CLASSIFICATION : PCS Licensed Transmitter Held to Ear (PCE)
TEST DATE(S) : Sep. 23, 2021 ~ Oct. 18, 2021

We, Sporton International (ShenZhen) Inc., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.26-2015 and shown compliance with the applicable technical standards.

This report contains data that were produced under subcontract by Sporton International (Kunshan) Inc.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (ShenZhen) Inc., the test report shall not be reproduced except in full.

Reviewed by: Derreck Chen / Supervisor

Approved by: Eric Shih / Manager



Sporton International (ShenZhen) Inc.

1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055

People's Republic of China



TABLE OF CONTENTS

REVISION HISTORY..... 3
SUMMARY OF TEST RESULT 4
1 GENERAL DESCRIPTION 5
1.1 Applicant 5
1.2 Manufacturer 5
1.3 Product Feature of Equipment Under Test 5
1.4 Product Specification of Equipment Under Test 6
1.5 Modification of EUT 6
1.6 Maximum EIRP Power and Emission Designator 6
1.7 Testing Site 7
1.8 Test Software 7
1.9 Applied Standards 8
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST 9
2.1 Test Mode 9
2.2 Connection Diagram of Test System 10
2.3 Support Unit used in test configuration and system 10
2.4 Measurement Results Explanation Example 11
2.5 Frequency List of Low/Middle/High Channels 11
3 CONDUCTED TEST ITEMS 12
3.1 Measuring Instruments 12
3.2 Test Setup 12
3.3 Test Result of Conducted Test 12
3.4 Conducted Output Power Measurement 13
3.5 Peak-to-Average Ratio 14
3.6 EIRP 15
3.7 Occupied Bandwidth 16
3.8 Conducted Band Edge Measurement 17
3.9 Conducted Spurious Emission Measurement 18
3.10 Frequency Stability Measurement 19
4 RADIATED TEST ITEMS 20
4.1 Measuring Instruments 20
4.2 Test Setup 20
4.3 Test Result of Radiated Test 21
4.4 Radiated Spurious Emission Measurement 22
5 LIST OF MEASURING EQUIPMENT 23
6 UNCERTAINTY OF EVALUATION 24
APPENDIX A. TEST RESULTS OF CONDUCTED TEST
APPENDIX B. TEST RESULTS OF RADIATED TEST
APPENDIX C. TEST SETUP PHOTOGRAPHS



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.4	§2.1046	Conducted Output Power	-	Reporting Only	-
3.5	§27.50 (k)(4)	Peak-to-Average Ratio	<13dB	PASS	
3.6	§27.50 (k)(3)	EIRP	EIRP < 1W (30dBm)	PASS	-
3.7	§2.1049	Occupied Bandwidth	-	Reporting Only	-
3.8	§2.1051 §27.53 (n)(2)	Conducted Band Edge Measurement	-13dBm/MHz	PASS	-
3.9	§2.1051 §27.53 (n)(2)	Conducted Spurious Emission	-13dBm/MHz	PASS	-
3.10	§2.1055 §27.54	Frequency Stability Temperature & Voltage	Within the band	PASS	-
4.4	§2.1053 §27.53 (n)(2)	Radiated Spurious Emission	-13dBm/MHz	PASS	Under limit 31.43 dB at 13962.000 MHz

Declaration of Conformity:
The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:
The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.



1 General Description

1.1 Applicant

Xiaomi Communications Co., Ltd.

#019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085

1.2 Manufacturer

Xiaomi Communications Co., Ltd.

#019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Phone
Brand Name	Redmi
Model Name	21091116UG
FCC ID	2AFZZ16UG
IMEI Code	Conducted: 861239050029141/861239050029158 Radiation: 861239050030347/861239050030354
HW Version	P2
SW Version	MIUI 12.5
EUT Stage	Identical Prototype

1.4 Product Specification of Equipment Under Test

Product Feature	
Tx/Rx Frequency	LTE Band 42: 3450 MHz ~ 3550 MHz
Bandwidth	5MHz / 10MHz / 15MHz / 20MHz
Maximum Output Power to Antenna	<p><Ant. 2> LTE Band 42 : 23.16 dBm</p> <p><Ant. 4> LTE Band 42 : 22.95 dBm</p> <p><Ant. 6> LTE Band 42 : 24.91 dBm</p> <p><Ant. 11> LTE Band 42 : 22.95 dBm</p>
Antenna Gain	<p><Ant. 2> LTE Band 42 : -1.8 dBi</p> <p><Ant. 4> LTE Band 42 : -3.5 dBi</p> <p><Ant. 6> LTE Band 42 : -2.57 dBi</p> <p><Ant. 11> LTE Band 42 : -2.65 dBi</p>
Type of Modulation	QPSK / 16QAM / 64QAM / 256QAM(Downlink only)

Note: The EIRP is calculated from Output power and antenna gain, so the maximum EIRP is shown in the report for Antenna 6.

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Maximum EIRP Power and Emission Designator

LTE Band 42		QPSK		16QAM/64QAM	
BW (MHz)	Frequency Range (MHz)	Maximum EIRP(W)	Emission Designator (99%OBW)	Maximum EIRP(W)	Emission Designator (99%OBW)
5	3452.5 ~ 3547.5	0.1710	4M52G7D	0.1340	4M50W7D
10	3455 ~ 3545	0.1683	9M07G7D	0.1346	9M05W7D
15	3457.5 ~ 3542.5	0.1679	13M4G7D	0.1355	13M5W7D
20	3460 ~ 3540	0.1714	17M9G7D	0.1358	17M9W7D

Note: All modulations have been tested, only the worst test results of PSK & QAM are shown in the report.

1.7 Testing Site

Sporton International (Shenzhen) Inc. is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

Test Firm	Sporton International (Shenzhen) Inc.		
Test Site Location	1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055 People's Republic of China TEL: +86-755-86379589 FAX: +86-755-86379595		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	TH01-SZ	CN1256	421272

Sporton International (Kunshan) Inc. is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International (Kunshan) Inc.		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158 FAX : +86-512-57900958		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	03CH04-KS	CN1257	314309

Test data subcontracted: conducted test case in section 4.4 of this report

1.8 Test Software

Item	Site	Manufacturer	Name	Version
1.	03CH04-KS	AUDIX	E3	6.2009-8-24a



1.9 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 2, Part 27 Subpart Q
- ♦ ANSI C63.26-2015
- ♦ FCC KDB 971168 Power Meas License Digital Systems D01 v03r01
- ♦ FCC KDB 412172 D01 Determining ERP and EIRP v01r01
- ♦

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

2.1 Test Mode


Antenna port conducted and radiated test items listed below are performed according to KDB 971168 D01 Power Meas. License Digital Systems v03r01 with maximum output power.

Radiated measurements are performed by rotating the EUT in three different orthogonal test planes to find the maximum emission.

Test Cases	Band	Bandwidth (MHz)	Modulation	RB #	Test Channel
		eg. 5M, 10M, 15M, 20M	eg. QPSK, 16QAM, 64QAM,	1RB, Partial RB, Full RB	L/M/H
Max. Output Power	LTE Band 42	5M, 10M, 15M, 20M	QPSK, 16QAM, 64QAM,	1RB, Partial RB, Full RB	L, M, H
Peak-to-Average Ratio	LTE Band 42	20M	QPSK, 16QAM, 64QAM	1RB, Full RB	L, M, H
E.I.R.P	LTE Band 42	5M, 10M, 15M, 20M	QPSK, 16QAM, 64QAM	1RB	L, M, H
26dB and 99% Bandwidth	LTE Band 42	5M, 10M, 15M, 20M	QPSK, 16QAM, 64QAM	Full RB	L, M, H
Conducted Band Edge	LTE Band 42	5M, 10M, 15M, 20M	QPSK, 16QAM, 64QAM	1RB, Full RB	L, H
Conducted Spurious Emission	LTE Band 42	5M, 10M, 15M, 20M	QPSK, 16QAM, 64QAM	1RB	L, M, H
Frequency Stability	LTE Band 42	10M	QPSK	Full RB	M
Radiated Spurious Emission	LTE Band 42	Worst case			M

Note: The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst case emissions are reported.

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	Base Station	Anritsu	MT8821C	N/A	N/A	Unshielded, 1.8 m
2.	Power Supply	GWINSTEK	PSS-2002	N/A	N/A	Unshielded, 1.8 m
3.	Earphone	MI	N/A	N/A	Unshielded, 1.2m	N/A

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

$$\text{Offset} = \text{RF cable loss} + \text{attenuator factor}.$$

Following shows an offset computation example with cable loss 9.5 dB and 10dB attenuator.

Example :

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\ &= 9.5 + 10 = 19.5 \text{ (dB)} \end{aligned}$$

2.5 Frequency List of Low/Middle/High Channels

LTE Band 42 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	42190	42590	42990
	Frequency	3460	3500	3540
15	Channel	42165	42590	43015
	Frequency	3457.5	3500	3542.5
10	Channel	42140	42590	43040
	Frequency	3455	3500	3545
5	Channel	42115	42590	43065
	Frequency	3452.5	3500	3547.5


3 Conducted Test Items

3.1 Measuring Instruments


See list of measuring instruments of this test report.

3.2 Test Setup


3.2.1 Conducted Output Power



3.2.2 Peak-to-Average Ratio, Occupied / 26dB Bandwidth, Band-Edge and Conducted Spurious Emission



3.2.3 Frequency Stability



3.3 Test Result of Conducted Test

Please refer to Appendix A.



3.4 Conducted Output Power Measurement

3.4.1 Description of the Conducted Output Power Measurement

A base station simulator was used to establish communication with the EUT. Its parameters were set to transmit the maximum power on the EUT. The measured power in the radio frequency on the transmitter output terminals shall be reported.

3.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2
2. The transmitter output port was connected to the system simulator.
3. Set EUT at maximum power through the system simulator.
4. Select lowest, middle, and highest channels for each band and different modulation.
5. Measure and record the power level from the system simulator.

3.5 Peak-to-Average Ratio

3.5.1 Description of the PAR Measurement

Power Complementary Cumulative Distribution Function (CCDF) curves provide a means for characterizing the power peaks of a digitally modulated signal on a statistical basis. A CCDF curve depicts the probability of the peak signal amplitude exceeding the average power level. Most contemporary measurement instrumentation include the capability to produce CCDF curves for an input signal provided that the instrument's resolution bandwidth can be set wide enough to accommodate the entire input signal bandwidth. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.5.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2.3.4 (CCDF).
2. The EUT was connected to spectrum and system simulator via a power divider.
3. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
4. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
5. Record the deviation as Peak to Average Ratio.

3.6 EIRP

3.6.1 Description of EIRP Limit

§ 27.50 (k)(3)

Mobile devices are limited to 1Watt (30 dBm) EIRP. Mobile devices operating in these bands must employ a means for limiting power to the minimum necessary for successful communications

3.6.2 Test Procedures

1. According to KDB 412172 D01 Power Approach,
2. $EIRP = P_T + G_T - L_C$, $ERP = EIRP - 2.15$, where
 P_T = transmitter output power in dBm
 G_T = gain of the transmitting antenna in dBi
 L_C = signal attenuation in the connecting cable between the transmitter and antenna in dB

3.7 Occupied Bandwidth

3.7.1 Description of Occupied Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

3.7.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.4
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
5. Set the detection mode to peak, and the trace mode to max hold.
6. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace.
(this is the reference value)
7. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
8. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “-X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
9. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.

3.8 Conducted Band Edge Measurement

3.8.1 Description of Conducted Band Edge Measurement

§ 27.53 (n)(2)

For mobile operations in the 3450-3550 MHz band, the conducted power of any emission outside the licensee's authorized bandwidth shall not exceed -13 dBm/MHz.

Compliance with this paragraph is based on the use of measurement instrumentation employing a resolution bandwidth of 1 megahertz or greater. However, in the 1 megahertz bands immediately outside and adjacent to the licensee's frequency block, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed, but limited to a maximum of 200 kHz. In the bands between 1 and 5 MHz removed from the licensee's frequency block, the minimum resolution bandwidth for the measurement shall be 500 kHz.

3.8.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The band edges of low and high channels for the highest RF powers were measured.
4. Set RBW $\geq 1\%$ EBW but limited to a maximum of 200 kHz in the 1MHz band immediately outside and adjacent to the band edge.
5. Beyond the 1 MHz and 5 MHz removed from the band edge, set RBW ≥ 500 KHz.
6. Beyond the 5 MHz removed from the band edge, set RBW = 1MHz.
7. Set spectrum analyzer with RMS detector.
8. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
9. Checked that all the results comply with the emission limit line.

3.9 Conducted Spurious Emission Measurement

3.9.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges shall not exceed -13 dBm/MHz.

It is measured by means of a calibrated spectrum analyzer and scanned from 30MHz up to a frequency including its 10th harmonic.

3.9.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz.
7. Set spectrum analyzer with RMS detector.
8. Taking the record of maximum spurious emission.
9. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
10. Checked that all the results comply with the emission limit line.

3.10 Frequency Stability Measurement

3.10.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block.

3.10.2 Test Procedures for Temperature Variation

1. The testing follows ANSI C63.26 section 5.6.4
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C step up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.10.3 Test Procedures for Voltage Variation

1. The testing follows ANSI C63.26 section 5.6.5.
2. The EUT was placed in a temperature chamber at $20\pm 5^{\circ}\text{C}$ and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value for other than hand carried battery equipment.
4. For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.
5. The variation in frequency was measured for the worst case.


4 Radiated Test Items

4.1 Measuring Instruments


See list of measuring instruments of this test report.

4.2 Test Setup


4.2.1 For radiated test below 30MHz



4.2.2 For radiated test from 30MHz to 1GHz



4.2.3 For radiated test above 1GHz



4.3 Test Result of Radiated Test

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

Please refer to Appendix B.

4.4 Radiated Spurious Emission Measurement

4.4.1 Description of Radiated Spurious Emission

The radiated spurious emission was measured by substitution method according to ANSI C63.26. The power of any emission outside of the authorized operating frequency ranges shall not exceed -13 dBm/MHz.

The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

4.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.5
2. The EUT was placed on a turntable with 0.8 meter height for frequency below 1GHz and 1.5 meter height for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the receiving antenna mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between 1m to 4m to search the maximum spurious emission for both horizontal and vertical polarizations.
6. During the measurement, the system simulator parameters were set to force the EUT transmitting at maximum output power.
7. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
8. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
9. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
$$\text{EIRP (dBm)} = \text{S.G. Power} - \text{Tx Cable Loss} + \text{Tx Antenna Gain}$$
$$\text{ERP (dBm)} = \text{EIRP} - 2.15$$
10. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.



5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101078	10Hz~40GHz	Apr. 08, 2021	Sep. 23, 2021~ Oct. 18, 2021	Apr. 07, 2022	Conducted (TH01-SZ)
Power Divider	TOJOIN	PS-2SM-04 265	60.06.020.007 7	0.4GHz~26.5GHz	Dec. 26, 2020	Sep. 23, 2021~ Oct. 18, 2021	Dec. 25, 2021	Conducted (TH01-SZ)
Thermal Chamber	Ten Billion Hongzhangroup	LP-150U	H2014081803	-40~+150°C	Jul. 14, 2021	Sep. 23, 2021~ Oct. 18, 2021	Jul. 13, 2022	Conducted (TH01-SZ)
EXA Spectrum Analyzer	Keysight	N9010A	MY55150244	10Hz-44G,MAX 30dB	Apr. 13, 2021	Oct. 09, 2021	Apr. 12, 2022	Radiation (03CH04-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Nov. 01, 2020	Oct. 09, 2021	Oct. 31, 2021	Radiation (03CH04-KS)
Bilog Antenna	TeseQ	CBL6111D	49922	30MHz-1GHz	Jun. 07, 2021	Oct. 09, 2021	Jun. 06, 2022	Radiation (03CH04-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	75957	1GHz~18GHz	Nov. 01, 2020	Oct. 09, 2021	Oct. 31, 2021	Radiation (03CH04-KS)
SHF-EHF Horn	Com-power	AH-840	101115	18GHz~40GHz	Jan. 06, 2021	Oct. 09, 2021	Jan. 05, 2022	Radiation (03CH04-KS)
Amplifier	SONOMA	310N	187289	9KHz-1GHz	Jan. 06, 2021	Oct. 09, 2021	Jan. 05, 2022	Radiation (03CH04-KS)
Amplifier	MITEQ	EM18G40G GA	060728	18~40GHz	Jan. 07, 2021	Oct. 09, 2021	Jan. 06, 2022	Radiation (03CH04-KS)
high gain Amplifier	MITEQ	AMF-7D-00 101800-30-1 QP	2025788	1Ghz-18Ghz	Jan. 06, 2021	Oct. 09, 2021	Jan. 05, 2022	Radiation (03CH04-KS)
Amplifier	Keysight	83017A	MY57280106	500MHz~26.5GHz	Oct. 14, 2020	Oct. 09, 2021	Oct. 13, 2021	Radiation (03CH04-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Oct. 09, 2021	NCR	Radiation (03CH04-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Oct. 09, 2021	NCR	Radiation (03CH04-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Oct. 09, 2021	NCR	Radiation (03CH04-KS)

NCR: No Calibration Required

6 Uncertainty of Evaluation

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.26-2015. All the measurement uncertainty value were shown with a coverage $K=2$ to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.3dB
---	--------------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.8dB
---	--------------

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.8dB
---	--------------

----- THE END -----



Appendix A. Test Results of Conducted Test

Conducted Output Power(Average power)

LTE Band 42:

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.
Channel				42190	42590	42990
Frequency (MHz)				3460	3500	3540
20	QPSK	1	0	24.79	24.91	24.68
20	QPSK	1	49	24.76	24.86	24.66
20	QPSK	1	99	24.60	24.69	24.57
20	QPSK	50	0	23.80	23.90	23.71
20	QPSK	50	24	23.73	23.89	23.69
20	QPSK	50	50	23.66	23.80	23.62
20	QPSK	100	0	23.73	23.86	23.68
20	16QAM	1	0	23.90	23.71	23.67
20	16QAM	1	49	23.86	23.75	23.73
20	16QAM	1	99	23.66	23.57	23.56
20	16QAM	50	0	22.94	22.78	22.73
20	16QAM	50	24	22.96	22.73	22.66
20	16QAM	50	50	22.80	22.66	22.64
20	16QAM	100	0	22.83	22.69	22.65
20	64QAM	1	0	22.62	22.45	22.43
20	64QAM	1	49	22.72	22.48	22.40
20	64QAM	1	99	22.39	22.39	22.38
20	64QAM	50	0	21.90	21.76	21.68
20	64QAM	50	24	21.84	21.71	21.65
20	64QAM	50	50	21.80	21.63	21.60
20	64QAM	100	0	21.87	21.73	21.68
Channel				42165	42590	43015
Frequency (MHz)				3457.5	3500	3542.5
15	QPSK	1	0	24.79	24.82	24.73
15	QPSK	1	37	24.71	24.69	24.79
15	QPSK	1	74	24.68	24.65	24.65
15	QPSK	36	0	23.85	23.70	23.85
15	QPSK	36	20	23.73	23.81	23.70
15	QPSK	36	39	23.66	23.77	23.78
15	QPSK	75	0	23.83	23.71	23.80
15	16QAM	1	0	23.89	23.82	23.82
15	16QAM	1	37	23.84	23.73	23.72
15	16QAM	1	74	23.46	23.51	23.61
15	16QAM	36	0	22.81	22.82	22.93
15	16QAM	36	20	22.85	22.83	22.82



15	16QAM	36	39	22.64	22.75	22.79
15	16QAM	75	0	22.81	22.79	22.78
15	64QAM	1	0	22.50	22.58	22.57
15	64QAM	1	37	22.56	22.59	22.64
15	64QAM	1	74	22.31	22.36	22.39
15	64QAM	36	0	21.87	21.76	21.87
15	64QAM	36	20	21.81	21.78	21.82
15	64QAM	36	39	21.64	21.79	21.71
15	64QAM	75	0	21.67	21.77	21.79
Channel				42140	42590	43040
Frequency (MHz)				3455	3500	3545
10	QPSK	1	0	24.73	24.77	24.81
10	QPSK	1	25	24.74	24.83	24.73
10	QPSK	1	49	24.59	24.49	24.56
10	QPSK	25	0	23.74	23.80	23.73
10	QPSK	25	12	23.88	23.80	23.78
10	QPSK	25	25	23.68	23.67	23.74
10	QPSK	50	0	23.83	23.85	23.74
10	16QAM	1	0	23.79	23.86	23.76
10	16QAM	1	25	23.81	23.69	23.83
10	16QAM	1	49	23.48	23.53	23.60
10	16QAM	25	0	22.92	22.75	22.87
10	16QAM	25	12	22.81	22.84	22.93
10	16QAM	25	25	22.65	22.78	22.72
10	16QAM	50	0	22.79	22.82	22.79
10	64QAM	1	0	22.59	22.43	22.60
10	64QAM	1	25	22.63	22.64	22.59
10	64QAM	1	49	22.35	22.36	22.40
10	64QAM	25	0	21.83	21.74	21.81
10	64QAM	25	12	21.67	21.64	21.72
10	64QAM	25	25	21.74	21.62	21.60
10	64QAM	50	0	21.77	21.70	21.70
Channel				42115	42590	43065
Frequency (MHz)				3452.5	3500	3547.5
5	QPSK	1	0	24.89	24.90	24.74
5	QPSK	1	12	24.74	24.66	24.71
5	QPSK	1	24	24.68	24.63	24.66
5	QPSK	12	0	23.75	23.84	23.69
5	QPSK	12	7	23.88	23.85	23.77
5	QPSK	12	13	23.72	23.67	23.73
5	QPSK	25	0	23.68	23.73	23.68
5	16QAM	1	0	23.83	23.84	23.81
5	16QAM	1	12	23.77	23.72	23.67
5	16QAM	1	24	23.48	23.55	23.52
5	16QAM	12	0	22.83	22.88	22.80
5	16QAM	12	7	22.77	22.79	22.93
5	16QAM	12	13	22.66	22.63	22.71
5	16QAM	25	0	22.81	22.68	22.74



5	64QAM	1	0	22.53	22.51	22.55
5	64QAM	1	12	22.59	22.60	22.53
5	64QAM	1	24	22.38	22.38	22.34
5	64QAM	12	0	21.75	21.74	21.74
5	64QAM	12	7	21.67	21.70	21.73
5	64QAM	12	13	21.70	21.73	21.69
5	64QAM	25	0	21.73	21.74	21.74



EIRP

LTE Band 42 (GT - LC = -2.57 dB) QPSK			
Bandwidth	5M		
Channel	42115	42590	43065
	(Low)	(Mid)	(High)
Frequency	3452.5	3500	3547.5
(MHz)			
Conducted Power (dBm)	24.89	24.90	24.74
Conducted Power (Watts)	0.3083	0.3090	0.2979
EIRP(dBm)	22.32	22.33	22.17
EIRP(Watts)	0.1706	0.1710	0.1648

LTE Band 42 (GT - LC = -2.57 dB) QPSK									
Bandwidth	10M			15M			20M		
Channel	42140	42590	43040	42165	42590	43015	42190	42590	42990
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(Mid)
Frequency	3455	3500	3545	3457.5	3500	3542.5	3460	3500	3540
(MHz)									
Conducted Power (dBm)	24.74	24.83	24.73	24.79	24.82	24.73	24.79	24.91	24.68
Conducted Power (Watts)	0.2979	0.3041	0.2972	0.3013	0.3034	0.2972	0.3013	0.3097	0.2938
EIRP(dBm)	22.17	22.26	22.16	22.22	22.25	22.16	22.22	22.34	22.11
EIRP(Watts)	0.1648	0.1683	0.1644	0.1667	0.1679	0.1644	0.1667	0.1714	0.1626



LTE Band 42 (GT - LC = -2.57 dB) 16QAM			
Bandwidth	5M		
Channel	42115	42590	43065
	(Low)	(Mid)	(High)
Frequency	3452.5	3500	3547.5
(MHz)			
Conducted Power (dBm)	23.83	23.84	23.81
Conducted Power (Watts)	0.2415	0.2421	0.2404
EIRP(dBm)	21.26	21.27	21.24
EIRP(Watts)	0.1337	0.1340	0.1330

LTE Band 42 (GT - LC = -2.57 dB) 16QAM									
Bandwidth	10M			15M			20M		
Channel	42140	42590	43040	42165	42590	43015	42190	42590	42990
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(Mid)
Frequency	3455	3500	3545	3457.5	3500	3542.5	3460	3500	3540
(MHz)									
Conducted Power (dBm)	23.79	23.86	23.76	23.89	23.82	23.82	23.90	23.71	23.67
Conducted Power (Watts)	0.2393	0.2432	0.2377	0.2449	0.2410	0.2410	0.2455	0.2350	0.2328
EIRP(dBm)	21.22	21.29	21.19	21.32	21.25	21.25	21.33	21.14	21.10
EIRP(Watts)	0.1324	0.1346	0.1315	0.1355	0.1334	0.1334	0.1358	0.1300	0.1288



LTE Band 42 (GT - LC = -2.57 dB) 64QAM			
Bandwidth	5M		
Channel	42115	42590	43065
	(Low)	(Mid)	(High)
Frequency	3452.5	3500	3547.5
(MHz)			
Conducted Power (dBm)	22.59	22.60	22.53
Conducted Power (Watts)	0.1816	0.1820	0.1791
EIRP(dBm)	20.02	20.03	19.96
EIRP(Watts)	0.1005	0.1007	0.0991

LTE Band 42 (GT - LC = -2.57 dB) 64QAM									
Bandwidth	10M			15M			20M		
Channel	42140	42590	43040	42165	42590	43015	42190	42590	42990
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(Mid)
Frequency	3455	3500	3545	3457.5	3500	3542.5	3460	3500	3540
(MHz)									
Conducted Power (dBm)	22.63	22.64	22.59	22.56	22.59	22.64	22.72	22.48	22.40
Conducted Power (Watts)	0.1832	0.1837	0.1816	0.1803	0.1816	0.1837	0.1871	0.1770	0.1738
EIRP(dBm)	20.06	20.07	20.02	19.99	20.02	20.07	20.15	19.91	19.83
EIRP(Watts)	0.1014	0.1016	0.1005	0.0998	0.1005	0.1016	0.1035	0.0979	0.0962




Peak-to-Average Ratio

Mode	LTE Band 42 / 20MHz				
Mod.	QPSK		16QAM		Limit: 13dB
RB Size	1RB	Full RB	1RB	Full RB	Result
Lowest CH	4.52	5.30	4.46	6.38	PASS
Middle CH	4.87	6.52	5.30	5.94	
Highest CH	5.48	6.20	5.51	6.35	
Mode	LTE Band 42 / 20MHz				
Mod.	64QAM				Limit: 13dB
RB Size	1RB	Full RB			Result
Lowest CH	5.71	6.87	-	-	PASS
Middle CH	6.03	7.01	-	-	
Highest CH	5.74	6.49	-	-	



LTE Band 42 / 20MHz / QPSK

Lowest Channel / 1RB




Date: 24_SEP_2021 15:59:59

Lowest Channel / Full RB




Date: 24_SEP_2021 15:58:08

Middle Channel / 1RB



Date: 24_SEP_2021 16:00:41

Middle Channel / Full RB




Date: 24_SEP_2021 16:03:26

Highest Channel / 1RB



Date: 24_SEP_2021 16:06:09

Highest Channel / Full RB




Date: 24_SEP_2021 16:03:57



LTE Band 42 / 20MHz / 16QAM

Lowest Channel / 1RB




Date: 24_SEP.2021 15:59:39

Lowest Channel / Full RB



Date: 24_SEP.2021 15:58:34

Middle Channel / 1RB




Date: 24_SEP.2021 16:03:04

Middle Channel / Full RB



Date: 24_SEP.2021 16:03:09

Highest Channel / 1RB



Date: 24_SEP.2021 16:05:46

Highest Channel / Full RB




Date: 24_SEP.2021 16:04:20




LTE Band 42 / 20MHz / 64QAM

Lowest Channel / 1RB



Date: 24_SEP.2021 15:59:23

Lowest Channel / Full RB




Date: 24_SEP.2021 15:58:49

Middle Channel / 1RB



Date: 24_SEP.2021 16:01:30

Middle Channel / Full RB




Date: 24_SEP.2021 16:02:57

Highest Channel / 1RB



Date: 24_SEP.2021 16:05:22

Highest Channel / Full RB



Date: 24_SEP.2021 16:04:43




26dB Bandwidth

Mode	LTE Band 42 : 26dB BW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	-	-	-	-	4.77	4.87	9.67	9.67	14.33	14.27	18.74	18.86
Middle CH	-	-	-	-	4.79	4.83	9.83	9.63	14.21	14.33	18.94	18.66
Highest CH	-	-	-	-	4.89	4.75	9.67	9.77	14.33	14.18	18.66	19.02
Mode	LTE Band 42 : 26dB BW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	64QAM		64QAM		64QAM		64QAM		64QAM		64QAM	
Lowest CH	-	-	-	-	4.81		9.69		14.27		18.82	
Middle CH	-	-	-	-	4.86		9.83		14.42		18.86	
Highest CH	-	-	-	-	4.78		9.63		14.42		18.66	




LTE Band 42

Lowest Channel / 5MHz / QPSK




Date: 24_SEP_2021 14:57:44

Lowest Channel / 5MHz / 16QAM




Date: 24_SEP_2021 14:59:53

Middle Channel / 5MHz / QPSK




Date: 24_SEP_2021 15:02:28

Middle Channel / 5MHz / 16QAM




Date: 24_SEP_2021 15:01:50

Highest Channel / 5MHz / QPSK



Date: 24_SEP_2021 15:03:05

Highest Channel / 5MHz / 16QAM




Date: 24_SEP_2021 15:03:38




LTE Band 42

Lowest Channel / 10MHz / QPSK




Date: 24_SEP_2021 15:13:13

Lowest Channel / 10MHz / 16QAM




Date: 24_SEP_2021 15:12:17

Middle Channel / 10MHz / QPSK




Date: 24_SEP_2021 15:16:33

Middle Channel / 10MHz / 16QAM




Date: 24_SEP_2021 15:17:08

Highest Channel / 10MHz / QPSK



Date: 24_SEP_2021 15:20:44

Highest Channel / 10MHz / 16QAM




Date: 24_SEP_2021 15:20:09




LTE Band 42

Lowest Channel / 15MHz / QPSK




Date: 24_SEP.2021 15:26:36

Lowest Channel / 15MHz / 16QAM




Date: 24_SEP.2021 15:25:09

Middle Channel / 15MHz / QPSK




Date: 24_SEP.2021 15:27:10

Middle Channel / 15MHz / 16QAM




Date: 24_SEP.2021 15:27:41

Highest Channel / 15MHz / QPSK



Date: 24_SEP.2021 15:30:30

Highest Channel / 15MHz / 16QAM




Date: 24_SEP.2021 15:30:03




LTE Band 42

Lowest Channel / 20MHz / QPSK




Date: 24.SEP.2021 15:45:25

Lowest Channel / 20MHz / 16QAM




Date: 24.SEP.2021 15:44:52

Middle Channel / 20MHz / QPSK




Date: 24.SEP.2021 15:47:08

Middle Channel / 20MHz / 16QAM




Date: 24.SEP.2021 15:47:39

Highest Channel / 20MHz / QPSK



Date: 24.SEP.2021 15:51:07

Highest Channel / 20MHz / 16QAM




Date: 24.SEP.2021 15:50:43




LTE Band 42

Lowest Channel / 5MHz / 64QAM




Date: 24_SEP.2021 15:00:33

Lowest Channel / 10MHz / 64QAM




Date: 24_SEP.2021 15:11:13

Middle Channel / 5MHz / 64QAM




Date: 24_SEP.2021 15:01:20

Middle Channel / 10MHz / 64QAM



Date: 24_SEP.2021 15:18:10

Highest Channel / 5MHz / 64QAM



Date: 24_SEP.2021 15:04:15

Highest Channel / 10MHz / 64QAM




Date: 24_SEP.2021 15:19:35




LTE Band 42

Lowest Channel / 15MHz / 64QAM




Date: 24_SEP.2021 15:41:56

Lowest Channel / 20MHz / 64QAM




Date: 24_SEP.2021 15:43:32

Middle Channel / 15MHz / 64QAM




Date: 24_SEP.2021 15:29:02

Middle Channel / 20MHz / 64QAM



Date: 24_SEP.2021 15:48:03

Highest Channel / 15MHz / 64QAM



Date: 24_SEP.2021 15:29:37

Highest Channel / 20MHz / 64QAM



Date: 24_SEP.2021 15:49:56




Occupied Bandwidth

Mode	LTE Band 42 : 99%OBW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	-	-	-	-	4.52	4.48	8.99	8.99	13.37	13.40	17.90	17.82
Middle CH	-	-	-	-	4.48	4.50	9.07	9.03	13.37	13.52	17.86	17.94
Highest CH	-	-	-	-	4.47	4.49	8.99	8.99	13.43	13.43	17.94	17.90
Mode	LTE Band 42 : 99%OBW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	64QAM		64QAM		64QAM		64QAM		64QAM		64QAM	
Lowest CH	-	-	-	-	4.48		8.97		13.34		17.90	
Middle CH	-	-	-	-	4.50		9.05		13.46		17.86	
Highest CH	-	-	-	-	4.49		9.01		13.46		17.86	




LTE Band 42

Lowest Channel / 5MHz / QPSK




Date: 24_SEP.2021 14:57:30

Lowest Channel / 5MHz / 16QAM




Date: 24_SEP.2021 14:59:43

Middle Channel / 5MHz / QPSK




Date: 24_SEP.2021 15:02:16

Middle Channel / 5MHz / 16QAM




Date: 24_SEP.2021 15:03:39

Highest Channel / 5MHz / QPSK



Date: 24_SEP.2021 15:02:52

Highest Channel / 5MHz / 16QAM




Date: 24_SEP.2021 15:03:26




LTE Band 42

Lowest Channel / 10MHz / QPSK




Date: 24_SEP.2021 15:13:05

Lowest Channel / 10MHz / 16QAM




Date: 24_SEP.2021 15:12:06

Middle Channel / 10MHz / QPSK




Date: 24_SEP.2021 15:15:43

Middle Channel / 10MHz / 16QAM




Date: 24_SEP.2021 15:16:58

Highest Channel / 10MHz / QPSK



Date: 24_SEP.2021 15:20:34

Highest Channel / 10MHz / 16QAM




Date: 24_SEP.2021 15:19:53




LTE Band 42

Lowest Channel / 15MHz / QPSK




Date: 24_SEP.2021 15:26:27

Lowest Channel / 15MHz / 16QAM




Date: 24_SEP.2021 15:23:49

Middle Channel / 15MHz / QPSK




Date: 24_SEP.2021 15:27:02

Middle Channel / 15MHz / 16QAM




Date: 24_SEP.2021 15:27:34

Highest Channel / 15MHz / QPSK



Date: 24_SEP.2021 15:30:20

Highest Channel / 15MHz / 16QAM




Date: 24_SEP.2021 15:29:51




LTE Band 42

Lowest Channel / 20MHz / QPSK




Date: 24_SEP.2021 15:45:17

Lowest Channel / 20MHz / 16QAM




Date: 24_SEP.2021 15:44:44

Middle Channel / 20MHz / QPSK




Date: 24_SEP.2021 15:46:57

Middle Channel / 20MHz / 16QAM




Date: 24_SEP.2021 15:47:31

Highest Channel / 20MHz / QPSK



Date: 24_SEP.2021 15:50:59

Highest Channel / 20MHz / 16QAM




Date: 24_SEP.2021 15:50:27




LTE Band 42

Lowest Channel / 5MHz / 64QAM




Date: 24_SEP.2021 15:01:20

Lowest Channel / 10MHz / 64QAM




Date: 24_SEP.2021 15:11:05

Middle Channel / 5MHz / 64QAM




Date: 24_SEP.2021 15:01:13

Middle Channel / 10MHz / 64QAM




Date: 24_SEP.2021 15:17:59

Highest Channel / 5MHz / 64QAM



Date: 24_SEP.2021 15:04:01

Highest Channel / 10MHz / 64QAM




Date: 24_SEP.2021 15:19:27




LTE Band 42

Lowest Channel / 15MHz / 64QAM




Date: 24_SEP.2021 15:41:47

Lowest Channel / 20MHz / 64QAM




Date: 24_SEP.2021 15:43:21

Middle Channel / 15MHz / 64QAM




Date: 24_SEP.2021 15:28:54

Middle Channel / 20MHz / 64QAM




Date: 24_SEP.2021 15:47:54

Highest Channel / 15MHz / 64QAM



Date: 24_SEP.2021 15:29:30


Highest Channel / 20MHz / 64QAM



Date: 24_SEP.2021 15:49:49




Conducted Band Edge






LTE Band 42 / 5MHz / 16QAM

Lowest Band Edge / 1 RB




Date: 23.SEP.2021 11:19:48

Highest Band Edge / 1 RB




Date: 23.SEP.2021 11:38:51

Lowest Band Edge / Full RB



Date: 23.SEP.2021 11:24:38

Highest Band Edge / Full RB




Date: 23.SEP.2021 11:41:20



LTE Band 42 / 5MHz / 64QAM

Lowest Band Edge / 1RB




Date: 23.SEP.2021 11:21:33

Highest Band Edge / 1 RB




Date: 23.SEP.2021 11:39:40

Lowest Band Edge / Full RB



Date: 23.SEP.2021 11:24:08

Highest Band Edge / Full RB



Date: 23.SEP.2021 11:40:16