



RF TEST REPORT

Applicant Xiaomi Communications Co., Ltd.
FCC ID 2AFZZJ20SG
Product Mobile Phone
Brand POCO
Model M2102J20SG
Report No. R2012A0844-R1
Issue Date January 19, 2021

TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **FCC CFR47 Part 2 (2019)/ FCC CFR 47 Part 22H (2019)**. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Prepared by: Peng Tao

Approved by: Kai Xu

TA Technology (Shanghai) Co., Ltd.

No.145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai, China

TEL: +86-021-50791141/2/3

FAX: +86-021-50791141/2/3-8000



TABLE OF CONTENT

1. Test Laboratory	4
1.1. Notes of the Test Report	4
1.2. Test facility	4
1.3. Testing Location	4
2. General Description of Equipment under Test.....	5
2.3. Applicant and Manufacturer Information	5
2.4. General Information.....	5
3. Applied Standards	7
4. Test Configuration.....	8
5. Test Case Results.....	10
5.1. RF Power Output and Effective Radiated Power	10
5.2. Occupied Bandwidth	15
5.3. Band Edge Compliance.....	26
5.4. Peak-to-Average Power Ratio (PAPR)	37
5.5. Frequency Stability.....	40
5.6. Spurious Emissions at Antenna Terminals	44
5.7. Radiates Spurious Emission	50
6. Main Test Instruments	56
ANNEX A: The EUT Appearance	57
ANNEX B: Test Setup Photos	58



Summary of measurement results

No.	Test Case	Clause in FCC rules	Verdict
1	RF Power Output and Effective Radiated Power	2.1046 22.913(a)(5)	PASS
2	Occupied Bandwidth	2.1049	PASS
3	Band Edge Compliance	2.1051 / 22.917(a)	PASS
4	Peak-to-Average Power Ratio	22.913(d)/ KDB 971168 D01(5.7)	PASS
5	Frequency Stability	2.1055 / 22.355	PASS
6	Spurious Emissions at Antenna Terminals	2.1051 / 22.917(a)	PASS
7	Radiates Spurious Emission	2.1053 / 22.917 (a)	PASS
Date of Testing: December 19, 2020 ~January 12, 2021			
Date of Sample Received: December 14, 2020			
Note: All indications of Pass/Fail in this report are opinions expressed by TA Technology (Shanghai) Co., Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only.			



1. Test Laboratory

1.1. Notes of the Test Report

This report shall not be reproduced in full or partial, without the written approval of **TA technology (shanghai) co., Ltd.** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above.

1.2. Test facility

FCC (Designation number: CN1179, Test Firm Registration Number: 446626)

TA Technology (Shanghai) Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform measurements.

A2LA (Certificate Number: 3857.01)

TA Technology (Shanghai) Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform measurement.

1.3. Testing Location

Company: TA Technology (Shanghai) Co., Ltd.
Address: No.145, Jintang Rd, Tangzhen Industry Park, Pudong
City: Shanghai
Post code: 201201
Country: P. R. China
Contact: Xu Kai
Telephone: +86-021-50791141/2/3
Fax: +86-021-50791141/2/3-8000
Website: <http://www.ta-shanghai.com>
E-mail: xukai@ta-shanghai.com

2. General Description of Equipment under Test

2.3. Applicant and Manufacturer Information

Applicant	Xiaomi Communications Co., Ltd.
Applicant address	#019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085
Manufacturer	Xiaomi Communications Co., Ltd.
Manufacturer address	#019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085

2.4. General Information

EUT Description			
Model	M2102J20SG		
IMEI	IMEI 1:864460050016600 IMEI 2:864460050016618		
Hardware Version	P1		
Software Version	MIUI12		
Power Supply	Battery / AC adapter		
Antenna Type	Internal Antenna		
Antenna Gain	Band	Main Antenna Gain(dBi)	Diversity Antenna Gain(dBi)
	GSM 850	-5.11	-3.59
	WCDMA Band V	-5.11	-3.59
	LTE Band 5	-5.11	-3.59
Test Mode(s)	GSM 850; WCDMA Band V; LTE Band 5;		
Test Modulation	(GSM/GPRS)GMSK, (EGPRS) GMSK/ 8PSK; (WCDMA) BPSK,QPSK,16QAM; (LTE)QPSK, 16QAM, 64QAM;		
GPRS Multislot Class	33		
EGPRS Multislot Class	33		
HSDPA UE Category	24		
HSUPA UE Category	6		
LTE Category	18		
Maximum E.R.P.	GSM 850:	27.78dBm	
	WCDMA Band V:	18.68dBm	
	LTE Band 5:	18.78dBm	
Rated Power Supply Voltage	3.87V		
Extreme Voltage	Minimum: 3.29V Maximum: 4.45V		
Extreme Temperature	Lowest: -30°C Highest: +50°C		
Operating Voltage	Minimum: 3.6V Maximum: 4.4V		



Operating Temperature	Lowest: 0°C Highest: +40°C		
Operating Frequency Range(s)	Band	Tx (MHz)	Rx (MHz)
	GSM850	824 ~ 849	869 ~ 894
	WCDMA Band V	824 ~ 849	869 ~ 894
	LTE Band 5	824 ~ 849	869 ~ 894
Note: 1. The EUT is sent from the applicant to TA and the information of the EUT is declared by the applicant.			



3. Applied Standards

According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

Test standards:

FCC CFR 47 Part 22H (2019)

ANSI C63.26 (2015)

Reference standard:

FCC CFR47 Part 2 (2019)

KDB 971168 D01 Power Meas License Digital Systems v03r01

4. Test Configuration

There is more than one SIM card slot, each one should be applied throughout the compliance test respectively, and however, only the worst case (SIM 1) will be recorded in this report.

Radiated measurements are performed by rotating the EUT in three different orthogonal test planes. EUT stand-up position (Z axis), lie-down position (X, Y axis). Receiver antenna polarization (horizontal and vertical), the worst emission was found in position (X axis, horizontal polarization) and the worst case was recorded.

All mode and data rates and positions and RB size and modulations were investigated. Subsequently, only the worst case emissions are reported.

The following testing in GSM/WCDMA/LTE is set based on the maximum RF Output Power.

Test modes are chosen to be reported as the worst case configuration below:

Test items	Modes/Modulation	
	GSM 850	WCDMA Band V
RF Power Output and Effective Radiated power	GSM GPRS EGPRS	RMC HSDPA/HSUPA DC-HSDPA/HSPA+
Occupied Bandwidth	GSM GPRS(1Tx slot) EGPRS(1Tx slot)	RMC
Band Edge Compliance	GSM GPRS(1Tx slot) EGPRS(1Tx slot)	RMC
Peak-to-Average Power Ratio	GSM GPRS(1Tx slot) EGPRS(1Tx slot)	RMC
Frequency Stability	GSM GPRS(1Tx slot) EGPRS(1Tx slot)	RMC
Spurious Emissions at Antenna Terminals	GSM	RMC
Radiates Spurious Emission	GSM	RMC



Test modes are chosen as the worst case configuration below for LTE Band 5.

Test items	Bandwidth (MHz)				Modulation			RB			Test Channel		
	1.4	3	5	10	QPSK	16QAM	64QAM	1	50%	100%	L	M	H
RF power output and Effective Radiated power	○	○	○	○	○	○	○	○	○	○	○	○	○
Occupied Bandwidth	○	○	○	○	○	○	○	-	-	○	○	○	○
Band Edge Compliance	○	○	○	○	○	○	○	○	-	○	○	-	○
Peak-to-Average Power Ratio	○	○	○	○	○	○	○	-	-	○	○	○	○
Frequency Stability	○	○	○	○	○	○	○	○	○	○	○	○	○
Spurious Emissions at Antenna Terminals	○	○	○	○	○	-	-	○	-	-	○	○	○
Radiates Spurious Emission	○	-	○	○	○	-	-	○	-	-	-	○	-
Note	1. The mark “○” means that this configuration is chosen for testing. 2. The mark “-” means that this configuration is not testing.												

5. Test Case Results

5.1. RF Power Output and Effective Radiated Power

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Methods of Measurement

During the process of the testing, The EUT was connected to the Base Station Simulator with a known loss. The EUT is controlled by the Base Station Simulator test set to ensure max power transmission with proper modulation.


ERP can then be calculated as follows:

$$\text{EIRP (dBm)} = \text{Output Power (dBm)} - \text{Losses (dB)} + \text{Antenna Gain (dBi)}$$

where:dBd refers to gain relative to an ideal dipole.

$$\text{EIRP (dBm)} = \text{ERP (dBm)} + 2.15 \text{ (dB)}.$$

Test Setup



Limits

No specific RF power output requirements in part 2.1046.

Rule Part 22.913(a)(5) specifies that "Mobile/portable stations are limited to 7 watts ERP".

Limit	≤ 7 W (38.45 dBm)
-------	-------------------

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 2$, $U = 0.4$ dB for RF power output, $k = 2$, $U = 1.19$ dB for ERP.



Test Results

GSM 850		Maximum Output Power (dBm)			ERP (dBm)					
					Main Antenna			Diversity Antenna		
		Channel 128	Channel 190	Channel 251	Channel 128	Channel 190	Channel 251	Channel 128	Channel 190	Channel 251
		824.2 (MHz)	836.6 (MHz)	848.8 (MHz)	824.2 (MHz)	836.6 (MHz)	848.8 (MHz)	824.2 (MHz)	836.6 (MHz)	848.8 (MHz)
GSM(GMSK)	Results	33.52	33.33	33.01	26.26	26.07	25.75	27.78	27.59	27.27
GPRS/EGPRS (GMSK)	1TXslot	33.50	33.21	32.93	26.24	25.95	25.67	27.76	27.47	27.19
	2TXslots	30.07	30.12	29.70	22.81	22.86	22.44	24.33	24.38	23.96
	3TXslots	28.21	28.20	27.81	20.95	20.94	20.55	22.47	22.46	22.07
	4TXslots	26.61	26.63	26.29	19.35	19.37	19.03	20.87	20.89	20.55
EGPRS (8PSK)	1TXslot	27.27	27.11	26.72	20.01	19.85	19.46	21.53	21.37	20.98
	2TXslots	24.01	24.19	24.00	16.75	16.93	16.74	18.27	18.45	18.26
	3TXslots	22.47	22.70	22.85	15.21	15.44	15.59	16.73	16.96	17.11
	4TXslots	21.63	21.40	20.76	14.37	14.14	13.50	15.89	15.66	15.02

WCDMA Band V		Maximum Output Power (dBm)			ERP (dBm)					
					Main Antenna			Diversity Antenna		
		Channel 4132	Channel 4183	Channel 4233	Channel 4132	Channel 4183	Channel 4233	Channel 4132	Channel 4183	Channel 4233
		826.4 (MHz)	836.6 (MHz)	846.6 (MHz)	826.4 (MHz)	836.6 (MHz)	846.6 (MHz)	826.4 (MHz)	836.6 (MHz)	846.6 (MHz)
RMC		24.29	24.42	24.27	17.03	17.16	17.01	18.55	18.68	18.53
HSDPA	Sub - Test 1	23.59	23.69	23.50	16.33	16.43	16.24	17.85	17.95	17.76
	Sub - Test 2	23.60	23.67	23.49	16.34	16.41	16.23	17.86	17.93	17.75
	Sub - Test 3	23.06	23.18	22.97	15.80	15.92	15.71	17.32	17.44	17.23
	Sub - Test 4	23.04	23.18	23.00	15.78	15.92	15.74	17.30	17.44	17.26
HSUPA	Sub - Test 1	23.60	23.70	23.54	16.34	16.44	16.28	17.86	17.96	17.80
	Sub - Test 2	21.58	21.72	21.56	14.32	14.46	14.30	15.84	15.98	15.82
	Sub - Test 3	22.60	22.67	22.53	15.34	15.41	15.27	16.86	16.93	16.79
	Sub - Test 4	21.60	21.71	21.55	14.34	14.45	14.29	15.86	15.97	15.81
	Sub - Test 5	23.63	23.69	23.54	16.37	16.43	16.28	17.89	17.95	17.80
DC-HSDPA	Sub - Test 1	23.58	23.66	23.46	16.32	16.40	16.20	17.84	17.92	17.72
	Sub - Test 2	23.14	23.18	23.27	15.88	15.92	16.01	17.40	17.44	17.53
	Sub - Test 3	23.02	23.04	23.09	15.76	15.78	15.83	17.28	17.30	17.35
	Sub - Test 4	22.80	22.88	22.98	15.54	15.62	15.72	17.06	17.14	17.24



HSPA+	16QAM	21.61	21.79	21.91	14.35	14.53	14.65	15.87	16.05	16.17
--------------	-------	-------	-------	-------	-------	-------	-------	-------	-------	-------

LTE Band 5				Maximum Output Power (dBm)			ERP (dBm)					
BW	Modulation	RB size	RB offset	Channel/Frequency(MHz)								
				Main Antenna			Diversity Antenna					
				20407 /824.7	20525 /836.5	20643 /848.3	20407 /824.7	20525 /836.5	20643 /848.3	20407 /824.7	20525 /836.5	20643 /848.3
1.4MHz	QPSK	1	0	24.49	24.39	24.44	17.23	17.13	17.18	18.75	18.65	18.70
		1	2	24.35	24.37	24.28	17.09	17.11	17.02	18.61	18.63	18.54
		1	5	24.27	24.37	24.31	17.01	17.11	17.05	18.53	18.63	18.57
		3	0	24.40	24.45	24.35	17.14	17.19	17.09	18.66	18.71	18.61
		3	2	24.41	24.47	24.36	17.15	17.21	17.10	18.67	18.73	18.62
		3	3	24.40	24.50	24.29	17.14	17.24	17.03	18.66	18.76	18.55
		6	0	23.38	23.58	23.51	16.12	16.32	16.25	17.64	17.84	17.77
	16QAM	1	0	23.17	23.36	23.28	15.91	16.10	16.02	17.43	17.62	17.54
		1	2	23.15	23.33	23.29	15.89	16.07	16.03	17.41	17.59	17.55
		1	5	22.96	23.28	23.15	15.70	16.02	15.89	17.22	17.54	17.41
		3	0	23.08	23.36	23.22	15.82	16.10	15.96	17.34	17.62	17.48
		3	2	23.03	23.34	23.20	15.77	16.08	15.94	17.29	17.60	17.46
		3	3	23.02	23.31	23.21	15.76	16.05	15.95	17.28	17.57	17.47
		6	0	22.16	22.41	22.35	14.90	15.15	15.09	16.42	16.67	16.61
	64QAM	1	0	22.97	23.29	23.23	15.71	16.03	15.97	17.23	17.55	17.49
		1	2	22.96	23.25	23.18	15.70	15.99	15.92	17.22	17.51	17.44
		1	5	23.12	23.46	23.13	15.86	16.20	15.87	17.38	17.72	17.39
		3	0	23.27	23.47	23.29	16.01	16.21	16.03	17.53	17.73	17.55
		3	2	23.34	23.58	23.38	16.08	16.32	16.12	17.60	17.84	17.64
		3	3	23.27	23.45	23.26	16.01	16.19	16.00	17.53	17.71	17.52
		6	0	22.30	22.47	22.36	15.04	15.21	15.10	16.56	16.73	16.62
BW	Modulation	RB size	RB offset	Channel/Frequency(MHz)								
				20415 /825.5	20525 /836.5	20635 /847.5	20415 /825.5	20525 /836.5	20635 /847.5	20415 /825.5	20525 /836.5	20635 /847.5
3MHz	QPSK	1	0	24.48	24.41	24.43	17.22	17.15	17.17	18.74	18.67	18.69
		1	7	24.31	24.36	24.29	17.05	17.10	17.03	18.57	18.62	18.55
		1	14	24.27	24.37	24.31	17.01	17.11	17.05	18.53	18.63	18.57
		8	0	23.47	23.52	23.44	16.21	16.26	16.18	17.73	17.78	17.70
		8	4	23.51	23.53	23.43	16.25	16.27	16.17	17.77	17.79	17.69
		8	7	23.48	23.59	23.35	16.22	16.33	16.09	17.74	17.85	17.61



	16QAM	15	0	23.38	23.61	23.52	16.12	16.35	16.26	17.64	17.87	17.78	
		1	0	23.17	23.34	23.28	15.91	16.08	16.02	17.43	17.60	17.54	
		1	7	23.15	23.31	23.30	15.89	16.05	16.04	17.41	17.57	17.56	
		1	14	22.95	23.30	23.14	15.69	16.04	15.88	17.21	17.56	17.40	
		8	0	22.17	22.45	22.31	14.91	15.19	15.05	16.43	16.71	16.57	
		8	4	22.11	22.42	22.28	14.85	15.16	15.02	16.37	16.68	16.54	
		8	7	22.09	22.38	22.30	14.83	15.12	15.04	16.35	16.64	16.56	
		15	0	22.17	22.41	22.33	14.91	15.15	15.07	16.43	16.67	16.59	
	64QAM	1	0	22.97	23.31	23.23	15.71	16.05	15.97	17.23	17.57	17.49	
		1	7	22.96	23.27	23.17	15.70	16.01	15.91	17.22	17.53	17.43	
		1	14	23.15	23.43	23.12	15.89	16.17	15.86	17.41	17.69	17.38	
		8	0	22.36	22.56	22.42	15.10	15.30	15.16	16.62	16.82	16.68	
		8	4	22.42	22.66	22.46	15.16	15.40	15.20	16.68	16.92	16.72	
		8	7	22.34	22.52	22.35	15.08	15.26	15.09	16.60	16.78	16.61	
		15	0	22.31	22.47	22.34	15.05	15.21	15.08	16.57	16.73	16.60	
BW	Modulation	RB size	RB offset	Channel/Frequency(MHz)									
				20425 /826.5	20525 /836.5	20625 /846.5	20425 /826.5	20525 /836.5	20625 /846.5	20425 /826.5	20525 /836.5	20625 /846.5	
5MHz	QPSK	1	0	24.49	24.38	24.44	17.23	17.12	17.18	18.75	18.64	18.70	
		1	13	24.32	24.40	24.30	17.06	17.14	17.04	18.58	18.66	18.56	
		1	24	24.26	24.36	24.30	17.00	17.10	17.04	18.52	18.62	18.56	
		12	0	23.48	23.53	23.45	16.22	16.27	16.19	17.74	17.79	17.71	
		12	6	23.51	23.53	23.43	16.25	16.27	16.17	17.77	17.79	17.69	
		12	13	23.47	23.60	23.36	16.21	16.34	16.10	17.73	17.86	17.62	
		25	0	23.40	23.59	23.51	16.14	16.33	16.25	17.66	17.85	17.77	
	16QAM	1	0	23.14	23.35	23.28	15.88	16.09	16.02	17.40	17.61	17.54	
		1	13	23.16	23.32	23.31	15.90	16.06	16.05	17.42	17.58	17.57	
		1	24	22.95	23.28	23.14	15.69	16.02	15.88	17.21	17.54	17.40	
		12	0	22.17	22.48	22.32	14.91	15.22	15.06	16.43	16.74	16.58	
		12	6	22.10	22.41	22.27	14.84	15.15	15.01	16.36	16.67	16.53	
		12	13	22.10	22.39	22.31	14.84	15.13	15.05	16.36	16.65	16.57	
	64QAM	25	0	22.17	22.41	22.33	14.91	15.15	15.07	16.43	16.67	16.59	
		1	0	22.94	23.28	23.23	15.68	16.02	15.97	17.20	17.54	17.49	
		1	13	22.97	23.24	23.18	15.71	15.98	15.92	17.23	17.50	17.44	
		1	24	23.15	23.44	23.16	15.89	16.18	15.90	17.41	17.70	17.42	
		12	0	22.38	22.63	22.43	15.12	15.37	15.17	16.64	16.89	16.69	
			12	6	22.42	22.67	22.48	15.16	15.41	15.22	16.68	16.93	16.74



BW	Modulation	RB size	RB offset	Channel/Frequency(MHz)								
				20450	20525	20600	20450	20525	20600	20450	20525	20600
				/829	/836.5	/844	/829	/836.5	/844	/829	/836.5	/844
10MHz	QPSK	12	13	22.35	22.53	22.36	15.09	15.27	15.10	16.61	16.79	16.62
		25	0	22.31	22.47	22.34	15.05	15.21	15.08	16.57	16.73	16.60
		1	0	24.46	24.34	24.41	17.20	17.08	17.15	18.72	18.60	18.67
		1	25	24.31	24.36	24.28	17.05	17.10	17.02	18.57	18.62	18.54
		1	49	24.24	24.35	24.27	16.98	17.09	17.01	18.50	18.61	18.53
		25	0	23.45	23.48	23.41	16.19	16.22	16.15	17.71	17.74	17.67
		25	13	23.49	23.49	23.40	16.23	16.23	16.14	17.75	17.75	17.66
	25	25	23.44	23.55	23.32	16.18	16.29	16.06	17.70	17.81	17.58	
	50	0	23.37	23.54	23.47	16.11	16.28	16.21	17.63	17.80	17.73	
	1	0	23.09	23.31	23.23	15.83	16.05	15.97	17.35	17.57	17.49	
	1	25	23.12	23.30	23.27	15.86	16.04	16.01	17.38	17.56	17.53	
	1	49	22.93	23.25	23.12	15.67	15.99	15.86	17.19	17.51	17.38	
	25	0	22.14	22.44	22.29	14.88	15.18	15.03	16.40	16.70	16.55	
	25	13	22.07	22.39	22.24	14.81	15.13	14.98	16.33	16.65	16.50	
	25	25	22.07	22.34	22.27	14.81	15.08	15.01	16.33	16.60	16.53	
	50	0	22.15	22.37	22.30	14.89	15.11	15.04	16.41	16.63	16.56	
	1	0	22.92	23.24	23.18	15.66	15.98	15.92	17.18	17.50	17.44	
	1	25	22.93	23.22	23.14	15.67	15.96	15.88	17.19	17.48	17.40	
	1	49	23.09	23.38	23.10	15.83	16.12	15.84	17.35	17.64	17.36	
	25	0	22.33	22.55	22.36	15.07	15.29	15.10	16.59	16.81	16.62	
	25	13	22.38	22.63	22.42	15.12	15.37	15.16	16.64	16.89	16.68	
	25	25	22.32	22.48	22.32	15.06	15.22	15.06	16.58	16.74	16.58	
	50	0	22.29	22.43	22.31	15.03	15.17	15.05	16.55	16.69	16.57	

5.2. Occupied Bandwidth

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa


Method of Measurement

The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The occupied bandwidth is measured using spectrum analyzer.

RBW is set to 6.2kHz, VBW is set to 18kHz for GSM 850,
 RBW is set to 51kHz, VBW is set to 160kHz for WCDMA Band V,
 RBW is set to 30 kHz, VBW is set to 91kHz for LTE Band 5 (1.4MHz),
 RBW is set to 62 kHz, VBW is set to 180kHz for LTE Band 5 (3MHz),
 RBW is set to 100 kHz, VBW is set to 300kHz for LTE Band 5 (5MHz),
 RBW is set to 200 kHz, VBW is set to 620kHz for LTE Band 5 (10MHz),

99% power and -26dBc occupied bandwidths are recorded. Spectrum analyzer plots are included on the following pages.

Test Setup



Limits

No specific occupied bandwidth requirements in part 2.1049.

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 2$, $U = 624\text{Hz}$.


Test Result


Mode	Channel	Frequency (MHz)	99% Power Bandwidth (MHz)	-26dBc Bandwidth(MHz)
GSM 850 (GMSK)	128	824.2	0.24055	0.3193
	190	836.6	0.24452	0.3018
	251	848.8	0.24361	0.3112
GPRS 850 (GMSK)	128	824.2	0.24552	0.3089
	190	836.6	0.24119	0.3134
	251	848.8	0.24133	0.3166
EGPRS 850 (8PSK)	128	824.2	0.24437	0.3034
	190	836.6	0.24262	0.3142
	251	848.8	0.23653	0.3021
WCDMA Band V (RMC)	4132	826.4	4.1293	4.700
	4183	836.6	4.1492	4.701
	4233	846.6	4.1423	4.699







LTE Band 5						
RB	Modulation	Bandwidth (MHz)	Channel	Frequency (MHz)	99% Power Bandwidth(MHz)	-26dBc Bandwidth(MHz)
100%	QPSK	1.4	20407	824.7	1.1062	1.232
			20525	836.5	1.0935	1.225
			20643	848.3	1.0888	1.239
		3	20415	825.5	2.7053	2.999
			20525	836.5	2.7090	3.018
			20635	847.5	2.7017	3.013
		5	20425	826.5	4.5159	4.956
			20525	836.5	4.5166	4.930
			20625	846.5	4.5070	4.981
		10	20450	829	8.9840	9.761
			20525	836.5	8.9797	9.707
			20600	844	8.9877	9.707
	16QAM	1.4	20407	824.7	1.0967	1.229
			20525	836.5	1.0951	1.238
			20643	848.3	1.0881	1.221















		3	20415	825.5	2.6924	2.996
			20525	836.5	2.6974	2.968
			20635	847.5	2.7008	3.034
		5	20425	826.5	4.5204	4.943
			20525	836.5	4.5142	4.966
			20625	846.5	4.5189	4.983
		10	20450	829	8.9443	9.756
			20525	836.5	8.9870	9.771
			20600	844	8.9829	9.692
	64QAM	1.4	20407	824.7	1.0909	1.241
			20525	836.5	1.0972	1.245
			20643	848.3	1.0893	1.232
		3	20415	825.5	2.7005	2.991
			20525	836.5	2.6988	2.964
			20635	847.5	2.6963	3.011
		5	20425	826.5	4.5150	4.922
			20525	836.5	4.5444	4.954
			20625	846.5	4.5260	4.934
10	20450	829	8.9583	9.762		
	20525	836.5	9.0065	9.674		
	20600	844	8.9800	9.823		


































5.3. Band Edge Compliance

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The band edge of the lowest and highest channels were measured. The average detector is used.

RBW is set to 6.2kHz,VBW is set to 18kHz for GSM 850,

RBW is set to 51kHz,VBW is set to 160kHz for WCDMA Band V,

RBW is set to 15kHz, VBW is set to 43kHz for LTE Band 5 (1.4MHz),


RBW is set to 30kHz,VBW is set to 91kHz for LTE Band 5 (3MHz),

RBW is set to 51kHz,VBW is set to 150kHz for LTE Band 5 (5MHz),

RBW is set to 100kHz,VBW is set to 300kHz for LTE Band 5 (10MHz),

Spectrum analyzer plots are included on the following pages.

Test Setup



Limits

Rule Part 22.917(a) specifies that “The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log(P) dB.”

Limit	-13 dBm
-------	---------

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 1.96$, $U=0.684$ dB.

Test Result:

GSM 850 CH-Low



GSM 850 CH-High



GSM 850 GPRS CH-Low




GSM 850 GPRS CH-High



GSM 850 EGPRS CH-Low



GSM 850 EGPRS CH-High






WCDMA Band V CH-Low




WCDMA Band V CH-High



LTE Band 5 QPSK 1.4MHz CH-Low 1RB



LTE Band 5 QPSK 1.4MHz CH-High 1RB



LTE Band 5 QPSK 1.4MHz CH-Low 100%RB




LTE Band 5 QPSK 1.4MHz CH-High 100%RB







LTE Band 5 QPSK 3MHz CH-Low 1RB



LTE Band 5 QPSK 3MHz CH-High 1RB




LTE Band 5 QPSK 3MHz CH-Low 100%RB




LTE Band 5 QPSK 3MHz CH-High 100%RB



LTE Band 5 QPSK 5MHz CH-Low 1RB




LTE Band 5 QPSK 5MHz CH-High 1RB






LTE Band 5 QPSK 5MHz CH-Low 100%RB




LTE Band 5 QPSK 5MHz CH-High 100%RB




LTE Band 5 QPSK 10MHz CH-Low 1RB



LTE Band 5 QPSK 10MHz CH-High 1RB



LTE Band 5 QPSK 10MHz CH-Low 100%RB




LTE Band 5 QPSK 10MHz CH-High 100%RB







LTE Band 5 16QAM 1.4MHz CH-Low 1RB



LTE Band 5 16QAM 1.4MHz CH-High 1RB




LTE Band 5 16QAM 1.4MHz CH-Low 100%RB




LTE Band 5 16QAM 1.4MHz CH-High 100%RB



LTE Band 5 16QAM 3MHz CH-Low 1RB




LTE Band 5 16QAM 3MHz CH-High 1RB






LTE Band 5 16QAM 3MHz CH-Low 100%RB




LTE Band 5 16QAM 3MHz CH-High 100%RB




LTE Band 5 16QAM 5MHz CH-Low 1RB



LTE Band 5 16QAM 5MHz CH-High 1RB




LTE Band 5 16QAM 5MHz CH-Low 100%RB




LTE Band 5 16QAM 5MHz CH-High 100%RB




LTE Band 5 16QAM 10MHz CH-Low 1RB



LTE Band 5 16QAM 10MHz CH-High 1RB




LTE Band 5 16QAM 10MHz CH-Low 100%RB




LTE Band 5 16QAM 10MHz CH-High 100%RB



LTE Band 5 64QAM 1.4MHz CH-Low 1RB




LTE Band 5 64QAM 1.4MHz CH-High 1RB






LTE Band 5 64QAM 1.4MHz CH-Low 100%RB




LTE Band 5 64QAM 1.4MHz CH-High 100%RB



LTE Band 5 64QAM 3MHz CH-Low 1RB



LTE Band 5 64QAM 3MHz CH-High 1RB




LTE Band 5 64QAM 3MHz CH-Low 100%RB




LTE Band 5 64QAM 3MHz CH-High 100%RB




LTE Band 5 64QAM 5MHz CH-Low 1RB




LTE Band 5 64QAM 5MHz CH-High 1RB




LTE Band 5 64QAM 5MHz CH-Low 100%RB




LTE Band 5 64QAM 5MHz CH-High 100%RB



LTE Band 5 64QAM 10MHz CH-Low 1RB




LTE Band 5 64QAM 10MHz CH-High 1RB





LTE Band 5 64QAM 10MHz CH-Low 100%RB



LTE Band 5 64QAM 10MHz CH-High 100%RB



5.4. Peak-to-Average Power Ratio (PAPR)

Ambient condition


Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Methods of Measurement

Measure the total peak power and record as P_{Pk} . And measure the total average power and record as P_{Avg} . Both the peak and average power levels must be expressed in the same logarithmic units (e.g., dBm). Determine the PAPR from:

$$PAPR (dB) = P_{Pk} (dBm) - P_{Avg} (dBm).$$

Test Setup



Limits

According to the Sec. 22.913(d), The peak-to-average ratio (PAR) of the transmission must not exceed 13 dB.

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 2$, $U = 0.4$ dB.



Test Results

Mode	Channel	Frequency (MHz)	Peak (dBm)	Avg (dBm)	PAPR (dB)	Limit (dB)	Conclusion
GSM 850 (GMSK)	128	824.2	34.75	33.52	1.23	≤13	PASS
	190	836.6	34.76	33.33	1.43	≤13	PASS
	251	848.8	34.27	33.01	1.26	≤13	PASS
GPRS 850 (GMSK)	128	824.2	34.79	33.50	1.29	≤13	PASS
	190	836.6	34.55	33.21	1.34	≤13	PASS
	251	848.8	34.24	32.93	1.31	≤13	PASS
EGPRS 850 (8PSK)	128	824.2	29.31	27.27	2.04	≤13	PASS
	190	836.6	29.20	27.11	2.09	≤13	PASS
	251	848.8	28.75	26.72	2.03	≤13	PASS
WCDMA Band V (RMC)	4132	826.4	26.74	23.80	2.94	≤13	PASS
	4183	836.6	26.72	23.79	2.93	≤13	PASS
	4233	846.6	26.60	23.71	2.89	≤13	PASS

LTE Band 5								
Modulation	Bandwidth (MHz)	Channel	Frequency (MHz)	Peak (dBm)	Avg (dBm)	PAPR (dB)	Limit (dB)	Conclusion
QPSK	1.4	20407	824.7	28.30	23.56	4.74	≤13	PASS
		20525	836.5	28.03	23.14	4.89	≤13	PASS
		20643	848.3	27.74	23.19	4.55	≤13	PASS
	3	20415	825.5	28.31	23.68	4.63	≤13	PASS
		20525	836.5	28.04	23.27	4.77	≤13	PASS
		20635	847.5	27.71	23.19	4.52	≤13	PASS
	5	20425	826.5	28.37	23.72	4.65	≤13	PASS
		20525	836.5	28.16	23.27	4.89	≤13	PASS
		20625	846.5	27.79	23.20	4.59	≤13	PASS
	10	20450	829	28.41	23.67	4.74	≤13	PASS
		20525	836.5	28.14	23.26	4.88	≤13	PASS
		20600	844	27.88	23.23	4.65	≤13	PASS
16QAM	1.4	20407	824.7	28.22	22.65	5.57	≤13	PASS
		20525	836.5	27.97	22.19	5.78	≤13	PASS
		20643	848.3	27.57	22.13	5.44	≤13	PASS
	3	20415	825.5	28.20	22.68	5.52	≤13	PASS
		20525	836.5	27.97	22.31	5.66	≤13	PASS



	5	20635	847.5	27.59	22.16	5.43	≤13	PASS	
		20425	826.5	28.17	22.68	5.49	≤13	PASS	
		20525	836.5	27.94	22.28	5.66	≤13	PASS	
		20625	846.5	27.58	22.17	5.41	≤13	PASS	
	10	20450	829	28.24	22.68	5.56	≤13	PASS	
		20525	836.5	27.98	22.30	5.68	≤13	PASS	
		20600	844	27.73	22.20	5.53	≤13	PASS	
	64QAM	1.4	20407	824.7	27.95	22.25	5.70	≤13	PASS
			20525	836.5	27.88	22.19	5.69	≤13	PASS
20643			848.3	27.63	22.19	5.44	≤13	PASS	
3		20415	825.5	27.97	22.34	5.63	≤13	PASS	
		20525	836.5	27.89	22.26	5.63	≤13	PASS	
		20635	847.5	27.56	22.20	5.36	≤13	PASS	
5		20425	826.5	27.95	22.35	5.60	≤13	PASS	
		20525	836.5	27.89	22.26	5.63	≤13	PASS	
		20625	846.5	27.54	22.17	5.37	≤13	PASS	
10		20450	829	27.93	22.28	5.65	≤13	PASS	
		20525	836.5	27.93	22.29	5.64	≤13	PASS	
		20600	844	27.70	22.24	5.46	≤13	PASS	

5.5. Frequency Stability

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

Frequency Stability (Temperature Variation)

The temperature inside the climate chamber is varied from -30°C to +50°C in 10°C step size,

(1) With all power removed, the temperature was decreased to 0°C and permitted to stabilize for three hours.

(2) Measure the carrier frequency with the test equipment in a “call mode”. These measurements should be made within 1 minute of powering up the mobile station, to prevent significant self warming.

(3) Repeat the above measurements at 10°C increments from -30°C to +50°C. Allow at least 1.5 hours at each temperature, un-powered, before making measurements.


Frequency Stability (Voltage Variation)

The frequency stability shall be measured with variation of primary supply voltage as follows:

Primary Supply Voltage: The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

This transceiver is specified to operate with an input voltage of between 3.29V and 4.45V, with a nominal voltage of 3.87V.

Test setup



Limits

According to the Sec. 22.355, the frequency stability of the carrier shall be accurate to within 2.5 ppm of the received frequency for mobile stations.

Limits	≤ 2.5 ppm
--------	-----------

Measurement Uncertainty

The assessed measurement uncertainty to ensure 99.75% confidence level for the normal distribution is with the coverage factor $k = 3$, $U = 0.01\text{ppm}$.

Test Result

GSM 850						
Condition		Freq.Error (Hz)	Freq.Error (Hz)	Frequency Stability (ppm)	Frequency Stability (ppm)	Verdict
Temperature	Voltage	GMSK	8PSK	GMSK	8PSK	
Normal (25°C)	Normal	2.72	13.90	0.00145	0.00739	PASS
Extreme (50°C)		3.90	12.45	0.00207	0.00662	PASS
Extreme (40°C)		11.25	11.91	0.00598	0.00633	PASS
Extreme (30°C)		14.41	13.61	0.00766	0.00724	PASS
Extreme (20°C)		8.36	2.25	0.00445	0.00119	PASS
Extreme (10°C)		14.19	7.16	0.00755	0.00381	PASS
Extreme (0°C)		6.43	13.63	0.00342	0.00725	PASS
Extreme (-10°C)		14.79	16.60	0.00787	0.00883	PASS
Extreme (-20°C)		8.44	12.15	0.00449	0.00646	PASS
Extreme (-30°C)		3.99	1.48	0.00212	0.00078	PASS
25°C	LV	5.32	13.70	0.00283	0.00729	PASS
	HV	10.31	14.11	0.00549	0.00750	PASS

WCDMA Band V						
Condition		Freq.Error (Hz)	Freq.Error (Hz)	Frequency Stability (ppm)	Frequency Stability (ppm)	Verdict
Temperature	Voltage	QPSK	BPSK	QPSK	BPSK	
Normal (25°C)	Normal	8.20	3.64	0.00436	0.00194	PASS
Extreme (50°C)		13.83	11.31	0.00736	0.00602	PASS
Extreme (40°C)		15.64	13.86	0.00832	0.00737	PASS
Extreme (30°C)		6.68	16.95	0.00355	0.00902	PASS
Extreme (20°C)		2.19	3.34	0.00117	0.00178	PASS
Extreme (10°C)		9.72	4.72	0.00517	0.00251	PASS
Extreme (0°C)		1.02	3.95	0.00054	0.00210	PASS
Extreme (-10°C)		4.20	7.79	0.00223	0.00414	PASS
Extreme (-20°C)		11.62	1.49	0.00618	0.00079	PASS
Extreme (-30°C)		1.78	11.24	0.00095	0.00598	PASS
25°C	LV	7.85	11.82	0.00418	0.00629	PASS
	HV	9.26	14.33	0.00493	0.00762	PASS



LTE Band 5								
Condition		Freq.Error (Hz)	Freq.Error (Hz)	Freq.Error (Hz)	Frequency Stability (ppm)	Frequency Stability (ppm)	Frequency Stability (ppm)	Verdict
BANDWIDTH	1.4MHz							
Temperature	Voltage	64QAM	16QAM	QPSK	64QAM	16QAM	QPSK	
Normal (25°C)	Normal	12.45	11.78	9.74	0.00662	0.00626	0.00518	PASS
Extreme (50°C)		15.24	13.15	3.37	0.00811	0.00699	0.00179	PASS
Extreme (40°C)		2.32	11.55	17.44	0.00123	0.00615	0.00928	PASS
Extreme (30°C)		17.76	9.90	12.68	0.00945	0.00527	0.00675	PASS
Extreme (20°C)		10.91	14.54	7.61	0.00580	0.00774	0.00405	PASS
Extreme (10°C)		13.38	7.01	5.44	0.00712	0.00373	0.00290	PASS
Extreme (0°C)		11.36	11.93	11.69	0.00604	0.00635	0.00622	PASS
Extreme (-10°C)		11.00	6.70	15.71	0.00585	0.00356	0.00835	PASS
Extreme (-20°C)		15.45	13.18	9.81	0.00822	0.00701	0.00522	PASS
Extreme (-30°C)		10.51	8.86	14.48	0.00559	0.00471	0.00770	PASS
25°C		LV	9.83	4.92	9.82	0.00523	0.00262	0.00522
	HV	10.44	16.02	11.29	0.00555	0.00852	0.00601	PASS
Condition		Freq.Error (Hz)	Freq.Error (Hz)	Freq.Error (Hz)	Frequency Stability (ppm)	Frequency Stability (ppm)	Frequency Stability (ppm)	Verdict
BANDWIDTH	3MHz							
Temperature	Voltage	64QAM	16QAM	QPSK	64QAM	16QAM	QPSK	
Normal (25°C)	Normal	5.74	10.37	17.64	0.00305	0.00552	0.00938	PASS
Extreme (50°C)		2.18	13.90	9.24	0.00116	0.00740	0.00491	PASS
Extreme (40°C)		8.95	13.51	8.33	0.00476	0.00719	0.00443	PASS
Extreme (30°C)		11.09	3.44	16.47	0.00590	0.00183	0.00876	PASS
Extreme (20°C)		9.60	6.60	4.79	0.00511	0.00351	0.00255	PASS
Extreme (10°C)		13.72	12.10	17.21	0.00730	0.00644	0.00915	PASS
Extreme (0°C)		10.63	2.13	9.45	0.00565	0.00113	0.00503	PASS
Extreme (-10°C)		12.21	3.90	3.82	0.00650	0.00207	0.00203	PASS
Extreme (-20°C)		13.52	13.11	7.02	0.00719	0.00698	0.00373	PASS
Extreme (-30°C)		15.63	6.51	5.76	0.00831	0.00346	0.00306	PASS
25°C		LV	16.56	17.28	1.68	0.00881	0.00919	0.00089
	HV	8.25	8.25	2.17	0.00439	0.00439	0.00115	PASS
Condition		Freq.Error (Hz)	Freq.Error (Hz)	Freq.Error (Hz)	Frequency Stability (ppm)	Frequency Stability (ppm)	Frequency Stability (ppm)	Verdict
BANDWIDTH	5MHz							
Temperature	Voltage	64QAM	16QAM	QPSK	64QAM	16QAM	QPSK	
Normal (25°C)	Normal	5.85	8.82	16.84	0.00311	0.00469	0.00896	PASS
Extreme (50°C)		16.03	11.40	2.94	0.00853	0.00606	0.00157	PASS



Extreme (40°C)		8.31	9.49	17.24	0.00442	0.00505	0.00917	PASS
Extreme (30°C)		15.28	13.53	16.30	0.00813	0.00720	0.00867	PASS
Extreme (20°C)		7.83	17.08	1.30	0.00416	0.00909	0.00069	PASS
Extreme (10°C)		2.84	10.32	10.99	0.00151	0.00549	0.00585	PASS
Extreme (0°C)		2.90	14.89	8.97	0.00154	0.00792	0.00477	PASS
Extreme (-10°C)		9.15	14.09	15.38	0.00487	0.00749	0.00818	PASS
Extreme (-20°C)		7.69	9.66	17.60	0.00409	0.00514	0.00936	PASS
Extreme (-30°C)		7.14	9.62	4.80	0.00380	0.00512	0.00255	PASS
25°C	LV	6.87	11.43	16.11	0.00366	0.00608	0.00857	PASS
	HV	13.26	6.87	17.62	0.00706	0.00365	0.00937	PASS
Condition		Freq.Error (Hz)	Freq.Error (Hz)	Freq.Error (Hz)	Frequency Stability (ppm)	Frequency Stability (ppm)	Frequency Stability (ppm)	Verdict
BANDWIDTH	10MHz							
Temperature	Voltage	64QAM	16QAM	QPSK	64QAM	16QAM	QPSK	
Normal (25°C)	Normal	1.23	3.36	9.80	0.00066	0.00179	0.00521	PASS
Extreme (50°C)		6.66	13.21	5.93	0.00354	0.00702	0.00315	PASS
Extreme (40°C)		10.37	2.98	7.81	0.00551	0.00158	0.00416	PASS
Extreme (30°C)		15.02	15.06	7.38	0.00799	0.00801	0.00392	PASS
Extreme (20°C)		8.21	17.02	1.75	0.00436	0.00905	0.00093	PASS
Extreme (10°C)		9.80	17.35	16.66	0.00521	0.00923	0.00886	PASS
Extreme (0°C)		8.44	15.25	16.72	0.00449	0.00811	0.00889	PASS
Extreme (-10°C)		8.49	13.84	12.92	0.00452	0.00736	0.00687	PASS
Extreme (-20°C)		10.77	13.96	2.25	0.00573	0.00742	0.00120	PASS
Extreme (-30°C)		3.63	6.61	12.50	0.00193	0.00352	0.00665	PASS
25°C	LV	3.92	10.20	6.54	0.00209	0.00543	0.00348	PASS
	HV	12.27	1.90	1.68	0.00653	0.00101	0.00089	PASS

5.6. Spurious Emissions at Antenna Terminals

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The measurement is carried out using a spectrum analyzer. The spectrum analyzer scans from 9kHz to the 10th harmonic of the carrier.

The peak detector is used.

RBW is set to 1 kHz (0.009MHz~ 0.15 MHz),

RBW is set to 10 kHz (0.15 MHz~ 30 MHz),


RBW is set to 100 kHz (30MHz~1000 MHz),

RBW is set to 1000 kHz (above 1000MHz),

Sweep is set to ATUO.

The modulation mode and RB allocation refer to section 5.1, using the maximum output power configuration.

Test setup



Limits

Rule Part 22.917(a) specifies that “The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log (P) dB.”

Limit	-13 dBm
-------	---------

**Measurement Uncertainty**

The assessed measurement uncertainty to ensure 99.75% confidence level for the normal distribution is with the coverage factor $k = 1.96$.

Frequency	Uncertainty
9kHz-1GHz	0.684 dB
1GHz-18GHz	1.407 dB



Test Result


Sweep the whole frequency band through the range from 9kHz to the 10th harmonic of the carrier, the emissions more than 20 dB below the limit are not reported.

The signal beyond the limit is carrier.


GSM 850 CH-Low 9kHz ~ 9GHz




GPRS 850 CH-Low 9kHz ~ 9GHz




GSM 850 CH-Middle 9kHz ~ 9GHz




GPRS 850 CH-Middle 9kHz ~ 9GHz



GSM 850 CH-High 9kHz ~ 9GHz




GPRS 850 CH-High 9kHz ~ 9GHz







EGPRS 850 CH-Low 9kHz ~ 9GHz




WCDMA BAND V CH-Low 9kHz ~ 9GHz




EGPRS 850 CH-Middle 9kHz ~ 9GHz




WCDMA BAND V CH-Middle 9kHz ~ 9GHz




EGPRS 850 CH-High 9kHz ~ 9GHz




WCDMA BAND V CH-High 9kHz ~ 9GHz




LTE Band 5 1.4MHz CH-Low 9kHz~10GHz




LTE Band 5 3MHz CH-Low 9kHz~10GHz




LTE Band 5 1.4MHz CH-Middle 9kHz~10GHz




LTE Band 5 3MHz CH-Middle 9kHz~10GHz




LTE Band 5 1.4MHz CH-High 9kHz~10GHz




LTE Band 5 3MHz CH-High 9kHz~10GHz




LTE Band 5 5MHz CH-Low 9kHz~10GHz




LTE Band 5 10MHz CH-Low 9kHz~10GHz




LTE Band 5 5MHz CH-Middle 9kHz~10GHz




LTE Band 5 10MHz CH-Middle 9kHz~10GHz



LTE Band 5 5MHz CH-High 9kHz~10GHz



LTE Band 5 10MHz CH-High 9kHz~10GHz



5.7. Radiates Spurious Emission

Ambient condition

Temperature	Relative humidity	Pressure
23°C ~25°C	45%~50%	101.5kPa

Method of Measurement

1. The testing follows FCC KDB 971168 v03r01 Section 5.8 and ANSI C63.26 (2015).
2. Below 1GHz: The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H). Above 1GHz: (Note: the FCC's permission to use 1.5m as an alternative per TCBC Conf call of Dec. 2, 2014.) The EUT is placed on a turntable 1.5 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).
3. A loop antenna, A log-periodic antenna or horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator and the level will be adjusted till the same power value on the spectrum analyzer or receiver. The level of the spurious emissions can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.
4. The EUT is then put into continuously transmitting mode at its maximum power level during the test. Set Test Receiver or Spectrum RBW=200Hz,VBW=600Hz for 9kHz-150kHz , RBW=10kHz, VBW=30kHz 150kHz-30MHz , RBW=100kHz,VBW=300kHz for 30MHz to 1GHz and RBW=1MHz, VBW=3MHz for above 1GHz, And the maximum value of the receiver should be recorded as (Pr).
5. The EUT shall be replaced by a substitution antenna. In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (PMea) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (Pr). The power of signal source (PMea) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.
6. A amplifier should be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitution Antenna. The cable loss (Pcl) ,the Substitution Antenna Gain (Ga) and the Amplifier Gain (PAg) should be recorded after test.
7. The measurement results are obtained as described below:
$$\text{Power(EIRP)} = \text{PMea} - \text{PAg} - \text{Pcl} + \text{Ga}$$


The measurement results are amend as described below:
$$\text{Power(EIRP)} = \text{PMea} - \text{Pcl} + \text{Ga}$$
8. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi)

and known input power. ERP can be calculated from EIRP by subtracting the gain of the dipole, $ERP = EIRP - 2.15\text{dBi}$.


The modulation mode and RB allocation refer to section 5.1, using the maximum output power configuration.

Test setup


9KHz ~ 30MHz



30MHz ~ 1GHz



Above 1GHz



Note: Area side: 2.4mX3.6m



Limits

Rule Part 22.917(a) specifies that “The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log (P)$ dB.”

Limit	-13 dBm
-------	---------

Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor $k = 1.96$, $U = 3.55$ dB.

**Test Result**

Sweep the whole frequency band through the range from 9kHz to the 10th harmonic of the carrier, the emissions below the noise floor will not be recorded in the report.

After the pretest, main antenna was selected as the worst antenna. only the worst case will be recorded in this report.

GSM 850 CH-Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1673.88	-52.02	2.00	10.75	Horizontal	-45.42	-13.0	32.42	45
3	2509.69	-48.20	2.51	11.05	Horizontal	-41.81	-13.0	28.81	0
4	3346.40	-60.63	4.20	11.15	Horizontal	-55.83	-13.0	42.83	45
5	4183.00	-59.39	5.20	11.15	Horizontal	-55.59	-13.0	42.59	315
6	5019.60	-56.64	5.50	11.95	Horizontal	-52.34	-13.0	39.34	135
7	5856.20	-60.23	5.70	13.55	Horizontal	-54.53	-13.0	41.53	45
8	6692.80	-59.83	6.30	13.75	Horizontal	-54.53	-13.0	41.53	135
9	7529.40	-54.37	6.80	13.85	Horizontal	-49.47	-13.0	36.47	45
10	8366.00	-56.58	6.90	14.25	Horizontal	-51.38	-13.0	38.38	180

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.
2.The worst emission was found in the antenna is Horizontal position.

WCDMA Band V CH-Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1673.20	-69.86	2.00	10.75	Horizontal	-63.26	-13.0	50.26	135
3	2509.80	-64.82	2.51	11.05	Horizontal	-58.43	-13.0	45.43	270
4	3346.40	-63.27	4.20	11.15	Horizontal	-58.47	-13.0	45.47	45
5	4183.00	-60.17	5.20	11.15	Horizontal	-56.37	-13.0	43.37	315
6	5019.60	-56.56	5.50	11.95	Horizontal	-52.26	-13.0	39.26	45
7	5856.20	-59.50	5.70	13.55	Horizontal	-53.80	-13.0	40.80	135
8	6692.80	-59.28	6.30	13.75	Horizontal	-53.98	-13.0	40.98	315
9	7529.40	-54.84	6.80	13.85	Horizontal	-49.94	-13.0	36.94	270
10	8366.00	-55.39	6.90	14.25	Horizontal	-50.19	-13.00	37.19	45

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.
2.The worst emission was found in the antenna is Horizontal position.



LTE Band 5 1.4MHz CH-Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1673.00	-67.57	2.00	10.75	Horizontal	-60.97	-13.0	47.97	45
3	2509.50	-64.42	2.51	11.05	Horizontal	-58.03	-13.00	45.03	135
4	3346.00	-65.16	4.20	11.15	Horizontal	-60.36	-13.00	47.36	45
5	4182.50	-59.42	5.20	11.15	Horizontal	-55.62	-13.00	42.62	180
6	5019.00	-57.28	5.50	11.95	Horizontal	-52.98	-13.00	39.98	225
7	5855.50	-59.42	5.70	13.55	Horizontal	-53.72	-13.00	40.72	315
8	6692.00	-59.34	6.30	13.75	Horizontal	-54.04	-13.00	41.04	0
9	7528.50	-56.30	6.80	13.85	Horizontal	-51.40	-13.00	38.40	45
10	8365.00	-58.04	6.90	14.25	Horizontal	-52.84	-13.00	39.84	180

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2.The worst emission was found in the antenna is Horizontal position.

LTE Band 5 5MHz CH-Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1668.60	-66.66	2.00	10.75	Horizontal	-60.06	-13.00	47.06	225
3	2503.30	-63.30	2.51	11.05	Horizontal	-56.91	-13.00	43.91	225
4	3466.20	-63.33	4.20	11.15	Horizontal	-58.53	-13.0	45.53	45
5	4215.90	-59.84	5.20	11.15	Horizontal	-56.04	-13.0	43.04	90
6	5165.60	-56.18	5.50	11.95	Horizontal	-51.88	-13.0	38.88	135
7	5815.30	-59.32	5.70	13.55	Horizontal	-53.62	-13.0	40.62	90
8	6765.00	-59.31	6.30	13.75	Horizontal	-54.01	-13.0	41.01	315
9	7614.70	-55.82	6.80	13.85	Horizontal	-50.92	-13.0	37.92	900
10	8464.40	-54.60	6.90	14.25	Horizontal	-49.40	-13.0	36.40	45

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2.The worst emission was found in the antenna is Horizontal position.



LTE Band 5 10MHz CH-Middle

Harmonic	Frequency (MHz)	SG (dBm)	Cable Loss (dB)	Gain (dBi)	Antenna Polarization	ERP Level (dBm)	Limit (dBm)	Margin (dB)	Azimuth (deg)
2	1664.40	-66.22	2.00	10.75	Horizontal	-59.62	-13.00	46.62	90
3	2496.60	-62.84	2.51	11.05	Horizontal	-56.45	-13.00	43.45	0
4	3346.00	-64.36	4.20	11.15	Horizontal	-59.56	-13.0	46.56	180
5	4182.50	-60.57	5.20	11.15	Horizontal	-56.77	-13.0	43.77	180
6	5019.00	-56.23	5.50	11.95	Horizontal	-51.93	-13.0	38.93	0
7	5855.50	-59.22	5.70	13.55	Horizontal	-53.52	-13.0	40.52	315
8	6692.00	-59.64	6.30	13.75	Horizontal	-54.34	-13.0	41.34	225
9	7528.50	-54.09	6.80	13.85	Horizontal	-49.19	-13.0	36.19	135
10	8365.00	-55.78	6.90	14.25	Horizontal	-50.58	-13.0	37.58	225

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2.The worst emission was found in the antenna is Horizontal position.



6. Main Test Instruments

Name	Manufacturer	Type	Serial Number	Calibration Date	Expiration Date
Base Station Simulator	R&S	CMW500	113824	2020-05-18	2021-05-17
Power Splitter	Hua Xiang	SHX-GF2-2-13	10120101	/	/
Spectrum Analyzer	Key sight	N9010A	MY50210259	2020-05-18	2021-05-17
Universal Radio Communication Tester	Key sight	E5515C	MY48367192	2020-05-27	2021-05-26
Signal Analyzer	R&S	FSV30	100815	2020-12-13	2021-12-12
Loop Antenna	SCHWARZBECK	FMZB1519	1519-047	2020-04-02	2023-04-01
TRILOG Broadband Antenna	SCHWARZBECK	VULB 9163	391	2019-12-16	2021-12-15
Horn Antenna	R&S	HF907	102723	2018-08-11	2021-08-10
Horn Antenna	ETS-Lindgren	3160-09	00102643	2018-06-20	2021-06-19
Signal generator	R&S	SMB 100A	102594	2020-05-18	2021-05-17
Climatic Chamber	ESPEC	SU-242	93000506	2020-12-13	2021-12-12
Preamplifier	R&S	SCU18	102327	2020-05-18	2021-05-17
MOB COMMS DC SUPPLY	Keysight	66319D	MY43004105	2020-05-18	2021-05-17
RF Cable	Agilent	SMA 15cm	0001	2020-12-10	2021-06-09
Software	R&S	EMC32	9.26.0	/	/

*****END OF REPORT *****



ANNEX A: The EUT Appearance

The EUT Appearance are submitted separately.



ANNEX B: Test Setup Photos

The Test Setup Photos are submitted separately.