







Test Report No.: RF200304W004-7














































Test Report No.: RF200304W004-7











Test Report No.: RF200304W004-7

























### 3.5 CONDUCTED SPURIOUS EMISSIONS


#### 3.5.1 LIMITS OF CONDUCTED SPURIOUS EMISSIONS MEASUREMENT

The power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) by at least  $55 + 10 \log_{10}(P)$  dB. The limit of emission is equal to -25dBm.

#### 3.5.2 TEST PROCEDURE

- a. The EUT makes a phone call to the communication simulator. All measurements were done at low, middle and high operational frequency range.
- b. Measuring frequency range is from 30MHz~26GHz for LTE Band 7 & 30MHz~27GHz for LTE Band 38. 10dB attenuation pad is connected with spectrum. RBW=1MHz and VBW=3MHz are used for conducted emission measurement.

#### 3.5.3 TEST SETUP






BUREAU VERITAS


Test Report No.: RF200304W004-7


### 3.5.4 TEST RESULTS


#### LTE BAND 7

#### 5MHz / QPSK












BUREAU VERITAS


Test Report No.: RF200304W004-7

LTE BAND CA\_7C






Test Report No.: RF200304W004-7







Test Report No.: RF200304W004-7






Test Report No.: RF200304W004-7










Test Report No.: RF200304W004-7











Test Report No.: RF200304W004-7

