



# FCC PART 15C TEST REPORT

**BLUETOOTH LOW ENERGY (BLE) PART**

**No. I19Z62195-IOT03**

**for**

**Xiaomi Communications Co., Ltd.**

**Mobile Phone**

**Model Name: M2001J2G,M2001J1G**

**FCC ID: 2AFZZJAG**

**with**

**Hardware Version: P2.2**

**Software Version: MIUI 11**

**Issued Date: 2020-3-3**

**Note:**

The test results in this test report relate only to the devices specified in this report. This report shall not be reproduced except in full without the written approval of CTTL.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.

**Test Laboratory:**

**CTTL, Telecommunication Technology Labs, CAICT**

No.52, HuayuanNorth Road, Haidian District, Beijing, P. R. China 100191.

Tel:+86(0)10-62304633-2512,Fax:+86(0)10-62304633-2504

Email:[cttl\\_terminals@caict.ac.cn](mailto:cttl_terminals@caict.ac.cn), website: [www.chinattl.com](http://www.chinattl.com)



## **REPORT HISTORY**

<b>Report Number</b>	<b>Revision</b>	<b>Description</b>	<b>Issue Date</b>
I19Z62195-IOT03	Rev.0	1st edition	2020-2-21
I19Z62195-IOT03	Rev.1	1. Update results of Peak Output Power - Conducted. 2. Add Antenna gain in chapter 3.1.	2020-3-3

## **CONTENTS**

<b>1. TEST LABORATORY.....</b>	<b>5</b>
1.1. INTRODUCTION & ACCREDITATION.....	5
1.2. TESTING LOCATION.....	5
1.3. TESTING ENVIRONMENT.....	6
1.4. PROJECT DATA.....	6
1.5. SIGNATURE.....	6
<b>2. CLIENT INFORMATION.....</b>	<b>7</b>
2.1. APPLICANT INFORMATION.....	7
2.2. MANUFACTURER INFORMATION.....	7
<b>3. EQUIPMENT UNDER TEST (EUT) AND ANCILLARY EQUIPMENT (AE).....</b>	<b>8</b>
3.1. ABOUT EUT.....	8
3.2. INTERNAL IDENTIFICATION OF EUT.....	8
3.3. INTERNAL IDENTIFICATION OF AE.....	8
3.4. NORMAL ACCESSORY SETTING.....	9
3.5. GENERAL DESCRIPTION.....	9
<b>4. REFERENCE DOCUMENTS.....</b>	<b>10</b>
4.1. DOCUMENTS SUPPLIED BY APPLICANT.....	10
4.2. REFERENCE DOCUMENTS FOR TESTING.....	10
<b>5. TEST RESULTS.....</b>	<b>11</b>
5.1. SUMMARY OF EUT MODE.....	11
5.2. SUMMARY OF TEST RESULTS.....	11
5.3. STATEMENTS.....	11
<b>6. TEST FACILITIES UTILIZED.....</b>	<b>12</b>
<b>7. MEASUREMENT UNCERTAINTY.....</b>	<b>13</b>
7.1. PEAK OUTPUT POWER - CONDUCTED.....	13
7.2. FREQUENCY BAND EDGES - CONDUCTED.....	13
7.3. FREQUENCY BAND EDGES - RADIATED.....	13
7.4. TRANSMITTER SPURIOUS EMISSION - CONDUCTED.....	13
7.5. TRANSMITTER SPURIOUS EMISSION - RADIATED.....	13
7.6. 6dB BANDWIDTH.....	13
7.7. MAXIMUM POWER SPECTRAL DENSITY LEVEL.....	14
7.8. AC POWERLINE CONDUCTED EMISSION.....	14
<b>ANNEX A: DETAILED TEST RESULTS.....</b>	<b>15</b>
A.1. MEASUREMENT METHOD.....	15
A.2. PEAK OUTPUT POWER - CONDUCTED.....	16
A.3. FREQUENCY BAND EDGES - CONDUCTED.....	18



A.4. FREQUENCY BAND EDGES –RADIATED.....20

A.5. TRANSMITTER SPURIOUS EMISSION - CONDUCTED.....27

A.6. TRANSMITTER SPURIOUS EMISSION - RADIATED..... 36

A.7. 6dB BANDWIDTH..... 47

A.8. MAXIMUM POWER SPECTRAL DENSITY LEVEL..... 50

A.9. AC POWERLINE CONDUCTED EMISSION.....53

**ANNEX B: ACCREDITATION CERTIFICATE.....60**



## **1. Test Laboratory**

### **1.1. Introduction & Accreditation**

Telecommunication Technology Labs, CAICT is an ISO/IEC 17025:2005 accredited test laboratory under NATIONAL VOLUNTARY LABORATORY ACCREDITATION PROGRAM (NVLAP) with lab code 600118-0, and is also an FCC accredited test laboratory (CN5017), and ISED accredited test laboratory (CN0066). The detail accreditation scope can be found on NVLAP website.

### **1.2. Testing Location**

Conducted testing Location: CTTL(huayuan North Road)

Address: No. 52, Huayuan North Road, Haidian District, Beijing,  
P. R. China 100191

Radiated testing Location: CTTL(huayuan North Road)

Address: No. 52, Huayuan North Road, Haidian District, Beijing,  
P. R. China 100191


### 1.3. Testing Environment

Normal Temperature: 15-35℃  
Relative Humidity: 20-75%

### 1.4. Project data

Testing Start Date: 2019-12-18  
Testing End Date: 2020-2-20

### 1.5. Signature



---

**Wu Le**  
**(Prepared this test report)**



---

**Sun Zhenyu**  
**(Reviewed this test report)**



---

**Li Zhuofang**  
**(Approved this test report)**



## **2. Client Information**

### **2.1. Applicant Information**

Company Name: Xiaomi Communications Co., Ltd.  
Address /Post: #019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District,  
Beijing, China, 100085  
City: Beijing  
Postal Code: 100085  
Country: China  
Telephone: 010-60606666-8088  
Fax: 010-60606666-1101

### **2.2. Manufacturer Information**

Company Name: Xiaomi Communications Co., Ltd.  
Address /Post: #019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District,  
Beijing, China, 100085  
City: Beijing  
Postal Code: 100085  
Country: China  
Telephone: 010-60606666-8088  
Fax: 010-60606666-1101

### 3. Equipment Under Test (EUT) and Ancillary Equipment (AE)

#### 3.1. About EUT

Description	Mobile Phone
Model Name	M2001J2G\M2001J1G
FCC ID	2AFZZJAG
Frequency Band	ISM 2400MHz~2483.5MHz
Type of Modulation(LE mode)	GFSK (Bluetooth Low Energy)
Number of Channels(LE mode)	40
Power Supply	3.85V (M2001J2G)\3.87V(M2001J1G)
Antenna 3 gain	-0.90dBi
Antenna 4 gain	-5.70dBi

#### 3.2. Internal Identification of EUT

EUT ID*	SN or IMEI	HW Version	SW Version
EUT3 (M2001J2G)	860211040055024	P2.2	MIUI 11
EUT4 (M2001J2G)	860211040054548	P2.2	MIUI 11
EUT5 (M2001J1G)	861543040045269	P2.2	MIUI 11
EUT2 (M2001J2G)	860211040037477/ 860211040037485	P2.2	MIUI 11

\*EUT ID: is used to identify the test sample in the lab internally.

#### 3.3. Internal Identification of AE

AE ID*	Description	SN	Remarks
AE1	battery	/	/
AE3	Travel charger	/	/
AE6	USB Cable	/	/
AE7	USB Cable	/	/
AE11	battery	/	/
AE13	Travel charger	/	/
AE16	USB Cable	/	/

##### AE1

Model	BM4N
Manufacturer	/
Capacitance	4680 mAh
Nominal voltage	3.85V

##### AE3

Model	MDY-11-EL
Manufacturer	Xiaomi Communications Co., Ltd.
Length of cable	/

**AE6**

Model	L63312
Manufacturer	LUXSHARE Precision Industry Co., Ltd.
Length of cable	/

**AE7**

Model	K63312
Manufacturer	SU ZHOU KELI SCIENCE&TECHNOLOGY DEVELOPMENT CO.,LTD.
Length of cable	/

**AE11**

Model	BM4M
Manufacturer	/
Capacitance	4400 mAh
Nominal voltage	3.87V

**AE13**

Model	MDY-11-EC
Manufacturer	Huizhou BYD Electronic Co.,Ltd.
Length of cable	/

**AE16**

Model	L63512
Manufacturer	LUXSHARE Precision Industry Co., Ltd.
Length of cable	/

\*AE ID: is used to identify the test sample in the lab internally.

### 3.4. Normal Accessory setting

Fully charged battery is used during the test.

### 3.5. General Description

The Equipment Under Test (EUT) is a model of Mobile Phone with integrated antenna. It consists of normal options: lithium battery, charger. Manual and specifications of the EUT were provided to fulfill the test. Samples undergoing test were selected by the Client.

## 4. Reference Documents

### 4.1. Documents supplied by applicant

EUT feature information is supplied by the client or manufacturer, which is the basis of testing.

### 4.2. Reference Documents for testing

The following documents listed in this section are referred for testing.

Reference	Title	Version
FCC Part15	FCC CFR 47, Part 15, Subpart C: 15.205 Restricted bands of operation; 15.209 Radiated emission limits, general requirements;	2018
ANSI C63.10	15.247 Operation within the bands 902–928MHz, 2400–2483.5 MHz, and 5725–5850 MHz. American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices	June,2013

## 5. Test Results

### 5.1. Summary of EUT Mode

Four modes are provided:

Mode	Conditions
Mode A	Antenna3 1Mbps
Mode B	Antenna3 2Mbps
Mode C	Antenna4 1Mbps
Mode D	Antenna4 2Mbps

\*For the test results, the EUT had been tested all conditions. But only the worst case(Mode B) was shown in test report except the " RF output power"test was shown all conditions.

### 5.2. Summary of Test Results

Abbreviations used in this clause:

- P** Pass, The EUT complies with the essential requirements in the standard.
- F** Fail, The EUT does not comply with the essential requirements in the standard
- NA** Not Applicable, The test was not applicable
- NP** Not Performed, The test was not performed by CTTL

SUMMARY OF MEASUREMENT RESULTS	Sub-clause	Verdict
Peak Output Power - Conducted	15.247 (b)(1)	<b>P</b>
Frequency Band Edges- Conducted	15.247 (d)	<b>P</b>
Frequency Band Edges- Radiated	15.247, 15.205, 15.209	<b>P</b>
Transmitter Spurious Emission - Conducted	15.247 (d)	<b>P</b>
Transmitter Spurious Emission - Radiated	15.247, 15.205, 15.209	<b>P</b>
6dB Bandwidth	15.247 (a)(2)	<b>P</b>
Maximum Power Spectral Density Level	15.247(e)	<b>P</b>
AC Powerline Conducted Emission	15.107, 15.207	<b>P</b>

Please refer to **ANNEX A** for detail.

The measurement is made according to ANSI C63.10.

### 5.3. Statements

CTTL has evaluated the test cases requested by the applicant /manufacturer as listed in section 5.1 of this report for the EUT specified in section 3 according to the standards or reference documents listed in section 4.2

The M2001J2G is a new product for this testing. The M2001J1G is a variant product of M2001J2G and shares the M2001J2G results.

## 6. Test Facilities Utilized

### Conducted test system

No.	Equipment	Model	Serial Number	Manufacturer	Calibration Period	Calibration Due date
1	Vector Signal Analyzer	FSQ26	200136	Rohde & Schwarz	1 year	2020-11-29
2	LISN	ENV216	101200	Rohde & Schwarz	1 year	2020-04-27
3	Test Receiver	ESCI	100344	Rohde & Schwarz	1 year	2020-03-14
4	Shielding Room	S81	/	ETS-Lindgren	/	/

### Radiated emission test system

No.	Equipment	Model	Serial Number	Manufacturer	Calibration Period	Calibration Due date
1	Test Receiver	ESU26	100235	R&S	1 year	2021-03-05
2	BiLog Antenna	VULB9163	1222	Schwarzbeck	1 year	2020-03-14
3	Dual-Ridge Waveguide Horn Antenna	3117	00139065	ETS-Lindgren	1 year	2020-11-10
4	Dual-Ridge Waveguide Horn Antenna	3116	2663	ETS-Lindgren	1 year	2020-06-18
5	Vector Signal Analyzer	FSV	101047	Rohde & Schwarz	1 year	2020-05-16

## 7. Measurement Uncertainty

### 7.1. Peak Output Power - Conducted

Measurement Uncertainty:

Measurement Uncertainty (k=2)	0.66dB
-------------------------------	--------

### 7.2. Frequency Band Edges - Conducted

Measurement Uncertainty:

Measurement Uncertainty (k=2)	0.66dB
-------------------------------	--------

### 7.3. Frequency Band Edges - Radiated

Measurement Uncertainty:

Measurement Uncertainty (k=2)	/
-------------------------------	---

### 7.4. Transmitter Spurious Emission - Conducted

Measurement Uncertainty:

Frequency Range	Uncertainty (k=2)
30 MHz ~ 8 GHz	1.22dB
8 GHz ~ 12.75 GHz	1.51dB
12.7GHz ~ 26 GHz	1.51dB

### 7.5. Transmitter Spurious Emission - Radiated

Measurement Uncertainty:

Frequency Range	Uncertainty(dBm) (k=2)
9kHz-30MHz	/
30MHz ≤ f ≤ 1GHz	5.40
1GHz ≤ f ≤ 18GHz	4.32
18GHz ≤ f ≤ 40GHz	5.26

### 7.6. 6dB Bandwidth

Measurement Uncertainty:

Measurement Uncertainty (k=2)	61.936Hz
-------------------------------	----------



### 7.7. Maximum Power Spectral Density Level

**Measurement Uncertainty:**

Measurement Uncertainty (k=2)	0.66dB
-------------------------------	--------

### 7.8. AC Powerline Conducted Emission

**Measurement Uncertainty:**

Measurement Uncertainty (k=2)	3.38dB
-------------------------------	--------

## **ANNEX A: Detailed Test Results**

### **A.1. Measurement Method**

#### **A.1.1. Conducted Measurements**

The measurement is made according to ANSI C63.10.

- 1). Connect the EUT to the test system correctly.
- 2). Set the EUT to the required work mode (Transmitter, receiver or transmitter & receiver).
- 3). Set the EUT to the required channel.
- 4). Set the EUT hopping mode (hopping or hopping off).
- 5). Set the spectrum analyzer to start measurement.
- 6). Record the values. Vector Signal Analyzer



#### **A.1.2. Radiated Emission Measurements**


The measurement is made according to ANSI C63.10.

The radiated emission test is performed in semi-anechoic chamber. The distance from the EUT to the reference point of measurement antenna is 3m. The test is carried out on both vertical and horizontal polarization and only maximization result of both polarizations is kept. During the test, the turntable is rotated 360° and the measurement antenna is moved from 1m to 4m to get the maximization result.

In the case of radiated emission, the used settings are as follows,

Sweep frequency from 30 MHz to 1GHz, RBW = 100 kHz, VBW = 300 kHz;

Sweep frequency from 1 GHz to 26GHz, RBW = 1MHz, VBW = 1MHz;



## A.2. Peak Output Power - Conducted

**Method of Measurement: See ANSI C63.10-clause 11.9.1.1**

- a) Set the RBW = 1 MHz.
- b) Set VBW = 3 MHz.
- c) Set span = 3 MHz.
- d) Sweep time = auto couple.
- e) Detector = peak.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use peak marker function to determine the peak amplitude level.

**Measurement Limit:**

Standard	Limit (dBm)
FCC Part 15.247(b)(3)	< 30

**Measurement Results:**

**Antenna 3**

Sample Rate	Channel No.	Frequency (MHz)	Peak Conducted Output Power (dBm)	Conclusion
1Mbps	0	2402	8.76	P
	19	2440	9.30	P
	39	2480	8.28	P
2Mbps	0	2402	9.18	P
	19	2440	9.50	P
	39	2480	8.87	P

**Conclusion: PASS**

**Antenna 4**

Sample Rate	Channel No.	Frequency (MHz)	Peak Conducted Output Power (dBm)	Conclusion
1Mbps	0	2402	7.47	P
	19	2440	8.35	P
	39	2480	7.65	P
2Mbps	0	2402	7.63	P
	19	2440	8.45	P
	39	2480	7.83	P

**Conclusion: PASS**

The Peak Output Power –Radiated is listed below:

Antenna 3 gain = -0.90 dBi

Antenna 4 gain = -5.70 dBi

**Antenna 3**

Sample Rate	Channel No.	Frequency (MHz)	Peak Output Power –Radiated (dBm)	Conclusion
1Mbps	0	2402	7.86	P
	19	2440	8.40	P
	39	2480	7.38	P
2Mbps	0	2402	8.28	P
	19	2440	8.60	P
	39	2480	7.97	P

Note: These \*values are calculated with the antenna gain.

**Conclusion: PASS**

**Antenna 4**

Sample Rate	Channel No.	Frequency (MHz)	Peak Output Power – Radiated (dBm)	Conclusion
1Mbps	0	2402	1.77	P
	19	2440	2.65	P
	39	2480	1.95	P
2Mbps	0	2402	1.93	P
	19	2440	2.75	P
	39	2480	2.13	P

Note: These \*values are calculated with the antenna gain.

**Conclusion: PASS**

### A.3. Frequency Band Edges - Conducted

**Method of Measurement: See ANSI C63.10-clause 6.10.4**

Connect the spectrum analyzer to the EUT using an appropriate RF cable connected to the EUT output. Configure the spectrum analyzer settings as described below.

- a) Set Span = 8MHz
- b) Sweep Time: Auto
- c) Set the RBW= 100 kHz
- c) Set the VBW= 300 kHz
- d) Detector: Peak
- e) Trace: Max hold

Observe the stored trace and measure the amplitude delta between the peak of the fundamental and the peak of the band-edge emission. This is not an absolute field strength measurement; it is only a relative measurement to determine the amount by which the emission drops at the band edge relative to the highest fundamental emission level.

**Measurement Limit:**

Standard	Limit (dBc)
FCC 47 CFR Part 15.247 (d)	< -20


**Measurement Result:**

**For GFSK**


Channel No.	Frequency (MHz)	Hopping	Band Edge Power ( dBc)		Conclusion
0	2402	Hopping OFF	Fig.1	-48.80	P
39	2480	Hopping OFF	Fig.2	-61.43	P

**Conclusion: PASS**

Test graphs as below



**Fig.1.** Frequency Band Edges: GFSK, 2402 MHz, Hopping Off



**Fig.2.** Frequency Band Edges: GFSK, 2480 MHz, Hopping Off

#### A.4. Frequency Band Edges –Radiated

**Method of Measurement: See ANSI C63.10-2013-clause 6.4 &6.5 & 6.6**

**Measurement Limit:**

Standard	Limit
FCC 47 CFR Part 15.247, 15.205, 15.209	20dB below peak output power

radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

**Limit in restricted band:**

Frequency (MHz)	Field strength( $\mu$ V/m)	Measurement distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30

Frequency of emission (MHz)	Field strength( $\mu$ V/m)	Field strength(dBuV/m)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54

**Set up:**

Tabletop devices shall be placed on a nonconducting platform with nominal top surface dimensions 1 m by 1.5 m and the table height shall be 1.5 m.

The EUT and transmitting antenna shall be centered on the turntable.

**Test Condition**

The EUT shall be tested 1 near top, 1 near middle, and 1 near bottom. Set the unlicensed wireless device to operate in continuous transmit mode. For unlicensed wireless devices unable to be configured for 100% duty cycle even in test mode, configure the system for the maximum duty cycle supported.

When required for unlicensed wireless devices, measurements of the variation of the input power or the radiated signal level of the fundamental frequency component of the emission, as appropriate, shall be performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage.

**Exploratory radiated emissions measurements**

Exploratory radiated measurements shall be performed at the measurement distance or at a closer distance than that specified for compliance to determine the emission characteristics of the EUT and, if applicable, the EUT configuration that produces the maximum level of emissions. The frequencies of maximum emission may be determined by manually positioning the antenna close

to the EUT, and then moving the antenna over all sides of the EUT while observing a spectral display. It is advantageous to have prior knowledge of the frequencies of emissions, although this may be determined from such a near-field scan. The near-field scan shall only be used to determine the frequency but not the amplitude of the emissions. Where exploratory measurements are not adequate to determine the worst-case operating modes and are used only to identify the frequencies of the highest emissions, additional preliminary tests can be required.

For emissions from the EUT, the maximum level shall be determined by rotating the EUT and its antenna through 0° to 360°. For each mode of operation required to be tested, the frequency spectrum (based on findings from exploratory measurements) shall be monitored.

Broadband antennas and a spectrum analyzer or a radio-noise meter with a panoramic display are often useful in this type of test. If either antenna height or EUT azimuth are not fully measured during exploratory testing, then complete testing can be required at the OATS or semi-anechoic chamber when the final full spectrum testing is performed.

#### **Final radiated emissions measurements**

The final measurements are using the orientation and equipment arrangement of the EUT based on the measurement results found during the preliminary (exploratory) measurements, the EUT arrangement, appropriate modulation, and modes of operation that produce the emissions that have the highest amplitude relative to the limit shall be selected for the final measurement.

For emissions from the EUT, the maximum level shall be determined by rotating the EUT and its antenna through 0° to 360°. Final measurements for the EUT require a measurement antenna height scan of 1 m to 4 m and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations. For each mode of operation required to be tested, the frequency spectrum (based on findings from exploratory measurements) shall be monitored.

For each mode selected, record the frequency and amplitude of the highest fundamental emission (if applicable), as well as the frequency and amplitude of the six highest spurious emissions relative to the limit. Emissions more than 20 dB below the limit do not need to be reported.

This maximization process was repeated with the EUT positioned in each of its three orthogonal orientations.

#### **The receiver references:**

Frequency of emission (MHz)	RBW/VBW	Sweep Time(s)
30-1000	100KHz/300KHz	5
1000-4000	1MHz/3MHz	15
4000-18000	1MHz/3MHz	40
18000-26500	1MHz/3MHz	20

EUT ID: EUT1

Measurement Results:

EUT ID: EUT3 ANT3

BLE 4.0

Mode	Channel	Frequency Range	Test Results	Conclusion
GFSK	0	2.38GHz ~2.45GHz	Fig.3	P
	39	2.45GHz ~2.5GHz	Fig.4	P

BLE 5.0

Mode	Channel	Frequency Range	Test Results	Conclusion
GFSK	0	2.38GHz ~2.45GHz	Fig.5	P
	39	2.45GHz ~2.5GHz	Fig.6	P

EUT ID: EUT4 ANT4

BLE 4.0


Mode	Channel	Frequency Range	Test Results	Conclusion
GFSK	0	2.38GHz ~2.45GHz	Fig.7	P
	39	2.45GHz ~2.5GHz	Fig.8	P

BLE 5.0


Mode	Channel	Frequency Range	Test Results	Conclusion
GFSK	0	2.38GHz ~2.45GHz	Fig.9	P
	39	2.45GHz ~2.5GHz	Fig.10	P

Conclusion: PASS


Test graphs as below




**Fig.3. Frequency Band Edges: EUT3 ANT3 BLE 4.0 GFSK, 2402 MHz, Hopping Off, 2.38 GHz – 2.45GHz**




**Fig.4. Frequency Band Edges: EUT3 ANT3 BLE 4.0GFSK, 2480 MHz, Hopping Off , 2.45 GHz - 2.50GHz**




**Fig.5. Frequency Band Edges: EUT3 ANT3 BLE 5.0 GFSK, 2402 MHz, Hopping Off, 2.38 GHz – 2.45GHz**




**Fig.6. Frequency Band Edges: EUT3 ANT3 BLE 5.0 GFSK, 2480 MHz, Hopping Off , 2.45 GHz - 2.50GHz**




**Fig.7. Frequency Band Edges: EUT4 ANT4 BLE 4.0 GFSK, 2402 MHz, Hopping Off, 2.38 GHz – 2.45GHz**



**Fig.8. Frequency Band Edges: EUT4 ANT4 BLE 4.0 GFSK, 2480 MHz, Hopping Off , 2.45 GHz - 2.50GHz**



**Fig.9. Frequency Band Edges: EUT4 ANT4 BLE 5.0 GFSK, 2402 MHz, Hopping Off, 2.38 GHz – 2.45GHz**



**Fig.10. Frequency Band Edges: EUT4 ANT4 BLE 5.0 GFSK, 2480 MHz, Hopping Off , 2.45 GHz - 2.50GHz**

## A.5. Transmitter Spurious Emission - Conducted

**Method of Measurement: See ANSI C63.10-clause 11.11.2 and clause 11.11.3**

### Measurement Procedure – Reference Level

1. Set the RBW = 100 kHz.
2. Set the VBW = 300 kHz.
3. Set the span to  $\geq 1.5$  times the DTS bandwidth.
4. Detector = peak.
5. Sweep time = auto couple.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use the peak marker function to determine the maximum PSD level. Next, determine the power in 100 kHz band segments outside of the authorized frequency band using the following measurement:

### Measurement Procedure - Unwanted Emissions

1. Set RBW = 100 kHz.
  2. Set VBW = 300 kHz.
  3. Set span to encompass the spectrum to be examined.
  4. Detector = peak.
  5. Trace Mode = max hold.
  6. Sweep = auto couple.
  7. Allow the trace to stabilize (this may take some time, depending on the extent of the span).
- Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) is attenuated by at least the minimum requirements specified above.

### Measurement Limit:


Standard	Limit
FCC 47 CFR Part 15.247 (d)	20dB below peak output power in 100 kHz bandwidth

**Measurement Results:  
For GFSK**


Channel No.	Frequency (MHz)	Frequency Range	Test Results	Conclusion
0	2402	Center Frequency	Fig.11	P
		30 MHz ~ 1 GHz	Fig.12	P
		1 GHz ~ 3 GHz	Fig.13	P
		3 GHz ~ 10 GHz	Fig.14	P
		10GHz ~ 26 GHz	Fig.15	P
19	2440	Center Frequency	Fig.16	P
		30 MHz ~ 1 GHz	Fig.17	P
		1 GHz ~ 3 GHz	Fig.18	P
		3 GHz ~ 10 GHz	Fig.19	P
		10GHz ~ 26 GHz	Fig.20	P
39	2480	Center Frequency	Fig.21	P
		30 MHz ~ 1 GHz	Fig.22	P
		1 GHz ~ 3GHz	Fig.23	P
		3 GHz ~ 10 GHz	Fig.24	P
		10 GHz ~ 26 GHz	Fig.25	P

**Conclusion: PASS**


**Test graphs as below**




**Fig.11.** Transmitter Spurious Emission - Conducted: GFSK,2402MHz




**Fig.12.** Transmitter Spurious Emission - Conducted: GFSK, 2402 MHz, 30MHz - 1GHz




**Fig.13.** Transmitter Spurious Emission - Conducted: GFSK, 2402 MHz, 1GHz - 3GHz




**Fig.14.** Transmitter Spurious Emission - Conducted: GFSK, 2402 MHz, 3GHz - 10GHz




**Fig.15.** Transmitter Spurious Emission - Conducted: GFSK, 2402 MHz, 10GHz - 26GHz




**Fig.16.** Transmitter Spurious Emission - Conducted: GFSK, 2440MHz




**Fig.17.** Transmitter Spurious Emission - Conducted: GFSK, 2440 MHz, 30MHz - 1GHz




**Fig.18.** Transmitter Spurious Emission - Conducted: GFSK, 2440 MHz, 1GHz – 3GHz




**Fig.19.** Transmitter Spurious Emission - Conducted: GFSK, 2440 MHz, 3GHz – 10GHz




**Fig.20.** Transmitter Spurious Emission - Conducted: GFSK, 2440 MHz, 10GHz – 26GHz




**Fig.21.** Transmitter Spurious Emission - Conducted: GFSK, 2480 MHz




**Fig.22.** Transmitter Spurious Emission - Conducted: GFSK, 2480 MHz, 30MHz - 1GHz



**Fig.23.** Transmitter Spurious Emission - Conducted: GFSK, 2480 MHz, 1GHz - 3GHz



**Fig.24.** Transmitter Spurious Emission - Conducted: GFSK, 2480 MHz, 3GHz - 10GHz



**Fig.25.** Transmitter Spurious Emission - Conducted: GFSK, 2480 MHz, 10GHz - 26GHz

## A.6. Transmitter Spurious Emission - Radiated

**Method of Measurement:** See ANSI C63.10-2013-clause 6.4 & 6.5 & 6.6

**Measurement Limit:**

Standard	Limit
FCC 47 CFR Part 15.247, 15.205, 15.209	20dB below peak output power

radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

**Limit in restricted band:**


Frequency (MHz)	Field strength( $\mu$ V/m)	Measurement distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30

Frequency of emission (MHz)	Field strength( $\mu$ V/m)	Field strength(dBuV/m)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54

**Set up:**

Tabletop devices shall be placed on a nonconducting platform with nominal top surface dimensions 1 m by 1.5 m. For emissions testing at or below 1 GHz, the table height shall be 80 cm above the reference ground plane. For emission measurements above 1 GHz, the table height shall be 1.5 m

The EUT and transmitting antenna shall be centered on the turntable.



### Test Condition

The EUT shall be tested 1 near top, 1 near middle, and 1 near bottom. Set the unlicensed wireless device to operate in continuous transmit mode. For unlicensed wireless devices unable to be configured for 100% duty cycle even in test mode, configure the system for the maximum duty cycle supported.

When required for unlicensed wireless devices, measurements of the variation of the input power or the radiated signal level of the fundamental frequency component of the emission, as appropriate, shall be performed with the supply voltage varied between 85% and 115% of the

nominal rated supply voltage.

### Exploratory radiated emissions measurements

Exploratory radiated measurements shall be performed at the measurement distance or at a closer distance than that specified for compliance to determine the emission characteristics of the EUT and, if applicable, the EUT configuration that produces the maximum level of emissions. The frequencies of maximum emission may be determined by manually positioning the antenna close to the EUT, and then moving the antenna over all sides of the EUT while observing a spectral display. It is advantageous to have prior knowledge of the frequencies of emissions, although this may be determined from such a near-field scan. The near-field scan shall only be used to determine the frequency but not the amplitude of the emissions. Where exploratory measurements are not adequate to determine the worst-case operating modes and are used only to identify the frequencies of the highest emissions, additional preliminary tests can be required.

For emissions from the EUT, the maximum level shall be determined by rotating the EUT and its antenna through 0° to 360°. For each mode of operation required to be tested, the frequency spectrum (based on findings from exploratory measurements) shall be monitored.

Broadband antennas and a spectrum analyzer or a radio-noise meter with a panoramic display are often useful in this type of test. If either antenna height or EUT azimuth are not fully measured during exploratory testing, then complete testing can be required at the OATS or semi-anechoic chamber when the final full spectrum testing is performed.

### Final radiated emissions measurements

The final measurements are using the orientation and equipment arrangement of the EUT based on the measurement results found during the preliminary (exploratory) measurements, the EUT arrangement, appropriate modulation, and modes of operation that produce the emissions that have the highest amplitude relative to the limit shall be selected for the final measurement.

For each mode of operation required to be tested, the frequency spectrum (based on findings from exploratory measurements) shall be monitored. The highest signal levels relative to the limit shall be determined by rotating the EUT from 0° to 360° and with varying the measurement antenna height between 1 m and 4 m in vertical and horizontal polarizations.

For each mode selected, record the frequency and amplitude of the highest fundamental emission (if applicable), as well as the frequency and amplitude of the six highest spurious emissions relative to the limit. Emissions more than 20 dB below the limit do not need to be reported.

This maximization process was repeated with the EUT positioned in each of its three orthogonal orientations.

#### The receiver references:

Frequency of emission (MHz)	RBW/VBW	Sweep Time(s)
30-1000	100KHz/300KHz	5
1000-4000	1MHz/3MHz	15
4000-18000	1MHz/3MHz	40
18000-26500	1MHz/3MHz	20

$P_{Mea}$  is the field strength recorded from the instrument.

The measurement results are obtained as described below:

Result=  $P_{Mea}$  + Cable Loss + Antenna Factor

Where:

$P_{Mea}$  field strength recorded from the instrument

### Average Measurement results

#### EUT3 ANT3 BLE4.0

##### GFSK 2402MHz

Frequency (MHz)	Meas. Result (dB $\mu$ V/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dB $\mu$ V)	Limit (dB $\mu$ V/m)	Margin (dB)	Antenna Pol. (H/V)
17967.000	34.30	-25.50	43.40	16.40	V	54.00	19.70
17971.500	34.30	-25.50	43.40	16.40	V	54.00	19.70
17976.000	34.30	-25.50	43.40	16.40	H	54.00	19.70
17983.500	34.30	-25.50	43.40	16.40	H	54.00	19.70
17986.500	34.30	-25.50	43.40	16.40	V	54.00	19.70
2389.400	40.10	-14.20	27.20	27.10	H	54.00	13.90

##### GFSK 2440MHz

Frequency (MHz)	Meas. Result (dB $\mu$ V/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dB $\mu$ V)	Limit (dB $\mu$ V/m)	Margin (dB)	Antenna Pol. (H/V)
17959.500	34.30	-25.50	43.40	16.40	V	54.00	19.70
17967.000	34.30	-25.50	43.40	16.40	V	54.00	19.70
17976.000	34.30	-25.50	43.40	16.40	V	54.00	19.70
17985.000	34.30	-25.50	43.40	16.40	V	54.00	19.70
17989.500	34.30	-25.50	43.40	16.40	V	54.00	19.70
17992.500	34.30	-25.50	43.40	16.40	V	54.00	19.70

##### GFSK 2480MHz

Frequency (MHz)	Meas. Result (dB $\mu$ V/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dB $\mu$ V)	Limit (dB $\mu$ V/m)	Margin (dB)	Antenna Pol. (H/V)
17964.000	34.40	-25.50	43.40	16.50	V	54.00	19.60
17977.500	34.40	-25.50	43.40	16.50	H	54.00	19.60
17982.000	34.40	-25.50	43.40	16.50	H	54.00	19.60
17983.500	34.40	-25.50	43.40	16.50	V	54.00	19.60
17953.500	34.30	-25.50	43.40	16.40	V	54.00	19.70
2488.900	39.30	-14.20	27.20	26.30	H	54.00	14.70

**EUT3 ANT3 BLE5.0**
**GFSK 2402MHz**

Frequency (MHz)	Meas. Result (dB $\mu$ V/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dB $\mu$ V)	Limit (dB $\mu$ V/m)	Margin (dB)	Antenna Pol. (H/V)
17979.000	34.40	-25.50	43.40	16.50	H	54.00	19.60
17976.000	34.30	-25.50	43.40	16.40	H	54.00	19.70
17988.000	34.30	-25.50	43.40	16.40	H	54.00	19.70
17950.500	34.20	-25.50	43.40	16.30	V	54.00	19.80
17967.000	34.20	-25.50	43.40	16.30	H	54.00	19.80
2381.500	40.00	-14.20	27.20	27.00	H	54.00	14.00

**GFSK 2440MHz**

Frequency (MHz)	Meas. Result (dB $\mu$ V/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dB $\mu$ V)	Limit (dB $\mu$ V/m)	Margin (dB)	Antenna Pol. (H/V)
17976.000	34.40	-25.50	43.40	16.50	V	54.00	19.60
17991.000	34.40	-25.50	43.40	16.50	V	54.00	19.60
17959.500	34.30	-25.50	43.40	16.40	H	54.00	19.70
17968.500	34.30	-25.50	43.40	16.40	H	54.00	19.70
17988.000	34.30	-25.50	43.40	16.40	V	54.00	19.70
17980.500	34.20	-25.50	43.40	16.30	H	54.00	19.80

**GFSK 2480MHz**

Frequency (MHz)	Meas. Result (dB $\mu$ V/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dB $\mu$ V)	Limit (dB $\mu$ V/m)	Margin (dB)	Antenna Pol. (H/V)
17995.500	34.40	-25.50	43.40	16.50	V	54.00	19.60
17988.000	34.30	-25.50	43.40	16.40	V	54.00	19.70
17997.000	34.30	-25.50	43.40	16.40	V	54.00	19.70
17964.000	34.20	-25.50	43.40	16.30	V	54.00	19.80
17977.500	34.20	-25.50	43.40	16.30	V	54.00	19.80
2498.700	39.20	-13.90	28.40	24.70	H	54.00	14.80

**EUT4 ANT4 BLE4.0**
**GFSK 2402MHz**

Frequency (MHz)	Meas. Result (dB $\mu$ V/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dB $\mu$ V)	Limit (dB $\mu$ V/m)	Margin (dB)	Antenna Pol. (H/V)
17967.000	34.40	-25.50	43.40	16.50	V	54.00	19.60
17979.000	34.30	-25.50	43.40	16.40	H	54.00	19.70
17997.000	34.30	-25.50	43.40	16.40	V	54.00	19.70
17964.000	34.20	-25.50	43.40	16.30	H	54.00	19.80
17970.000	34.20	-25.50	43.40	16.30	V	54.00	19.80
2388.000	40.10	-14.20	27.20	27.10	H	54.00	13.90

**GFSK 2440MHz**

Frequency (MHz)	Meas. Result (dB $\mu$ V/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dB $\mu$ V)	Limit (dB $\mu$ V/m)	Margin (dB)	Antenna Pol. (H/V)
17980.500	34.40	-25.50	43.40	16.50	V	54.00	19.60
17988.000	34.30	-25.50	43.40	16.40	H	54.00	19.70
17991.000	34.30	-25.50	43.40	16.40	V	54.00	19.70
17962.500	34.20	-25.50	43.40	16.30	V	54.00	19.80
17992.500	34.20	-25.50	43.40	16.30	H	54.00	19.80
17994.000	34.20	-25.50	43.40	16.30	V	54.00	19.80

**GFSK 2480MHz**

Frequency (MHz)	Meas. Result (dB $\mu$ V/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dB $\mu$ V)	Limit (dB $\mu$ V/m)	Margin (dB)	Antenna Pol. (H/V)
17973.000	34.30	-25.50	43.40	16.40	V	54.00	19.70
17982.000	34.30	-25.50	43.40	16.40	V	54.00	19.70
17983.500	34.30	-25.50	43.40	16.40	V	54.00	19.70
17994.000	34.30	-25.50	43.40	16.40	V	54.00	19.70
17979.000	34.20	-25.50	43.40	16.30	V	54.00	19.80
2485.800	39.30	-14.20	27.20	26.30	V	54.00	14.70

**EUT4 ANT4 BLE5.0**
**GFSK 2402MHz**

Frequency (MHz)	Meas. Result (dB $\mu$ V/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dB $\mu$ V)	Limit (dB $\mu$ V/m)	Margin (dB)	Antenna Pol. (H/V)
17973.000	34.30	-25.50	43.40	16.40	V	54.00	19.70
17991.000	34.30	-25.50	43.40	16.40	H	54.00	19.70
17961.000	34.20	-25.50	43.40	16.30	V	54.00	19.80
17976.000	34.20	-25.50	43.40	16.30	H	54.00	19.80
17989.500	34.20	-25.50	43.40	16.30	H	54.00	19.80
2349.100	39.80	-14.60	27.20	27.20	H	54.00	14.20

**GFSK 2440MHz**

Frequency (MHz)	Meas. Result (dB $\mu$ V/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dB $\mu$ V)	Limit (dB $\mu$ V/m)	Margin (dB)	Antenna Pol. (H/V)
17985.000	34.30	-25.50	43.40	16.40	V	54.00	19.70
17986.500	34.30	-25.50	43.40	16.40	H	54.00	19.70
17982.000	34.20	-25.50	43.40	16.30	V	54.00	19.80
17988.000	34.20	-25.50	43.40	16.30	V	54.00	19.80
17994.000	34.20	-25.50	43.40	16.30	V	54.00	19.80
17997.000	34.20	-25.50	43.40	16.30	V	54.00	19.80

**GFSK 2480MHz**

Frequency (MHz)	Meas. Result (dB $\mu$ V/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dB $\mu$ V)	Limit (dB $\mu$ V/m)	Margin (dB)	Antenna Pol. (H/V)
17962.500	34.20	-25.50	43.40	16.30	V	54.00	19.80
17973.000	34.20	-25.50	43.40	16.30	V	54.00	19.80
17980.500	34.20	-25.50	43.40	16.30	V	54.00	19.80
17991.000	34.20	-25.50	43.40	16.30	H	54.00	19.80
17913.000	34.10	-25.50	43.40	16.20	V	54.00	19.90
2498.800	39.00	-13.90	28.40	24.50	V	54.00	15.00

**Peak Measurement results**
**EUT3 ANT3 BLE4.0**
**GFSK 2402MHz**

Frequency (MHz)	Meas. Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
17809.500	46.70	-25.50	43.40	28.80	H	74.00	27.30
17953.500	46.20	-25.50	43.40	28.30	H	74.00	27.80
17790.000	46.10	-25.50	43.40	28.20	H	74.00	27.90
17940.000	46.10	-25.50	43.40	28.20	V	74.00	27.90
17955.000	46.10	-25.50	43.40	28.20	H	74.00	27.90
2386.700	53.00	-14.20	27.20	40.00	H	74.00	21.00

**GFSK 2440MHz**

Frequency (MHz)	Meas. Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
17796.000	46.80	-25.50	43.40	28.90	V	74.00	27.20
17890.500	46.60	-25.50	43.40	28.70	V	74.00	27.40
17989.500	46.40	-25.50	43.40	28.50	V	74.00	27.60
17908.500	46.30	-25.50	43.40	28.40	V	74.00	27.70
17995.500	46.30	-25.50	43.40	28.40	V	74.00	27.70
17937.000	46.20	-25.50	43.40	28.30	H	74.00	27.80

**GFSK 2480MHz**

Frequency (MHz)	Meas. Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
17853.000	46.30	-25.50	43.40	28.40	H	74.00	27.70
17911.500	46.00	-25.50	43.40	28.10	V	74.00	28.00
17968.500	46.00	-25.50	43.40	28.10	V	74.00	28.00
17854.500	45.90	-25.50	43.40	28.00	H	74.00	28.10
17890.500	45.90	-25.50	43.40	28.00	H	74.00	28.10
2489.800	52.30	-14.20	27.20	39.30	H	74.00	21.70

**EUT3 ANT3 BLE5.0**
**GFSK 2402MHz**

Frequency (MHz)	Meas. Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
17901.000	46.60	-25.50	43.40	28.70	H	74.00	27.40
17944.500	46.30	-25.50	43.40	28.40	V	74.00	27.70
17941.500	46.10	-25.50	43.40	28.20	V	74.00	27.90
17967.000	46.00	-25.50	43.40	28.10	H	74.00	28.00
17881.500	45.80	-25.50	43.40	27.90	V	74.00	28.20
2383.800	52.40	-14.20	27.20	39.40	H	74.00	21.60

**GFSK 2440MHz**

Frequency (MHz)	Meas. Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
17950.500	46.80	-25.50	43.40	28.90	H	74.00	27.20
17989.500	46.80	-25.50	43.40	28.90	V	74.00	27.20
17968.500	46.10	-25.50	43.40	28.20	H	74.00	27.90
17973.000	46.10	-25.50	43.40	28.20	H	74.00	27.90
17995.500	46.10	-25.50	43.40	28.20	V	74.00	27.90
17772.000	45.90	-25.50	43.40	28.00	V	74.00	28.10

**GFSK 2480MHz**

Frequency (MHz)	Meas. Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
17800.500	47.20	-25.50	43.40	29.30	H	74.00	26.80
17983.500	47.00	-25.50	43.40	29.10	H	74.00	27.00
17908.500	46.40	-25.50	43.40	28.50	H	74.00	27.60
17979.000	46.40	-25.50	43.40	28.50	V	74.00	27.60
17812.500	46.10	-25.50	43.40	28.20	V	74.00	27.90
2485.100	52.40	-14.20	27.20	39.40	V	74.00	21.60

**EUT4 ANT4 BLE4.0**
**GFSK 2402MHz**

Frequency (MHz)	Meas. Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
17893.500	46.80	-25.50	43.40	28.90	V	74.00	27.20
17880.000	46.60	-25.50	43.40	28.70	H	74.00	27.40
17928.000	46.50	-25.50	43.40	28.60	V	74.00	27.50
17946.000	46.50	-25.50	43.40	28.60	V	74.00	27.50
17971.500	46.40	-25.50	43.40	28.50	V	74.00	27.60
2380.200	53.20	-14.20	27.20	40.20	H	74.00	20.80

**GFSK 2440MHz**

Frequency (MHz)	Meas. Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
17959.500	46.40	-25.50	43.40	28.50	H	74.00	27.60
17905.500	46.10	-25.50	43.40	28.20	V	74.00	27.90
17784.000	46.00	-25.50	43.40	28.10	V	74.00	28.00
17995.500	46.00	-25.50	43.40	28.10	H	74.00	28.00
17812.500	45.90	-25.50	43.40	28.00	V	74.00	28.10
17986.500	45.90	-25.50	43.40	28.00	H	74.00	28.10

**GFSK 2480MHz**

Frequency (MHz)	Meas. Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
17979.000	46.90	-25.50	43.40	29.00	V	74.00	27.10
17955.000	46.80	-25.50	43.40	28.90	V	74.00	27.20
17992.500	46.50	-25.50	43.40	28.60	H	74.00	27.50
17995.500	46.40	-25.50	43.40	28.50	V	74.00	27.60
17913.000	46.30	-25.50	43.40	28.40	H	74.00	27.70
2497.700	52.40	-14.20	27.20	39.40	V	74.00	21.60

**EUT4 ANT4 BLE5.0**
**GFSK 2402MHz**

Frequency (MHz)	Meas. Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
17868.000	47.10	-25.50	43.40	29.20	V	74.00	26.90
17952.000	46.90	-25.50	43.40	29.00	V	74.00	27.10
17958.000	46.90	-25.50	43.40	29.00	V	74.00	27.10
17926.500	46.30	-25.50	43.40	28.40	V	74.00	27.70
17980.500	46.30	-25.50	43.40	28.40	H	74.00	27.70
2377.600	52.50	-14.20	27.20	39.50	V	74.00	21.50

**GFSK 2440MHz**

Frequency (MHz)	Meas. Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
17980.500	46.20	-25.50	43.40	28.30	H	74.00	27.80
17824.500	46.00	-25.50	43.40	28.10	V	74.00	28.00
17886.000	45.90	-25.50	43.40	28.00	H	74.00	28.10
17892.000	45.80	-25.50	43.40	27.90	V	74.00	28.20
17958.000	45.80	-25.50	43.40	27.90	H	74.00	28.20
17785.500	45.70	-25.50	43.40	27.80	H	74.00	28.30

**GFSK 2480MHz**

Frequency (MHz)	Meas. Result (dBμV/m)	Cable loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBμV)	Limit (dBμV/m)	Margin (dB)	Antenna Pol. (H/V)
17865.000	46.90	-25.50	43.40	29.00	V	74.00	27.10
17929.500	46.40	-25.50	43.40	28.50	V	74.00	27.60
17971.500	46.10	-25.50	43.40	28.20	H	74.00	27.90
17961.000	46.00	-25.50	43.40	28.10	V	74.00	28.00
17967.000	46.00	-25.50	43.40	28.10	V	74.00	28.00
2496.100	52.10	-14.20	27.20	39.10	H	74.00	21.90

Sample: 17865.000MHz

 Result= P<sub>Mea</sub> + Cable Loss + Antenna Factor

 Result(46.90dBμV/m)= P<sub>Mea</sub>(29.00dBμV/m) + Cable Loss(-25.50dB) + Antenna Factor(43.40dB/m)

**Conclusion: PASS**

## A.7. 6dB Bandwidth

### Method of Measurement:

The measurement is made according to ANSI C63.10 clause 11.8.1

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) = 300 kHz.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

### Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.247(a)(2)	$\geq 500\text{KHz}$


### Measurement Results:

#### For GFSK


Channel No.	Frequency (MHz)	6dB Bandwidth (kHz)		Conclusion
0	2402	Fig.26	1147.50	P
19	2440	Fig.27	1150.00	P
39	2480	Fig.28	1153.00	P

**Conclusion: PASS**


**Test graphs as below:**



**Fig.26.** 6dB Bandwidth: GFSK, 2402 MHz



**Fig.27.** 6dB Bandwidth: GFSK, 2440 MHz



**Fig.28.** 6dB Bandwidth: GFSK, 2480 MHz

## A.8. Maximum Power Spectral Density Level

### Method of Measurement:

The measurement is made according to ANSI C63.10 clause 11.10.2

1. Set the RBW = 3 kHz.
2. Set the VBW = 10 kHz.
3. Set the span to 2 times the DTS bandwidth.
4. Detector = peak.
5. Sweep time = auto couple.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use the peak marker function to determine the maximum amplitude level within the RBW.

### Measurement Limit:


Standard	Limit
FCC 47 CFR Part 15.247(e)	$\leq 8.0\text{dBm}/3\text{kHz}$

### Measurement Results:


#### For GFSK

Channel No.	Frequency (MHz)	Maximum Power Spectral Density Level(dBm/3kHz)		Conclusion
0	2402	Fig.29	-9.05	P
19	2440	Fig.30	-8.90	P
39	2480	Fig.31	-9.10	P


Test graphs as below:



**Fig.29.** Maximum Power Spectral Density Level Function: GFSK, 2402 MHz



**Fig.30.** Maximum Power Spectral Density Level Function: GFSK, 2440 MHz



**Fig.31.** Maximum Power Spectral Density Level Function: GFSK, 2480 MHz


## A.9. AC Powerline Conducted Emission

**Method of Measurement: See ANSI C63.10-clause 6.2**

### Setup:

A stand-alone EUT shall be placed in the center along the back edge of the tabletop. For multiunit tabletop systems, the EUT shall be centered laterally (left to right facing the tabletop) on the tabletop and its rear shall be flush with the rear of the table.

Accessories that are part of an EUT system tested on a tabletop shall be placed in a test arrangement on one or both sides of the host with a 10 cm separation between the nearest points of the cabinets. The rear of the host and accessories shall be flush with the back of the supporting tabletop unless that would not be typical of normal use. If more than two accessories are present, then an equipment test arrangement shall be chosen that maintains 10 cm spacing between cabinets unless the equipment is normally located closer together.



### Exploratory ac power-line conducted emission measurements

Exploratory measurements shall be used to identify the frequency of the emission that has the highest amplitude relative to the limit by operating the EUT in a range of typical modes of operation, cable positions, and with a typical system equipment configuration and arrangement. For each mode of operation and for each ac power current-carrying conductor, cable manipulation shall be performed within the range of likely configurations. For this measurement or series of measurements, the frequency spectrum of interest shall be monitored looking for the emission that has the highest amplitude relative to the limit. Once that emission is found for each current-carrying conductor of each power cord associated with the EUT (but not the cords

associated with non-EUT equipment in the overall system), the one configuration and arrangement and mode of operation that produces the emission closest to the limit over all of the measured conductors shall be recorded.

#### **Final ac power-line conducted emission measurements**

Based on the exploratory tests of the EUT, the one EUT cable configuration and arrangement and mode of operation that produced the emission with the highest amplitude relative to the limit is selected for the final measurement, while applying the appropriate modulating signal to the EUT. If the EUT is relocated from an exploratory test site to a final test site, the highest emissions shall be remaximized at the final test location before final ac power-line conducted emission measurements are performed. The final test on all current-carrying conductors of all of the power cords to the equipment that comprises the EUT (but not the cords associated with other non-EUT equipment in the system) is then performed for the full frequency range for which the EUT is being tested for compliance without further variation of the EUT arrangement, cable positions, or EUT mode of operation. If the EUT is composed of equipment units that have their own separate ac power connections (e.g., floor-standing equipment with independent power cords for each shelf that are able to connect directly to the ac power network), then each current-carrying conductor of one unit is measured while the other units are connected to a second (or more) LISN(s). All units shall be measured separately. If a power strip is provided by the manufacturer, to supply all of the units making up the EUT, only the conductors in the power cord of the power strip shall be measured.

#### **Test Condition:**

<b>Voltage (V)</b>	<b>Frequency (Hz)</b>
120	60

**Measurement Result and limit:**
**EUT3+AE1+AE3+AE6**

Bluetooth (Quasi-peak Limit)

Frequency range (MHz)	Quasi-peak Limit (dB $\mu$ V)	Result (dB $\mu$ V)		Conclusion
		With charger		
		bluetooth	Idle	
0.15 to 0.5	66 to 56	Fig.A.9.1	Fig.A.9.2	<b>P</b>
0.5 to 5	56			
5 to 30	60			

NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

Bluetooth (Average Limit)

Frequency range (MHz)	Average Limit (dB $\mu$ V)	Result (dB $\mu$ V)		Conclusion
		With charger		
		bluetooth	Idle	
0.15 to 0.5	56 to 46	Fig.A.9.1	Fig.A.9.2	<b>P</b>
0.5 to 5	46			
5 to 30	50			

NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

**EUT5+AE11+AE13+AE16**

Bluetooth (Quasi-peak Limit)

Frequency range (MHz)	Quasi-peak Limit (dB $\mu$ V)	Result (dB $\mu$ V)		Conclusion
		With charger		
		bluetooth	Idle	
0.15 to 0.5	67 to 56	Fig.A.9.3	Fig.A.9.4	<b>P</b>
0.5 to 5	56			
5 to 30	60			

NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.


Bluetooth (Average Limit)

Frequency range (MHz)	Average Limit (dB $\mu$ V)	Result (dB $\mu$ V)		Conclusion
		With charger		
		bluetooth	Idle	
0.15 to 0.5	56 to 46	Fig.A.9.3	Fig.A.9.4	<b>P</b>
0.5 to 5	46			
5 to 30	50			

NOTE: The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.5 MHz.

**Conclusion: Pass**

Test graphs as below:



**Fig.A.9.1 AC Powerline Conducted Emission- Bluetooth EUT3(M2001J2G)+AE1+AE3+AE6**


Note: The graphic result above is the maximum of the measurements for both phase line and neutral line.

Measurement Result 1:

Frequency (MHz)	QuasiPeak (dBµV)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.213000	40.3	N	19.9	22.8	63.1
0.258000	36.8	L1	19.8	24.7	61.5
3.322500	28.8	N	19.8	27.2	56.0
3.669000	28.3	N	19.8	27.7	56.0
9.087000	37.9	L1	19.8	22.1	60.0
12.097500	38.6	L1	19.8	21.4	60.0

Measurement Result 2:

Frequency (MHz)	Average (dBµV)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.213000	31.0	L1	19.8	22.1	53.1
0.298500	23.2	N	19.9	27.0	50.3
0.514500	20.1	N	19.9	25.9	46.0
4.758000	23.5	L1	19.8	22.5	46.0
9.199500	32.5	L1	19.8	17.5	50.0
12.088500	33.2	L1	19.8	16.8	50.0



**Fig.A.9.2 AC Powerline Conducted Emission-Idle EUT3(M2001J2G)+AE1+AE3+AE6**


Note: The graphic result above is the maximum of the measurements for both phase line and neutral line.

Measurement Result 1:

Frequency (MHz)	QuasiPeak (dBµV)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.172500	50.1	L1	19.8	14.8	64.8
0.285000	38.5	L1	19.8	22.2	60.7
3.322500	30.8	N	19.8	25.2	56.0
4.614000	31.6	L1	19.8	24.4	56.0
9.019500	40.4	L1	19.8	19.6	60.0
11.710500	40.7	L1	19.8	19.3	60.0

Measurement Result 2:

Frequency (MHz)	Average (dBµV)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.172500	41.2	L1	19.8	13.7	54.8
0.289500	32.3	L1	19.8	18.3	50.5
0.460500	28.0	N	19.9	18.7	46.7
4.996500	24.7	L1	19.8	21.3	46.0
9.276000	34.5	L1	19.8	15.5	50.0
12.381000	34.8	L1	19.9	15.2	50.0



**Fig.A.9.1 AC Powerline Conducted Emission- Bluetooth  
EUT5(M2001J2G)+AE11+AE13+AE16**


Note: The graphic result above is the maximum of the measurements for both phase line and neutral line.

Measurement Result 1:

Frequency (MHz)	QuasiPeak (dBµV)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.411000	32.1	L1	19.8	25.5	57.6
0.469500	32.7	L1	19.8	23.8	56.5
0.910500	32.3	L1	19.8	23.7	56.0
1.761000	28.7	N	19.8	27.3	56.0
2.823000	33.5	L1	19.8	22.5	56.0
4.434000	31.9	L1	19.8	24.1	56.0

Measurement Result 2:

Frequency (MHz)	Average (dBµV)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.406500	19.7	L1	19.8	28.1	47.7
0.433500	20.5	L1	19.8	26.7	47.2
0.780000	19.9	L1	19.8	26.1	46.0
1.689000	23.8	N	19.8	22.2	46.0
2.800500	28.1	L1	19.8	17.9	46.0
3.907500	26.6	L1	19.8	19.4	46.0



**Fig.A.9.2 AC Powerline Conducted Emission-Idle**

**EUT5(M2001J2G)+AE11+AE13+AE16**

Note: The graphic result above is the maximum of the measurements for both phase line and neutral line.

Measurement Result 1:

Frequency (MHz)	QuasiPeak (dBµV)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.375000	31.1	N	19.9	27.3	58.4
0.532500	36.3	L1	19.8	19.7	56.0
0.789000	33.9	N	19.9	22.1	56.0
1.887000	30.9	N	19.8	25.1	56.0
3.295500	36.7	N	19.8	19.3	56.0
3.835500	35.0	L1	19.8	21.0	56.0

Measurement Result 2:

Frequency (MHz)	Average (dBµV)	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.379500	19.3	N	19.9	29.0	48.3
0.514500	29.4	N	19.9	16.6	46.0
0.789000	24.7	N	19.9	21.3	46.0
1.896000	23.9	L1	19.8	22.1	46.0
3.390000	28.3	N	19.8	17.7	46.0
3.835500	28.2	L1	19.8	17.8	46.0

## ANNEX B: Accreditation Certificate

<p>United States Department of Commerce National Institute of Standards and Technology</p> 	
<hr/> <p><b>Certificate of Accreditation to ISO/IEC 17025:2005</b></p> <hr/>	
<p>NVLAP LAB CODE: 600118-0</p>	
<p><b>Telecommunication Technology Labs, CAICT</b> Beijing China</p>	
<p><i>is accredited by the National Voluntary Laboratory Accreditation Program for specific services, listed on the Scope of Accreditation, for:</i></p>	
<p><b>Electromagnetic Compatibility &amp; Telecommunications</b></p>	
<p><i>This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communique dated January 2009).</i></p>	
<hr/> <p>2019-09-26 through 2020-09-30 <i>Effective Dates</i></p>	 <hr/> <p><i>[Signature]</i> For the National Voluntary Laboratory Accreditation Program</p>

\*\*\*END OF REPORT\*\*\*