



FCC Test Report

APPLICANT : Xiaomi Communications Co., Ltd.
EQUIPMENT : Mobile Phone
BRAND NAME : Xiaomi
MODEL NAME : M2102K1G
FCC ID : 2AFZZK1G
STANDARD : 47 CFR Part 15 Subpart B
CLASSIFICATION : Certification

The product was received on Dec. 30, 2020 and testing was completed on Jan. 25, 2021. We, Sporton International (Kunshan) Inc., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI C63.4-2014 and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Kunshan) Inc., the test report shall not be reproduced except in full.

Jason Jia

Reviewed by: Jason Jia / Supervisor

James Huang

Approved by: James Huang / Manager



Sporton International (Kunshan) Inc.

**No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300
People's Republic of China**



TABLE OF CONTENTS

REVISION HISTORY..... 3

SUMMARY OF TEST RESULT 4

1. GENERAL DESCRIPTION 5

 1.1. Applicant..... 5

 1.2. Manufacturer 5

 1.3. Product Feature of Equipment Under Test 5

 1.4. Product Specification of Equipment Under Test 6

 1.5. Modification of EUT 7

 1.6. Test Location 8

 1.7. Test Software 8

 1.8. Applicable Standards 8

2. TEST CONFIGURATION OF EQUIPMENT UNDER TEST 9

 2.1. Test Mode 9

 2.2. Connection Diagram of Test System 11

 2.3. Support Unit used in test configuration and system 12

 2.4. EUT Operation Test Setup 12

3. TEST RESULT 13

 3.1. Test of AC Conducted Emission Measurement 13

 3.2. Test of Radiated Emission Measurement 17

4. LIST OF MEASURING EQUIPMENT 21

5. UNCERTAINTY OF EVALUATION 22

APPENDIX A. SETUP PHOTOGRAPHS



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FC0D3003	Rev. 01	Initial issue of report	Feb. 09, 2021



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.107	AC Conducted Emission	< 15.107 limits	PASS	Under limit 3.57 dB at 0.154 MHz
3.2	15.109	Radiated Emission	< 15.109 limits	PASS	Under limit 6.42 dB at 52.310 MHz

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.



1. General Description

1.1. Applicant

Xiaomi Communications Co., Ltd.

#019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085

1.2. Manufacturer

Xiaomi Communications Co., Ltd.

#019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085

1.3. Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Phone
Brand Name	Xiaomi
Model Name	M2102K1G
FCC ID	2AFZZK1G
EUT supports Radios application	GSM/WCDMA/LTE/5G NR WLAN 2.4GHz 802.11b/g/n HT20/HT40 WLAN 2.4GHz 802.11ax HE20/HE40 WLAN 5GHz 802.11a/n HT20/HT40 WLAN 5GHz 802.11ac VHT20/VHT40/VHT80/VHT160 WLAN 5GHz 802.11ax HE20/HE40/HE80/HE160 WLAN 6GHz 802.11ax HE20/HE40/HE80/HE160 Bluetooth BR / EDR / LE NFC / GNSS / WPT
IMEI Code	Conduction: 861487050010674/861487050010682 Radiation: 861487050012050/861487050012068
HW Version	P2
SW Version	MIUI12
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.



	802.11a/n/ac/ax: 5150 MHz ~ 5250 MHz; 5250 MHz ~ 5350 MHz; 5470 MHz ~ 5730 MHz 5725 MHz ~ 5850 MHz 802.11ax : 5925 MHz ~ 6425 MHz 6425 MHz ~ 6525 MHz 6525 MHz ~ 6875 MHz 6875 MHz ~ 7125 MHz Bluetooth: 2400 MHz ~ 2483.5 MHz NFC : 13.56 MHz GNSS : 1559 MHz ~ 1610 MHz; 1164 MHz ~ 1215 MHz WPT: 110kHz~ 148 kHz
Antenna Type	WWAN : PIFA Antenna WLAN : PIFA Antenna Bluetooth : PIFA Antenna GNSS: PIFA Antenna NFC : planar Antenna WPT : Coil Antenna
Type of Modulation	GSM: GMSK GPRS: GMSK EDGE(MCS 0-4): GMSK / (MCS 5-9): 8PSK WCDMA : BPSK HSDPA/DC-HSDPA : QPSK HSUPA : QPSK HSPA+ : 16QAM (16QAM uplink is not supported) DC-HSDPA : 64QAM LTE: QPSK / 16QAM / 64QAM / 256QAM 5G NR: DFT-s-OFDM (PI/2 BPSK / QPSK / 16QAM / 64QAM / 256QAM) CP-OFDM (QPSK / 16QAM / 64QAM / 256QAM) 802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11a/g/n: OFDM (BPSK / QPSK / 16QAM / 64QAM) 802.11ac: OFDM (BPSK / QPSK / 16QAM / 64QAM /256QAM/) 802.11ax:OFDM (BPSK / QPSK / 16QAM / 64QAM /256QAM/1024QAM) Bluetooth LE : GFSK Bluetooth (1Mbps) : GFSK Bluetooth (2Mbps) : $\pi/4$ -DQPSK Bluetooth (3Mbps) : 8-DPSK GNSS : BPSK NFC: ASK WPT: ASK

1.5. Modification of EUT

No modifications are made to the EUT during all test items.



1.6. Test Location

Sporton International (Kunshan) Inc. is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International (Kunshan) Inc.		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158 FAX : +86-512-57900958		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	CO01-KS 03CH02-KS	CN1257	314309

1.7. Test Software

Item	Site	Manufacturer	Name	Version
1.	03CH02-KS	AUDIX	E3	6.2009-8-24a
2.	CO01-KS	AUDIX	E3	6.2009-8-24

1.8. Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 15 Subpart B
- ANSI C63.4-2014

Remark: All test items were verified and recorded according to the standards and without any deviation during the test.



2. Test Configuration of Equipment Under Test

2.1. Test Mode


The EUT has been associated with peripherals pursuant to ANSI C63.4-2014 and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (30MHz to the 5th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).

Test Items	Function Type
AC Conducted Emission	Mode 1: GSM 850 Rx(Middle) + Bluetooth Idle + WLAN (2.4G) Idle + Camera(Rear) + USB Cable (Charging from Adapter) + Battery + ANT 1 + SIM 1
	Mode 2: WCDMA Band V Rx(High) + Bluetooth Idle + WLAN (5G) Idle + Camera(Front) + USB Cable (Charging from Adapter) + Battery + ANT 4 + SIM 2
	Mode 3: LTE Band 5 Rx(Low) + Bluetooth Idle + WLAN (5G) Idle + MPEG4(Run Color Bar) + USB Cable (Charging from Adapter) + Battery + ANT 1 + SIM 1
	Mode 4: LTE Band 12 Rx(Middle) + Bluetooth Idle + WLAN (2.4G) Idle + NFC On + USB Cable (Charging from Adapter) + Battery + ANT 4 + SIM 2
	Mode 5: LTE Band 17 Rx(Low) + Bluetooth Idle + WLAN (5G) Idle + GNSS Rx + USB Cable (Charging from Adapter) + Battery + ANT 1 + SIM 1
	Mode 6: 5G NR n77 Idle + Bluetooth Idle + WLAN Idle + GNSS Rx + USB Cable (Data Idle with Notebook) + Battery + ANT 8 + SIM 2
	Mode 7: GSM 850 Rx(Middle) + Bluetooth Link + WLAN (2.4G) Idle + WPC(Charge the other phones) + USB Cable (Charging from Adapter) + Battery + ANT 1 + SIM 1
	Mode 8: GSM 850 Rx(Middle) + Bluetooth Link + WLAN (6E) Rx + WPT(Power From Wireless Charger) + USB Cable (Wireless Charger Power from Adapter) + Battery + ANT 1 + SIM 2

Radiated Emissions	<p>Mode 1: GSM 850 Rx(Middle) + Bluetooth Idle + WLAN (2.4G) Idle + Camera(Rear) + USB Cable (Charging from Adapter) + Battery + ANT 1 + SIM 1</p> <p>Mode 2: WCDMA Band V Rx(High) + Bluetooth Idle + WLAN (5G) Idle + Camera(Front) + Earphone + Battery + ANT 4 + SIM 2</p> <p>Mode 3: LTE Band 5 Rx(Low) + Bluetooth Idle + WLAN (5G) Idle + MPEG4(Run Color Bar) + USB Cable (Charging from Adapter) + Battery + ANT 1 + SIM 1</p> <p>Mode 4: LTE Band 12 Rx(Middle) + Bluetooth Idle + WLAN (2.4G) Idle + NFC On + USB Cable (Charging from Adapter) + Battery + ANT 4 + SIM 2</p> <p>Mode 5: LTE Band 17 Rx(Low) + Bluetooth Idle + WLAN (5G) Idle + GNSS Rx + USB Cable (Charging from Adapter) + Battery + ANT 1 + SIM 1</p> <p>Mode 6: 5G NR n77 Idle + Bluetooth Idle + WLAN Idle + GNSS Rx + USB Cable (Data Idle with Notebook) + Battery + ANT 8 + SIM 2</p> <p>Mode 7: GSM 850 Rx(Middle) + Bluetooth Link + WLAN (2.4G) Idle + WPC(Charge the other phones) + USB Cable (Charging from Adapter) + Battery + ANT 1 + SIM 1</p> <p>Mode 8: GSM 850 Rx(Middle) + Bluetooth Link + WLAN (5G) Link + WPT(Power From Wireless Charger) + USB Cable (Wireless Charger Power from Adapter) + Battery + ANT 1 + SIM 2</p>
<p>Remark:</p> <ol style="list-style-type: none"> 1. The worst case of AC is mode 1; only the test data of this mode is reported. 2. The worst case of RE is mode 1; only the test data of this mode is reported. 3. Data Link with Notebook means data application transferred mode between EUT and Notebook. 4. Pre-scanned Low/Middle/High channel for below 1GHz, the worst channel was recorded in this report. 	

2.2.Connection Diagram of Test System



The EUT has been associated with peripherals pursuant to ANSI C63.4-2014 and configuration operated in a manner tended to maximize its emission characteristics in a typical application

2.3. Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	LTE Base Station	Anritsu	MT8821C	N/A	N/A	Unshielded, 1.8m
2.	LTE Base Station	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8m
3.	NR Base Station	Anritsu	MT8000A	N/A	N/A	Unshielded, 1.8m
4.	GNSS Station	R&S	SMBV100A	258305	N/A	N/A
5.	WLAN AP	D-link	DIR-655	KA21R655B1	N/A	Unshielded, 1.8m
6.	WLAN AP	TP-Link	TL-WDR5600	N/A	N/A	Unshielded, 1.8m
7.	Bluetooth Earphone	Xiaomi	LYEJ02LM	N/A	N/A	N/A
8.	Notebook	Lenovo	G480	QDS-BRCM1050I	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
9.	Notebook	Dell	Latitude3440	N/A	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
10.	Hard Disk	Lenovo	F310	DoC	Shielded, 1.2m	N/A
11.	Hard disk	KINGSHARE	KSP6120G	Fcc DoC	Shielded, 1.2m	N/A
12.	SD Card	Kingston	8GB	N/A	N/A	N/A
13.	NFC Card	N/A	N/A	N/A	N/A	N/A
14.	Mobile phone	N/A	N/A	N/A	N/A	N/A
15.	WPC charging	N/A	N/A	N/A	N/A	N/A

2.4. EUT Operation Test Setup

The EUT was in GSM or WCDMA or LTE or 5G NR idle mode during the testing. The EUT was synchronized to the BCCH, and is in continuous receiving mode by setting system simulator's paging reorganization.

At the same time, the EUT was attached to the Bluetooth earphone or WLAN AP, and the following programs installed in the EUT were programmed during the test.

1. Data application is transferred between notebook and EUT via USB cable.
2. Turn on GNSS function to make the EUT receive continuous signals from GNSS station.
3. Turn on camera to capture images.
4. Turn on MPEG4 function.

3. Test Result

3.1. Test of AC Conducted Emission Measurement

3.1.1 Limits of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

<Class B Limit>

Frequency of emission (MHz)	Conducted limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedure

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.


3.1.4 Test Setup





3.1.5 Test Result of AC Conducted Emission

Test Engineer :	Amos Zhang	Temperature :	25.3~26.2°C
		Relative Humidity :	38~40%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		




Site : CO01-KS
 Condition : FCC CLASS-B TWO-LISN-CN02-L LINE

	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
1 *	0.154	62.21	-3.57	65.78	42.10	9.64	10.47	QP
2	0.154	40.41	-15.37	55.78	20.30	9.64	10.47	Average
3	0.162	60.89	-4.45	65.34	40.80	9.64	10.45	QP
4	0.162	40.39	-14.95	55.34	20.30	9.64	10.45	Average
5	0.222	51.19	-11.55	62.74	31.20	9.64	10.35	QP
6	0.222	31.19	-21.55	52.74	11.20	9.64	10.35	Average
7	0.246	49.18	-12.73	61.91	29.20	9.64	10.34	QP
8	0.246	27.18	-24.73	51.91	7.20	9.64	10.34	Average
9	0.320	47.14	-12.57	59.71	27.20	9.64	10.30	QP
10	0.320	26.54	-23.17	49.71	6.60	9.64	10.30	Average
11	0.377	41.52	-16.82	58.34	21.60	9.64	10.28	QP
12	0.377	25.52	-22.82	48.34	5.60	9.64	10.28	Average
13	0.431	41.50	-16.74	57.24	21.59	9.65	10.26	QP
14	0.431	24.50	-22.74	47.24	4.59	9.65	10.26	Average
15	3.642	41.98	-14.02	56.00	21.60	10.13	10.25	QP
16	3.642	37.58	-8.42	46.00	17.20	10.13	10.25	Average



Test Engineer :	Amos Zhang	Temperature :	25.3~26.2°C
		Relative Humidity :	38~40%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		



Site : CO01-KS
 Condition : FCC CLASS-B TWO-LISN-CN02-N NEUTRAL

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1 *	0.155	61.87	-3.87	65.74	41.59	9.81	10.47	QP
2	0.155	39.57	-16.17	55.74	19.29	9.81	10.47	Average
3	0.183	50.46	-13.87	64.33	30.19	9.87	10.40	QP
4	0.183	33.06	-21.27	54.33	12.79	9.87	10.40	Average
5	0.242	51.78	-10.26	62.04	31.60	9.84	10.34	QP
6	0.242	28.78	-23.26	52.04	8.60	9.84	10.34	Average
7	0.313	46.29	-13.59	59.88	26.21	9.78	10.30	QP
8	0.313	26.59	-23.29	49.88	6.51	9.78	10.30	Average
9	0.408	41.22	-16.46	57.68	21.21	9.75	10.26	QP
10	0.408	23.32	-24.36	47.68	3.31	9.75	10.26	Average
11	0.502	37.46	-18.54	56.00	17.49	9.73	10.24	QP
12	0.502	22.26	-23.74	46.00	2.29	9.73	10.24	Average
13	9.204	38.45	-21.55	60.00	17.60	10.52	10.33	QP
14	9.204	34.45	-15.55	50.00	13.60	10.52	10.33	Average

Note:

- Level(dBμV) = Read Level(dBμV) + LISN Factor(dB) + Cable Loss(dB)
- Over Limit(dB) = Level(dBμV) – Limit Line(dBμV)



3.2. Test of Radiated Emission Measurement

3.2.1. Limit of Radiated Emission

The emissions from an unintentional radiator shall not exceed the field strength levels specified in the following table:

<Class B Limit>

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.2.2. Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

3.2.3. Test Procedures


1. The EUT was placed on a turntable with 0.8 meter above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest radiation.
4. The antenna is a Bi-Log antenna and its height is adjusted between one to four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode (RBW=120kHz/VBW=300kHz for frequency below 1GHz; RBW=1MHz VBW=3MHz (Peak), RBW=1MHz/VBW=10Hz (Average) for frequency above 1GHz).
7. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, peak values of EUT will be reported. Otherwise, the emission will be repeated by using the quasi-peak method and reported.
8. Emission level (dBµV/m) = 20 log Emission level (µV/m)
9. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level

3.2.4. Test Setup of Radiated Emission

For radiated emissions from 30MHz to 1GHz




For radiated emissions above 1GHz





3.2.5. Test Result of Radiated Emission

Test Engineer :	Level Zhao	Temperature :	21~22°C
		Relative Humidity :	41~42%
Test Distance :	3m	Polarization :	Horizontal
Remark :	#6 is system simulator signal which can be ignored.		




Site : 03CH02-KS
 Condition : FCC CLASS-B 3m LF 49922 HORIZONTAL

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Cable Factor	Preamp Loss	A/Pos	T/Pos	Remark	
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	30.97	19.59	-20.41	40.00	26.14	24.81	0.84	32.20	---	---	Peak
2	89.17	22.13	-21.37	43.50	37.98	14.77	1.64	32.26	---	---	Peak
3	179.38	20.25	-23.25	43.50	34.77	15.25	2.33	32.10	---	---	Peak
4	206.54	22.20	-21.30	43.50	36.56	15.24	2.51	32.11	---	---	Peak
5	216.24	22.52	-23.48	46.00	36.73	15.36	2.56	32.13	---	---	Peak
6	881.66	34.84			32.73	29.22	5.16	32.27	---	---	Peak
7	950.53	28.27	-17.73	46.00	24.08	31.04	5.35	32.20	100	0	Peak
8	2000.00	39.12	-34.88	74.00	60.22	32.40	7.85	61.35	---	---	Peak
9	5080.00	42.11	-31.89	74.00	55.78	35.58	12.46	61.71	---	---	Peak
10	8712.00	44.79	-29.21	74.00	52.30	38.11	16.70	62.32	---	---	Peak
11	10548.00	46.55	-27.45	74.00	50.79	39.32	18.40	61.96	---	---	Peak
12	12627.00	47.05	-26.95	74.00	48.06	40.35	20.13	61.49	---	---	Peak
13	17118.00	47.43	-26.57	74.00	42.01	43.27	23.70	61.55	---	---	Peak



Test Engineer :	Level Zhao	Temperature :	21~22°C
		Relative Humidity :	41~42%
Test Distance :	3m	Polarization :	Vertical
Remark :	#7 is system simulator signal which can be ignored.		



Site : 03CH02-KS
 Condition : FCC CLASS-B 3m LF 49922 VERTICAL

	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	30.97	29.81	-10.19	40.00	36.36	24.81	0.84	32.20	---	---	Peak
2	52.31	33.58	-6.42	40.00	50.75	13.78	1.25	32.20	100	0	Peak
3	89.17	26.89	-16.61	43.50	42.74	14.77	1.64	32.26	---	---	Peak
4	179.38	26.81	-16.69	43.50	41.33	15.25	2.33	32.10	---	---	Peak
5	210.42	27.99	-15.51	43.50	42.29	15.29	2.53	32.12	---	---	Peak
6	859.35	25.03	-20.97	46.00	23.03	29.27	5.09	32.36	---	---	Peak
7	881.66	33.46			31.35	29.22	5.16	32.27	---	---	Peak
8	2024.00	38.89	-35.11	74.00	59.95	32.44	7.88	61.38	---	---	Peak
9	5448.00	42.44	-31.56	74.00	55.54	35.51	13.03	61.64	---	---	Peak
10	8664.00	45.09	-28.91	74.00	52.82	37.97	16.62	62.32	---	---	Peak
11	10449.00	46.51	-27.49	74.00	50.85	39.31	18.33	61.98	---	---	Peak
12	12537.00	47.27	-26.73	74.00	48.36	40.32	20.07	61.48	---	---	Peak
13	17505.00	47.65	-26.35	74.00	41.27	43.50	24.07	61.19	---	---	Peak

Note:

- Level(dBμV/m) = Read Level(dBμV) + Antenna Factor(dB/m) + Cable Loss(dB) - Preamp Factor(dB)
- Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)



4. List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EMI Test Receiver	R&S	ESR7	101403	9kHz~7GHz;Max 30dBm	Oct. 17, 2020	Jan. 05, 2021	Oct. 16, 2021	Radiation (03CH02-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55370528	10Hz-44G,MAX 30dB	Oct. 17, 2020	Jan. 05, 2021	Oct. 16, 2021	Radiation (03CH02-KS)
Bilog Antenna	TeseQ	CBL6111D	44483	30MHz-1GHz	Dec. 29, 2020	Jan. 05, 2021	Dec. 28, 2021	Radiation (03CH02-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	75957	1GHz~18GHz	Nov. 09, 2020	Jan. 05, 2021	Nov. 08, 2021	Radiation (03CH02-KS)
SHF-EHF Horn	Com-power	AH-840	101115	18GHz~40GHz	Nov. 09, 2020	Jan. 05, 2021	Nov. 08, 2021	Radiation (03CH02-KS)
Amplifier	MITEQ	EM18G40GGA	060728	18~40GHz	Jan. 08, 2020	Jan. 05, 2021	Jan. 07, 2021	Radiation (03CH02-KS)
Amplifier	SONOMA	310N	187289	9KHz-1GHz	Jan. 02, 2021	Jan. 05, 2021	Jan. 01, 2022	Radiation (03CH02-KS)
Amplifier	Keysight	83017A	MY53270316	500MHz~26.5GHz	Oct. 17, 2020	Jan. 05, 2021	Oct. 16, 2021	Radiation (03CH02-KS)
AC Power Source	Chroma	61601	616010002473	N/A	NCR	Jan. 05, 2021	NCR	Radiation (03CH02-KS)
Turn Table	MF	MF7802	N/A	0~360 degree	NCR	Jan. 05, 2021	NCR	Radiation (03CH02-KS)
Antenna Mast	MF	MF7802	N/A	1 m~4 m	NCR	Jan. 05, 2021	NCR	Radiation (03CH02-KS)
EMI Receiver	R&S	ESC17	100768	9kHz~7GHz;	Apr. 14, 2020	Jan. 25, 2021	Apr. 13, 2021	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060103	9kHz~30MHz	Oct. 17, 2020	Jan. 25, 2021	Oct. 16, 2021	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060105	9kHz~30MHz	Oct. 17, 2020	Jan. 25, 2021	Oct. 16, 2021	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP000000811	AC 0V~300V, 45Hz~1000Hz	Oct. 17, 2020	Jan. 25, 2021	Oct. 16, 2021	Conduction (CO01-KS)

NCR: No Calibration Required



5. Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.9dB
---	-------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.9dB
---	-------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.0dB
---	-------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.1dB
---	-------