



BUREAU  
VERITAS

FCC RF Exposure Test Report



Certificate #6613.01

# FCC SAR Exemption Evaluation Report

Report No. : PBJ-QBJ2506090216SA02

Applicant : Xiaomi Communications Co., Ltd.

Address : #019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085

Product : Tablet Keyboard

FCC ID : 2AFZZKB3CG

Brand : REDMI

Model No. : 25097KB3CG

Standards : FCC 47 CFR Part 2 (2.1093)  
KDB 447498 D01 v06

Date of Testing : Jun. 11, 2025 ~ Jun. 26, 2025

Test Lab : The FCC Site Registration No. is 434559; The Designation No. is CN1325.

Issued By : Huarui 7layers High Technology (Suzhou) Co., Ltd.

Address : Tower N, Innovation Center, 88 Zuyi Road, High-tech District, Suzhou City, Anhui Province, China

**CERTIFICATION:** The above equipment have been tested by **HUARUI 7LAYERS HIGH TECHNOLOGY (SUZHOU) CO., LTD.**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's SAR characteristics under the conditions specified in this report. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product certification, approval, or endorsement by A2LA or any government agencies.

Prepared By : Chang Gao Approved By : Sam Feibo  
Chang Gao/ Engineer Peibo Sun/ Manager

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.



## Table of Contents

RELEASE CONTROL RECORD .....	3
1. DESCRIPTION OF EQUIPMENT UNDER TEST .....	4
2. SAR EXEMPTION EVALUATION .....	5
2.1 MAXIMUM TUNE-UP POWER (DECLARED BY MANUFACTURER).....	6
2.2 SAR TEST EXCLUSION THRESHOLDS.....	6
3. INFORMATION ON THE TESTING LABORATORIES.....	7





## 1. Description of Equipment Under Test

<b>EUT Type*</b>	Tablet Keyboard
<b>Brand Name*</b>	REDMI
<b>Model Name*</b>	25097KB3CG
<b>Tx Frequency Bands (Unit: MHz)</b>	BT-LE: 2402 ~ 2480
<b>Uplink Modulations</b>	BT-LE: GFSK
<b>Maximum Tune-up Conducted Power (Unit: dBm)</b>	BT-LE: 3dBm
<b>Antenna Type*</b>	PCB Antenna
<b>HW VERSION*</b>	V0.20
<b>SW VERSION*</b>	1
<b>EUT Stage*</b>	Identical Prototype

**NOTE:**

- \*Since the above data and/or information is provided by the client relevant results or conclusions of this report are only made for these data and/or information , Test Lab is not responsible for the authenticity, integrity and results of the data and information and/or the validity of the conclusion.
- The above EUT information is declared by manufacturer and for more detailed features description please refers to the manufacturer's specifications or User's Manual.



## 2. SAR Exemption Evaluation

### Following FCC KDB 447498 D01 “General SAR test exclusion guidance”

The corresponding SAR Exclusion Threshold condition, listed below:

- 1) The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:  
[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]  $\cdot [\sqrt{f_{\text{GHz}}}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where
  - $f_{\text{GHz}}$  is the RF channel transmit frequency in GHz
  - Power and distance are rounded to the nearest mW and mm before calculation
  - The result is rounded to one decimal place for comparisonThe test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.
- 2) At 100 MHz to 6 GHz and for test separation distances  $> 50$  mm, the SAR test exclusion threshold is determined according to the following:
  - a) [Threshold at 50 mm in step 1) + (test separation distance - 50 mm)  $\cdot (f_{\text{MHz}}/150)$ ] mW, at 100MHz to 1500 MHz
  - b) [Threshold at 50 mm in step 1) + (test separation distance - 50 mm)  $\cdot 10$ ] mW at  $> 1500$  MHz and  $\leq 6$  GHz
- 3) At frequencies below 100 MHz, the following may be considered for SAR test exclusion.
  - a) The threshold at the corresponding test separation distance at 100 MHz in step 2) is multiplied by  $[1 + \log(100/f_{\text{MHz}})]$  for test separation distances  $> 50$  mm and  $< 200$  mm.
  - b) The threshold determined by the equation in a) for 50 mm and 100 MHz is multiplied by  $\frac{1}{2}$  for test separation distances  $\leq 50$  mm.
  - c) SAR measurement procedures are not established below 100 MHz. When SAR test exclusion cannot be applied, a KDB inquiry is required to determine SAR evaluation requirements for any test results to be acceptable.

### Smallest distance from the antenna and radiating structures or outer surface of the device

The minimum test separation distance is determined by the smallest distance from the antenna and radiating structures or outer surface of the device, according to the host form factor, exposure conditions and platform requirements, to any part of the body or extremity of a user or bystander.



**2.1 Maximum Tune-up Power (declared by manufacturer)**

Mode	Tune-up Power
Bluetooth LE	3dBm

**2.2 SAR Test Exclusion Thresholds**

Mode	Frequency (MHz)	Max. Tune-up Power (dBm)	Minimum separation distance (mm)	Calculated Result	Limit for 1-g SAR	Limit for 10-g extremity SAR	Verdict
Bluetooth LE	2480	3	0	0.63	<b>3.0</b>	7.5	Exempt from SAR

**Conclusion**

According to the table above, the device can meet the SAR test exclusion thresholds requirement of FCC KDB 447498 D01, and SAR evaluation is not required.

Therefore, this device complies with FCC's RF radiation exposure limits for general population without SAR evaluation.



BUREAU  
VERITAS



### **3. Information on the Testing Laboratories**

We, Huarui 7layers High Technology (Suzhou) Co., Ltd. ,were founded in 2020 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

Huarui 7Layers High Technology (Suzhou) Co., Ltd.

Lab Address:

Tower N, Innovation Center, 88 Zuyi Road, High-tech District, Suzhou City, Anhui Province, China

Accredited Test Lab Cert 6613.01

If you have any comments, please feel free to contact us at the following:

Suzhou EMC/RF Lab:

Tel: +86 (0557) 368 1008

---END--