



Test report No:
2560810R.701B

FCC TEST REPORT

Product Name	Xiaomi Stylus
Trademark	Xiaomi
Model and /or type reference	2508DMP70G
FCC ID	2AFZZMP70G
Applicant's name / address	Xiaomi Communications Co., Ltd. #019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085
Test method requested, standard	47 CFR FCC Part 15 (Section 15.247) ANSI C63.10: 2020
Verdict Summary	IN COMPLIANCE
Documented by (name / position & signature)	Jun Xu/ Project Engineer 
Approved by (name / position & signature)	Frank He/Technical Manager 
Date of issue	2025-08-27
Report Version	V1.0
Report template No	Template_FCC Part 15C-RF-V1.0

INDEX

	page
General conditions	4
Environmental conditions	4
Possible test case verdicts	4
Abbreviations.....	5
Document History.....	6
Remarks and Comments	6
Used Equipment.....	7
Uncertainty	9
1 General Information	10
1.1 General Description of the Item(s).....	10
1.2 Channel List.....	11
2 Description of Test Setup.....	12
3 Verdict summary section.....	13
3.1 Standards	13
3.2 Deviation(s) from the Standard(s) / Test Specification(s).....	13
3.3 Overview of results	14
3.4 Power setting in test	15
3.5 Test Facility.....	16
4 Test Items Of Limit/Setup/Procedure.....	17
4.1 DTS Bandwidth.....	17
4.1.1 Limit	17
4.1.2 Test Setup	17
4.1.3 Test Procedure	17
4.2 Occupied Channel Bandwidth	18
4.2.1 Limit	18
4.2.2 Test Setup	18
4.2.3 Test Procedure	18
4.3 Maximum Conducted Output Power.....	19
4.3.1 Limit	19
4.3.2 Test Setup	19
4.3.3 Test Procedure	20
4.4 Maximum Power Spectral Density.....	21
4.4.1 Limit	21
4.4.2 Test Setup	21

4.4.3	Test Procedure	21
4.5	Band Edge Measurements	22
4.5.1	Limit	22
4.5.2	Test Setup	22
4.5.3	Test Procedure	22
4.6	Conducted Spurious Emission	23
4.6.1	Limit	23
4.6.2	Test Setup	23
4.6.3	Test Procedure	23
4.7	Duty cycle	24
4.7.1	Limit	24
4.7.2	Test Setup	24
4.7.3	Test Procedure	24
4.8	Emissions in Restricted Bands	25
4.8.1	Limit	25
4.8.2	Test Setup	27
4.8.3	Test Procedure	28
4.9	AC Power Line Conducted Emission.....	29
4.9.1	Limit	29
4.9.2	Test Setup	29
4.9.3	Test Procedure	29
4.10	Antenna Requirement.....	30
4.10.1	Limit:	30
4.10.2	Antenna Connector Construction:	30
5	Test setup photo and EUT Photo	30
6	Test Result.....	31
	Appendix A: DTS Bandwidth.....	31
	Appendix B: Maximum conducted output power	34
	Appendix C: Maximum power spectral density.....	35
	Appendix D: Band edge measurements	38
	Appendix E: Conducted Spurious Emission	54
	Appendix F: Duty Cycle	65
	Appendix G: Emissions in Restricted Bands	68

COMPETENCES AND GUARANTEES

DEKRA is a testing laboratory competent to carry out the tests described in this report.

In order to assure the traceability to other national and international laboratories, DEKRA has a calibration and maintenance program for its measurement equipment.

DEKRA guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated in the report and it is based on the knowledge and technical facilities available at DEKRA at the time of performance of the test.

DEKRA is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Test Report apply only to the particular item under test established in this document.

IMPORTANT: No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA.

GENERAL CONDITIONS

Test Location	No. 99, Hongye Road, Suzhou Industrial Park Suzhou, 215006, P.R. China
Date(receive sample)	Jul. 18, 2025
Date (start test)	Jul. 25, 2025
Date (finish test)	Jul. 30, 2025

1. This report is only referred to the item that has undergone the test.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or Competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of DEKRA.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of DEKRA.

ENVIRONMENTAL CONDITIONS

The climatic conditions during the tests are within the limits specified by the manufacturer for the operation of the EUT and the test equipment. The climatic conditions during the tests were within the following limits:

Ambient temperature	15 °C – 35 °C
Relative Humidity air	30% - 60%

If explicitly required in the basic standard or applied product / product family standard the climatic values are recorded and documented separately in this test report.

POSSIBLE TEST CASE VERDICTS

Test case does not apply to test object	N/A
Test object does meet requirement	P (Pass) / PASS
Test object does not meet requirement	F (Fail) / FAIL
Not measured	N/M

ABBREVIATIONS

For the purposes of the present document, the following abbreviations apply:

EUT	: Equipment Under Test
QP	: Quasi-Peak
CAV	: CISPR Average
AV	: Average
CDN	: Coupling Decoupling Network
SAC	: Semi-Anechoic Chamber
OATS	: Open Area Test Site
BW	: Bandwidth
AM	: Amplitude Modulation
PM	: Pulse Modulation
HCP	: Horizontal Coupling Plane
VCP	: Vertical Coupling Plane
U_N	: Nominal voltage
T_x	: Transmitter
R_x	: Receiver
N/A	: Not Applicable
N/M	: Not Measured

DOCUMENT HISTORY

Report No.	Version	Description	Issued Date
2560810R.701B	V1.0	Initial issue of report.	2025-08-27

REMARKS AND COMMENTS

1. The equipment under test (EUT) does meet the essential requirements of the stated standard(s)/test(s).
2. These test results on a sample of the device are for the purpose of demonstrating Compliance with 47 CFR FCC Part 15 (Section 15.247).
3. The measurement result is considered in conformance with the requirement if it is within the prescribed limit, It is not necessary to account the uncertainty associated with the measurement result.
4. The test results presented in this report relate only to the object tested.
5. The test report shall not be reproduced without the written approval of DEKRA Testing and Certification (Suzhou) Co., Ltd.
6. This report will not be used for social proof function in China market.
7. DEKRA declines any responsibility with the following test data provided by customer that may affect the validity of result:
 - Chapter 1.1 General Description of the Item(s);
 - Chapter 1.2 Channel List.

USED EQUIPMENT

Conducted Test/ TR8

Instrument	Manufacturer	Model No.	Serial No.	Cal. Date	Next Cal. Date	Firmware Versiom	Software version
Wireless Connectivity Tester	R&S	CMW 270	102593	2025.05.10	2026.05.09	V 4.0.60	N/A
Coaxial Cable	N/A	N/A	2477	2025.06.10	2026.06.09	N/A	N/A
Coaxial Cable	N/A	N/A	2478	2025.06.10	2026.06.09	N/A	N/A
High and low temperature and fast temperature change test box	ASTUOD	ASTD-FBT-225K	N/A	2025.03.16	2026.03.15	N/A	N/A
Temperature/Humidity Meter	RTS	RTS-8S	RF07	2025.06.17	2026.06.16	N/A	N/A
Test system							
Instrument	Manufacturer	Model No.	Serial No.	Cal. Date	Next Cal. Date	Firmware Versiom	Software version
MAX Signal Analyzer	Keysight	N9010A	MY48030494	2024.10.26	2025.10.25	A.14.03	N/A
RF Control Unit	Tonscend	JS0806-2	22G8060594	2025.01.26	2026.01.25	N/A	N/A
MXG-B RF Vector Signal Generator	Keysight	N5182B	MY61252529	2025.03.23	2026.03.22	B.01.96	N/A
Frequency extender for EXG or MXG	Keysight	N5182BX07	MY59362500	2025.03.23	2026.03.22	N/A	N/A
EXG-B MW Analog Signal Generator	Keysight	N5173B	MY61252566	2025.05.10	2026.05.09	B.01.95	N/A
Test Software	Tonscend	TS1120	JS1120-3	N/A	N/A	N/A	V3.0.22

Radiated Emission(9KHz-1GHz) / AC2

Instrument	Manufacturer	Model No.	Serial No.	Cal. Date	Next Cal. Date	Firmware Versiom	Software version
EMI Test Receiver	R&S	ESCI	100176	2025.03.23	2026.03.22	4.42 SP3	N/A
Loop Antenna	R&S	HFH2-Z2E	101149	2025.04.16	2026.04.15	N/A	N/A
Bilog Antenna	Teseq GmbH	CBL6112D	27613	2024.09.08	2025.09.07	N/A	N/A
Temperature/Humidity Meter	RTS	RTS-8S	AC2-TH	2025.06.17	2026.06.16	N/A	N/A
Coaxial Cable	Huber+Suhner	SUCOFLEX 106	AC2-C	2025.03.16	2026.03.15	N/A	N/A
Dekra test software	Dekra	N/A	N/A	N/A	N/A	N/A	3

Radiated Emissions (30MHz-40GHz) / AC6

Instrument	Manufacturer	Model No.	Serial No.	Cal. Date	Next Cal. Date	Firmware Version	Software version
Signal analyzer	Agilent	N9020A	MY49100159	2025.05.10	2026.05.09	A 08.54	N/A
Horn Antenna	RFSPIN	DRH18-E	CE2C07A18EN	2024.12.07	2025.12.06	N/A	N/A
Pre-Amplifier	XH	LNA1845	LNA23040284	2025.05.17	2026.05.16	N/A	N/A
Broad-Band Horn Antenna	Schwarzbeck	BBHA9170	750	2024.11.24	2025.11.23	N/A	N/A
Pre-Amplifier	SCHWARZBECK	BBV 9721	00114	2025.05.17	2026.05.16	N/A	N/A
Half Wave Tuned Dipole Antenna	COM-POWER	AD-100	40137	2023.04.07	2026.04.06	N/A	N/A
Notch Filter	Micro-mve	MFN-2400.2485.S1	AN0003N	2025.06.10	2026.06.09	N/A	N/A
Coaxial Cable	N/A	N/A	2225	2025.06.10	2026.06.09	N/A	N/A
Coaxial Cable	N/A	N/A	2229	2025.06.10	2026.06.09	N/A	N/A
Temperature/Humidity Meter	RTS	RTS-8S	RF04	2025.06.17	2026.06.16	N/A	N/A
Temperature/Humidity Meter	RTS	RTS-8S	RF08	2025.06.17	2026.06.16	N/A	N/A
Test Software	Tonscend	JS36	JS36-RSE	N/A	N/A	N/A	5.0.0

UNCERTAINTY

Uncertainties have been calculated according to the DEKRA internal document. The reported expanded uncertainties are based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95% .

Test item Test Location	Uncertainty
AC Power Line Conducted Emission	± 2.92 dB
Peak Power Output	± 1.13 dB
Radiated Emission(30MHz~1GHz)	Horizontal: 30MHz~200MHz: 4.60 dB 200MHz~1GHz: 4.10 dB Vertical: 30MHz~200MHz: 4.80 dB 200MHz~1GHz: 4.10 dB
Radiated Emission(1GHz~40GHz)	Horizontal: 1GHz~18GHz: 5.00 dB Vertical: 1GHz~18GHz: 4.80 dB Horizontal: 18GHz~40GHz: 4.70 dB Vertical: 18GHz~40GHz: 4.60 dB
RF antenna conducted test	± 1.13 dB
Radiated Emission Band Edge	± 5.00 dB
DTS Bandwidth	± 279 Hz
Occupied Bandwidth	± 279 Hz
Power Density	± 1.13 dB

1 GENERAL INFORMATION

1.1 General Description of the Item(s)

Product Name:	Xiaomi Stylus				
Model No.:	2508DMP70G				
Trademark:	Xiaomi				
Hardware Version:	V01				
Software Version:	V0.0.13				
FCC ID:	2AFZZMP70G				
Power Supply:	External power supply voltage: 5.0Vdc Battery Powered: 3.80 Vdc				
Manufacturer:	Xiaomi Communications Co., Ltd.				
Manufacturer address:	#019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085				
Test EUT:	RF Conducted	#1			
	RSE	#1			
Wireless specification:	Bluetooth (LE)				
Operating frequency range(s):	2402~2480MHz				
Type of Modulation:	GFSK				
PHYs:	<input checked="" type="checkbox"/>	LE 1M	<input checked="" type="checkbox"/>	LE 2M	<input type="checkbox"/> LE Coded S=2/8
Data Rate:	<input checked="" type="checkbox"/>	1Mbit/s	<input checked="" type="checkbox"/>	2Mbit/s	<input type="checkbox"/> 500/125 Kbit/s
Antenna Type:	Ceramic Antenna				
Antenna Gain:	2.0dBi				

Remark:

As above information is provided and confirmed by the applicant. DEKRA is not liable to the accuracy, suitability, reliability or/and integrity of the information.

1.2 Channel List

Bluetooth Working Frequency of Each Channel:							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
00	2402 MHz	01	2404 MHz	02	2406 MHz	03	2408 MHz
04	2410 MHz	05	2412 MHz	06	2414 MHz	07	2416 MHz
08	2418 MHz	09	2420 MHz	10	2422 MHz	11	2424 MHz
12	2426 MHz	13	2428 MHz	14	2430 MHz	15	2432 MHz
16	2434 MHz	17	2436 MHz	18	2438 MHz	19	2440 MHz
20	2442 MHz	21	2444 MHz	22	2446 MHz	23	2448 MHz
24	2450 MHz	25	2452 MHz	26	2454 MHz	27	2456 MHz
28	2458 MHz	29	2460 MHz	30	2462 MHz	31	2464 MHz
32	2466 MHz	33	2468 MHz	34	2470 MHz	35	2472 MHz
36	2474 MHz	37	2476 MHz	38	2478 MHz	39	2480 MHz

Note: The General Description of the Item, Channel List in clause 1 are provided and confirmed by the client.

2 DESCRIPTION OF TEST SETUP

Auxiliary equipment	Type / Version	Manufacturer	Supplied by
(1) Notebook	Think pad x220	Lenovo	Adapter
(2) USB Control Cable	N/A	N/A	N/A
(3) USB Control Cable	N/A	N/A	N/A
software	Type / Version		
Smartsnippets _toolbox	N/A		

Accessories Information	Cable		
	Length used during test [m]	Attached during test	Shielded
(2)USB Control Cable	1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
(3)USB Control Cable	8	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>

3 VERDICT SUMMARY SECTION

This chapter presents an overview of standards and results. Refer to the next chapters for details of measured test results and applied test levels.

3.1 Standards

Standard	Year	Description
CFR 47, FCC Part 15 C	2024	Operation within the bands 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz.
ANSI C63.10	2020	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices

3.2 Deviation(s) from the Standard(s) / Test Specification(s)

The following deviation(s) was / were made from the published requirements of the listed standards: N/A.

(Please define the deviations from the standard(s) if applicable)

3.3 Overview of results

Requirement – Test Item of FCC	Standard(s)	Verdict	Remark
DTS Bandwidth	FCC 15.247(a)(2)	PASS	Test data please refer to Appendix A
Maximum conducted output power	15.247 (b)(3)	PASS	Test data please refer to Appendix B
Maximum power spectral density	FCC 15.247(e)	PASS	Test data please refer to Appendix C
Band edge measurements	FCC 15.247(d) FCC 15.205 FCC 15.209	PASS	Test data please refer to Appendix D
Conducted Spurious Emission	FCC 15.247(d), FCC 15.209	PASS	Test data please refer to Appendix E
Duty cycle	ANSI C63.10:2020	PASS	Test data please refer to Appendix F
Emissions in Restricted Bands	FCC 15.205 FCC 15.209	PASS	Test data please refer to Appendix G
AC Power Line Conducted Emission	FCC 15.207	N/A	N/A (See Note1)
Antenna Requirement	FCC 15.203	PASS	---

Note1: The EUT does not support adapter charging and is not applicable.

Note2: The radiation measurement is pre tested under X, Y, and Z axis positioning to find the worst placement for final testing.

3.4 Power setting in test

Mode	Channel	Frequency (MHz)	Power setting
LE 1M	00	2402	default
	19	2440	default
	39	2480	default
LE 2M	00	2402	default
	19	2440	default
	39	2480	default

3.5 Test Facility

Tset Location : FCC Designation Number: CN1199

Tset Location : FCC Company Number: 566524

4 TEST ITEMS OF LIMIT/SETUP/PROCEDURE


4.1 DTS Bandwidth	VERDICT: PASS
--------------------------	----------------------

4.1.1 Limit

Standard	FCC Part 15 Subpart C Paragraph 15.247 (a)(2);
-----------------	--

Systems using digital modulation techniques operate in the 2400-2483.5 MHz. The minimum 6 dB bandwidth shall be at least 500 kHz

4.1.2 Test Setup



4.1.3 Test Procedure

	Reference Rule	Chapter	Description
<input checked="" type="checkbox"/>	ANSI C63.10	11.8	DTS bandwidth
<input checked="" type="checkbox"/>	ANSI C63.10	11.8.1	Option 1
<input type="checkbox"/>	ANSI C63.10	11.8.2	Option 2


4.2 Occupied Channel Bandwidth	VERDICT: PASS
---------------------------------------	----------------------

4.2.1 Limit

Standard	RSS-Gen Issue 5 Paragraph 6.7
-----------------	-------------------------------

The occupied bandwidth or the “99% emission bandwidth” is defined as the frequency range between two points, one above and the other below the carrier frequency, within which 99% of the total transmitted power of the fundamental transmitted emission is contained. The occupied bandwidth shall be reported for all equipment in addition to the specified bandwidth required in the applicable RSSs

4.2.2 Test Setup



4.2.3 Test Procedure

	Reference Rule	Chapter	Description
<input checked="" type="checkbox"/>	ANSI C63.10	6.9	Occupied bandwidth tests
<input type="checkbox"/>	ANSI C63.10	6.9.2	Option 1
<input checked="" type="checkbox"/>	ANSI C63.10	6.9.3	Option 2

4.3 Maximum Conducted Output Power	VERDICT: PASS
---	----------------------


4.3.1 Limit

Standard	FCC Part 15 Subpart C Paragraph 15.247 (b)(3);	
<input checked="" type="checkbox"/>	GTX < 6dBi	Pout ≤ 30dBm
<input type="checkbox"/>	GTX > 6dBi	
<input type="checkbox"/>	Non-Fix point-point	$P_{out} \leq 30 - (GTX - 6)$
<input type="checkbox"/>	Fix point-point	$P_{out} \leq 30 - [(GTX - 6)]/3$
<input type="checkbox"/>	Point-to-multipoint	$P_{out} \leq 30 - (GTX - 6)$
<input type="checkbox"/>	Overlap Beams	$P_{out} \leq 30 - [(GTX - 6)]/3$
<input type="checkbox"/>	Aggregate power transmitted simultaneously on all beams	$P_{out} \leq 30 - [(GTX - 6)]/3$
<input type="checkbox"/>	single directional beam	$P_{out} \leq 30 - [(GTX - 6)]/3 + 8dB$

Note 1 : GTX directional gain of transmitting antennas.

Note 2 : Pout is maximum peak conducted output power .

4.3.2 Test Setup



4.3.3 Test Procedure				
	References Rule		Chapter	Description
<input checked="" type="checkbox"/>	ANSI C63.10		11.9	Fundamental emission output power
<input type="checkbox"/>	ANSI C63.10		11.9.1	Maximum peak conducted output power
	<input type="checkbox"/>	ANSI C63.10	11.9.1.1	RBW \geq DTS bandwidth
	<input type="checkbox"/>	ANSI C63.10	11.9.1.2	Integrated band power method
	<input type="checkbox"/>	ANSI C63.10	11.9.1.3	PKPM1 Peak power meter method
<input checked="" type="checkbox"/>	ANSI C63.10		11.9.2	Maximum conducted (average) output power
	<input type="checkbox"/>	ANSI C63.10	11.9.2.2	Measurement using a spectrum analyzer (SA)
	<input type="checkbox"/>	ANSI C63.10	11.9.2.2.2	Method AVGSA-1(Duty cycle \geq 98%)
	<input type="checkbox"/>	ANSI C63.10	11.9.2.2.3	Method AVGSA-1A(Duty cycle \geq 98%)
	<input type="checkbox"/>	ANSI C63.10	11.9.2.2.4	Method AVGSA-2(Duty cycle \leq 98%)
	<input type="checkbox"/>	ANSI C63.10	11.9.2.2.5	Method AVGSA-2A(Duty cycle \leq 98%)
	<input type="checkbox"/>	ANSI C63.10	11.9.2.2.4	Method AVGSA-3
	<input type="checkbox"/>	ANSI C63.10	11.9.2.2.5	Method AVGSA-3A
	<input checked="" type="checkbox"/>	ANSI C63.10	11.9.2.3	Measurement using a power meter (PM)
	<input checked="" type="checkbox"/>	ANSI C63.10	11.9.2.3.1	Method AVGPM
	<input type="checkbox"/>	ANSI C63.10	11.9.2.3.2	Method AVGPM-G


4.4 Maximum Power Spectral Density	VERDICT: PASS
---	----------------------

4.4.1 Limit

Standard	FCC Part 15 Subpart C Paragraph 15.247 (b)(3);
-----------------	--

Power Spectral Density ≤ 8dBm/3kHz

4.4.2 Test Setup



4.4.3 Test Procedure

	References Rule	Chapter	Description
<input checked="" type="checkbox"/>	ANSI C63.10	11.10	Maximum power spectral density level in the fundamental emission
<input checked="" type="checkbox"/>	ANSI C63.10	11.10.2	Method PKPSD (peak PSD)
<input type="checkbox"/>	ANSI C63.10	11.10.3	Method AVGPSD-1(Duty cycle ≥ 98%)
<input type="checkbox"/>	ANSI C63.10	11.10.4	Method AVGPSD-1A(Duty cycle ≥ 98%)
<input type="checkbox"/>	ANSI C63.10	11.10.5	Method AVGPSD-2(Duty cycle < 98%)
<input type="checkbox"/>	ANSI C63.10	11.10.6	Method AVGPSD-2A(Duty cycle < 98%)
<input type="checkbox"/>	ANSI C63.10	11.10.7	Method AVGPSD-3
<input type="checkbox"/>	ANSI C63.10	11.10.8	Method AVGPSD-3A

4.5 Band Edge Measurements	VERDICT: PASS
-----------------------------------	----------------------


4.5.1 Limit

Standard		FCC Part 15 Subpart C Paragraph 15.247(d) , 15.209;		
Frequency bands (MHz)	Detector	Limit (dBμV/m)	RBW (MHz)	Distance (m)
2310-2390	PK	74	1	3
2483.5-2500	AV	54	1	3

Note: The field strength of emissions appearing within these frequency bands shall not exceed the limits.

4.5.2 Test Setup

Above 1GHz Test Setup:



4.5.3 Test Procedure

	References Rule	Chapter	Description
<input checked="" type="checkbox"/>	ANSI C63.10	6.10	Band-edge testing
	<input checked="" type="checkbox"/> ANSI C63.10	6.10.5	Restricted-band band-edge measurements
	<input type="checkbox"/> ANSI C63.10	6.10.6	Marker-delta method
<input checked="" type="checkbox"/>	ANSI C63.10	11.12	Emissions in restricted frequency bands
	<input checked="" type="checkbox"/> ANSI C63.10	11.12.1	Radiated emission measurements
	<input checked="" type="checkbox"/> ANSI C63.10	11.12.2.7	Radiated spurious emission test
<input type="checkbox"/>	ANSI C63.10	6.4	Radiated emissions from unlicensed wireless devices below 30 MHz
<input type="checkbox"/>	ANSI C63.10	6.5	Radiated emissions from unlicensed wireless devices in the frequency range of 30 MHz to 1000 MHz
<input checked="" type="checkbox"/>	ANSI C63.10	6.6	Radiated emissions from unlicensed wireless devices above 1 GHz

4.6 Conducted Spurious Emission	VERDICT: PASS
--	----------------------


4.6.1 Limit

Standard	FCC Part 15 Subpart C Paragraph 15.247(d);
RF Output power (Detection methods)	Limit(dB)
RF Output power(Average detector)	30dBc(Note1)
RF Output power(PK detector)	20dBc(Note2)

Note 1: If maximum conducted (average) output power was used to demonstrate compliance as described in 9.2, then the peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 30 dBc).

Note 2: If the maximum peak conducted output power procedure was used, then the peak output power measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz (i.e., 20 dBc).

4.6.2 Test Setup



4.6.3 Test Procedure


References Rule	Chapter	Description
<input checked="" type="checkbox"/> ANSI C63.10	11.11	Emissions in non-restricted frequency bands
<input checked="" type="checkbox"/> ANSI C63.10	11.11.1	General
<input checked="" type="checkbox"/> ANSI C63.10	11.11.2	Reference level measurement
<input checked="" type="checkbox"/> ANSI C63.10	11.11.3	Emission level measurement

4.7 Duty cycle	VERDICT: PASS
-----------------------	----------------------

4.7.1 Limit

N/A

4.7.2 Test Setup



4.7.3 Test Procedure

References Rule	Chapter	Description
<input checked="" type="checkbox"/> ANSI C63.10	11.6	Duty cycle (D), transmission duration (T), and maximum power control level

4.8 Emissions in Restricted Bands	VERDICT: PASS
--	----------------------

4.8.1 Limit			
Standard		FCC Part 15 Subpart C Paragraph 15.205	
Restricted Bands of operation			
Frequency (MHz)	Frequency (MHz)	Frequency (MHz)	Frequency (GHz)
0.090 – 0.110	16.42 – 16.423	399.9 – 410	4.5 – 5.15
0.495 – 0.505	16.69475 – 16.69525	608 – 614	5.35 – 5.46
2.1735 – 2.1905	16.80425 – 16.80475	960 – 1240	7.25 – 7.75
4.125 – 4.128	25.5 – 25.67	1300 – 1427	8.025 – 8.5
4.17725 – 4.17775	37.5 – 38.25	1435 – 1626.5	9.0 – 9.2
4.20725 – 4.20775	73 – 74.6	1645.5 – 1646.5	9.3 – 9.5
6.215 – 6.218	74.8 – 75.2	1660 – 1710	10.6 – 12.7
6.26775 – 6.26825	108 – 121.94	1718.8 – 1722.2	13.25 – 13.4
6.31175 – 6.31225	123 – 138	2200 – 2300	14.47 – 14.5
8.291 – 8.294	149.9 – 150.05	2310 – 2390	15.35 – 16.2
8.362 – 8.366	156.52475 – 156.52525	2483.5 – 2500	17.7 – 21.4
8.37625 – 8.38675	156.7 – 156.9	2690 – 2900	22.01 – 23.12
8.81425 – 8.81475	162.0125 – 167.17	3260 – 3267	23.6 – 24.0
12.29 – 12.293	167.72 – 173.2	3332 – 3339	31.2 – 31.8
12.51975 – 12.52025	240 – 285	3345.8 – 3358	36.43 – 36.5
12.57675 – 12.57725	322 – 335.4	3600 – 4400	
13.36 – 13.41			

Restricted Band Emissions Limit			
FCC Part 15 Subpart C Paragraph 15.209			
Frequency (MHz)	Field strength (µV/m)	Field strength (dBµV/m)	Measurement distance (m)
0.009 - 0.49	2400/F(kHz)	48.5 – 13.8	300 _(Note 1)
0.49 - 1.705	24000/F(kHz)	33.8 - 23	30 _(Note 1)
1.705 - 30	30	29.5	30 _(Note 1)
30 - 88	100	40	3 _(Note 2)
88 - 216	150	43.5	3 _(Note 2)
216 - 960	200	46	3 _(Note 2)
Above 960	500	54	3 _(Note 2)


Note 1: At frequencies below 30 MHz, measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field. Pending the development of an appropriate measurement procedure for measurements performed below 30 MHz, when performing measurements at a closer distance than specified, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade).

Note 2: At frequencies at or above 30 MHz, measurements may be performed at a distance other than what is specified provided: measurements are not made in the near field except where it can be shown that near field measurements are appropriate due to the characteristics of the device; and it can be demonstrated that the signal levels needed to be measured at the distance employed can be detected by the measurement equipment. Measurements shall not be


performed at a distance greater than 30 meters unless it can be further demonstrated that measurements at a distance of 30 meters or less are impractical. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse linear-distance for field strength measurements; inverse-linear-distance-squared for power density measurements).

4.8.2 Test Setup


Below 30MHz Test Setup:



30MHz-1GHz Test Setup:



Above 1GHz Test Setup:



4.8.3 Test Procedure			
	References Rule	Chapter	Description
<input checked="" type="checkbox"/>	ANSI C63.10	11.12	Emissions in restricted frequency bands
<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/> ANSI C63.10	11.12.1	Radiated emission measurements
<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/> ANSI C63.10	11.12.2.7	Radiated spurious emission test
<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/> ANSI C63.10	6.4	Radiated emissions from unlicensed wireless devices below 30 MHz
<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/> ANSI C63.10	6.5	Radiated emissions from unlicensed wireless devices in the frequency range of 30 MHz to 1000 MHz
<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/> ANSI C63.10	6.6	Radiated emissions from unlicensed wireless devices above 1 GHz

4.9 AC Power Line Conducted Emission	VERDICT: N/A
---	---------------------

4.9.1 Limit

Standard	FCC Part 15 Subpart C Paragraph 15.207;	
Frequency range [MHz]	Limit: QP [dB(μV) ¹⁾	Limit: AV [dB(μV) ¹⁾
0,15 - 0,50	66 - 56 ²⁾	56 - 46 ²⁾
0,50 - 5,0	56	46
5,0 - 30	60	50


¹⁾ At the transition frequency, the lower limit applies.

²⁾ The limit decreases linearly with the logarithm of the frequency.

NOTE 1: The exclusion band for transmitters shall be considered for transmitters operating at frequencies below 30 MHz.

NOTE 2: Where the AC output port is directly connected (or via a circuit breaker) to the AC power input port of the EUT the AC power output port need not to be tested.

4.9.2 Test Setup



4.9.3 Test Procedure

	References Rule	Chapter	Item
<input type="checkbox"/>	ANSI C63.10	6.2	Standard test method for ac power-line conducted emissions from unlicensed wireless devices

4.10 Antenna Requirement	VERDICT: PASS
---------------------------------	----------------------

4.10.1 Limit:

Standard	FCC Part 15 Subpart C Paragraph 15.203;
-----------------	---

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

4.10.2 Antenna Connector Construction:

<input checked="" type="checkbox"/>	The use of a permanently attached antenna
<input type="checkbox"/>	The antenna use of a unique coupling to the intentional radiator
<input type="checkbox"/>	The use of a nonstandard antenna jack or electrical connector

Please refer to the attached document "Internal Photograph" to show the antenna connector.

5 TEST SETUP PHOTO AND EUT PHOTO

Remark: The test setup photo and EUT Photo please see appendix.

6 TEST RESULT

Appendix A: DTS Bandwidth

TestMode	Antenna	Frequency[MHz]	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE_1M	Ant1	2402	0.656	2401.672	2402.328	0.5	PASS
BLE_1M	Ant1	2440	0.656	2439.672	2440.328	0.5	PASS
BLE_1M	Ant1	2480	0.656	2479.672	2480.328	0.5	PASS
BLE_2M	Ant1	2402	1.136	2401.444	2402.580	0.5	PASS
BLE_2M	Ant1	2440	1.108	2439.452	2440.560	0.5	PASS
BLE_2M	Ant1	2480	1.096	2479.464	2480.560	0.5	PASS

BLE_1M-Ant1-2402-PASS



BLE_1M-Ant1-2440-PASS



BLE_1M-Ant1-2480-PASS



BLE_2M-Ant1-2402-PASS



BLE_2M-Ant1-2440-PASS



BLE_2M-Ant1-2480-PASS



Appendix B: Maximum conducted output power

Test Mode	Frequency (MHz)	Measured Power (dBm)	Conducted Limit[dBm]
LE_1M	2402	-5.22	≤ 30
	2440	-5.39	≤ 30
	2480	-5.45	≤ 30
LE_2M	2402	-5.13	≤ 30
	2440	-5.26	≤ 30
	2480	-5.38	≤ 30


Appendix C: Maximum power spectral density

TestMode	Antenna	Frequency[MHz]	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
BLE_1M	Ant1	2402	-20.55	≤8.00	PASS
BLE_1M	Ant1	2440	-20.77	≤8.00	PASS
BLE_1M	Ant1	2480	-20.86	≤8.00	PASS
BLE_2M	Ant1	2402	-20.89	≤8.00	PASS
BLE_2M	Ant1	2440	-21.12	≤8.00	PASS
BLE_2M	Ant1	2480	-21.20	≤8.00	PASS


BLE_1M-Ant1-2402-PASS




BLE_1M-Ant1-2440-PASS




BLE_1M-Ant1-2480-PASS






Appendix D: Band edge measurements

Transmit at 2402MHz by LE_1Mbps




Data List									
NO	Frequency [MHz]	Reading [dBµV]	Level [dBµV/m]	Factor [dB/m]	Limit [dBµV/m]	Margin [dB]	Det	Pol	Verdict
1	2389.61	42.4	42.31	-0.050	74.00	31.69	PK	Horizo	PASS
2	2390.00	41.4	41.32	-0.050	74.00	32.68	PK	Horizo	PASS

Transmit at 2402MHz by LE_1Mbps




Data List									
NO	Frequency [MHz]	Reading [dBµV]	Level [dBµV/m]	Factor [dB/m]	Limit [dBµV/m]	Margin [dB]	Det	Pol	Verdict
1	2377.36	41.4	41.33	-0.080	74.00	32.67	PK	Vertic	PASS
2	2390.00	40.8	40.77	-0.050	74.00	33.23	PK	Vertic	PASS

Transmit at 2402MHz by LE_1Mbps




Data List									
NO	Frequency [MHz]	Reading [dBµV]	Level [dBµV/m]	Factor [dB/m]	Limit [dBµV/m]	Margin [dB]	Det	Pol	Verdict
1	2365.77	30.1	29.98	-0.110	54.00	24.02	AV	Horizo	PASS
2	2390.00	29.0	28.96	-0.050	54.00	25.04	AV	Horizo	PASS

Transmit at 2402MHz by LE_1Mbps




Data List									
NO	Frequency [MHz]	Reading [dBµV]	Level [dBµV/m]	Factor [dB/m]	Limit [dBµV/m]	Margin [dB]	Det	Pol	Verdict
1	2340.88	29.2	29.00	-0.170	54.00	25.00	AV	Vertic	PASS
2	2390.00	29.2	29.16	-0.050	54.00	24.84	AV	Vertic	PASS
3	2401.96	78.3	78.24	-0.030	-	-	AV	Vertic	NA

Transmit at 2480MHz by LE_1Mbps




Data List									
NO	Frequency [MHz]	Reading [dBµV]	Level [dBµV/m]	Factor [dB/m]	Limit [dBµV/m]	Margin [dB]	Det	Pol	Verdict
1	2483.50	49.8	50.04	0.270	74.00	23.96	PK	Horizo	PASS

Transmit at 2480MHz by LE_1Mbps




Data List									
NO	Frequency [MHz]	Reading [dBµV]	Level [dBµV/m]	Factor [dB/m]	Limit [dBµV/m]	Margin [dB]	Det	Pol	Verdict
1	2483.50	48.8	49.06	0.270	74.00	24.94	PK	Vertic	PASS

Transmit at 2480MHz by LE_1Mbps




Data List									
NO	Frequency [MHz]	Reading [dBµV]	Level [dBµV/m]	Factor [dB/m]	Limit [dBµV/m]	Margin [dB]	Det	Pol	Verdict
1	2483.50	29.9	30.15	0.270	54.00	23.85	AV	Horizo	PASS
2	2484.08	30.9	31.19	0.270	54.00	22.81	AV	Horizo	PASS

Transmit at 2480MHz by LE_1Mbps




Data List									
NO	Frequency [MHz]	Reading [dBµV]	Level [dBµV/m]	Factor [dB/m]	Limit [dBµV/m]	Margin [dB]	Det	Pol	Verdict
1	2483.50	29.0	29.31	0.270	54.00	24.69	AV	Vertic	PASS
2	2483.90	29.4	29.67	0.270	54.00	24.33	AV	Vertic	PASS

Transmit at 2402MHz by LE_2Mbps




Data List									
NO	Frequency [MHz]	Reading [dBµV]	Level [dBµV/m]	Factor [dB/m]	Limit [dBµV/m]	Margin [dB]	Det	Pol	Verdict
1	2387.90	41.8	41.77	-0.060	74.00	32.23	PK	Horizo	PASS
2	2390.00	41.4	41.39	-0.050	74.00	32.61	PK	Horizo	PASS

Transmit at 2402MHz by LE_2Mbps




Data List									
NO	Frequency [MHz]	Reading [dBµV]	Level [dBµV/m]	Factor [dB/m]	Limit [dBµV/m]	Margin [dB]	Det	Pol	Verdict
1	2389.14	42.0	41.95	-0.060	74.00	32.05	PK	Vertic	PASS
2	2390.00	41.2	41.19	-0.050	74.00	32.81	PK	Vertic	PASS

Transmit at 2402MHz by LE_2Mbps




Data List									
NO	Frequency [MHz]	Reading [dBµV]	Level [dBµV/m]	Factor [dB/m]	Limit [dBµV/m]	Margin [dB]	Det	Pol	Verdict
1	2389.42	29.2	29.12	-0.050	54.00	24.88	AV	Horizo	PASS
2	2390.00	29.0	28.91	-0.050	54.00	25.09	AV	Horizo	PASS

Transmit at 2402MHz by LE_2Mbps




Data List									
NO	Frequency [MHz]	Reading [dBµV]	Level [dBµV/m]	Factor [dB/m]	Limit [dBµV/m]	Margin [dB]	Det	Pol	Verdict
1	2388.57	29.5	29.46	-0.060	54.00	24.54	AV	Vertic	PASS
2	2390.00	29.0	28.91	-0.050	54.00	25.09	AV	Vertic	PASS

Transmit at 2480MHz by LE_2Mbps




Data List									
NO	Frequency [MHz]	Reading [dBµV]	Level [dBµV/m]	Factor [dB/m]	Limit [dBµV/m]	Margin [dB]	Det	Pol	Verdict
1	2483.50	49.9	50.21	0.270	74.00	23.79	PK	Horizo	PASS
2	2484.10	53.8	54.03	0.270	74.00	19.97	PK	Horizo	PASS

Transmit at 2480MHz by LE_2Mbps




Data List									
NO	Frequency [MHz]	Reading [dBµV]	Level [dBµV/m]	Factor [dB/m]	Limit [dBµV/m]	Margin [dB]	Det	Pol	Verdict
1	2483.50	49.0	49.29	0.270	74.00	24.71	PK	Vertic	PASS
2	2487.95	50.4	50.68	0.290	74.00	23.32	PK	Vertic	PASS

Transmit at 2480MHz by LE_2Mbps



Data List									
NO	Frequency [MHz]	Reading [dBµV]	Level [dBµV/m]	Factor [dB/m]	Limit [dBµV/m]	Margin [dB]	Det	Pol	Verdict
1	2483.50	33.7	33.96	0.270	54.00	20.04	AV	Horizo	PASS
2	2485.95	30.3	30.61	0.290	54.00	23.39	AV	Horizo	PASS

Transmit at 2480MHz by LE_2Mbps



Data List									
NO	Frequency [MHz]	Reading [dBµV]	Level [dBµV/m]	Factor [dB/m]	Limit [dBµV/m]	Margin [dB]	Det	Pol	Verdict
1	2483.50	29.6	29.87	0.270	54.00	24.13	AV	Vertic	PASS
2	2488.65	29.4	29.69	0.290	54.00	24.31	AV	Vertic	PASS

Note:

1. Level=Reading+Factor .

2. Margin=Limit-Level.

Appendix E: Conducted Spurious Emission

Reference level measurement :

BLE_1M-Ant1-2402-PASS



BLE_1M-Ant1-2440-PASS



BLE_1M-Ant1-2480-PASS



BLE_2M-Ant1-2402-PASS



BLE_2M-Ant1-2440-PASS




BLE_2M-Ant1-2480-PASS




Band edge measurements :


BLE_1M-Ant1-2402-PASS




BLE_1M-Ant1-2480-PASS




BLE_2M-Ant1-2402-PASS




BLE_2M-Ant1-2480-PASS



Conducted Spurious Emission :




BLE_1M-Ant1-2440-30~1000-PASS



BLE_1M-Ant1-2440-1000~25000-PASS




BLE_1M-Ant1-2480-30~1000-PASS



BLE_1M-Ant1-2480-1000~25000-PASS




BLE_2M-Ant1-2402-30~1000-PASS




BLE_2M-Ant1-2402-1000~25000-PASS




BLE_2M-Ant1-2440-30~1000-PASS



BLE_2M-Ant1-2440-1000~25000-PASS



BLE_2M-Ant1-2480-30~1000-PASS




BLE_2M-Ant1-2480-1000~25000-PASS




Appendix F: Duty Cycle

TestMode	Antenna	Frequency[MHz]	ON Time [ms]	Period [ms]	Duty Cycle [%]	Duty Cycle Factor[dB]
BLE_1M	Ant1	2402	0.40	0.62	64.52	1.90
BLE_1M	Ant1	2440	0.40	0.62	64.52	1.90
BLE_1M	Ant1	2480	0.40	0.62	64.52	1.90
BLE_2M	Ant1	2402	0.22	0.62	35.48	4.50
BLE_2M	Ant1	2440	0.22	0.63	34.92	4.57
BLE_2M	Ant1	2480	0.22	0.63	34.92	4.57


NTNV-BLE_1M-Ant1-2402




NTNV-BLE_1M-Ant1-2440




NTNV-BLE_1M-Ant1-2480




NTNV-BLE_2M-Ant1-2402



NTNV-BLE_2M-Ant1-2440




NTNV-BLE_2M-Ant1-2480




Appendix G: Emissions in Restricted Bands

Transmit at 2402MHz by LE_1Mbps




Data List									
NO	Frequency [MHz]	Reading [dBµV]	Level [dBµV/m]	Factor [dB/m]	Limit [dBµV/m]	Margin [dB]	Det	Pol	Verdict
1	4804.00	46.0	37.55	-8.480	74.00	36.45	PK	Horizo	PASS
2	4804.00	38.5	29.98	-8.480	54.00	24.02	AV	Horizo	PASS
3	7206.00	35.8	34.14	-1.620	54.00	19.86	AV	Horizo	PASS
4	7206.00	43.9	42.29	-1.620	74.00	31.71	PK	Horizo	PASS
5	9608.00	43.3	44.72	1.380	74.00	29.28	PK	Horizo	PASS
6	9608.00	34.5	35.91	1.380	54.00	18.09	AV	Horizo	PASS

Transmit at 2402MHz by LE_1Mbps




Data List									
NO	Frequency [MHz]	Reading [dBµV]	Level [dBµV/m]	Factor [dB/m]	Limit [dBµV/m]	Margin [dB]	Det	Pol	Verdict
1	4804.00	46.2	37.73	-8.480	74.00	36.27	PK	Vertic	PASS
2	4804.00	40.9	32.44	-8.480	54.00	21.56	AV	Vertic	PASS
3	7206.00	44.0	42.40	-1.620	74.00	31.60	PK	Vertic	PASS
4	7206.00	36.1	34.45	-1.620	54.00	19.55	AV	Vertic	PASS
5	9608.00	42.9	44.23	1.380	74.00	29.77	PK	Vertic	PASS
6	9608.00	34.4	35.82	1.380	54.00	18.18	AV	Vertic	PASS

Transmit at 2440MHz by LE_1Mbps




Data List									
NO	Frequency [MHz]	Reading [dBµV]	Level [dBµV/m]	Factor [dB/m]	Limit [dBµV/m]	Margin [dB]	Det	Pol	Verdict
1	4880.00	46.9	38.72	-8.160	74.00	35.28	PK	Horizo	PASS
2	4880.00	38.3	30.12	-8.160	54.00	23.88	AV	Horizo	PASS
3	7320.00	44.7	43.20	-1.450	74.00	30.80	PK	Horizo	PASS
4	7320.00	35.9	34.46	-1.450	54.00	19.54	AV	Horizo	PASS
5	9760.00	41.6	43.07	1.450	74.00	30.93	PK	Horizo	PASS
6	9760.00	34.7	36.12	1.450	54.00	17.88	AV	Horizo	PASS

Transmit at 2440MHz by LE_1Mbps




Data List									
NO	Frequency [MHz]	Reading [dBµV]	Level [dBµV/m]	Factor [dB/m]	Limit [dBµV/m]	Margin [dB]	Det	Pol	Verdict
1	4880.00	47.8	39.60	-8.160	74.00	34.40	PK	Vertic	PASS
2	4880.00	39.0	30.88	-8.160	54.00	23.12	AV	Vertic	PASS
3	7320.00	44.3	42.82	-1.450	74.00	31.18	PK	Vertic	PASS
4	7320.00	36.3	34.87	-1.450	54.00	19.13	AV	Vertic	PASS
5	9760.00	42.8	44.25	1.450	74.00	29.75	PK	Vertic	PASS
6	9760.00	34.8	36.21	1.450	54.00	17.79	AV	Vertic	PASS

Transmit at 2480MHz by LE_1Mbps




Data List									
NO	Frequency [MHz]	Reading [dBµV]	Level [dBµV/m]	Factor [dB/m]	Limit [dBµV/m]	Margin [dB]	Det	Pol	Verdict
1	4960.00	47.6	39.80	-7.830	74.00	34.20	PK	Horizo	PASS
2	4960.00	38.8	30.98	-7.830	54.00	23.02	AV	Horizo	PASS
3	7440.00	35.5	34.23	-1.300	54.00	19.77	AV	Horizo	PASS
4	7440.00	43.7	42.43	-1.300	74.00	31.57	PK	Horizo	PASS
5	9920.00	41.3	43.61	2.350	74.00	30.39	PK	Horizo	PASS
6	9920.00	33.4	35.71	2.350	54.00	18.29	AV	Horizo	PASS

Transmit at 2480MHz by LE_1Mbps




Data List									
NO	Frequency [MHz]	Reading [dBµV]	Level [dBµV/m]	Factor [dB/m]	Limit [dBµV/m]	Margin [dB]	Det	Pol	Verdict
1	4960.00	48.4	40.59	-7.830	74.00	33.41	PK	Vertic	PASS
2	4960.00	38.1	30.31	-7.830	54.00	23.69	AV	Vertic	PASS
3	7440.00	43.7	42.36	-1.300	74.00	31.64	PK	Vertic	PASS
4	7440.00	35.5	34.23	-1.300	54.00	19.77	AV	Vertic	PASS
5	9920.00	41.6	43.94	2.350	74.00	30.06	PK	Vertic	PASS
6	9920.00	33.0	35.32	2.350	54.00	18.68	AV	Vertic	PASS

Transmit at 2402MHz by LE_2Mbps




Data List									
NO	Frequency [MHz]	Reading [dBµV]	Level [dBµV/m]	Factor [dB/m]	Limit [dBµV/m]	Margin [dB]	Det	Pol	Verdict
1	4804.00	46.7	38.20	-8.480	74.00	35.80	PK	Horizo	PASS
2	4804.00	38.0	29.53	-8.480	54.00	24.47	AV	Horizo	PASS
3	7206.00	35.6	33.95	-1.620	54.00	20.05	AV	Horizo	PASS
4	7206.00	43.1	41.44	-1.620	74.00	32.56	PK	Horizo	PASS
5	9608.00	43.3	44.71	1.380	74.00	29.29	PK	Horizo	PASS
6	9608.00	35.0	36.41	1.380	54.00	17.59	AV	Horizo	PASS

Transmit at 2402MHz by LE_2Mbps




Data List									
NO	Frequency [MHz]	Reading [dBµV]	Level [dBµV/m]	Factor [dB/m]	Limit [dBµV/m]	Margin [dB]	Det	Pol	Verdict
1	4804.00	49.8	41.36	-8.480	74.00	32.64	PK	Vertic	PASS
2	4804.00	40.3	31.86	-8.480	54.00	22.14	AV	Vertic	PASS
3	7206.00	43.4	41.82	-1.620	74.00	32.18	PK	Vertic	PASS
4	7206.00	35.6	33.99	-1.620	54.00	20.01	AV	Vertic	PASS
5	9608.00	43.0	44.35	1.380	74.00	29.65	PK	Vertic	PASS
6	9608.00	34.1	35.50	1.380	54.00	18.50	AV	Vertic	PASS

Transmit at 2440MHz by LE_2Mbps




Data List									
NO	Frequency [MHz]	Reading [dBµV]	Level [dBµV/m]	Factor [dB/m]	Limit [dBµV/m]	Margin [dB]	Det	Pol	Verdict
1	4880.00	47.0	38.85	-8.160	74.00	35.15	PK	Horizo	PASS
2	4880.00	38.6	30.48	-8.160	54.00	23.52	AV	Horizo	PASS
3	7320.00	43.1	41.64	-1.450	74.00	32.36	PK	Horizo	PASS
4	7320.00	35.2	33.76	-1.450	54.00	20.24	AV	Horizo	PASS
5	9760.00	41.9	43.36	1.450	74.00	30.64	PK	Horizo	PASS
6	9760.00	34.1	35.55	1.450	54.00	18.45	AV	Horizo	PASS

Transmit at 2440MHz by LE_2Mbps




Data List									
NO	Frequency [MHz]	Reading [dBµV]	Level [dBµV/m]	Factor [dB/m]	Limit [dBµV/m]	Margin [dB]	Det	Pol	Verdict
1	4880.00	46.8	38.66	-8.160	74.00	35.34	PK	Vertic	PASS
2	4880.00	39.0	30.84	-8.160	54.00	23.16	AV	Vertic	PASS
3	7320.00	36.5	35.07	-1.450	54.00	18.93	AV	Vertic	PASS
4	7320.00	43.6	42.12	-1.450	74.00	31.88	PK	Vertic	PASS
5	9760.00	41.7	43.19	1.450	74.00	30.81	PK	Vertic	PASS
6	9760.00	34.3	35.74	1.450	54.00	18.26	AV	Vertic	PASS

Transmit at 2480MHz by LE_2Mbps



Data List									
NO	Frequency [MHz]	Reading [dBµV]	Level [dBµV/m]	Factor [dB/m]	Limit [dBµV/m]	Margin [dB]	Det	Pol	Verdict
1	4960.00	46.3	38.47	-7.830	74.00	35.53	PK	Horizo	PASS
2	4960.00	37.9	30.06	-7.830	54.00	23.94	AV	Horizo	PASS
3	7440.00	35.8	34.52	-1.300	54.00	19.48	AV	Horizo	PASS
4	7440.00	44.4	43.11	-1.300	74.00	30.89	PK	Horizo	PASS
5	9920.00	41.6	43.98	2.350	74.00	30.02	PK	Horizo	PASS
6	9920.00	33.3	35.62	2.350	54.00	18.38	AV	Horizo	PASS

Transmit at 2480MHz by LE_2Mbps




Data List									
NO	Frequency [MHz]	Reading [dBµV]	Level [dBµV/m]	Factor [dB/m]	Limit [dBµV/m]	Margin [dB]	Det	Pol	Verdict
1	4960.00	38.4	30.55	-7.830	54.00	23.45	AV	Vertic	PASS
2	4960.00	46.6	38.75	-7.830	74.00	35.25	PK	Vertic	PASS
3	7440.00	35.7	34.41	-1.300	54.00	19.59	AV	Vertic	PASS
4	7440.00	44.3	43.02	-1.300	74.00	30.98	PK	Vertic	PASS
5	9920.00	33.3	35.66	2.350	54.00	18.34	AV	Vertic	PASS
6	9920.00	41.7	44.03	2.350	74.00	29.97	PK	Vertic	PASS

Note:

- 1.Level=Reading+Factor .
2. Margin=Limit-Level.
3. The test frequency range, 9kHz~30MHz, worst case are at least 20dB below the limits, therefore no data appear in the report.
4. The test frequency range, 18GHz~26GHz test result on peak is lower than average limit, all is the noise base, therefore no data appear in the report.


The worst case of Radiated Emission below 1GHz :

Transmit at 2402MHz by LE_1Mbps



Data List									
NO	Frequency [MHz]	Reading [dBµV]	Level [dBµV/m]	Factor [dB/m]	Limit [dBµV/m]	Margin [dB]	Det	Pol	Verdict
1	36.31	5.9	19.30	13.360	40.00	20.70	PK	Horizo	PASS
2	70.98	5.2	15.37	10.200	40.00	24.63	PK	Horizo	PASS
3	110.51	5.2	17.38	12.160	43.50	26.12	PK	Horizo	PASS
4	201.93	5.3	17.29	11.990	43.50	26.21	PK	Horizo	PASS
5	331.19	5.8	20.81	14.970	46.00	25.19	PK	Horizo	PASS
6	726.22	6.1	27.22	21.160	46.00	18.78	PK	Horizo	PASS

Transmit at 2402MHz by LE_1Mbps



Data List									
NO	Frequency [MHz]	Reading [dBµV]	Level [dBµV/m]	Factor [dB/m]	Limit [dBµV/m]	Margin [dB]	Det	Pol	Verdict
1	35.34	4.8	17.99	13.220	40.00	22.01	PK	Vertic	PASS
2	76.56	5.7	15.69	9.960	40.00	24.31	PK	Vertic	PASS
3	104.69	6.5	18.97	12.460	43.50	24.53	PK	Vertic	PASS
4	190.54	4.8	16.02	11.260	43.50	27.48	PK	Vertic	PASS
5	269.83	6.3	19.95	13.680	46.00	26.05	PK	Vertic	PASS
6	563.26	5.7	24.51	18.820	46.00	21.49	PK	Vertic	PASS

Note: The final result only applies for using QP detector, if the pre-test result on peak is lower than limit, then QP measurement needn't be performed.

The End