



FCC TEST REPORT (Part 15, Subpart C)

Applicant:	Xiaomi Communications Co., Ltd.
Address:	#019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085

Manufacturer or Supplier:	Xiaomi Communications Co., Ltd.
Address:	#019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085
Product:	Mobile Phone
Brand Name:	POCO
Model Name:	25053PC47G
FCC ID:	2AFZZPC47G
Date of tests:	Feb. 13, 2025-Mar. 26, 2025

The tests have been carried out according to the requirements of the following standard:

- FCC Part 15, Subpart C, Section 15.247
- ANSI C63.10-2020

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Prepared by Hanwen Xu Engineer / Mobile Department	Approved by Peibo Sun Manager / Mobile Department
Date: Mar. 26, 2025	Date: Mar. 26, 2025

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.



TABLE OF CONTENTS

RELEASE CONTROL RECORD 5

1. SUMMARY OF TEST RESULTS..... 6

1.1 MEASUREMENT UNCERTAINTY 7

2 GENERAL INFORMATION 8

2.2 GENERAL DESCRIPTION OF EUT..... 8

2.3 DESCRIPTION OF TEST MODES..... 9

2.2.1 CONFIGURATION OF SYSTEM UNDER TEST 10

2.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL..... 10

2.4 DUTY CYCLE OF TEST SIGNAL 12

2.5 GENERAL DESCRIPTION OF APPLIED STANDARDS..... 12

2.6 DESCRIPTION OF SUPPORT UNITS..... 13

3 TEST TYPES AND RESULTS..... 14

3.1 CONDUCTED EMISSION MEASUREMENT 14

3.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT 14

3.1.2 TEST INSTRUMENTS..... 15

3.1.3 TEST PROCEDURES 16

3.1.4 DEVIATION FROM TEST STANDARD 16

3.1.5 TEST SETUP 17

3.1.6 EUT OPERATING CONDITIONS 17

3.1.7 TEST RESULTS 18

3.2 RADIATED EMISSION MEASUREMENT 20

3.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT 20

3.2.2 TEST INSTRUMENTS..... 21

3.2.3 TEST PROCEDURES 22

3.2.4 DEVIATION FROM TEST STANDARD 22

3.2.5 TEST SETUP 23

3.2.6 EUT OPERATING CONDITIONS 24

3.2.7 TEST RESULTS 25

ANT 0..... 25

ANT 1..... 47

3.3 6 DB BANDWIDTH MEASUREMENT..... 69

3.3.1 LIMITS OF 6DB BANDWIDTH MEASUREMENT 69

3.3.2 TEST INSTRUMENTS..... 69

3.3.3 TEST PROCEDURE..... 70

3.3.4 DEVIATION FROM TEST STANDARD 71

3.3.5 TEST SETUP 71

3.3.6 EUT OPERATING CONDITIONS 71



3.3.7	TEST RESULTS	71
3.4	CONDUCTED OUTPUT POWER	72
3.4.1	LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT	72
3.4.2	TEST SETUP	72
3.4.3	TEST INSTRUMENTS.....	72
3.4.4	TEST PROCEDURES	72
3.4.5	DEVIATION FROM TEST STANDARD	72
3.4.6	EUT OPERATING CONDITIONS	72
3.4.7	TEST RESULTS	73
3.4.7.1	MAXIMUM PEAK OUTPUT POWER	73
3.4.7.2	AVERAGE OUTPUT POWER (FOR REFERENCE).....	74
3.5	POWER SPECTRAL DENSITY MEASUREMENT	75
3.5.1	LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT	75
3.5.2	TEST SETUP	75
3.5.3	TEST INSTRUMENTS.....	75
3.5.4	TEST PROCEDURE.....	75
3.5.5	DEVIATION FROM TEST STANDARD	75
3.5.6	EUT OPERATING CONDITION	75
3.5.7	TEST RESULTS	76
3.6	OUT OF BAND EMISSION MEASUREMENT	77
3.6.1	LIMITS OF OUT OF BAND EMISSION MEASUREMENT	77
3.6.2	TEST SETUP	77
3.6.3	TEST INSTRUMENTS.....	77
3.6.4	TEST PROCEDURE.....	77
3.6.5	DEVIATION FROM TEST STANDARD	78
3.6.6	EUT OPERATING CONDITION	78
3.6.7	TEST RESULTS	78
3.7	ANTENNA REQUIREMENTS	79
3.7.1	STANDARD APPLICABLE	79
3.7.2	ANTENNA CONNECTED CONSTRUCTION.....	79
3.7.3	ANTENNA GAIN	79
4	PHOTOGRAPHS OF THE TEST CONFIGURATION	80
5	MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB	81
6	APPENDIX B:BLE.....	82
	DTS BANDWIDTH.....	82
	ANT0 TEST RESULT.....	82
	ANT1 TEST RESULT.....	82



ANT0 TEST GRAPHS	83
ANT1 TEST GRAPHS	86
OCCUPIED CHANNEL BANDWIDTH.....	89
TEST RESULT	89
TEST GRAPHS.....	90
MAXIMUM CONDUCTED OUTPUT POWER.....	93
TEST RESULT	93
MAXIMUM POWER SPECTRAL DENSITY	93
ANT0 TEST RESULT.....	93
ANT1 TEST RESULT.....	94
ANT0 TEST GRAPHS	95
ANT1 TEST GRAPHS	98
BAND EDGE MEASUREMENTS	101
ANT0 TEST RESULT.....	101
ANT1 TEST RESULT.....	102
ANT0 TEST GRAPHS	102
ANT1 TEST GRAPHS	105
CONDUCTED SPURIOUS EMISSION	107
ANT0 TEST RESULT.....	107
ANT1 TEST RESULT.....	108
ANT0 TEST GRAPHS	109
ANT1 TEST GRAPHS	112
DUTY CYCLE	115
TEST RESULT	115
TEST GRAPHS.....	115



RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
PSZ-QBJ2501200112RF09	Original release	Mar. 26, 2025



1. SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC PART 15, SUBPART C (SECTION 15.247)			
STANDARD SECTION	TEST TYPE AND LIMIT	RESULT	TEST LAB*
15.207	AC Power Conducted Emission	Compliance	A
15.205 15.209	Radiated Emissions	Compliance	A
15.247(d)	Out of band Emission Measurement	Compliance	A
15.247(a)(2)	6dB bandwidth	Compliance	A
15.247(b)	Conducted Output power	Compliance	A
15.247(e)	Power Spectral Density	Compliance	A
15.203	Antenna Requirement	Compliance	A

Note : Except RSE and AC Power Conducted Emission, other data please refer to Appendix B.

*Test Lab Information Reference

Lab A:

Huarui 7Layers High Technology (Suzhou) Co., Ltd.

Lab Address:

Tower N, Innovation Center, 88 Zuyi Road, High-tech District, Suzhou City, Anhui Province

Accredited Test Lab Cert 6613.01

The FCC Site Registration No. is 434559; The Designation No. is CN1325.




1.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	UNCERTAINTY
AC Power Conducted emissions	±2.70dB
Radiated emissions (9KHz~30MHz)	±2.68dB
Radiated emissions (30MHz~1GHz)	±4.98dB
Radiated emissions (1GHz ~6GHz)	±4.70dB
Radiated emissions (6GHz ~18GHz)	±4.60dB
Radiated emissions (18GHz ~40GHz)	±4.12dB
Conducted emissions	±4.01dB
Occupied Channel Bandwidth	±43.58KHz
Conducted Output power	±2.06dB
Power Spectral Density	±0.85 dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k = 2.



The verdicts in this test report are given according the above diagram:

Case	Measured Value	Uncertainty Range	Verdict
1	below pass mark	below pass mark	Passed
2	below pass mark	within pass mark	Passed
3	above pass mark	within pass mark	Failed
4	above pass mark	above pass mark	Failed

That means, the laboratory applies, as decision rule (see ISO/IEC 17025:2017), the so-called shared risk principle.



2 GENERAL INFORMATION

2.2 GENERAL DESCRIPTION OF EUT

PRODUCT*	Mobile Phone		
BRAND NAME*	POCO		
MODEL NAME*	25053PC47G		
NOMINAL VOLTAGE*	5/3.6-20V dc (adapter or host equipment) 3.93Vdc (Li-ion, battery)		
MODULATION *	BLE	GFSK	
TRANSMISSION RATE*	BT_LE: 1 Mbps/2 Mbps		
OPERATING FREQUENCY	2402-2480MHz for BT-LE		
MAX. OUTPUT POWER	BT-LE: 8.45mW (Maximum)		
ANTENNA GAIN*	BLE	ANT0	-0.02dBi
		ANT1	-2.74dBi
ANTENNA TYPE*	BLE	PIFA	
HW VERSION*	13510O10U		
SW VERSION*	Xiaomi HyperOS 2.0		
I/O PORTS*	Refer to user's manual		
CABLE SUPPLIED*	USB cable1: non-shielded cable, with w/o ferrite core, 1.0 meter USB cable2: non-shielded cable, with w/o ferrite core, 1.0 meter		

NOTE:

- *Since the above data and/or information is provided by the client relevant results or conclusions of this report are only made for these data and/or information, Test Lab is not responsible for the authenticity, integrity and results of the data and information and/or the validity of the conclusion.
- For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
- The EUT incorporates a SISO function. Physically, the EUT provides one completed transmitter and one receiver.

MODULATION MODE	TX/RX FUNCTION
BT_LE(1MHz)	2TX/2RX
BT_LE(2MHz)	2TX/2RX

- For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.
- Antenna gain and EUT conducted cable loss are provided by the customer, and the laboratory will record the results based on these items that involve these two parameters.



2.3 DESCRIPTION OF TEST MODES

BT-LE							
CHANNEL	FREQ. (MHZ)	CHANNEL	FREQ. (MHZ)	CHANNEL	FREQ. (MHZ)	CHANNEL	FREQ. (MHZ)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480



2.2.1 CONFIGURATION OF SYSTEM UNDER TEST

Please see section 4 photographs of the test configuration for reference.

2.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports. The worst case was found when positioned on Y axis for radiated emission. Following test modes were selected for the final test, and the final worst case is marked in boldface and recorded in the report:

EUT CONFIGURE MODE	APPLICABLE TO				MODE
	RE<1G	RE≥1G	PLC	APCM	
-	√	√	√	√	-

Where **RE<1G**: Radiated Emission below 1GHz **RE≥1G**: Radiated Emission above 1GHz
PLC: Power Line Conducted Emission **APCM**: Antenna Port Conducted Measurement

NOTE: No need to concern of Conducted Emission due to the EUT is powered by battery.

RADIATED EMISSION TEST (BELOW 1GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- The following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	DATA RATE (Mbps)
BT-LE	0 to 39	19	GFSK	2



RADIATED EMISSION TEST (ABOVE 1GHz):

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

The following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	DATA RATE (Mbps)
BT-LE	0 to 39	0,19, 39	GFSK	1.0
BT-LE	1 to 38	1,19, 38	GFSK	2.0

BANDEDGE MEASUREMENT:

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

The following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	DATA RATE (Mbps)
BT-LE	0 to 39	0,19, 39	GFSK	1.0
BT-LE	1 to 38	1,19, 38	GFSK	2.0

ANTENNA PORT CONDUCTED MEASUREMENT:

This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

The following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	DATA RATE (Mbps)
BT-LE	0 to 39	0,19, 39	GFSK	1.0
BT-LE	1 to 38	1,19, 38	GFSK	2.0

TEST CONDITION			
APPLICABLE TO	ENVIRONMENTAL CONDITIONS	TEST VOLTAGE	TESTED BY
RE<1G	23deg. C, 70%RH	DC 3.93V By Adapter	Hanwen Xu
RE≥1G	23deg. C, 70%RH	DC 3.93V By Adapter	Hanwen Xu
PLC	25deg. C, 52%RH	DC 3.93V By Adapter	Hanwen Xu
APCM	25deg. C, 60%RH	DC 3.93V By Adapter	Hanwen Xu



2.4 DUTY CYCLE OF TEST SIGNAL

Please Refer to Appendix B Of this test report..

2.5 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C, Section 15.247

KDB 558074 D01 DTS Meas Guidance v05r02

ANSI C63.10-2020

Note :

1. All test items have been performed and recorded as per the above standards.
2. The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (Certification). The test report has been issued separately.



2.6 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	Laptop	Lenovo	Thinkpad E14	SL10W47313	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	USB cable1: non-shielded cable, with w/o ferrite core, 1.0 meter
2	USB cable2: non-shielded cable, with w/o ferrite core, 1.0 meter



3 TEST TYPES AND RESULTS

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB μ V)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.
3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.



3.1.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESR3	102749	Feb.24,24	Feb.23,26
ELEKTRA test software	Rohde&Schwarz	ELEKTRA	NA	N/A	N/A
LISN network	Rohde&Schwarz	ENV216	102640	Feb.16,24	Feb.15,26
CABLE	Rohde&Schwarz	W61.01	N/A	Apr.27,24	Apr.26,26
CABLE	Rohde&Schwarz	W601	N/A	Apr.27,24	Apr.26,26

NOTE:

1. The test was performed in CE shielded room.
2. The calibration interval of the above test instruments is 12/24 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.



3.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.


NOTE: All modes of operation were investigated and the worst-case emissions are reported.

3.1.4 DEVIATION FROM TEST STANDARD

No deviation.



3.1.5 TEST SETUP



- Note:**
- 1.Support units were connected to second LISN.
 - 2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

3.1.6 EUT OPERATING CONDITIONS

- a. Turned on the power and connected of all equipment.
- b. EUT was operated according to the type used was description in manufacturer's specifications or the User's Manual.




3.1.7 TEST RESULTS

CONDUCTED WORST-CASE DATA			
Frequency Range	150KHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120Vac, 60Hz	Environmental Conditions	26deg. C, 51%RH
Tested By	Hanwen Xu		

Rg	Frequency [MHz]	QPK Level [dBμV]	QPK Limit [dBμV]	QPK Margin [dB]	CAV Level [dBμV]	CAV: AVG Limit [dBμV]	CAV Margin [dB]	Correction [dB]	Line	Meas. BW [kHz]
1	0.218	45.94	62.91	16.97	33.02	52.91	19.89	11.97	L1	9.000
1	0.519	31.84	56.00	24.16	10.97	46.00	35.03	11.75	L1	9.000
1	1.410	30.10	56.00	25.90	20.01	46.00	25.99	11.75	L1	9.000
1	4.659	26.86	56.00	29.14	17.30	46.00	28.70	11.79	L1	9.000
1	9.578	29.25	60.00	30.75	20.73	50.00	29.27	11.83	L1	9.000
1	23.528	20.39	60.00	39.61	14.67	50.00	35.33	11.89	L1	9.000

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Limit value -Emission level
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.






Frequency Range	150KHz ~ 30MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120Vac, 60Hz	Environmental Conditions	26deg. C, 51%RH
Tested By	Hanwen Xu		

Rg	Frequency [MHz]	QPK Level [dBμV]	QPK Limit [dBμV]	QPK Margin [dB]	CAV Level [dBμV]	CAV: AVG Limit [dBμV]	CAV Margin [dB]	Correction [dB]	Line	Meas. BW [kHz]
1	0.164	40.02	65.28	25.26	27.36	55.28	27.92	12.18	N	9.000
1	0.501	33.71	56.00	22.29	24.37	46.00	21.63	12.78	N	9.000
1	1.167	27.62	56.00	28.38	20.72	46.00	25.28	12.73	N	9.000
1	3.467	25.98	56.00	30.02	19.27	46.00	26.73	12.75	N	9.000
1	9.123	28.30	60.00	31.70	22.20	50.00	27.80	12.79	N	9.000
1	24.536	25.24	60.00	34.76	19.74	50.00	30.26	12.87	N	9.000

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Limit value -Emission level
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.





3.2 RADIATED EMISSION MEASUREMENT

3.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



3.2.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Pre-Amplifier	R&S	SCU18F1	100815	Aug.29,24	Aug.28,26
Pre-Amplifier	R&S	SCU08F1	101028	Sep.15,24	Sep.14,26
Signal Generator	R&S	SMB100A	182185	Feb.15,24	Feb.14,26
3m Fully-anechoic Chamber	TDK	9m*6m*6m	HRSW-SZ-EMC-01Chamber	Nov.25,22	Nov.24,25
3m Semi-anechoic Chamber	TDK	9m*6m*6m	HRSW-SZ-EMC-02Chamber	Nov.25,22	Nov.24,25
EMI TEST Receiver	R&S	ESW44	101973	Feb.24,24	Feb.23,26
Bilog Antenna	SCHWARZBECK	VULB 9163	1264	Feb.27,24	Feb.26,26
Horn Antenna	ETS-LINDGREN	3117	227836	Aug.21,24	Aug.20,26
Horn Antenna (18GHz-40GHz)	Steatite Q-par Antennas	QMS 00880	23486	Feb.22,24	Feb.21,26
Horn Antenna	Steatite Q-par Antennas	QMS 00208	23485	Aug.21,24	Aug.20,26
Loop Antenna	SCHWARZ	HFH2-Z2/Z2E	100976	Feb.22,24	Feb.21,26
WIDEBANDRADIO COMMUNICATION TESTER	R&S	CMW500	169399	Jun.26,24	Jun.25,26
Test Software	ELEKTRA	ELEKTRA4.32	N/A	N/A	N/A
Open Switch and Control Unit	R&S	OSP220	101964	N/A	N/A
DC Source	HYELEC	HY3010B	551016	Aug.30,24	Aug.29,26
Hygrothermograph	DELI	20210528	SZ014	Sep.05,24	Sep.04,26
6DB attenuator	Tonscend Technology Co., Ltd	N/A	23062787	N/A	N/A
PC	LENOVO	E14	HRSW0024	N/A	N/A
TMC-AMI18843A(CABLE)	R&S	HF290-NMNM-7.00M	N/A	N/A	N/A
TMC-AMI18843A(CABLE)	R&S	HF290-NMNM-4.00M	N/A	N/A	N/A
CABLE	R&S	W13.02	N/A	Apr.27,24	Apr.26,26
CABLE	R&S	W12.14	N/A	Apr.27,24	Apr.26,26

NOTE:

1. The calibration interval of the above test instruments is 12/ 24 / 36 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
2. The test was performed in 3m Chamber.
3. The FCC Site Registration No. is 434559; The Designation No. is CN1325.



3.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters (for below 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, For battery operated equipment, the equipment tests shall be perform using fresh batteries. The turntable was rotated to maximize the emission level.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for RMS Average (Duty cycle < 98%) for Average detection (AV) at frequency above 1GHz, then the measurement results was added to a correction factor ($10 \log(1/\text{duty cycle})$).
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.
5. All modes of operation were investigated and the worst-case emissions are reported.


3.2.4 DEVIATION FROM TEST STANDARD

No deviation





3.2.5 TEST SETUP

<Frequency Range 9KHz~30MHz >



< Frequency Range 30MHz~1GHz >



<Frequency Range above 1GHz>

Note: Above 1G is a directional antenna

Depends on the EUT height and the antenna 3dB beamwidth both, refer to section 7.3 of CISPR 16-2-3.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

3.2.6 EUT OPERATING CONDITIONS

- a. Set the EUT under full load condition and placed them on a testing table.
- b. Set the transmitter part of EUT under transmission condition continuously at specific channel frequency.
- c. The necessary accessories enable the EUT in full functions.



3.2.7 TEST RESULTS

ANT 0


BELOW 1GHz WORST-CASE DATA

BT-LE_2M			
CHANNEL	TX Channel 19	ODETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M									
Rg	Frequency [MHz]	QPK Level [dBμV/m]	QPK Limit [dBμV/m]	QPK Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]	Meas. BW [kHz]
1	45.763	31.22	40.00	8.78	-2.91	H	359.1	1.00	120.000
1	96.057	24.49	43.50	19.01	-5.80	H	55.9	2.00	120.000
1	192.184	21.89	43.50	21.61	-4.89	H	5.6	1.00	120.000
1	286.856	23.53	46.00	22.47	-0.47	H	147.5	1.00	120.000
1	425.566	26.58	46.00	19.42	3.79	H	5.6	1.00	120.000
1	507.919	27.63	46.00	18.37	3.41	H	212.5	2.00	120.000

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Limit value – Emission Level






CHANNEL		TX Channel 19			DETECTOR FUNCTION		Quasi-Peak (QP)		
FREQUENCY RANGE		30MHz ~ 1GHz							
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M									
Rg	Frequency [MHz]	QPK Level [dBμV/m]	QPK Limit [dBμV/m]	QPK Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]	Meas. BW [kHz]
1	34.268	34.54	40.00	5.46	-7.66	V	294.5	1.00	120.000
1	45.181	29.81	40.00	10.19	-4.09	V	355.1	2.00	120.000
1	76.851	21.69	40.00	18.31	-10.75	V	355.1	2.00	120.000
1	154.839	20.54	43.50	22.96	-7.51	V	355.1	2.00	120.000
1	185.734	21.95	43.50	21.55	-5.66	V	355.1	2.00	120.000
1	280.600	22.58	46.00	23.42	-1.16	V	145	1.00	120.000

REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Limit value – Emission Level






ABOVE 1GHz TEST DATA

Note:

1. For radiated emissions testing , the full testing range of different modes have been scanned , only the worst case harmonic data is reported in the sheet.
2. All other emissions were greater than 20dB below the limit was not recorded





ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M


Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
5	2,387.500	31.84	54.00	22.16	6.51	H	158.6	2.00
5	2,390.000	31.76	54.00	22.24	6.52	H	1.2	2.00
5	2,402.000	91.52			6.53	H	5	1.00





ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M


Rg	Frequency [MHz]	PK+ Level [dB μ V/m]	PK+ Limit [dB μ V/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
5	2,314.500	46.69	74.00	27.31	6.44	V	41.1	1.00
5	2,390.000	45.61	74.00	28.39	6.52	V	359.1	1.00
5	2,402.500	87.30			6.53	V	224.5	2.00





ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
5	2,386.000	31.82	54.00	22.18	6.51	V	4.2	1.00
5	2,390.000	31.71	54.00	22.29	6.52	V	11.2	2.00
5	2,402.000	77.72			6.53	V	45.8	1.00



REMARKS:


1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
2. Margin value = Limit value–Emission level.
3. 2402MHz: Fundamental frequency.



CHANNEL	TX Channel 19	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M


Rg	Frequency [MHz]	PK+ Level [dBµV/m]	PK+ Limit [dBµV/m]	PK+ Margin [dB]	AVG Level [dBµV/m]	AVG Limit [dBµV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	4,880.000	50.23	74.00	23.77	39.47	54.00	14.53	14.77	H	359	2.00
2	7,320.000	55.90	74.00	18.10	44.89	54.00	9.11	21.11	H	359	2.00





ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBµV/m]	PK+ Limit [dBµV/m]	PK+ Margin [dB]	AVG Level [dBµV/m]	AVG Limit [dBµV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	4,880.000	50.68	74.00	23.32	39.63	54.00	14.37	14.77	V	1	1.00
2	7,320.000	54.70	74.00	19.30	44.83	54.00	9.17	21.11	V	20.6	2.00



REMARKS:


1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
2. Margin value = Limit value–Emission level.
3. 2440MHz: Fundamental frequency.



CHANNEL	TX Channel 39	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M


Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
6	2,480.250	98.62			6.81	H	77.4	2.00
6	2,483.500	52.05	74.00	21.95	6.80	H	77.4	2.00
6	2,485.250	47.49	74.00	26.51	6.80	H	77.4	2.00





ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M


Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
6	2,480.000	91.76			6.81	H	58.3	2.00
6	2,483.500	32.27	54.00	21.73	6.80	H	58.3	2.00
6	2,485.000	32.08	54.00	21.92	6.80	H	58.3	2.00





ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M


Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
6	2,479.750	89.23			6.81	V	76.2	2.00
6	2,483.500	45.83	74.00	28.17	6.80	V	1	2.00
6	2,484.000	46.99	74.00	27.01	6.80	V	1	2.00






ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
6	2,480.000	78.41			6.81	V	58.3	2.00
6	2,483.500	31.83	54.00	22.17	6.80	V	211.3	2.00
6	2,492.000	32.01	54.00	21.99	6.80	V	2.8	2.00



REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
2. Margin value = Limit value–Emission level.
3. 2480MHz: Fundamental frequency.





ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M


Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
5	2,387.500	31.84	54.00	22.16	6.51	H	212.5	2.00
5	2,390.000	31.78	54.00	22.22	6.52	H	359	2.00
5	2,404.000	82.99			6.54	H	57.1	2.00





ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M


Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
5	2,383.500	46.35	74.00	27.65	6.51	V	193	1.00
5	2,390.000	45.78	74.00	28.22	6.52	V	359	1.00
5	2,404.500	86.36			6.54	V	217.3	2.00






ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
5	2,386.500	31.82	54.00	22.18	6.51	V	110.8	2.00
5	2,390.000	31.72	54.00	22.28	6.52	V	1	1.00
5	2,404.000	70.47			6.54	V	58.3	2.00



REMARKS:


1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
2. Margin value = Limit value–Emission level.
3. 2404MHz: Fundamental frequency.





ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBµV/m]	PK+ Limit [dBµV/m]	PK+ Margin [dB]	AVG Level [dBµV/m]	AVG Limit [dBµV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	4,880.000	50.05	74.00	23.95	39.53	54.00	14.47	14.77	V	260.3	2.00
2	7,320.000	55.78	74.00	18.22	44.90	54.00	9.10	21.11	V	94.8	1.00



REMARKS:


1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor.
2. Margin value = Limit value–Emission level.
3. 2440MHz: Fundamental frequency.



CHANNEL	TX Channel 38	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M


Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
6	2,478.500	97.72			6.81	H	65.5	2.00
6	2,483.500	47.91	74.00	26.09	6.80	H	1	1.00
6	2,493.750	47.19	74.00	26.81	6.80	H	359.1	1.00





ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M


Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
6	2,478.000	82.66			6.81	H	64.3	2.00
6	2,483.500	31.92	54.00	22.08	6.80	H	0.9	2.00
6	2,491.750	32.04	54.00	21.96	6.80	H	213.8	2.00





ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M


Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
6	2,477.500	86.56			6.81	V	65.4	2.00
6	2,483.500	46.33	74.00	27.67	6.80	V	355	1.00
6	2,493.500	47.13	74.00	26.87	6.80	V	359	1.00





ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
6	2,478.000	71.34			6.81	V	63	2.00
6	2,483.500	31.81	54.00	22.19	6.80	V	1	2.00
6	2,490.500	32.01	54.00	21.99	6.80	V	294.6	1.00



REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
2. Margin value = Limit value–Emission level.
3. 2478MHz: Fundamental frequency.



ANT 1

BELOW 1GHz WORST-CASE DATA


BT-LE_2M			
CHANNEL	TX Channel 19	ODETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	QPK Level [dBμV/m]	QPK Limit [dBμV/m]	QPK Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]	Meas. BW [kHz]
1	44.211	30.98	40.00	9.02	-3.08	H	359	1.00	120.000
1	94.748	26.89	43.50	16.61	-6.05	H	302.9	1.00	120.000
1	144.460	27.86	43.50	15.64	-8.46	H	61.8	2.00	120.000
1	184.376	28.36	43.50	15.14	-6.14	H	61.8	2.00	120.000
1	287.729	23.41	46.00	22.59	-0.44	H	148.7	1.00	120.000
1	504.088	27.83	46.00	18.17	3.34	H	212.5	2.00	120.000

REMARKS:

- Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
- Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
- The other emission levels were very low against the limit.
- Margin value = Limit value – Emission Level






CHANNEL		TX Channel 19		DETECTOR FUNCTION		Quasi-Peak (QP)			
FREQUENCY RANGE		30MHz ~ 1GHz							
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M									
Rg	Frequency [MHz]	QPK Level [dBμV/m]	QPK Limit [dBμV/m]	QPK Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]	Meas. BW [kHz]
1	33.977	30.35	40.00	9.65	-7.74	V	1	2.00	120.000
1	50.370	29.65	40.00	10.35	-3.88	V	1	2.00	120.000
1	94.748	29.34	43.50	14.16	-6.03	V	1	1.00	120.000
1	183.018	21.43	43.50	22.07	-5.97	V	59.5	2.00	120.000
1	434.345	26.07	46.00	19.93	3.39	V	151.1	1.00	120.000
1	607.878	29.38	46.00	16.62	3.83	V	151.1	1.00	120.000

REMARKS:

5. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
6. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
7. The other emission levels were very low against the limit.
8. Margin value = Limit value – Emission Level





ABOVE 1GHz TEST DATA


Note:

- 4. For radiated emissions testing , the full testing range of different modes have been scanned , only the worst case harmonic data is reported in the sheet.
- 5. All other emissions were greater than 20dB below the limit was not recorded

BT-LE _1M			
CHANNEL	TX Channel 0	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
5	2,382.000	47.13	74.00	26.87	6.50	H	49.9	2.00
5	2,390.000	45.63	74.00	28.37	6.52	H	257.4	1.00
5	2,402.000	98.45			6.53	H	259	2.00



Legend: PK+ Level@CriticalPoint, PK+ Level@Spectrum Overview, PK+ Limit@BT2.0&BLE CH0(XIAO MI)



ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M


Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
5	2,387.500	31.86	54.00	22.14	6.51	H	352.2	1.00
5	2,390.000	31.73	54.00	22.27	6.52	H	352.2	1.00
5	2,402.000	89.89			6.53	H	210	2.00





ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M


Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
5	2,378.500	46.46	74.00	27.54	6.50	V	206.6	2.00
5	2,390.000	45.97	74.00	28.03	6.52	V	359.1	1.00
5	2,402.000	91.12			6.53	V	206.6	2.00





ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
5	2,387.000	31.85	54.00	22.15	6.51	V	355.8	2.00
5	2,390.000	31.75	54.00	22.25	6.52	V	49.5	1.00
5	2,402.000	82.84			6.53	V	209	2.00



REMARKS:

- Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
- Margin value = Limit value–Emission level.
- 2402MHz: Fundamental frequency.