



BUREAU
VERITAS

Test Report No.: PSZ-QBJ2501200112RF02



Certificate #6613.01

FCC TEST REPORT (PART 24)

Applicant:	Xiaomi Communications Co., Ltd.
Address:	#019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085

Manufacturer or Supplier:	Xiaomi Communications Co., Ltd.
Address:	#019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085
Product:	Mobile Phone
Brand Name:	POCO
Model Name:	25053PC47G
FCC ID	2AFZZPC47G
Date of tests	Feb. 13, 2025-Mar. 26, 2025

The tests have been carried out according to the requirements of the following standard:

- | | |
|---|---|
| <input checked="" type="checkbox"/> FCC PART 24, Subpart E | <input checked="" type="checkbox"/> ANSI/TIA/EIA-603-E |
| <input checked="" type="checkbox"/> FCC PART 2 | <input checked="" type="checkbox"/> ANSI C63.26-2015 |
| <input checked="" type="checkbox"/> ANSI/TIA/EIA-603-D | |

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Prepared by Hanwen Xu Engineer / Mobile Department	Approved by Peibo Sun Manager / Mobile Department
Date: Mar. 26, 2025	Date: Mar. 26, 2025

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

Huarui 7layers High Technology
(Suzhou) Co., Ltd.

Tower N, Innovation Center, 88 Zuyi Road, High-tech District,
Suzhou City, Anhui Province

Tel: +86 (0557)
368 1008



TABLE OF CONTENTS

RELEASE CONTROL RECORD	4
1 SUMMARY OF TEST RESULTS.....	5
1.1 MEASUREMENT UNCERTAINTY	6
1.2 TEST SITE AND INSTRUMENTS	7
2 GENERAL INFORMATION	8
2.1 GENERAL DESCRIPTION OF EUT	8
2.2 CONFIGURATION OF SYSTEM UNDER TEST	10
2.3 DESCRIPTION OF SUPPORT UNITS	11
2.4 TEST ITEM AND TEST CONFIGURATION.....	11
2.5 EUT OPERATING CONDITIONS	15
2.6 GENERAL DESCRIPTION OF APPLIED STANDARDS	15
3 TEST TYPES AND RESULTS.....	16
3.1 OUTPUT POWER MEASUREMENT.....	16
3.1.1 LIMITS OF OUTPUT POWER MEASUREMENT.....	16
3.1.2 TEST PROCEDURES	16
3.1.3 TEST SETUP.....	17
3.1.4 TEST RESULTS	17
3.2 FREQUENCY STABILITY MEASUREMENT.....	37
3.2.1 LIMITS OF FREQUENCY STABILITY MEASUREMENT.....	37
3.2.2 TEST PROCEDURE.....	37
3.2.3 TEST SETUP.....	37
3.2.4 TEST RESULTS	37
3.3 OCCUPIED BANDWIDTH MEASUREMENT	38
3.3.1 LIMITS OF OCCUPIED BANDWIDTH MEASUREMENT	38
3.3.2 TEST SETUP.....	38
3.3.3 TEST PROCEDURES	38
3.3.4 TEST RESULTS	38
3.4 BAND EDGE MEASUREMENTC	39
3.4.1 LIMITS OF BAND EDGE MEASUREMENT	39
3.4.2 TEST SETUP.....	39
3.4.3 TEST PROCEDURES	40
3.4.4 TEST RESULTS	40
3.5 CONDUCTED SPURIOUS EMISSIONS	41
3.5.1 LIMITS OF CONDUCTED SPURIOUS EMISSIONS MEASUREMENT	41
3.5.2 TEST PROCEDURE.....	41
3.5.3 TEST SETUP.....	41
3.5.4 TEST RESULTS	41
3.6 RADIATED EMISSION MEASUREMENT	42
3.6.1 LIMITS OF RADIATED EMISSION MEASUREMENT	42
3.6.2 TEST PROCEDURES	42
3.6.3 DEVIATION FROM TEST STANDARD	42
3.6.4 TEST SETUP.....	43
3.6.5 TEST RESULTS	45



BUREAU VERITAS Test Report No.: PSZ-QBJ2501200112RF02

3.7	PEAK TO AVERAGE RATIO	81
3.7.1	LIMITS OF PEAK TO AVERAGE RATIO MEASUREMENT	81
3.7.2	TEST SETUP	81
3.7.3	TEST PROCEDURES	81
3.7.4	TEST RESULTS	81
4	INFORMATION ON THE TESTING LABORATORIES	82
5	MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB	83
6	APPENDIX.....	84



BUREAU
VERITAS

Test Report No.: PSZ-QBJ2501200112RF02

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
PSZ-QBJ2501200112RF02	Original release	Mar. 26, 2025



1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 24 & Part 2			
STANDARD SECTION	TEST TYPE	RESULT	Test lab*
§2.1046	Conducted Output Power	Compliance	A
§24.232(c)	Equivalent Isotropic Radiated Power	Compliance	A
§2.1055 §24.235	Frequency Stability	Compliance	A
§2.1049	Occupied Bandwidth	Compliance	A
§24.232(d)	Peak to average ratio*	Compliance	A
§24.238(a)(b)	Band Edge Measurements	Compliance	A
§2.1051 §24.238(a)(b)	Conducted Spurious Emissions	Compliance	A
§2.1053 §24.238(a)(b)	Radiated Spurious Emissions	Compliance	A

* Refer to KDB 971168 D01 Power Meas License Digital Systems v03r01.

*Test Lab Information Reference

Lab A:

Huarui 7Layers High Technology (Suzhou) Co., Ltd.

Lab Address:

Tower N, Innovation Center, 88 Zuyi Road, High-tech District, Suzhou City, Anhui Province

Accredited Test Lab Cert 6613.01

The FCC Site Registration No. is 434559; The Designation No. is CN1325.




1.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	UNCERTAINTY
Frequency Stability	±76.97Hz
Radiated emissions (9KHz~30MHz)	±2.68dB
Radiated emissions & Radiated Power (30MHz~1GHz)	±4.98dB
Radiated emissions & Radiated Power (1GHz ~6GHz)	±4.70dB
Radiated emissions (6GHz ~18GHz)	±4.60dB
Radiated emissions (18GHz ~40GHz)	±4.12dB
Conducted emissions	±4.01dB
Occupied Channel Bandwidth	±43.58KHz
Conducted Output power	±2.06dB
Band Edge Measurements	±4.70dB
Peak to average ratio	±0.76dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.



The verdicts in this test report are given according the above diagram:

Case	Measured Value	Uncertainty Range	Verdict
1	below pass mark	below pass mark	Passed
2	below pass mark	within pass mark	Passed
3	above pass mark	within pass mark	Failed
4	above pass mark	above pass mark	Failed

That means, the laboratory applies, as decision rule (see ISO/IEC 17025:2017), the so-called shared risk principle.



1.2 TEST SITE AND INSTRUMENTS

2	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
	Pre-Amplifier	R&S	SCU18F1	100815	Aug.29,24	Aug.28,26
	Pre-Amplifier	R&S	SCU08F1	101028	Sep.15,24	Sep.14,26
	Vector Signal Generator	R&S	SMBV100B	102176	Feb.15,24	Feb.14,26
	Signal Generator	R&S	SMB100A	182185	Feb.15,24	Feb.14,26
	3m Fully-anechoic Chamber	TDK	9m*6m*6m	HRSW-SZ-EMC-01Chamber	Nov.25,22	Nov.24,25
	3m Semi-anechoic Chamber	TDK	9m*6m*6m	HRSW-SZ-EMC-02Chamber	Nov.25,22	Nov.24,25
	EMI TEST Receiver	R&S	ESR26	101734	Feb.24,24	Feb.23,26
	EMI TEST Receiver	R&S	ESW44	101973	Feb.24,24	Feb.23,26
	Bilog Antenna	SCHWARZBECK	VULB 9163	1264	Feb.27,24	Feb.26,26
	Horn Antenna	ETS-LINDGREN	3117	227836	Aug.21,24	Aug.20,26
	Horn Antenna (18GHz-40GHz)	Steatite Q-par Antennas	QMS 00880	23486	Feb.22,24	Feb.21,26
	Horn Antenna	Steatite Q-par Antennas	QMS 00208	23485	Aug.21,24	Aug.20,26
	Loop Antenna	SCHWARZ	HFH2-Z2/Z2E	100976	Feb.22,24	Feb.21,26
	WIDEBANDRADIO COMMUNICATION TESTER	R&S	CMW500	169399	Jun.26,24	Jun.25,26
	Test Software	EMC32	EMC32	N/A	N/A	N/A
	Test Software	ELEKTRA	ELEKTRA4.32	N/A	N/A	N/A
	Open Switch and Control Unit	R&S	OSP220	101964	Sep.30,24	Sep.39,26
	DC Source	HYELEC	HY3010B	551016	Aug.30,24	Aug.29,26
	Hygrothermograph	DELI	20210528	SZ014	Sep.05,24	Sep.04,26
	PC	LENOVO	E14	HRSW0024	N/A	N/A
	TMC-AMI18843A(CABLE)	R&S	HF290-NMNM-7.00M	N/A	N/A	N/A
	TMC-AMI18843A(CABLE)	R&S	HF290-NMNM-4.00M	N/A	N/A	N/A
	CABLE	R&S	W13.02	N/A	Apr.26,24	Oct.25,25
	CABLE	R&S	W12.14	N/A	Apr.26,24	Oct.25,25
	CABLE	R&S	J12J103539-00-1	SEP-03-20-069	Apr.26,24	Oct.25,25
	CABLE	R&S	J12J103539-00-1	SEP-03-20-070	Apr.26,24	Oct.25,25
	Temperature Chamber	votsch	VT4002	58566078100050	May.30,24	May.29,26

NOTE:

1. The calibration interval of the above test instruments is 12/24/36 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
2. The test was performed in 3m Semi-anechoic Chamber and RF Oven Room.
3. The horn antenna is used only for the measurement of emission frequency above 1GHz if tested.
4. The FCC Site Registration No. is 434559; The Designation No. is CN1325.



3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT*	Mobile Phone	
BRAND NAME*	POCO	
MODEL NAME*	25053PC47G	
NOMINAL VOLTAGE*	5/3.6-20V dc (adapter or host equipment) 3.93Vdc (Li-ion, battery)	
MODULATION TYPE*	GSM/GPRS: GMSK EDGE: 8PSK WCDMA: QPSK, 16QAM LTE Band 2: QPSK, 16QAM, 64QAM, 256QAM	
FREQUENCY RANGE	GPRS, EDGE	1850.2MHz ~ 1909.8MHz
	WCDMA	1852.4MHz ~ 1907.6MHz
	LTE Band 2 Channel Bandwidth: 1.4MHz	1850.7MHz ~ 1909.3MHz
	LTE Band 2 Channel Bandwidth: 3MHz	1851.5MHz ~ 1908.5MHz
	LTE Band 2 Channel Bandwidth: 5MHz	1852.5MHz ~ 1907.5MHz
	LTE Band 2 Channel Bandwidth: 10MHz	1855.0MHz ~ 1905.0MHz
	LTE Band 2 Channel Bandwidth: 15MHz	1857.5MHz ~ 1902.5MHz
	LTE Band 2 Channel Bandwidth: 20MHz	1860.0MHz ~ 1900.0MHz
MAX. EIRP POWER	GSM/GPRS	644.17mW
	EDGE	260.02mW
	WCDMA	177.01mW
	LTE Band 2 Channel Bandwidth: 1.4MHz	158.85mW
	LTE Band 2 Channel Bandwidth: 3MHz	157.40mW
	LTE Band 2 Channel Bandwidth: 5MHz	161.44mW
	LTE Band 2 Channel Bandwidth: 10MHz	159.59mW
	LTE Band 2 Channel Bandwidth: 15MHz	157.04mW
	LTE Band 2 Channel Bandwidth: 20MHz	161.81mW
EMISSION DESIGNATOR	GPRS	318KGXW



	EDGE	316KG7W	
	WCDMA	4M71F9W	
	LTE Band 2 Channel Bandwidth: 1.4MHz	QPSK: 1M10G7D	
		16QAM: 1M10W7D	
	LTE Band 2 Channel Bandwidth: 3MHz	QPSK: 2M70G7D	
		16QAM: 2M70W7D	
	LTE Band 2 Channel Bandwidth: 5MHz	QPSK: 4M49G7D	
		16QAM: 4M49W7D	
LTE Band 2 Channel Bandwidth: 10MHz	QPSK: 8M98G7D		
	16QAM: 8M97W7D		
LTE Band 2 Channel Bandwidth: 15MHz	QPSK: 13M5G7D		
	16QAM: 13M5W7D		
LTE Band 2 Channel Bandwidth: 20MHz	QPSK: 17M9G7D		
	16QAM: 17M9W7D		
ANTENNA GAIN*	GSM1900/ WCDMA II/LTE B2	ANT2	-1.7dBi
		ANT3	-4.87dBi
ANTENNA TYPE*	PIFA		
HW VERSION*	13510O10U		
SW VERSION*	Xiaomi HyperOS 2.0		
I/O PORTS*	Refer to user's manual		
CABLE SUPPLIED*	USB cable1: non-shielded cable, with w/o ferrite core, 1.0 meter USB cable2: non-shielded cable, with w/o ferrite core, 1.0 meter		
EXTREME TEMPERATURE*	0°C-40°C		
EXTREME VOLTAGE*	3.8V-4.3V		

NOTE:

- *Since the above data and/or information is provided by the client relevant results or conclusions of this report are only made for these data and/or information , Test Lab is not responsible for the authenticity, integrity and results of the data and information and/or the validity of the conclusion.
- For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
- The EUT incorporates a SISO function. Physically, the EUT provides two completed transmitter and two receivers.



MODULATION MODE	TX FUNCTION
GSM/GPRS/EDGE	2TX/2RX
WCDMA	2TX/2RX
LTE	2TX/2RX

- For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.



3.2 CONFIGURATION OF SYSTEM UNDER TEST

FOR RADIATION EMISSION TEST





3.3 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	Laptop	Lenovo	ThinkPad E14	HRSW00024	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	USB cable1: non-shielded cable, with w/o ferrite core, 1.0 meter
2	USB cable2: non-shielded cable, with w/o ferrite core, 1.0 meter

3.4 TEST ITEM AND TEST CONFIGURATION

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports. The worst case in EIRP and radiated emission was found when positioned on X-plane for GSM/EDGE/ LTE. Following channel(s) was (were) selected for the final test as listed below:

EUT CONFIGURE MODE	DESCRIPTION
A	EUT + Adapter with GSM or WCDMA or LTE link
B	EUT + DC Supply with GSM or WCDMA or LTE link

GSM MODE				
EUT CONFIGURE MODE	TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	MODE
A	EIRP	512 to 810	512, 661, 810	GSM,EDGE
B	FREQUENCY STABILITY	512 to 810	512, 661, 810	GSM,EDGE
A	OCCUPIED BANDWIDTH	512 to 810	512, 661, 810	GSM,EDGE
A	PEAK TO AVERAGE RATIO	512 to 810	512, 661, 810	GSM,EDGE
A	BAND EDGE	512 to 810	512, 810	GSM,EDGE
A	CONDCUDED EMISSION	512 to 810	512, 661, 810	GSM,EDGE
A	RADIATED EMISSION	512 to 810	512, 661, 810	GSM,EDGE



WCDMA				
EUT CONFIGURE MODE	TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	MODE
A	EIRP	9262 to 9538	9262, 9400, 9538	WCDMA
B	FREQUENCY STABILITY	9262 to 9538	9262, 9400, 9538	WCDMA
A	OCCUPIED BANDWIDTH	9262 to 9538	9262, 9400, 9538	WCDMA
A	PEAK TO AVERAGE RATIO	9262 to 9538	9262, 9400, 9538	WCDMA
A	BAND EDGE	9262 to 9538	9262, 9538	WCDMA
A	CONDCUDED EMISSION	9262 to 9538	9262, 9400, 9538	WCDMA
A	RADIATED EMISSION	9262 to 9538	9262, 9400, 9538	WCDMA

LTE BAND 2 MODE						
EUT CONFIGURE MODE	TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	CHANNEL BANDWIDTH	MODULATION	MODE
A	EIRP	18607 to 19193	18607, 18900, 19193	1.4MHz	QPSK,16QAM,64QAM,256QAM	1 RB / 0 RB offset
		18615 to 19185	18615, 18900, 19185	3MHz	QPSK,16QAM,64QAM,256QAM	1 RB / 0 RB offset
		18625 to 19175	18625, 18900, 19175	5MHz	QPSK,16QAM,64QAM,256QAM	1 RB / 0 RB offset
		18650 to 19150	18650, 18900, 19150	10MHz	QPSK,16QAM,64QAM,256QAM	1 RB / 0 RB offset
		18675 to 19125	18675, 18900, 19125	15MHz	QPSK,16QAM,64QAM,256QAM	1 RB / 0 RB offset
		18700 to 19100	18700, 18900, 19100	20MHz	QPSK,16QAM,64QAM,256QAM	1 RB / 0 RB offset
B	FREQUENCY STABILITY	18650 to 19150	18650, 18900, 19150	20MHz	QPSK	Full RB / 0 RB Offset
A	OCCUPIED BANDWIDTH	18607 to 19193	18607, 18900, 19193	1.4MHz	QPSK,16QAM	Full RB / 0 RB Offset
		18615 to 19185	18615, 18900, 19185	3MHz	QPSK,16QAM	Full RB / 0 RB Offset
		18625 to 19175	18625, 18900, 19175	5MHz	QPSK,16QAM	Full RB / 0 RB Offset
		18650 to 19150	18650, 18900, 19150	10MHz	QPSK,16QAM	Full RB / 0 RB Offset
		18675 to 19125	18675, 18900, 19125	15MHz	QPSK,16QAM	Full RB / 0 RB Offset
		18700 to 19100	18700, 18900, 19100	20MHz	QPSK,16QAM	Full RB / 0 RB Offset



BUREAU VERITAS Test Report No.: PSZ-QBJ2501200112RF02

A	PEAK TO AVERAGE RATIO	18700 to 19100	18700, 18900, 19100	20MHz	QPSK	1 RB / 0 RB Offset Full RB / 0 RB Offset
A	BAND EDGE	18607 to 19193	18607	1.4MHz	QPSK,16QAM, 64QAM, 256QAM	1 RB / 0 RB Offset Full RB / 0 RB Offset
			19193	1.4MHz	QPSK,16QAM, 64QAM, 256QAM	1 RB / 5 RB Offset Full RB / 0 RB Offset
		18615 to 19185	18615	3MHz	QPSK,16QAM, 64QAM, 256QAM	1 RB / 0 RB Offset Full RB / 0 RB Offset
			19185	3MHz	QPSK,16QAM, 64QAM, 256QAM	1 RB / 14 RB Offset Full RB / 0 RB Offset
		18625 to 19175	18625	5MHz	QPSK,16QAM, 64QAM, 256QAM	1 RB / 0 RB Offset Full RB / 0 RB Offset
			19175	5MHz	QPSK,16QAM, 64QAM, 256QAM	1 RB / 24 RB Offset Full RB / 0 RB Offset
		18650 to 19150	18650	10MHz	QPSK,16QAM, 64QAM, 256QAM	1 RB / 0 RB Offset Full RB / 0 RB Offset
			19150	10MHz	QPSK,16QAM, 64QAM, 256QAM	1 RB / 49 RB Offset Full RB / 0 RB Offset
		18675 to 19125	18675	15MHz	QPSK,16QAM, 64QAM, 256QAM	1 RB / 0 RB Offset Full RB / 0 RB Offset
			19125	15MHz	QPSK,16QAM, 64QAM, 256QAM	1 RB / 74 RB Offset Full RB / 0 RB Offset
		18700 to 19100	18700	20MHz	QPSK,16QAM, 64QAM, 256QAM	1 RB / 0 RB Offset Full RB / 0 RB Offset
			19100	20MHz	QPSK,16QAM, 64QAM, 256QAM	1 RB / 99 RB Offset Full RB / 0 RB Offset



BUREAU VERITAS Test Report No.: PSZ-QBJ2501200112RF02

A	CONDCUDED EMISSION	18607 to 19193	18607, 18900, 19193	1.4MHz	QPSK	1 RB / 0 RB Offset
		18615 to 19185	18615, 18900, 19185	3MHz	QPSK	1 RB / 0 RB Offset
		18625 to 19175	18625, 18900, 19175	5MHz	QPSK	1 RB / 0 RB Offset
		18650 to 19150	18650, 18900, 19150	10MHz	QPSK	1 RB / 0 RB Offset
		18675 to 19125	18675, 18900, 19125	15MHz	QPSK	1 RB / 0 RB Offset
		18700 to 19100	18700, 18900, 19100	20MHz	QPSK	1 RB / 0 RB Offset
A	RADIATED EMISSION	18607 to 19193	18900	1.4MHz	QPSK	1 RB / 0 RB Offset
		18615 to 19185	18900	3MHz	QPSK	1 RB / 0 RB Offset
		18625 to 19175	18900	5MHz	QPSK	1 RB / 0 RB Offset
		18650 to 19150	18650, 18900, 19150	10MHz	QPSK	1 RB / 0 RB Offset
		18675 to 19125	18900	15MHz	QPSK	1 RB / 0 RB Offset
		18700 to 19100	18900	20MHz	QPSK	1 RB / 0 RB Offset

Note: 1. This device was tested under all bandwidths, RB configurations and modulations. The worst case was found in QPSK modulation.

TEST CONDITION			
TEST ITEM	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
ERP	23deg. C, 70%RH	DC 3.93V By Battery	Hanwen Xu
FREQUENCY STABILITY	23deg. C, 70%RH	DC 5V By DC Source	Hanwen Xu
OCCUPIED BANDWIDTH	23deg. C, 70%RH	DC 3.93V By Battery	Hanwen Xu
BAND EDGE	23deg. C, 70%RH	DC 3.93V By Battery	Hanwen Xu
CONDCUDED EMISSION	23deg. C, 70%RH	DC 3.93V By Battery	Hanwen Xu
RADIATED EMISSION	23deg. C, 70%RH	AC 120V/60MHz	Hanwen Xu
PEAK TO AVERAGE RATIO	23deg. C, 70%RH	DC 3.93V By Battery	Hanwen Xu



3.5 EUT OPERATING CONDITIONS

The EUT makes a call to the communication simulator. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency.

3.6 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC 47 CFR Part 2

FCC 47 CFR Part 24

KDB 971168 D01 Power Meas License Digital Systems v03r01

ANSI/TIA/EIA-603-D

ANSI/TIA/EIA-603-E

ANSI C63.26-2015

NOTE: All test items have been performed and recorded as per the above standards.



4 TEST TYPES AND RESULTS

4.1 OUTPUT POWER MEASUREMENT

4.1.1 LIMITS OF OUTPUT POWER MEASUREMENT

Mobile and portable stations are limited to 2 watts EIRP.

4.1.2 TEST PROCEDURES

EIRP MEASUREMENT:

Per KDB 971168 D01 Power Meas License Digital Systems v03r01 or subclause 5.2.5.5 of ANSI C63.26-2015, the relevant equation for determining the ERP or EIRP from the conducted RF output power measured using the guidance provided above is:

$$\text{ERP or EIRP} = P_{\text{Meas}} + G_{\text{T}} - L_{\text{C}}$$

Where:

ERP or EIRP = effective radiated power or equivalent isotropically radiated power, respectively

(expressed in the same units as P_{Meas} , typically dBW or dBm);

P_{Meas} = measured transmitter output power or PSD, in dBm or dBW;

G_{T} = gain of the transmitting antenna, in dBd (ERP) or dBi (EIRP);

L_{C} = signal attenuation in the connecting cable between the transmitter and antenna, in dB.


CONDUCTED POWER MEASUREMENT:

The EUT was set up for the maximum power with WCDMA link data modulation and link up with simulator. Set the EUT to transmit under low, middle and high channel and record the power level shown on simulator.



4.1.3 TEST SETUP

EIRP / ERP Measurement:
CONDUCTED POWER MEASUREMENT:



4.1.4 TEST RESULTS

CONDUCTED OUTPUT POWER (dBm) :

Band	GSM1900_Ant2			GSM1900_Ant3		
	512	661	810	512	661	810
Channel	512	661	810	512	661	810
Frequency (MHz)	1850.2	1880	1909.8	1850.2	1880	1909.8
GSM	29.23	29.62	29.79	28.97	29.28	29.50
GPRS 1Tx Slot	29.26	29.44	29.74	28.95	29.27	29.48
GPRS 2Tx Slot	27.07	27.27	27.08	26.65	26.73	26.93
GPRS 3Tx Slot	25.26	25.08	25.35	24.35	24.63	24.71
GPRS 4Tx Slot	23.70	23.89	23.95	23.66	23.91	23.96
EDGE 1Tx Slot	25.38	25.74	25.85	25.86	25.91	25.96
EDGE 2Tx Slot	23.19	23.08	22.98	23.69	23.74	23.75
EDGE 3Tx Slot	21.42	21.47	21.17	21.85	21.97	21.99
EDGE 4Tx Slot	20.23	20.09	19.97	20.64	20.74	20.79

Band	WCDMA II_Ant2			WCDMA II_Ant3		
	9262	9400	9538	9262	9400	9538
TX Channel	9262	9400	9538	9262	9400	9538
Rx Channel	9662	9800	9938	9662	9800	9938
Frequency (MHz)	1852.4	1880	1907.6	1852.4	1880	1907.6
RMC 12.2K	24.18	23.98	23.91	23.91	23.98	23.68
HSDPA Subtest-1	22.64	23.03	22.77	22.61	22.73	22.58
HSDPA Subtest-2	22.77	22.71	23.10	22.56	22.60	22.77
HSDPA Subtest-3	22.15	22.42	22.29	21.87	22.25	21.96
HSDPA Subtest-4	22.60	22.30	22.39	21.94	22.12	22.18
DC-HSDPA Subtest-1	22.73	22.82	23.03	22.55	22.56	22.87
DC-HSDPA Subtest-2	22.81	22.86	22.82	22.66	22.58	22.69
DC-HSDPA Subtest-3	22.25	22.54	22.37	21.97	22.32	22.06
DC-HSDPA Subtest-4	22.18	22.31	22.20	22.01	22.11	22.12
HSUPA Subtest-1	22.89	22.90	23.02	22.64	22.65	22.63
HSUPA Subtest-2	22.25	22.47	22.47	21.80	22.11	22.18
HSUPA Subtest-3	22.82	23.00	22.70	22.39	22.67	22.52
HSUPA Subtest-4	22.79	22.78	22.73	22.38	22.65	22.53
HSUPA Subtest-5	22.87	22.85	22.95	22.38	22.69	22.54



LTE Band 2_Ant2

BW: 1.4M

BW	Modulation	RB Size	RB Offset	Low	Mid	High
		Channel		18607	18900	19193
		Frequency (MHz)		1850.7	1880	1909.3
1.4M	QPSK	1	0	23.47	23.61	23.6
		1	2	23.71	23.64	23.66
		1	5	23.63	23.56	23.56
		3	0	23.16	23.26	23.37
		3	1	23.4	23.35	23.38
		3	3	23.25	23.37	23.41
		6	0	22.46	22.52	22.55
	16QAM	1	0	22.75	22.76	22.6
		1	2	22.84	22.74	22.7
		1	5	22.67	22.68	22.71
		3	0	22.31	22.36	22.41
		3	1	22.27	22.27	22.17
		3	3	22.3	22.45	22.34
		6	0	21.45	21.42	21.47
	64QAM	1	0	21.66	21.6	21.59
		1	2	21.74	21.83	21.71
		1	5	21.84	21.8	21.46
		3	0	21.25	21.34	21.21
		3	1	21.26	21.33	21.26
		3	3	21.2	21.31	21.12
		6	0	20.39	20.48	20.37
	256QAM	1	0	18.55	18.65	18.53
		1	2	18.55	18.7	18.65
		1	5	18.49	18.66	18.45
		3	0	18.46	18.5	18.39
		3	1	18.42	18.52	18.53
		3	3	18.63	18.66	18.38
		6	0	18.42	18.49	18.53



BW	Modulation	RB Size	RB Offset	Low	Mid	High
		Channel		18615	18900	19185
		Frequency (MHz)		1851.5	1880	1908.5
3M	QPSK	1	0	23.42	23.54	23.61
		1	7	23.66	23.56	23.67
		1	14	23.5	23.5	23.56
		8	0	22.38	22.53	22.63
		8	3	22.54	22.57	22.72
		8	7	22.45	22.48	22.64
		15	0	22.51	22.59	22.59
	16QAM	1	0	22.74	22.76	22.57
		1	7	22.77	22.78	22.7
		1	14	22.66	22.75	22.62
		8	0	21.47	21.63	21.37
		8	3	21.41	21.54	21.41
		8	7	21.51	21.56	21.63
		15	0	21.35	21.53	21.49
	64QAM	1	0	21.68	21.61	21.57
		1	7	21.68	21.78	21.71
		1	14	21.73	21.76	21.45
		8	0	20.52	20.63	20.36
		8	3	20.53	20.55	20.41
		8	7	20.51	20.47	20.26
		15	0	20.4	20.49	20.38
	256QAM	1	0	18.54	18.66	18.49
		1	7	18.51	18.79	18.61
		1	14	18.43	18.55	18.55
		8	0	18.56	18.43	18.41
		8	3	18.48	18.58	18.54
		8	7	18.67	18.63	18.47
		15	0	18.48	18.5	18.44



BW	Modulation	RB Size	RB Offset	Low	Mid	High
		Channel		18625	18900	19175
		Frequency (MHz)		1852.5	1880	1907.5
5M	QPSK	1	0	23.5	23.6	23.73
		1	12	23.69	23.61	23.78
		1	24	23.57	23.55	23.7
		12	0	22.44	22.47	22.67
		12	6	22.54	22.64	22.62
		12	13	22.54	22.56	22.62
		25	0	22.44	22.59	22.61
		25	0	22.44	22.59	22.61
	16QAM	1	0	22.77	22.81	22.64
		1	12	22.89	22.84	22.71
		1	24	22.67	22.76	22.68
		12	0	21.45	21.63	21.29
		12	6	21.42	21.62	21.43
		12	13	21.63	21.67	21.65
		25	0	21.43	21.44	21.49
		25	0	21.43	21.44	21.49
	64QAM	1	0	21.64	21.64	21.51
		1	12	21.8	21.76	21.66
		1	24	21.77	21.8	21.53
		12	0	20.4	20.56	20.41
		12	6	20.45	20.56	20.43
		12	13	20.48	20.51	20.33
		25	0	20.4	20.47	20.41
		25	0	20.4	20.47	20.41
	256QAM	1	0	18.63	18.73	18.54
		1	12	18.55	18.67	18.56
		1	24	18.55	18.52	18.46
		12	0	18.45	18.44	18.35
		12	6	18.47	18.5	18.54
		12	13	18.63	18.58	18.45
		25	0	18.41	18.58	18.52
		25	0	18.41	18.58	18.52



BUREAU VERITAS Test Report No.: PSZ-QBJ2501200112RF02

BW: 10M

BW	Modulation	RB Size	RB Offset	Low	Mid	High
		Channel		18650	18900	19150
		Frequency (MHz)		1855	1880	1905
10M	QPSK	1	0	23.47	23.48	23.73
		1	24	23.61	23.61	23.71
		1	49	23.57	23.59	23.6
		25	0	22.42	22.53	22.54
		25	12	22.63	22.66	22.61
		25	25	22.51	22.48	22.61
		50	0	22.43	22.48	22.65
	16QAM	1	0	22.75	22.68	22.67
		1	24	22.88	22.71	22.75
		1	49	22.6	22.78	22.72
		25	0	21.55	21.63	21.33
		25	12	21.38	21.58	21.45
		25	25	21.56	21.66	21.54
		50	0	21.4	21.47	21.38
	64QAM	1	0	21.58	21.68	21.55
		1	24	21.8	21.75	21.71
		1	49	21.73	21.72	21.47
		25	0	20.49	20.63	20.41
		25	12	20.56	20.53	20.39
		25	25	20.5	20.53	20.31
		50	0	20.34	20.52	20.29
	256QAM	1	0	18.6	18.76	18.58
		1	24	18.58	18.7	18.63
		1	49	18.54	18.65	18.55
		25	0	18.5	18.54	18.44
		25	12	18.43	18.61	18.4
		25	25	18.71	18.53	18.43
		50	0	18.5	18.44	18.52



BUREAU VERITAS Test Report No.: PSZ-QBJ2501200112RF02

BW: 15M

BW	Modulation	RB Size	RB Offset	Low	Mid	High
		Channel		18675	18900	19125
		Frequency (MHz)		1857.5	1880	1902.5
15M	QPSK	1	0	23.55	23.49	23.66
		1	37	23.61	23.58	23.57
		1	74	23.61	23.52	23.56
		36	0	22.43	22.5	22.63
		36	19	22.65	22.58	22.72
		36	39	22.54	22.59	22.64
		75	0	22.47	22.46	22.63
	16QAM	1	0	22.72	22.67	22.62
		1	37	22.91	22.84	22.72
		1	74	22.63	22.73	22.68
		36	0	21.48	21.61	21.28
		36	19	21.48	21.58	21.43
		36	39	21.57	21.6	21.57
		75	0	21.35	21.46	21.4
	64QAM	1	0	21.68	21.64	21.59
		1	37	21.69	21.85	21.7
		1	74	21.75	21.74	21.44
		36	0	20.52	20.62	20.46
		36	19	20.58	20.56	20.49
		36	39	20.38	20.51	20.28
		75	0	20.33	20.49	20.29
	256QAM	1	0	18.58	18.73	18.59
		1	37	18.47	18.71	18.64
		1	74	18.45	18.53	18.47
		36	0	18.5	18.43	18.41
		36	19	18.45	18.5	18.45
		36	39	18.7	18.63	18.43
		75	0	18.46	18.54	18.45



BW	Modulation	RB Size	RB Offset	Low	Mid	High
		Channel		18700	18900	19100
		Frequency (MHz)		1860	1880	1900
20M	QPSK	1	0	23.57	23.62	23.74
		1	50	23.75	23.69	23.79
		1	99	23.64	23.6	23.71
		50	0	22.53	22.59	22.68
		50	25	22.68	22.71	22.73
		50	50	22.6	22.61	22.66
		100	0	22.52	22.61	22.7
	16QAM	1	0	22.78	22.82	22.72
		1	50	22.92	22.85	22.76
		1	99	22.72	22.79	22.75
		50	0	21.59	21.67	21.38
		50	25	21.52	21.64	21.51
		50	50	21.66	21.68	21.66
		100	0	21.48	21.55	21.52
	64QAM	1	0	21.72	21.73	21.64
		1	50	21.82	21.86	21.81
		1	99	21.85	21.85	21.58
		50	0	20.53	20.67	20.51
		50	25	20.6	20.64	20.5
		50	50	20.53	20.61	20.35
		100	0	20.42	20.57	20.42
	256QAM	1	0	18.64	18.78	18.62
		1	50	18.62	18.8	18.66
		1	99	18.58	18.67	18.56
		50	0	18.58	18.56	18.45
		50	25	18.51	18.65	18.55
		50	50	18.73	18.67	18.53
		100	0	18.51	18.59	18.54



LTE Band 2_Ant3

BW: 1.4M

BW	Modulation	RB Size	RB Offset	Low	Mid	High
		Channel		18607	18900	19193
		Frequency (MHz)		1850.7	1880	1909.3
1.4M	QPSK	1	0	23.53	23.63	23.62
		1	2	23.88	23.77	23.75
		1	5	23.68	23.7	23.63
		3	0	23.36	23.53	23.32
		3	1	23.65	23.49	23.58
		3	3	23.45	23.43	23.55
		6	0	22.74	22.57	22.67
	16QAM	1	0	22.88	22.83	22.96
		1	2	22.76	22.91	22.93
		1	5	22.88	22.88	22.96
		3	0	22.52	22.63	22.47
		3	1	22.52	22.66	22.48
		3	3	22.5	22.55	22.42
		6	0	21.68	21.69	21.76
	64QAM	1	0	21.68	21.69	21.65
		1	2	21.82	21.86	21.82
		1	5	21.87	21.89	21.92
		3	0	21.48	21.6	21.4
		3	1	21.64	21.72	21.58
		3	3	21.5	21.64	21.53
		6	0	20.8	20.86	20.75
	256QAM	1	0	18.67	18.82	18.8
		1	2	18.74	18.87	18.71
		1	5	18.84	18.85	18.86
		3	0	18.62	18.64	18.68
		3	1	18.68	18.79	18.9
		3	3	18.79	18.74	18.71
		6	0	18.78	18.83	18.64



BUREAU VERITAS Test Report No.: PSZ-QBJ2501200112RF02

BW: 3M

BW	Modulation	RB Size	RB Offset	Low	Mid	High
		Channel		18615	18900	19185
		Frequency (MHz)		1851.5	1880	1908.5
3M	QPSK	1	0	23.48	23.69	23.65
		1	7	23.74	23.76	23.8
		1	14	23.67	23.7	23.64
		8	0	22.62	22.68	22.49
		8	3	22.77	22.78	22.73
		8	7	22.67	22.73	22.72
		15	0	22.75	22.67	22.58
	16QAM	1	0	22.83	22.83	22.87
		1	7	22.79	22.9	22.93
		1	14	22.81	22.84	22.84
		8	0	21.69	21.76	21.66
		8	3	21.59	21.71	21.77
		8	7	21.6	21.69	21.67
		15	0	21.75	21.65	21.78
	64QAM	1	0	21.65	21.81	21.78
		1	7	21.83	21.92	21.95
		1	14	21.91	21.85	21.8
		8	0	20.6	20.78	20.59
		8	3	20.69	20.87	20.7
		8	7	20.6	20.73	20.62
		15	0	20.72	20.76	20.75
	256QAM	1	0	18.64	18.81	18.78
		1	7	18.75	18.89	18.73
		1	14	18.88	18.8	18.89
		8	0	18.66	18.7	18.66
		8	3	18.68	18.85	18.9
		8	7	18.72	18.77	18.66
		15	0	18.74	18.77	18.69



BW	Modulation	RB Size	RB Offset	Low	Mid	High
		Channel		18625	18900	19175
		Frequency (MHz)		1852.5	1880	1907.5
5M	QPSK	1	0	23.44	23.64	23.63
		1	12	23.87	23.72	23.72
		1	24	23.78	23.65	23.64
		12	0	22.66	22.76	22.52
		12	6	22.71	22.69	22.75
		12	13	22.73	22.59	22.64
		25	0	22.72	22.68	22.63
	16QAM	1	0	22.78	22.85	22.94
		1	12	22.84	22.79	22.86
		1	24	22.88	22.81	22.92
		12	0	21.75	21.7	21.66
		12	6	21.65	21.72	21.71
		12	13	21.65	21.74	21.67
		25	0	21.69	21.72	21.66
	64QAM	1	0	21.68	21.8	21.73
		1	12	21.86	21.86	21.85
		1	24	21.92	21.79	21.86
		12	0	20.64	20.67	20.7
		12	6	20.69	20.79	20.67
		12	13	20.63	20.82	20.59
		25	0	20.71	20.79	20.8
	256QAM	1	0	18.67	18.78	18.85
		1	12	18.74	18.84	18.73
		1	24	18.84	18.78	18.84
		12	0	18.58	18.67	18.7
		12	6	18.71	18.79	18.86
		12	13	18.83	18.76	18.6
		25	0	18.72	18.78	18.65



BUREAU VERITAS Test Report No.: PSZ-QBJ2501200112RF02

BW: 10M

BW	Modulation	RB Size	RB Offset	Low	Mid	High
		Channel		18650	18900	19150
		Frequency (MHz)		1855	1880	1905
10M	QPSK	1	0	23.53	23.76	23.66
		1	24	23.83	23.79	23.77
		1	49	23.78	23.72	23.62
		25	0	22.53	22.77	22.59
		25	12	22.78	22.66	22.71
		25	25	22.68	22.67	22.6
		50	0	22.68	22.71	22.6
	16QAM	1	0	22.87	22.92	22.88
		1	24	22.84	22.83	22.84
		1	49	22.88	22.8	22.82
		25	0	21.74	21.8	21.65
		25	12	21.68	21.71	21.71
		25	25	21.71	21.68	21.67
		50	0	21.69	21.66	21.65
	64QAM	1	0	21.65	21.76	21.65
		1	24	21.86	21.84	21.91
		1	49	21.95	21.78	21.91
		25	0	20.6	20.73	20.69
		25	12	20.76	20.8	20.73
		25	25	20.68	20.8	20.65
		50	0	20.78	20.86	20.82
	256QAM	1	0	18.65	18.78	18.85
		1	24	18.81	18.93	18.76
		1	49	18.9	18.71	18.92
		25	0	18.58	18.69	18.6
		25	12	18.69	18.86	18.88
		25	25	18.79	18.7	18.63
		50	0	18.76	18.82	18.71



BUREAU VERITAS Test Report No.: PSZ-QBJ2501200112RF02

BW: 15M

BW	Modulation	RB Size	RB Offset	Low	Mid	High
		Channel		18675	18900	19125
		Frequency (MHz)		1857.5	1880	1902.5
15M	QPSK	1	0	23.47	23.68	23.6
		1	37	23.77	23.68	23.78
		1	74	23.71	23.68	23.61
		36	0	22.63	22.73	22.59
		36	19	22.81	22.68	22.73
		36	39	22.66	22.68	22.6
		75	0	22.64	22.69	22.55
	16QAM	1	0	22.81	22.91	22.9
		1	37	22.8	22.84	22.84
		1	74	22.76	22.81	22.84
		36	0	21.68	21.68	21.68
		36	19	21.56	21.74	21.75
		36	39	21.72	21.65	21.59
		75	0	21.65	21.78	21.78
	64QAM	1	0	21.67	21.79	21.65
		1	37	21.94	21.85	21.96
		1	74	21.93	21.91	21.82
		36	0	20.71	20.72	20.7
		36	19	20.74	20.92	20.73
		36	39	20.66	20.73	20.59
		75	0	20.68	20.89	20.71
	256QAM	1	0	18.71	18.83	18.79
		1	37	18.75	18.84	18.72
		1	74	18.95	18.83	18.92
		36	0	18.68	18.73	18.59
		36	19	18.58	18.89	18.84
		36	39	18.81	18.66	18.65
		75	0	18.66	18.82	18.59



BW	Modulation	RB Size	RB Offset	Low	Mid	High
		Channel		18700	18900	19100
		Frequency (MHz)		1860	1880	1900
20M	QPSK	1	0	23.58	23.77	23.69
		1	50	23.89	23.82	23.86
		1	99	23.8	23.8	23.71
		50	0	22.67	22.79	22.63
		50	25	22.83	22.81	22.76
		50	50	22.76	22.74	22.74
		100	0	22.77	22.72	22.69
	16QAM	1	0	22.92	22.97	22.98
		1	50	22.89	22.94	22.96
		1	99	22.91	22.95	22.97
		50	0	21.82	21.82	21.78
		50	25	21.7	21.86	21.8
		50	50	21.74	21.8	21.73
		100	0	21.76	21.79	21.8
	64QAM	1	0	21.75	21.82	21.8
		1	50	21.96	21.93	21.97
		1	99	21.98	21.92	21.95
		50	0	20.72	20.8	20.71
		50	25	20.84	20.93	20.81
		50	50	20.73	20.86	20.73
		100	0	20.83	20.9	20.85
	256QAM	1	0	18.78	18.9	18.88
		1	50	18.87	18.99	18.84
		1	99	18.96	18.86	18.93
		50	0	18.7	18.79	18.73
		50	25	18.73	18.93	18.94
		50	50	18.87	18.78	18.73
		100	0	18.8	18.89	18.73



EIRP POWER (dBm)

GSM1900_Ant2							
Modulation	Channel	Frequency (MHz)	Conducted Power (dBm)	Gain (dB)	EIRP (dBm)	EIRP (mW)	FCC Limit (W)
GPRS	512	1850.2	29.26	-1.7	27.56	570.16	2
	661	1880	29.62	-1.7	27.92	619.44	2
	810	1909.8	29.79	-1.7	28.09	644.17	2
EDGE	512	1850.2	25.38	-1.7	23.68	233.35	2
	661	1880	25.74	-1.7	24.04	253.51	2
	810	1909.8	25.85	-1.7	24.15	260.02	2

GSM1900_Ant3							
Modulation	Channel	Frequency (MHz)	Conducted Power (dBm)	Gain (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
GPRS	512	1850.2	28.97	-4.87	24.10	257.04	2
	661	1880	29.28	-4.87	24.41	276.06	2
	810	1909.8	29.50	-4.87	24.63	290.40	2
EDGE	512	1850.2	25.86	-4.87	20.99	125.60	2
	661	1880	25.91	-4.87	21.04	127.06	2
	810	1909.8	25.96	-4.87	21.09	128.53	2

WCDMA II_Ant2						
Channel	Frequency (MHz)	Conducted Power (dBm)	Gain (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
9262	1852.4	24.18	-1.7	22.48	177.01	2
9400	1880	23.98	-1.7	22.28	169.04	2
9538	1907.6	23.91	-1.7	22.21	166.34	2
WCDMA II_Ant3						
Channel	Frequency (MHz)	Conducted Power (dBm)	Gain (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
9262	1852.4	23.91	-4.87	19.04	80.17	2
9400	1880	23.98	-4.87	19.11	81.47	2
9538	1907.6	23.68	-4.87	18.81	76.03	2



LTE Band 2_Ant2

BW [MHz] Modulation	Channel	Frequency (MHz)	Conducted Power (dBm)	Gain (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
20M-QPSK	18700	1860	23.75	-1.7	22.05	160.32	2
	18900	1880	23.69	-1.7	21.99	158.12	2
	19100	1900	23.79	-1.7	22.09	161.81	2
20M- 16QAM	18700	1860	22.92	-1.7	21.22	132.43	2
	18900	1880	22.85	-1.7	21.15	130.32	2
	19100	1900	22.76	-1.7	21.06	127.64	2
20M- 64QAM	18700	1860	21.85	-1.7	20.15	103.51	2
	18900	1880	21.86	-1.7	20.16	103.75	2
	19100	1900	21.81	-1.7	20.11	102.57	2
20M- 256QAM	18700	1860	18.73	-1.7	17.03	50.47	2
	18900	1880	18.80	-1.7	17.10	51.29	2
	19100	1900	18.66	-1.7	16.96	49.66	2
BW [MHz] Modulation	Channel	Frequency (MHz)	Conducted Power (dBm)	Gain (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
15M-QPSK	18675	1857.5	23.61	-1.7	21.91	155.24	2
	18900	1880	23.58	-1.7	21.88	154.17	2
	19125	1902.5	23.66	-1.7	21.96	157.04	2
15M- 16QAM	18675	1857.5	22.91	-1.7	21.21	132.13	2
	18900	1880	22.84	-1.7	21.14	130.02	2
	19125	1902.5	22.72	-1.7	21.02	126.47	2
15M- 64QAM	18675	1857.5	21.75	-1.7	20.05	101.16	2
	18900	1880	21.85	-1.7	20.15	103.51	2
	19125	1902.5	21.70	-1.7	20.00	100.00	2
15M- 256QAM	18675	1857.5	18.70	-1.7	17.00	50.12	2
	18900	1880	18.73	-1.7	17.03	50.47	2
	19125	1902.5	18.64	-1.7	16.94	49.43	2
BW [MHz] Modulation	Channel	Frequency (MHz)	Conducted Power (dBm)	Gain (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
10M-QPSK	18650	1855	23.61	-1.7	21.91	155.24	2
	18900	1880	23.61	-1.7	21.91	155.24	2
	19150	1905	23.73	-1.7	22.03	159.59	2
10M- 16QAM	18650	1855	22.88	-1.7	21.18	131.22	2
	18900	1880	22.78	-1.7	21.08	128.23	2
	19150	1905	22.75	-1.7	21.05	127.35	2
10M-	18650	1855	21.80	-1.7	20.10	102.33	2

Huarui 7layers High Technology
(Suzhou) Co., Ltd.

Tower N, Innovation Center, 88 Zuyi Road, High-tech District,
Suzhou City, Anhui Province

Tel: +86 (0557)
368 1008



BUREAU VERITAS Test Report No.: PSZ-QBJ2501200112RF02

64QAM	18900	1880	21.75	-1.7	20.05	101.16	2
	19150	1905	21.71	-1.7	20.01	100.23	2
10M-256QAM	18650	1855	18.71	-1.7	17.01	50.23	2
	18900	1880	18.76	-1.7	17.06	50.82	2
	19150	1905	18.63	-1.7	16.93	49.32	2
BW [MHz] Modulation	Channel	Frequency (MHz)	Conducted Power (dBm)	Gain (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
5M-QPSK	18625	1852.5	23.69	-1.7	21.99	158.12	2
	18900	1880	23.61	-1.7	21.91	155.24	2
	19175	1907.5	23.78	-1.7	22.08	161.44	2
5M-16QAM	18625	1852.5	22.89	-1.7	21.19	131.52	2
	18900	1880	22.84	-1.7	21.14	130.02	2
	19175	1907.5	22.71	-1.7	21.01	126.18	2
5M-64QAM	18625	1852.5	21.80	-1.7	20.10	102.33	2
	18900	1880	21.80	-1.7	20.10	102.33	2
	19175	1907.5	21.66	-1.7	19.96	99.08	2
5M-256QAM	18625	1852.5	18.63	-1.7	16.93	49.32	2
	18900	1880	18.73	-1.7	17.03	50.47	2
	19175	1907.5	18.56	-1.7	16.86	48.53	2
BW [MHz] Modulation	Channel	Frequency (MHz)	Conducted Power (dBm)	Gain (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
3M-QPSK	18615	1851.5	23.66	-1.7	21.96	157.04	2
	18900	1880	23.56	-1.7	21.86	153.46	2
	19185	1908.5	23.67	-1.7	21.97	157.40	2
3M-16QAM	18615	1851.5	22.77	-1.7	21.07	127.94	2
	18900	1880	22.78	-1.7	21.08	128.23	2
	19185	1908.5	22.70	-1.7	21.00	125.89	2
3M-64QAM	18615	1851.5	21.73	-1.7	20.03	100.69	2
	18900	1880	21.78	-1.7	20.08	101.86	2
	19185	1908.5	21.71	-1.7	20.01	100.23	2
3M-256QAM	18615	1851.5	18.67	-1.7	16.97	49.77	2
	18900	1880	18.79	-1.7	17.09	51.17	2
	19185	1908.5	18.61	-1.7	16.91	49.09	2
BW [MHz] Modulation	Channel	Frequency (MHz)	Conducted Power (dBm)	Gain (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
1.4M-QPSK	18607	1850.7	23.71	-1.7	22.01	158.85	2
	18900	1880	23.64	-1.7	21.94	156.31	2
	19193	1909.3	23.66	-1.7	21.96	157.04	2



BUREAU VERITAS Test Report No.: PSZ-QBJ2501200112RF02

1.4M-16QAM	18607	1850.7	22.84	-1.7	21.14	130.02	2
	18900	1880	22.76	-1.7	21.06	127.64	2
	19193	1909.3	22.71	-1.7	21.01	126.18	2
1.4M-64QAM	18607	1850.7	21.84	-1.7	20.14	103.28	2
	18900	1880	21.83	-1.7	20.13	103.04	2
	19193	1909.3	21.71	-1.7	20.01	100.23	2
1.4M-256QAM	18607	1850.7	18.63	-1.7	16.93	49.32	2
	18900	1880	18.70	-1.7	17.00	50.12	2
	19193	1909.3	18.65	-1.7	16.95	49.55	2



LTE Band 2_Ant3

BW [MHz] Modulation	Channel	Frequency (MHz)	Conducted Power (dBm)	Gain (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
20M-QPSK	18700	1860	23.89	-4.87	19.02	79.80	2
	18900	1880	23.82	-4.87	18.95	78.52	2
	19100	1900	23.86	-4.87	18.99	79.25	2
20M-16QAM	18700	1860	22.92	-4.87	18.05	63.83	2
	18900	1880	22.97	-4.87	18.10	64.57	2
	19100	1900	22.98	-4.87	18.11	64.71	2
20M-64QAM	18700	1860	21.98	-4.87	17.11	51.40	2
	18900	1880	21.93	-4.87	17.06	50.82	2
	19100	1900	21.97	-4.87	17.10	51.29	2
20M-256QAM	18700	1860	18.96	-4.87	14.09	25.64	2
	18900	1880	18.99	-4.87	14.12	25.82	2
	19100	1900	18.94	-4.87	14.07	25.53	2
BW [MHz] Modulation	Channel	Frequency (MHz)	Conducted Power (dBm)	Gain (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
15M-QPSK	18675	1857.5	23.77	-4.87	18.90	77.62	2
	18900	1880	23.68	-4.87	18.81	76.03	2
	19125	1902.5	23.78	-4.87	18.91	77.80	2
15M-16QAM	18675	1857.5	22.81	-4.87	17.94	62.23	2
	18900	1880	22.91	-4.87	18.04	63.68	2
	19125	1902.5	22.90	-4.87	18.03	63.53	2
15M-64QAM	18675	1857.5	21.94	-4.87	17.07	50.93	2
	18900	1880	21.91	-4.87	17.04	50.58	2
	19125	1902.5	21.96	-4.87	17.09	51.17	2
15M-256QAM	18675	1857.5	18.95	-4.87	14.08	25.59	2
	18900	1880	18.89	-4.87	14.02	25.23	2
	19125	1902.5	18.92	-4.87	14.05	25.41	2
BW [MHz] Modulation	Channel	Frequency (MHz)	Conducted Power (dBm)	Gain (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
10M-QPSK	18650	1855	23.83	-4.87	18.96	78.70	2
	18900	1880	23.79	-4.87	18.92	77.98	2
	19150	1905	23.77	-4.87	18.90	77.62	2
10M-16QAM	18650	1855	22.88	-4.87	18.01	63.24	2
	18900	1880	22.92	-4.87	18.05	63.83	2
	19150	1905	22.88	-4.87	18.01	63.24	2
10M-	18650	1855	21.95	-4.87	17.08	51.05	2

Huarui 7layers High Technology
(Suzhou) Co., Ltd.

Tower N, Innovation Center, 88 Zuyi Road, High-tech District,
Suzhou City, Anhui Province

Tel: +86 (0557)
368 1008



BUREAU VERITAS Test Report No.: PSZ-QBJ2501200112RF02

64QAM	18900	1880	21.84	-4.87	16.97	49.77	2
	19150	1905	21.91	-4.87	17.04	50.58	2
10M-256QAM	18650	1855	18.90	-4.87	14.03	25.29	2
	18900	1880	18.93	-4.87	14.06	25.47	2
	19150	1905	18.92	-4.87	14.05	25.41	2
BW [MHz] Modulation	Channel	Frequency (MHz)	Conducted Power (dBm)	Gain (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
5M-QPSK	18625	1852.5	23.87	-4.87	19.00	79.43	2
	18900	1880	23.72	-4.87	18.85	76.74	2
	19175	1907.5	23.72	-4.87	18.85	76.74	2
5M-16QAM	18625	1852.5	22.88	-4.87	18.01	63.24	2
	18900	1880	22.85	-4.87	17.98	62.81	2
	19175	1907.5	22.94	-4.87	18.07	64.12	2
5M-64QAM	18625	1852.5	21.92	-4.87	17.05	50.70	2
	18900	1880	21.86	-4.87	16.99	50.00	2
	19175	1907.5	21.86	-4.87	16.99	50.00	2
5M-256QAM	18625	1852.5	18.84	-4.87	13.97	24.95	2
	18900	1880	18.84	-4.87	13.97	24.95	2
	19175	1907.5	18.86	-4.87	13.99	25.06	2
BW [MHz] Modulation	Channel	Frequency (MHz)	Conducted Power (dBm)	Gain (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
3M-QPSK	18615	1851.5	23.74	-4.87	18.87	77.09	2
	18900	1880	23.76	-4.87	18.89	77.45	2
	19185	1908.5	23.80	-4.87	18.93	78.16	2
3M-16QAM	18615	1851.5	22.83	-4.87	17.96	62.52	2
	18900	1880	22.90	-4.87	18.03	63.53	2
	19185	1908.5	22.93	-4.87	18.06	63.97	2
3M-64QAM	18615	1851.5	21.91	-4.87	17.04	50.58	2
	18900	1880	21.92	-4.87	17.05	50.70	2
	19185	1908.5	21.95	-4.87	17.08	51.05	2
3M-256QAM	18615	1851.5	18.88	-4.87	14.01	25.18	2
	18900	1880	18.89	-4.87	14.02	25.23	2
	19185	1908.5	18.90	-4.87	14.03	25.29	2
BW [MHz] Modulation	Channel	Frequency (MHz)	Conducted Power (dBm)	Gain (dB)	EIRP (dBm)	EIRP (mW)	Limit (W)
1.4M-QPSK	18607	1850.7	23.88	-4.87	19.01	79.62	2
	18900	1880	23.77	-4.87	18.90	77.62	2
	19193	1909.3	23.75	-4.87	18.88	77.27	2



BUREAU VERITAS Test Report No.: PSZ-QBJ2501200112RF02

1.4M-16QAM	18607	1850.7	22.88	-4.87	18.01	63.24	2
	18900	1880	22.91	-4.87	18.04	63.68	2
	19193	1909.3	22.96	-4.87	18.09	64.42	2
1.4M-64QAM	18607	1850.7	21.87	-4.87	17.00	50.12	2
	18900	1880	21.89	-4.87	17.02	50.35	2
	19193	1909.3	21.92	-4.87	17.05	50.70	2
1.4M-256QAM	18607	1850.7	18.84	-4.87	13.97	24.95	2
	18900	1880	18.87	-4.87	14.00	25.12	2
	19193	1909.3	18.90	-4.87	14.03	25.29	2

REMARKS: ERP Output Power (dBm) = EIRP (dBm) -2.15(dB).



4.2 FREQUENCY STABILITY MEASUREMENT

4.2.1 LIMITS OF FREQUENCY STABILITY MEASUREMENT


The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block.

4.2.2 TEST PROCEDURE

- Device is placed at the oven room. The oven room could control the temperatures and humidity. Power warm up is at least 15 min and power applied should perform before recording frequency error.
- EUT is connected the external power supply to control the DC input power. The test voltage range is from minimum to maximum working voltage. Each step shall be record the frequency error rate.
- The temperature range step is 10 degrees in this test items. All temperature levels shall be hold the $\pm 0.5^{\circ}\text{C}$ during the measurement testing. The each temperature step shall be at least 0.5 hours, consider the EUT could be test under the stability condition.

NOTE: The frequency error was recorded frequency error from the communication simulator.

4.2.3 TEST SETUP



4.2.4 TEST RESULTS

Please Refer to Appendix of this test report.




4.3 OCCUPIED BANDWIDTH MEASUREMENT

3.3.1 LIMITS OF OCCUPIED BANDWIDTH MEASUREMENT

The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 %of the total mean power of a given emission.

3.3.2 TEST SETUP



3.3.3 TEST PROCEDURES

- The conducted occupied bandwidth used the power splitter via EUT RF power connector between simulation base station and spectrum analyzer.
- Use OBW measurement function of Spectrum analyzer to measure 99 % occupied bandwidth.

3.3.4 TEST RESULTS

Please Refer to Appendix of this test report.




4.4 BAND EDGE MEASUREMENTC

4.4.1 LIMITS OF BAND EDGE MEASUREMENT

Power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. In the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

4.4.2 TEST SETUP





4.4.3 TEST PROCEDURES

- a) All measurements were done at low and high operational frequency range
- b) Connect the transmitter to the spectrum analyzer via coaxial cable while ensuring proper impedance matching.
- c) Tune the analyzer to the nominal center frequency of the emission bandwidth

(EBW)

- d) .Set the resolution bandwidth (RBW) $\geq 1\%$ EBW in the 1MHz band immediately outside and adjacent to the band edge.
- e) Beyond the 1MHz band from the band edge, RBW=1MHz was used.
- f) Set the video bandwidth (VBW) to $\geq 3 \times$ RBW.
- g) Select the average power (RMS) display detector.
- h) Set the number of measurement points to ≥ 1001 .
- i) Use auto-coupled sweep time.
- j) Perform the measurement over an interval of time when the transmission is continuous and at its maximum power level.
- k) The RF fundamental frequency should be excluded against the limit line in the operating frequency band and use RBW is 10KHz or 100KHz.
- l) Record the max trace plot into the test report.

4.4.4 TEST RESULTS

Please Refer to Appendix of this test report.



4.5 CONDUCTED SPURIOUS EMISSIONS


4.5.1 LIMITS OF CONDUCTED SPURIOUS EMISSIONS MEASUREMENT

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. The emission limit equal to -13dBm .

4.5.2 TEST PROCEDURE

- a. The EUT makes a phone call to the communication simulator. All measurements were done at low, middle and high operational frequency range.
- b. Measuring frequency range is from 30MHz up to a frequency including its 10th harmonic. 10dB attenuation pad is connected with spectrum. RBW=1MHz and VBW=3MHz is used for conducted emission measurement.

4.5.3 TEST SETUP



4.5.4 TEST RESULTS

NOTE : The 9K~30MHz amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required in the report.

Please Refer to Appendix of this test report.



4.6 RADIATED EMISSION MEASUREMENT

4.6.1 LIMITS OF RADIATED EMISSION MEASUREMENT

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. The emission limit equal to -13dBm .

4.6.2 TEST PROCEDURES

- a. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The “Read Value” is the spectrum reading the maximum power value.
- b. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to “Read Value “ of step a. Record the power level of S.G
- c. $\text{EIRP} = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn}$.

NOTE: The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1MHz/3MHz.


4.6.3 DEVIATION FROM TEST STANDARD

No deviation





4.6.4 TEST SETUP

< Frequency Range below 30MHz >



< Frequency Range 30MHz~1GHz >





Note: Above 1G is a directional antenna

Depends on the EUT height and the antenna 3dB beamwidth both, refer to section 7.3 of CISPR 16-2-3.

For the actual test configuration, please refer to the attached file (Test Setup Photo).



4.6.5 TEST RESULTS


NOTE : The 9K~30MHz amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required in the report.

BELOW 1GHz WORST-CASE DATA

EDGE 1900 CHANNEL BANDWIDTH			
MODE	TX channel 512	FREQUENCY RANGE	30 MHz – 1GHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	120Vac 60HZ
TESTED BY	Hanwen Xu		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	37.760	-50.80	-13.00	37.80	6.39	H	110.4	1.00
1	57.160	-53.28	-13.00	40.28	1.73	H	355	2.00
1	111.965	-44.59	-13.00	31.59	-4.53	H	221.6	1.00
1	226.425	-32.56	-13.00	19.56	6.66	H	355	2.00
1	384.535	-48.74	-13.00	35.74	7.53	H	141.9	2.00
1	681.355	-49.37	-13.00	36.37	8.32	H	250.7	2.00






**BUREAU
VERITAS**

Test Report No.: PSZ-QBJ2501200112RF02

MODE	TX channel 512	FREQUENCY RANGE	30 MHz – 1GHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	120Vac 60HZ
TESTED BY	Hanwen Xu		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	35.820	-54.03	-13.00	41.03	-3.57	V	1	1.00
1	99.840	-45.11	-13.00	32.11	11.16	V	218	1.00
1	181.320	-37.21	-13.00	24.21	-2.58	V	218	1.00
1	277.835	-49.05	-13.00	36.05	4.89	V	354.3	2.00
1	469.895	-44.75	-13.00	31.75	5.33	V	4.9	1.00
1	647.890	-51.97	-13.00	38.97	7.11	V	4.9	1.00



Huarui 7layers High Technology
(Suzhou) Co., Ltd.

Tower N, Innovation Center, 88 Zuyi Road, High-tech District,
Suzhou City, Anhui Province

Tel: +86 (0557)
368 1008




ABOVE 1GHz DATA

Note: For higher frequency, the emission is too low to be detected.

PCS 1900			
MODE	TX channel 512	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	120Vac 60HZ
TESTED BY	Hanwen Xu		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	3,700.400	-50.70	-13.00	37.70	21.11	H	253.9	1.00
4	5,550.600	-48.24	-13.00	35.24	24.26	H	106	2.00






MODE	TX channel 512	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	120Vac 60HZ
TESTED BY	Hanwen Xu		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	3,700.400	-49.57	-13.00	36.57	21.71	V	359	2.00
4	5,550.600	-47.06	-13.00	34.06	24.96	V	0.9	2.00






MODE	TX channel 661	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	120Vac 60HZ
TESTED BY	Hanwen Xu		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	3,760.000	-50.22	-13.00	37.22	21.64	H	1	1.00
4	5,640.000	-49.15	-13.00	36.15	24.79	H	103.7	2.00






MODE	TX channel 661	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	120Vac 60HZ
TESTED BY	Hanwen Xu		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	3,760.000	-49.69	-13.00	36.69	22.13	V	359	2.00
4	5,640.000	-47.00	-13.00	34.00	25.13	V	1	2.00






MODE	TX channel 810	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	120Vac 60HZ
TESTED BY	Hanwen Xu		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	3,819.600	-47.57	-13.00	34.57	22.23	H	359	1.00
4	5,729.400	-47.80	-13.00	34.80	25.33	H	359	1.00






**BUREAU
VERITAS**

Test Report No.: PSZ-QBJ2501200112RF02

MODE	TX channel 810	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	120Vac 60HZ
TESTED BY	Hanwen Xu		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	3,819.600	-48.14	-13.00	35.14	22.58	V	104.9	2.00
4	5,729.400	-48.27	-13.00	35.27	25.79	V	359	2.00






EDGE 1900			
MODE	TX channel 512	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	120Vac 60HZ
TESTED BY	Hanwen Xu		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	3,700.400	-50.37	-13.00	37.37	21.11	H	1	1.00
4	5,550.600	-48.25	-13.00	35.25	24.26	H	0.9	2.00






MODE	TX channel 512	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	120Vac 60HZ
TESTED BY	Hanwen Xu		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	3,700.400	-50.50	-13.00	37.50	21.71	V	359	2.00
4	5,550.600	-48.19	-13.00	35.19	24.96	V	359	2.00






MODE	TX channel 661	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	120Vac 60HZ
TESTED BY	Hanwen Xu		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	3,760.000	-50.55	-13.00	37.55	21.64	H	103.7	2.00
4	5,640.000	-48.53	-13.00	35.53	24.79	H	359	2.00






MODE	TX channel 661	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	120Vac 60HZ
TESTED BY	Hanwen Xu		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	3,760.000	-49.64	-13.00	36.64	22.13	V	0.9	2.00
4	5,640.000	-47.43	-13.00	34.43	25.13	V	265.8	1.00






MODE	TX channel 810	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	120Vac 60HZ
TESTED BY	Hanwen Xu		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	3,819.600	-48.00	-13.00	35.00	22.23	H	262.2	1.00
4	5,729.400	-48.06	-13.00	35.06	25.33	H	262.2	1.00






**BUREAU
VERITAS**

Test Report No.: PSZ-QBJ2501200112RF02

MODE	TX channel 810	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	120Vac 60HZ
TESTED BY	Hanwen Xu		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	3,819.600	-48.20	-13.00	35.20	22.58	V	258.6	1.00
4	5,729.400	-47.49	-13.00	34.49	25.79	V	1	1.00






WCDMA Band II			
MODE	TX channel 9262	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	120Vac 60HZ
TESTED BY	Hanwen Xu		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	3,704.800	-46.07	-13.00	33.07	26.44	H	359	2.00
4	5,557.200	-39.52	-13.00	26.52	34.21	H	359	2.00






MODE	TX channel 9262	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	120Vac 60HZ
TESTED BY	Hanwen Xu		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	3,704.800	-47.18	-13.00	34.18	26.25	V	113.1	2.00
4	5,557.200	-39.33	-13.00	26.33	33.96	V	359	2.00






MODE	TX channel 9400	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	120Vac 60HZ
TESTED BY	Hanwen Xu		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	3,760.000	-45.01	-13.00	32.01	28.21	H	114.2	2.00
4	5,640.000	-39.89	-13.00	26.89	34.24	H	359	2.00






MODE	TX channel 9400	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	120Vac 60HZ
TESTED BY	Hanwen Xu		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	3,760.000	-45.02	-13.00	32.02	27.89	V	0.9	2.00
4	5,640.000	-39.53	-13.00	26.53	33.97	V	108.4	2.00






MODE	TX channel 9538	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	120Vac 60HZ
TESTED BY	Hanwen Xu		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	3,815.200	-42.85	-13.00	29.85	27.79	H	248.2	1.00
4	5,722.800	-40.71	-13.00	27.71	34.60	H	359	1.00






MODE	TX channel 9538	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	120Vac 60HZ
TESTED BY	Hanwen Xu		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	3,815.200	-44.80	-13.00	31.80	27.50	V	359	2.00
4	5,722.800	-40.32	-13.00	27.32	34.34	V	0.9	2.00






LTE Band 2			
CHANNEL BANDWIDTH	1.4MHz / QPSK	MODE	TX channel 18900
FREQUENCY RANGE	Above 1000MHz	ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH
INPUT POWER	120Vac 60HZ	TESTED BY	Hanwen Xu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	3,758.740	-45.73	-13.00	32.73	28.00	H	359.1	1.00
4	5,638.110	-39.46	-13.00	26.46	34.62	H	1	1.00






CHANNEL BANDWIDTH	1.4MHz / QPSK	MODE	TX channel 18900
FREQUENCY RANGE	Above 1000MHz	ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH
INPUT POWER	120Vac 60HZ	TESTED BY	Hanwen Xu

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	3,758.740	-45.09	-13.00	32.09	27.69	V	1	1.00
4	5,638.110	-39.67	-13.00	26.67	34.35	V	1	1.00






CHANNEL BANDWIDTH	3MHz / QPSK	MODE	TX channel 18900
FREQUENCY RANGE	Above 1000MHz	ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH
INPUT POWER	120Vac 60HZ	TESTED BY	Hanwen Xu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	3,757.300	-45.52	-13.00	32.52	27.86	H	1	1.00
4	5,635.950	-39.10	-13.00	26.10	35.00	H	117.8	2.00






CHANNEL BANDWIDTH	3MHz / QPSK	MODE	TX channel 18900
FREQUENCY RANGE	Above 1000MHz	ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH
INPUT POWER	120Vac 60HZ	TESTED BY	Hanwen Xu

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	3,757.300	-44.97	-13.00	31.97	27.55	V	245.8	1.00
4	5,635.950	-40.01	-13.00	27.01	34.73	V	111.9	2.00






CHANNEL BANDWIDTH	5MHz / QPSK	MODE	TX channel 18900
FREQUENCY RANGE	Above 1000MHz	ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH
INPUT POWER	120Vac 60HZ	TESTED BY	Hanwen Xu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	3,760.500	-42.53	-13.00	29.53	28.18	H	109.5	2.00
4	5,633.250	-39.32	-13.00	26.32	35.57	H	244.6	1.00






CHANNEL BANDWIDTH	5MHz / QPSK	MODE	TX channel 18900
FREQUENCY RANGE	Above 1000MHz	ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH
INPUT POWER	120Vac 60HZ	TESTED BY	Hanwen Xu

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	3,755.500	-41.27	-13.00	28.27	27.98	V	359	2.00
4	5,633.250	-39.35	-13.00	26.35	35.31	V	1	1.00






CHANNEL BANDWIDTH	10MHz / QPSK	MODE	TX channel 18650
FREQUENCY RANGE	Above 1000MHz	ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH
INPUT POWER	120Vac 60HZ	TESTED BY	Hanwen Xu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	3,701.000	-47.74	-13.00	34.74	26.35	H	0.9	2.00
4	5,551.500	-40.35	-13.00	27.35	34.57	H	249.4	1.00






CHANNEL BANDWIDTH	10MHz / QPSK	MODE	TX channel 18650
FREQUENCY RANGE	Above 1000MHz	ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH
INPUT POWER	120Vac 60HZ	TESTED BY	Hanwen Xu

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	3,701.000	-47.48	-13.00	34.48	26.17	V	359.1	1.00
4	5,551.500	-39.80	-13.00	26.80	34.32	V	254.2	1.00






BUREAU VERITAS Test Report No.: PSZ-QBJ2501200112RF02

CHANNEL BANDWIDTH	10MHz / QPSK	MODE	TX channel 18900
FREQUENCY RANGE	Above 1000MHz	ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH
INPUT POWER	120Vac 60HZ	TESTED BY	Hanwen Xu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	3,751.000	-46.00	-13.00	33.00	26.95	H	128.6	2.00
4	5,626.500	-37.63	-13.00	24.63	35.71	H	359	1.00






CHANNEL BANDWIDTH	10MHz / QPSK	MODE	TX channel 19150
FREQUENCY RANGE	Above 1000MHz	ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH
INPUT POWER	120Vac 60HZ	TESTED BY	Hanwen Xu

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	3,751.000	-46.03	-13.00	33.03	26.66	V	350	1.00
4	5,626.500	-39.20	-13.00	26.20	35.45	V	125	2.00






CHANNEL BANDWIDTH	10MHz / QPSK	MODE	TX channel 19150
FREQUENCY RANGE	Above 1000MHz	ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH
INPUT POWER	120Vac 60HZ	TESTED BY	Hanwen Xu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	3,801.000	-45.05	-13.00	32.05	27.47	H	1	2.00
4	5,701.500	-39.48	-13.00	26.48	35.70	H	359.1	1.00






CHANNEL BANDWIDTH	10MHz / QPSK	MODE	TX channel 19150
FREQUENCY RANGE	Above 1000MHz	ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH
INPUT POWER	120Vac 60HZ	TESTED BY	Hanwen Xu

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	3,801.000	-45.63	-13.00	32.63	27.17	V	359	2.00
4	5,701.500	-39.21	-13.00	26.21	35.43	V	359	2.00






CHANNEL BANDWIDTH	15MHz / QPSK	MODE	TX channel 18900
FREQUENCY RANGE	Above 1000MHz	ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH
INPUT POWER	120Vac 60HZ	TESTED BY	Hanwen Xu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	3,746.500	-45.71	-13.00	32.71	27.08	H	359	1.00
4	5,619.750	-40.82	-13.00	27.82	34.89	H	243.4	1.00






CHANNEL BANDWIDTH	15MHz / QPSK	MODE	TX channel 18900
FREQUENCY RANGE	Above 1000MHz	ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH
INPUT POWER	120Vac 60HZ	TESTED BY	Hanwen Xu

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	3,746.500	-46.50	-13.00	33.50	26.79	V	359.1	1.00
4	5,619.750	-40.21	-13.00	27.21	34.63	V	1	1.00





CHANNEL BANDWIDTH	20MHz / QPSK	MODE	TX channel 18900
FREQUENCY RANGE	Above 1000MHz	ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH
INPUT POWER	120Vac 60HZ	TESTED BY	Hanwen Xu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	3,742.000	-46.87	-13.00	33.87	27.41	H	1	1.00
4	5,613.000	-40.27	-13.00	27.27	34.70	H	0.9	2.00

