



FCC RF Test Report

APPLICANT : Xiaomi Communications Co., Ltd.
EQUIPMENT : Mobile Phone
BRAND NAME : Xiaomi
MODEL NAME : 25010PN30G
FCC ID : 2AFZZPN30G
STANDARD : 47 CFR Part 22, 24, 27
CLASSIFICATION : PCS Licensed Transmitter Held to Ear (PCE)
TEST DATE(S) : Nov. 16, 2024 ~ Nov. 27, 2024

We, Sporton International Inc. (Kunshan), would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.26-2015 and shown compliance with the applicable technical standards.

This report contains data that were produced under subcontract by Sporton International Inc. (Shenzhen).

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.

Jason Jia

Approved by: Jason Jia



Sporton International Inc. (Kunshan)

No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300
People's Republic of China



TABLE OF CONTENTS

REVISION HISTORY	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant	5
1.2 Manufacturer	5
1.3 Product Feature of Equipment Under Test	5
1.4 Product Specification of Equipment Under Test	5
1.5 Modification of EUT	6
1.6 Maximum ERP/EIRP and Emission Designator	7
1.7 Testing Location	8
1.8 Test Software	9
1.9 Applicable Standards	9
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	10
2.1 Test Mode	10
2.2 Connection Diagram of Test System	12
2.3 Support Unit used in test configuration and system	12
2.4 Measurement Results Explanation Example	13
2.5 Frequency List of Low/Middle/High Channels	13
3 CONDUCTED TEST ITEMS	16
3.1 Measuring Instruments	16
3.2 Test Setup	16
3.3 Test Result of Conducted Test	16
3.4 Conducted Output Power and ERP/EIRP	17
3.5 Peak-to-Average Ratio	18
3.6 Occupied Bandwidth	19
3.7 Conducted Band Edge	20
3.8 Conducted Spurious Emission	22
3.9 Frequency Stability	23
4 RADIATED TEST ITEMS	24
4.1 Measuring Instruments	24
4.2 Test Setup	24
4.3 Test Result of Radiated Test	25
4.4 Radiated Spurious Emission	26
5 LIST OF MEASURING EQUIPMENT	27
6 MEASUREMENT UNCERTAINTY	28
APPENDIX A. TEST RESULTS OF CONDUCTED TEST	
APPENDIX B. TEST RESULTS OF RADIATED TEST	
APPENDIX C. TEST SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG4O2501J	Rev. 01	Initial issue of report	Dec. 12, 2024

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.4	§2.1046	Conducted Output Power	Reporting Only	PASS	-
	§22.913(a)(5)	Effective Radiated Power (5G NR n5, n26)	ERP < 7 Watt		
	§24.232(c)	Equivalent Isotropic Radiated Power (5G NR n2, n25)	EIRP < 2Watt		
	§27.50(d)(4)	Equivalent Isotropic Radiated Power (5G NR n66)	EIRP < 1Watt		
3.5	§24.232(d)	Peak-to-Average Ratio	<13 dB	PASS	-
3.6	§2.1049	Occupied Bandwidth	Reporting Only	PASS	-
3.7	§2.1051 §22.917(a) §24.238(a) §27.53(h)	Conducted Band Edge Measurement (5G NR n5, n26) (5G NR n2, n25) (5G NR n66)	< 43+10log ₁₀ (P[Watts])	PASS	-
3.8	§2.1051 §22.917(a) §24.238(a) §27.53(h)	Conducted Spurious Emission (5G NR n5, n26) (5G NR n2, n25) (5G NR n66)	< 43+10log ₁₀ (P[Watts])	PASS	-
3.9	§2.1055 §22.355	Frequency Stability Temperature & Voltage	< 2.5 ppm for Part 22	PASS	-
	§24.235 §27.54		Within Authorized Band		
4.4	§2.1053 §22.917(a) §24.238(a) §27.53(h)	Radiated Spurious Emission (5G NR n5, n26) (5G NR n2, n25) (5G NR n66)	< 43+10log ₁₀ (P[Watts])	PASS	Under limit 32.79 dB at 2480.00 MHz

Conformity Assessment Condition:

- The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
- The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty"

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.



1 General Description

1.1 Applicant

Xiaomi Communications Co., Ltd.

#019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085

1.2 Manufacturer

Xiaomi Communications Co., Ltd.

#019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Phone
Brand Name	Xiaomi
Model Name	25010PN30G
FCC ID	2AFZZPN30G
IMEI Code	Conducted : 869203070050067/869203070050281 Radiation : 869203070052501
HW Version	1353000O1
SW Version	Xiaomi HyperOS 2.0
EUT Stage	Identical Prototype

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx Frequency	5G NR n2 : 1850 MHz ~ 1910 MHz 5G NR n5 : 824 MHz ~ 849 MHz 5G NR n25 : 1850 MHz ~ 1915 MHz 5G NR n26 : 824 MHz ~ 849 MHz 5G NR n66 : 1710 MHz ~ 1780 MHz
Rx Frequency	5G NR n2 : 1930 MHz ~ 1990 MHz 5G NR n5 : 869 MHz ~ 894 MHz 5G NR n25 : 1930 MHz ~ 1995 MHz 5G NR n26 : 869 MHz ~ 894 MHz 5G NR n66 : 2110 MHz~ 2180 MHz
Bandwidth	n2, n25 SA: 5MHz / 10MHz / 15MHz / 20MHz / 25MHz / 30MHz / 35MHz / 40MHz n5 SA/NSA, n26 SA: 5MHz / 10MHz / 15MHz / 20MHz n66 SA: 5MHz / 10MHz / 15MHz / 20MHz / 25MHz / 30MHz / 35MHz / 40MHz / 45MHz n66 nSA: 5MHz / 10MHz / 15MHz / 20MHz / 25MHz / 30MHz / 35MHz / 40MHz
SCS	15kHz
Antenna Gain	<Ant. 0>: n5: -4.8 dBi

	n26: -4.8 dBi <Ant. 1>: n5: -3.8 dBi n26: -3.8 dBi <Ant. 4>: n2: -0.8 dBi n25: -0.8 dBi n66: -1.1 dBi <Ant. 5>: n2: -3.1 dBi n25: -2.7 dBi n66: -3.5 dBi <Ant. 6>: n2: -2.0 dBi n25: -2.0 dBi n66: -2.0 dBi <Ant. 7>: n2: -3.5 dBi n25: -2.1 dBi n66: -2.4 dBi
Type of Modulation	CP-OFDM: QPSK / 16QAM / 64QAM / 256QAM DFT-s-OFDM: PI/2 BPSK / QPSK / 16QAM / 64QAM / 256QAM

Remark:

1. The maximum ERP/EIRP is calculated from max output power and max antenna gain, only the maximum ERP/EIRP are shown in the report, 5G NR n25/n2 for Ant. 5 and n26/n5 for Ant. 1 and n66 for Ant. 4.
2. For conducted test items, only the test data of the worse antennas for each band are shown in the report according to the maximum power, 5G NR n26 for Ant. 0, n25 for Ant. 5 and n66 for Ant. 5/6.
3. The device supports three PAs for 5G NR n66 (main PA, other PA1 and other PA2), only the worst EIRP results are shown in the report.
4. 5G NR n5/n66 support SA mode and NSA mode, n2/n25/n26 support SA mode only. According to the maximum power between SA and NSA mode, SA covers NSA mode for n66, n2 covered by n25, n5 covered by n26, and RSE added test for n5 NSA.
5. The EN-DC mode combination could be referred to the product spec.
6. All the supported ENDC combinations are verified conducted power, only the ENDC combination with highest power are shown in the report.

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Maximum ERP/EIRP and Emission Designator

5G NR n2		PI/2 BPSK / QPSK		16QAM / 64QAM / 256QAM	
BW (MHz)	Frequency Range (MHz)	Maximum EIRP(W)	Emission Designator (99%OBW)	Maximum EIRP(W)	Emission Designator (99%OBW)
5	1852.5 ~ 1907.5	0.0920	4M47G7D	0.0791	4M48W7D
10	1855.0 ~ 1905.0	0.0968	9M28G7D	0.0800	9M28W7D
15	1857.5 ~ 1902.5	0.0977	14M1G7D	0.0824	14M1W7D
20	1860.0 ~ 1900.0	0.0977	18M9G7D	0.0834	18M9W7D
25	1862.5 ~ 1897.5	0.1005	23M7G7D	0.0841	23M8W7D
30	1865.0 ~ 1895.0	0.0984	28M6G7D	0.0824	28M6W7D
35	1867.5 ~ 1892.5	0.1159	33M5G7D	0.0986	33M5W7D
40	1870.0 ~ 1890.0	0.1189	38M5G7D	0.1005	38M6W7D
5G NR n25		PI/2 BPSK / QPSK		16QAM / 64QAM / 256QAM	
BW (MHz)	Frequency Range (MHz)	Maximum EIRP(W)	Emission Designator (99%OBW)	Maximum EIRP(W)	Emission Designator (99%OBW)
5	1852.5 ~ 1912.5	0.1343	4M47G7D	0.1096	4M48W7D
10	1855.0 ~ 1910.0	0.1352	9M28G7D	0.1000	9M28W7D
15	1857.5 ~ 1907.5	0.1371	14M1G7D	0.1002	14M1W7D
20	1860.0 ~ 1905.0	0.1368	18M9G7D	0.1132	18M9W7D
25	1862.5 ~ 1902.5	0.1330	23M7G7D	0.1102	23M8W7D
30	1865.0 ~ 1900.0	0.1276	28M6G7D	0.1030	28M6W7D
35	1867.5 ~ 1897.5	0.1282	33M5G7D	0.1107	33M5W7D
40	1870.0 ~ 1895.0	0.1380	38M5G7D	0.1148	38M6W7D
5G NR n5		PI/2 BPSK / QPSK		16QAM / 64QAM / 256QAM	
BW (MHz)	Frequency Range (MHz)	Maximum ERP(W)	Emission Designator (99%OBW)	Maximum ERP(W)	Emission Designator (99%OBW)
5	826.5 ~ 846.5	0.0838	4M46G7D	0.0708	4M50W7D
10	829.0 ~ 844.0	0.0845	9M27G7D	0.0684	9M29W7D
15	831.5 ~ 841.5	0.0836	14M1G7D	0.0692	14M1W7D
20	834.0 ~ 839.0	0.0847	18M9G7D	0.0692	19M0W7D
5G NR n26		PI/2 BPSK / QPSK		16QAM / 64QAM / 256QAM	
BW (MHz)	Frequency Range (MHz)	Maximum ERP(W)	Emission Designator (99%OBW)	Maximum ERP(W)	Emission Designator (99%OBW)
5	826.5 ~ 846.5	0.0843	4M46G7D	0.0711	4M50W7D
10	829.0 ~ 844.0	0.0841	9M27G7D	0.0695	9M29W7D
15	831.5 ~ 841.5	0.0863	14M1G7D	0.0718	14M1W7D
20	834.0 ~ 839.0	0.0871	18M9G7D	0.0710	19M0W7D



5G NR n66		PI/2 BPSK / QPSK		16QAM / 64QAM / 256QAM	
BW (MHz)	Frequency Range (MHz)	Maximum EIRP(W)	Emission Designator (99%OBW)	Maximum EIRP(W)	Emission Designator (99%OBW)
5	1712.5 ~ 1777.5	0.1854	4M49G7D	0.1510	4M49W7D
10	1715.0 ~ 1775.0	0.1897	9M28G7D	0.1521	9M31W7D
15	1717.5 ~ 1772.5	0.1945	14M1G7D	0.1517	14M1W7D
20	1720.0 ~ 1770.0	0.1862	19M0G7D	0.1483	19M0W7D
25	1722.5 ~ 1767.5	0.1982	23M8G7D	0.1556	23M8W7D
30	1725.0 ~ 1765.0	0.1936	28M6G7D	0.1524	28M6W7D
35	1727.5 ~ 1762.5	0.1888	33M6G7D	0.1503	33M7W7D
40	1730.0 ~ 1760.0	0.1972	38M5G7D	0.1521	38M6W7D
45	1732.5 ~ 1757.5	0.2014	43M2G7D	0.1592	43M3W7D

Note:

- 5G NR n26 overlaps the entire frequency range of 5G NR n5. Therefore, the test results provided in this report covers 5G NR n5 and the portion of 5G NR n26 subject to Part 22.
- 5G NR n25 overlaps the entire frequency range of 5G NR n2. Therefore, the test results provided in this report covers 5G NR n25 as well as 5G NR n2.
- All modulations have been tested, only the worst test results of PSK & QAM are shown in the report.

1.7 Testing Location

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International Inc. (Kunshan)		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	03CH04-KS	CN1257	314309



Sporton International Inc. (ShenZhen) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

Test Firm	Sporton International Inc. (ShenZhen)		
Test Site Location	1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055 People's Republic of China TEL: +86-755-86379589 FAX: +86-755-86379595		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	TH01-SZ	CN1256	421272

Note: Test data subcontracted: Conducted test cases in section 3.4~3.9 of this report.

1.8 Test Software

Item	Site	Manufacture	Name	Version
1.	03CH04-KS	AUDIX	E3	210616

1.9 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 22, 24, 27
- ♦ ANSI C63.26-2015
- ♦ FCC KDB 971168 D01 Power Meas License Digital Systems v03r01
- ♦ FCC KDB 412172 D01 Determining ERP and EIRP v01r01

Remark:

All test items were verified and recorded according to the standards and without any deviation during the test.



2 Test Configuration of Equipment Under Test

2.1 Test Mode

Antenna port conducted and radiated test items are performed according to KDB 971168 D01 Power Meas License Digital Systems v03r01 with maximum output power.

For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (X/Y plane) were recorded in this report.

The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst case emissions are reported.


Orthogonal Planes of EUT	X Plane	Y Plane	Z Plane

Test Items	5G NR	Bandwidth (MHz)														Modulation					RB #		Test Channel		
		5	10	15	20	25	30	35	40	45	70	80	90	100	PI/2 BPSK	QPSK	16QAM	64QAM	256QAM	1	Full	L	M	H	
Max. Output Power	n2	v	v	v	v	v	v	v	v	-	-	-	-	-	v	v	v	v	v	v	v	v	v	v	
	n5	v	v	v	v	-	-	-	-	-	-	-	-	-	v	v	v	v	v	v	v	v	v	v	
	n25	v	v	v	v	v	v	v	v	-	-	-	-	-	v	v	v	v	v	v	v	v	v	v	
	n26	v	v	v	v	-	-	-	-	-	-	-	-	-	v	v	v	v	v	v	v	v	v	v	
	n66	v	v	v	v	v	v	v	v	v	-	-	-	-	v	v	v	v	v	v	v	v	v	v	
Peak-to-Average Ratio	n25				v					-	-	-	-	-	v	v					v		v		
	n26				v	-	-	-	-	-	-	-	-	-	v	v					v		v		
	n66				v						-	-	-	-	v	v					v		v		
26dB and 99% Bandwidth	n25	v	v	v	v	v	v	v	v	-	-	-	-	-		v	v	v	v		v		v		
	n26	v	v	v	v	-	-	-	-	-	-	-	-	-		v	v	v	v		v		v		
	n66	v	v	v	v	v	v	v	v	v	-	-	-	-		v	v	v	v		v		v		
Conducted Band Edge	n25	v			v				v	-	-	-	-	-	v	v				v	v	v		v	
	n26	v	v		v	-	-	-	-	-	-	-	-	-	v	v				v	v	v		v	
	n66	v			v				v	v	-	-	-	-	v	v				v	v	v		v	
Conducted Spurious Emission	n25	v			v				v	-	-	-	-	-	v	v				v		v	v	v	
	n26	v	v		v	-	-	-	-	-	-	-	-	-	v	v				v		v	v	v	
	n66	v			v				v	v					v	v				v		v	v	v	



Test Items	5G NR	Bandwidth (MHz)													Modulation					RB #		Test Channel		
		5	10	15	20	25	30	35	40	45	70	80	90	100	PI/2 BPSK	QPSK	16QAM	64QAM	256QAM	1	Full	L	M	H
Frequency Stability	n25				v					-	-	-	-	-		v					v		v	
	n26				v	-	-	-	-	-	-	-	-	-		v					v		v	
	n66				v						-	-	-	-		v					v		v	
E.R.P / E.I.R.P	n2	v	v	v	v	v	v	v	v	-	-	-	-	-	v	v	v	v	v	v	v	v	v	v
	n5	v	v	v	v	-	-	-	-	-	-	-	-	-	v	v	v	v	v	v	v	v	v	v
	n25	v	v	v	v	v	v	v	v	-	-	-	-	-	v	v	v	v	v	v	v	v	v	v
	n26	v	v	v	v	-	-	-	-	-	-	-	-	-	v	v	v	v	v	v	v	v	v	v
	n66	v	v	v	v	v	v	v	v	v	-	-	-	-	v	v	v	v	v	v	v	v	v	v
Radiated Spurious Emission	n5	Worst Case																					v	
	n25	Worst Case																					v	
	n26	Worst Case																					v	
	n66	Worst Case																					v	
Note	1. The mark “v “ means that this configuration is chosen for testing 2. The mark “-“ means that this bandwidth is not supported. 3. The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst case emissions are reported. 4. Frequency Stability : Normal Voltage = 3.69V ; Low Voltage =3.30V. ; High Voltage =4.10V																							

2.2 Connection Diagram of Test System



The EUT has been configuration operated in a manner tended to maximize its emission characteristics in a typical application.

2.3 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	DC Power Supply	GW	GPS-3030D	N/A	N/A	Unshielded, 1.8 m
2.	LTE Base Station	Anritsu	MT8821C	N/A	N/A	Unshielded, 1.8 m
3.	NR Base Station	Anritsu	MT8000A	N/A	N/A	Unshielded, 1.8 m



2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss.

Offset = RF cable loss.

Following shows an offset computation example with cable loss 8.0 dB.

Example :

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)}. \\ &= 8.0 \text{ (dB)}\end{aligned}$$

2.5 Frequency List of Low/Middle/High Channels

5G NR n2 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
40	Channel	374000	376000	378000
	Frequency	1870	1880	1890
35	Channel	373500	376000	378500
	Frequency	1867.5	1880	1892.5
30	Channel	373000	376000	379000
	Frequency	1865	1880	1895
25	Channel	372500	376000	379500
	Frequency	1862.5	1880	1897.5
20	Channel	372000	376000	380000
	Frequency	1860	1880	1900
15	Channel	371500	376000	380500
	Frequency	1857.5	1880	1902.5
10	Channel	371000	376000	381000
	Frequency	1855	1880	1905
5	Channel	370500	376000	381500
	Frequency	1852.5	1880	1907.5



5G NR n5 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	166800	167300	167800
	Frequency	834	836.5	839
15	Channel	166300	167300	168300
	Frequency	831.5	836.5	841.5
10	Channel	165800	167300	168800
	Frequency	829	836.5	844
5	Channel	165300	167300	169300
	Frequency	826.5	836.5	846.5

5G NR n25 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
40	Channel	390000	392500	395000
	Frequency	1870	1882.5	1895
35	Channel	373500	376500	379500
	Frequency	1867.5	1882.5	1897.5
30	Channel	389000	392500	396000
	Frequency	1865	1882.5	1900
25	Channel	388500	392500	396500
	Frequency	1862.5	1882.5	1902.5
20	Channel	372000	376500	381000
	Frequency	1860	1882.5	1905
15	Channel	371500	376500	381500
	Frequency	1857.5	1882.5	1907.5
10	Channel	371000	376500	382000
	Frequency	1855	1882.5	1910
5	Channel	370500	376500	382500
	Frequency	1852.5	1882.5	1912.5



5G NR n26 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	166800	167300	167800
	Frequency	834	836.5	839
15	Channel	166300	167300	168300
	Frequency	831.5	836.5	841.5
10	Channel	165800	167300	168800
	Frequency	829	836.5	844
5	Channel	165300	167300	169300
	Frequency	826.5	836.5	846.5

5G NR n66 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
45	Channel	346500	349000	351500
	Frequency	1732.5	1745	1757.5
40	Channel	346000	349000	352000
	Frequency	1730	1745	1760
35	Channel	345500	349000	352500
	Frequency	1727.5	1745	1762.5
30	Channel	345000	349000	353000
	Frequency	1725	1745	1765
25	Channel	344500	349000	353500
	Frequency	1722.5	1745	1767.5
20	Channel	344000	349000	354000
	Frequency	1720	1745	1770
15	Channel	343500	349000	354500
	Frequency	1717.5	1745	1772.5
10	Channel	343000	349000	355000
	Frequency	1715	1745	1775
5	Channel	342500	349000	355500
	Frequency	1712.5	1745	1777.5

3 Conducted Test Items

3.1 Measuring Instruments


See list of measuring instruments of this test report.

3.2 Test Setup

3.2.1 Conducted Output Power



3.2.2 Peak-to-Average Ratio, Occupied Bandwidth, Conducted Band-Edge and Conducted Spurious Emission



3.2.3 Frequency Stability



3.3 Test Result of Conducted Test

Please refer to Appendix A.

3.4 Conducted Output Power and ERP/EIRP

3.4.1 Description of the Conducted Output Power Measurement and ERP/EIRP Measurement

A system simulator was used to establish communication with the EUT. Its parameters were set to force the EUT transmitting at maximum output power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

The ERP of mobile transmitters must not exceed 7 Watts for 5G NR n5, n26.

The EIRP of mobile transmitters must not exceed 2 Watts for 5G NR n2, n25.

The EIRP of mobile transmitters must not exceed 1 Watts for 5G NR n66.

According to KDB 412172 D01 Power Approach,

$EIRP = P_T + G_T - L_C$, $ERP = EIRP - 2.15$, where

P_T = transmitter output power in dBm

G_T = gain of the transmitting antenna in dBi

L_C = signal attenuation in the connecting cable between the transmitter and antenna in dB

3.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2
2. The transmitter output port was connected to the system simulator.
3. Set EUT at maximum power through the system simulator.
4. Select lowest, middle, and highest channels for each band and different modulation.
5. Measure and record the power level from the system simulator.

3.5 Peak-to-Average Ratio

3.5.1 Description of the PAR Measurement

Power Complementary Cumulative Distribution Function (CCDF) curves provide a means for characterizing the power peaks of a digitally modulated signal on a statistical basis. A CCDF curve depicts the probability of the peak signal amplitude exceeding the average power level. Most contemporary measurement instrumentation include the capability to produce CCDF curves for an input signal provided that the instrument's resolution bandwidth can be set wide enough to accommodate the entire input signal bandwidth. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.5.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2.3.4 (CCDF).
2. The EUT was connected to spectrum and system simulator via a power divider.
3. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
4. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
5. Record the deviation as Peak to Average Ratio.

3.6 Occupied Bandwidth

3.6.1 Description of Occupied Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

3.6.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.4
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
5. Set the detection mode to peak, and the trace mode to max hold.
6. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace.
(this is the reference value)
7. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
8. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “-X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
9. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.

3.7 Conducted Band Edge

3.7.1 Description of Conducted Band Edge Measurement

22.917(a)

For operations in the 824 – 849 MHz band, the FCC limit is $43 + 10\log_{10}(P[\text{Watts}])$ dB below the transmitter power $P(\text{Watts})$ in a 100kHz bandwidth. However, in the 1MHz bands immediately outside and adjacent to the licensee's frequency block, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

24.238 (a)

For operations in the 1850-1910 and 1930-1990 MHz band, the FCC limit is $43 + 10\log_{10}(P[\text{Watts}])$ dB below the transmitter power $P(\text{Watts})$ in a 1MHz bandwidth. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

27.53 (h)

For operations in the 1710 – 1755 MHz band, the FCC limit is $43 + 10\log_{10}(P[\text{Watts}])$ dB below the transmitter power $P(\text{Watts})$ in a 1 MHz bandwidth. However, in the 1MHz bands immediately outside and adjacent to the licensee's frequency block, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

3.7.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The band edges of low and high channels for the highest RF powers were measured.
4. Set RBW $\geq$ 1% EBW in the 1MHz band immediately outside and adjacent to the band edge.
5. Beyond the 1 MHz band from the band edge, RBW=1MHz was used or a narrower RBW was used (generally limited to no less than 1% of the OBW) and the measured power was integrated over the full required measurement bandwidth.
6. Set spectrum analyzer with RMS detector.
7. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
8. Checked that all the results comply with the emission limit line.

Example:

The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)

$$= P(W) - [43 + 10\log(P)] \text{ (dB)}$$

$$= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)} = -13\text{dBm}.$$

9. When using the integration method, the starting frequency of the integration shall be centered at one-half of the RBW away from the band edge.

3.8 Conducted Spurious Emission

3.8.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.

3.8.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.
The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz.
7. Set spectrum analyzer with RMS detector.
8. Taking the record of maximum spurious emission.
9. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
10. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10\log(P)]$ (dB)
 $= [30 + 10\log(P)]$ (dBm) - $[43 + 10\log(P)]$ (dB)
 $= -13\text{dBm}$.

3.9 Frequency Stability

3.9.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.

3.9.2 Test Procedures for Temperature Variation

1. The testing follows ANSI C63.26 section 5.6.4
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C step up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.9.3 Test Procedures for Voltage Variation

1. The testing follows ANSI C63.26 section 5.6.5
2. The EUT was placed in a temperature chamber at $20\pm 5^{\circ}\text{C}$ and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value for other than hand carried battery equipment.
4. For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.
5. The variation in frequency was measured for the worst case.

4 Radiated Test Items

4.1 Measuring Instruments


See list of measuring instruments of this test report.

4.2 Test Setup


4.2.1 For radiated test below 30MHz



4.2.2 For radiated test from 30MHz to 1GHz



4.2.3 For radiated test above 1GHz



4.3 Test Result of Radiated Test

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

Please refer to Appendix B.



4.4 Radiated Spurious Emission

4.4.1 Description of Radiated Spurious Emission

The radiated spurious emission was measured by substitution method according to ANSI C63.26. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

4.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.5
2. The EUT was placed on a turntable with 0.8 meter height for frequency below 1GHz and 1.5 meter height for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the receiving antenna mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between 1m to 4m to search the maximum spurious emission for both horizontal and vertical polarizations.
6. During the measurement, the system simulator parameters were set to force the EUT transmitting at maximum output power.
7. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
8. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
9. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
10. $EIRP \text{ (dBm)} = S.G. \text{ Power} - Tx \text{ Cable Loss} + Tx \text{ Antenna Gain}$
11. $ERP \text{ (dBm)} = EIRP - 2.15$
12. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)

$$= P(W) - [43 + 10\log(P)] \text{ (dB)}$$

$$= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$$

$$= -13\text{dBm}.$$



5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101078	10Hz~40GHz	Apr. 09, 2024	Nov. 16, 2024~ Nov 27, 2024	Apr. 08, 2025	Conducted (TH01-SZ)
DC Power Supply	TTI	PL330P	290070	Max 32V, 3A	Oct. 15, 2024	Nov. 16, 2024~ Nov 27, 2024	Oct. 14, 2025	Conducted (TH01-SZ)
Power Divider	TOJOIN	PS-2SM-04 265	60.06.020.007 7	0.4GHz~26.5GHz	Dec. 25, 2023	Nov. 16, 2024~ Nov 27, 2024	Dec. 24, 2024	Conducted (TH01-SZ)
Thermal Chamber	Ten Billion Hongzhangroup	LP-150U	H2014081803	-40~+150°C	Jul. 03, 2024	Nov. 16, 2024~ Nov 27, 2024	Jul. 02, 2025	Conducted (TH01-SZ)
EXA Spectrum Analyzer	Keysight	N9010A	MY55370528	10Hz-44G,MAX 30dB	Oct. 11, 2024	Nov. 23, 2024	Oct. 10, 2025	Radiation (03CH04-KS)
Loop Antenna	R&S	HFH2-Z2E	101125	9kHz~30MHz	Sep. 08, 2024	Nov. 23, 2024	Sep. 07, 2025	Radiation (03CH04-KS)
Bilog Antenna	TeseQ	CBL6111D	44483	30MHz-1GHz	Dec. 06, 2023	Nov. 23, 2024	Dec. 05, 2024	Radiation (03CH04-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00227860	1GHz~18GHz	Aug. 16, 2024	Nov. 23, 2024	Aug. 15, 2025	Radiation (03CH04-KS)
SHF-EHF Horn	Com-power	AH-840	101070	18GHz~40GHz	Jan. 27, 2024	Nov. 23, 2024	Jan. 26, 2025	Radiation (03CH04-KS)
Amplifier	SONOMA	310N	413740	9KHz-1GHz	Jan. 03, 2024	Nov. 23, 2024	Jan. 02, 2025	Radiation (03CH04-KS)
Amplifier	EM	EM18G40G A	060728	18~40GHz	Jan. 02, 2024	Nov. 23, 2024	Jan. 01, 2025	Radiation (03CH04-KS)
high gain Amplifier	EM	EM01G18G A	060840	1Ghz-18Ghz	Oct. 09, 2024	Nov. 23, 2024	Oct. 08, 2025	Radiation (03CH04-KS)
Amplifier	EM	EM01G18G A	060892	1Ghz-18Ghz	Oct. 09, 2024	Nov. 23, 2024	Oct. 08, 2025	Radiation (03CH04-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Nov. 23, 2024	NCR	Radiation (03CH04-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Nov. 23, 2024	NCR	Radiation (03CH04-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Nov. 23, 2024	NCR	Radiation (03CH04-KS)

NCR: No Calibration Required

6 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.26-2015. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Measurement

Test Item	Uncertainty
Conducted Spurious Emission & Bandedge	± 1.34 dB
Occupied Channel Bandwidth	± 0.012 MHz
Conducted Power	± 1.34 dB
Peak to Average Ratio	± 1.34 dB
Frequency Stability	± 1.3 Hz

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.83 dB
---	---------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.83 dB
---	---------

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.82 dB
---	---------

----- THE END -----



Appendix A. Test Results of Conducted Test

Test Engineer :	Khan Zhen	Temperature :	22~23℃
		Relative Humidity :	40~42%



Software Version: 23.06.1602

FR1 N2 ANT5

Transmitter Conducted Output Power And EIRP, ($G_T - L_C$)=-3.1dB

NR Band	SCS	Band Width	Arfcn	Freq(MHz)	Modulation	RB	Conducted Power(dBm)	EIRP(dBm)	EIRP(W)
2	15	5	370500	1852.5	DFT-s-OFDM QPSK	1@1	22.69	19.59	0.0910
2	15	5	370500	1852.5	DFT-s-OFDM 16 QAM	1@1	22.08	18.98	0.0791
2	15	5	376000	1880	DFT-s-OFDM QPSK	1@1	22.74	19.64	0.0920
2	15	5	376000	1880	DFT-s-OFDM 16 QAM	1@1	22.03	18.93	0.0782
2	15	5	381500	1907.5	DFT-s-OFDM QPSK	1@1	22.65	19.55	0.0902
2	15	5	381500	1907.5	DFT-s-OFDM 16 QAM	1@1	21.97	18.87	0.0771
2	15	10	371000	1855	DFT-s-OFDM QPSK	1@1	22.96	19.86	0.0968
2	15	10	371000	1855	DFT-s-OFDM 16 QAM	1@1	22.13	19.03	0.0800
2	15	10	376000	1880	DFT-s-OFDM QPSK	1@1	22.82	19.72	0.0938
2	15	10	376000	1880	DFT-s-OFDM 16 QAM	1@1	22.13	19.03	0.0800
2	15	10	381000	1905	DFT-s-OFDM QPSK	1@1	22.88	19.78	0.0951
2	15	10	381000	1905	DFT-s-OFDM 16 QAM	1@1	22.07	18.97	0.0789
2	15	15	371500	1857.5	DFT-s-OFDM QPSK	1@1	22.90	19.80	0.0955
2	15	15	371500	1857.5	DFT-s-OFDM 16 QAM	1@1	22.14	19.04	0.0802
2	15	15	376000	1880	DFT-s-OFDM QPSK	1@1	22.89	19.79	0.0953
2	15	15	376000	1880	DFT-s-OFDM 16 QAM	1@1	22.13	19.03	0.0800
2	15	15	380500	1902.5	DFT-s-OFDM QPSK	1@1	23.00	19.90	0.0977
2	15	15	380500	1902.5	DFT-s-OFDM 16 QAM	1@1	22.26	19.16	0.0824
2	15	20	372000	1860	DFT-s-OFDM QPSK	1@1	22.88	19.78	0.0951
2	15	20	372000	1860	DFT-s-OFDM 16 QAM	1@1	22.01	18.91	0.0778
2	15	20	376000	1880	DFT-s-OFDM QPSK	1@1	22.69	19.59	0.0910
2	15	20	376000	1880	DFT-s-OFDM 16 QAM	1@1	22.10	19.00	0.0794
2	15	20	380000	1900	DFT-s-OFDM QPSK	1@1	23.00	19.90	0.0977
2	15	20	380000	1900	DFT-s-OFDM 16 QAM	1@1	22.31	19.21	0.0834
2	15	25	372500	1862.5	DFT-s-OFDM QPSK	1@1	22.86	19.76	0.0946
2	15	25	372500	1862.5	DFT-s-OFDM 16 QAM	1@1	22.11	19.01	0.0796
2	15	25	376000	1880	DFT-s-OFDM QPSK	1@1	22.75	19.65	0.0923
2	15	25	376000	1880	DFT-s-OFDM 16 QAM	1@1	22.05	18.95	0.0785
2	15	25	379500	1897.5	DFT-s-OFDM QPSK	1@1	23.12	20.02	0.1005
2	15	25	379500	1897.5	DFT-s-OFDM 16 QAM	1@1	22.35	19.25	0.0841



2	15	30	373000	1865	DFT-s-OFDM QPSK	1@1	23.02	19.92	0.0982
2	15	30	373000	1865	DFT-s-OFDM 16 QAM	1@1	22.20	19.10	0.0813
2	15	30	376000	1880	DFT-s-OFDM QPSK	1@1	22.81	19.71	0.0935
2	15	30	376000	1880	DFT-s-OFDM 16 QAM	1@1	21.99	18.89	0.0774
2	15	30	379000	1895	DFT-s-OFDM QPSK	1@1	23.03	19.93	0.0984
2	15	30	379000	1895	DFT-s-OFDM 16 QAM	1@1	22.26	19.16	0.0824
2	15	35	373500	1867.5	DFT-s-OFDM QPSK	1@1	23.74	20.64	0.1159
2	15	35	373500	1867.5	DFT-s-OFDM 16 QAM	1@1	23.04	19.94	0.0986
2	15	35	376000	1880	DFT-s-OFDM QPSK	1@1	23.56	20.46	0.1112
2	15	35	376000	1880	DFT-s-OFDM 16 QAM	1@1	22.91	19.81	0.0957
2	15	35	378500	1892.5	DFT-s-OFDM QPSK	1@1	23.61	20.51	0.1125
2	15	35	378500	1892.5	DFT-s-OFDM 16 QAM	1@1	22.99	19.89	0.0975
2	15	40	374000	1870	DFT-s-OFDM PI/2 BPSK	108@54	23.69	20.59	0.1146
2	15	40	374000	1870	DFT-s-OFDM PI/2 BPSK	1@1	23.69	20.59	0.1146
2	15	40	374000	1870	DFT-s-OFDM PI/2 BPSK	1@214	23.80	20.70	0.1175
2	15	40	374000	1870	DFT-s-OFDM QPSK	108@54	23.65	20.55	0.1135
2	15	40	374000	1870	DFT-s-OFDM QPSK	1@1	23.70	20.60	0.1148
2	15	40	374000	1870	DFT-s-OFDM QPSK	1@214	23.85	20.75	0.1189
2	15	40	374000	1870	DFT-s-OFDM 16 QAM	108@54	22.87	19.77	0.0948
2	15	40	374000	1870	DFT-s-OFDM 16 QAM	1@1	22.93	19.83	0.0962
2	15	40	374000	1870	DFT-s-OFDM 16 QAM	1@214	23.12	20.02	0.1005
2	15	40	374000	1870	DFT-s-OFDM 64 QAM	108@54	21.34	18.24	0.0667
2	15	40	374000	1870	DFT-s-OFDM 64 QAM	1@1	21.46	18.36	0.0685
2	15	40	374000	1870	DFT-s-OFDM 64 QAM	1@214	21.59	18.49	0.0706
2	15	40	374000	1870	DFT-s-OFDM 256 QAM	108@54	19.34	16.24	0.0421
2	15	40	374000	1870	DFT-s-OFDM 256 QAM	1@1	19.13	16.03	0.0401
2	15	40	374000	1870	DFT-s-OFDM 256 QAM	1@214	19.24	16.14	0.0411
2	15	40	374000	1870	CP-OFDM QPSK	108@54	22.50	19.40	0.0871
2	15	40	374000	1870	CP-OFDM QPSK	1@1	22.81	19.71	0.0935
2	15	40	374000	1870	CP-OFDM QPSK	1@214	22.95	19.85	0.0966
2	15	40	376000	1880	DFT-s-OFDM PI/2 BPSK	108@54	23.61	20.51	0.1125
2	15	40	376000	1880	DFT-s-OFDM PI/2 BPSK	1@1	23.59	20.49	0.1119
2	15	40	376000	1880	DFT-s-OFDM PI/2 BPSK	1@214	23.72	20.62	0.1153
2	15	40	376000	1880	DFT-s-OFDM QPSK	108@54	23.75	20.65	0.1161
2	15	40	376000	1880	DFT-s-OFDM QPSK	1@1	23.61	20.51	0.1125
2	15	40	376000	1880	DFT-s-OFDM QPSK	1@214	23.82	20.72	0.1180
2	15	40	376000	1880	DFT-s-OFDM 16 QAM	108@54	22.94	19.84	0.0964
2	15	40	376000	1880	DFT-s-OFDM 16 QAM	1@1	22.78	19.68	0.0929



2	15	40	376000	1880	DFT-s-OFDM 16 QAM	1@214	22.93	19.83	0.0962
2	15	40	376000	1880	DFT-s-OFDM 64 QAM	108@54	21.44	18.34	0.0682
2	15	40	376000	1880	DFT-s-OFDM 64 QAM	1@1	21.33	18.23	0.0665
2	15	40	376000	1880	DFT-s-OFDM 64 QAM	1@214	21.51	18.41	0.0693
2	15	40	376000	1880	DFT-s-OFDM 256 QAM	108@54	19.46	16.36	0.0433
2	15	40	376000	1880	DFT-s-OFDM 256 QAM	1@1	18.94	15.84	0.0384
2	15	40	376000	1880	DFT-s-OFDM 256 QAM	1@214	19.10	16.00	0.0398
2	15	40	376000	1880	CP-OFDM QPSK	108@54	22.54	19.44	0.0879
2	15	40	376000	1880	CP-OFDM QPSK	1@1	22.57	19.47	0.0885
2	15	40	376000	1880	CP-OFDM QPSK	1@214	22.74	19.64	0.0920
2	15	40	378000	1890	DFT-s-OFDM PI/2 BPSK	108@54	23.76	20.66	0.1164
2	15	40	378000	1890	DFT-s-OFDM PI/2 BPSK	1@1	23.61	20.51	0.1125
2	15	40	378000	1890	DFT-s-OFDM PI/2 BPSK	1@214	23.61	20.51	0.1125
2	15	40	378000	1890	DFT-s-OFDM QPSK	108@54	23.81	20.71	0.1178
2	15	40	378000	1890	DFT-s-OFDM QPSK	1@1	23.74	20.64	0.1159
2	15	40	378000	1890	DFT-s-OFDM QPSK	1@214	23.62	20.52	0.1127
2	15	40	378000	1890	DFT-s-OFDM 16 QAM	108@54	23.08	19.98	0.0995
2	15	40	378000	1890	DFT-s-OFDM 16 QAM	1@1	22.92	19.82	0.0959
2	15	40	378000	1890	DFT-s-OFDM 16 QAM	1@214	22.81	19.71	0.0935
2	15	40	378000	1890	DFT-s-OFDM 64 QAM	108@54	21.57	18.47	0.0703
2	15	40	378000	1890	DFT-s-OFDM 64 QAM	1@1	21.46	18.36	0.0685
2	15	40	378000	1890	DFT-s-OFDM 64 QAM	1@214	21.46	18.36	0.0685
2	15	40	378000	1890	DFT-s-OFDM 256 QAM	108@54	19.54	16.44	0.0441
2	15	40	378000	1890	DFT-s-OFDM 256 QAM	1@1	19.06	15.96	0.0394
2	15	40	378000	1890	DFT-s-OFDM 256 QAM	1@214	19.00	15.90	0.0389
2	15	40	378000	1890	CP-OFDM QPSK	108@54	22.68	19.58	0.0908
2	15	40	378000	1890	CP-OFDM QPSK	1@1	22.74	19.64	0.0920
2	15	40	378000	1890	CP-OFDM QPSK	1@214	22.65	19.55	0.0902



Software Version: 23.06.1602

FR1 N5 ANT1

Transmitter Conducted Output Power And ERP, (G_T - L_C)=-3.1dB

NR Band	SCS	Band Width	Arfcn	Freq (MHz)	Modulation	RB	Conducted Power(dBm)	ERP (dBm)	ERP (W)
5	15	5	165300	826.5	DFT-s-OFDM QPSK	1@1	25.18	19.23	0.0838
5	15	5	165300	826.5	DFT-s-OFDM 16 QAM	1@1	24.45	18.5	0.0708
5	15	5	167300	836.5	DFT-s-OFDM QPSK	1@1	25.06	19.11	0.0815
5	15	5	167300	836.5	DFT-s-OFDM 16 QAM	1@1	24.28	18.33	0.0681
5	15	5	169300	846.5	DFT-s-OFDM QPSK	1@1	25.08	19.13	0.0818
5	15	5	169300	846.5	DFT-s-OFDM 16 QAM	1@1	24.31	18.36	0.0685
5	15	10	165800	829	DFT-s-OFDM QPSK	1@1	25.09	19.14	0.0820
5	15	10	165800	829	DFT-s-OFDM 16 QAM	1@1	24.3	18.35	0.0684
5	15	10	167300	836.5	DFT-s-OFDM QPSK	1@1	25.22	19.27	0.0845
5	15	10	167300	836.5	DFT-s-OFDM 16 QAM	1@1	24.28	18.33	0.0681
5	15	10	168800	844	DFT-s-OFDM QPSK	1@1	25.15	19.2	0.0832
5	15	10	168800	844	DFT-s-OFDM 16 QAM	1@1	24.18	18.23	0.0665
5	15	15	166300	831.5	DFT-s-OFDM QPSK	1@1	25.17	19.22	0.0836
5	15	15	166300	831.5	DFT-s-OFDM 16 QAM	1@1	24.31	18.36	0.0685
5	15	15	167300	836.5	DFT-s-OFDM QPSK	1@1	25.17	19.22	0.0836
5	15	15	167300	836.5	DFT-s-OFDM 16 QAM	1@1	24.35	18.4	0.0692
5	15	15	168300	841.5	DFT-s-OFDM QPSK	1@1	25.15	19.2	0.0832
5	15	15	168300	841.5	DFT-s-OFDM 16 QAM	1@1	24.29	18.34	0.0682
5	15	20	166800	834	DFT-s-OFDM PI/2 BPSK	50@25	25.11	19.16	0.0824
5	15	20	166800	834	DFT-s-OFDM PI/2 BPSK	1@1	25.12	19.17	0.0826
5	15	20	166800	834	DFT-s-OFDM PI/2 BPSK	1@104	25.06	19.11	0.0815
5	15	20	166800	834	DFT-s-OFDM QPSK	50@25	25.2	19.25	0.0841
5	15	20	166800	834	DFT-s-OFDM QPSK	1@1	25.22	19.27	0.0845
5	15	20	166800	834	DFT-s-OFDM QPSK	1@104	25.08	19.13	0.0818
5	15	20	166800	834	DFT-s-OFDM 16 QAM	50@25	24.29	18.34	0.0682
5	15	20	166800	834	DFT-s-OFDM 16 QAM	1@1	24.19	18.24	0.0667
5	15	20	166800	834	DFT-s-OFDM 16 QAM	1@104	24.28	18.33	0.0681
5	15	20	166800	834	DFT-s-OFDM 64 QAM	50@25	22.88	16.93	0.0493
5	15	20	166800	834	DFT-s-OFDM 64 QAM	1@1	22.83	16.88	0.0488
5	15	20	166800	834	DFT-s-OFDM 64 QAM	1@104	22.72	16.77	0.0475
5	15	20	166800	834	DFT-s-OFDM 256 QAM	50@25	20.78	14.83	0.0304
5	15	20	166800	834	DFT-s-OFDM 256 QAM	1@1	20.38	14.43	0.0277
5	15	20	166800	834	DFT-s-OFDM 256 QAM	1@104	20.23	14.28	0.0268
5	15	20	166800	834	CP-OFDM QPSK	53@26	23.89	17.94	0.0622



5	15	20	166800	834	CP-OFDM QPSK	1@1	24.14	18.19	0.0659
5	15	20	166800	834	CP-OFDM QPSK	1@104	23.99	18.04	0.0637
5	15	20	167300	836.5	DFT-s-OFDM PI/2 BPSK	50@25	25.19	19.24	0.0839
5	15	20	167300	836.5	DFT-s-OFDM PI/2 BPSK	1@1	25.17	19.22	0.0836
5	15	20	167300	836.5	DFT-s-OFDM PI/2 BPSK	1@104	24.97	19.02	0.0798
5	15	20	167300	836.5	DFT-s-OFDM QPSK	50@25	25.23	19.28	0.0847
5	15	20	167300	836.5	DFT-s-OFDM QPSK	1@1	25.21	19.26	0.0843
5	15	20	167300	836.5	DFT-s-OFDM QPSK	1@104	25	19.05	0.0804
5	15	20	167300	836.5	DFT-s-OFDM 16 QAM	50@25	24.24	18.29	0.0675
5	15	20	167300	836.5	DFT-s-OFDM 16 QAM	1@1	24.35	18.4	0.0692
5	15	20	167300	836.5	DFT-s-OFDM 16 QAM	1@104	24.19	18.24	0.0667
5	15	20	167300	836.5	DFT-s-OFDM 64 QAM	50@25	22.82	16.87	0.0486
5	15	20	167300	836.5	DFT-s-OFDM 64 QAM	1@1	22.87	16.92	0.0492
5	15	20	167300	836.5	DFT-s-OFDM 64 QAM	1@104	22.64	16.69	0.0467
5	15	20	167300	836.5	DFT-s-OFDM 256 QAM	50@25	20.73	14.78	0.0301
5	15	20	167300	836.5	DFT-s-OFDM 256 QAM	1@1	20.38	14.43	0.0277
5	15	20	167300	836.5	DFT-s-OFDM 256 QAM	1@104	20.22	14.27	0.0267
5	15	20	167300	836.5	CP-OFDM QPSK	53@26	23.92	17.97	0.0627
5	15	20	167300	836.5	CP-OFDM QPSK	1@1	24.1	18.15	0.0653
5	15	20	167300	836.5	CP-OFDM QPSK	1@104	23.94	17.99	0.0630
5	15	20	167800	839	DFT-s-OFDM PI/2 BPSK	50@25	25.08	19.13	0.0818
5	15	20	167800	839	DFT-s-OFDM PI/2 BPSK	1@1	25.2	19.25	0.0841
5	15	20	167800	839	DFT-s-OFDM PI/2 BPSK	1@104	24.99	19.04	0.0802
5	15	20	167800	839	DFT-s-OFDM QPSK	50@25	25.16	19.21	0.0834
5	15	20	167800	839	DFT-s-OFDM QPSK	1@1	25.19	19.24	0.0839
5	15	20	167800	839	DFT-s-OFDM QPSK	1@104	25.13	19.18	0.0828
5	15	20	167800	839	DFT-s-OFDM 16 QAM	50@25	24.16	18.21	0.0662
5	15	20	167800	839	DFT-s-OFDM 16 QAM	1@1	24.29	18.34	0.0682
5	15	20	167800	839	DFT-s-OFDM 16 QAM	1@104	24.27	18.32	0.0679
5	15	20	167800	839	DFT-s-OFDM 64 QAM	50@25	22.72	16.77	0.0475
5	15	20	167800	839	DFT-s-OFDM 64 QAM	1@1	22.83	16.88	0.0488
5	15	20	167800	839	DFT-s-OFDM 64 QAM	1@104	22.72	16.77	0.0475
5	15	20	167800	839	DFT-s-OFDM 256 QAM	50@25	20.61	14.66	0.0292
5	15	20	167800	839	DFT-s-OFDM 256 QAM	1@1	20.41	14.46	0.0279
5	15	20	167800	839	DFT-s-OFDM 256 QAM	1@104	20.29	14.34	0.0272
5	15	20	167800	839	CP-OFDM QPSK	53@26	23.79	17.84	0.0608
5	15	20	167800	839	CP-OFDM QPSK	1@1	24.1	18.15	0.0653
5	15	20	167800	839	CP-OFDM QPSK	1@104	24.04	18.09	0.0644



Software Version: 23.06.1602

FR1 N25 ANT5

Transmitter Conducted Output Power And EIRP, ($G_T - L_c$)=-2.7dB

NR Band	SCS	Band Width	Arfcn	Freq MHz)	Modulation	RB	Conducted Power(dBm)	EIRP(dBm)	EIRP(W)
25	15	5	370500	1852.5	DFT-s-OFDM QPSK	1@1	23.85	21.15	0.1303
25	15	5	370500	1852.5	DFT-s-OFDM 16 QAM	1@1	23.00	20.30	0.1072
25	15	5	376500	1882.5	DFT-s-OFDM QPSK	1@1	23.98	21.28	0.1343
25	15	5	376500	1882.5	DFT-s-OFDM 16 QAM	1@1	23.10	20.40	0.1096
25	15	5	382500	1912.5	DFT-s-OFDM QPSK	1@1	23.30	20.60	0.1148
25	15	5	382500	1912.5	DFT-s-OFDM 16 QAM	1@1	22.51	19.81	0.0957
25	15	10	371000	1855	DFT-s-OFDM QPSK	1@1	23.63	20.93	0.1239
25	15	10	371000	1855	DFT-s-OFDM 16 QAM	1@1	22.67	19.97	0.0993
25	15	10	376500	1882.5	DFT-s-OFDM QPSK	1@1	24.01	21.31	0.1352
25	15	10	376500	1882.5	DFT-s-OFDM 16 QAM	1@1	22.70	20.00	0.1000
25	15	10	382000	1910	DFT-s-OFDM QPSK	1@1	23.90	21.20	0.1318
25	15	10	382000	1910	DFT-s-OFDM 16 QAM	1@1	22.50	19.80	0.0955
25	15	15	371500	1857.5	DFT-s-OFDM QPSK	1@1	24.07	21.37	0.1371
25	15	15	371500	1857.5	DFT-s-OFDM 16 QAM	1@1	22.71	20.01	0.1002
25	15	15	376500	1882.5	DFT-s-OFDM QPSK	1@1	24.02	21.32	0.1355
25	15	15	376500	1882.5	DFT-s-OFDM 16 QAM	1@1	22.69	19.99	0.0998
25	15	15	381500	1907.5	DFT-s-OFDM QPSK	1@1	24.06	21.36	0.1368
25	15	15	381500	1907.5	DFT-s-OFDM 16 QAM	1@1	22.69	19.99	0.0998
25	15	20	372000	1860	DFT-s-OFDM QPSK	1@1	24.06	21.36	0.1368
25	15	20	372000	1860	DFT-s-OFDM 16 QAM	1@1	22.58	19.88	0.0973
25	15	20	376500	1882.5	DFT-s-OFDM QPSK	1@1	23.55	20.85	0.1216
25	15	20	376500	1882.5	DFT-s-OFDM 16 QAM	1@1	22.57	19.87	0.0971
25	15	20	381000	1905	DFT-s-OFDM QPSK	1@1	23.68	20.98	0.1253
25	15	20	381000	1905	DFT-s-OFDM 16 QAM	1@1	23.24	20.54	0.1132
25	15	25	372500	1862.5	DFT-s-OFDM QPSK	1@1	23.63	20.93	0.1239
25	15	25	372500	1862.5	DFT-s-OFDM 16 QAM	1@1	23.12	20.42	0.1102



25	15	25	376500	1882.5	DFT-s-OFDM QPSK	1@1	23.94	21.24	0.1330
25	15	25	376500	1882.5	DFT-s-OFDM 16 QAM	1@1	23.06	20.36	0.1086
25	15	25	380500	1902.5	DFT-s-OFDM QPSK	1@1	23.78	21.08	0.1282
25	15	25	380500	1902.5	DFT-s-OFDM 16 QAM	1@1	22.82	20.12	0.1028
25	15	30	373000	1865	DFT-s-OFDM QPSK	1@1	23.74	21.04	0.1271
25	15	30	373000	1865	DFT-s-OFDM 16 QAM	1@1	22.72	20.02	0.1005
25	15	30	376500	1882.5	DFT-s-OFDM QPSK	1@1	23.50	20.80	0.1202
25	15	30	376500	1882.5	DFT-s-OFDM 16 QAM	1@1	22.66	19.96	0.0991
25	15	30	380000	1900	DFT-s-OFDM QPSK	1@1	23.76	21.06	0.1276
25	15	30	380000	1900	DFT-s-OFDM 16 QAM	1@1	22.83	20.13	0.1030
25	15	35	373500	1867.5	DFT-s-OFDM QPSK	1@1	23.78	21.08	0.1282
25	15	35	373500	1867.5	DFT-s-OFDM 16 QAM	1@1	23.05	20.35	0.1084
25	15	35	376500	1882.5	DFT-s-OFDM QPSK	1@1	23.63	20.93	0.1239
25	15	35	376500	1882.5	DFT-s-OFDM 16 QAM	1@1	22.98	20.28	0.1067
25	15	35	379500	1897.5	DFT-s-OFDM QPSK	1@1	23.72	21.02	0.1265
25	15	35	379500	1897.5	DFT-s-OFDM 16 QAM	1@1	23.14	20.44	0.1107
25	15	40	374000	1870	DFT-s-OFDM PI/2 BPSK	108@54	23.87	21.17	0.1309
25	15	40	374000	1870	DFT-s-OFDM PI/2 BPSK	1@1	23.81	21.11	0.1291
25	15	40	374000	1870	DFT-s-OFDM PI/2 BPSK	1@214	23.88	21.18	0.1312
25	15	40	374000	1870	DFT-s-OFDM QPSK	108@54	23.76	21.06	0.1276
25	15	40	374000	1870	DFT-s-OFDM QPSK	1@1	23.83	21.13	0.1297
25	15	40	374000	1870	DFT-s-OFDM QPSK	1@214	24.10	21.40	0.1380
25	15	40	374000	1870	DFT-s-OFDM 16 QAM	108@54	23.11	20.41	0.1099
25	15	40	374000	1870	DFT-s-OFDM 16 QAM	1@1	23.12	20.42	0.1102
25	15	40	374000	1870	DFT-s-OFDM 16 QAM	1@214	23.30	20.60	0.1148
25	15	40	374000	1870	DFT-s-OFDM 64 QAM	108@54	21.50	18.80	0.0759
25	15	40	374000	1870	DFT-s-OFDM 64 QAM	1@1	21.73	19.03	0.0800
25	15	40	374000	1870	DFT-s-OFDM 64 QAM	1@214	21.76	19.06	0.0805
25	15	40	374000	1870	DFT-s-OFDM 256 QAM	108@54	19.52	16.82	0.0481
25	15	40	374000	1870	DFT-s-OFDM 256 QAM	1@1	19.29	16.59	0.0456
25	15	40	374000	1870	DFT-s-OFDM 256 QAM	1@214	19.44	16.74	0.0472



25	15	40	374000	1870	CP-OFDM QPSK	108@54	22.69	19.99	0.0998
25	15	40	374000	1870	CP-OFDM QPSK	1@1	22.89	20.19	0.1045
25	15	40	374000	1870	CP-OFDM QPSK	1@214	23.11	20.41	0.1099
25	15	40	376500	1882.5	DFT-s-OFDM PI/2 BPSK	108@54	23.87	21.17	0.1309
25	15	40	376500	1882.5	DFT-s-OFDM PI/2 BPSK	1@1	23.74	21.04	0.1271
25	15	40	376500	1882.5	DFT-s-OFDM PI/2 BPSK	1@214	23.77	21.07	0.1279
25	15	40	376500	1882.5	DFT-s-OFDM QPSK	108@54	23.88	21.18	0.1312
25	15	40	376500	1882.5	DFT-s-OFDM QPSK	1@1	23.72	21.02	0.1265
25	15	40	376500	1882.5	DFT-s-OFDM QPSK	1@214	23.83	21.13	0.1297
25	15	40	376500	1882.5	DFT-s-OFDM 16 QAM	108@54	23.13	20.43	0.1104
25	15	40	376500	1882.5	DFT-s-OFDM 16 QAM	1@1	23.03	20.33	0.1079
25	15	40	376500	1882.5	DFT-s-OFDM 16 QAM	1@214	23.08	20.38	0.1091
25	15	40	376500	1882.5	DFT-s-OFDM 64 QAM	108@54	21.70	19.00	0.0794
25	15	40	376500	1882.5	DFT-s-OFDM 64 QAM	1@1	21.38	18.68	0.0738
25	15	40	376500	1882.5	DFT-s-OFDM 64 QAM	1@214	21.57	18.87	0.0771
25	15	40	376500	1882.5	DFT-s-OFDM 256 QAM	108@54	19.59	16.89	0.0489
25	15	40	376500	1882.5	DFT-s-OFDM 256 QAM	1@1	19.09	16.39	0.0436
25	15	40	376500	1882.5	DFT-s-OFDM 256 QAM	1@214	19.25	16.55	0.0452
25	15	40	376500	1882.5	CP-OFDM QPSK	108@54	22.71	20.01	0.1002
25	15	40	376500	1882.5	CP-OFDM QPSK	1@1	22.86	20.16	0.1038
25	15	40	376500	1882.5	CP-OFDM QPSK	1@214	22.94	20.24	0.1057
25	15	40	379000	1895	DFT-s-OFDM PI/2 BPSK	108@54	23.99	21.29	0.1346
25	15	40	379000	1895	DFT-s-OFDM PI/2 BPSK	1@1	23.80	21.10	0.1288
25	15	40	379000	1895	DFT-s-OFDM PI/2 BPSK	1@214	23.96	21.26	0.1337
25	15	40	379000	1895	DFT-s-OFDM QPSK	108@54	23.98	21.28	0.1343
25	15	40	379000	1895	DFT-s-OFDM QPSK	1@1	23.86	21.16	0.1306
25	15	40	379000	1895	DFT-s-OFDM QPSK	1@214	23.95	21.25	0.1334
25	15	40	379000	1895	DFT-s-OFDM 16 QAM	108@54	23.22	20.52	0.1127
25	15	40	379000	1895	DFT-s-OFDM 16 QAM	1@1	23.26	20.56	0.1138
25	15	40	379000	1895	DFT-s-OFDM 16 QAM	1@214	23.28	20.58	0.1143
25	15	40	379000	1895	DFT-s-OFDM 64 QAM	108@54	21.85	19.15	0.0822
25	15	40	379000	1895	DFT-s-OFDM 64 QAM	1@1	21.82	19.12	0.0817
25	15	40	379000	1895	DFT-s-OFDM 64 QAM	1@214	21.68	18.98	0.0791



25	15	40	379000	1895	DFT-s-OFDM 256 QAM	108@54	19.73	17.03	0.0505
25	15	40	379000	1895	DFT-s-OFDM 256 QAM	1@1	19.37	16.67	0.0465
25	15	40	379000	1895	DFT-s-OFDM 256 QAM	1@214	19.34	16.64	0.0461
25	15	40	379000	1895	CP-OFDM QPSK	108@54	22.95	20.25	0.1059
25	15	40	379000	1895	CP-OFDM QPSK	1@1	23.05	20.35	0.1084
25	15	40	379000	1895	CP-OFDM QPSK	1@214	22.92	20.22	0.1052


Frequency Stability

NR Band	SCS (kHz)	Bandwidth (MHz)	Arfcn	Freq (MHz)	Modulation	RB	Deviation (Hz)	Verdict	Environment
25	15	20	376500	1882.5	DFT-s-OFDM QPSK	100@0	11.3	PASS	NV
25	15	20	376500	1882.5	DFT-s-OFDM QPSK	100@0	12.7	PASS	LV
25	15	20	376500	1882.5	DFT-s-OFDM QPSK	100@0	18.6	PASS	HV
25	15	20	376500	1882.5	DFT-s-OFDM QPSK	100@0	11.6	PASS	-30°C
25	15	20	376500	1882.5	DFT-s-OFDM QPSK	100@0	11	PASS	-20°C
25	15	20	376500	1882.5	DFT-s-OFDM QPSK	100@0	15.6	PASS	-10°C
25	15	20	376500	1882.5	DFT-s-OFDM QPSK	100@0	12	PASS	0°C
25	15	20	376500	1882.5	DFT-s-OFDM QPSK	100@0	15.1	PASS	10°C
25	15	20	376500	1882.5	DFT-s-OFDM QPSK	100@0	18.6	PASS	20°C
25	15	20	376500	1882.5	DFT-s-OFDM QPSK	100@0	12.3	PASS	30°C
25	15	20	376500	1882.5	DFT-s-OFDM QPSK	100@0	11.6	PASS	40°C
25	15	20	376500	1882.5	DFT-s-OFDM QPSK	100@0	12.8	PASS	50°C


Peak to Average Ratio

NR Band	SCS (kHz)	Bandwidth (MHz)	Arfcn	Freq (MHz)	Modulation	RB	Result (dB)	Limit (dB)	Verdict
25	15	20	376500	1882.5	DFT-s-OFDM PI/2 BPSK	100@0	4.04	13	PASS
25	15	20	376500	1882.5	DFT-s-OFDM QPSK	100@0	5.2	13	PASS

N25(20M)_DFT-s-OFDM_PI_2-BPSK_Outer_Full_Mid_CH



N25(20M)_DFT-s-OFDM_QPSK_Outer_Full_Mid_CH



**Occupied Bandwidth**

NR Band	SCS (kHz)	Bandwidth (MHz)	Arfcn	Freq (MHz)	Modulation	RB	OBW (MHz)	26dB BW (MHz)
25	15	5	376500	1882.5	CP-OFDM QPSK	25@0	4.469	5.007
25	15	5	376500	1882.5	CP-OFDM 16 QAM	25@0	4.4722	5.036
25	15	5	376500	1882.5	CP-OFDM 64 QAM	25@0	4.4649	4.997
25	15	5	376500	1882.5	CP-OFDM 256 QAM	25@0	4.4778	5.041
25	15	10	376500	1882.5	CP-OFDM QPSK	52@0	9.2849	10.05
25	15	10	376500	1882.5	CP-OFDM 16 QAM	52@0	9.2846	9.9
25	15	10	376500	1882.5	CP-OFDM 64 QAM	52@0	9.2468	9.97
25	15	10	376500	1882.5	CP-OFDM 256 QAM	52@0	9.2627	10.09
25	15	15	376500	1882.5	CP-OFDM QPSK	79@0	14.075	14.99
25	15	15	376500	1882.5	CP-OFDM 16 QAM	79@0	14.088	14.83
25	15	15	376500	1882.5	CP-OFDM 64 QAM	79@0	14.102	14.75
25	15	15	376500	1882.5	CP-OFDM 256 QAM	79@0	14.079	14.96
25	15	20	376500	1882.5	CP-OFDM QPSK	106@0	18.916	19.84
25	15	20	376500	1882.5	CP-OFDM 16 QAM	106@0	18.936	19.83
25	15	20	376500	1882.5	CP-OFDM 64 QAM	106@0	18.87	19.85
25	15	20	376500	1882.5	CP-OFDM 256 QAM	106@0	18.884	19.73
25	15	25	376500	1882.5	CP-OFDM QPSK	133@0	23.705	24.69
25	15	25	376500	1882.5	CP-OFDM 16 QAM	133@0	23.76	24.93
25	15	25	376500	1882.5	CP-OFDM 64 QAM	133@0	23.748	24.75
25	15	25	376500	1882.5	CP-OFDM 256 QAM	133@0	23.731	24.66
25	15	30	376500	1882.5	CP-OFDM QPSK	160@0	28.552	29.67
25	15	30	376500	1882.5	CP-OFDM 16 QAM	160@0	28.575	29.59



25	15	30	376500	1882.5	CP-OFDM 64 QAM	160@0	28.497	29.53
25	15	30	376500	1882.5	CP-OFDM 256 QAM	160@0	28.552	29.58
25	15	35	376500	1882.5	CP-OFDM QPSK	188@0	33.528	34.8
25	15	35	376500	1882.5	CP-OFDM 16 QAM	188@0	33.464	34.75
25	15	35	376500	1882.5	CP-OFDM 64 QAM	188@0	33.515	34.79
25	15	35	376500	1882.5	CP-OFDM 256 QAM	188@0	33.51	34.71
25	15	40	376500	1882.5	CP-OFDM QPSK	216@0	38.52	40.06
25	15	40	376500	1882.5	CP-OFDM 16 QAM	216@0	38.578	40.02
25	15	40	376500	1882.5	CP-OFDM 64 QAM	216@0	38.47	39.99
25	15	40	376500	1882.5	CP-OFDM 256 QAM	216@0	38.544	39.88




N25(5M)_CP-
OFDM_QPSK_Outer_Full_Mid_CH




N25(5M)_CP-OFDM_16
QAM_Outer_Full_Mid_CH



N25(5M)_CP-OFDM_64
QAM_Outer_Full_Mid_CH




N25(5M)_CP-OFDM_256
QAM_Outer_Full_Mid_CH






N25(10M)_CP-
OFDM_QPSK_Outer_Full_Mid_CH




N25(10M)_CP-OFDM_16
QAM_Outer_Full_Mid_CH



N25(10M)_CP-OFDM_64
QAM_Outer_Full_Mid_CH




N25(10M)_CP-OFDM_256
QAM_Outer_Full_Mid_CH







N25(15M)_CP-
OFDM_QPSK_Outer_Full_Mid_CH




N25(15M)_CP-OFDM_16
QAM_Outer_Full_Mid_CH



N25(15M)_CP-OFDM_64
QAM_Outer_Full_Mid_CH




N25(15M)_CP-OFDM_256
QAM_Outer_Full_Mid_CH







N25(20M)_CP-
OFDM_QPSK_Outer_Full_Mid_CH




N25(20M)_CP-OFDM_16
QAM_Outer_Full_Mid_CH



N25(20M)_CP-OFDM_64
QAM_Outer_Full_Mid_CH




N25(20M)_CP-OFDM_256
QAM_Outer_Full_Mid_CH







N25(25M)_CP-
OFDM_QPSK_Outer_Full_Mid_CH




N25(25M)_CP-OFDM_16
QAM_Outer_Full_Mid_CH



N25(25M)_CP-OFDM_64
QAM_Outer_Full_Mid_CH



N25(25M)_CP-OFDM_256
QAM_Outer_Full_Mid_CH







N25(30M)_CP-
OFDM_QPSK_Outer_Full_Mid_CH




N25(30M)_CP-OFDM_16
QAM_Outer_Full_Mid_CH



N25(30M)_CP-OFDM_64
QAM_Outer_Full_Mid_CH




N25(30M)_CP-OFDM_256
QAM_Outer_Full_Mid_CH







N25(35M)_CP-
OFDM_QPSK_Outer_Full_Mid_CH




N25(35M)_CP-OFDM_16
QAM_Outer_Full_Mid_CH



N25(35M)_CP-OFDM_64
QAM_Outer_Full_Mid_CH




N25(35M)_CP-OFDM_256
QAM_Outer_Full_Mid_CH







N25(40M)_CP-
OFDM_QPSK_Outer_Full_Mid_CH




N25(40M)_CP-OFDM_16
QAM_Outer_Full_Mid_CH



N25(40M)_CP-OFDM_64
QAM_Outer_Full_Mid_CH



N25(40M)_CP-OFDM_256
QAM_Outer_Full_Mid_CH



**Conducted Spurious Emissions**

NR Band	SCS (kHz)	Bandwidth (MHz)	Arfcn	Freq (MHz)	Modulation	RB	Result	Verdict
25	15	5	370500	1852.5	DFT-s-OFDM BPSK	1@0	see graph	---
25	15	5	370500	1852.5	DFT-s-OFDM BPSK	1@0	see graph	PASS
25	15	5	370500	1852.5	DFT-s-OFDM QPSK	1@0	see graph	---
25	15	5	370500	1852.5	DFT-s-OFDM QPSK	1@0	see graph	PASS
25	15	5	376500	1882.5	DFT-s-OFDM BPSK	1@0	see graph	---
25	15	5	376500	1882.5	DFT-s-OFDM BPSK	1@0	see graph	PASS
25	15	5	376500	1882.5	DFT-s-OFDM QPSK	1@0	see graph	---
25	15	5	376500	1882.5	DFT-s-OFDM QPSK	1@0	see graph	PASS
25	15	5	382500	1912.5	DFT-s-OFDM BPSK	1@0	see graph	---
25	15	5	382500	1912.5	DFT-s-OFDM BPSK	1@0	see graph	PASS
25	15	5	382500	1912.5	DFT-s-OFDM QPSK	1@0	see graph	---
25	15	5	382500	1912.5	DFT-s-OFDM QPSK	1@0	see graph	PASS
25	15	20	372000	1860.0	DFT-s-OFDM BPSK	1@0	see graph	---
25	15	20	372000	1860.0	DFT-s-OFDM BPSK	1@0	see graph	PASS
25	15	20	372000	1860.0	DFT-s-OFDM QPSK	1@0	see graph	---
25	15	20	372000	1860.0	DFT-s-OFDM QPSK	1@0	see graph	PASS
25	15	20	376500	1882.5	DFT-s-OFDM BPSK	1@0	see graph	---
25	15	20	376500	1882.5	DFT-s-OFDM BPSK	1@0	see graph	PASS
25	15	20	376500	1882.5	DFT-s-OFDM QPSK	1@0	see graph	---
25	15	20	376500	1882.5	DFT-s-OFDM QPSK	1@0	see graph	PASS




25	15	20	381000	1905.0	DFT-s-OFDM BPSK	1@0	see graph	---
25	15	20	381000	1905.0	DFT-s-OFDM BPSK	1@0	see graph	PASS
25	15	20	381000	1905.0	DFT-s-OFDM QPSK	1@0	see graph	---
25	15	20	381000	1905.0	DFT-s-OFDM QPSK	1@0	see graph	PASS
25	15	40	374000	1870.0	DFT-s-OFDM BPSK	1@0	see graph	---
25	15	40	374000	1870.0	DFT-s-OFDM BPSK	1@0	see graph	PASS
25	15	40	374000	1870.0	DFT-s-OFDM QPSK	1@0	see graph	---
25	15	40	374000	1870.0	DFT-s-OFDM QPSK	1@0	see graph	PASS
25	15	40	376500	1882.5	DFT-s-OFDM BPSK	1@0	see graph	---
25	15	40	376500	1882.5	DFT-s-OFDM BPSK	1@0	see graph	PASS
25	15	40	376500	1882.5	DFT-s-OFDM QPSK	1@0	see graph	---
25	15	40	376500	1882.5	DFT-s-OFDM QPSK	1@0	see graph	PASS
25	15	40	379000	1895.0	DFT-s-OFDM BPSK	1@0	see graph	---
25	15	40	379000	1895.0	DFT-s-OFDM BPSK	1@0	see graph	PASS
25	15	40	379000	1895.0	DFT-s-OFDM QPSK	1@0	see graph	---
25	15	40	379000	1895.0	DFT-s-OFDM QPSK	1@0	see graph	PASS




N25(5M)_DFT-s-
OFDM_BPSK_Edge_1RB_Left_Low_CH




N25(5M)_DFT-s-
OFDM_QPSK_Edge_1RB_Left_Low_CH



N25(5M)_DFT-s-
OFDM_BPSK_Edge_1RB_Left_Mid_CH



N25(5M)_DFT-s-
OFDM_QPSK_Edge_1RB_Left_Mid_CH







N25(5M)_DFT-s-
OFDM_BPSK_Edge_1RB_Left_High_CH




N25(5M)_DFT-s-
OFDM_QPSK_Edge_1RB_Left_High_CH



N25(20M)_DFT-s-
OFDM_BPSK_Edge_1RB_Left_Low_CH




N25(20M)_DFT-s-
OFDM_QPSK_Edge_1RB_Left_Low_CH






N25(20M)_DFT-s-OFDM_BPSK_Edge_1RB_Left_Mid_CH




N25(20M)_DFT-s-OFDM_QPSK_Edge_1RB_Left_Mid_CH



N25(20M)_DFT-s-OFDM_BPSK_Edge_1RB_Left_High_CH




N25(20M)_DFT-s-OFDM_QPSK_Edge_1RB_Left_High_CH







N25(40M)_DFT-s-
OFDM_BPSK_Edge_1RB_Left_Low_CH




N25(40M)_DFT-s-
OFDM_QPSK_Edge_1RB_Left_Low_CH



N25(40M)_DFT-s-
OFDM_BPSK_Edge_1RB_Left_Mid_CH




N25(40M)_DFT-s-
OFDM_QPSK_Edge_1RB_Left_Mid_CH






N25(40M)_DFT-s-
OFDM_BPSK_Edge_1RB_Left_High_CH



N25(40M)_DFT-s-
OFDM_QPSK_Edge_1RB_Left_High_CH



**Conducted Band Edge**


NR Band	SCS (kHz)	Bandwidth (MHz)	Arfcn	Freq (MHz)	Modulation	RB	Result	Verdict
25	15	5	370500	1852.5	DFT-s-OFDM BPSK	1@0	see graph	PASS
25	15	5	370500	1852.5	DFT-s-OFDM QPSK	1@0	see graph	PASS
25	15	5	370500	1852.5	DFT-s-OFDM BPSK	25@0	see graph	PASS
25	15	5	370500	1852.5	DFT-s-OFDM QPSK	25@0	see graph	PASS
25	15	5	382500	1912.5	DFT-s-OFDM BPSK	1@24	see graph	PASS
25	15	5	382500	1912.5	DFT-s-OFDM QPSK	1@24	see graph	PASS
25	15	5	382500	1912.5	DFT-s-OFDM BPSK	25@0	see graph	PASS
25	15	5	382500	1912.5	DFT-s-OFDM QPSK	25@0	see graph	PASS
25	15	20	372000	1860.0	DFT-s-OFDM BPSK	1@0	see graph	PASS
25	15	20	372000	1860.0	DFT-s-OFDM QPSK	1@0	see graph	PASS
25	15	20	372000	1860.0	DFT-s-OFDM BPSK	100@0	see graph	PASS
25	15	20	372000	1860.0	DFT-s-OFDM QPSK	100@0	see graph	PASS
25	15	20	381000	1905.0	DFT-s-OFDM BPSK	1@105	see graph	PASS
25	15	20	381000	1905.0	DFT-s-OFDM QPSK	1@105	see graph	PASS
25	15	20	381000	1905.0	DFT-s-OFDM BPSK	100@0	see graph	PASS
25	15	20	381000	1905.0	DFT-s-OFDM QPSK	100@0	see graph	PASS
25	15	40	374000	1870.0	DFT-s-OFDM BPSK	1@0	see graph	PASS
25	15	40	374000	1870.0	DFT-s-OFDM QPSK	1@0	see graph	PASS
25	15	40	374000	1870.0	DFT-s-OFDM BPSK	216@0	see graph	PASS
25	15	40	374000	1870.0	DFT-s-OFDM QPSK	216@0	see graph	PASS




25	15	40	379000	1895.0	DFT-s-OFDM BPSK	1@215	see graph	PASS
25	15	40	379000	1895.0	DFT-s-OFDM QPSK	1@215	see graph	PASS
25	15	40	379000	1895.0	DFT-s-OFDM BPSK	216@0	see graph	PASS
25	15	40	379000	1895.0	DFT-s-OFDM QPSK	216@0	see graph	PASS




N25(5M)_DFT-s-
OFDM_BPSK_Edge_1RB_Left_Low_CH




N25(5M)_DFT-s-
OFDM_QPSK_Edge_1RB_Left_Low_CH



N25(5M)_DFT-s-
OFDM_BPSK_Outer_Full_Low_CH




N25(5M)_DFT-s-
OFDM_QPSK_Outer_Full_Low_CH







N25(5M)_DFT-s-
OFDM_BPSK_Edge_1RB_Right_High_CH




N25(5M)_DFT-s-
OFDM_QPSK_Edge_1RB_Right_High_CH



N25(5M)_DFT-s-
OFDM_BPSK_Outer_Full_High_CH




N25(5M)_DFT-s-
OFDM_QPSK_Outer_Full_High_CH







N25(20M)_DFT-s-
OFDM_BPSK_Edge_1RB_Left_Low_CH




N25(20M)_DFT-s-
OFDM_QPSK_Edge_1RB_Left_Low_CH



N25(20M)_DFT-s-
OFDM_BPSK_Outer_Full_Low_CH




N25(20M)_DFT-s-
OFDM_QPSK_Outer_Full_Low_CH







N25(20M)_DFT-s-
OFDM_BPSK_Edge_1RB_Right_High_CH




N25(20M)_DFT-s-
OFDM_QPSK_Edge_1RB_Right_High_CH



N25(20M)_DFT-s-
OFDM_BPSK_Outer_Full_High_CH




N25(20M)_DFT-s-
OFDM_QPSK_Outer_Full_High_CH







N25(40M)_DFT-s-
OFDM_BPSK_Edge_1RB_Left_Low_CH




N25(40M)_DFT-s-
OFDM_QPSK_Edge_1RB_Left_Low_CH



N25(40M)_DFT-s-
OFDM_BPSK_Outer_Full_Low_CH




N25(40M)_DFT-s-
OFDM_QPSK_Outer_Full_Low_CH







N25(40M)_DFT-s-
OFDM_BPSK_Edge_1RB_Right_High_CH




N25(40M)_DFT-s-
OFDM_QPSK_Edge_1RB_Right_High_CH



N25(40M)_DFT-s-
OFDM_BPSK_Outer_Full_High_CH



N25(40M)_DFT-s-
OFDM_QPSK_Outer_Full_High_CH





FR1 N26 ANT1

Transmitter Conducted Output Power And ERP, (G_T - L_C)=-3.8dB

NR Band	SCS	Band Width	Arfcn	Freq (MHz)	Modulation	RB	Conducted Power(dBm)	ERP(dBm)	ERP(W)
26	15	5	165300	826.5	DFT-s-OFDM QPSK	1@1	25.17	19.22	0.0836
26	15	5	165300	826.5	DFT-s-OFDM 16 QAM	1@1	24.39	18.44	0.0698
26	15	5	167300	836.5	DFT-s-OFDM QPSK	1@1	25.21	19.26	0.0843
26	15	5	167300	836.5	DFT-s-OFDM 16 QAM	1@1	24.47	18.52	0.0711
26	15	5	169300	846.5	DFT-s-OFDM QPSK	1@1	25.08	19.13	0.0818
26	15	5	169300	846.5	DFT-s-OFDM 16 QAM	1@1	24.25	18.3	0.0676
26	15	10	165800	829	DFT-s-OFDM QPSK	1@1	25.16	19.21	0.0834
26	15	10	165800	829	DFT-s-OFDM 16 QAM	1@1	24.33	18.38	0.0689
26	15	10	167300	836.5	DFT-s-OFDM QPSK	1@1	25.2	19.25	0.0841
26	15	10	167300	836.5	DFT-s-OFDM 16 QAM	1@1	24.31	18.36	0.0685
26	15	10	168800	844	DFT-s-OFDM QPSK	1@1	25.13	19.18	0.0828
26	15	10	168800	844	DFT-s-OFDM 16 QAM	1@1	24.37	18.42	0.0695
26	15	15	166300	831.5	DFT-s-OFDM QPSK	1@1	25.19	19.24	0.0839
26	15	15	166300	831.5	DFT-s-OFDM 16 QAM	1@1	24.38	18.43	0.0697
26	15	15	167300	836.5	DFT-s-OFDM QPSK	1@1	25.31	19.36	0.0863
26	15	15	167300	836.5	DFT-s-OFDM 16 QAM	1@1	24.51	18.56	0.0718
26	15	15	168300	841.5	DFT-s-OFDM QPSK	1@1	25.19	19.24	0.0839
26	15	15	168300	841.5	DFT-s-OFDM 16 QAM	1@1	24.42	18.47	0.0703
26	15	20	166800	834	DFT-s-OFDM PI/2 BPSK	50@25	25.27	19.32	0.0855
26	15	20	166800	834	DFT-s-OFDM PI/2 BPSK	1@1	25.2	19.25	0.0841
26	15	20	166800	834	DFT-s-OFDM PI/2 BPSK	1@104	25.19	19.24	0.0839
26	15	20	166800	834	DFT-s-OFDM QPSK	50@25	25.35	19.4	0.0871
26	15	20	166800	834	DFT-s-OFDM QPSK	1@1	25.22	19.27	0.0845
26	15	20	166800	834	DFT-s-OFDM QPSK	1@104	25.16	19.21	0.0834
26	15	20	166800	834	DFT-s-OFDM 16 QAM	50@25	24.26	18.31	0.0678
26	15	20	166800	834	DFT-s-OFDM 16 QAM	1@1	24.33	18.38	0.0689



26	15	20	166800	834	DFT-s-OFDM 16 QAM	1@104	24.2	18.25	0.0668
26	15	20	166800	834	DFT-s-OFDM 64 QAM	50@25	22.8	16.85	0.0484
26	15	20	166800	834	DFT-s-OFDM 64 QAM	1@1	22.94	16.99	0.0500
26	15	20	166800	834	DFT-s-OFDM 64 QAM	1@104	22.79	16.84	0.0483
26	15	20	166800	834	DFT-s-OFDM 256 QAM	50@25	20.81	14.86	0.0306
26	15	20	166800	834	DFT-s-OFDM 256 QAM	1@1	20.44	14.49	0.0281
26	15	20	166800	834	DFT-s-OFDM 256 QAM	1@104	20.34	14.39	0.0275
26	15	20	166800	834	CP-OFDM QPSK	53@26	23.98	18.03	0.0635
26	15	20	166800	834	CP-OFDM QPSK	1@1	24.19	18.24	0.0667
26	15	20	166800	834	CP-OFDM QPSK	1@104	24.08	18.13	0.0650
26	15	20	167300	836.5	DFT-s-OFDM PI/2 BPSK	50@25	25.22	19.27	0.0845
26	15	20	167300	836.5	DFT-s-OFDM PI/2 BPSK	1@1	25.28	19.33	0.0857
26	15	20	167300	836.5	DFT-s-OFDM PI/2 BPSK	1@104	25.08	19.13	0.0818
26	15	20	167300	836.5	DFT-s-OFDM QPSK	50@25	25.24	19.29	0.0849
26	15	20	167300	836.5	DFT-s-OFDM QPSK	1@1	25.3	19.35	0.0861
26	15	20	167300	836.5	DFT-s-OFDM QPSK	1@104	25.09	19.14	0.0820
26	15	20	167300	836.5	DFT-s-OFDM 16 QAM	50@25	24.31	18.36	0.0685
26	15	20	167300	836.5	DFT-s-OFDM 16 QAM	1@1	24.46	18.51	0.0710
26	15	20	167300	836.5	DFT-s-OFDM 16 QAM	1@104	24.27	18.32	0.0679
26	15	20	167300	836.5	DFT-s-OFDM 64 QAM	50@25	22.89	16.94	0.0494
26	15	20	167300	836.5	DFT-s-OFDM 64 QAM	1@1	22.97	17.02	0.0504
26	15	20	167300	836.5	DFT-s-OFDM 64 QAM	1@104	22.77	16.82	0.0481
26	15	20	167300	836.5	DFT-s-OFDM 256 QAM	50@25	20.78	14.83	0.0304
26	15	20	167300	836.5	DFT-s-OFDM 256 QAM	1@1	20.5	14.55	0.0285
26	15	20	167300	836.5	DFT-s-OFDM 256 QAM	1@104	20.3	14.35	0.0272
26	15	20	167300	836.5	CP-OFDM QPSK	53@26	23.95	18	0.0631
26	15	20	167300	836.5	CP-OFDM QPSK	1@1	24.16	18.21	0.0662
26	15	20	167300	836.5	CP-OFDM QPSK	1@104	23.96	18.01	0.0632
26	15	20	167800	839	DFT-s-OFDM PI/2 BPSK	50@25	25.14	19.19	0.0830
26	15	20	167800	839	DFT-s-OFDM PI/2 BPSK	1@1	25.22	19.27	0.0845
26	15	20	167800	839	DFT-s-OFDM PI/2 BPSK	1@104	25.14	19.19	0.0830
26	15	20	167800	839	DFT-s-OFDM QPSK	50@25	25.26	19.31	0.0853
26	15	20	167800	839	DFT-s-OFDM QPSK	1@1	25.33	19.38	0.0867



26	15	20	167800	839	DFT-s-OFDM QPSK	1@104	25.16	19.21	0.0834
26	15	20	167800	839	DFT-s-OFDM 16 QAM	50@25	24.27	18.32	0.0679
26	15	20	167800	839	DFT-s-OFDM 16 QAM	1@1	24.36	18.41	0.0693
26	15	20	167800	839	DFT-s-OFDM 16 QAM	1@104	24.34	18.39	0.0690
26	15	20	167800	839	DFT-s-OFDM 64 QAM	50@25	22.81	16.86	0.0485
26	15	20	167800	839	DFT-s-OFDM 64 QAM	1@1	22.92	16.97	0.0498
26	15	20	167800	839	DFT-s-OFDM 64 QAM	1@104	22.81	16.86	0.0485
26	15	20	167800	839	DFT-s-OFDM 256 QAM	50@25	20.69	14.74	0.0298
26	15	20	167800	839	DFT-s-OFDM 256 QAM	1@1	20.42	14.47	0.0280
26	15	20	167800	839	DFT-s-OFDM 256 QAM	1@104	20.4	14.45	0.0279
26	15	20	167800	839	CP-OFDM QPSK	53@26	23.86	17.91	0.0618
26	15	20	167800	839	CP-OFDM QPSK	1@1	24.14	18.19	0.0659
26	15	20	167800	839	CP-OFDM QPSK	1@104	24.03	18.08	0.0643




Frequency Stability

NR Band	SCS (kHz)	Bandwidth (MHz)	Arfcn	Freq (MHz)	Modulation	RB	Deviation (ppm)	Verdict	Environment
26	15	20	167300	836.5	DFT-s-OFDM QPSK	100@0	0.0066	PASS	NV
26	15	20	167300	836.5	DFT-s-OFDM QPSK	100@0	0.0067	PASS	LV
26	15	20	167300	836.5	DFT-s-OFDM QPSK	100@0	0.0043	PASS	HV
26	15	20	167300	836.5	DFT-s-OFDM QPSK	100@0	0.0063	PASS	-30°C
26	15	20	167300	836.5	DFT-s-OFDM QPSK	100@0	0.0054	PASS	-20°C
26	15	20	167300	836.5	DFT-s-OFDM QPSK	100@0	0.0047	PASS	-10°C
26	15	20	167300	836.5	DFT-s-OFDM QPSK	100@0	0.0023	PASS	0°C
26	15	20	167300	836.5	DFT-s-OFDM QPSK	100@0	0.0034	PASS	10°C
26	15	20	167300	836.5	DFT-s-OFDM QPSK	100@0	0.0066	PASS	20°C
26	15	20	167300	836.5	DFT-s-OFDM QPSK	100@0	0.0045	PASS	30°C
26	15	20	167300	836.5	DFT-s-OFDM QPSK	100@0	0.0063	PASS	40°C
26	15	20	167300	836.5	DFT-s-OFDM QPSK	100@0	0.0063	PASS	50°C

Peak to Average Ratio

NR Band	SCS (kHz)	Bandwidth (MHz)	Arfcn	Freq (MHz)	Modulation	RB	Result (dB)	Limit (dB)	Verdict
26	15	20	167300	836.5	DFT-s-OFDM PI/2 BPSK	100@0	3.92	13	PASS
26	15	20	167300	836.5	DFT-s-OFDM QPSK	100@0	5.23	13	PASS

N26(20M)_DFT-s-OFDM_PI_2-BPSK_Outer_Full_Mid_CH



N26(20M)_DFT-s-OFDM_QPSK_Outer_Full_Mid_CH



Occupied Bandwidth

NR Band	SCS (kHz)	Bandwidth (MHz)	Arfcn	Freq (MHz)	Modulation	RB	OBW (MHz)	26dB BW (MHz)
26	15	5	167300	836.5	CP-OFDM QPSK	25@0	4.4628	5.105
26	15	5	167300	836.5	CP-OFDM 16 QAM	25@0	4.4991	5.083
26	15	5	167300	836.5	CP-OFDM 64 QAM	25@0	4.457	5.036
26	15	5	167300	836.5	CP-OFDM 256 QAM	25@0	4.4746	5.04
26	15	10	167300	836.5	CP-OFDM QPSK	52@0	9.2702	9.982
26	15	10	167300	836.5	CP-OFDM 16 QAM	52@0	9.2927	10.02
26	15	10	167300	836.5	CP-OFDM 64 QAM	52@0	9.2736	9.933
26	15	10	167300	836.5	CP-OFDM 256 QAM	52@0	9.2645	9.973
26	15	15	167300	836.5	CP-OFDM QPSK	79@0	14.09	14.86
26	15	15	167300	836.5	CP-OFDM 16 QAM	79@0	14.09	14.97
26	15	15	167300	836.5	CP-OFDM 64 QAM	79@0	14.094	14.85
26	15	15	167300	836.5	CP-OFDM 256 QAM	79@0	14.076	15.04
26	15	20	167300	836.5	CP-OFDM QPSK	106@0	18.913	19.79
26	15	20	167300	836.5	CP-OFDM 16 QAM	106@0	18.917	19.8
26	15	20	167300	836.5	CP-OFDM 64 QAM	106@0	18.887	19.71
26	15	20	167300	836.5	CP-OFDM 256 QAM	106@0	18.954	19.6