



FCC RF Test Report

APPLICANT : Xiaomi Communications Co., Ltd.
EQUIPMENT : Mobile Phone
BRAND NAME : Xiaomi
MODEL NAME : 2405CPX3DG
FCC ID : 2AFZZPX3DG
STANDARD : 47 CFR Part 2, 22(H), 24(E), 27(L), 27(H)
CLASSIFICATION : PCS Licensed Transmitter Held to Ear (PCE)
TEST DATE(S) : Apr. 05, 2024 ~ May 30, 2024

We, Sporton International Inc. (Kunshan), would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.26-2015 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.

Jason Jia

Approved by: Jason Jia



Sporton International Inc. (Kunshan)

**No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300
People's Republic of China**



TABLE OF CONTENTS

REVISION HISTORY... 3
SUMMARY OF TEST RESULT ... 4
1 GENERAL DESCRIPTION ... 5
1.1 Applicant ... 5
1.2 Manufacturer ... 5
1.3 Product Feature of Equipment Under Test ... 5
1.4 Product Specification of Equipment Under Test ... 5
1.5 Modification of EUT ... 6
1.6 Maximum ERP/EIRP Power and Emission Designator ... 7
1.7 Testing Location ... 9
1.8 Test Software ... 9
1.9 Applicable Standards ... 9
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST ... 10
2.1 Test Mode ... 10
2.2 Connection Diagram of Test System ... 12
2.3 Support Unit used in test configuration and system ... 12
2.4 Measurement Results Explanation Example ... 12
2.5 Frequency List of Low/Middle/High Channels ... 13
3 CONDUCTED TEST ITEMS ... 16
3.1 Measuring Instruments ... 16
3.2 Test Setup ... 16
3.3 Test Result of Conducted Test ... 16
3.4 Conducted Output Power and ERP/EIRP ... 17
3.5 Peak-to-Average Ratio ... 18
3.6 Occupied Bandwidth ... 19
3.7 Conducted Band Edge ... 20
3.8 Conducted Spurious Emission ... 22
3.9 Frequency Stability ... 23
4 RADIATED TEST ITEMS ... 24
4.1 Measuring Instruments ... 24
4.2 Test Setup ... 24
4.3 Test Result of Radiated Test ... 25
4.4 Radiated Spurious Emission ... 26
5 LIST OF MEASURING EQUIPMENT ... 27
6 MEASUREMENT UNCERTAINTY ... 28
APPENDIX A. TEST RESULTS OF CONDUCTED TEST
APPENDIX B. TEST RESULTS OF RADIATED TEST
APPENDIX C. TEST SETUP PHOTOGRAPHS



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.4	§2.1046	Conducted Output Power	-	Report Only	-
	§22.913(a)(5)	Effective Radiated Power (Band 5) (Band 26)	ERP < 7 Watt	PASS	-
	§27.50(c)(10)	Effective Radiated Power (Band 12) (Band 17)	ERP < 3 Watt		-
	§24.232(c) §27.50(h)(2)	Equivalent Isotropic Radiated Power (Band 2)	EIRP < 2 Watt		-
	§27.50(d)(4)	Equivalent Isotropic Radiated Power (Band 4) (Band 66)	EIRP < 1 Watt		-
3.5	§24.232(d)	Peak-to-Average Ratio	<13 dB	PASS	-
3.6	§2.1049	Occupied Bandwidth	-	Report Only	-
3.7	§2.1051 §22.917(a) §24.238(a) §27.53(g) §27.53(h)	Conducted Band Edge Measurement (Band 2) (Band 4) (Band 5) (Band 12) (Band 17) (Band 26) (Band 66)	< 43+10log ₁₀ (P[Watts])	PASS	-
3.8	§2.1051 §22.917(a) §24.238(a) §27.53(g) §27.53(h)	Conducted Spurious Emission (Band 2) (Band 4) (Band 5) (Band 12) (Band 17) (Band 26) (Band 66)	< 43+10log ₁₀ (P[Watts])	PASS	-
3.9	§2.1055 §22.355	Frequency Stability Temperature & Voltage	< 2.5 ppm for Part 22	PASS	-
	§2.1055 §24.235 §27.54		Within Authorized Band		
4.4	§2.1053 §22.917(a) §24.238(a) §27.53(g) §27.53(h)	Radiated Spurious Emission (Band 2) (Band 4) (Band 5) (Band 12) (Band 17) (Band 26) (Band 66)	< 43+10log ₁₀ (P[Watts])	PASS	Under limit 34.14 dB at 3450.000 MHz

Conformity Assessment Condition:

- The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacturer who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
- The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty"

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.



1 General Description

1.1 Applicant

Xiaomi Communications Co., Ltd.

#019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085

1.2 Manufacturer

Xiaomi Communications Co., Ltd.

#019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Phone
Brand Name	Xiaomi
Model Name	2405CPX3DG
FCC ID	2AFZZPX3DG
IMEI Code	Conducted: 8665680700250507/8665680700250515 Radiation: 866568070019426/866568070019434
HW Version	135100N8
SW Version	Xiaomi HyperOS 1.0
EUT Stage	Identical Prototype

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx Frequency	LTE Band 2 : 1850 MHz ~ 1910 MHz LTE Band 4 : 1710 MHz ~ 1755 MHz LTE Band 5 : 824 MHz ~ 849 MHz LTE Band 12 : 699 MHz ~ 716 MHz LTE Band 17 : 704 MHz ~ 716 MHz LTE Band 26 : 824 MHz ~ 849 MHz LTE Band 66 : 1710 MHz ~ 1780 MHz
Rx Frequency	LTE Band 2 : 1930 MHz ~ 1990 MHz LTE Band 4 : 2110 MHz ~ 2155 MHz LTE Band 5 : 869 MHz ~ 894 MHz LTE Band 12 : 729 MHz ~ 746 MHz LTE Band 17 : 734 MHz ~ 746 MHz LTE Band 26 : 869 MHz ~ 894 MHz LTE Band 66 : 2110 MHz~ 2200 MHz
Bandwidth	LTE Band 2 : 1.4MHz / 3MHz / 5MHz / 10MHz / 15MHz / 20MHz LTE Band 4 : 1.4MHz / 3MHz / 5MHz / 10MHz / 15MHz / 20MHz LTE Band 5 : 1.4MHz / 3MHz / 5MHz / 10MHz LTE Band 12 : 1.4MHz / 3MHz / 5MHz / 10MHz LTE Band 17 : 5MHz / 10MHz LTE Band 26 : 1.4MHz / 3MHz / 5MHz / 10MHz / 15MHz LTE Band 66 : 1.4MHz / 3MHz / 5MHz / 10MHz / 15MHz / 20MHz



Maximum Output Power to Antenna	<Ant.0> LTE Band 4 : 25.12 dBm LTE Band 5 : 24.83 dBm LTE Band 12 : 24.83 dBm LTE Band 17 : 24.77 dBm LTE Band 26 : 24.84 dBm LTE Band 66 : 22.51 dBm <Ant.1> LTE Band 4 : 24.85 dBm LTE Band 5 : 24.57 dBm LTE Band 12 : 24.64 dBm LTE Band 17 : 24.57 dBm LTE Band 26 : 24.59 dBm LTE Band 66 : 22.07 dBm <Ant.5> LTE Band 2 : 23.99 dBm LTE Band 4 : 24.79 dBm LTE Band 66 : 24.84 dBm <Ant.6> LTE Band 2 : 23.36 dBm LTE Band 4 : 23.99 dBm LTE Band 66 : 23.99 dBm																																																																	
	<table border="1"> <thead> <tr> <th rowspan="2">Band</th> <th colspan="2">Ant.0</th> <th colspan="2">Ant.1</th> </tr> <tr> <th>Open(dBi)</th> <th>Close(dBi)</th> <th>Open(dBi)</th> <th>Close(dBi)</th> </tr> </thead> <tbody> <tr> <td>LTE Band 4</td> <td>-4.8</td> <td>-6.7</td> <td>-5.7</td> <td>-6.7</td> </tr> <tr> <td>LTE Band 5</td> <td>-9.7</td> <td>-11.3</td> <td>-5.1</td> <td>-8.5</td> </tr> <tr> <td>LTE Band 12</td> <td>-9.3</td> <td>-15</td> <td>-5.6</td> <td>-13.5</td> </tr> <tr> <td>LTE Band 17</td> <td>-9.4</td> <td>-15.2</td> <td>-5.6</td> <td>-13.5</td> </tr> <tr> <td>LTE Band 26</td> <td>-9.7</td> <td>-11.3</td> <td>-5.1</td> <td>-8.5</td> </tr> <tr> <td>LTE Band 66</td> <td>-4.8</td> <td>-6.1</td> <td>-5.7</td> <td>-6.7</td> </tr> </tbody> </table> <table border="1"> <thead> <tr> <th rowspan="2">Band</th> <th colspan="2">Ant.5</th> <th colspan="2">Ant.6</th> </tr> <tr> <th>Open(dBi)</th> <th>Close(dBi)</th> <th>Open(dBi)</th> <th>Close(dBi)</th> </tr> </thead> <tbody> <tr> <td>LTE Band 2</td> <td>-2.8</td> <td>-3.7</td> <td>-6.6</td> <td>-2.66</td> </tr> <tr> <td>LTE Band 4</td> <td>-2.1</td> <td>-2.9</td> <td>-3.6</td> <td>-6.02</td> </tr> <tr> <td>LTE Band 66</td> <td>-2.1</td> <td>-2.9</td> <td>-2.1</td> <td>-6.02</td> </tr> </tbody> </table>				Band	Ant.0		Ant.1		Open(dBi)	Close(dBi)	Open(dBi)	Close(dBi)	LTE Band 4	-4.8	-6.7	-5.7	-6.7	LTE Band 5	-9.7	-11.3	-5.1	-8.5	LTE Band 12	-9.3	-15	-5.6	-13.5	LTE Band 17	-9.4	-15.2	-5.6	-13.5	LTE Band 26	-9.7	-11.3	-5.1	-8.5	LTE Band 66	-4.8	-6.1	-5.7	-6.7	Band	Ant.5		Ant.6		Open(dBi)	Close(dBi)	Open(dBi)	Close(dBi)	LTE Band 2	-2.8	-3.7	-6.6	-2.66	LTE Band 4	-2.1	-2.9	-3.6	-6.02	LTE Band 66	-2.1	-2.9	-2.1
Band	Ant.0		Ant.1																																																															
	Open(dBi)	Close(dBi)	Open(dBi)	Close(dBi)																																																														
LTE Band 4	-4.8	-6.7	-5.7	-6.7																																																														
LTE Band 5	-9.7	-11.3	-5.1	-8.5																																																														
LTE Band 12	-9.3	-15	-5.6	-13.5																																																														
LTE Band 17	-9.4	-15.2	-5.6	-13.5																																																														
LTE Band 26	-9.7	-11.3	-5.1	-8.5																																																														
LTE Band 66	-4.8	-6.1	-5.7	-6.7																																																														
Band	Ant.5		Ant.6																																																															
	Open(dBi)	Close(dBi)	Open(dBi)	Close(dBi)																																																														
LTE Band 2	-2.8	-3.7	-6.6	-2.66																																																														
LTE Band 4	-2.1	-2.9	-3.6	-6.02																																																														
LTE Band 66	-2.1	-2.9	-2.1	-6.02																																																														
Antenna Gain																																																																		
Type of Modulation	QPSK / 16QAM / 64QAM / 256QAM																																																																	

Note:

1. The device is a folding phone, the maximum ERP/EIRP is calculated from max output power and antenna gain, only the maximum ERP/EIRP of Ant.5 for LTE Band 2/4/66, and Ant.1 for LTE Band 5/12/17/26 is shown in the report.
2. The device supports two PAs for LTE Band 4/66, the maximum power of Main PA is higher than the other PA, therefore, we chose higher power of main PA to calculate the EIRP and show in the report.

1.5 Modification of EUT

No modifications are made to the EUT during all test items.



1.6 Maximum ERP/EIRP Power and Emission Designator

LTE Band 2		QPSK		16QAM/64QAM/256QAM	
BW (MHz)	Frequency Range (MHz)	Maximum EIRP(W)	Emission Designator (99%OBW)	Maximum EIRP(W)	Emission Designator (99%OBW)
1.4	1850.7 ~ 1909.3	0.1294	1M10G7D	0.1038	1M10W7D
3	1851.5 ~ 1908.5	0.1285	2M72G7D	0.1030	2M73W7D
5	1852.5 ~ 1907.5	0.1306	4M51G7D	0.1030	4M54W7D
10	1855.0 ~ 1905.0	0.1294	9M05G7D	0.1016	9M11W7D
15	1857.5 ~ 1902.5	0.1297	13M5G7D	0.1019	13M5W7D
20	1860.0 ~ 1900.0	0.1315	17M9G7D	0.1042	17M9W7D
LTE Band 4		QPSK		16QAM/64QAM/256QAM	
BW (MHz)	Frequency Range (MHz)	Maximum EIRP(W)	Emission Designator (99%OBW)	Maximum EIRP(W)	Emission Designator (99%OBW)
1.4	1710.7 ~ 1754.3	0.1845	1M10G7D	0.1449	1M10W7D
3	1711.5 ~ 1753.5	0.1816	2M73G7D	0.1462	2M73W7D
5	1712.5 ~ 1752.5	0.1824	4M48G7D	0.1479	4M49W7D
10	1715.0 ~ 1750.0	0.1849	9M09G7D	0.1479	9M07W7D
15	1717.5 ~ 1747.5	0.1816	13M5G7D	0.1462	13M4W7D
20	1720.0 ~ 1745.0	0.1858	17M9G7D	0.1486	17M9W7D
LTE Band 5		QPSK		16QAM/64QAM/256QAM	
BW (MHz)	Frequency Range (MHz)	Maximum ERP(W)	Emission Designator (99%OBW)	Maximum ERP(W)	Emission Designator (99%OBW)
1.4	824.7 ~ 848.3	0.0531	1M09G7D	0.0412	1M10W7D
3	825.5 ~ 847.5	0.0530	2M73G7D	0.0414	2M72W7D
5	826.5 ~ 846.5	0.0535	4M49G7D	0.0414	4M52W7D
10	829.0 ~ 844.0	0.0540	9M07G7D	0.0423	9M07W7D
LTE Band 26		QPSK		16QAM/64QAM/256QAM	
BW (MHz)	Frequency Range (MHz)	Maximum ERP(W)	Emission Designator (99%OBW)	Maximum ERP(W)	Emission Designator (99%OBW)
1.4	824.7 ~ 848.3	0.0533	1M09G7D	0.0420	1M10W7D
3	825.5 ~ 847.5	0.0535	2M73G7D	0.0418	2M72W7D
5	826.5 ~ 846.5	0.0527	4M49G7D	0.0425	4M52W7D
10	829.0 ~ 844.0	0.0525	9M07G7D	0.0428	9M07W7D
15	831.5 ~ 841.5	0.0542	13M5G7D	0.0429	13M4W7D
CH26790	824.0	0.0533	13M5G7D	0.0405	13M4W7D



LTE Band 12		QPSK		16QAM/64QAM/256QAM	
BW (MHz)	Frequency Range (MHz)	Maximum ERP(W)	Emission Designator (99%OBW)	Maximum ERP(W)	Emission Designator (99%OBW)
1.4	699.7 ~ 715.3	0.0479	1M09G7D	0.0378	1M11W7D
3	700.5 ~ 714.5	0.0483	2M72G7D	0.0375	2M73W7D
5	701.5 ~ 713.5	0.0486	4M50G7D	0.0375	4M50W7D
10	704.0 ~ 711.0	0.0489	8M99G7D	0.0382	9M07W7D
LTE Band 17		QPSK		16QAM/64QAM/256QAM	
BW (MHz)	Frequency Range (MHz)	Maximum ERP(W)	Emission Designator (99%OBW)	Maximum ERP(W)	Emission Designator (99%OBW)
5	706.5 ~ 713.5	0.0473	4M50G7D	0.0389	4M50W7D
10	709.0 ~ 711.0	0.0481	8M99G7D	0.0398	9M07W7D
LTE Band 66		QPSK		16QAM/64QAM/256QAM	
BW (MHz)	Frequency Range (MHz)	Maximum EIRP(W)	Emission Designator (99%OBW)	Maximum EIRP(W)	Emission Designator (99%OBW)
1.4	1710.7 ~ 1779.3	0.1849	1M10G7D	0.1435	1M10W7D
3	1711.5 ~ 1778.5	0.1871	2M73G7D	0.1449	2M72W7D
5	1712.5 ~ 1777.5	0.1866	4M51G7D	0.1445	4M48W7D
10	1715.0 ~ 1775.0	0.1858	9M03G7D	0.1462	9M07W7D
15	1717.5 ~ 1772.5	0.1466	13M5G7D	0.1178	13M5W7D
20	1720.0 ~ 1770.0	0.1879	17M9G7D	0.1466	17M9W7D

Note:

1. LTE Band 26 overlaps the entire frequency range of LTE Band 5. Therefore, the test results provided in this report covers Band 5 and the portion of Band 26 subject to Part 22.
2. LTE Band 66 overlaps the entire frequency range of LTE Band 4. Therefore, the test results provided in this report covers Band 66 as well as Band 4 for main PA.
3. LTE Band 12 overlaps the entire frequency range of LTE Band 17. Therefore, the test results provided in this report covers Band 12 as well as Band 17.



1.7 Testing Location

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International Inc. (Kunshan)		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	03CH04-KS TH01-KS	CN1257	314309

1.8 Test Software

Item	Site	Manufacture	Name	Version
1.	TH01-KS	SPORTON	FCC LTE_Ver2.0 Auto_china_210503	2.0
2.	03CH04-KS	AUDIX	E3	210616

1.9 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 2, 22(H), 24(E), 27(L)
- ♦ ANSI C63.26-2015
- ♦ FCC KDB 971168 D01 Power Meas License Digital Systems v03r01
- ♦ FCC KDB 412172 D01 Determining ERP and EIRP v01r01

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

2.1 Test Mode

Antenna port conducted and radiated test items listed below are performed according to KDB 971168 D01 Power Meas License Digital Systems v03r01 with maximum output power.


Radiated measurements are performed by rotating the EUT in three different orthogonal test planes to find the maximum emission.

Test Items	Band	Bandwidth (MHz)						Modulation				RB #			Test Channel			
		1.4	3	5	10	15	20	QPSK	16 QAM	64 QAM	256 QAM	1	Half	Full	L	M	H	
Max. Output Power	2	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v
	4	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v
	5	v	v	v	v	-	-	v	v	v	v	v	v	v	v	v	v	v
	12	v	v	v	v	-	-	v	v	v	v	v	v	v	v	v	v	v
	17	-	-	v	v	-	-	v	v	v	v	v	v	v	v	v	v	v
	26	v	v	v	v	v	-	v	v	v	v	v	v	v	v	v	v	v
66	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v	
Peak-to-Average Ratio	2						v	v	v	v	v			v		v		
	4						v	v	v	v	v			v		v		
	12				v	-	-	v	v	v	v			v		v		
	26				v		-	v	v	v	v			v		v		
	66						v	v	v	v	v			v		v		
26dB and 99% Bandwidth	2	v	v	v	v	v	v	v	v					v		v		
	4	v	v	v	v	v	v	v	v					v		v		
	12	v	v	v	v	-	-	v	v					v		v		
	26	v	v	v	v	v	-	v	v					v		v		
	66	v	v	v	v	v	v	v	v					v		v		
Conducted Band Edge	2	v	v	v	v	v	v	v				v			v	v	v	
	4	v	v	v	v	v	v	v				v			v	v	v	
	12	v	v	v	v	-	-	v				v			v	v	v	
	26	v	v	v	v	v	-	v				v			v	v	v	
	66	v	v	v	v	v	v	v				v			v	v	v	
Conducted Spurious Emission	2	v	v	v	v	v	v	v				v			v	v	v	
	4	v	v	v	v	v	v	v				v			v	v	v	
	12	v	v	v	v	-	-	v				v			v	v	v	
	26	v	v	v	v	v	-	v				v			v	v	v	



	66	v	v	v	v	v	v	v	v				v			v	v	v
Frequency Stability	2				v			v							v		v	
	4				v			v							v		v	
	12				v	-	-	v							v		v	
	26				v		-	v							v		v	
	66				v			v							v		v	
E.R.P / E.I.R.P	2	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v
	4	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v
	5	v	v	v	v	-	-	v	v	v	v	v	v	v	v	v	v	v
	12	v	v	v	v	-	-	v	v	v	v	v	v	v	v	v	v	v
	17	-	-	v	v	-	-	v	v	v	v	v	v	v	v	v	v	v
	26	v	v	v	v	v	-	v	v	v	v	v	v	v	v	v	v	v
	66	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v
Radiated Spurious Emission	2	Worst Case															v	
	4	Worst Case															v	
	12	Worst Case															v	
	26	Worst Case															v	
	66	Worst Case															v	
Note	<ol style="list-style-type: none"> The mark "v " means that this configuration is chosen for testing The mark "- " means that this bandwidth is not supported. The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst case emissions are reported. LTE Band 26 overlaps the entire frequency range of LTE Band 5. Therefore, the test results provided in this report covers Band 5 and the portion of Band 26 subject to Part 22. LTE Band 12 overlaps the entire frequency range of LTE Band 17. Therefore, the test results provided in this report covers Band 12 as well as Band 17. 																	

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	Power Supply	GWINSTEK	PSS-2002	N/A	N/A	Unshielded, 1.8 m
2.	LTE Base Station	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.6 dB and 10dB attenuator.

Example :

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\ &= 4.6 + 10 = 14.6 \text{ (dB)} \end{aligned}$$



2.5 Frequency List of Low/Middle/High Channels

LTE Band 2 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	18700	18900	19100
	Frequency	1860	1880	1900
15	Channel	18675	18900	19125
	Frequency	1857.5	1880	1902.5
10	Channel	18650	18900	19150
	Frequency	1855	1880	1905
5	Channel	18625	18900	19175
	Frequency	1852.5	1880	1907.5
3	Channel	18615	18900	19185
	Frequency	1851.5	1880	1908.5
1.4	Channel	18607	18900	19193
	Frequency	1850.7	1880	1909.3

LTE Band 4 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	20050	20175	20300
	Frequency	1720	1732.5	1745
15	Channel	20025	20175	20325
	Frequency	1717.5	1732.5	1747.5
10	Channel	20000	20175	20350
	Frequency	1715	1732.5	1750
5	Channel	19975	20175	20375
	Frequency	1712.5	1732.5	1752.5
3	Channel	19965	20175	20385
	Frequency	1711.5	1732.5	1753.5
1.4	Channel	19957	20175	20393
	Frequency	1710.7	1732.5	1754.3



LTE Band 5 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
10	Channel	20450	20525	20600
	Frequency	829	836.5	844
5	Channel	20425	20525	20625
	Frequency	826.5	836.5	846.5
3	Channel	20415	20525	20635
	Frequency	825.5	836.5	847.5
1.4	Channel	20407	20525	20643
	Frequency	824.7	836.5	848.3

LTE Band 12 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
10	Channel	23060	23095	23130
	Frequency	704	707.5	711
5	Channel	23035	23095	23155
	Frequency	701.5	707.5	713.5
3	Channel	23025	23095	23165
	Frequency	700.5	707.5	714.5
1.4	Channel	23017	23095	23173
	Frequency	699.7	707.5	715.3

LTE Band 17 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
10	Channel	23780	23790	23800
	Frequency	709	710	711
5	Channel	23755	23790	23825
	Frequency	706.5	710	713.5



LTE Band 26 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
15	Channel	26865	26915	26965
	Frequency	831.5	836.5	841.5
10	Channel	26840	26915	26990
	Frequency	829	836.5	844
5	Channel	26815	26915	27015
	Frequency	826.5	836.5	846.5
3	Channel	26805	26915	27025
	Frequency	825.5	836.5	847.5
1.4	Channel	26797	26915	27033
	Frequency	824.7	836.5	848.3

LTE Band 66 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	132072	132322	132572
	Frequency	1720	1745	1770
15	Channel	132047	132322	132597
	Frequency	1717.5	1745	1772.5
10	Channel	132022	132322	132622
	Frequency	1715	1745	1775
5	Channel	131997	132322	132647
	Frequency	1712.5	1745	1777.5
3	Channel	131987	132322	132657
	Frequency	1711.5	1745	1778.5
1.4	Channel	131979	132322	132665
	Frequency	1710.7	1745	1779.3


3 Conducted Test Items

3.1 Measuring Instruments


See list of measuring instruments of this test report.

3.2 Test Setup


3.2.1 Conducted Output Power



3.2.2 Peak-to-Average Ratio, Occupied Bandwidth ,Conducted Band-Edge and Conducted Spurious Emission



3.2.3 Frequency Stability



3.3 Test Result of Conducted Test

Please refer to Appendix A.



3.4 Conducted Output Power and ERP/EIRP

3.4.1 Description of the Conducted Output Power Measurement and ERP/EIRP Measurement

A system simulator was used to establish communication with the EUT. Its parameters were set to force the EUT transmitting at maximum output power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

The ERP of mobile transmitters must not exceed 7 Watts for LTE Band 5 and Band 26.

The ERP of mobile transmitters must not exceed 3 Watts for LTE Band 12 and Band 17.

The EIRP of mobile transmitters must not exceed 2 Watts for LTE Band 2.

The EIRP of mobile transmitters must not exceed 1 Watts for LTE Band 4 and Band 66.

According to KDB 412172 D01 Power Approach,

$EIRP = P_T + G_T - L_C$, $ERP = EIRP - 2.15$, where

P_T = transmitter output power in dBm

G_T = gain of the transmitting antenna in dBi

L_C = signal attenuation in the connecting cable between the transmitter and antenna in dB

3.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2
2. The transmitter output port was connected to the system simulator.
3. Set EUT at maximum power through the system simulator.
4. Select lowest, middle, and highest channels for each band and different modulation.
5. Measure and record the power level from the system simulator.



3.5 Peak-to-Average Ratio

3.5.1 Description of the PAR Measurement

Power Complementary Cumulative Distribution Function (CCDF) curves provide a means for characterizing the power peaks of a digitally modulated signal on a statistical basis. A CCDF curve depicts the probability of the peak signal amplitude exceeding the average power level. Most contemporary measurement instrumentation include the capability to produce CCDF curves for an input signal provided that the instrument's resolution bandwidth can be set wide enough to accommodate the entire input signal bandwidth. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.5.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2.3.4 (CCDF).
2. The EUT was connected to spectrum and system simulator via a power divider.
3. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
4. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
5. Record the deviation as Peak to Average Ratio.



3.6 Occupied Bandwidth

3.6.1 Description of Occupied Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

3.6.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.4
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
5. Set the detection mode to peak, and the trace mode to max hold.
6. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace.
(this is the reference value)
7. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
8. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “-X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
9. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.



3.7 Conducted Band Edge

3.7.1 Description of Conducted Band Edge Measurement

22.917(a)

For operations in the 824 – 849 MHz band, the FCC limit is $43 + 10\log_{10}(P[\text{Watts}])$ dB below the transmitter power $P(\text{Watts})$ in a 100kHz bandwidth. However, in the 1MHz bands immediately outside and adjacent to the licensee's frequency block, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

24.238 (a)

For operations in the 1850-1910 and 1930-1990 MHz band, the FCC limit is $43 + 10\log_{10}(P[\text{Watts}])$ dB below the transmitter power $P(\text{Watts})$ in a 1MHz bandwidth. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

27.53 (g)

For operations in the 600MHz band and 698 -746 MHz band, the FCC limit is $43 + 10\log_{10}(P[\text{Watts}])$ dB below the transmitter power $P(\text{Watts})$ in a 100 kHz bandwidth. However, in the 100 kilohertz bands immediately outside and adjacent to a licensee's frequency block, a resolution bandwidth of at least 30 kHz may be employed.

27.53 (h)

For operations in the 1710 – 1755 MHz band, the FCC limit is $43 + 10\log_{10}(P[\text{Watts}])$ dB below the transmitter power $P(\text{Watts})$ in a 1 MHz bandwidth. However, in the 1MHz bands immediately outside and adjacent to the licensee's frequency block, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.



3.7.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
2. The band edges of low and high channels for the highest RF powers were measured.
3. Set RBW \geq 1% EBW in the 1MHz band immediately outside and adjacent to the band edge.
4. Beyond the 1 MHz band from the band edge, RBW=1MHz was used or a narrower RBW was used and the measured power was integrated over the full required measurement bandwidth of 1 MHz.
5. Set spectrum analyzer with RMS detector.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
7. Checked that all the results comply with the emission limit line.

Example:

The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)

$$= P(W) - [43 + 10\log(P)] \text{ (dB)}$$

$$= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)} = -13\text{dBm}.$$

8. When using the integration method, the starting frequency of the integration shall be centered at one-half of the RBW away from the band edge.



3.8 Conducted Spurious Emission

3.8.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.

3.8.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz.
7. Set spectrum analyzer with RMS detector.
8. Taking the record of maximum spurious emission.
9. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
10. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
= P(W)- [43 + 10log(P)] (dB)
= [30 + 10log(P)] (dBm) - [43 + 10log(P)] (dB)
= -13dBm.



3.9 Frequency Stability

3.9.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.

3.9.2 Test Procedures for Temperature Variation

1. The testing follows ANSI C63.26 section 5.6.4
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C step up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.9.3 Test Procedures for Voltage Variation

1. The testing follows ANSI C63.26 section 5.6.5
2. The EUT was placed in a temperature chamber at $20\pm 5^{\circ}\text{C}$ and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value for other than hand carried battery equipment.
4. For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.
5. The variation in frequency was measured for the worst case.


4 Radiated Test Items

4.1 Measuring Instruments


See list of measuring instruments of this test report.

4.2 Test Setup


4.2.1 For radiated test below 30MHz



4.2.2 For radiated test from 30MHz to 1GHz



4.2.3 For radiated test above 1GHz



4.3 Test Result of Radiated Test

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

Please refer to Appendix B.



4.4 Radiated Spurious Emission

4.4.1 Description of Radiated Spurious Emission

The radiated spurious emission was measured by substitution method according to ANSI C63.26. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

4.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.5
2. The EUT was placed on a turntable with 0.8 meter height for frequency below 1GHz and 1.5 meter height for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the receiving antenna mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between 1m to 4m to search the maximum spurious emission for both horizontal and vertical polarizations.
6. During the measurement, the system simulator parameters were set to force the EUT transmitting at maximum output power.
7. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
8. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
9. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
10. $EIRP \text{ (dBm)} = S.G. \text{ Power} - Tx \text{ Cable Loss} + Tx \text{ Antenna Gain}$
11. $ERP \text{ (dBm)} = EIRP - 2.15$
12. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
= $P(W) - [43 + 10\log(P)]$ (dB)
= $[30 + 10\log(P)]$ (dBm) - $[43 + 10\log(P)]$ (dB)
= -13dBm.



5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EXA Spectrum Analyzer	Keysight	N9010B	MY57471079	10Hz-44G,MAX 30dB	Oct. 10, 2023	Apr. 14, 2024~ May 28, 2024	Oct. 09, 2024	Radiation (03CH04-KS)
Loop Antenna	R&S	HFH2-Z2E	101125	9kHz~30MHz	Sep. 11 2023	Apr. 14, 2024~ May 28, 2024	Sep. 10, 2024	Radiation (03CH04-KS)
Bilog Antenna	TeseQ	CBL6111D	59913	30MHz-1GHz	Aug. 19, 2023	Apr. 14, 2024~ May 28, 2024	Aug. 18, 2024	Radiation (03CH04-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00251694	1GHz~18GHz	Jul. 12, 2023	Apr. 14, 2024~ May 28, 2024	Jul. 11, 2024	Radiation (03CH04-KS)
SHF-EHF Horn	Com-power	AH-840	101070	18GHz~40GHz	Jan. 05, 2024	Apr. 14, 2024~ May 28, 2024	Jan. 04, 2025	Radiation (03CH04-KS)
Amplifier	SONOMA	310N	380827	9KHz-1GHz	Jul. 06, 2023	Apr. 14, 2024~ May 28, 2024	Jul. 05, 2024	Radiation (03CH04-KS)
Amplifier	MITEQ	EM18G40G GA	060728	18~40GHz	Jan. 05, 2024	Apr. 14, 2024~ May 28, 2024	Jan. 04, 2025	Radiation (03CH04-KS)
high gain Amplifier	EM	EM01G18G A	060840	1Ghz-18Ghz	Oct. 10, 2023	Apr. 14, 2024~ May 28, 2024	Oct. 09, 2024	Radiation (03CH04-KS)
Amplifier	Agilent	8449B	3008A02370	1Ghz-18Ghz	Oct. 10, 2023	Apr. 14, 2024~ May 28, 2024	Oct. 09, 2024	Radiation (03CH04-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Apr. 14, 2024~ May 28, 2024	NCR	Radiation (03CH04-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Apr. 14, 2024~ May 28, 2024	NCR	Radiation (03CH04-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Apr. 14, 2024~ May 28, 2024	NCR	Radiation (03CH04-KS)
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Oct. 11, 2023	Apr. 05, 2024~ May 30, 2024	Oct. 10, 2024	Conducted (TH01-KS)
Power divider	STI	STI08-0055	-	0.5~40GHz	/	Apr. 05, 2024~ May 30, 2024	/	Conducted (TH01-KS)
Temperature & humidity chamber	Hongzhan	LP-150U	H2014011440	-40~+150°C 20%~95%RH	Jul. 06, 2023	Apr. 05, 2024~ May 30, 2024	Jul. 05, 2024	Conducted (TH01-KS)

NCR: No Calibration Required



6 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.26-2015. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Measurement

Test Item	Uncertainty
Conducted Spurious Emission & Bandedge	±2.26 dB
Occupied Channel Bandwidth	±0.1%
Conducted Power	±0.46 dB
Peak to Average Ratio	±0.46 dB
Frequency Stability	±0.4 Hz

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.82dB
---	--------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.56dB
---	--------

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.54dB
---	--------

----- THE END -----



Appendix A. Test Results of Conducted Test

Test Engineer :	Simle Wang	Temperature :	22~23°C
		Relative Humidity :	40~42%

Conducted Output Power(Average power) and ERP/EIRP

LTE Band 2_Ant.5

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	EIRP(W) < 2W Test Results: Pass		
Channel				18700	18900	19100			
Frequency (MHz)				1860	1880	1900	L	M	H
20	QPSK	1	0	23.85	23.99	23.90	0.1274	0.1315	0.1288
20	QPSK	1	99	23.85	23.89	23.82	0.1274	0.1285	0.1265
20	QPSK	100	0	22.95	22.96	22.90	0.1035	0.1038	0.1023
20	16QAM	1	0	22.91	22.98	22.92	0.1026	0.1042	0.1028
20	64QAM	1	0	21.78	21.86	21.78	0.0791	0.0805	0.0791
20	256QAM	1	0	19.09	19.15	19.13	0.0426	0.0432	0.0430
Channel				18675	18900	19125	EIRP(W)		
Frequency (MHz)				1857.5	1880	1902.5	L	M	H
15	QPSK	1	0	23.79	23.93	23.87	0.1256	0.1297	0.1279
15	16QAM	1	0	22.86	22.88	22.85	0.1014	0.1019	0.1012
Channel				18650	18900	19150	EIRP(W)		
Frequency (MHz)				1855	1880	1905	L	M	H
10	QPSK	1	0	23.75	23.92	23.84	0.1245	0.1294	0.1271
10	16QAM	1	0	22.83	22.87	22.84	0.1007	0.1016	0.1009
Channel				18625	18900	19175	EIRP(W)		
Frequency (MHz)				1852.5	1880	1907.5	L	M	H
5	QPSK	1	0	23.76	23.96	23.82	0.1247	0.1306	0.1265
5	16QAM	1	0	22.86	22.93	22.84	0.1014	0.1030	0.1009
Channel				18615	18900	19185	EIRP(W)		
Frequency (MHz)				1851.5	1880	1908.5	L	M	H
3	QPSK	1	0	23.77	23.89	23.86	0.1250	0.1285	0.1276
3	16QAM	1	0	22.84	22.93	22.88	0.1009	0.1030	0.1019
Channel				18607	18900	19193	EIRP(W)		
Frequency (MHz)				1850.7	1880	1909.3	L	M	H
1.4	QPSK	1	0	23.82	23.92	23.86	0.1265	0.1294	0.1276
1.4	16QAM	1	0	22.83	22.96	22.83	0.1007	0.1038	0.1007



LTE Band 4_Ant.5

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	EIRP(W) < 1W Test Results: Pass		
Channel				20050	20175	20300			
Frequency (MHz)				1720	1732.5	1745	L	M	H
20	QPSK	1	0	24.66	24.79	24.74	0.1803	0.1858	0.1837
20	QPSK	1	99	24.67	24.70	24.61	0.1807	0.1820	0.1782
20	QPSK	100	0	23.66	23.69	23.63	0.1432	0.1442	0.1422
20	16QAM	1	0	23.72	23.82	23.71	0.1452	0.1486	0.1449
20	64QAM	1	0	23.26	23.30	23.25	0.1306	0.1318	0.1303
20	256QAM	1	0	19.54	19.65	19.56	0.0555	0.0569	0.0557
Channel				20025	20175	20325	EIRP(W)		
Frequency (MHz)				1717.5	1732.5	1747.5	L	M	H
15	QPSK	1	0	24.57	24.69	24.65	0.1766	0.1816	0.1799
15	16QAM	1	0	23.66	23.75	23.62	0.1432	0.1462	0.1419
Channel				20000	20175	20350	EIRP(W)		
Frequency (MHz)				1715	1732.5	1750	L	M	H
10	QPSK	1	0	24.60	24.77	24.70	0.1778	0.1849	0.1820
10	16QAM	1	0	23.68	23.80	23.63	0.1439	0.1479	0.1422
Channel				19975	20175	20375	EIRP(W)		
Frequency (MHz)				1712.5	1732.5	1752.5	L	M	H
5	QPSK	1	0	24.65	24.71	24.66	0.1799	0.1824	0.1803
5	16QAM	1	0	23.64	23.80	23.69	0.1426	0.1479	0.1442
Channel				19965	20175	20385	EIRP(W)		
Frequency (MHz)				1711.5	1732.5	1753.5	L	M	H
3	QPSK	1	0	24.61	24.69	24.68	0.1782	0.1816	0.1811
3	16QAM	1	0	23.66	23.75	23.68	0.1432	0.1462	0.1439
Channel				19950	20175	20393	EIRP(W)		
Frequency (MHz)				1710	1732.5	1754.3	L	M	H
1.4	QPSK	1	0	24.63	24.76	24.67	0.1791	0.1845	0.1807
1.4	16QAM	1	0	23.66	23.71	23.69	0.1432	0.1449	0.1442



LTE Band 66_Ant.5

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	EIRP(W) < 1W Test Results: Pass		
Channel				132072	132322	132572			
Frequency (MHz)				1720	1745	1770	L	M	H
20	QPSK	1	0	24.74	24.84	24.76	0.1837	0.1879	0.1845
20	QPSK	1	99	24.74	24.82	24.80	0.1837	0.1871	0.1862
20	QPSK	100	0	23.50	23.59	23.49	0.1380	0.1409	0.1377
20	16QAM	1	0	23.70	23.76	23.72	0.1445	0.1466	0.1452
20	64QAM	1	0	22.78	22.81	22.80	0.1169	0.1178	0.1175
20	256QAM	1	0	19.58	19.66	19.60	0.0560	0.0570	0.0562
Channel				132047	132322	132597	EIRP(W)		
Frequency (MHz)				1717.5	1745	1772.5	L	M	H
15	QPSK	1	0	23.70	23.76	23.72	0.1445	0.1466	0.1452
15	16QAM	1	0	22.78	22.81	22.80	0.1169	0.1178	0.1175
Channel				19.58	19.66	19.6	EIRP(W)		
Frequency (MHz)				1715	1745	1775	L	M	H
10	QPSK	1	0	24.66	24.79	24.65	0.1803	0.1858	0.1799
10	16QAM	1	0	23.64	23.75	23.62	0.1426	0.1462	0.1419
Channel				131997	132322	132647	EIRP(W)		
Frequency (MHz)				1712.5	1745	1777.5	L	M	H
5	QPSK	1	0	24.64	24.81	24.71	0.1795	0.1866	0.1824
5	16QAM	1	0	23.65	23.70	23.66	0.1429	0.1445	0.1432
Channel				131987	132322	132657	EIRP(W)		
Frequency (MHz)				1711.5	1745	1778.5	L	M	H
3	QPSK	1	0	24.69	24.82	24.69	0.1816	0.1871	0.1816
3	16QAM	1	0	23.67	23.71	23.66	0.1435	0.1449	0.1432
Channel				131979	132322	132665	EIRP(W)		
Frequency (MHz)				1710.7	1745	1779.3	L	M	H
1.4	QPSK	1	0	24.66	24.77	24.72	0.1803	0.1849	0.1828
1.4	16QAM	1	0	23.60	23.67	23.66	0.1413	0.1435	0.1432



LTE Band 5_Ant.1

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	ERP(W) < 7W Test Results: Pass		
Channel				20450	20525	20600			
Frequency (MHz)				829	836.5	844	L	M	H
10	QPSK	1	0	24.47	24.57	24.52	0.0527	0.0540	0.0533
10	QPSK	1	49	24.44	24.48	24.41	0.0524	0.0528	0.0520
10	QPSK	50	0	23.48	23.50	23.48	0.0420	0.0422	0.0420
10	16QAM	1	0	23.46	23.51	23.43	0.0418	0.0423	0.0415
10	64QAM	1	0	22.50	22.51	22.47	0.0335	0.0336	0.0333
10	256QAM	1	0	19.62	19.67	19.63	0.0173	0.0175	0.0173
Channel				20425	20525	20625	ERP(W)		
Frequency (MHz)				826.5	836.5	846.5	L	M	H
5	QPSK	1	0	24.45	24.53	24.43	0.0525	0.0535	0.0522
5	16QAM	1	0	23.41	23.40	23.42	0.0413	0.0412	0.0414
Channel				20415	20525	20635	ERP(W)		
Frequency (MHz)				825.5	836.5	847.5	L	M	H
3	QPSK	1	0	24.38	24.48	24.49	0.0516	0.0528	0.0530
3	16QAM	1	0	23.42	23.41	23.42	0.0414	0.0413	0.0414
Channel				20407	20525	20643	ERP(W)		
Frequency (MHz)				824.7	836.5	848.3	L	M	H
1.4	QPSK	1	0	24.37	24.50	24.42	0.0515	0.0531	0.0521
1.4	16QAM	1	0	23.40	23.40	23.34	0.0412	0.0412	0.0406



LTE Band 26_Ant.1

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	ERP(W) < 7W Test Results: Pass			
Channel				26790	26865	26915	26965				
Frequency (MHz)				824	831.5	836.5	841.5	Straddle Ch	L	M	H
15	QPSK	1	0	24.52	24.49	24.59	24.45	0.0533	0.0530	0.0542	0.0525
15	QPSK	1	74	24.33	24.44	24.50	24.47	0.0511	0.0524	0.0531	0.0527
15	QPSK	75	0	23.25	23.55	23.57	23.52	0.0398	0.0427	0.0429	0.0424
15	16QAM	1	0	23.32	23.46	23.57	23.56	0.0405	0.0418	0.0429	0.0428
15	64QAM	1	0	22.35	22.51	22.57	22.52	0.0324	0.0336	0.0340	0.0337
15	256QAM	1	0	19.26	19.45	19.51	19.45	0.0159	0.0166	0.0168	0.0166
Channel				26790	26840	26915	26990	ERP(W)			
Frequency (MHz)				824	829	836.5	844	Straddle Ch	L	M	H
10	QPSK	1	0	24.33	24.45	24.45	24.44	0.0511	0.0525	0.0525	0.0524
10	16QAM	1	0	23.23	23.45	23.56	23.48	0.0396	0.0417	0.0428	0.0420
Channel				26790	26815	26915	27015	ERP(W)			
Frequency (MHz)				824	826.5	836.5	846.5	Straddle Ch	L	M	H
5	QPSK	1	0	24.32	24.47	24.45	24.41	0.0509	0.0527	0.0525	0.0520
5	16QAM	1	0	23.59	23.41	23.52	23.53	0.0431	0.0413	0.0424	0.0425
Channel				26790	26815	26915	27025	ERP(W)			
Frequency (MHz)				824	825.5	836.5	847.5	Straddle Ch	L	M	H
3	QPSK	1	0	24.26	24.40	24.53	24.36	0.0502	0.0519	0.0535	0.0514
3	16QAM	1	0	23.14	23.43	23.46	23.46	0.0388	0.0415	0.0418	0.0418
Channel				26790	26797	26915	27033	ERP(W)			
Frequency (MHz)				824	824.7	836.5	848.3	Straddle Ch	L	M	H
1.4	QPSK	1	0	24.29	24.38	24.52	24.35	0.0506	0.0516	0.0533	0.0513
1.4	16QAM	1	0	23.40	23.42	23.48	23.48	0.0412	0.0414	0.0420	0.0420



LTE Band 12_Ant.1

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	ERP(W) < 3W Test Results: Pass		
Channel				23060	23095	23130			
Frequency (MHz)				704	707.5	711	L	M	H
10	QPSK	1	0	24.51	24.64	24.53	0.0474	0.0489	0.0476
10	QPSK	1	49	24.54	24.60	24.58	0.0478	0.0484	0.0482
10	QPSK	50	0	23.51	23.54	23.43	0.0377	0.0379	0.0370
10	16QAM	1	0	23.52	23.57	23.49	0.0378	0.0382	0.0375
10	64QAM	1	0	22.47	22.57	22.56	0.0296	0.0303	0.0303
10	256QAM	1	0	19.53	19.57	19.52	0.0151	0.0152	0.0150
Channel				23035	23095	23155	ERP(W)		
Frequency (MHz)				701.5	707.5	713.5	L	M	H
5	QPSK	1	0	24.48	24.62	24.51	0.0471	0.0486	0.0474
5	16QAM	1	0	23.49	23.49	23.40	0.0375	0.0375	0.0367
Channel				23025	23095	23165	ERP(W)		
Frequency (MHz)				700.5	707.5	714.5	L	M	H
3	QPSK	1	0	24.46	24.59	24.47	0.0469	0.0483	0.0470
3	16QAM	1	0	23.47	23.49	23.46	0.0373	0.0375	0.0372
Channel				23017	23095	23173	ERP(W)		
Frequency (MHz)				699.7	707.5	715.3	L	M	H
1.4	QPSK	1	0	24.43	24.55	24.50	0.0466	0.0479	0.0473
1.4	16QAM	1	0	23.47	23.52	23.45	0.0373	0.0378	0.0372

LTE Band 17_Ant.1


BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	ERP(W) < 3W Test Results: Pass		
Channel				23780	23790	23800			
Frequency (MHz)				709	710	711	L	M	H
10	QPSK	1	0	24.39	24.57	24.50	0.0461	0.0481	0.0473
10	QPSK	1	49	24.39	24.46	24.35	0.0461	0.0469	0.0457
10	QPSK	50	0	23.48	23.50	23.44	0.0374	0.0376	0.0371
10	16QAM	1	0	23.69	23.75	23.72	0.0393	0.0398	0.0395
10	64QAM	1	0	22.54	22.64	22.55	0.0301	0.0308	0.0302
10	256QAM	1	0	19.50	19.57	19.50	0.0150	0.0152	0.0150
Channel				23755	23790	23825	ERP(W)		
Frequency (MHz)				706.5	710	713.5	L	M	H
5	QPSK	1	0	24.37	24.50	24.46	0.0459	0.0473	0.0469
5	16QAM	1	0	23.61	23.64	23.65	0.0385	0.0388	0.0389



LTE Band 2

Peak-to-Average Ratio


Mode	LTE Band 2 / 20MHz				
Mod.	QPSK	16QAM	64QAM	256QAM	Limit: 13dB
RB Size	Full RB	Full RB	Full RB	Full RB	Result
Middle CH	4.29	5.48	6.26	6.38	PASS





26dB Bandwidth


Mode	LTE Band 2 : 26dB BW(MHz)	
BW	1.4MHz	
Mod.	QPSK	16QAM
Middle CH	1.31	1.37
BW	3MHz	
Mod.	QPSK	16QAM
Middle CH	3.12	3.10
BW	5MHz	
Mod.	QPSK	16QAM
Middle CH	5.08	5.07
BW	10MHz	
Mod.	QPSK	16QAM
Middle CH	10.07	9.91
BW	15MHz	
Mod.	QPSK	16QAM
Middle CH	14.30	14.27
BW	20MHz	
Mod.	QPSK	16QAM
Middle CH	18.82	18.98






LTE Band 2

Middle Channel / 3MHz / QPSK



Date: 6.APR.2024 16:46:22

Middle Channel / 3MHz / 16QAM



Date: 6.APR.2024 16:47:16


LTE Band 2

Middle Channel / 5MHz / QPSK



Date: 6.APR.2024 16:29:54

Middle Channel / 5MHz / 16QAM



Date: 6.APR.2024 16:30:47

LTE Band 2

Middle Channel / 10MHz / QPSK



Date: 6.APR.2024 16:27:25

Middle Channel / 10MHz / 16QAM




Date: 6.APR.2024 16:28:19




LTE Band 2

Middle Channel / 15MHz / QPSK



Date: 6.APR.2024 16:23:41


Middle Channel / 15MHz / 16QAM



Date: 6.APR.2024 16:24:36


LTE Band 2

Middle Channel / 20MHz / QPSK



Date: 6.APR.2024 16:11:20

Middle Channel / 20MHz / 16QAM




Date: 6.APR.2024 16:12:16



Occupied Bandwidth


Mode	LTE Band 2 : 99%OBW(MHz)	
BW	1.4MHz	
Mod.	QPSK	16QAM
Middle CH	1.10	1.10
BW	3MHz	
Mod.	QPSK	16QAM
Middle CH	2.72	2.73
BW	5MHz	
Mod.	QPSK	16QAM
Middle CH	4.51	4.54
BW	10MHz	
Mod.	QPSK	16QAM
Middle CH	9.05	9.11
BW	15MHz	
Mod.	QPSK	16QAM
Middle CH	13.49	13.46
BW	20MHz	
Mod.	QPSK	16QAM
Middle CH	17.86	17.94






LTE Band 2

Middle Channel / 3MHz / QPSK



Date: 6.APR.2024 16:46:16


Middle Channel / 3MHz / 16QAM



Date: 6.APR.2024 16:47:02


LTE Band 2

Middle Channel / 5MHz / QPSK



Date: 6.APR.2024 16:30:08


Middle Channel / 5MHz / 16QAM



Date: 6.APR.2024 16:30:33


LTE Band 2

Middle Channel / 10MHz / QPSK



Date: 6.APR.2024 16:27:39

Middle Channel / 10MHz / 16QAM




Date: 6.APR.2024 16:28:05




LTE Band 2

Middle Channel / 15MHz / QPSK



Date: 6.APR.2024 16:23:55


Middle Channel / 15MHz / 16QAM



Date: 6.APR.2024 16:24:21


LTE Band 2

Middle Channel / 20MHz / QPSK



Date: 6.APR.2024 16:11:34

Middle Channel / 20MHz / 16QAM






Date: 6.APR.2024 16:12:30



Conducted Band Edge


LTE Band 2 / 1.4MHz / QPSK






LTE Band 2 / 1.4MHz / 16QAM

Lowest Band Edge / 1 RB




Date: 6.APR.2024 14:03:51

Highest Band Edge / 1 RB




Date: 6.APR.2024 14:26:08

Lowest Band Edge / Full RB



Date: 6.APR.2024 14:13:34

Highest Band Edge / Full RB




Date: 6.APR.2024 14:35:54



LTE Band 2 / 1.4MHz / 64QAM

Lowest Band Edge / 1 RB




Date: 6.APR.2024 14:06:16

Highest Band Edge / 1 RB




Date: 6.APR.2024 14:28:33

Lowest Band Edge / Full RB



Date: 6.APR.2024 14:16:00

Highest Band Edge / Full RB




Date: 6.APR.2024 14:38:20




LTE Band 2 / 1.4MHz / 256QAM

Lowest Band Edge / 1RB




Date: 6.APR.2024 14:08:42

Highest Band Edge / 1RB



Date: 6.APR.2024 14:30:59

Lowest Band Edge / Full RB



Date: 6.APR.2024 14:18:26

Highest Band Edge / Full RB




Date: 6.APR.2024 14:40:45




LTE Band 2 / 3MHz / QPSK

Lowest Band Edge / 1RB




Date: 6.APR.2024 14:45:07

Highest Band Edge / 1 RB



Date: 6.APR.2024 14:57:26

Lowest Band Edge / Full RB



Date: 6.APR.2024 14:51:33

Highest Band Edge / Full RB




Date: 6.APR.2024 15:00:29




LTE Band 2 / 3MHz / 16QAM

Lowest Band Edge / 1 RB




Date: 6.APR.2024 14:47:33

Highest Band Edge / 1 RB



Date: 6.APR.2024 14:58:12

Lowest Band Edge / Full RB



Date: 6.APR.2024 14:52:19

Highest Band Edge / Full RB




Date: 6.APR.2024 15:01:15




LTE Band 2 / 3MHz / 64QAM

Lowest Band Edge / 1 RB




Date: 6.APR.2024 14:49:59

Highest Band Edge / 1 RB




Date: 6.APR.2024 14:58:58

Lowest Band Edge / Full RB



Date: 6.APR.2024 14:53:05

Highest Band Edge / Full RB




Date: 6.APR.2024 15:02:01




LTE Band 2 / 3MHz / 256QAM

Lowest Band Edge / 1RB




Date: 6.APR.2024 14:50:45

Highest Band Edge / 1 RB



Date: 6.APR.2024 14:59:44

Lowest Band Edge / Full RB



Date: 6.APR.2024 14:53:51

Highest Band Edge / Full RB




Date: 6.APR.2024 15:02:47




LTE Band 2 / 5MHz / QPSK

Lowest Band Edge / 1 RB




Date: 6.APR.2024 15:05:29

Highest Band Edge / 1 RB



Date: 6.APR.2024 15:14:25

Lowest Band Edge / Full RB



Date: 6.APR.2024 15:08:32

Highest Band Edge / Full RB




Date: 6.APR.2024 15:17:28




LTE Band 2 / 5MHz / 16QAM


Lowest Band Edge / 1RB



Highest Band Edge / 1 RB



Lowest Band Edge / Full RB




Highest Band Edge / Full RB






LTE Band 2 / 5MHz / 64QAM

Lowest Band Edge / 1RB




Date: 6.APR.2024 15:07:00

Highest Band Edge / 1 RB




Date: 6.APR.2024 15:15:56

Lowest Band Edge / Full RB



Date: 6.APR.2024 15:10:03

Highest Band Edge / Full RB




Date: 6.APR.2024 15:19:00




LTE Band 2 / 5MHz / 256QAM

Lowest Band Edge / 1RB




Date: 6.APR.2024 15:07:46

Highest Band Edge / 1 RB



Date: 6.APR.2024 15:16:42

Lowest Band Edge / Full RB



Date: 6.APR.2024 15:10:49

Highest Band Edge / Full RB





Date: 6.APR.2024 15:19:45



LTE Band 2 / 10MHz / QPSK

Lowest Band Edge / 1 RB

Highest Band Edge / 1 RB




Date: 6.APR.2024 15:22:27

Date: 6.APR.2024 15:31:27

Lowest Band Edge / Full RB

Highest Band Edge / Full RB




Date: 6.APR.2024 15:25:34

Date: 6.APR.2024 15:34:30




LTE Band 2 / 10MHz / 16QAM

Lowest Band Edge / 1 RB




Date: 6.APR.2024 15:23:13

Highest Band Edge / 1 RB




Date: 6.APR.2024 15:32:13

Lowest Band Edge / Full RB



Date: 6.APR.2024 15:26:20

Highest Band Edge / Full RB




Date: 6.APR.2024 15:35:16




LTE Band 2 / 10MHz / 64QAM


Lowest Band Edge / 1 RB




Highest Band Edge / 1 RB



Lowest Band Edge / Full RB




Highest Band Edge / Full RB






LTE Band 2 / 10MHz / 256QAM

Lowest Band Edge / 1 RB




Date: 6.APR.2024 15:24:45

Highest Band Edge / 1 RB



Date: 6.APR.2024 15:33:44

Lowest Band Edge / Full RB



Date: 6.APR.2024 15:27:51

Highest Band Edge / Full RB



Date: 6.APR.2024 15:36:47