



# FCC RF Test Report

**APPLICANT** : Xiaomi Communications Co., Ltd.  
**EQUIPMENT** : Mobile Phone  
**BRAND NAME** : Redmi  
**MODEL NAME** : 25080RABDG  
**FCC ID** : 2AFZZRABDG  
**STANDARD** : 47 CFR Part 22(H), 24(E), 27(L)  
**CLASSIFICATION** : PCS Licensed Transmitter Held to Ear (PCE)  
**TEST DATE(S)** : Jul. 03, 2025 ~ Jul. 16, 2025

We, Sporton International Inc. (ShenZhen), would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.26-2015 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (ShenZhen), the test report shall not be reproduced except in full.



Approved by: Fly Liang

**Sporton International Inc. (ShenZhen)**

**1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055**

**People's Republic of China**



# TABLE OF CONTENTS

**REVISION HISTORY..... 3**

**SUMMARY OF TEST RESULT ..... 4**

**1 GENERAL DESCRIPTION ..... 5**

    1.1 Applicant..... 5

    1.2 Manufacturer ..... 5

    1.3 Product Feature of Equipment Under Test ..... 5

    1.4 Product Specification of Equipment Under Test ..... 6

    1.5 Modification of EUT ..... 7

    1.6 Maximum ERP/EIRP and Emission Designator ..... 7

    1.7 Testing Location ..... 7

    1.8 Test Software ..... 8

    1.9 Applicable Standards ..... 8

**2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST ..... 9**

    2.1 Test Mode..... 9

    2.2 Connection Diagram of Test System ..... 10

    2.3 Support Unit used in test configuration ..... 10

    2.4 Measurement Results Explanation Example ..... 11

    2.5 Frequency List of Low/Middle/High Channels..... 11

**3 CONDUCTED TEST RESULT..... 12**

    3.1 Measuring Instruments..... 12

    3.2 Test Setup ..... 12

    3.3 Test Result of Conducted Test..... 12

    3.4 Conducted Output Power and ERP/EIRP ..... 13

    3.5 Peak-to-Average Ratio ..... 14

    3.6 99% Occupied Bandwidth and 26dB Bandwidth Measurement..... 15

    3.7 Conducted Band Edge ..... 16

    3.8 Conducted Spurious Emission ..... 17

    3.9 Frequency Stability..... 18

**4 RADIATED TEST ITEMS ..... 19**

    4.1 Measuring Instruments..... 19

    4.2 Test Setup ..... 19

    4.3 Test Result of Radiated Test..... 20

    4.4 Field Strength of Spurious Radiation Measurement ..... 21

**5 LIST OF MEASURING EQUIPMENT ..... 22**

**6 MEASUREMENT UNCERTAINTY ..... 23**

**APPENDIX A. TEST RESULTS OF CONDUCTED TEST**

**APPENDIX B. TEST RESULTS OF RADIATED TEST**

**APPENDIX C. TEST SETUP PHOTOGRAPHS**





## SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.4	§2.1046	Conducted Output Power	-	Report Only	-
	§22.913(a)(5)	Effective Radiated Power	< 7 Watts	PASS	-
	§24.232(c)	Equivalent Isotropic Radiated Power	< 2 Watts	PASS	-
	§27.50(d)(4)	Equivalent Isotropic Radiated Power	< 1 Watts	PASS	-
3.5	§24.232(d)	Peak-to-Average Ratio	< 13 dB	PASS	-
3.6	§2.1049	Occupied Bandwidth	Reporting Only	PASS	-
3.7	§2.1051 §22.917(a) §24.238(a) §27.53(h)	Band Edge Measurement	< 43+10log10(P[Watts])	PASS	-
3.8	§2.1051 §22.917(a) §24.238(a) §27.53(h)	Conducted Emission	< 43+10log10(P[Watts])	PASS	-
3.9	§2.1055 §22.355	Frequency Stability for Temperature & Voltage	< 2.5 ppm for Part 22	PASS	-
	§2.1055 §24.235 §27.54		Within Authorized Band		
4.4	§2.1053; §22.917(a); §24.238(a); §27.53(h)	Field Strength of Spurious Radiation	< 43+10log10(P[Watts])	PASS	Under limit 33.97 dB at 5640.00 MHz

**Conformity Assessment Condition:**

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacturer who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty"

**Disclaimer:**

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.



# 1 General Description

## 1.1 Applicant

Xiaomi Communications Co., Ltd.

#019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085

## 1.2 Manufacturer

Xiaomi Communications Co., Ltd.

#019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085

## 1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Phone
Brand Name	Redmi
Model Name	25080RABDG
FCC ID	2AFZZRABDG
IMEI Code	Conducted: 862542070023583/862542070023591 Radiation: 862542070040926/862542070040934
HW Version	135100P16
SW Version	Xiaomi HyperOS 2.0
EUT Stage	Identical Prototype

**Remark:** The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.



### 1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
<b>Tx Frequency</b>	<b>GSM/GPRS/EDGE:</b> 850: 824 MHz ~ 849 MHz 1900: 1850MHz ~ 1910MHz <b>WCDMA:</b> Band V: 824 MHz ~ 849 MHz Band II: 1850 MHz ~ 1910 MHz Band IV: 1710 MHz ~ 1755 MHz
<b>Rx Frequency</b>	<b>GSM/GPRS/EDGE:</b> 850: 869 MHz ~ 894 MHz 1900: 1930 MHz ~ 1990 MHz <b>WCDMA:</b> Band V: 869 MHz ~ 894 MHz Band II: 1930 MHz ~ 1990 MHz Band IV: 2110 MHz ~ 2155 MHz
<b>Maximum Output Power to Antenna</b>	<b>GSM/GPRS/EDGE:</b> 850: <Ant.0> 32.29 dBm <Ant.2> 32.21 dBm 1900: <Ant.1> 29.06 dBm <Ant.5> 29.53 dBm <b>WCDMA:</b> Band V: <Ant.0> 24.14 dBm <Ant.2> 24.07 dBm Band II: <Ant.1> 24.43 dBm <Ant.5> 24.12 dBm Band IV: <Ant.1> 24.27 dBm <Ant.5> 24.58 dBm
<b>Antenna Type</b>	PIFA Antenna
<b>Antenna Gain</b>	<b>&lt;Ant.0&gt;</b> Cellular Band: -3.9 dBi <b>&lt;Ant.1&gt;</b> PCS Band: -3.9 dBi AWS Band: -4.3 dBi <b>&lt;Ant.2&gt;</b> Cellular Band: -7.1 dBi <b>&lt;Ant.5&gt;</b> PCS Band: -0.92 dBi AWS Band: -2.86 dBi
<b>Type of Modulation</b>	GSM: GMSK GPRS: GMSK EDGE: GMSK / 8PSK WCDMA : BPSK HSDPA/DC-HSDPA : QPSK HSUPA : QPSK HSPA+ : 16QAM DC-HSDPA : 64QAM



Note:

1. The maximum ERP/EIRP is calculated from max output power and max antenna gain, so only the maximum ERP/EIRP of Ant.0 for GSM 850/WCDMA Band V and Ant.5 for GSM1900/WCDMA Band II/ IV are shown in the report.
2. The test data of Ant. 0 for GSM850/WCDMA B5, and Ant.1 for WCDMA B2, and Ant.5 for GSM1900/WCDMA B4 is showed in the report according to the maximum conducted power for conducted test items.

### 1.5 Modification of EUT

No modifications are made to the EUT during all test items.

### 1.6 Maximum ERP/EIRP and Emission Designator

FCC Rule	Frequency Band	Frequency Range (MHz)	Type of Modulation	Maximum ERP/EIRP (W)	Emission Designator
Part 22	GSM850 (GPRS)	824.2 ~ 848.8	GMSK	0.4207	245KGXW
Part 22	GSM850 (EDGE)	824.2 ~ 848.8	8PSK	0.1146	252KG7W
Part 22	WCDMA Band V	826.4 ~ 846.6	BPSK	0.0644	4M15F9W
Part 24	GSM1900 (GPRS)	1850.2 ~ 1909.8	GMSK	0.7261	245KGXW
Part 24	GSM1900 (EDGE)	1850.2 ~ 1909.8	8PSK	0.3069	253KG7W
Part 24	WCDMA Band II	1852.4 ~ 1907.6	BPSK	0.2089	4M18F9W
Part 27	WCDMA Band IV	1712.4 ~ 1752.6	BPSK	0.1486	4M16F9W

### 1.7 Testing Location

Sporton International Inc. (ShenZhen) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

<b>Test Firm</b>	Sporton International Inc. (ShenZhen)		
<b>Test Site Location</b>	101, 1st Floor, Block B, Building 1, No. 2, Tengfeng 4th Road, Fenghuang Community, Fuyong Street, Baoan District, Shenzhen City, Guangdong Province 518103 People's Republic of China TEL: +86-755-86066985		
<b>Test Site No.</b>	<b>Sporton Site No.</b>	<b>FCC Designation No.</b>	<b>FCC Test Firm Registration No.</b>
	TH01-SZ 03CH01-SZ	CN1256	421272



### 1.8 Test Software

Item	Site	Manufacturer	Name	Version
1.	03CH01-SZ	AUDIX	E3	6.2009-8-24

### 1.9 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 22(H), 24(E), 27(L)
- ♦ ANSI C63.26-2015
- ♦ FCC KDB 971168 D01 Power Meas. License Digital Systems v03r01
- ♦ FCC KDB 412172 D01 Determining ERP and EIRP v01r01

**Remark:**

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



## 2 Test Configuration of Equipment Under Test

### 2.1 Test Mode

Antenna port conducted and radiated test items were performed according to KDB 971168 D01 Power Meas. License Digital Systems v03r01 with maximum output power.

Radiated measurements were performed with rotating EUT in different three orthogonal test planes to find the maximum emission.

Radiated emissions were investigated as following frequency range:


1. 30 MHz to 9000 MHz for GSM850 and WCDMA Band V.
2. 30 MHz to 18000 MHz for WCDMA Band IV.
3. 30 MHz to 19100 MHz for GSM1900 and WCDMA Band II.

All modes and data rates and positions were investigated.

Test modes are chosen to be reported as the worst case configuration below:

Test Modes		
Band	Radiated TCs	Conducted TCs
GSM 850	<ul style="list-style-type: none"> <li>■ GSM Link</li> <li>■ EDGE 1 Tx slots Link</li> </ul>	<ul style="list-style-type: none"> <li>■ GSM Link</li> <li>■ EDGE 1 Tx slots Link</li> </ul>
GSM 1900	<ul style="list-style-type: none"> <li>■ GSM Link</li> <li>■ EDGE 1 Tx slots Link</li> </ul>	<ul style="list-style-type: none"> <li>■ GSM Link</li> <li>■ EDGE 1 Tx slots Link</li> </ul>
WCDMA Band V	<ul style="list-style-type: none"> <li>■ RMC 12.2Kbps Link</li> </ul>	<ul style="list-style-type: none"> <li>■ RMC 12.2Kbps Link</li> </ul>
WCDMA Band II	<ul style="list-style-type: none"> <li>■ RMC 12.2Kbps Link</li> </ul>	<ul style="list-style-type: none"> <li>■ RMC 12.2Kbps Link</li> </ul>
WCDMA Band IV	<ul style="list-style-type: none"> <li>■ HSDPA Link</li> </ul>	<ul style="list-style-type: none"> <li>■ HSDPA Link</li> </ul>

## 2.2 Connection Diagram of Test System



The EUT has been configuration operated in a manner tended to maximize its emission characteristics in a typical application.

## 2.3 Support Unit used in test configuration

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m



## 2.4 Measurement Results Explanation Example

**For all conducted test items:**

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

$$\text{Offset} = \text{RF cable loss} + \text{attenuator factor}.$$

The following shows an offset computation example with RF cable loss 4.0 dB and a 10dB attenuator.

Example :

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\ &= 4.0 + 10 = 14.0 \text{ (dB)} \end{aligned}$$

## 2.5 Frequency List of Low/Middle/High Channels

Frequency List				
Band	Channel/Frequency(MHz)	Lowest	Middle	Highest
GSM850	Channel	128	189	251
	Frequency	824.2	836.4	848.8
WCDMA Band V	Channel	4132	4182	4233
	Frequency	826.4	836.4	846.6
GSM1900	Channel	512	661	810
	Frequency	1850.2	1880.0	1909.8
WCDMA Band II	Channel	9262	9400	9538
	Frequency	1852.4	1880.0	1907.6
WCDMA Band IV	Channel	1312	1413	1513
	Frequency	1712.4	1732.6	1752.6


### 3 Conducted Test Result

#### 3.1 Measuring Instruments


See list of measuring instruments of this test report.

#### 3.2 Test Setup


##### 3.2.1 Conducted Output Power



##### 3.2.2 Peak-to-Average Ratio, Occupied Bandwidth, Conducted Band-Edge and Conducted Spurious Emission



##### 3.2.3 Frequency Stability



### 3.3 Test Result of Conducted Test

Please refer to Appendix A.



### 3.4 Conducted Output Power and ERP/EIRP

#### 3.4.1 Description of the Conducted Output Power and ERP/EIRP

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

The ERP of mobile transmitters must not exceed 7 Watts for GSM850 and WCDMA Band V.

The EIRP of mobile transmitters must not exceed 2 Watts for GSM1900 and WCDMA Band II.

The EIRP of mobile transmitters must not exceed 1 Watts for WCDMA Band IV.

According to KDB 412172 D01 Power Approach,

$EIRP = P_T + G_T - L_C$ ,  $ERP = EIRP - 2.15$ , where

$P_T$  = transmitter output power in dBm

$G_T$  = gain of the transmitting antenna in dBi

$L_C$  = signal attenuation in the connecting cable between the transmitter and antenna in dB

#### 3.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2
2. The transmitter output port was connected to the system simulator.
3. Set EUT at maximum power through the system simulator.
4. Select lowest, middle, and highest channels for each band and different modulation.
5. Measure and record the power level from the system simulator.



## **3.5 Peak-to-Average Ratio**

### **3.5.1 Description of the PAR Measurement**

The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

### **3.5.2 Test Procedures**

1. The testing follows ANSI C63.26 Section 5.2.3.4 (CCDF).
2. The EUT was connected to spectrum and system simulator via a power divider.
3. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
4. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
5. Record the deviation as Peak to Average Ratio.



### 3.6 99% Occupied Bandwidth and 26dB Bandwidth Measurement

#### 3.6.1 Description of 99% Occupied Bandwidth and 26dB Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

#### 3.6.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.4
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
5. Set the detection mode to peak, and the trace mode to max hold.
6. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace. (this is the reference value)
7. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
8. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “-X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
9. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.



## **3.7 Conducted Band Edge**

### **3.7.1 Description of Conducted Band Edge Measurement**

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least  $43 + 10 \log (P)$  dB.

### **3.7.2 Test Procedures**

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The band edges of low and high channels for the highest RF powers were measured.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
6. The limit line is derived from  $43 + 10\log(P)$  dB below the transmitter power P(Watts)



## 3.8 Conducted Spurious Emission

### 3.8.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least  $43 + 10 \log (P)$  dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10<sup>th</sup> harmonic.

### 3.8.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
7. The limit line is derived from  $43 + 10\log(P)$  dB below the transmitter power P(Watts)



## **3.9 Frequency Stability**

### **3.9.1 Description of Frequency Stability Measurement**

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within  $\pm 0.00025\%$  ( $\pm 2.5\text{ppm}$ ) of the center frequency.

### **3.9.2 Test Procedures for Temperature Variation**

1. The testing follows ANSI C63.26 section 5.6.4
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to  $-30^{\circ}\text{C}$  and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in  $10^{\circ}\text{C}$  step up to  $50^{\circ}\text{C}$ . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

### **3.9.3 Test Procedures for Voltage Variation**

1. The testing follows ANSI C63.26 section 5.6.5
2. The EUT was placed in a temperature chamber at  $20\pm 5^{\circ}\text{C}$  and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value for other than hand carried battery equipment.
4. For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.
5. The variation in frequency was measured for the worst case.


## 4 Radiated Test Items

### 4.1 Measuring Instruments


See list of measuring instruments of this test report.

### 4.2 Test Setup


#### 4.2.1 For radiated test below 30MHz



#### 4.2.2 For radiated test from 30MHz to 1GHz



### 4.2.3 For radiated test above 1GHz



## 4.3 Test Result of Radiated Test

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

Please refer to Appendix B.



## 4.4 Field Strength of Spurious Radiation Measurement

### 4.4.1 Description of Field Strength of Spurious Radiated Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least  $43 + 10 \log (P)$  dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

### 4.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.5
2. The EUT was placed on a rotatable wooden table 0.8 meters for frequency below 1GHz and 1.5 meter for frequency above 1GHz above the ground.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between one meter and four meters to search for the maximum spurious emission for both horizontal and vertical polarizations.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking record of maximum spurious emission.
7. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
8. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
9. Taking the record of output power at antenna port.
10. Repeat step 7 to step 8 for another polarization.
11.  $EIRP \text{ (dBm)} = S.G. \text{ Power} - Tx \text{ Cable Loss} + Tx \text{ Antenna Gain}$
12.  $ERP \text{ (dBm)} = EIRP - 2.15$
13. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
14. The limit line is derived from  $43 + 10\log(P)$  dB below the transmitter power P(Watts)



## 5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101078	10Hz~40GHz	Apr. 02, 2025	Jul. 03, 2025~ Jul. 04, 2025	Apr. 01, 2026	Conducted (TH01-SZ)
DC Power Supply	TTI	PL330P	290070	Max 32V , 3A	Oct.14,2024	Jul. 03, 2025~ Jul. 04, 2025	Oct. 13, 2025	Conducted (TH01-SZ)
Power Divider	Titan	P02N005180	923402	0.4GHz~26.5GHz	Nov. 08, 2024	Jul. 03, 2025~ Jul. 04, 2025	Nov. 07, 2025	Conducted (TH01-SZ)
Thermal Chamber	Ten Billion Hongzhangroup	LP-150U	H2014081803	-40~+150°C	Jul. 02, 2025	Jul. 03, 2025~ Jul. 04, 2025	Jul. 01, 2026	Conducted (TH01-SZ)
EMI Test Receiver&SA	Agilent	N9038A	MY52260185	20Hz~26.5GHz	Dec. 25, 2024	Jul. 16, 2025	Dec. 24, 2025	Radiation (03CH01-SZ)
Loop Antenna	R&S	HFH2-Z2E	101141	9kHz~30MHz	Dec. 28, 2024	Jul. 16, 2025	Dec. 27, 2025	Radiation (03CH01-SZ)
HF Amplifier	KEYSIGHT	83017A	MY53270105	0.5GHz~26.5GHz	Oct. 14, 2024	Jul. 16, 2025	Oct. 13, 2025	Radiation (03CH01-SZ)
Bilog Antenna	TeseQ	CBL6112D	35407	30MHz~2GHz	Oct. 24, 2023	Jul. 16, 2025	Oct. 23, 2025	Radiation (03CH01-SZ)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00119436	1GHz~18GHz	Jul. 04, 2025	Jul. 16, 2025	Jul. 03, 2026	Radiation (03CH01-SZ)
SHF-EHF Horn	com-power	AH-840	101071	18GHz~40GHz	Apr. 03, 2025	Jul. 16, 2025	Apr. 02, 2027	Radiation (03CH01-SZ)
LF Amplifier	EM Electronics	EM330	060788	20MHz~3GHz	Dec. 25, 2024	Jul. 16, 2025	Dec. 24, 2025	Radiation (03CH01-SZ)
HF Amplifier	MITEQ	AMF-7D-00101800-30-10P-R	1943528	1GHz~18GHz	Oct. 14, 2024	Jul. 16, 2025	Oct. 13, 2025	Radiation (03CH01-SZ)
HF Amplifier	MITEQ	TTA1840-35-HG	1871923	18GHz~40GHz	Jul. 03, 2025	Jul. 16, 2025	Jul. 02, 2026	Radiation (03CH01-SZ)
AC Power Source	Chroma	61601	616010001985	N/A	Oct. 14, 2024	Jul. 16, 2025	Oct. 13, 2025	Radiation (03CH01-SZ)
Turn Table	EM	EM1000	N/A	0~360 degree	NCR	Jul. 16, 2025	NCR	Radiation (03CH01-SZ)
Antenna Mast	EM	EM1000	N/A	1 m~4 m	NCR	Jul. 16, 2025	NCR	Radiation (03CH01-SZ)

NCR: No Calibration Required



## 6 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.26-2015. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

### Uncertainty of Conducted Measurement

Test Item	Uncertainty
Conducted Spurious Emission & Bandedge	±1.34 dB
Occupied Channel Bandwidth	±0.012 MHz
Conducted Power	±1.34 dB
Peak to Average Ratio	±1.34 dB
Frequency Stability	±1.3 Hz

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.48 dB
---	---------

### Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.53 dB
---	---------

### Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	4.02 dB
---	---------

----- THE END -----



## Appendix A. Test Results of Conducted Test

Test Engineer :	Nina Cheng	Temperature :	24~26°C
		Relative Humidity :	50~53%

### Conducted Output Power(Average power) and ERP/EIRP

#### GSM850\_ANT0:

GSM850 TX Channel	Burst Average Power (dBm)			ERP(W)		
	128	189	251	L	M	H
Frequency (MHz)	824.2	836.4	848.8			
GSM 1 Tx slot	32.15	32.27	32.15	0.4074	0.4188	0.4074
GPRS 1 Tx slot	32.16	32.29	32.14	0.4083	0.4207	0.4064
GPRS 2 Tx slots	29.65	29.76	29.56	0.2291	0.2350	0.2244
GPRS 3 Tx slots	27.58	27.72	27.51	0.1422	0.1469	0.1400
GPRS 4 Tx slots	26.42	26.44	26.33	0.1089	0.1094	0.1067
EDGE 1 Tx slot	26.64	26.58	26.53	0.1146	0.1130	0.1117
EDGE 2 Tx slots	23.57	23.55	23.37	0.0565	0.0562	0.0540
EDGE 3 Tx slots	21.28	21.17	21.13	0.0333	0.0325	0.0322
EDGE 4 Tx slots	19.92	19.85	19.79	0.0244	0.0240	0.0237

#### GSM1900\_ANT5:

GSM1900 TX Channel	Burst Average Power (dBm)			EIRP(W)		
	512	661	810	L	M	H
Frequency (MHz)	1850.2	1880	1909.8			
GSM 1 Tx slot	29.41	29.52	29.40	0.7063	0.7244	0.7047
GPRS 1 Tx slot	29.43	29.53	29.41	0.7096	0.7261	0.7063
GPRS 2 Tx slots	26.88	26.95	26.91	0.3945	0.4009	0.3972
GPRS 3 Tx slots	24.89	24.97	24.93	0.2495	0.2541	0.2518
GPRS 4 Tx slots	23.77	23.82	23.78	0.1928	0.1950	0.1932
EDGE 1 Tx slot	25.79	25.58	25.45	0.3069	0.2924	0.2838
EDGE 2 Tx slots	22.87	22.60	22.58	0.1567	0.1472	0.1466
EDGE 3 Tx slots	20.56	20.20	20.21	0.0920	0.0847	0.0849
EDGE 4 Tx slots	19.13	19.04	19.01	0.0662	0.0649	0.0644



**WCDMA Band V\_ANT0:**

Band		WCDMA V			ERP(W)		
TX Channel		4132	4182	4233			
Rx Channel		4357	4407	4458	L M H		
Frequency (MHz)		826.4	836.4	846.6			
3GPP Rel 99	AMR 12.2Kbps	23.98	24.13	24.06	0.0621	0.0643	0.0632
3GPP Rel 99	RMC 12.2Kbps	24.10	24.14	23.98	0.0638	0.0644	0.0621
3GPP Rel 6	HSDPA Subtest-1	23.09	23.14	23.05	0.0506	0.0512	0.0501
3GPP Rel 6	HSDPA Subtest-2	23.08	23.08	23.00	0.0505	0.0505	0.0495
3GPP Rel 6	HSDPA Subtest-3	22.59	22.57	22.55	0.0451	0.0449	0.0447
3GPP Rel 6	HSDPA Subtest-4	22.42	22.63	22.56	0.0434	0.0455	0.0448
3GPP Rel 8	DC-HSDPA Subtest-1	23.04	23.05	23.04	0.0500	0.0501	0.0500
3GPP Rel 8	DC-HSDPA Subtest-2	22.99	23.01	22.93	0.0494	0.0497	0.0488
3GPP Rel 8	DC-HSDPA Subtest-3	22.47	22.55	22.49	0.0439	0.0447	0.0441
3GPP Rel 8	DC-HSDPA Subtest-4	22.31	22.55	22.49	0.0423	0.0447	0.0441
3GPP Rel 6	HSUPA Subtest-1	22.86	22.95	22.99	0.0480	0.0490	0.0494
3GPP Rel 6	HSUPA Subtest-2	21.00	21.06	21.07	0.0313	0.0317	0.0318
3GPP Rel 6	HSUPA Subtest-3	22.14	22.19	22.15	0.0406	0.0411	0.0407
3GPP Rel 6	HSUPA Subtest-4	21.02	21.02	21.01	0.0314	0.0314	0.0313
3GPP Rel 6	HSUPA Subtest-5	22.96	23.11	22.94	0.0491	0.0508	0.0489
3GPP Rel 7	HSPA+ (16QAM) Subtest-1	20.55	20.71	20.58	0.0282	0.0292	0.0284

**WCDMA Band II\_ANT5:**

Band		WCDMA II			EIRP(W)		
TX Channel		9262	9400	9538			
Rx Channel		9662	9800	9938	L M H		
Frequency (MHz)		1852.4	1880	1907.6			
3GPP Rel 99	AMR 12.2Kbps	23.89	23.98	23.97	0.1982	0.2023	0.2018
3GPP Rel 99	RMC 12.2Kbps	24.09	24.12	23.80	0.2075	0.2089	0.1941
3GPP Rel 6	HSDPA Subtest-1	22.96	23.12	23.05	0.1600	0.1660	0.1633
3GPP Rel 6	HSDPA Subtest-2	22.99	23.03	22.94	0.1611	0.1626	0.1592
3GPP Rel 6	HSDPA Subtest-3	22.53	22.64	22.53	0.1449	0.1486	0.1449
3GPP Rel 6	HSDPA Subtest-4	22.45	22.49	22.45	0.1422	0.1435	0.1422
3GPP Rel 8	DC-HSDPA Subtest-1	22.99	23.02	23.01	0.1611	0.1622	0.1618
3GPP Rel 8	DC-HSDPA Subtest-2	22.92	22.99	22.92	0.1585	0.1611	0.1585
3GPP Rel 8	DC-HSDPA Subtest-3	22.43	22.50	22.39	0.1416	0.1439	0.1403
3GPP Rel 8	DC-HSDPA Subtest-4	22.29	22.50	22.49	0.1371	0.1439	0.1435
3GPP Rel 6	HSUPA Subtest-1	22.88	23.00	22.94	0.1570	0.1614	0.1592
3GPP Rel 6	HSUPA Subtest-2	20.97	21.07	21.03	0.1012	0.1035	0.1026
3GPP Rel 6	HSUPA Subtest-3	22.09	22.09	22.15	0.1309	0.1309	0.1327
3GPP Rel 6	HSUPA Subtest-4	20.98	20.94	20.87	0.1014	0.1005	0.0989
3GPP Rel 6	HSUPA Subtest-5	22.86	23.01	22.95	0.1563	0.1618	0.1596
3GPP Rel 7	HSPA+ (16QAM) Subtest-1	20.56	20.67	20.59	0.0920	0.0944	0.0927



WCDMA Band IV\_ANT5:

Band		WCDMA IV			EIRP(W)		
TX Channel		1312	1413	1513			
Rx Channel		1537	1638	1738			
Frequency (MHz)		1712.4	1732.6	1752.6	L	M	H
3GPP Rel 99	AMR 12.2Kbps	24.36	24.38	24.40	0.1413	0.1419	0.1426
3GPP Rel 99	RMC 12.2Kbps	24.18	24.58	24.39	0.1355	0.1486	0.1422
3GPP Rel 6	HSDPA Subtest-1	23.40	23.49	23.45	0.1132	0.1156	0.1146
3GPP Rel 6	HSDPA Subtest-2	23.39	23.38	23.34	0.1130	0.1127	0.1117
3GPP Rel 6	HSDPA Subtest-3	22.95	22.99	22.90	0.1021	0.1030	0.1009
3GPP Rel 6	HSDPA Subtest-4	22.80	22.97	22.85	0.0986	0.1026	0.0998
3GPP Rel 8	DC-HSDPA Subtest-1	23.39	23.48	23.38	0.1130	0.1153	0.1127
3GPP Rel 8	DC-HSDPA Subtest-2	23.30	23.37	23.31	0.1107	0.1125	0.1109
3GPP Rel 8	DC-HSDPA Subtest-3	22.77	22.97	22.84	0.0979	0.1026	0.0995
3GPP Rel 8	DC-HSDPA Subtest-4	22.70	22.83	22.80	0.0964	0.0993	0.0986
3GPP Rel 6	HSUPA Subtest-1	23.22	23.35	23.32	0.1086	0.1119	0.1112
3GPP Rel 6	HSUPA Subtest-2	21.42	21.42	21.37	0.0718	0.0718	0.0710
3GPP Rel 6	HSUPA Subtest-3	22.44	22.53	22.56	0.0908	0.0927	0.0933
3GPP Rel 6	HSUPA Subtest-4	21.29	21.44	21.34	0.0697	0.0721	0.0705
3GPP Rel 6	HSUPA Subtest-5	23.31	23.37	23.38	0.1109	0.1125	0.1127
3GPP Rel 7	HSPA+ (16QAM) Subtest-1	20.91	21.06	20.97	0.0638	0.0661	0.0647





# A1. GSM

## Peak-to-Average Ratio

Mode	GSM850(dB)		Limit: 13dB
Mod.	GSM	EDGE class 8	Result
Lowest CH	0.14	3.07	PASS
Middle CH	0.20	2.96	
Highest CH	0.17	3.13	

Mode	GSM1900(dB)		Limit: 13dB
Mod.	GSM	EDGE class 8	Result
Lowest CH	0.14	2.99	PASS
Middle CH	0.17	2.75	
Highest CH	0.23	2.75	







**26dB Bandwidth**

Mode	GSM850(MHz)	
Mod.	GSM	EDGE class 8
Lowest CH	0.32	0.31
Middle CH	0.31	0.32
Highest CH	0.31	0.32

Mode	GSM1900(MHz)	
Mod.	GSM	EDGE class 8
Lowest CH	0.32	0.32
Middle CH	0.31	0.32
Highest CH	0.31	0.33



GSM850 (GSM)


Lowest Channel



Date: 3.JUL.2025 14:36:14


GSM850 (EDGE class 8)

Lowest Channel




Date: 3.JUL.2025 14:53:27

Middle Channel




Date: 3.JUL.2025 14:41:04

Middle Channel




Date: 3.JUL.2025 14:57:57

Highest Channel



Date: 3.JUL.2025 14:43:26

Highest Channel



Date: 3.JUL.2025 15:05:25



GSM1900 (GSM)


Lowest Channel



Date: 4 JUL 2025 06:42:13


GSM1900 (EDGE class 8)

Lowest Channel




Date: 4 JUL 2025 06:55:23

Middle Channel




Date: 4 JUL 2025 06:45:29

Middle Channel




Date: 4 JUL 2025 07:01:03

Highest Channel



Date: 4 JUL 2025 06:49:39

Highest Channel



Date: 4 JUL 2025 07:02:11



### Occupied Bandwidth


Mode	GSM850(MHz)	
Mod.	GSM	EDGE class 8
Lowest CH	0.244	0.250
Middle CH	0.243	0.251
Highest CH	0.245	0.252

Mode	GSM1900(MHz)	
Mod.	GSM	EDGE class 8
Lowest CH	0.242	0.252
Middle CH	0.245	0.250
Highest CH	0.243	0.253



GSM850 (GSM)


Lowest Channel



Date: 3 JUL 2025 14:36:48


GSM850 (EDGE class 8)

Lowest Channel




Date: 3 JUL 2025 14:54:03

Middle Channel




Date: 3 JUL 2025 14:41:40

Middle Channel




Date: 3 JUL 2025 14:58:31

Highest Channel



Date: 3 JUL 2025 14:43:44

Highest Channel



Date: 3 JUL 2025 15:00:46



GSM1900 (GSM)


Lowest Channel



Date: 4 JUL 2025 06:42:39


GSM1900 (EDGE class 8)

Lowest Channel




Date: 4 JUL 2025 06:56:21

Middle Channel




Date: 4 JUL 2025 06:45:48

Middle Channel




Date: 4 JUL 2025 07:06:44

Highest Channel



Date: 4 JUL 2025 06:50:10



Highest Channel



Date: 4 JUL 2025 07:02:34




# Conducted Band Edge






GSM1900 (GSM)

Lowest Band Edge




Highest Band Edge




GSM1900 (EDGE class 8)

Lowest Band Edge




Highest Band Edge






# Conducted Spurious Emission





GSM1900 (GSM)


Lowest Channel



Date: 4 JUL 2025 06:43:06


GSM1900 (EDGE class 8)

Lowest Channel




Date: 4 JUL 2025 07:00:00

Middle Channel




Date: 4 JUL 2025 06:46:37

Middle Channel




Date: 4 JUL 2025 07:01:18

Highest Channel



Date: 4 JUL 2025 06:53:28

Highest Channel



Date: 4 JUL 2025 07:02:47



**Frequency Stability**

Test Conditions Temperature (°C)	Middle Channel Voltage (Volt)	GSM850 (GSM)	GSM850 (EDGE class 8)	Limit 2.5ppm
		Deviation (ppm)		Result
50	Normal Voltage	0.0010	0.0002	PASS
40	Normal Voltage	0.0007	0.0023	
30	Normal Voltage	0.0012	0.0004	
20(Ref.)	Normal Voltage	0.0000	0.0000	
10	Normal Voltage	0.0005	0.0020	
0	Normal Voltage	0.0018	0.0033	
-10	Normal Voltage	0.0023	0.0038	
-20	Normal Voltage	0.0005	0.0020	
-30	Normal Voltage	0.0011	0.0026	
20	Maximum Voltage	0.0014	0.0030	
20	Normal Voltage	0.0000	0.0000	
20	Battery End Point	0.0042	0.0036	

Test Conditions Temperature (°C)	Middle Channel Voltage (Volt)	GSM1900 (GSM)	GSM1900 (EDGE class 8)	Limit Note 2.
		Deviation (ppm)		Result
50	Normal Voltage	0.0014	0.0021	PASS
40	Normal Voltage	0.0011	0.0004	
30	Normal Voltage	0.0012	0.0006	
20(Ref.)	Normal Voltage	0.0000	0.0000	
10	Normal Voltage	0.0020	0.0013	
0	Normal Voltage	0.0013	0.0006	
-10	Normal Voltage	0.0007	0.0001	
-20	Normal Voltage	0.0008	0.0002	
-30	Normal Voltage	0.0005	0.0002	
20	Maximum Voltage	0.0002	0.0008	
20	Normal Voltage	0.0000	0.0000	
20	Battery End Point	0.0010	0.0005	

**Note:**


1. Normal Voltage = 3.89V. ; Battery End Point (BEP) = 3.6 V. ; Maximum Voltage =4.3V
2. The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.




## A2. WCDMA

### Peak-to-Average Ratio

Mode	WCDMA Band V(dB)	WCDMA Band II(dB)	WCDMA Band IV(dB)	Limit: 13dB
Mod.	RMC 12.2Kbps	RMC 12.2Kbps	RMC 12.2Kbps	Result
Lowest CH	2.99	2.90	3.13	<b>PASS</b>
Middle CH	3.07	3.07	2.67	
Highest CH	3.01	2.72	3.04	








**26dB Bandwidth**

Mode	WCDMA Band V(MHz)	WCDMA Band II(MHz)	WCDMA Band IV(MHz)
Mod.	RMC 12.2Kbps	RMC 12.2Kbps	RMC 12.2Kbps
Lowest CH	4.69	4.69	4.70
Middle CH	4.70	4.69	4.73
Highest CH	4.69	4.72	4.71



WCDMA Band V (RMC 12.2Kbps)


Lowest Channel



Date: 3 JUL 2025 13:59:04


WCDMA Band II (RMC 12.2Kbps)

Lowest Channel




Date: 3 JUL 2025 12:42:51

Middle Channel




Date: 3 JUL 2025 14:03:10

Middle Channel




Date: 3 JUL 2025 13:41:08

Highest Channel




Date: 3 JUL 2025 14:06:01

Highest Channel



Date: 3 JUL 2025 13:43:56






### Occupied Bandwidth

Mode	WCDMA Band V(MHz)	WCDMA Band II(MHz)	WCDMA Band IV(MHz)
Mod.	RMC 12.2Kbps	RMC 12.2Kbps	RMC 12.2Kbps
Lowest CH	4.15	4.17	4.15
Middle CH	4.14	4.14	4.16
Highest CH	4.15	4.18	4.16




WCDMA Band V (RMC 12.2Kbps)

Lowest Channel




WCDMA Band II (RMC 12.2Kbps)


Lowest Channel




Middle Channel



Middle Channel



Highest Channel



Highest Channel

