




Fig.53. Conducted spurious emission: 8DPSK, Channel 0, 30MHz - 1GHz




Fig.54. Conducted spurious emission: 8DPSK, Channel 0, 1GHz - 3GHz




Fig.55. Conducted spurious emission: 8DPSK, Channel 0, 3GHz - 10GHz




Fig.56. Conducted spurious emission: 8DPSK, Channel 0, 10GHz - 26GHz




Fig.57. Conducted spurious emission: 8DPSK, Channel 39, 2441MHz




Fig.58. Conducted spurious emission: 8DPSK, Channel 39, 30MHz - 1GHz




Fig.59. Conducted spurious emission: 8DPSK, Channel 39, 1GHz - 3GHz




Fig.60. Conducted spurious emission: 8DPSK, Channel 39, 3GHz - 10GHz




Fig.61. Conducted spurious emission: 8DPSK, Channel 39, 10GHz – 26GHz




Fig.62. Conducted spurious emission: 8DPSK, Channel 78, 2480MHz




Fig.63. Conducted spurious emission: 8DPSK, Channel 78, 30MHz - 1GHz




Fig.64. Conducted spurious emission: 8DPSK, Channel 78, 1GHz - 3GHz




Fig.65. Conducted spurious emission: 8DPSK, Channel 78, 3GHz - 10GHz




Fig.66. Conducted spurious emission: 8DPSK, Channel 78, 10GHz - 26GHz

B.5. Radiated Unwanted Emission

Limits

Measurement Limit

Standard	Limit
FCC 47 CFR Part 15.247, 15.205, 15.209	20dB below peak output power

In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

Limit in restricted band

Frequency (MHz)	Field strength($\mu\text{V/m}$)	Measurement distance (m)
0.009 - 0.490	$2400/F(\text{kHz})$	300
0.490 - 1.705	$24000/F(\text{kHz})$	30
1.705 – 30.0	30	30

Frequency of emission (MHz)	Field strength ($\mu\text{V/m}$)	Field strength (dBuV/m)	Measurement distance (m)
30-88	100	40	3
88-216	150	43.5	3
216-960	200	46	3
Above 960	500	54	3

Note: When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor.

Test setup




Figure B.5.1. Test Site Diagram (9kHz-30MHz)




Figure B.5.2. Test Site Diagram (30MHz-1GHz)




Figure B.5.3. Test Site Diagram (1GHz-40GHz)

Test Procedures

Radiated unwanted emissions from the EUT were measured according to ANSI C63.10-2013 (ANSI C63.10-2020).

Test setting

Frequency of emission (MHz)	RBW/VBW	Sweep Time(s)
30-1000	100kHz/300kHz	5
1000-3000	1MHz/3MHz	15
3000-18000	1MHz/3MHz	40
18000-26500	1MHz/3MHz	20

Sample Calculation

A "reference path loss" is established and the A_{Rpl} is the attenuation of "reference path loss", and including the gain of receive antenna, the gain of the preamplifier, the cable loss.

P_{Mea} is the field strength recorded from the instrument.

The measurement results are obtained as described below:

Result= $P_{Mea}+A_{Rpl}=P_{Mea}+CableLoss+Antenna\ Factor$

Test note

1. Investigation has been done on all modes and modulations/data rates. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.
2. Spurious emissions for all channels were investigated and almost the same below 1GHz. According to FCC 47 CFR §15.31, emission levels are not report much lower than the limit by over 20dB.
3. Measurement frequencies were performed from 9 kHzto the 10th harmonic of highest fundamental frequency or 40GHz, whichever is lower.
- 4.No spurious emissions were detected within 20dBof the limit below 30MHz. OFS and semi-chamber comparison testing had been performed and the result came out very similar.
(KDB 414788)

Test Result

EUT ID:EUT1

Radiated Spurious Emission

GFSK Ch 0

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17899.500	55.75	-25.90	46.00	35.65	74.00	18.25	H
13738.000	51.74	-29.10	41.10	39.74	74.00	22.26	V
12996.000	49.68	-29.40	40.10	38.98	74.00	24.32	V
8417.500	47.64	-33.80	37.40	44.04	74.00	26.36	H
7429.500	46.89	-34.50	36.50	44.89	74.00	27.11	H
2348.800	55.93	-19.30	28.20	47.03	74.00	18.07	V

GFSK Ch 39

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17924.500	56.22	-25.90	46.00	36.12	74.00	17.78	V
13782.000	51.77	-29.00	41.20	39.57	74.00	22.23	V
12829.000	48.99	-30.30	39.90	39.39	74.00	25.01	H
9418.000	46.55	-33.50	37.90	42.15	74.00	27.45	V
7411.500	46.53	-34.40	36.60	44.33	74.00	27.47	V
4770.000	41.92	-37.00	33.10	45.82	74.00	32.08	V

GFSK Ch 78

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17917.000	56.00	-25.90	46.00	35.90	74.00	18.00	V
14107.000	51.43	-29.10	41.70	38.83	74.00	22.57	V
12763.000	49.01	-30.50	39.60	39.91	74.00	24.99	V
9583.500	46.80	-33.00	37.50	42.30	74.00	27.20	H
7632.500	46.10	-34.60	36.30	44.40	74.00	27.90	H
2486.400	56.32	-19.00	28.20	47.12	74.00	17.68	H

$\pi/4$ DQPSK Ch 0

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17910.000	55.82	-25.90	46.00	35.72	74.00	18.18	V
13817.000	52.52	-28.90	41.20	40.22	74.00	21.48	V
11843.500	48.74	-31.10	39.10	40.74	74.00	25.26	H
9609.000	46.55	-33.00	37.60	41.95	74.00	27.45	V
7204.000	46.39	-34.50	36.20	44.69	74.00	27.61	H
2342.100	56.01	-19.30	28.20	47.11	74.00	17.99	V

$\pi/4$ DQPSK Ch 39

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17945.500	55.87	-25.90	46.00	35.77	74.00	18.13	H
14038.000	51.37	-28.90	41.60	38.67	74.00	22.63	H
11832.000	49.56	-31.10	39.10	41.56	74.00	24.44	H
9027.500	46.51	-33.50	37.80	42.21	74.00	27.49	V
7612.500	46.21	-34.70	36.30	44.61	74.00	27.79	H
4881.500	42.36	-36.90	33.40	45.86	74.00	31.64	H

$\pi/4$ DQPSK Ch 78

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17417.000	55.40	-27.30	43.80	38.90	74.00	18.60	H
13846.500	51.12	-28.90	41.20	38.82	74.00	22.88	H
12955.500	48.83	-29.70	40.00	38.43	74.00	25.17	V
9076.000	48.08	-33.60	37.70	43.98	74.00	25.92	V
7187.500	46.32	-34.50	36.20	44.62	74.00	27.68	V
2493.600	56.83	-19.00	28.20	47.63	74.00	17.17	V

8DPSK Ch 0

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17907.000	55.63	-25.90	46.00	35.53	74.00	18.37	H
13699.500	51.68	-29.30	41.00	39.98	74.00	22.32	H
11859.000	49.79	-31.10	39.10	41.79	74.00	24.21	V
9540.500	46.88	-33.10	37.60	42.38	74.00	27.12	H
7623.500	46.34	-34.70	36.30	44.74	74.00	27.66	V
2386.900	56.24	-19.20	28.20	47.24	74.00	17.76	V

8DPSK Ch 39

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17922.000	56.08	-25.90	46.00	35.98	74.00	17.92	V
13588.500	51.69	-29.80	40.80	40.69	74.00	22.31	V
12261.500	48.58	-30.40	39.00	40.08	74.00	25.42	V
9199.000	47.19	-33.80	37.70	43.29	74.00	26.81	H
7526.500	46.27	-34.80	36.30	44.77	74.00	27.73	V
4882.500	41.55	-36.90	33.40	45.05	74.00	32.45	H

8DPSK Ch 78

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17948.000	56.11	-25.90	46.00	36.01	74.00	17.89	H
14069.000	51.74	-29.10	41.70	39.14	74.00	22.26	H
12561.000	48.99	-30.40	39.20	40.19	74.00	25.01	V
8956.500	47.32	-33.60	37.70	43.22	74.00	26.68	V
7532.000	46.29	-34.80	36.30	44.79	74.00	27.71	H
2499.600	56.97	-19.00	28.20	47.77	74.00	17.03	V

Average Measurement results

GFSK Ch 0

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17893.000	46.28	-25.90	46.00	26.18	54.00	7.72	H
14088.000	42.04	-29.10	41.70	29.44	54.00	11.96	V
4803.500	41.65	-36.90	33.00	45.55	54.00	12.35	H
12832.500	39.69	-30.30	39.90	30.09	54.00	14.31	H
9081.000	36.92	-33.60	37.70	32.82	54.00	17.08	H
2361.200	44.28	-19.30	28.20	35.38	54.00	9.72	H

GFSK Ch 39

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17924.500	46.61	-25.90	46.00	26.51	54.00	7.39	V
14116.500	41.61	-29.40	41.70	29.31	54.00	12.39	V
12841.000	39.44	-30.30	39.90	29.84	54.00	14.56	V
9611.500	37.21	-33.00	37.60	32.61	54.00	16.79	H
7436.500	36.31	-34.50	36.50	34.31	54.00	17.69	V
4882.000	35.81	-36.90	33.40	39.31	54.00	18.19	H

GFSK Ch 78

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17913.500	46.34	-25.90	46.00	26.24	54.00	7.66	H
13802.500	42.28	-29.00	41.20	30.08	54.00	11.72	H
12837.500	39.32	-30.30	39.90	29.72	54.00	14.68	V
4960.000	39.22	-36.80	33.60	42.42	54.00	14.78	H
9054.500	37.13	-33.50	37.80	32.83	54.00	16.87	H
2496.900	45.00	-19.00	28.20	35.80	54.00	9.00	H

$\pi/4$ DQPSK Ch 0

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17920.000	46.28	-25.90	46.00	26.18	54.00	7.72	V
4803.500	42.13	-36.90	33.00	46.03	54.00	11.87	H
13824.500	41.97	-28.90	41.20	29.67	54.00	12.03	V
12979.500	39.29	-29.40	40.10	28.59	54.00	14.71	V
8525.500	37.06	-33.80	37.40	33.46	54.00	16.94	H
2373.600	44.31	-19.30	28.20	35.41	54.00	9.69	V

$\pi/4$ DQPSK Ch 39

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17918.500	46.25	-25.90	46.00	26.15	54.00	7.75	H
13712.000	41.76	-29.30	41.00	30.06	54.00	12.24	H
12401.500	38.97	-30.10	38.90	30.17	54.00	15.03	H
9426.500	37.35	-33.50	37.90	32.95	54.00	16.65	H
7526.500	37.10	-34.80	36.30	35.60	54.00	16.90	H
4881.500	35.85	-36.90	33.40	39.35	54.00	18.15	H

$\pi/4$ DQPSK Ch 78

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17893.500	46.39	-25.90	46.00	26.29	54.00	7.61	H
4960.000	42.35	-36.80	33.60	45.55	54.00	11.65	H
13789.000	41.82	-29.00	41.20	29.62	54.00	12.18	H
12983.500	39.03	-29.40	40.10	28.33	54.00	14.97	V
9814.500	37.17	-33.10	37.90	32.37	54.00	16.83	H
2485.800	44.77	-19.00	28.20	35.57	54.00	9.23	H

8DPSK Ch 0

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17932.000	46.59	-25.90	46.00	26.49	54.00	7.41	V
14125.500	41.63	-29.40	41.70	29.33	54.00	12.37	H
4804.000	39.68	-36.90	33.00	43.58	54.00	14.32	H
12400.500	39.41	-30.10	38.90	30.61	54.00	14.59	V
9626.500	37.30	-33.00	37.60	32.70	54.00	16.70	H
2385.000	44.54	-19.20	28.20	35.54	54.00	9.46	H

8DPSK Ch 39

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17905.500	46.41	-25.90	46.00	26.31	54.00	7.59	H
13834.000	42.18	-28.90	41.20	29.88	54.00	11.82	V
12384.000	39.16	-30.10	38.90	30.36	54.00	14.84	V
9721.000	37.26	-33.10	37.80	32.56	54.00	16.74	H
7433.500	36.77	-34.50	36.50	34.77	54.00	17.23	H
4882.000	36.30	-36.90	33.40	39.80	54.00	17.70	H

8DPSK Ch 78

Frequency (MHz)	Measurement Result (dBuV/m)	Cable Loss (dB)	Antenna Factor (dB/m)	Receiver Reading (dBuV)	Limit (dBuV/m)	Margin (dB)	Antenna Pol. (H/V)
17967.500	46.22	-25.90	46.00	26.12	54.00	7.78	H
13813.000	41.66	-28.90	41.20	29.36	54.00	12.34	H
4960.000	40.23	-36.80	33.60	43.43	54.00	13.77	H
12988.000	39.19	-29.40	40.10	28.49	54.00	14.81	V
9929.000	37.42	-33.30	37.90	32.82	54.00	16.58	V
2499.800	44.76	-19.00	28.20	35.56	54.00	9.24	V

Conclusion: Pass

Note: the spurious emission above 18G is noise only and did not show on the report.

Band edge compliance

Mode	Channel	Frequency Range	Test Results	Conclusion
GFSK	0	2.31GHz ~2.43GHz	Fig.67	P
	78	2.45GHz ~2.5GHz	Fig.68	P

Mode	Channel	Frequency Range	Test Results	Conclusion
$\pi/4$ DQPSK	0	2.31GHz ~2.43GHz	Fig.69	P
	78	2.45GHz ~2.5GHz	Fig.70	P

Mode	Channel	Frequency Range	Test Results	Conclusion
8DPSK	0	2.31GHz ~2.43GHz	Fig.71	P
	78	2.45GHz ~2.5GHz	Fig.72	P

Conclusion: PASS

Test graphs as below




Fig.67. Frequency Band Edges: GFSK, Channel 0, Hopping Off, 2.31 GHz – 2.45GHz




Fig.68. Frequency Band Edges: GFSK, Channel 78, Hopping Off, ch11, 2.45 GHz - 2.50GHz




Fig.69. Frequency Band Edges: $\pi/4$ DQPSK, Channel 0, Hopping Off, 2.31 GHz - 2.45GHz




Fig.70. Frequency Band Edges: $\pi/4$ DQPSK, Channel 78, Hopping Off, 2.45 GHz - 2.50GHz




Fig.71. Frequency Band Edges: 8DPSK, Channel 0, 2.31 GHz - 2.45GHz




Fig.72. Frequency Band Edges: 8DPSK, Channel 78, 2.45 GHz - 2.50GHz

B.6. Time of Occupancy (Dwell Time)

Method of Measurement: See ANSI C63.10-clause 7.8.4

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

- Span = zero span, centered on a hopping channel
- RBW = 1 MHz
- VBW $\geq$ RBW
- Sweep = as necessary to capture the entire dwell time per hopping channel
- Detector function = peak
- Trace = max hold

Measure a pulse time in time domain at middle frequency and then count the hopping number in 31.6s(which equals with 0.4 multiply 79) of middle frequency ,then multiply the pulse time and hopping number and record them.

Measurement Limit:

Standard	Limit (ms)
FCC 47 CFR Part 15.247(a) (1)(iii)	< 400

Measurement Result:

For GFSK

Channel	Packet	Pulse time (ms)		Number of Transmissions		Dwell Time (ms)	Conclusion
39	DH1	Fig.73	0.37	Fig.74	320	118.4	P
	DH3	Fig.75	1.63	Fig.76	110	179.3	P
	DH5	Fig.77	2.88	Fig.78	59	169.92	P

For $\pi/4$ DQPSK

Channel	Packet	Pulse time (ms)		Number of Transmissions		Dwell Time (ms)	Conclusion
39	2DH1	Fig.79	0.38	Fig.80	321	121.98	P
	2DH3	Fig.81	1.63	Fig.82	102	166.26	P
	2DH5	Fig.83	2.88	Fig.84	64	184.32	P

For 8DPSK

Channel	Packet	Pulse time (ms)		Number of Transmissions		Dwell Time (ms)	Conclusion
39	3DH1	Fig.85	0.38	Fig.86	320	121.6	P
	3DH3	Fig.87	1.63	Fig.88	102	166.26	P
	3DH5	Fig.89	2.88	Fig.90	64	184.32	P

Conclusion: PASS

Test graphs as below:




Fig.73. Time of occupancy (Dwell Time): Channel 39, Packet DH1




Fig.74. Number of Transmissions Measurement:Channel 39,Packet DH1




Fig.75. Time of occupancy (Dwell Time): Channel 39, Packet DH3




Fig.76. Number of Transmissions Measurement:Channel 39,Packet DH3




Fig.77. Time of occupancy (Dwell Time): Channel 39, Packet DH5




Fig.78. Number of Transmissions Measurement:Channel 39,Packet DH5




Fig.79. Time of occupancy (Dwell Time): Channel 39, Packet 2-DH1




Fig.80. Number of Transmissions Measurement:Channel 39,Packet 2-DH1




Fig.81. Time of occupancy (Dwell Time): Channel 39, Packet 2-DH3




Fig.82. Number of Transmissions Measurement:Channel 39,Packet 2-DH3




Fig.83. Time of occupancy (Dwell Time): Channel 39, Packet 2-DH5




Fig.84. Number of Transmissions Measurement: Channel 39, Packet 2-DH5




Fig.85. Time of occupancy (Dwell Time): Channel 39, Packet 3-DH1




Fig.86. Number of Transmissions Measurement:Channel 39,Packet 3-DH1




Fig.87. Time of occupancy (Dwell Time): Channel 39, Packet 3-DH3




Fig.88. Number of Transmissions Measurement:Channel 39,Packet 3-DH3




Fig.89. Time of occupancy (Dwell Time): Channel 39, Packet 3-DH5




Fig.90. Number of Transmissions Measurement:Channel 39,Packet 3-DH5

B.7. 20dB Bandwidth

Method of Measurement: See ANSI C63.10-clause 6.9.2

Measurement Procedure - Unwanted Emissions

1. Set RBW = 30kHz.
2. Set VBW = 100 kHz.
3. Set span to 3MHz
4. Detector = peak.
5. Trace Mode = max hold.
6. Sweep = auto couple.
7. Allow the trace to stabilize (this may take some time, depending on the extent of the span).

Measurement Limit:

Standard	Limit
FCC 47 CFR Part 15.247(a)(1)	NA *

Use NdB Down function of the SA to measure the 20dB Bandwidth

* Comment: This test case is not required according to the latest FCC 47 CFR Part 15.247. But the test results are necessary for “carrier frequency separation” test case, in Annex A.8.

Measurement Results:

For GFSK

Channel	20dB Bandwidth (kHz)		Conclusion
0	Fig.91	943.50	NA
39	Fig.92	939.75	NA
78	Fig.93	942.75	NA

For $\pi/4$ DQPSK

Channel	20dB Bandwidth (kHz)		Conclusion
0	Fig.94	1257.00	NA
39	Fig.95	1208.25	NA
78	Fig.96	1254.75	NA

For 8DPSK

Channel	20dB Bandwidth (kHz)		Conclusion
0	Fig.97	1200.75	NA
39	Fig.98	1200.75	NA
78	Fig.99	1252.50	NA

Conclusion: NA

Test graphs as below:




Fig.91. 20dB Bandwidth: GFSK, Channel 0




Fig.92. 20dB Bandwidth: GFSK, Channel 39




Fig.93. 20dB Bandwidth: GFSK, Channel 78






Fig.94. 20dB Bandwidth: $\pi/4$ DQPSK, Channel 0


Fig.95. 20dB Bandwidth: $\pi/4$ DQPSK, Channel 39

Fig.96. 20dB Bandwidth: $\pi/4$ DQPSK, Channel 78




Fig.97. 20dB Bandwidth: 8DPSK, Channel 0




Fig.98. 20dB Bandwidth: 8DPSK, Channel 39




Fig.99. 20dB Bandwidth: 8DPSK, Channel 78

B.8. Carrier Frequency Separation

Method of Measurement: See ANSI C63.10-clause 7.8.2

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

- Span = 3MHz
- RBW=300kHz
- VBW=300kHz
- Sweep = auto
- Detector function = peak
- Trace = max hold
- Allow the trace to stabilize

Search the peak marks of the middle frequency and adjacent channel, then record the separation between them.

* Comment: This limit should be over 25 kHz or $(2/3) * 20\text{dB}$ bandwidth, whichever is greater.

Measurement Limit:

Standard	Limit(kHz)
FCC 47 CFR Part 15.247(a)(1)	over 25 kHz or $(2/3) * 20\text{dB}$ bandwidth

Measurement Result:

For GFSK

Channel	Carrier frequency separation (kHz)		Conclusion
39	Fig.100	1133.25	P

For $\pi/4$ DQPSK

Channel	Carrier frequency separation (kHz)		Conclusion
39	Fig.101	1029.75	P

For 8DPSK

Channel	Carrier frequency separation (kHz)		Conclusion
39	Fig.102	1110.00	P

Conclusion: PASS

Test graphs as below:




Fig.100. Carrier frequency separation measurement: GFSK, Channel 39




Fig.101. Carrier frequency separation measurement: $\pi/4$ DQPSK, Channel 39