

FCC TEST REPORT

(Part 15, Subpart C)

Applicant:	Xiaomi Communications Co., Ltd.
Address:	#019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085


Manufacturer or Supplier:	Xiaomi Communications Co., Ltd.
Address:	#019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085
Product:	Tablet Computer
Brand Name:	Redmi
Model Name:	25099RP13G
FCC ID:	2AFZZRP13G
Date of tests:	Jul. 28, 2025 ~ Jul. 31, 2025

The tests have been carried out according to the requirements of the following standard:

☒ FCC Part 15, Subpart C, Section 15.247

☒ ANSI C63.10-2020

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Prepared by Hanwen Xu Engineer / Mobile Department	Approved by Peibo Sun Manager / Mobile Department
	
Date: Jul. 31, 2025	Date: Jul. 31, 2025

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

TABLE OF CONTENTS

RELEASE CONTROL RECORD	6
1. SUMMARY OF TEST RESULTS.....	7
1.1 MEASUREMENT UNCERTAINTY	8
2 GENERAL INFORMATION	9
2.2 GENERAL DESCRIPTION OF EUT	9
2.3 DESCRIPTION OF TEST MODES	11
2.2.1 CONFIGURATION OF SYSTEM UNDER TEST	12
2.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL.....	12
2.4 DUTY CYCLE OF TEST SIGNAL	16
2.5 GENERAL DESCRIPTION OF APPLIED STANDARDS	16
2.6 DESCRIPTION OF SUPPORT UNITS	17
3 TEST TYPES AND RESULTS.....	18
3.1 CONDUCTED EMISSION MEASUREMENT	18
3.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT	18
3.1.2 TEST INSTRUMENTS.....	19
3.1.3 TEST PROCEDURES	20
3.1.4 DEVIATION FROM TEST STANDARD	20
3.1.5 TEST SETUP	21
3.1.6 EUT OPERATING CONDITIONS	21
3.1.7 TEST RESULTS	22
3.2 RADIATED EMISSION MEASUREMENT	24
3.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT	24
3.2.2 TEST INSTRUMENTS.....	25
3.2.3 TEST PROCEDURES	27
3.2.4 DEVIATION FROM TEST STANDARD	27
3.2.5 TEST SETUP	28
3.2.6 EUT OPERATING CONDITIONS	29
3.2.7 TEST RESULTS	30
3.3 6 DB BANDWIDTH MEASUREMENT	224
3.3.1 LIMITS OF 6DB BANDWIDTH MEASUREMENT	224
3.3.2 TEST INSTRUMENTS.....	224
3.3.3 TEST PROCEDURE.....	225
3.3.4 DEVIATION FROM TEST STANDARD	226
3.3.5 TEST SETUP	226
3.3.6 EUT OPERATING CONDITIONS	226
3.3.7 TEST RESULTS	226
3.4 CONDUCTED OUTPUT POWER	227



3.4.1	LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT	227
3.4.2	TEST SETUP	227
3.4.3	TEST INSTRUMENTS.....	227
3.4.4	TEST PROCEDURES	227
3.4.5	DEVIATION FROM TEST STANDARD	227
3.4.6	EUT OPERATING CONDITIONS	227
3.4.7	TEST RESULTS	228
3.4.7.1	MAXIMUM PEAK OUTPUT POWER	228
3.4.7.2	AVERAGE OUTPUT POWER (FOR REFERENCE).....	229
3.5	POWER SPECTRAL DENSITY MEASUREMENT	230
3.5.1	LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT	230
3.5.2	TEST SETUP	230
3.5.3	TEST INSTRUMENTS.....	230
3.5.4	TEST PROCEDURE.....	230
3.5.5	DEVIATION FROM TEST STANDARD	230
3.5.6	EUT OPERATING CONDITION	230
3.5.7	TEST RESULTS	231
3.6	OUT OF BAND EMISSION MEASUREMENT	232
3.6.1	LIMITS OF OUT OF BAND EMISSION MEASUREMENT	232
3.6.2	TEST SETUP	232
3.6.3	TEST INSTRUMENTS.....	232
3.6.4	TEST PROCEDURE.....	232
3.6.5	DEVIATION FROM TEST STANDARD	233
3.6.6	EUT OPERATING CONDITION	233
3.6.7	TEST RESULTS	233
3.7	ANTENNA REQUIREMENTS	234
3.7.1	STANDARD APPLICABLE	234
3.7.2	ANTENNA CONNECTED CONSTRUCTION	234
3.7.3	ANTENNA GAIN	234
4	PHOTOGRAPHS OF THE TEST CONFIGURATION	235
5	MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB	236
6	APPENDIX A:WIFI	237
	DTS BANDWIDTH	237
	TEST RESULT	237
	TEST GRAPHS.....	239
	OCCUPIED CHANNEL BANDWIDTH	245
	TEST RESULT	245



TEST GRAPHS.....	247
MAXIMUM CONDUCTED OUTPUT POWER	253
TEST RESULT PEAK	253
TEST RESULT AVERAGE	256
MAXIMUM POWER SPECTRAL DENSITY	259
TEST RESULT	259
TEST GRAPHS.....	261
BAND EDGE MEASUREMENTS	267
TEST RESULT	267
TEST GRAPHS.....	269
CONDUCTED SPURIOUS EMISSION.....	273
TEST RESULT	273
TEST GRAPHS.....	277
DUTY CYCLE	295
TEST RESULT	295
TEST GRAPHS.....	296
7 APPENDIX B:BLE.....	306
DTS BANDWIDTH	306
TEST RESULT	306
TEST GRAPHS.....	307
OCCUPIED CHANNEL BANDWIDTH	315
TEST RESULT	315
TEST GRAPHS.....	316
MAXIMUM CONDUCTED OUTPUT POWER	324
TEST RESULT PEAK	324
TEST RESULT AVERAGE	325
MAXIMUM POWER SPECTRAL DENSITY	326
TEST RESULT	326
TEST GRAPHS.....	327
BAND EDGE MEASUREMENTS	335
TEST RESULT	335
TEST GRAPHS.....	336
CONDUCTED SPURIOUS EMISSION.....	342
TEST RESULT	342
TEST GRAPHS.....	345
DUTY CYCLE	369
TEST RESULT	369
TEST GRAPHS.....	370



8	APPENDIX C: RU WLAN.....	378
	DTS BANDWIDTH	378
	TEST RESULT	378
	TEST GRAPHS.....	380
	OCCUPIED CHANNEL BANDWIDTH	383
	TEST RESULT	383
	TEST GRAPHS.....	385
	MAXIMUM CONDUCTED OUTPUT POWER	388
	MAXIMUM POWER SPECTRAL DENSITY	389
	TEST RESULT	389
	TEST GRAPHS.....	390
	BAND EDGE MEASUREMENTS	393
	TEST RESULT	393
	TEST GRAPHS.....	393
	CONDUCTED SPURIOUS EMISSION.....	396
	TEST RESULT	396
	TEST GRAPHS.....	399
	DUTY CYCLE	410
	TEST RESULT	410
	TEST GRAPHS.....	411



RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
PSU-QBJ2507100110RF02	Original release	Jul. 31, 2025



1. SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC PART 15, SUBPART C (SECTION 15.247)			
STANDARD SECTION	TEST TYPE AND LIMIT	RESULT	TEST LAB*
15.207	AC Power Conducted Emission	Compliance	A
15.205 15.209	Radiated Emissions	Compliance	A
15.247(d)	Out of band Emission Measurement	Compliance	A
15.247(a)(2)	6dB bandwidth	Compliance	A
15.247(b)	Conducted Output power	Compliance	A
15.247(e)	Power Spectral Density	Compliance	A
15.203	Antenna Requirement	Compliance	A

Note : Except RSE and AC Power Conducted Emission, other data please refer to Appendix B.

*Test Lab Information Reference

Lab A:

Huarui 7Layers High Technology (Suzhou) Co., Ltd.

Lab Address:

Tower N, Innovation Center, 88 Zuyi Road, High-tech District, Suzhou City, Anhui Province, China

Accredited Test Lab Cert 6613.01

The FCC Site Registration No. is 434559; The Designation No. is CN1325.




1.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	UNCERTAINTY
AC Power Conducted emissions	$\pm 2.70\text{dB}$
Radiated emissions (9KHz~30MHz)	$\pm 2.68\text{dB}$
Radiated emissions (30MHz~1GHz)	$\pm 4.98\text{dB}$
Radiated emissions (1GHz ~6GHz)	$\pm 4.70\text{dB}$
Radiated emissions (6GHz ~18GHz)	$\pm 4.60\text{dB}$
Radiated emissions (18GHz ~40GHz)	$\pm 4.12\text{dB}$
Conducted emissions	$\pm 4.01\text{dB}$
Occupied Channel Bandwidth	$\pm 43.58\text{KHz}$
Conducted Output power	$\pm 2.06\text{dB}$
Power Spectral Density	$\pm 0.85\text{ dB}$

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k = 2$.



The verdicts in this test report are given according the above diagram:

Case	Measured Value	Uncertainty Range	Verdict
1	below pass mark	below pass mark	Passed
2	below pass mark	within pass mark	Passed
3	above pass mark	within pass mark	Failed
4	above pass mark	above pass mark	Failed

That means, the laboratory applies, as decision rule (see ISO/IEC 17025:2017), the so-called shared risk principle.



2 GENERAL INFORMATION

2.2 GENERAL DESCRIPTION OF EUT

PRODUCT*	Tablet Computer	
BRAND NAME*	Redmi	
MODEL NAME*	25099RP13G	
NOMINAL VOLTAGE*	5/3.6-11Vdc(adapter or host equipment) 3.91Vdc(Li-ion,battery)	
MODULATION *	BLE	GFSK
	2.4G WIFI	DSSS,OFDM,OFDMA
TRANSMISSION RATE*	BT_LE: 0.125 Mbps /0.5 Mbps /1 Mbps/2 Mbps	
	802.11b: 11/5.5/2.0/1.0 Mbps	
	802.11g: 54/48/36/24/18/9/6 Mbps	
	802.11n(HT20)/802.11ac(HT20)/ax(HE20): up to 144.4 Mbps	
	802.11n(HT40)/ 802.11ac(HT40)/ax(HE40): up to 300 Mbps	
OPERATING FREQUENCY	2412-2462MHz for 11b/g/n(HT20) /ax(HE20)/ ax(20/40M RU26/52/106) 2402-2480MHz for BT-LE(GFSK) 2422-2452MHz for 11n(HT40) /ax(HE40)	
MAX. OUTPUT POWER	BT-LE: 4.21mW (Maximum)	
	WLAN: 765.60mW (Maximum)	
	RU WLAN: 766.31mW (Maximum)	
ANTENNA GAIN*	BLE	ANT 7 :1.6dBi ANT 10 :1.6dBi
	2.4G WIFI	ANT 7 :-2.68dBi ANT 10 :1.60dBi
ANTENNA TYPE*	BLE	ANT 7 : PIFA Antenna ANT 10 : PIFA Antenna
	2.4G WIFI	ANT 7 : PIFA Antenna ANT 10 : PIFA Antenna
HW VERSION*	135700P83	
SW VERSION*	Xiaomi HyperOS 2.0	
I/O PORTS*	Refer to user's manual	
CABLE SUPPLIED*	USB cable1: non-shielded cable, with w/o ferrite core, 1.0 meter USB cable2: non-shielded cable, with w/o ferrite core, 1.0 meter USB cable3: non-shielded cable, with w/o ferrite core, 1.0 meter USB cable4: non-shielded cable, with w/o ferrite core, 1.0 meter	

**NOTE:**

1. *Since the above data and/or information is provided by the client relevant results or conclusions of this report are only made for these data and/or information, Test Lab is not responsible for the authenticity, integrity and results of the data and information and/or the validity of the conclusion.
2. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
3. The EUT incorporates a MIMO function. Physically, the EUT provides two completed transmitter and two receiver.

MODULATION MODE	TX/RX FUNCTION
802.11b	2TX/2RX
802.11g	2TX/2RX
802.11n(HT20)/11ax(HE20)/11ac(HE20)/ax(20M RU26/52/106)	2TX/2RX
802.11n(HT40)/11ax(HE40)/11ac(HE20)	2TX/2RX
BT_LE(1MHz)	2TX/2RX
BT_LE(2MHz)	2TX/2RX
BT_LE(S2)	2TX/2RX
BT_LE(S8)	2TX/2RX

4. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.
5. Antenna gain and EUT conducted cable loss are provided by the customer, and the laboratory will record the results based on these items that involve these two parameters.

2.3 DESCRIPTION OF TEST MODES

11 Channels are provided for 802.11b, 802.11g and 802.11n20 (HT20),802.11ax20 (HE20),802.11ax20(RU 26/52/106):

802.11b/802.11g/802.11n20 (HT20)/802.11ax20 (HE20)			
CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
1	2412 MHz	7	2442 MHz
2	2417 MHz	8	2447 MHz
3	2422 MHz	9	2452 MHz
4	2427 MHz	10	2457 MHz
5	2432 MHz	11	2462 MHz
6	2437 MHz		

802.11n40 (HT40)/ 802.11ax40 (HE40)			
CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
3	2422 MHz	7	2442 MHz
4	2427 MHz	8	2447 MHz
5	2432 MHz	9	2452 MHz
6	2437 MHz		

BT-LE							
CHANNEL	FREQ. (MHZ)	CHANNEL	FREQ. (MHZ)	CHANNEL	FREQ. (MHZ)	CHANNEL	FREQ. (MHZ)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480



2.2.1 CONFIGURATION OF SYSTEM UNDER TEST

Please see section 4 photographs of the test configuration for reference.

2.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports.
The worst case was found when positioned on Y axis for radiated emission. Following test modes were selected for the final test, and the final worst case is marked in boldface and recorded in the report:

EUT CONFIGURE MODE	APPLICABLE TO				MODE
	RE<1G	RE≥1G	PLC	APCM	
-	√	√	√	√	-

Where **RE<1G**: Radiated Emission below 1GHz

RE≥1G: Radiated Emission above 1GHz

PLC: Power Line Conducted Emission

APCM: Antenna Port Conducted Measurement

NOTE: No need to concern of Conducted Emission due to the EUT is powered by battery.

RADIATED EMISSION TEST (BELOW 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ The following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	DATA RATE (Mbps)
802.11ax(20 RU26)	1 to 11	6	OFDM	MCS0
BT-LE	0 to 39	19	GFSK	0.5



RADIATED EMISSION TEST (ABOVE 1GHz):

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ The following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	1.0
802.11g	1 to 11	1, 6, 11	OFDM	6.0
802.11n20(HT20)	1 to 11	1, 6, 11	OFDM	MCS0
802.11ax20(HE20)	1 to 11	1, 6, 11	OFDMA	MCS0
802.11ax20(HE20 RU26/52/106)	1 to 11	1, 6, 11	OFDMA	MCS0
802.11n(HT40)	3 to 9	3,6,9	OFDM	MCS0
802.11ax(HE40)	3 to 9	3,6,9	OFDMA	MCS0
BT-LE	0 to 39	0,19, 39	GFSK	0.125&0.5&1.0
BT-LE	1 to 38	1,19, 38	GFSK	2.0

POWER LINE CONDUCTED EMISSION TEST

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ The following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	DATA RATE (Mbps)
802.11n20	1 to 11	6	OFDM	MCS0



BANDEDGE MEASUREMENT:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ The following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	1.0
802.11g	1 to 11	1, 6, 11	OFDM	6.0
802.11n20(HT20)	1 to 11	1, 6, 11	OFDM	MCS0
802.11ax20(HE20)	1 to 11	1, 6, 11	OFDMA	MCS0
802.11ax20(HE20 RU26/52/106)	1 to 11	1, 6, 11	OFDMA	MCS0
802.11n(HT40)	3 to 9	3,6,9	OFDM	MCS0
802.11ax(HE40)	3 to 9	3,6,9	OFDMA	MCS0
BT-LE	0 to 39	0,19, 39	GFSK	0.125&0.5&1.0
BT-LE	1 to 38	1,19, 38	GFSK	2.0



ANTENNA PORT CONDUCTED MEASUREMENT:

- ☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ The following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	1.0
802.11g	1 to 11	1, 6, 11	OFDM	6.0
802.11n20(HT20)	1 to 11	1, 6, 11	OFDM	MCS0
802.11ax20(HE20)	1 to 11	1, 6, 11	OFDMA	MCS0
802.11ax20(HE20 RU26/52/106)	1 to 11	1, 6, 11	OFDMA	MCS0
802.11n(HT40)	3 to 9	3,6,9	OFDM	MCS0
802.11ax(HE40)	3 to 9	3,6,9	OFDMA	MCS0
BT-LE	0 to 39	0,19, 39	GFSK	0.125&0.5&1.0
BT-LE	1 to 38	1,19, 38	GFSK	2.0

TEST CONDITION			
APPLICABLE TO	ENVIRONMENTAL CONDITIONS	TEST VOLTAGE	TESTED BY
RE<1G	23deg. C, 70%RH	DC 3.8V By Adapter	Hanwen Xu
RE≥1G	23deg. C, 70%RH	DC 3.8V By Adapter	Hanwen Xu
PLC	25deg. C, 52%RH	DC 3.8V By Adapter	Hanwen Xu
APCM	25deg. C, 60%RH	DC 3.8V By Adapter	Hanwen Xu

2.4 DUTY CYCLE OF TEST SIGNAL

Please Refer to Appendix B Of this test report..

2.5 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C, Section 15.247

KDB 558074 D01 DTS Meas Guidance v05r02

ANSI C63.10-2020

Note :

1. All test items have been performed and recorded as per the above standards.
2. The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (Certification). The test report has been issued separately.



2.6 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	Laptop	Lenovo	Thinkpad E14	SL10W47313	N/A
2	Adapter	N/A	N/A	N/A	N/A
3	Mouse	Lenovo	DOK M689E	N/A	N/A
4	Earphone	MI	N/A	N/A	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	AC Line: Unshielded, Detachable 1.5m
2	USB Line: Unshielded, Detachable, 1.0m;



3 TEST TYPES AND RESULTS

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB μ V)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.
3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.



3.1.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
WIDEBANDRADIO COMMUNICATION TESTER	Rohde&Schwarz	CMW500	169399	Jun.19,24	Jun.18,26
EMI Test Receiver	Rohde&Schwarz	ESR3	102749	Mar.28,24	Mar.27,26
ELEKTRA test software	Rohde&Schwarz	ELEKTRA	NA	N/A	N/A
LISN network	Rohde&Schwarz	ENV216	102640	Mar.29,24	Mar.28,26
CABLE	Rohde&Schwarz	W61.01	N/A	Apr.26,25	Apr.25,26
CABLE	Rohde&Schwarz	W601	N/A	Apr.26,25	Apr.25,26

NOTE:

1. The test was performed in CE shielded room.
2. The calibration interval of the above test instruments is 12/24 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.



3.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.


NOTE: All modes of operation were investigated and the worst-case emissions are reported.

3.1.4 DEVIATION FROM TEST STANDARD

No deviation.



3.1.5 TEST SETUP



Note: 1.Support units were connected to second LISN.
2.Both of LISNs (AMN) are 80 cm from EUT and at least 80
from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

3.1.6 EUT OPERATING CONDITIONS

- a. Turned on the power and connected of all equipment.
- b. EUT was operated according to the type used was description in manufacturer's specifications or the User's Manual.



3.1.7 TEST RESULTS

CONDUCTED WORST-CASE DATA										
Frequency Range	150KHz ~ 30MHz					Detector Function & Resolution Bandwidth		Quasi-Peak (QP) / Average (AV), 9 kHz		
Input Power	120Vac, 60Hz					Environmental Conditions		26deg. C, 51%RH		
Tested By	Hanwen Xu									

Rg	Frequency [MHz]	QPK Level [dBμV]	QPK Limit [dBμV]	QPK Margin [dB]	CAV Level [dBμV]	CAV: AVG Limit [dBμV]	CAV Margin [dB]	Correction [dB]	Line	Meas. BW [kHz]
1	0.186	38.78	64.21	25.43	26.45	54.21	27.76	9.79	L1	9.000
1	0.438	39.80	57.10	17.30	33.94	47.10	13.16	9.75	L1	9.000
1	1.581	19.63	56.00	36.37	9.47	46.00	36.53	9.79	L1	9.000
1	4.227	25.47	56.00	30.53	18.20	46.00	27.80	10.06	L1	9.000
1	12.228	39.14	60.00	20.86	32.85	50.00	17.15	11.55	L1	9.000
1	27.690	37.87	60.00	22.13	28.65	50.00	21.35	14.44	L1	9.000

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.

2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.

3. The emission levels of other frequencies were very low against the limit.

4. Margin value = Limit value -Emission level

5. Correction factor = Insertion loss + Cable loss

6. Emission Level = Correction Factor + Reading Value.

Level in dBμV

70

67.5

65

62.5

60

57.5

55

52.5

50

47.5

45

42.5

40

37.5

35

32.5

30

27.5

25

22.5

20

17.5

15

12.5

10

7.5

5

2.5

0

150 k

200 k

300 k

400 k

500 k

600 k

800 k

1 M

2 M

3 M

4 M

5 M

6 M

7 M

8 M

10 M

20 M

30 M

Frequency in Hz

AVG Level @Spectrum Overview

◇ CAV Level @Final Results

PK+ Level @Spectrum Overview

◇ QPK Level @Final Results

AVG Limit @FCC Part 15 Voltage Mains Class B

◇ QPK Limit @FCC Part 15 Voltage Mains Class B



Frequency Range		150KHz ~ 30MHz				Detector Function & Resolution Bandwidth		Quasi-Peak (QP) / Average (AV), 9 kHz		
Input Power		120Vac, 60Hz				Environmental Conditions		26deg. C, 51%RH		
Tested By		Hanwen Xu								
Rg	Frequency [MHz]	QPK Level [dBμV]	QPK Limit [dBμV]	QPK Margin [dB]	CAV Level [dBμV]	CAV: AVG Limit [dBμV]	CAV Margin [dB]	Correction [dB]	Line	Meas. BW [kHz]
1	0.159	41.42	65.52	24.10	25.11	55.52	30.41	9.82	N	9.000
1	0.434	40.18	57.19	17.01	33.18	47.19	14.01	9.77	N	9.000
1	1.626	27.53	56.00	28.47	18.83	46.00	27.17	9.81	N	9.000
1	5.541	28.80	60.00	31.20	22.32	50.00	27.68	10.25	N	9.000
1	12.318	40.07	60.00	19.93	33.83	50.00	16.17	11.64	N	9.000
1	27.695	37.15	60.00	22.85	28.06	50.00	21.94	14.22	N	9.000

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Limit value -Emission level
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



**3.2 RADIATED EMISSION MEASUREMENT****3.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT**

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



3.2.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Pre-Amplifier	R&S	SCU18F1	100815	Aug.30,23	Aug.29,25
Pre-Amplifier	R&S	SCU08F1	101028	Jan.22,24	Jan.21,26
Signal Generator	R&S	SMB100A	182185	Mar.29,24	Mar.28,26
3m Fully-anechoic Chamber	TDK	9m*6m*6m	HRSW-SZ-EMC-01Chamber	Nov.25,22	Nov.24,25
3m Semi-anechoic Chamber	TDK	9m*6m*6m	HRSW-SZ-EMC-02Chamber	Nov.25,22	Nov.24,25
EMI TEST Receiver	R&S	ESW44	101973	Mar.28,24	Mar.27,26
Bilog Antenna	SCHWARZBECK	VULB 9163	1264	Dec.26,23	Dec.25,25
Horn Antenna	ETS-LINDGREN	3117	227836	Aug.22,23	Aug.21,25
Horn Antenna (18GHz-40GHz)	Steatite Q-par Antennas	QMS 00880	23486	Jul.15,24	Jul.14,26
Horn Antenna	Steatite Q-par Antennas	QMS 00208	23485	Aug.22,23	Aug.21,25
Loop Antenna	SCHWARZ	HFH2-Z2/Z2E	100976	Feb.22,25	Feb.21,27
WIDEBANDRADIO COMMUNICATION TESTER	R&S	CMW500	169399	Jun.19,24	Jun.18,26
Test Software	ELEKTRA	ELEKTRA4.32	N/A	N/A	N/A
Open Switch and Control Unit	R&S	OSP220	101964	N/A	N/A
DC Source	HYELEC	HY3010B	551016	Aug.31,23	Aug.30,25
Hygrothermograph	DELI	20210528	SZ014	Mar.18,25	Mar.17,27
6DB attenuator	Tonscend Technology Co., Ltd	N/A	23062787	N/A	N/A
PC	LENOVO	E14	HRSW0024	N/A	N/A
TMC-AMI18843A(CABLE)	R&S	HF290-NMNM-7.00M	N/A	N/A	N/A
TMC-AMI18843A(CABLE)	R&S	HF290-NMNM-4.00M	N/A	N/A	N/A
CABLE	R&S	W13.02	N/A	Apr.26,25	Apr.25,26



CABLE	R&S	W12.14	N/A	Apr.26,25	Apr.25,26
-------	-----	--------	-----	-----------	-----------

NOTE:

1. The calibration interval of the above test instruments is 12/ 24 / 36 months and the calibrations are traceable to CEPREI/CHINA, GREGT/CHINA and NIM/CHINA.
2. The test was performed in 3m Chamber.
3. The FCC Site Registration No. is 434559; The Designation No. is CN1325.



3.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters (for below 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, For battery operated equipment, the equipment tests shall be perform using fresh batteries. The turntable was rotated to maximize the emission level.

Note:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for RMS Average (Duty cycle < 98%) for Average detection (AV) at frequency above 1GHz, then the measurement results was added to a correction factor ($10 \log(1/\text{duty cycle})$).
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz.
5. All modes of operation were investigated and the worst-case emissions are reported.

3.2.4 DEVIATION FROM TEST STANDARD


No deviation




<Frequency Range 9KHz~30MHz >



< Frequency Range 30MHz~1GHz >



<Frequency Range above 1GHz>



Note: Above 1G is a directional antenna

Depends on the EUT height and the antenna 3dB beamwidth both, refer to section 7.3 of CISPR 16-2-3.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

3.2.6 EUT OPERATING CONDITIONS

- Set the EUT under full load condition and placed them on a testing table.
- Set the transmitter part of EUT under transmission condition continuously at specific channel frequency.
- The necessary accessories enable the EUT in full functions.



3.2.7 TEST RESULTS

BELOW 1GHz WORST-CASE DATA

NOTE: The 9K~30MHz amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required in the report.

802.11ax(20MHz RU26)


CHANNEL	TX Channel 6	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	QPK Level [dBμV/m]	QPK Limit [dBμV/m]	QPK Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]	Meas. BW [kHz]
1	37.324	29.98	40.00	10.02	-10.56	H	1	1.00	120.000
1	52.747	25.49	40.00	14.51	-8.98	H	301.7	1.00	120.000
1	109.637	16.95	43.50	26.55	-11.17	H	13.4	2.00	120.000
1	322.552	21.16	46.00	24.84	-6.39	H	301.7	1.00	120.000
1	456.024	20.03	46.00	25.97	-2.60	H	355.8	2.00	120.000
1	571.212	21.00	46.00	25.00	-2.77	H	4.2	1.00	120.000

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
2. Margin value = Limit value- Emission level.






CHANNEL		TX Channel 6		DETECTOR FUNCTION		Quasi-Peak (QP)			
FREQUENCY RANGE		30MHz ~ 1GHz							
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M									
Rg	Frequency [MHz]	QPK Level [dBμV/m]	QPK Limit [dBμV/m]	QPK Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]	Meas. BW [kHz]
1	33.783	25.05	40.00	14.95	-13.71	V	4.2	1.00	120.000
1	50.807	22.91	40.00	17.09	-10.01	V	172.6	1.00	120.000
1	86.503	18.32	40.00	21.68	-13.29	V	172.6	1.00	120.000
1	197.713	14.32	43.50	29.18	-10.65	V	4.2	1.00	120.000
1	361.934	17.73	46.00	28.27	-4.03	V	4.2	1.00	120.000
1	627.811	22.24	46.00	23.76	-2.07	V	355.2	2.00	120.000

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
2. Margin value = Limit value- Emission level.






ABOVE 1GHz WORST-CASE DATA

Note:

1. For radiated emissions testing, the full testing range of different modes have been scanned, only the worst case harmonic data is reported in the sheet.
2. All other emissions were greater than 20dB below the limit was not recorded





ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M


Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,389.665	43.21	54.00	10.79	37.09	H	40.2	1.00
1	2,390.000	43.20	54.00	10.80	37.10	H	40.2	1.00
1	2,411.418	98.42			37.39	H	40.2	1.00






ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M


Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,338.533	57.99	74.00	16.01	36.90	V	350.6	1.00
1	2,390.000	57.12	74.00	16.88	37.10	V	264.8	1.00
1	2,413.400	106.20			37.42	V	96.4	2.00





REMARKS:


1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
2. Margin value = Limit value- Emission level.
3. 2412MHz: Fundamental frequency.






ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	4,874.000	50.34	74.00	23.66	38.78	54.00	15.22	14.76	V	0.9	2.00
2	7,311.000	55.61	74.00	18.39	45.23	54.00	8.77	21.05	V	359.1	1.00



REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
2. Margin value = Limit value- Emission level.
3. 2437MHz: Fundamental frequency.





ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M


Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	2,462.680	97.59			37.83	H	348.6	1.00
2	2,483.500	43.49	54.00	10.51	37.88	H	41.4	1.00
2	2,487.520	44.45	54.00	9.55	37.89	H	41.4	1.00





ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M


Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	2,460.760	105.15			37.82	V	43.8	1.00
2	2,483.500	57.23	74.00	16.77	37.88	V	359	1.00
2	2,495.560	59.09	74.00	14.91	37.90	V	0.9	2.00






ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	2,462.680	101.96			37.83	V	172.8	1.00
2	2,483.500	43.90	54.00	10.10	37.88	V	140.6	2.00
2	2,487.640	44.58	54.00	9.42	37.89	V	96.5	2.00



REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
2. Margin value = Limit value- Emission level.
3. 2462MHz: Fundamental frequency.





ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M


Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,389.665	44.93	54.00	9.07	37.09	H	41.4	1.00
1	2,390.000	45.52	54.00	8.48	37.10	H	41.4	1.00
1	2,413.395	94.35			37.42	H	230.3	2.00





ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M


Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,389.383	59.30	74.00	14.70	37.09	V	54.4	2.00
1	2,390.000	59.42	74.00	14.58	37.10	V	144.1	2.00
1	2,410.850	109.37			37.38	V	276.8	2.00






ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,388.818	44.82	54.00	9.18	37.08	V	47.4	2.00
1	2,390.000	46.05	54.00	7.95	37.10	V	200.2	1.00
1	2,411.418	98.19			37.39	V	92.8	2.00



REMARKS:


1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
2. Margin value = Limit value- Emission level.
3. 2412MHz: Fundamental frequency.






ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	4,874.000	49.17	74.00	24.83	38.69	54.00	15.31	14.76	V	27.3	2.00
2	7,311.000	56.09	74.00	17.91	45.28	54.00	8.72	21.05	V	90.1	1.00



REMARKS:


1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor Margin value = Limit value- Emission level.
2. 2437MHz: Fundamental frequency.





ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M


Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	2,462.320	94.66			37.83	H	28.2	2.00
2	2,483.500	45.60	54.00	8.40	37.88	H	351.9	2.00
2	2,484.040	45.60	54.00	8.40	37.88	H	351.9	2.00





ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M


Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	2,460.880	109.80			37.82	V	219.4	1.00
2	2,483.500	62.38	74.00	11.62	37.88	V	276.8	2.00
2	2,484.640	62.89	74.00	11.11	37.88	V	276.8	2.00





ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	2,462.920	98.61			37.83	V	164.6	1.00
2	2,483.500	47.82	54.00	6.18	37.88	V	164.6	1.00
2	2,484.160	47.36	54.00	6.64	37.88	V	164.6	1.00



REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
2. Margin value = Limit value- Emission level.
3. 2462MHz: Fundamental frequency.




802.11n (20MHz)

CHANNEL	TX Channel 1	DETECTOR	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz	FUNCTION	Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,389.665	59.47	74.00	14.53	37.09	H	41.4	1.00
1	2,390.000	59.36	74.00	14.64	37.10	H	41.4	1.00
1	2,413.960	105.35			37.42	H	229.1	2.00





ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,389.665	45.99	54.00	8.01	37.09	H	40.2	1.00
1	2,390.000	46.32	54.00	7.68	37.10	H	40.2	1.00
1	2,414.243	93.60			37.43	H	229.1	2.00

