



FCC TEST REPORT (Part 15, Subpart E)

Applicant:	Xiaomi Communications Co., Ltd.
Address:	#019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085

Manufacturer or Supplier:	Xiaomi Communications Co., Ltd.
Address:	#019, 9th Floor, Building 6, 33 Xi'erqi Middle Road, Haidian District, Beijing, China, 100085
Product:	Tablet Computer
Brand Name:	POCO
Model Name:	2509ARPDG
FCC ID:	2AFZZRPBDG
Date of tests:	Jul. 28, 2025 ~ Jul. 31, 2025

The tests have been carried out according to the requirements of the following standard:

FCC Part 15, Subpart E, Section 15.407

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Prepared by Hanwen Xu Engineer / Mobile Department	Approved by Peibo Sun Manager / Mobile Department
Date: Jul. 31, 2025	Date: Jul. 31, 2025

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report included all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.



TABLE OF CONTENTS

RELEASE CONTROL RECORD 4

1 SUMMARY OF TEST RESULTS 5

1.1 MEASUREMENT UNCERTAINTY 6

2 GENERAL INFORMATION 7

2.1 GENERAL DESCRIPTION OF EUT 7

2.2 DESCRIPTION OF TEST MODES 10

2.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL 13

2.3 DUTY CYCLE OF TEST SIGNAL 17

2.4 DESCRIPTION OF SUPPORT UNITS 18

2.4.1 CONFIGURATION OF SYSTEM UNDER TEST 19

2.5 GENERAL DESCRIPTION OF APPLIED STANDARDS 20

3 TEST TYPES AND RESULTS 21

3.1 RADIATED EMISSION AND BANDEDGE MEASUREMENT 21

3.1.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT 21

3.1.2 LIMITS OF UNWANTED EMISSION 22

3.1.3 TEST INSTRUMENTS 23

3.1.4 TEST PROCEDURES 24

3.1.5 DEVIATION FROM TEST STANDARD 25

3.1.6 TEST SETUP 26

3.1.7 EUT OPERATING CONDITION 27

3.1.8 TEST RESULTS 28

3.2 CONDUCTED EMISSION MEASUREMENT 448

3.2.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT 448

3.2.2 TEST INSTRUMENTS 448

3.2.3 TEST PROCEDURES 449

3.2.4 DEVIATION FROM TEST STANDARD 450

3.2.5 TEST SETUP 450

3.2.6 EUT OPERATING CONDITIONS 450

3.2.7 TEST RESULTS 451

3.3 MAXIMUM CONDUCTED OUTPUT POWER MEASUREMENT 453

3.3.1 LIMITS OF MAXIMUM CONDUCTED OUTPUT POWER MEASUREMENT 453

3.3.2 TEST SETUP 454

3.3.3 TEST INSTRUMENTS 455

3.3.4 TEST PROCEDURE 456

3.3.5 DEVIATION FROM TEST STANDARD 457

3.3.6 EUT OPERATING CONDITIONS 457

3.3.7 TEST RESULTS 458

3.4 MAXIMUM POWER SPECTRAL DENSITY MEASUREMENT 459

3.4.1 LIMITS OF MAXIMUM POWER SPECTRAL DENSITY MEASUREMENT 459

3.4.2 TEST SETUP 459

3.4.3 TEST INSTRUMENTS 459

3.4.4 TEST PROCEDURES 460

3.4.5 DEVIATION FROM TEST STANDARD 460

3.4.6 EUT OPERATING CONDITIONS 460

3.4.7 TEST RESULTS 461

3.5 AUTOMATICALLY DISCONTINUE TRANSMISSION 462

3.5.1 LIMIT OF AUTOMATICALLY DISCONTINUE TRANSMISSION 462

3.5.2 TEST INSTRUMENTS 462

3.5.3 TEST RESULT 462

3.6 ANTENNA REQUIREMENTS 463

3.6.1 STANDARD APPLICABLE 463

3.6.2 ANTENNA CONNECTED CONSTRUCTION 463

3.6.3 ANTENNA GAIN 464

4. PHOTOGRAPHS OF THE TEST CONFIGURATION 465

**5. MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB
466**

6. APPENDIX 467

RLAN 467

EMISSION BANDWIDTH 467

TEST RESULT 467

TEST GRAPHS 472

OCCUPIED CHANNEL BANDWIDTH 492

TEST RESULT 492

TEST GRAPHS 498

MIN EMISSION BANDWIDTH 523



BUREAU VERITAS Test Report No.: PSU-QBJ2507100210RF03

TEST RESULT B4	523
TEST GRAPHS B4	524
DUTY CYCLE	529
TEST RESULT	529
TEST GRAPHS	534
MAXIMUM CONDUCTED OUTPUT POWER.....	559
TEST RESULT CHANNEL POWER.....	559
MAXIMUM POWER SPECTRAL DENSITY	566
TEST RESULT	566
TEST GRAPHS	573
AX PART RU-RLAN	602
EMISSION BANDWIDTH	602
TEST RESULT	602
TEST GRAPHS	607
OCCUPIED CHANNEL BANDWIDTH	617
TEST RESULT	617
TEST GRAPHS	623
MIN EMISSION BANDWIDTH.....	636
TEST RESULT	636
TEST GRAPHS	638
MAXIMUM CONDUCTED OUTPUT POWER.....	641
TEST RESULT	641
MAXIMUM POWER SPECTRAL DENSITY	647
TEST RESULT	647
TEST GRAPHS	651
DUTY CYCLE	666
TEST RESULT	666
TEST GRAPHS	669



BUREAU VERITAS Test Report No.: PSU-QBJ2507100210RF03

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
PSU-QBJ2507100210RF03	Original release	Jul. 31, 2025



1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC PART 15, SUBPART E		
STANDARD SECTION	TEST TYPE AND LIMIT	RESULT
15.407(b)(9)	AC Power Conducted Emission	Compliance
15.407(b) (1/2/3/4/5)	Radiated Emission & Band Edge Measurement	Compliance
15.407(a/1/2/3)	Maximum conducted output Power	Compliance
15.407(a/1/2/3)	Peak Power Spectral Density	Compliance
15.407(a)(2)(12)	26 dB Bandwidth	Compliance
15.407(e)	6 dB Bandwidth	Compliance
15.203	Antenna Requirement	Compliance

NOTE:

1. Except the data of RSE and Band Edge Measurement, other data please refer to Appendix.
2. Preliminary Investigation scans were completed to compare Full RU Tone modes and Single User Tone modes. It was found that SU modes were the worst case over Full RU-Tone mode in every instance, and the physical waveforms of SU mode and FULL RU-Tone are the same, and both FULL RU-Tone mode have lower power than SU mode. Therefore, only SU mode was report as it is representative of Full RU-Tone worst case scenario.
3. RLAN 5G supports SISO&MIMO mode, the whole testing has assessed the MIMO mode by referring to their maximum conducted power. and the 802.11ax HE40/80MHz RU26T/52T/106T/242T modes are cover by the 11ax HE20MHz modes, the 802.11ax HE80MHz RU484T modes are cover by the 11ax HE40MHz modes.
4. For 802.11n HT20/ ac VHT20 and 802.11n HT40 / ac VHT40 mode, the whole testing is assessed only 802.11n HT20/ HT40 by referring to their higher conducted power.
5. Only the worse data was reported.

***Test Lab Information Reference**

Lab A:

Huarui 7Layers High Technology (Suzhou) Co., Ltd.

Lab Address:

Tower N, Innovation Center, 88 Zuyi Road, High-tech District, Suzhou City, Anhui Province, China

Accredited Test Lab Cert 6613.01

The FCC Site Registration No. is 434559; The Designation No. is CN1325.




1.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	UNCERTAINTY
AC Power Conducted emissions	±2.70dB
Radiated emissions (9KHz~30MHz)	±2.68dB
Radiated emissions (30MHz~1GHz)	±4.98dB
Radiated emissions (1GHz ~6GHz)	±4.70dB
Radiated emissions (6GHz ~18GHz)	±4.60dB
Radiated emissions (18GHz ~40GHz)	±4.12dB
Conducted emissions	±4.01dB
Occupied Channel Bandwidth	±43.58KHz
Conducted Output power	±2.06dB
Power Spectral Density	±0.85 dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k = 2.



The verdicts in this test report are given according the above diagram:

Case	Measured Value	Uncertainty Range	Verdict
1	below pass mark	below pass mark	Passed
2	below pass mark	within pass mark	Passed
3	above pass mark	within pass mark	Failed
4	above pass mark	above pass mark	Failed

That means, the laboratory applies, as decision rule (see ISO/IEC 17025:2017), the so-called shared risk principle.



2 GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

PRODUCT*	Tablet Computer	
BRAND NAME*	POCO	
MODEL NAME*	2509ARPDG	
NOMINAL VOLTAGE*	5/3.6-11Vdc(adapter or host equipment) 3.91Vdc(Li-ion,battery)	
MODULATION *	OFDM,OFDMA	
TRANSFER RATE*	802.11a: 54.0/ 48.0/ 36.0/ 24.0/ 18.0/ 12.0/ 9.0/ 6.0Mbps	
	802.11n: up to 300.0Mbps	
	802.11ac: up to 866.7Mbps	
	802.11ax: up to 1020.8Mbps	
OPERATING FREQUENCY*	5180~5240MHz, 5260~5320MHz	
	5500~5720MHz, 5745~5825MHz	
NUMBER OF CHANNEL	5180~5240MHz	4 for 802.11a,802.11n/ac/ax (20MHz),802.11ax(20M RU 26/52/106)
		2 for 802.11n/ac/ax (40MHz)
		1 for 802.11ac/ax (80MHz)
		1 for 802.11ac/ax (160MHz)
	5260~5320MHz	4 for 802.11a,802.11n/ac/ax(20MHz)/ 802.11ax(20M RU 26/52/106)
		2 for 802.11n/ac/ax(40MHz)
		1 for 802.11ac/ax(80MHz)
	5500~5720MHz	12 for 802.11a, 802.11n/ac/ax (20MHz) 802.11ax(20M RU 26/52/106)
		6 for 802.11n/ac/ax (40MHz)
		3 for 802.11ac/ax (80MHz)
		1 for 802.11ac/ax(160MHz)
	5745~5825MHz	5 for 802.11a, 802.11n/ac/ax (20MHz) 802.11ax(20M RU 26/52/106)
		2 for 802.11n/ac/ax (40MHz)



		1 for 802.11ac/ax (80MHz)
MAX. OUTPUT POWER	87.10mW for 5180 ~ 5240MHz	
	88.31mW for 5260 ~ 5320MHz	
	82.41mW for 5500 ~ 5720MHz	
	85.90mW for 5745 ~ 5825MHz	
ANTENNA TYPE*	PIFA Antenna	
ANTENNA GAIN*	5180 ~ 5240MHz	ANT7: 0.75dBi ANT10: 0.71dBi MIMO:0.75dBi
	5260 ~ 5320MHz	ANT7: 0.35dBi ANT10: 0.78dBi MIMO:0.35dBi
	5500 ~ 5720MHz	ANT7: -0.67dBi ANT10: 0.38dBi MIMO:0.38dBi
	5745 ~ 5825MHz	ANT7: 0.02dBi ANT10: -0.34dBi MIMO:0.02dBi
HW VERSION*	135700P83	
SW VERSION*	Xiaomi HyperOS 2.0	
I/O PORTS*	Refer to user's manual	
CABLE SUPPLIED*	USB cable1: non-shielded cable, with w/o ferrite core, 1.0 meter USB cable2: non-shielded cable, with w/o ferrite core, 1.0 meter USB cable3: non-shielded cable, with w/o ferrite core, 1.0 meter USB cable4: non-shielded cable, with w/o ferrite core, 1.0 meter	

NOTE:

- *Since the above data and/or information is provided by the client relevant results or conclusions of this report are only made for these data and/or information, Test Lab is not responsible for the authenticity, integrity and results of the data and information and/or the validity of the conclusion.
- For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
- The EUT incorporates a MIMO function. Physically, the EUT provides two completed transmitter and two receiver.

MODULATION MODE	TX FUNCTION
802.11a	2TX/2RX
802.11n/802.11ac/ax (20MHz)	2TX/2RX
802.11n/802.11ac/ax (40MHz)	2TX/2RX
802.11ac/ax (80MHz)	2TX/2RX
802.11ac/ax (160MHz)	2TX/2RX



802.11ax (20/40/80/160M RU26/52/106)	2TX/2RX
---------------------------------------------	---------

- 4. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.
- 5. Antenna gain and EUT conducted cable loss are provided by the customer, and the laboratory will record the results based on these items that involve these two parameters.



2.2 DESCRIPTION OF TEST MODES

FOR 5180~5240MHz			
802.11a, 802.11n, 802.11ac/ax(20MHz),802.11ax(20MHz RU 26/52/106)			
CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
36	5180 MHz	44	5220 MHz
40	5200 MHz	48	5240 MHz

802.11n, 802.11ac/ax (40MHz)			
CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
38	5190 MHz	46	5230 MHz

802.11ac/ax (80MHz)			
CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
42	5210 MHz		

802.11ac/ax (160MHz)			
CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
50	5250 MHz		

FOR 5260 ~ 5320MHz			
802.11a, 802.11n, 802.11ac/ax (20MHz), 802.11ax(20MHz RU 26/52/106)			
CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
52	5260 MHz	60	5300 MHz
56	5280 MHz	64	5320 MHz

802.11n, 802.11ac/ax (40MHz)			
CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
54	5270 MHz	62	5310 MHz

802.11ac/ax (80MHz)			
CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
58	5290 MHz		



FOR 5500 ~ 5720MHz			
802.11a, 802.11n, 802.11ac/ax (20MHz), 802.11ax(20MHz RU 26/52/106)			
CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
100	5500 MHz	124	5620MHz
104	5520 MHz	128	5640MHz
108	5540 MHz	132	5660 MHz
112	5560 MHz	136	5680 MHz
116	5580 MHz	140	5700 MHz
120	5600 MHz	144	5720 MHz

802.11n, 802.11ac/ax (40MHz)			
CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
102	5510 MHz	126	5630MHz
110	5550 MHz	134	5670 MHz
118	5590 MHz	142	5710 MHz

802.11ac/ax (80MHz)			
CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
106	5530 MHz	122	5610 MHz
138	5690 MHz		

802.11ac/ax (160MHz)			
CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
114	5570 MHz		



FOR 5745 ~ 5825MHz			
802.11a, 802.11n, 802.11ac/ax (20MHz)			
CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
149	5745 MHz	161	5805 MHz
153	5765 MHz	165	5825 MHz
157	5785 MHz		

802.11n, 802.11ac/ax (40MHz)			
CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
142	5710 MHz	159	5795 MHz
151	5755 MHz		

802.11ac/ax (80MHz)			
CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
138	5690 MHz	155	5775 MHz



2.2.1 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE≥1G	RE<1G	PLC	APCM	
A	√	√	√	-	Powered by Adapter with wifi(5G) link
B	-	-	-	√	Powered by Battery with wifi(5G) link
C	-	-	-	-	Powered by USB with wifi(5G) link

Where **RE≥1G**: Radiated Emission above 1GHz **RE<1G**: Radiated Emission below 1GHz
PLC: Power Line Conducted Emission **APCM**: Antenna Port Conducted Measurement

NOTE:
The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on **X-plane**.
NOTE: "-" means no effect

RADIATED EMISSION TEST (BELOW 1GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- The following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	FREQ. BAND (MHz)	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	DATA RATE (Mbps)
A	802.11ax(20MHz RU106)	5500-5720	100 to 144	140	OFDMA	MCS0



RADIATED EMISSION TEST (ABOVE 1GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- The following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	FREQ. BAND (MHz)	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	DATA RATE (Mbps)
A	802.11a	5180-5240	36 to 48	36, 40, 48	OFDM	6.0
A	802.11n/ax/ac (20MHz)/802.11ax(20MHz RU 26/52/106)		36 to 48	36, 40, 48	OFDM, OFDMA	MCS0
A	802.11n/ac/ax (40MHz)		38 to 46	38, 46	OFDM, OFDMA	MCS0
A	802.11ac/ax (80MHz)		42	42	OFDM, OFDMA	MCS0
A	802.11ac/ax (160MHz)		50	50	OFDM, OFDMA	MCS0
A	802.11a	5260-5320	52 to 64	52, 60, 64	OFDM	6.0
A	802.11n/ax/ac (20MHz)/802.11ax(20MHz RU 26/52/106)		52 to 64	52, 60, 64	OFDM, OFDMA	MCS0
A	802.11n/ac/ax (40MHz)		54 to 62	54, 62	OFDM, OFDMA	MCS0
A	802.11ac/ax (80MHz)		58	58	OFDM, OFDMA	MCS0
A	802.11a	5500-5720	100 to 144	100, 116, 140, 144	OFDM	6.0
A	802.11n/ax/ac (20MHz)/802.11ax(20MHz RU 26/52/106)		100 to 144	100, 116, 140, 144	OFDM, OFDMA	MCS0
A	802.11n/ac/ax (40MHz)		102 to 142	102, 110, 134, 142	OFDM, OFDMA	MCS0
A	802.11ac/ax (80MHz)		106 to 138	106, 122, 138	OFDM, OFDMA	MCS0
A	802.11ac/ax (160MHz)		114	114	OFDM, OFDMA	MCS0
A	802.11a	5745-5825	149 to 165	149, 157, 165	OFDM	6.0
A	802.11n/ax/ac (20MHz)/802.11ax(20MHz RU 26/52/106)		149 to 165	149, 157, 165	OFDM, OFDMA	MCS0
A	802.11n/ac/ax (40MHz)		151 to 159	151, 159	OFDM, OFDMA	MCS0
A	802.11ac/ax (80MHz)		155	155	OFDM, OFDMA	MCS0



POWER LINE CONDUCTED EMISSION TEST:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- The following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	FREQ. BAND (MHz)	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	DATA RATE (Mbps)
A	802.11ac(80MHz)	5500-5720	106 to 138	138	OFDM	MCS0

BANDEGE MEASUREMENT:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- The following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	FREQ. BAND (MHz)	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	DATA RATE (Mbps)
A	802.11a	5180-5240	36 to 48	36, 40, 48	OFDM	6.0
A	802.11n/ax/ac (20MHz)/802.11ax(20MHz RU 26/52/106)		36 to 48	36, 40, 48	OFDM, OFDMA	MCS0
A	802.11n/ac/ax (40MHz)		38 to 46	38, 46	OFDM, OFDMA	MCS0
A	802.11ac/ax (80MHz)		42	42	OFDM, OFDMA	MCS0
A	802.11ac/ax (160MHz)		50	50	OFDM, OFDMA	MCS0
A	802.11a	5260-5320	52 to 64	52, 60, 64	OFDM	6.0
A	802.11n/ax/ac (20MHz)/802.11ax(20MHz RU 26/52/106)		52 to 64	52, 60, 64	OFDM, OFDMA	MCS0
A	802.11n/ac/ax (40MHz)		54 to 62	54, 62	OFDM, OFDMA	MCS0
A	802.11ac/ax (80MHz)		58	58	OFDM, OFDMA	MCS0
A	802.11a	5500-5720	100 to 144	100, 116, 140, 144	OFDM	6.0
A	802.11n/ax/ac (20MHz)/802.11ax(20MHz RU 26/52/106)		100 to 144	100, 116, 140, 144	OFDM, OFDMA	MCS0
A	802.11n/ac/ax (40MHz)		102 to 142	102, 110, 134, 142	OFDM, OFDMA	MCS0
A	802.11ac/ax (80MHz)		106 to 138	106, 122, 138	OFDM, OFDMA	MCS0
A	802.11ac/ax (160MHz)		114	114	OFDM, OFDMA	MCS0
A	802.11a	5745-5825	149 to 165	149, 157, 165	OFDM	6.0
A	802.11n/ax/ac (20MHz)/802.11ax(20MHz RU 26/52/106)		149 to 165	149, 157, 165	OFDM, OFDMA	MCS0
A	802.11n/ac/ax (40MHz)		151 to 159	151, 159	OFDM, OFDMA	MCS0
A	802.11ac/ax (80MHz)		155	155	OFDM, OFDMA	MCS0



ANTENNA PORT CONDUCTED MEASUREMENT:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- The following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	MODE	FREQ. BAND (MHz)	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	DATA RATE (Mbps)
A	802.11a	5180-5240	36 to 48	36, 40, 48	OFDM	6.0
A	802.11n/ax/ac (20MHz)/802.11ax(20MHz RU 26/52/106)		36 to 48	36, 40, 48	OFDM, OFDMA	MCS0
A	802.11n/ac/ax (40MHz)		38 to 46	38, 46	OFDM, OFDMA	MCS0
A	802.11ac/ax (80MHz)		42	42	OFDM, OFDMA	MCS0
A	802.11ac/ax (160MHz)		50	50	OFDM, OFDMA	MCS0
A	802.11a	5260-5320	52 to 64	52, 60, 64	OFDM	6.0
A	802.11n/ax/ac (20MHz)/802.11ax(20MHz RU 26/52/106)		52 to 64	52, 60, 64	OFDM, OFDMA	MCS0
A	802.11n/ac/ax (40MHz)		54 to 62	54, 62	OFDM, OFDMA	MCS0
A	802.11ac/ax (80MHz)		58	58	OFDM, OFDMA	MCS0
A	802.11a	5500-5720	100 to 144	100, 116, 140, 144	OFDM	6.0
A	802.11n/ax/ac (20MHz)/802.11ax(20MHz RU 26/52/106)		100 to 144	100, 116, 140, 144	OFDM, OFDMA	MCS0
A	802.11n/ac/ax (40MHz)		102 to 142	102, 110, 134, 142	OFDM, OFDMA	MCS0
A	802.11ac/ax (80MHz)		106 to 138	106, 122, 138	OFDM, OFDMA	MCS0
A	802.11ac/ax (160MHz)		114	114	OFDM, OFDMA	MCS0
A	802.11a	5745-5825	149 to 165	149, 157, 165	OFDM	6.0
A	802.11n/ax/ac (20MHz)/802.11ax(20MHz RU 26/52/106)		149 to 165	149, 157, 165	OFDM, OFDMA	MCS0
A	802.11n/ac/ax (40MHz)		151 to 159	151, 159	OFDM, OFDMA	MCS0
A	802.11ac/ax (80MHz)		155	155	OFDM, OFDMA	MCS0

TEST CONDITION			
APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
RE<1G	23deg. C, 70%RH	DC3.8V By Adapter	Hanwen Xu
RE≥1G	23deg. C, 70%RH	DC3.8V By Adapter	Hanwen Xu
PLC	25deg. C, 52%RH	DC3.8V By Adapter	Hanwen Xu
APCM	25deg. C, 60%RH	DC 3.89V By Battery	Hanwen Xu



BUREAU VERITAS Test Report No.: PSU-QBJ2507100210RF03

2.3 DUTY CYCLE OF TEST SIGNAL

Please Refer to Appendix of this test report.



2.4 DESCRIPTION OF SUPPORT UNITS




The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	Laptop	Lenovo	Thinkpad E14	SL10W47313	N/A
2	Adapter	N/A	N/A	N/A	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	AC Line: Unshielded, Detachable 1.5m
2	USB Line: Unshielded, Detachable, 1.0m;



2.4.1 CONFIGURATION OF SYSTEM UNDER TEST





2.5 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart E (15.407)

KDB 789033 D02 General U-NII Test Procedures New Rules v02r01

ANSI C63.10-2020

All test items have been performed and recorded as per the above standards.

NOTE: The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (Certification). The test report has been issued separately.



3 TEST TYPES AND RESULTS

3.1 RADIATED EMISSION AND BANDEDGE MEASUREMENT

3.1.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table:

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



3.1.2 LIMITS OF UNWANTED EMISSION

RESTRICTED BANDS	APPLICABLE TO	LIMIT	
	789033 D02 General UNII Test Procedures New Rules v02r01	FIELD STRENGTH AT 3m (dBµV/m)	
	PK : 74	AV : 54	
OUT OF THE RESTRICTED BANDS	APPLICABLE TO	EIRP LIMIT (dBm/MHz)	EQUIVALENT FIELD STRENGTH AT 3m (dBµV/m)
	15.407(b)(1)	PK : -27	PK : 68.2
	15.407(b)(2)		
	15.407(b)(3)		
	15.407(b)(4)	See note 2 (FCC 16-24)	

NOTE:

- The following formula is used to convert the equipment isotropic radiated power (eirp) to field strength:

$$E = \frac{1000000\sqrt{30P}}{3} \mu\text{V/m, where P is the eirp (Watts).$$
- All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.



3.1.3 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Pre-Amplifier	R&S	SCU18F1	100815	Aug.30,23	Aug.29,25
Pre-Amplifier	R&S	SCU08F1	101028	Jan.22,24	Jan.21,26
Signal Generator	R&S	SMB100A	182185	Mar.29,24	Mar.28,26
3m Fully-anechoic Chamber	TDK	9m*6m*6m	HRSW-SZ-EMC-01Chamber	Nov.25,22	Nov.24,25
3m Semi-anechoic Chamber	TDK	9m*6m*6m	HRSW-SZ-EMC-02Chamber	Nov.25,22	Nov.24,25
EMI TEST Receiver	R&S	ESW44	101973	Mar.28,24	Mar.27,26
Bilog Antenna	SCHWARZBECK	VULB 9163	1264	Dec.26,23	Dec.25,25
Horn Antenna	ETS-LINDGREN	3117	227836	Aug.22,23	Aug.21,25
Horn Antenna (18GHz-40GHz)	Steatite Q-par Antennas	QMS 00880	23486	Jul.15,24	Jul.14,26
Horn Antenna	Steatite Q-par Antennas	QMS 00208	23485	Aug.22,23	Aug.21,25
Loop Antenna	SCHWARZ	HFH2-Z2/Z2E	100976	Feb.22,25	Feb.21,27
WIDEBANDRADIO COMMUNICATION TESTER	R&S	CMW500	169399	Jun.19,24	Jun.18,26
Test Software	ELEKTRA	ELEKTRA4.32	N/A	N/A	N/A
Open Switch and Control Unit	R&S	OSP220	101964	N/A	N/A
DC Source	HYELEC	HY3010B	551016	Aug.31,23	Aug.30,25
Hygrothermograph	DELI	20210528	SZ014	Mar.18,25	Mar.17,27
6DB attenuator	Tonscend Technology Co., Ltd	N/A	23062787	N/A	N/A
PC	LENOVO	E14	HRSW0024	N/A	N/A
TMC-AMI18843A(CABLE)	R&S	HF290-NMNM-7.00M	N/A	N/A	N/A
TMC-AMI18843A(CABLE)	R&S	HF290-NMNM-4.00M	N/A	N/A	N/A
CABLE	R&S	W13.02	N/A	Apr.26,25	Apr.25,26



CABLE	R&S	W12.14	N/A	Apr.26,25	Apr.25,26
-------	-----	--------	-----	-----------	-----------

NOTE:

1. The calibration interval of the above test instruments is 12/ 24 / 36 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
2. The test was performed in 3m Chamber.
3. The FCC Site Registration No. is 434559; The Designation No. is CN1325.

3.1.4 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 0.8 meters (for below 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3-meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise, the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for RMS Average (Duty cycle < 98%) for Average detection (AV) at frequency above 1GHz, then the measurement results was added to a correction factor ($10 \log(1/\text{duty cycle})$).
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz (Duty cycle \geq 98%) for Average detection (AV) at frequency above 1GHz.
5. All modes of operation were investigated, and the worst-case emissions are reported.



BUREAU VERITAS Test Report No.: PSU-QBJ2507100210RF03


3.1.5 DEVIATION FROM TEST STANDARD

No deviation.




3.1.6 TEST SETUP

<Frequency Range 9KHz~30MHz >




< Frequency Range 30MHz~1GHz >





<Frequency Range above 1GHz>



Note: Above 1G is a directional antenna

Depends on the EUT height and the antenna 3dB beamwidth both, refer to section 7.3 of CISPR 16-2-3.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

3.1.7 EUT OPERATING CONDITION

- Set the EUT under full load condition and placed them on a testing table.
- Set the transmitter part of EUT under transmission condition continuously at specific channel frequency.
- The necessary accessories enable the EUT in full functions.



3.1.8 TEST RESULTS

NOTE : The 9K~30MHz amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required in the report.


BAND EDGE MEASUREMENT
BADN 1

802.11a

CHANNEL	TX Channel 36	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	5,140.600	58.68	74.00	15.32	43.81	H	319.9	2.00
1	5,150.000	57.34	74.00	16.66	43.83	H	175.2	1.00
1	5,178.400	106.82			43.96	H	264.7	1.00





ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M


Rg	Frequency [MHz]	AVG Level [dBµV/m]	AVG Limit [dBµV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	5,148.700	43.83	54.00	10.17	43.83	H	183.7	2.00
1	5,150.000	43.86	54.00	10.14	43.83	H	183.7	2.00
1	5,177.950	93.56			43.96	H	265.9	1.00






ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	5,146.450	58.65	74.00	15.35	43.82	V	320	2.00
1	5,150.000	58.25	74.00	15.75	43.83	V	227.9	1.00
1	5,178.400	112.63			43.96	V	95.3	2.00





REMARKS:


1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
2. Margin value = Limit value- Emission level.
3. 5180MHz: Fundamental frequency.



CHANNEL	TX Channel 40	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M


Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	5,116.600	58.04	74.00	15.96	43.75	H	44.9	2.00
2	5,150.000	57.35	74.00	16.65	43.83	H	183.6	2.00
2	5,202.700	104.54			44.00	H	263.6	1.00





ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M


Rg	Frequency [MHz]	AVG Level [dB μ V/m]	AVG Limit [dB μ V/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	5,149.300	43.11	54.00	10.89	43.83	H	152.6	2.00
2	5,150.000	43.13	54.00	10.87	43.83	H	41.3	1.00
2	5,201.800	92.07			44.01	H	355	2.00





ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M


Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	5,135.800	58.38	74.00	15.62	43.79	V	253.1	2.00
2	5,150.000	57.02	74.00	16.98	43.83	V	268.4	1.00
2	5,198.200	110.49			44.03	V	223	1.00





ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	AVG Level [dBµV/m]	AVG Limit [dBµV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	5,149.600	43.57	54.00	10.43	43.83	V	255.4	1.00
2	5,150.000	43.56	54.00	10.44	43.83	V	311.5	2.00
2	5,201.800	99.84			44.01	V	255.4	1.00



REMARKS:


1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
2. Margin value = Limit value- Emission level.
3. 5200MHz: Fundamental frequency.



CHANNEL	TX Channel 48	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M


Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
3	5,141.125	58.20	74.00	15.80	43.81	H	359	2.00
3	5,150.000	56.90	74.00	17.10	43.83	H	315.1	1.00
3	5,243.130	103.74			43.73	H	269.6	1.00





ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M


Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
3	5,145.250	43.03	54.00	10.97	43.82	H	359	2.00
3	5,150.000	43.01	54.00	10.99	43.83	H	359	1.00
3	5,242.375	93.61			43.73	H	34.2	2.00





ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M


Rg	Frequency [MHz]	PK+ Level [dBµV/m]	PK+ Limit [dBµV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
3	5,148.625	57.89	74.00	16.11	43.83	V	351.8	1.00
3	5,150.000	56.70	74.00	17.30	43.83	V	163.4	2.00
3	5,240.880	109.83			43.74	V	221.8	1.00






ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	AVG Level [dBµV/m]	AVG Limit [dBµV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
3	5,147.500	43.07	54.00	10.93	43.82	V	227.9	2.00
3	5,149.750	43.00	54.00	11.00	43.83	V	1	1.00
3	5,237.875	98.23			43.76	V	249.4	1.00



REMARKS:


1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
2. Margin value = Limit value- Emission level.
3. 5240MHz: Fundamental frequency.







ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	5,141.050	43.04	54.00	10.96	43.81	H	132.2	2.00
1	5,150.000	42.95	54.00	11.05	43.83	H	132.2	2.00
1	5,180.650	86.63			43.97	H	40.2	2.00







REMARKS:


1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
2. Margin value = Limit value- Emission level.
3. 5180MHz: Fundamental frequency.



CHANNEL	TX Channel 40	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M


Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	5,140.600	58.13	74.00	15.87	43.81	H	177.8	2.00
2	5,150.000	56.55	74.00	17.45	43.83	H	5.1	1.00
2	5,198.800	103.23			44.03	H	41.4	1.00





ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M


Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	5,138.800	43.14	54.00	10.86	43.80	H	355.5	2.00
2	5,150.000	42.96	54.00	11.04	43.83	H	1	1.00
2	5,200.900	91.01			44.02	H	42.6	1.00





ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M


Rg	Frequency [MHz]	PK+ Level [dBµV/m]	PK+ Limit [dBµV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	5,112.100	58.28	74.00	15.72	43.74	V	85.7	2.00
2	5,150.000	57.02	74.00	16.98	43.83	V	5.1	1.00
2	5,201.200	106.35			44.02	V	274.4	1.00





ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	AVG Level [dBµV/m]	AVG Limit [dBµV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	5,142.700	43.08	54.00	10.92	43.81	V	85.6	2.00
2	5,150.000	43.12	54.00	10.88	43.83	V	273.2	1.00
2	5,201.500	93.99			44.01	V	273.2	1.00



REMARKS:


1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
2. Margin value = Limit value- Emission level.
3. 5200MHz: Fundamental frequency.



CHANNEL	TX Channel 44	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M


Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
3	5,133.625	57.71	74.00	16.29	43.79	H	42.6	1.00
3	5,149.750	56.55	74.00	17.45	43.83	H	42.6	1.00
3	5,241.250	104.24			43.74	H	42.6	1.00





ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M


Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
3	5,140.750	42.97	54.00	11.03	43.81	H	316.3	2.00
3	5,150.000	42.96	54.00	11.04	43.83	H	1	1.00
3	5,241.250	92.11			43.74	H	42.5	1.00






ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M


Rg	Frequency [MHz]	PK+ Level [dBµV/m]	PK+ Limit [dBµV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
3	5,147.125	57.93	74.00	16.07	43.82	V	227.8	1.00
3	5,150.000	57.13	74.00	16.87	43.83	V	0.9	2.00
3	5,241.250	105.02			43.74	V	275.6	1.00





REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
2. Margin value = Limit value- Emission level.
3. 5240MHz: Fundamental frequency.





ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	AVG Level [dBµV/m]	AVG Limit [dBµV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	5,145.500	43.51	54.00	10.49	43.82	H	88	1.00
1	5,150.000	43.54	54.00	10.46	43.83	H	272	1.00
1	5,192.000	88.21			44.02	H	272	1.00

